



---

Wowza Media Server® 3

# Server-Side API

---

# **Wowza Media Server 3: Server-Side API**



## **Version 3.6**

---

Copyright © 2006 – 2013 Wowza Media Systems, LLC  
<http://www.wowza.com>

---

**This document is for informational purposes only and in no way shall be interpreted or construed to create any warranties of any kind, either express or implied, regarding the information contained herein.**

### **Third Party Information**

This document contains links to third party websites that are not under the control of Wowza Media Systems, LLC (“Wowza”) and Wowza is not responsible for the content on any linked site. If you access a third party website mentioned in this document, then you do so at your own risk. Wowza provides these links only as a convenience, and the inclusion of any link does not imply that Wowza endorses or accepts any responsibility for the content on third party sites.

This document also refers to other third party software that is not licensed, sold, distributed or otherwise endorsed by Wowza. Please ensure that any and all use of Wowza® software and third party software is properly licensed.

### **Trademarks**

Wowza, Wowza Media Systems, Wowza Media Server and related logos are either registered trademarks or trademarks of Wowza Media System, LLC in the United States and/or other countries.

Adobe and Flash are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Microsoft and Silverlight are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

QuickTime, iPhone, iPad and iPod touch are either registered trademarks or trademarks of Apple, Inc. in the United States and/or other countries.

Other product names, logos, designs, titles, words or phrases mentioned may be third party registered trademarks or trademarks in the United States and/or other countries.

Third party trademarks are used solely to identify and describe third party products as being compatible with Wowza products. Wowza is in no way sponsored, endorsed by or otherwise affiliated with any such third party trademark owners.

### **Third Party Copyright Notices**

Apache Commons Lang: Copyright © 2001-2011, The Apache Software Foundation

Apache Commons Modeler Component: Copyright © 2002-2008, The Apache Software Foundation

Bouncy Castle Crypto APIs: Copyright © 2000 – 2008, Legion of the Bouncy Castle

Jackson JSON Parser: Copyright © 2009, FasterXML, LLC

Java ID3 Tag Library and JLayer 1.0 (classic): Copyright © 1991, 1999, Free Software Foundation, Inc.

Joda-Time version 2.1: Copyright © 2012, Joda.org

Libgcc\_s-4 library and Libstdc++ library: Copyright © 2011, Free Software Foundation, Inc.

LibVA libraries: Copyright © 2007, Intel Corporation. All rights reserved.

Log4j and Mina: Copyright © 2006, The Apache Software Foundation

NVIDIA Video Codec SDK: Copyright © 2013, NVIDIA Corporation

Silver Egg Technology: Copyright © 2001, Silver Egg Technology

---

Speex Codec: Copyright © 2002-2003, Jean-Marc Valin/Xiph.Org Foundation

VideoEncoderH264VAAPllmpl: Copyright © 2012, Intel Corporation. All Rights Reserved.

Vorbis/Ogg libraries: Copyright © 2011, Xiph.Org Foundation

WebM VP8 Codec libraries: Copyright © 2010, Google Inc. All rights reserved.

Copyright © 2006 - 2013 Wowza Media Systems, LLC. All rights reserved.



---

## Document History

Version	Description	Release date
Doc v3.5.0	Initial document release for Wowza Media Server 3.5	11-08-2012
Doc v3.6.0	Updated for Wowza Media Server 3.6.0	05-28-2013

### Note

A more recent version of this document may be available online. See the [Wowza Media Systems Documentation webpage](http://www.wowza.com/forums/content.php?188) (<http://www.wowza.com/forums/content.php?188>) for the latest updates.

---

Package

**com.wowza.io**

## com.wowza.io Interface IRandomAccessReader

public interface **IRandomAccessReader**  
extends

### Field Summary

public static final	<a href="#"><u>FORWARD</u></a> Value: <b>1</b>
public static final	<a href="#"><u>REVERSE</u></a> Value: <b>-1</b>

### Method Summary

void	<a href="#"><u>close()</u></a> Close the media asset
boolean	<a href="#"><u>exists()</u></a> Does the media asset exist
String	<a href="#"><u>getBasePath()</u></a> Get the basePath for the random access reader
int	<a href="#"><u>getDirecton()</u></a> Get the current direction hint for the random access reader.
long	<a href="#"><u>getFilePointer()</u></a> Get the current byte location in the media asset
String	<a href="#"><u>getMediaExtension()</u></a> Get the media extension
String	<a href="#"><u>getMediaName()</u></a> Get the media name
String	<a href="#"><u>getPath()</u></a> Get the unique path to the media asset item
void	<a href="#"><u>init(IApplicationInstance appInstance, IMediaStream stream, String basePath, String mediaName, String mediaExtension)</u></a> Intialize RandomAccessReader
boolean	<a href="#"><u>isOpen()</u></a> Is the media asset open
long	<a href="#"><u>lastModified()</u></a> Return the lastModified date (same format as File.lastModified)
long	<a href="#"><u>length()</u></a> Get the media asset length in bytes

void	<a href="#"><u>open()</u></a> Open the media asset
int	<a href="#"><u>read</u></a> (byte[] buf, int off, int size) Read bytes from the media asset
void	<a href="#"><u>seek</u></a> (long pos) Seek to a position in the media asset
void	<a href="#"><u>setDirecton</u></a> (int directon) Set the current direction hint

## Fields

### FORWARD

```
public static final int FORWARD
```

Constant value: **1**

### REVERSE

```
public static final int REVERSE
```

Constant value: **-1**

## Methods

### init

```
public void init(IApplicationInstance appInstance,
IMediaStream stream,
String basePath,
String mediaName,
String mediaExtension)
```

Intialize RandomAccessReader

#### Parameters:

appInstance - application instance  
stream - parent stream if one exists  
basePath - basePath for IApplicationInstance  
mediaName - media name  
mediaExtension - media extension from mediaReaders

### open

```
public void open()
throws java.io.IOException
```

Open the media asset

#### Throws:

IOException

## close

```
public void close()  
    throws java.io.IOException
```

Close the media asset

**Throws:**

IOException

---

## isOpen

```
public boolean isOpen()
```

Is the media asset open

**Returns:**

true if media asset is open

---

## getFilePointer

```
public long getFilePointer()
```

Get the current byte location in the media asset

**Returns:**

current byte location in the media asset

---

## seek

```
public void seek(long pos)
```

Seek to a position in the media asset

**Parameters:**

pos - position to seek to

---

## read

```
public int read(byte[] buf,  
               int off,  
               int size)
```

Read bytes from the media asset

**Parameters:**

buf - buffer to fill

off - offset in buffer

size - size of block to read

**Returns:**

number of bytes read, -1 if failure

---

## getDirecton

```
public int getDirecton()
```

(continued on next page)

---

(continued from last page)

Get the current direction hint for the random access reader. The underlying system will call `setDirection` to hint at the current direction the media assets is being read.

**Returns:**

current direction hint for the random access reader

---

## **setDirecton**

```
public void setDirecton(int directon)
```

Set the current direction hint

**Parameters:**

`directon` - current direction hint for the random access reader

---

## **getBasePath**

```
public String getBasePath()
```

Get the `basePath` for the random access reader

**Returns:**

`basePath` for the random access reader

---

## **getMediaName**

```
public String getMediaName()
```

Get the media name

**Returns:**

media name

---

## **getMediaExtension**

```
public String getMediaExtension()
```

Get the media extension

**Returns:**

media extension

---

## **exists**

```
public boolean exists()
```

Does the media asset exist

**Returns:**

true if media assets exists

---

## **lastModified**

```
public long lastModified()
```

Return the `lastModified` date (same format as `File.lastModified`)

**Returns:**

`lastModified` date (same format as `File.lastModified`)

---

## length

```
public long length()
```

Get the media asset length in bytes

**Returns:**

media asset length in bytes

---

## getPath

```
public String getPath()
```

Get the unique path to the media asset item

**Returns:**

unique path to the media asset item

---

---

Package

**com.wowza.util**



## com.wowza.util Class AMFUtils

java.lang.Object

└─com.wowza.util.AMFUtils

public class **AMFUtils**  
extends Object

Utilities for the conversion between Java and AMF

### Constructor Summary

public	<a href="#">AMFUtils()</a>
--------	----------------------------

### Method Summary

static <a href="#">AMFData[]</a>	<a href="#">convertParams</a> (Object[] params) Converts an array of Java native data values and class to AMF data types.
----------------------------------	--

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### AMFUtils

public **AMFUtils**()

### Methods

#### convertParams

public static [AMFData\[\]](#) **convertParams**(Object[] params)

(continued from last page)

Converts an array of Java native data values and class to AMF data types. It will box primitive data types into wrapper classes. Supported input data types are:

- null
- Double
- Float
- Long
- Integer
- Short
- Byte
- Number
- Date
- Boolean
- String
- StringBuffer
- byte[] - assumed to be raw AMFData
- ByteBuffer - assumed to be raw AMFData
- AMFData
- AMFDataMixedArray
- AMFDataArray
- AMFDataItem
- AMFDataList
- AMFDataObj

**Parameters:**

params - Array of Java

**Returns:**

Array of AMFData[] objects

## com.wowza.util Class Base64

```
java.lang.Object
|
+-com.wowza.util.Base64
```

public class **Base64**  
extends Object

Encodes and decodes to and from Base64 notation.

Homepage: <http://iharder.net/base64>.

Change Log:

- v2.2.1 - Fixed bug using URL\_SAFE and ORDERED encodings. Fixed bug when using very small files (~< 40 bytes).
- v2.2 - Added some helper methods for encoding/decoding directly from one file to the next. Also added a main() method to support command line encoding/decoding from one file to the next. Also added these Base64 dialects:
  1. The default is RFC3548 format.
  2. Calling Base64.setFormat(Base64.BASE64\_FORMAT.URLSAFE\_FORMAT) generates URL and file name friendly format as described in Section 4 of RFC3548. <http://www.faqs.org/rfcs/rfc3548.html>
  3. Calling Base64.setFormat(Base64.BASE64\_FORMAT.ORDERED\_FORMAT) generates URL and file name friendly format that preserves lexical ordering as described in <http://www.faqs.org/qa/rfcc-1940.html>
 Special thanks to Jim Kellerman at <http://www.powerset.com/> for contributing the new Base64 dialects.
- v2.1 - Cleaned up javadoc comments and unused variables and methods. Added some convenience methods for reading and writing to and from files.
- v2.0.2 - Now specifies UTF-8 encoding in places where the code fails on systems with other encodings (like EBCDIC).
- v2.0.1 - Fixed an error when decoding a single byte, that is, when the encoded data was a single byte.
- v2.0 - I got rid of methods that used booleans to set options. Now everything is more consolidated and cleaner. The code now detects when data that's being decoded is gzip-compressed and will decompress it automatically. Generally things are cleaner. You'll probably have to change some method calls that you were making to support the new options format (ints that you "OR" together).
- v1.5.1 - Fixed bug when decompressing and decoding to a byte[] using decode( String s, boolean gzipCompressed ). Added the ability to "suspend" encoding in the Output Stream so you can turn on and off the encoding if you need to embed base64 data in an otherwise "normal" stream (like an XML file).
- v1.5 - Output stream pases on flush() command but doesn't do anything itself. This helps when using GZIP streams. Added the ability to GZip-compress objects before encoding them.
- v1.4 - Added helper methods to read/write files.
- v1.3.6 - Fixed OutputStream.flush() so that 'position' is reset.
- v1.3.5 - Added flag to turn on and off line breaks. Fixed bug in input stream where last buffer being read, if not completely full, was not returned.
- v1.3.4 - Fixed when "improperly padded stream" error was thrown at the wrong time.
- v1.3.3 - Fixed I/O streams which were totally messed up.

I am placing this code in the Public Domain. Do with it as you will. This software comes with no guarantees or warranties but with plenty of well-wishing instead! Please visit <http://iharder.net/base64> periodically to check for updates or to contribute improvements.

### Nested Class Summary

class	<a href="#">Base64.InputStream</a> Base64.InputStream
class	<a href="#">Base64.OutputStream</a> Base64.OutputStream

## Field Summary

<code>public static final</code>	<a href="#"><u>DECODE</u></a> Specify decoding. Value: <b>0</b>
<code>public static final</code>	<a href="#"><u>DONT_BREAK_LINES</u></a> Don't break lines when encoding (violates strict Base64 specification) Value: <b>8</b>
<code>public static final</code>	<a href="#"><u>ENCODE</u></a> Specify encoding. Value: <b>1</b>
<code>public static final</code>	<a href="#"><u>GZIP</u></a> Specify that data should be gzip-compressed. Value: <b>2</b>
<code>public static final</code>	<a href="#"><u>NO_OPTIONS</u></a> No options specified. Value: <b>0</b>
<code>public static final</code>	<a href="#"><u>ORDERED</u></a> Encode using the special "ordered" dialect of Base64 described here: <a href="http://www.faqs.org/qa/rfc3548.html">http://www.faqs.org/qa/rfc3548.html</a> . Value: <b>32</b>
<code>public static final</code>	<a href="#"><u>URL_SAFE</u></a> Encode using Base64-like encoding that is URL- and Filename-safe as described in Section 4 of RFC3548: <a href="http://www.faqs.org/rfcs/rfc3548.html">http://www.faqs.org/rfcs/rfc3548.html</a> . Value: <b>16</b>

## Method Summary

<code>static byte[]</code>	<a href="#"><u>decode</u></a> (byte[] source, int off, int len, int options) Very low-level access to decoding ASCII characters in the form of a byte array.
<code>static byte[]</code>	<a href="#"><u>decode</u></a> (String s) Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.
<code>static byte[]</code>	<a href="#"><u>decode</u></a> (String s, int options) Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.
<code>static void</code>	<a href="#"><u>decodeFileToFile</u></a> (String infile, String outfile) Reads infile and decodes it to outfile.
<code>static byte[]</code>	<a href="#"><u>decodeFromFile</u></a> (String filename) Convenience method for reading a base64-encoded file and decoding it.
<code>static void</code>	<a href="#"><u>decodeString</u></a> (String inString) Decodes inString and outputs result to stdout
<code>static boolean</code>	<a href="#"><u>decodeToFile</u></a> (String dataToDecode, String filename) Convenience method for decoding data to a file.

static Object	<a href="#"><code>decodeToObject</code></a> (String encodedObject) Attempts to decode Base64 data and deserialize a Java Object within.
static String	<a href="#"><code>encodeBytes</code></a> (byte[] source) Encodes a byte array into Base64 notation.
static String	<a href="#"><code>encodeBytes</code></a> (byte[] source, int options) Encodes a byte array into Base64 notation.
static String	<a href="#"><code>encodeBytes</code></a> (byte[] source, int off, int len) Encodes a byte array into Base64 notation.
static String	<a href="#"><code>encodeBytes</code></a> (byte[] source, int off, int len, int options) Encodes a byte array into Base64 notation.
static void	<a href="#"><code>encodeFileToFile</code></a> (String infile, String outfile) Reads infile and encodes it to outfile.
static String	<a href="#"><code>encodeFromFile</code></a> (String filename) Convenience method for reading a binary file and base64-encoding it.
static String	<a href="#"><code>encodeObject</code></a> (java.io.Serializable serializableObject) Serializes an object and returns the Base64-encoded version of that serialized object.
static String	<a href="#"><code>encodeObject</code></a> (java.io.Serializable serializableObject, int options) Serializes an object and returns the Base64-encoded version of that serialized object.
static void	<a href="#"><code>encodeString</code></a> (String inString) Encodes inString and outputs result to stdout
static boolean	<a href="#"><code>encodeToFile</code></a> (byte[] dataToEncode, String filename) Convenience method for encoding data to a file.
static void	<a href="#"><code>main</code></a> (String[] args) Encodes or decodes two files from the command line; <b>feel free to delete this method (in fact you probably should) if you're embedding this code into a larger program.</b>

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### NO\_OPTIONS

public static final int **NO\_OPTIONS**

No options specified. Value is zero.  
Constant value: **0**

### ENCODE

public static final int **ENCODE**

Specify encoding.  
Constant value: **1**

---

## DECODE

```
public static final int DECODE
```

Specify decoding.  
Constant value: **0**

---

## GZIP

```
public static final int GZIP
```

Specify that data should be gzip-compressed.  
Constant value: **2**

---

## DONT\_BREAK\_LINES

```
public static final int DONT_BREAK_LINES
```

Don't break lines when encoding (violates strict Base64 specification)  
Constant value: **8**

---

## URL\_SAFE

```
public static final int URL_SAFE
```

Encode using Base64-like encoding that is URL- and Filename-safe as described in Section 4 of RFC3548: <http://www.faqs.org/rfcs/rfc3548.html>. It is important to note that data encoded this way is *not* officially valid Base64, or at the very least should not be called Base64 without also specifying that it was encoded using the URL- and Filename-safe dialect.  
Constant value: **16**

---

## ORDERED

```
public static final int ORDERED
```

Encode using the special "ordered" dialect of Base64 described here: <http://www.faqs.org/qa/rfc-1940.html>.  
Constant value: **32**

---

## Methods

### main

```
public final static void main(String[] args)
```

Encodes or decodes two files from the command line; **feel free to delete this method (in fact you probably should) if you're embedding this code into a larger program.**

---

### encodeObject

```
public static String encodeObject(java.io.Serializable serializableObject)
```

Serializes an object and returns the Base64-encoded version of that serialized object. If the object cannot be serialized or there is another error, the method will return null. The object is not GZip-compressed before being encoded.

#### Parameters:

serializableObject - The object to encode

#### Returns:

The Base64-encoded object

---

## encodeObject

```
public static String encodeObject(java.io.Serializable serializableObject,  
    int options)
```

Serializes an object and returns the Base64-encoded version of that serialized object. If the object cannot be serialized or there is another error, the method will return null.

Valid options:

GZIP: gzip-compresses object before encoding it.  
DONT\_BREAK\_LINES: don't break lines at 76 characters  
*Note: Technically, this makes your encoding non-compliant.*

Example: `encodeObject( myObj, Base64.GZIP )` or

Example: `encodeObject( myObj, Base64.GZIP | Base64.DONT_BREAK_LINES )`

### Parameters:

`serializableObject` - The object to encode  
`options` - Specified options

### Returns:

The Base64-encoded object

### See Also:

[GZIP](#)  
[DONT\\_BREAK\\_LINES](#)

---

## encodeBytes

```
public static String encodeBytes(byte[] source)
```

Encodes a byte array into Base64 notation. Does not GZip-compress data.

### Parameters:

`source` - The data to convert

---

## encodeBytes

```
public static String encodeBytes(byte[] source,  
    int options)
```

(continued from last page)

Encodes a byte array into Base64 notation.

Valid options:

GZIP: gzip-compresses object before encoding it.  
DONT\_BREAK\_LINES: don't break lines at 76 characters  
*Note: Technically, this makes your encoding non-compliant.*

Example: `encodeBytes( myData, Base64.GZIP )` or

Example: `encodeBytes( myData, Base64.GZIP | Base64.DONT_BREAK_LINES )`

**Parameters:**

source - The data to convert  
options - Specified options

**See Also:**

[GZIP](#)  
[DONT\\_BREAK\\_LINES](#)

---

## encodeBytes

```
public static String encodeBytes(byte[] source,  
    int off,  
    int len)
```

Encodes a byte array into Base64 notation. Does not GZip-compress data.

**Parameters:**

source - The data to convert  
off - Offset in array where conversion should begin  
len - Length of data to convert

---

## encodeBytes

```
public static String encodeBytes(byte[] source,  
    int off,  
    int len,  
    int options)
```

Encodes a byte array into Base64 notation.

Valid options:

GZIP: gzip-compresses object before encoding it.  
DONT\_BREAK\_LINES: don't break lines at 76 characters  
*Note: Technically, this makes your encoding non-compliant.*

Example: `encodeBytes( myData, Base64.GZIP )` or

Example: `encodeBytes( myData, Base64.GZIP | Base64.DONT_BREAK_LINES )`



(continued from last page)

**Parameters:**

- source - The data to convert
- off - Offset in array where conversion should begin
- len - Length of data to convert
- options - Specified options, alphabet type is pulled from this (standard, url-safe, ordered)

**See Also:**

[GZIP](#)  
[DONT\\_BREAK\\_LINES](#)

---

## decode

```
public static byte[] decode(byte[] source,  
    int off,  
    int len,  
    int options)
```

Very low-level access to decoding ASCII characters in the form of a byte array. Does not support automatically gunzipping or any other "fancy" features.

**Parameters:**

- source - The Base64 encoded data
- off - The offset of where to begin decoding
- len - The length of characters to decode

**Returns:**

decoded data

---

## decode

```
public static byte[] decode(String s)
```

Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.

**Parameters:**

- s - the string to decode

**Returns:**

the decoded data

---

## decode

```
public static byte[] decode(String s,  
    int options)
```

Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.

**Parameters:**

- s - the string to decode
- options - encode options such as URL\_SAFE

**Returns:**

the decoded data

---

## decodeToObject

```
public static Object decodeToObject(String encodedObject)
```

(continued from last page)

Attempts to decode Base64 data and deserialize a Java Object within. Returns null if there was an error.

**Parameters:**

encodedObject - The Base64 data to decode

**Returns:**

The decoded and deserialized object

---

## encodeToFile

```
public static boolean encodeToFile(byte[] dataToEncode,  
    String filename)
```

Convenience method for encoding data to a file.

**Parameters:**

dataToEncode - byte array of data to encode in base64 form  
filename - Filename for saving encoded data

**Returns:**

true if successful, false otherwise

---

## decodeToFile

```
public static boolean decodeToFile(String dataToDecode,  
    String filename)
```

Convenience method for decoding data to a file.

**Parameters:**

dataToDecode - Base64-encoded data as a string  
filename - Filename for saving decoded data

**Returns:**

true if successful, false otherwise

---

## decodeFromFile

```
public static byte[] decodeFromFile(String filename)
```

Convenience method for reading a base64-encoded file and decoding it.

**Parameters:**

filename - Filename for reading encoded data

**Returns:**

decoded byte array or null if unsuccessful

---

## encodeFromFile

```
public static String encodeFromFile(String filename)
```

Convenience method for reading a binary file and base64-encoding it.

**Parameters:**

filename - Filename for reading binary data

**Returns:**

base64-encoded string or null if unsuccessful

---

---

## encodeFileToFile

```
public static void encodeFileToFile(String infile,  
                                     String outfile)
```

Reads infile and encodes it to outfile.

**Parameters:**

infile - Input file  
outfile - Output file

---

## encodeString

```
public static void encodeString(String inString)
```

Encodes inString and outputs result to stdout

**Parameters:**

inString - Input string

---

## decodeString

```
public static void decodeString(String inString)
```

Decodes inString and outputs result to stdout

**Parameters:**

inString - Input string

---

## decodeFileToFile

```
public static void decodeFileToFile(String infile,  
                                     String outfile)
```

Reads infile and decodes it to outfile.

**Parameters:**

infile - Input file  
outfile - Output file

---

## com.wowza.util Class Base64.InputStream

```

java.lang.Object
  |
  +- java.io.InputStream
        |
        +- java.io.FilterInputStream
              |
              +- com.wowza.util.Base64.InputStream
  
```

### All Implemented Interfaces:

java.io.Closeable

public static class **Base64.InputStream**  
extends java.io.FilterInputStream

A [Base64.InputStream](#) will read data from another java.io.InputStream, given in the constructor, and encode/decode to/from Base64 notation on the fly.

### See Also:

[Base64](#)

#### Fields inherited from class java.io.FilterInputStream

in

### Constructor Summary

public	<a href="#">Base64.InputStream</a> (java.io.InputStream in) Constructs a <a href="#">Base64.InputStream</a> in DECODE mode.
public	<a href="#">Base64.InputStream</a> (java.io.InputStream in, int options) Constructs a <a href="#">Base64.InputStream</a> in either ENCODE or DECODE mode.

### Method Summary

int	<a href="#">read</a> () Reads enough of the input stream to convert to/from Base64 and returns the next byte.
int	<a href="#">read</a> (byte[] dest, int off, int len) Calls <a href="#">read()</a> repeatedly until the end of stream is reached or len bytes are read.

#### Methods inherited from class java.io.FilterInputStream

available, close, mark, markSupported, read, read, read, reset, skip

#### Methods inherited from class java.io.InputStream

available, close, mark, markSupported, read, read, read, reset, skip

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface java.io.Closeable

```
close
```

## Constructors

### Base64.InputStream

```
public Base64.InputStream( java.io.InputStream in)
```

Constructs a [Base64.InputStream](#) in DECODE mode.

**Parameters:**

in - the java.io.InputStream from which to read data.

### Base64.InputStream

```
public Base64.InputStream( java.io.InputStream in,  
                           int options)
```

Constructs a [Base64.InputStream](#) in either ENCODE or DECODE mode.

Valid options:

```
ENCODE or DECODE: Encode or Decode as data is read.  
DONT_BREAK_LINES: don't break lines at 76 characters  
    (only meaningful when encoding)  
Note: Technically, this makes your encoding non-compliant.
```

Example: new Base64.InputStream( in, Base64.DECODE )

**Parameters:**

in - the java.io.InputStream from which to read data.

options - Specified options

**See Also:**

[Base64.ENCODE](#)

[Base64.DECODE](#)

[Base64.DONT\\_BREAK\\_LINES](#)

## Methods

### read

```
public int read()  
    throws java.io.IOException
```

Reads enough of the input stream to convert to/from Base64 and returns the next byte.

**Returns:**

next byte

(continued from last page)

**read**

```
public int read(byte[] dest,  
               int off,  
               int len)  
throws java.io.IOException
```

Calls [read\(\)](#) repeatedly until the end of stream is reached or len bytes are read. Returns number of bytes read into array or -1 if end of stream is encountered.

**Parameters:**

dest - array to hold values  
off - offset for array  
len - max number of bytes to read into array

**Returns:**

bytes read into array or -1 if end of stream is encountered.

## com.wowza.util Class Base64.OutputStream

```

java.lang.Object
  |
  +- java.io.OutputStream
        |
        +- java.io.FilterOutputStream
              |
              +- com.wowza.util.Base64.OutputStream
  
```

### All Implemented Interfaces:

java.io.Flushable, java.io.Closeable

public static class **Base64.OutputStream**  
extends java.io.FilterOutputStream

A [Base64.OutputStream](#) will write data to another java.io.OutputStream, given in the constructor, and encode/decode to/from Base64 notation on the fly.

### See Also:

[Base64](#)

### Fields inherited from class java.io.FilterOutputStream

out

## Constructor Summary

public	<a href="#">Base64.OutputStream</a> ( java.io.OutputStream out) Constructs a <a href="#">Base64.OutputStream</a> in ENCODE mode.
public	<a href="#">Base64.OutputStream</a> ( java.io.OutputStream out, int options) Constructs a <a href="#">Base64.OutputStream</a> in either ENCODE or DECODE mode.

## Method Summary

void	<a href="#">close</a> () Flushes and closes (I think, in the superclass) the stream.
void	<a href="#">flushBase64</a> () Method added by PHIL.
void	<a href="#">resumeEncoding</a> () Resumes encoding of the stream.
void	<a href="#">suspendEncoding</a> () Suspends encoding of the stream.
void	<a href="#">write</a> (byte[] theBytes, int off, int len) Calls <a href="#">write(int)</a> repeatedly until len bytes are written.
void	<a href="#">write</a> (int theByte) Writes the byte to the output stream after converting to/from Base64 notation.

### Methods inherited from class java.io.FilterOutputStream

```
close, flush, write, write, write
```

#### Methods inherited from class `java.io.OutputStream`

```
close, flush, write, write, write
```

#### Methods inherited from class `java.lang.Object`

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

#### Methods inherited from interface `java.io.Closeable`

```
close
```

#### Methods inherited from interface `java.io.Flushable`

```
flush
```

## Constructors

### Base64.OutputStream

```
public Base64.OutputStream(java.io.OutputStream out)
```

Constructs a [Base64.OutputStream](#) in ENCODE mode.

#### Parameters:

out - the java.io.OutputStream to which data will be written.

### Base64.OutputStream

```
public Base64.OutputStream(java.io.OutputStream out,  
                           int options)
```

Constructs a [Base64.OutputStream](#) in either ENCODE or DECODE mode.

Valid options:

```
ENCODE or DECODE: Encode or Decode as data is read.  
DONT_BREAK_LINES: don't break lines at 76 characters  
    (only meaningful when encoding)  
Note: Technically, this makes your encoding non-compliant.
```

Example: `new Base64.OutputStream( out, Base64.ENCODE )`

#### Parameters:

out - the java.io.OutputStream to which data will be written.  
options - Specified options.



(continued from last page)

**See Also:**[Base64.ENCODER](#)[Base64.DECODER](#)[Base64.DONT\\_BREAK\\_LINES](#)

## Methods

### write

```
public void write(int theByte)
    throws java.io.IOException
```

Writes the byte to the output stream after converting to/from Base64 notation. When encoding, bytes are buffered three at a time before the output stream actually gets a `write()` call. When decoding, bytes are buffered four at a time.

**Parameters:**

`theByte` - the byte to write

### write

```
public void write(byte[] theBytes,
    int off,
    int len)
    throws java.io.IOException
```

Calls [write\(int\)](#) repeatedly until `len` bytes are written.

**Parameters:**

`theBytes` - array from which to read bytes

`off` - offset for array

`len` - max number of bytes to read into array

### flushBase64

```
public void flushBase64()
    throws java.io.IOException
```

Method added by PHIL. [Thanks, PHIL. -Rob] This pads the buffer without closing the stream.

### close

```
public void close()
    throws java.io.IOException
```

Flushes and closes (I think, in the superclass) the stream.

### suspendEncoding

```
public void suspendEncoding()
    throws java.io.IOException
```

Suspends encoding of the stream. May be helpful if you need to embed a piece of base64-encoded data in a stream.

### resumeEncoding

```
public void resumeEncoding()
```

Resumes encoding of the stream. May be helpful if you need to embed a piece of base64-encoded data in a stream.

## com.wowza.util Class BufferUtils

java.lang.Object

└─com.wowza.util.BufferUtils

public class **BufferUtils**  
extends Object

BufferUtils: utilities for converting between binary data and Java primitive types. Faster than Java runtime equivalents

### Field Summary

public static final	<a href="#">alphas</a>
public static final	<a href="#">hexadecimal</a>

### Constructor Summary

public	<a href="#">BufferUtils()</a>
--------	-------------------------------

### Method Summary

static int	<a href="#">byteArrayToInt</a> (byte[] b) Convert byte array to int
static int	<a href="#">byteArrayToInt</a> (byte[] b, int offset) Conver byte array to int with offset
static int	<a href="#">byteArrayToInt</a> (byte[] b, int offset, int count) Convert byte array to int with offset.
static int	<a href="#">byteArrayToInt</a> (byte[] b, int offset, int count, boolean isReverse) Convert byte array to int with offset.
static long	<a href="#">byteArrayToLong</a> (byte[] b) Convert byte array to long
static long	<a href="#">byteArrayToLong</a> (byte[] b, int offset) Conver byte array to long with offset
static long	<a href="#">byteArrayToLong</a> (byte[] b, int offset, int count) Convert byte array to long with offset.
static long	<a href="#">byteArrayToLong</a> (byte[] b, int offset, int count, boolean isReverse) Convert byte array to long with offset.
static int	<a href="#">byteArrayToShort</a> (byte[] b) Convert byte array to int

static int	<a href="#"><code>byteArrayToShort</code></a> (byte[] b, int offset) Convert byte array to int with offset
static int	<a href="#"><code>byteArrayToShort</code></a> (byte[] b, int offset, int count) Convert byte array to int with offset.
static int	<a href="#"><code>byteArrayToShort</code></a> (byte[] b, int offset, int count, boolean isReverse) Convert byte array to int with offset.
static String	<a href="#"><code>byteArrayToString</code></a> (byte[] b) Convert a byte array to a String (UTF-8 encoding assumed)
static String	<a href="#"><code>byteArrayToString</code></a> (byte[] b, int offset, int count) Convert a byte array to a String (UTF-8 encoding assumed)
static byte[]	<a href="#"><code>decodeHexString</code></a> (String hexStr) Decode a string as a byte array
static int	<a href="#"><code>doCRC32</code></a> (int crc, byte[] buffer, int offset, int len) Calculate an IEEE CRC32 value for MPEG transport stream from a starting crc value
static String	<a href="#"><code>encodeHexString</code></a> (byte[] bytes) Encode a byte array as a string
static String	<a href="#"><code>encodeHexString</code></a> (byte[] bytes, int offset, int len) Encode a byte array as a string
static int	<a href="#"><code>getUnsignedShort</code></a> (java.nio.ByteBuffer buffer)
static int	<a href="#"><code>indexOf</code></a> (byte[] source, byte[] pattern) Finds the first occurrence of a byte pattern in a byte buffer.
static int	<a href="#"><code>indexOfDifferent</code></a> (byte[] buffer1, byte[] buffer2) Compare two byte buffers, and return the index of the first byte that is different.
static byte[]	<a href="#"><code>intToByteArray</code></a> (int value) Convert a int value to a byte array in network order
static void	<a href="#"><code>intToByteArray</code></a> (int value, byte[] buffer, int offset, int size) Convert a int value to a byte array in network order
static void	<a href="#"><code>intToByteArray</code></a> (int value, byte[] buffer, int offset, int size, boolean isReverse) Convert a int value to a byte array in network order
static byte[]	<a href="#"><code>intToByteArray</code></a> (int value, int size) Convert a int value to a byte array in network order
static byte[]	<a href="#"><code>longToByteArray</code></a> (long value) Convert a long value to a byte array in network order
static void	<a href="#"><code>longToByteArray</code></a> (long value, byte[] buffer, int offset, int size) Convert a long value to a byte array in network order
static void	<a href="#"><code>longToByteArray</code></a> (long value, byte[] buffer, int offset, int size, boolean isReverse) Convert a long value to a byte array in network order
static byte[]	<a href="#"><code>longToByteArray</code></a> (long value, int size) Convert a long value to a byte array in network order

static boolean

[startsWith](#)(byte[] source, byte[] pattern)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### hexadecimal

public static final java.lang.String **hexadecimal**

### alphas

public static final java.lang.String **alphas**

## Constructors

### BufferUtils

public **BufferUtils**()

## Methods

### encodeHexString

public static String **encodeHexString**(byte[] bytes)

Encode a byte array as a string

**Parameters:**

bytes - byte array

**Returns:**

string

### encodeHexString

public static String **encodeHexString**(byte[] bytes,  
int offset,  
int len)

Encode a byte array as a string

**Parameters:**

bytes - byte array

offset - offset

len - length

(continued from last page)

**Returns:**  
string

---

## decodeHexString

```
public static byte[] decodeHexString(String hexStr)
```

Decode a string as a byte array

**Parameters:**  
hexStr - string

**Returns:**  
byte array

---

## byteArrayToString

```
public static String byteArrayToString(byte[] b)
```

Convert a byte array to a String (UTF-8 encoding assumed)

**Parameters:**  
b - byte array

**Returns:**  
resultant string

---

## byteArrayToString

```
public static String byteArrayToString(byte[] b,  
    int offset,  
    int count)
```

Convert a byte array to a String (UTF-8 encoding assumed)

**Parameters:**  
b - byte array  
offset - offset  
count - len

**Returns:**  
resultant string

---

## byteArrayToLong

```
public static long byteArrayToLong(byte[] b)
```

Convert byte array to long

**Parameters:**  
b - byte array (8 bytes)

**Returns:**  
long value

(continued from last page)

## byteArrayToLong

```
public static long byteArrayToLong(byte[] b,  
    int offset)
```

Conver byte array to long with offset

**Parameters:**

b - byte array (8 bytes)

offset - offset

**Returns:**

long value

---

## byteArrayToLong

```
public static long byteArrayToLong(byte[] b,  
    int offset,  
    int count)
```

Convert byte array to long with offset. Count is the number of bytes. Can be less than 8. If less than 8 just fills lower bits in value.

**Parameters:**

b - byte array

offset - offset

count - number of bytes

**Returns:**

long value

---

## byteArrayToLong

```
public static long byteArrayToLong(byte[] b,  
    int offset,  
    int count,  
    boolean isReverse)
```

Convert byte array to long with offset. Count is the number of bytes. Can be less than 8. If less than 8 just fills lower bits in value. The reverse flag allows data to be in reverse order.

**Parameters:**

b - byte array

offset - offset

count - number of bytes

isReverse - is data in reverse order

**Returns:**

long value

---

## byteArrayToInt

```
public static int byteArrayToInt(byte[] b)
```

Convert byte array to int

**Parameters:**

b - byte array (4 bytes)

**Returns:**

(continued from last page)

int value

---

## byteArrayToInt

```
public static int byteArrayToInt(byte[] b,  
    int offset)
```

Conver byte array to int with offset

### Parameters:

b - byte array (4 bytes)  
offset - offset

### Returns:

int value

---

## byteArrayToInt

```
public static int byteArrayToInt(byte[] b,  
    int offset,  
    int count)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 4. If less than 4 just fills lower bits in value.

### Parameters:

b - byte array  
offset - offset  
count - number of bytes

### Returns:

int value

---

## byteArrayToInt

```
public static int byteArrayToInt(byte[] b,  
    int offset,  
    int count,  
    boolean isReverse)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 4. If less than 4 just fills lower bits in value. The reverse flag allows data to be in reverse order.

### Parameters:

b - byte array  
offset - offset  
count - number of bytes  
isReverse - is data in reverse order

### Returns:

int value

---

## byteArrayToShort

```
public static int byteArrayToShort(byte[] b)
```

Convert byte array to int

### Parameters:

b - byte array (2 bytes)

---

(continued from last page)

**Returns:**

int value

---

## byteArrayToShort

```
public static int byteArrayToShort(byte[] b,  
    int offset)
```

Conver byte array to int with offset

**Parameters:**

b - byte array (2 bytes)  
offset - offset

**Returns:**

int value

---

## byteArrayToShort

```
public static int byteArrayToShort(byte[] b,  
    int offset,  
    int count)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 2. If less than 2 just fills lower bits in value.

**Parameters:**

b - byte array  
offset - offset  
count - number of bytes

**Returns:**

int value

---

## byteArrayToShort

```
public static int byteArrayToShort(byte[] b,  
    int offset,  
    int count,  
    boolean isReverse)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 2. If less than 2 just fills lower bits in value. The reverse flag allows data to be in reverse order.

**Parameters:**

b - byte array  
offset - offset  
count - number of bytes  
isReverse - is data in reverse order

**Returns:**

int value

---

## intToByteArray

```
public static byte[] intToByteArray(int value)
```

Convert a int value to a byte array in network order

**Parameters:**

value - value



(continued from last page)

**Returns:**4-byte array with value

---

**intToByteArray**

```
public static byte[] intToByteArray(int value,
                                     int size)
```

Convert a int value to a byte array in network order

**Parameters:**

value - value

size - size of resultant byte array

**Returns:**size-byte array with value

---

**intToByteArray**

```
public static void intToByteArray(int value,
                                   byte[] buffer,
                                   int offset,
                                   int size)
```

Convert a int value to a byte array in network order

**Parameters:**

value - value

buffer - destination byte array

offset - starting offset in byte array

size - number of bytes to write

---

**intToByteArray**

```
public static void intToByteArray(int value,
                                   byte[] buffer,
                                   int offset,
                                   int size,
                                   boolean isReverse)
```

Convert a int value to a byte array in network order

**Parameters:**

value - value

buffer - destination byte array

offset - starting offset in byte array

size - number of bytes to write

isReverse - is data in reverse order

---

**longToByteArray**

```
public static byte[] longToByteArray(long value)
```

Convert a long value to a byte array in network order

**Parameters:**

value - value

**Returns:**

(continued from last page)

8-byte array with value

---

## longToByteArray

```
public static byte[] longToByteArray(long value,  
                                     int size)
```

Convert a long value to a byte array in network order

**Parameters:**

value - value

size - size of resultant byte array

**Returns:**

size-byte array with value

---

## longToByteArray

```
public static void longToByteArray(long value,  
                                   byte[] buffer,  
                                   int offset,  
                                   int size)
```

Convert a long value to a byte array in network order

**Parameters:**

value - value

buffer - destination byte array

offset - starting offset in byte array

size - number of bytes to write

---

## longToByteArray

```
public static void longToByteArray(long value,  
                                   byte[] buffer,  
                                   int offset,  
                                   int size,  
                                   boolean isReverse)
```

Convert a long value to a byte array in network order

**Parameters:**

value - value

buffer - destination byte array

offset - starting offset in byte array

size - number of bytes to write

isReverse - is data in reverse order

---

## getUnsignedShort

```
public static int getUnsignedShort(java.nio.ByteBuffer buffer)
```

---

## doCRC32

```
public static int doCRC32(int crc,  
                           byte[] buffer,  
                           int offset,  
                           int len)
```

---

(continued from last page)

Calculate an IEEE CRC32 value for MPEG transport stream from a starting crc value

**Parameters:**

crc - starting crc value  
buffer - buffer  
offset - offset  
len - len

**Returns:**

crc value

---

## indexOf

```
public static int indexOf(byte[] source,  
                        byte[] pattern)
```

Finds the first occurrence of a byte pattern in a byte buffer.

Note: If we want to improve the performance, we could implement the Knuth-Morris-Pratt algorithm. But I don't need the speed nor do I have time today!

**Parameters:**

source - The source byte buffer  
pattern - the pattern we're looking for.

**Returns:**

the index of source where the pattern is found, else -1

---

## indexOfDifferent

```
public static int indexOfDifferent(byte[] buffer1,  
                                   byte[] buffer2)
```

Compare two byte buffers, and return the index of the first byte that is different.

**Parameters:**

buffer1 - byte array1  
buffer2 - byte array2

**Returns:**

index where buffers differ, or -1.

---

## startsWith

```
public static boolean startsWith(byte[] source,  
                                 byte[] pattern)
```

## com.wowza.util Class DebugUtils

java.lang.Object

└─com.wowza.util.DebugUtils

public final class **DebugUtils**  
extends Object

DebugUtils: Debugging utilities.

### Constructor Summary

public	<a href="#">DebugUtils()</a>
--------	------------------------------

### Method Summary

static java.io.File	<a href="#">byteArrayToFile</a> (byte[] data, String filePath) Dump a buffer of bytes to a file.
static boolean	<a href="#">doesStackContainMethod</a> (String methodName) Examine current stack trace to determine if the specified method name in the the trace.
static String	<a href="#">formatBytes</a> (byte[] data) Format byte array for printing.
static String	<a href="#">formatBytes</a> (byte[] data, boolean showIndex) Format byte array for printing.
static String	<a href="#">formatBytes</a> (byte[] data, int offset, int len) Format byte array for printing.
static String	<a href="#">formatBytes</a> (byte[] data, int offset, int len, boolean showIndex) Format byte array for printing.
static String	<a href="#">formatBytesInSingleRow</a> (byte[] data, int offset, int len) Format byte array for printing.
static String	<a href="#">formatBytesShort</a> (byte[] data) Format byte array for printing.
static String	<a href="#">formatBytesShort</a> (byte[] data, int offset, int len) Format byte array for printing.
static String	<a href="#">formatBytesStruct</a> (byte[] data)
static String	<a href="#">formatBytesStruct</a> (byte[] data, int offset, int len) Format byte array for printing.
static String	<a href="#">formatMilliseconds</a> (long ms) Give a time in seconds, return a String representing the time in hh:mm:ss.mmm.

static String	<a href="#"><code>formatSeconds</code></a> (long t) Give a time in seconds, return a String representing the time in hh:mm:ss.
static String	<a href="#"><code>formatUtcTime</code></a> (long utcTime)
static String	<a href="#"><code>stackTraceToSingleLineString</code></a> (Throwable e, int maxLines) Given an exception, return single line String representation.
static String	<a href="#"><code>stackTraceToString</code></a> (Throwable e) Given an exception, return String representation.
static String	<a href="#"><code>stackTraceToString</code></a> (Throwable e, int maxLines, String separator) Given an exception, return single line String representation.
static String	<a href="#"><code>toHex</code></a> (byte value) Format a byte value to a 0xff format
static String	<a href="#"><code>toHex</code></a> (int value) Format a byte value to a 0xffffffff format
static String	<a href="#"><code>toLong</code></a> (long value) Format a long value to a 0xffffffffffffffff format

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### DebugUtils

```
public DebugUtils()
```

## Methods

### formatBytesShort

```
public static String formatBytesShort(byte[] data)
```

Format byte array for printing. Simple format as rows of hex values (16 values per row)

#### Parameters:

data - byte array

#### Returns:

formatted string

### formatBytesShort

```
public static String formatBytesShort(byte[] data,  
    int offset,  
    int len)
```

(continued from last page)

Format byte array for printing. Simple format as rows of hex values (16 values per row)

**Parameters:**

data - byte array  
offset - offset in array  
len - data len

**Returns:**

formatted string

---

## formatBytes

```
public static String formatBytes(byte[] data)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

**Parameters:**

data - byte array

**Returns:**

formatted string

---

## formatBytes

```
public static String formatBytes(byte[] data,  
    boolean showIndex)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

**Parameters:**

data - byte array

**Returns:**

formatted string

---

## formatBytes

```
public static String formatBytes(byte[] data,  
    int offset,  
    int len)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

**Parameters:**

data - byte array  
offset - start index in array  
len - length to format

**Returns:**

formatted string

---

## formatBytes

```
public static String formatBytes(byte[] data,  
    int offset,  
    int len,  
    boolean showIndex)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

---

(continued from last page)

**Parameters:**

data - byte array  
offset - start index in array  
len - length to format

**Returns:**

formatted string

---

## formatBytesInSingleRow

```
public static String formatBytesInSingleRow(byte[] data,  
    int offset,  
    int len)
```

Format byte array for printing. Format as rows of hex values all in one row along with text representation of data.

**Parameters:**

data - byte array  
offset - start index in array  
len - length to format

**Returns:**

formatted string

---

## formatBytesStruct

```
public static String formatBytesStruct(byte[] data)
```

---

## formatBytesStruct

```
public static String formatBytesStruct(byte[] data,  
    int offset,  
    int len)
```

Format byte array for printing. Format as Java primitive byte values (8 per row).

**Parameters:**

data - byte array

**Returns:**

formatted string

---

## toHex

```
public static String toHex(byte value)
```

Format a byte value to a 0xff format

**Parameters:**

value - byte value

**Returns:**

return string

---

## toHex

```
public static String toHex(int value)
```

(continued from last page)

Format a byte value to a 0xffffffff format

**Parameters:**

value - int value

**Returns:**

return string

---

## toLong

```
public static String toLong(long value)
```

Format a long value to a 0xffffffffffffffff format

**Parameters:**

value - long value

**Returns:**

return string

---

## byteArrayToFile

```
public static java.io.File byteArrayToFile(byte[] data,  
String filePath)
```

Dump a buffer of bytes to a file. Useful for debugging.

**Parameters:**

data - a buffer of bytes

filePath - The path and filename

---

## formatSeconds

```
public static String formatSeconds(long t)
```

Give a time in seconds, return a String representing the time in hh:mm:ss.

123 s --> 00:02:03

**Parameters:**

t

**Returns:**

time representation

---

## formatMilliseconds

```
public static String formatMilliseconds(long ms)
```

Give a time in seconds, return a String representing the time in hh:mm:ss.mmm.

123456 ms --> 00:02:03.456

**Parameters:**

ms

**Returns:**

time representation

---



## formatUtcTime

```
public static String formatUtcTime(long utcTime)
```

---

## stackTraceToString

```
public static String stackTraceToString(Throwable e)
```

Given an exception, return String representation. Note: this is the entire raw stack trace including tabs and line endings

**Parameters:**

e - throwable

**Returns:**

stack trace representation

---

## stackTraceToSingleLineString

```
public static String stackTraceToSingleLineString(Throwable e,  
int maxLines)
```

Given an exception, return single line String representation. Note: line endings are replaced with "|" character. Tabs are removed.

**Parameters:**

e - throwable

maxLines - If greater than zero, returns only first maxLines of trace

**Returns:**

stack trace info

---

## stackTraceToString

```
public static String stackTraceToString(Throwable e,  
int maxLines,  
String seperator)
```

Given an exception, return single line String representation. Note: line endings are replaced with "|" character. Tabs are removed.

**Parameters:**

e - throwable

maxLines - If greater than zero, returns only first maxLines of trace

seperator - character to replace line endings with

**Returns:**

stack trace info

---

## doesStackContainMethod

```
public static boolean doesStackContainMethod(String methodName)
```

Examine current stack trace to determine if the specified method name in the the trace.

Could be enhanced quite a bit by also checking for Class and method. But simple for now.

**Parameters:**

(continued from last page)

methodName

**Returns:**

true if in trace, else false

## com.wowza.util Class ElapsedTimer

java.lang.Object

└─com.wowza.util.ElapsedTimer

public class **ElapsedTimer**  
extends Object

ElapsedTimer: Utility class for keep track of the duration an object has been in existence.

### Constructor Summary

public	<a href="#">ElapsedTimer()</a> Construct a new ElapsedTimer and start the clock
--------	--

### Method Summary

java.util.Date	<a href="#">getDate()</a> Get the date the object was created
String	<a href="#">getDateString()</a> Get the date object was created as formatted String
long	<a href="#">getTime()</a> Get elapsed time object in existence (milliseconds)
double	<a href="#">getTimeSeconds()</a> Get elapsed time object in seconds
String	<a href="#">getTimeString()</a> Get elapsed time object in existence as formatted String (Ex: 3 days 2 minutes 5 seconds)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### ElapsedTimer

public **ElapsedTimer()**

Construct a new ElapsedTimer and start the clock

### Methods

(continued from last page)

## getDate

```
public java.util.Date getDate()
```

Get the date the object was created

**Returns:**

date object created

---

## getDateString

```
public String getDateString()
```

Get the date object was created as formatted String

**Returns:**

date object created as formatted String

---

## getTime

```
public long getTime()
```

Get elapsed time object in existence (milliseconds)

**Returns:**

elapsed time (milliseconds)

---

## getTimeSeconds

```
public double getTimeSeconds()
```

Get elapsed time object in seconds

**Returns:**

elapsed time in seconds

---

## getTimeString

```
public String getTimeString()
```

Get elapsed time object in existence as formatted String (Ex: 3 days 2 minutes 5 seconds)

**Returns:**

elapsed time as formatted String

---

## com.wowza.util Class FileUtils

java.lang.Object

└─com.wowza.util.FileUtils

public class **FileUtils**  
extends Object

FileUtils: File utilities

### Constructor Summary

public	<a href="#">FileUtils()</a>
--------	-----------------------------

### Method Summary

static void	<a href="#">closeQuietly</a> (java.io.InputStream stream)
static void	<a href="#">closeQuietly</a> (java.io.OutputStream stream)
static void	<a href="#">closeQuietly</a> (java.io.Reader reader)
static void	<a href="#">copyFile</a> (java.io.File fromFile, java.io.File toFile) Simple file copy routine
static void	<a href="#">copyFile2</a> (java.io.File fromFile, java.io.File toFile)
static boolean	<a href="#">deleteDirectory</a> (java.io.File path)
static byte[]	<a href="#">fileToByteArray</a> (java.io.File file)
static String	<a href="#">streamNameToValidFilename</a> (String name) Encode a stream name (deal with path elements) to a valid filename.
static String	<a href="#">toValidFilename</a> (String name) Encode a name to a valid filename.
static void	<a href="#">traverseDirectory</a> (java.io.File dir, <a href="#">IFileProcess</a> fileNotify) Traverse a directory recursively calling fileNotify for each file and folder encountered
static java.io.File	<a href="#">versionFile</a> (java.io.File newFile) Rename a file using the file format [original-name]_#[.ext].

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### FileUtils

```
public FileUtils()
```

## Methods

### fileToByteArray

```
public static byte[] fileToByteArray(java.io.File file)
```

---

### streamNameToValidFilename

```
public static String streamNameToValidFilename(String name)
```

Encode a stream name (deal with path elements) to a valid filename.

**Parameters:**

name - stream name

**Returns:**

encoded filename

---

### toValidFilename

```
public static String toValidFilename(String name)
```

Encode a name to a valid filename.

**Parameters:**

name

**Returns:**

encoded filename

---

### copyFile

```
public static void copyFile(java.io.File fromFile,  
                             java.io.File toFile)
```

Simple file copy routine

**Parameters:**

fromFile - from file

toFile - to file

---

### copyFile2

```
public static void copyFile2(java.io.File fromFile,  
                              java.io.File toFile)  
    throws java.io.IOException
```

## closeQuietly

```
public static void closeQuietly(java.io.InputStream stream)
```

---

## closeQuietly

```
public static void closeQuietly(java.io.OutputStream stream)
```

---

## closeQuietly

```
public static void closeQuietly(java.io.Reader reader)
```

---

## deleteDirectory

```
public static boolean deleteDirectory(java.io.File path)
```

---

## versionFile

```
public static java.io.File versionFile(java.io.File newFile)
```

Rename a file using the file format [original-name]\_#[.ext].

**Parameters:**

newFile - input file

**Returns:**

renamed file

---

## traverseDirectory

```
public static void traverseDirectory(java.io.File dir,  
    IFileProcess fileNotify)
```

Traverse a directory recursively calling fileNotify for each file and folder encountered

**Parameters:**

dir - starting directory

fileNotify - file notify object

---

## com.wowza.util Class FLVUtils

java.lang.Object

└─com.wowza.util.FLVUtils

public final class **FLVUtils**  
extends Object

FLVUtils: utility for reading and writing .flv files.

### Field Summary

public static final	<a href="#"><u>FLV_CHUNKHEADER_BUFFERSIZE</u></a> Size of temporary buffer needed for flv reading (byte[]) Value: <b>13</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_FIRSTBYTE</u></a> Header values: first byte of packet data Value: <b>3</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_HEADERSIZE</u></a> Size of packet header (byte[]) Value: <b>11</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_ISIZE</u></a> Header values: packet size Value: <b>1</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_ITIMECODE</u></a> Header values: timecode (milliseconds) Value: <b>2</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_ITYPE</u></a> Header values: packet type Value: <b>0</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_SECONDBYTE</u></a> Header values: second byte of packet data Value: <b>4</b>
public static final	<a href="#"><u>FLV_CHUNKHEADER_VALUESIZE</u></a> Size of header values array (long[]) Value: <b>5</b>
public static final	<a href="#"><u>FLV_DFRAME</u></a> D video frame type (partial frame based on key frame) Value: <b>3</b>
public static final	<a href="#"><u>FLV_KFRAME</u></a> Key video frame type Value: <b>1</b>



public static final	<a href="#">FLV_PFRAME</a> P video frame type (partial frame based on previous frame) Value: <b>2</b>
public static final	<a href="#">FLV_TCINDEXAUDIO</a> Value: <b>0</b>
public static final	<a href="#">FLV_TCINDEXDATA</a> Value: <b>2</b>
public static final	<a href="#">FLV_TCINDEXVIDEO</a> Value: <b>1</b>
public static final	<a href="#">FLV_UFRAME</a> Unknown video frame type Value: <b>0</b>

## Constructor Summary

public	<a href="#">FLVUtils()</a>
--------	----------------------------

## Method Summary

static long	<a href="#">adjustFirstPacketTCs</a> (java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs) Align list of timecode for each data type.
static int	<a href="#">audioCodecStringToId</a> (String codecString) Parse a string to get the codec ID defined by IVHost.CODEC_AUDIO_*
static String	<a href="#">audioCodecToMetaDataString</a> (int codec) Get a printable string representation of the audio codecs defined as IVHost.CODEC_AUDIO_* as the string used in the onMetaData event
static String	<a href="#">audioCodecToString</a> (int codec) Get a printable string representation of the audio codecs defined as IVHost.CODEC_AUDIO_*
static String	<a href="#">frameTypeToString</a> (int frameType)
static int	<a href="#">getAudioCodec</a> ( <a href="#">AMFPacket</a> packet) Get the codec id for this audio packet.
static int	<a href="#">getAudioCodec</a> (int value) Return the codec portion of the first byte of an audio packet.
static int	<a href="#">getAudioMP3Layer</a> ( <a href="#">AMFPacket</a> packet) Audio marked as MP3 is really MPEG1 Layer 1-3.
static int	<a href="#">getFrameType</a> (byte value) Given the first byte of a video packet, determine the frame type (FLV_*FRAME)
static int	<a href="#">getFrameType</a> (int value) Given the first byte of a video packet, determine the frame type (FLV_*FRAME)

static int	<a href="#"><u>getFrameType</u></a> (int[] values) Given the headers values (including first byte of the packet), determine the type of video frame (FLV_*FRAME)
static long	<a href="#"><u>getLastTC</u></a> (java.io.File file) Get the duration of an .flv file.
static OnMetadataBasic	<a href="#"><u>getOnMetadataData</u></a> ( <a href="#"><u>AMFPacket</u></a> metaDataPacket)
static int	<a href="#"><u>getVideoCodec</u></a> ( <a href="#"><u>AMFPacket</u></a> packet) Get the codec id for this video packet.
static int	<a href="#"><u>getVideoCodec</u></a> (int value) Return the codec portion of the first byte of an video packet.
static int	<a href="#"><u>getVideoFrameType</u></a> ( <a href="#"><u>AMFPacket</u></a> packet)
static int	<a href="#"><u>getVideoTimecodeOffset</u></a> ( <a href="#"><u>AMFPacket</u></a> packet) Get the timecode offset in milliseconds between the PTS and DTS for this frame.
static int	<a href="#"><u>getVideoTimecodeOffset</u></a> (byte[] buffer) Get the timecode offset in milliseconds between the PTS and DTS for this frame.
static java.util.List	<a href="#"><u>interleavePackets</u></a> (java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, long[] currentTCs) This is a utility function primarily used for IMediaWriters.
static java.util.List	<a href="#"><u>interleavePackets</u></a> (java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, long[] currentTCs) This is a utility function primarily used for IMediaWriters.
static boolean	<a href="#"><u>isAudioCodecConfig</u></a> ( <a href="#"><u>AMFPacket</u></a> packet) Returns true if the packet is a video codec config packet
static boolean	<a href="#"><u>isOnMetadataPacket</u></a> ( <a href="#"><u>AMFPacket</u></a> packet) Returns true if packet is onMetaData or [@setDataFrame, onMetaData] data packet.
static boolean	<a href="#"><u>isVideoCodecConfig</u></a> ( <a href="#"><u>AMFPacket</u></a> packet) Returns true if the packet is a video codec config packet
static boolean	<a href="#"><u>isVideoKeyFrame</u></a> ( <a href="#"><u>AMFPacket</u></a> packet) Returns true if the packet is a video key frame
static boolean	<a href="#"><u>isVideoKeyFrame</u></a> (byte[] buffer) Returns true if the packet is a video key frame
static boolean	<a href="#"><u>isVideoKeyFrame</u></a> (java.nio.ByteBuffer buffer) Returns true if the packet is a video key frame
static boolean	<a href="#"><u>isVideoKeyFrame</u></a> (int[] chunkHeaderValues) Returns true if the packet is a video key frame
static <a href="#"><u>AMFPacket</u></a>	<a href="#"><u>readChunk</u></a> (java.io.DataInput is) Read a packets worth of .flv data from an InputStream and return as an AMFPacket
static <a href="#"><u>AMFPacket</u></a>	<a href="#"><u>readChunk</u></a> (java.io.InputStream is) Read a packets worth of .flv data from an InputStream and return as an AMFPacket

static void	<a href="#"><u>readChunkHeader</u></a> (java.io.RandomAccessFile is, byte[] buffer, int[] values) Read packet header.
static boolean	<a href="#"><u>readHeader</u></a> (java.io.DataInput is) Read file header.
static boolean	<a href="#"><u>readHeader</u></a> (java.io.InputStream is) Read file header.
static void	<a href="#"><u>readPrevChunkHeader</u></a> (java.io.RandomAccessFile is, byte[] buffer, int[] values) Back up one packet from current position in the file and read the packet header.
static String	<a href="#"><u>streamCodecToString</u></a> (int codec) Get a printable string representation of the stream codecs defined as IVHost.CODEC_STREAM_*
static <a href="#"><u>AMFPacket</u></a>	<a href="#"><u>updateOnCuePointTimecode</u></a> ( <a href="#"><u>AMFPacket</u></a> packet, long timecode)
static java.nio.ByteBuffer	<a href="#"><u>updateOnCuePointTimecode</u></a> (java.nio.ByteBuffer data, int dataType, long timecode)
static int	<a href="#"><u>videoCodecStringToId</u></a> (String codecString) Parse a string to get the codec ID defined by IVHost.CODEC_VIDEO_*
static String	<a href="#"><u>videoCodecToMetaDataString</u></a> (int codec) Get a printable string representation of the video codecs defined as IVHost.CODEC_VIDEO_* as the string used in the onMetaData event
static String	<a href="#"><u>videoCodecToString</u></a> (int codec) Get a printable string representation of the video codecs defined as IVHost.CODEC_VIDEO_*
static void	<a href="#"><u>writeChunk</u></a> (java.io.DataOutput ds, java.nio.ByteBuffer data, int size, long timecode, byte type)
static void	<a href="#"><u>writeChunk</u></a> (java.io.OutputStream ds, java.nio.ByteBuffer data, int size, long timecode, byte type) Write a packets worth of data.
static void	<a href="#"><u>writeDuration</u></a> (java.io.File file, double duration) Write the duration to an existing .flv file.
static void	<a href="#"><u>writeHeader</u></a> (java.io.OutputStream ds, double duration, int audiocodecid, int videocodecid, String createdBy, java.util.Map extraMetadata) Write file header including onMetaData packet.
static void	<a href="#"><u>writeHeader</u></a> (java.io.OutputStream ds, double duration, java.util.Map extraMetadata) Write file header including onMetaData packet.
static void	<a href="#"><u>writePackets</u></a> (java.io.OutputStream ds, java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, long[] currentTCs) Write a bunch of packets to .flv file all at once.

static void	<a href="#">writePackets</a> (java.io.OutputStream ds, java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, long[] currentTCs, IFLVWriterAdjustTimecode dataPacketTimecodeAdjuster) Write a bunch of packets to .flv file all at once.
static void	<a href="#">writePackets</a> (java.io.OutputStream ds, java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, long[] currentTCs) Write a bunch of packets to .flv file all at once.
static void	<a href="#">writePackets</a> (java.io.OutputStream ds, java.util.List packetList, long tcOffset) Write audio/video/data packets to an .flv file.
static void	<a href="#">writeShortHeader</a> (java.io.DataOutput ds)
static void	<a href="#">writeShortHeader</a> (java.io.OutputStream ds) Write just the FLV file header (without the metadata packet)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### FLV\_CHUNKHEADER\_ITYPE

```
public static final int FLV_CHUNKHEADER_ITYPE
```

Header values: packet type  
Constant value: **0**

### FLV\_CHUNKHEADER\_ISIZE

```
public static final int FLV_CHUNKHEADER_ISIZE
```

Header values: packet size  
Constant value: **1**

### FLV\_CHUNKHEADER\_IMECODE

```
public static final int FLV_CHUNKHEADER_IMECODE
```

Header values: timecode (milliseconds)  
Constant value: **2**

### FLV\_CHUNKHEADER\_FIRSTBYTE

```
public static final int FLV_CHUNKHEADER_FIRSTBYTE
```

Header values: first byte of packet data  
Constant value: **3**

(continued from last page)

---

## FLV\_CHUNKHEADER\_SECONDBYTE

```
public static final int FLV_CHUNKHEADER_SECONDBYTE
```

Header values: second byte of packet data  
Constant value: **4**

---

## FLV\_CHUNKHEADER\_HEADERSIZE

```
public static final int FLV_CHUNKHEADER_HEADERSIZE
```

Size of packet header (byte[])  
Constant value: **11**

---

## FLV\_CHUNKHEADER\_BUFFERSIZE

```
public static final int FLV_CHUNKHEADER_BUFFERSIZE
```

Size of temporary buffer needed for flv reading (byte[])  
Constant value: **13**

---

## FLV\_CHUNKHEADER\_VALUESIZE

```
public static final int FLV_CHUNKHEADER_VALUESIZE
```

Size of header values array (long[])  
Constant value: **5**

---

## FLV\_UFRAME

```
public static final int FLV_UFRAME
```

Unknown video frame type  
Constant value: **0**

---

## FLV\_KFRAME

```
public static final int FLV_KFRAME
```

Key video frame type  
Constant value: **1**

---

## FLV\_DFRAME

```
public static final int FLV_DFRAME
```

D video frame type (partial frame based on key frame)  
Constant value: **3**

---

## FLV\_PFRAME

```
public static final int FLV_PFRAME
```

P video frame type (partial frame based on previous frame)  
Constant value: **2**

---

## FLV\_TCINDEXAUDIO

```
public static final int FLV_TCINDEXAUDIO
```

---

(continued from last page)

Constant value: **0**

---

## FLV\_TCINDEXVIDEO

```
public static final int FLV_TCINDEXVIDEO
```

Constant value: **1**

---

## FLV\_TCINDEXDATA

```
public static final int FLV_TCINDEXDATA
```

Constant value: **2**

## Constructors

### FLVUtils

```
public FLVUtils()
```

## Methods

### streamCodecToString

```
public static String streamCodecToString(int codec)
```

Get a printable string representation of the stream codecs defined as IVHost.CODEC\_STREAM\_\*

**Parameters:**

codec - codec id defined IVHost.CODEC\_STREAM\_\*

**Returns:**

codec name

---

### audioCodecStringToId

```
public static int audioCodecStringToId(String codecString)
```

Parse a string to get the codec ID defined by IVHost.CODEC\_AUDIO\_\*

**Parameters:**

codecString - codec string

**Returns:**

codec ID

---

### videoCodecToMetaDataString

```
public static String videoCodecToMetaDataString(int codec)
```

Get a printable string representation of the video codecs defined as IVHost.CODEC\_VIDEO\_\* as the string used in the onMetaData event

(continued from last page)

**Parameters:**

codec - codec id defined IVHost.CODEC\_VIDEO\_\*

**Returns:**

codec name

---

## audioCodecToMetaDataString

```
public static String audioCodecToMetaDataString(int codec)
```

Get a printable string representation of the audio codecs defined as IVHost.CODEC\_AUDIO\_\* as the string used in the onMetaData event

**Parameters:**

codec - codec id defined IVHost.CODEC\_AUDIO\_\*

**Returns:**

codec name

---

## audioCodecToString

```
public static String audioCodecToString(int codec)
```

Get a printable string representation of the audio codecs defined as IVHost.CODEC\_AUDIO\_\*

**Parameters:**

codec - codec id defined IVHost.CODEC\_AUDIO\_\*

**Returns:**

codec name

---

## videoCodecStringToId

```
public static int videoCodecStringToId(String codecString)
```

Parse a string to get the codec ID defined by IVHost.CODEC\_VIDEO\_\*

**Parameters:**

codecString - codec string

**Returns:**

codec ID

---

## videoCodecToString

```
public static String videoCodecToString(int codec)
```

Get a printable string representation of the video codecs defined as IVHost.CODEC\_VIDEO\_\*

**Parameters:**

codec - codec id defined IVHost.CODEC\_VIDEO\_\*

**Returns:**

codec name

---

## frameTypeToString

```
public static String frameTypeToString(int frameType)
```

(continued from last page)

---

## getFrameType

```
public static int getFrameType(int[] values)
```

Given the headers values (including first byte of the packet), determine the type of video frame (FLV\_\*FRAME)

**Parameters:**

values - header values

**Returns:**

type of video frame (FLV\_\*FRAME)

---

## getFrameType

```
public static int getFrameType(int value)
```

Given the first byte of a video packet, determine the frame type (FLV\_\*FRAME)

**Parameters:**

value - first byte of packet

**Returns:**

type of video frame (FLV\_\*FRAME)

---

## getAudioCodec

```
public static int getAudioCodec(int value)
```

Return the codec portion of the first byte of an audio packet. Return should be one of IVHost.CODEC\_AUDIO\_\*

**Parameters:**

value - first byte of audio packet

**Returns:**

codec id

---

## getVideoCodec

```
public static int getVideoCodec(int value)
```

Return the codec portion of the first byte of an video packet. Return should be one of IVHost.CODEC\_VIDEO\_\*

**Parameters:**

value - first byte of audio packet

**Returns:**

codec id

---

## getFrameType

```
public static int getFrameType(byte value)
```

Given the first byte of a video packet, determine the frame type (FLV\_\*FRAME)

**Parameters:**

value - first byte of packet

---



(continued from last page)

**Returns:**

type of video frame (FLV\_\*FRAME)

---

**readChunk**

```
public static AMFPacket readChunk(java.io.InputStream is)
```

Read a packets worth of .flv data from an InputStream and return as an AMFPacket

**Parameters:**

is - InputStream

**Returns:**

AMFPacket of data or null if unsuccessful or end of file

---

**readChunk**

```
public static AMFPacket readChunk(java.io.DataInput is)
```

Read a packets worth of .flv data from an InputStream and return as an AMFPacket

**Parameters:**

is - InputStream

**Returns:**

AMFPacket of data or null if unsuccessful or end of file

---

**readPrevChunkHeader**

```
public static void readPrevChunkHeader(java.io.RandomAccessFile is,  
    byte[] buffer,  
    int[] values)
```

Back up one packet from current position in the file and read the packet header. This includes reading the first byte of the packet data. The file pointer will be positioned at the first byte of the packet data. values[FLV\_CHUNKHEADER\_ITYPE] will be set to 0x7f if failure or start of file.

**Parameters:**

is - RandomAccessFile

buffer - temporary buffer byte[FLV\_CHUNKHEADER\_BUFFERSIZE]

values - header values long[FLV\_CHUNKHEADER\_VALUESIZE]

---

**readChunkHeader**

```
public static void readChunkHeader(java.io.RandomAccessFile is,  
    byte[] buffer,  
    int[] values)
```

Read packet header. This includes reading the first byte of the packet data. The file pointer will be positioned at the first byte of the packet data. values[FLV\_CHUNKHEADER\_ITYPE] will be set to 0x7f if failure or end of file.

**Parameters:**

is - RandomAccessFile

buffer - temporary buffer byte[FLV\_CHUNKHEADER\_BUFFERSIZE]

values - header values long[FLV\_CHUNKHEADER\_VALUESIZE]

---

(continued from last page)

---

## readHeader

```
public static boolean readHeader(java.io.InputStream is)
```

Read file header. Return true if successful. Basically this just skips first 13 bytes in file.

---

## readHeader

```
public static boolean readHeader(java.io.DataInput is)
```

Read file header. Return true if successful. Basically this just skips first 13 bytes in file.

---

## writeShortHeader

```
public static void writeShortHeader(java.io.OutputStream ds)
```

Write just the FLV file header (without the metadata packet)

**Parameters:**

ds - OutputStream

---

## writeShortHeader

```
public static void writeShortHeader(java.io.DataOutput ds)
```

---

## writeHeader

```
public static void writeHeader(java.io.OutputStream ds,  
    double duration,  
    java.util.Map extraMetadata)
```

Write file header including onMetaData packet.

**Parameters:**

ds - OutputStream

duration - duration of .flv file in seconds

extraMetadata - Map of name/value pairs of metadata that will be appended to the onMetaData block

---

## writeHeader

```
public static void writeHeader(java.io.OutputStream ds,  
    double duration,  
    int audiocodecid,  
    int videocodecid,  
    String createdBy,  
    java.util.Map extraMetadata)
```

(continued from last page)

Write file header including onMetaData packet.

With this method you can provide a Map of metadata to write to the file. This map can include a mixture of simple types like: int, long, String, boolean. These types will be wrapped in AMFData classes before they are written to the file. This map can also contain AMFData items. For example if you wanted to insert an array of **cuePoints** the code would look like:

```
Map extraMetadata = new HashMap();

AMFDataArray amfArray = new AMFDataArray();
for(int i=0;i
```

#### Parameters:

ds - OutputStream  
duration - duration of .flv file in seconds  
audiocodecid - audio codec ID see IVHost.CODEC\_AUDIO\_\* (-1 for now audio)  
videocodecid - video codec ID see IVHost.CODEC\_VIDEO\_\* (-1 for now video)  
createdBy - created by string (null for empty)  
extraMetadata - Map of name/value pairs of metadata that will be appended to the onMetaData block

---

## writeChunk

```
public static void writeChunk(java.io.OutputStream ds,
    java.nio.ByteBuffer data,
    int size,
    long timecode,
    byte type)
```

Write a packets worth of data.

#### Parameters:

ds - OutputStream  
data - packet data  
size - size of the packet  
timecode - timecode (milliseconds)  
type - type of packet IVHost.CONTENT\_TYPE\_\*

---

## writeChunk

```
public static void writeChunk(java.io.DataOutput ds,
    java.nio.ByteBuffer data,
    int size,
    long timecode,
    byte type)
```

---

(continued from last page)

## interleavePackets

```
public static java.util.List interleavePackets(java.util.List audioPackets,
        java.util.List videoPackets,
        java.util.List dataPackets,
        java.util.List audioTCs,
        java.util.List videoTCs,
        java.util.List dataTCs,
        long[] currentTCs)
```

This is a utility function primarily used for IMediaWriters. It is a way of taking the discrete audio/video/data packets and timecodes and interleaving them into a single list of AMFPacket objects. The currentTCs array is an array of longs containing the last timecode for each of the packet types FLV\_TCINDEX\* (long[3]). This array will be used to calculate the absolute timecode for a given packet. For example if the relative timecode for an audio packet is 26 and the currentTCs value for the audio channel is 1003 then the absolute timecode for that packet will be 1029. The currentTCs array will be updated after this call to reflect the absolute timecode of the last packet processed of each type.

### Parameters:

audioPackets - list of audio packets (ByteBuffer)  
 videoPackets - list of video packets (ByteBuffer)  
 dataPackets - list of data packets (ByteBuffer)  
 audioTCs - list of relative audio timecodes (Long)  
 videoTCs - list of relative video timecodes (Long)  
 dataTCs - list of relative data timecodes (Long)  
 currentTCs - array of longs containing last TCs written for each packet type FLV\_TCINDEX\* (long[3]). Last timecode written for each packet type will be returned in this same array.

### Returns:

List of AMFPacket objects sorted by timecodes

## interleavePackets

```
public static java.util.List interleavePackets(java.util.List audioPackets,
        java.util.List videoPackets,
        java.util.List dataPackets,
        java.util.List audioTCs,
        java.util.List videoTCs,
        java.util.List dataTCs,
        java.util.List dataTypes,
        long[] currentTCs)
```

This is a utility function primarily used for IMediaWriters. It is a way of taking the discrete audio/video/data packets and timecodes and interleaving them into a single list of AMFPacket objects. The currentTCs array is an array of longs containing the last timecode for each of the packet types FLV\_TCINDEX\* (long[3]). This array will be used to calculate the absolute timecode for a given packet. For example if the relative timecode for an audio packet is 26 and the currentTCs value for the audio channel is 1003 then the absolute timecode for that packet will be 1029. The currentTCs array will be updated after this call to reflect the absolute timecode of the last packet processed of each type.

### Parameters:

audioPackets - list of audio packets (ByteBuffer)  
 videoPackets - list of video packets (ByteBuffer)  
 dataPackets - list of data packets (ByteBuffer)  
 audioTCs - list of relative audio timecodes (Long)  
 videoTCs - list of relative video timecodes (Long)  
 dataTCs - list of relative data timecodes (Long)  
 dataTypes - list of integer packets types (IVHost.CONTENTTYPE\_DATA0, IVHost.CONTENTTYPE\_DATA3) - if null assumed to be IVHost.CONTENTTYPE\_DATA0  
 currentTCs - array of longs containing last TCs written for each packet type FLV\_TCINDEX\* (long[3]). Last timecode written for each packet type will be returned in this same array.

### Returns:

List of AMFPacket objects sorted by timecodes

---

## writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List packetList,
    long tcOffset)
```

Write audio/video/data packets to an .flv file. They will be written in the packetList order.

### Parameters:

ds - OutputStream  
 packetList - List of AMFPacket objects  
 tcOffset - timecode offset

---

## writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    long[] currentTCs)
```

Write a bunch of packets to .flv file all at once. The packets will be sorted by timecode as written

### Parameters:

ds - OutputStream  
 audioPackets - list of audio packets (ByteBuffer)  
 videoPackets - list of video packets (ByteBuffer)  
 dataPackets - list of data packets (ByteBuffer)  
 audioTCs - list of relative audio timecodes (Long)  
 videoTCs - list of relative video timecodes (Long)  
 dataTCs - list of relative data timecodes (Long)  
 currentTCs - array of longs containing last TCs written for each packet type FLV\_TCINDEX\* (long[3]). Last timecode written for each packet type will be returned in this same array.

---

## writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    java.util.List dataTypes,
    long[] currentTCs)
```

Write a bunch of packets to .flv file all at once. The packets will be sorted by timecode as written

### Parameters:

ds - OutputStream  
 audioPackets - list of audio packets (ByteBuffer)  
 videoPackets - list of video packets (ByteBuffer)  
 dataPackets - list of data packets (ByteBuffer)  
 audioTCs - list of relative audio timecodes (Long)  
 videoTCs - list of relative video timecodes (Long)  
 dataTCs - list of relative data timecodes (Long)  
 dataTypes - list of integer packets types (IVHost.CONTENTTYPE\_DATA0, IVHost.CONTENTTYPE\_DATA3) - if null assumed to be IVHost.CONTENTTYPE\_DATA0

---

(continued from last page)

currentTCs - array of longs containing last TCs written for each packet type FLV\_TCINDEX\* (long[3]). Last timecode written for each packet type will be returned in this same array.

---

## writePackets

```
public static void writePackets(java.io.OutputStream ds,  
    java.util.List audioPackets,  
    java.util.List videoPackets,  
    java.util.List dataPackets,  
    java.util.List audioTCs,  
    java.util.List videoTCs,  
    java.util.List dataTCs,  
    java.util.List dataTypes,  
    long[] currentTCs,  
    IFLVWriterAdjustTimecode dataPacketTimecodeAdjuster)
```

Write a bunch of packets to .flv file all at once. The packets will be sorted by timecode as written

### Parameters:

ds - OutputStream  
audioPackets - list of audio packets (ByteBuffer)  
videoPackets - list of video packets (ByteBuffer)  
dataPackets - list of data packets (ByteBuffer)  
audioTCs - list of relative audio timecodes (Long)  
videoTCs - list of relative video timecodes (Long)  
dataTCs - list of relative data timecodes (Long)  
dataTypes - list of integer packets types (IVHost.CONTENTTYPE\_DATA0, IVHost.CONTENTTYPE\_DATA3) - if null assumed to be IVHost.CONTENTTYPE\_DATA0  
currentTCs - array of longs containing last TCs written for each packet type FLV\_TCINDEX\* (long[3]). Last timecode written for each packet type will be returned  
dataPacketTimecodeAdjuster - class that implements the IFLVWriterAdjustTimecode interface for adjusting timecodes in this same array.

---

## adjustFirstPacketTCs

```
public static long adjustFirstPacketTCs(java.util.List audioTCs,  
    java.util.List videoTCs,  
    java.util.List dataTCs)
```

Align list of timecode for each data type. Assume first entry in each list is absolute timecode. When done lowest entry in three lists will be zero and other lists will be offset accordingly.

### Parameters:

audioTCs - list of audio timecodes  
videoTCs - list of video timecodes  
dataTCs - list of data timecodes

### Returns:

lowest of three absolute timecodes

---

## writeDuration

```
public static void writeDuration(java.io.File file,  
    double duration)
```

Write the duration to an existing .flv file. This routine will hunt through the .flv file for the onMetaData packet and the duration metadata. It will rewrite the value if found. If not found it will do nothing.

### Parameters:

file - .flv file  
duration - new duration value (seconds)

---

## getLastTC

```
public static long getLastTC(java.io.File file)
```

Get the duration of an .flv file. This routine will find the onMetaData packet and the duration metadata and return the value. If not found it will read the last packet in the file and return the timecode of that packet.

**Parameters:**

file

**Returns:**

duration (milliseconds)

---

## isVideoKeyFrame

```
public static boolean isVideoKeyFrame(AMFPacket packet)
```

Returns true if the packet is a video key frame

**Parameters:**

packet - packet

**Returns:**

true if is video key frame

---

## isVideoCodecConfig

```
public static boolean isVideoCodecConfig(AMFPacket packet)
```

Returns true if the packet is a video codec config packet

**Parameters:**

packet

**Returns:**

true if the packet is a video codec config packet

---

## isAudioCodecConfig

```
public static boolean isAudioCodecConfig(AMFPacket packet)
```

Returns true if the packet is a video codec config packet

**Parameters:**

packet

**Returns:**

true if the packet is a video codec config packet

---

## getAudioMP3Layer

```
public static int getAudioMP3Layer(AMFPacket packet)
```

Audio marked as MP3 is really MPEG1 Layer 1-3. Only MPEG1 Layer 3 is truly MP3. This function will return the layer number for this packet.

**Parameters:**

packet - amf packet

---

(continued from last page)

**Returns:**

layer number

---

## getAudioCodec

```
public static int getAudioCodec(AMFPacket packet)
```

Get the codec id for this audio packet. Returns IVHost.CODEC\_AUDIO\_UNKNOWN is unknown or not audio packet

**Parameters:**

packet - packet

**Returns:**

codec id IVHost.CODEC\_AUDIO\_\*

---

## getVideoCodec

```
public static int getVideoCodec(AMFPacket packet)
```

Get the codec id for this video packet. Returns IVHost.CODEC\_VIDEO\_UNKNOWN is unknown or not video packet

**Parameters:**

packet - packet

**Returns:**

codec id IVHost.CODEC\_VIDEO\_\*

---

## getVideoFrameType

```
public static int getVideoFrameType(AMFPacket packet)
```

---

## getVideoTimecodeOffset

```
public static int getVideoTimecodeOffset(AMFPacket packet)
```

Get the timecode offset in milliseconds between the PTS and DTS for this frame.

**Parameters:**

packet - AMFPacket

**Returns:**

timecode offset in milliseconds (can be negative)

---

## getVideoTimecodeOffset

```
public static int getVideoTimecodeOffset(byte[] buffer)
```

Get the timecode offset in milliseconds between the PTS and DTS for this frame.

**Parameters:**

buffer - video packet buffer

**Returns:**

timecode offset in milliseconds (can be negative)



## isVideoKeyFrame

```
public static boolean isVideoKeyFrame(java.nio.ByteBuffer buffer)
```

Returns true if the packet is a video key frame

**Parameters:**

buffer - packet data (only need first two bytes of data)

**Returns:**

true if is video key frame

---

## isVideoKeyFrame

```
public static boolean isVideoKeyFrame(byte[] buffer)
```

Returns true if the packet is a video key frame

**Parameters:**

buffer - packet data (only need first two bytes of data)

**Returns:**

true if is video key frame

---

## isVideoKeyFrame

```
public static boolean isVideoKeyFrame(int[] chunkHeaderValues)
```

Returns true if the packet is a video key frame

**Parameters:**

chunkHeaderValues - chunk header values returned by FLVUtils.readChunkHeader

**Returns:**

true if is video key frame

---

## updateOnCuePointTimecode

```
public static AMFPacket updateOnCuePointTimecode(AMFPacket packet,  
long timecode)
```

---

## updateOnCuePointTimecode

```
public static java.nio.ByteBuffer updateOnCuePointTimecode(java.nio.ByteBuffer data,  
int dataType,  
long timecode)
```

---

## isOnMetadataPacket

```
public static boolean isOnMetadataPacket(AMFPacket packet)
```

Returns true if packet is onMetaData or [@setDataFrame, onMetaData] data packet.

**Parameters:**

(continued from last page)

packet - packet

**Returns:**

true if onMetaData packet

---

## getOnMetadataData

```
public static OnMetadataBasic getOnMetadataData(AMFPacket metaDataPacket)
```

## com.wowza.util Class HTTPUtils

java.lang.Object

└─com.wowza.util.HTTPUtils

public class **HTTPUtils**  
extends Object

HTTPUtils: utility class for making http requests.

### Field Summary

public static final	<a href="#">COOKIEFORMAT</a>
---------------------	------------------------------

### Constructor Summary

public	<a href="#">HTTPUtils()</a>
--------	-----------------------------

### Method Summary

static String	<a href="#">assembleQueryStr</a> (java.util.Map queryMap) Assemble a map of name value pairs into a single query string.
static String	<a href="#">formatDeleteCookie</a> (String name, String path, String domain) Formats a cookie header value that is in the past to delete a cookie
static String	<a href="#">formatSetCookie</a> (String name, String value, int timeoffset, String path, String domain, boolean isSecure) Format a HTTP header Set-Cookie value
static byte[]	<a href="#">HTTPRequestToByteArray</a> (String inUrl, String method, String data, java.util.Map headers) Make a HTTP request and return the result as a byte array
static byte[]	<a href="#">HTTPRequestToByteArray</a> (String inUrl, String method, String data, java.util.Map inHeaders, java.util.Map outHeaders, long dataLimit) Make a HTTP request and return the result as a byte array
static boolean	<a href="#">HTTPRequestToFile</a> (java.io.File file, String inUrl, String method, String data, java.util.List headers) Make a HTTP request and have the result saved to a file.
static java.util.List	<a href="#">splitCookie</a> (String str) Breaks Cookies header value into a list of name/value pairs.
static String[]	<a href="#">splitPragmas</a> (String str) Split HTTP Pragma values at commas that separate values.
static java.util.Map	<a href="#">splitQueryStr</a> (String queryStr) Split a query string into a map and URL decode the values

`static String``statusCodeToStr(int statusCode)``Convert an HTTP status code to a string`**Methods inherited from class** `java.lang.Object``clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

## Fields

### COOKIEDATEFORMAT

`public static final org.apache.commons.lang.time.FastDateFormat COOKIEDATEFORMAT`

## Constructors

### HTTPUtils

`public HTTPUtils()`

## Methods

### HTTPRequestToFile

```
public static boolean HTTPRequestToFile(java.io.File file,
    String inUrl,
    String method,
    String data,
    java.util.List headers)
```

Make a HTTP request and have the result saved to a file.

**Parameters:**

`file` - destination  
`inUrl` - url (will work with http and https)  
`method` - method (POST, GET)  
`data` - post data  
`headers` - map of headers (Content-type...)

**Returns:**

true if successful

### HTTPRequestToByteArray

```
public static byte[] HTTPRequestToByteArray(String inUrl,
    String method,
    String data,
    java.util.Map headers)
```

Make a HTTP request and return the result as a byte array

**Parameters:**

`inUrl` - url (will work with http and https)

(continued from last page)

method - method (POST, GET)  
data - post data  
headers - map of headers (Content-type...)

**Returns:**

byte array of result or null if not successful

---

## HTTPRequestToByteArray

```
public static byte[] HTTPRequestToByteArray(String inUrl,  
      String method,  
      String data,  
      java.util.Map inHeaders,  
      java.util.Map outHeaders,  
      long dataLimit)
```

Make a HTTP request and return the result as a byte array

**Parameters:**

inUrl - url (will work with http and https)  
method - method (POST, GET)  
data - data  
inHeaders - map of headers (Content-type...)  
outHeaders - response headers  
dataLimit - maximum number of bytes to read, zero for no limit

**Returns:**

byte array of result or null if not successful

---

## assembleQueryStr

```
public static String assembleQueryStr(java.util.Map queryMap)
```

Assemble a map of name value pairs into a single query string. URL encode query string values.

**Parameters:**

queryMap - name value pairs

**Returns:**

query string

---

## splitQueryStr

```
public static java.util.Map splitQueryStr(String queryStr)
```

Split a query string into a map and URL decode the values

**Parameters:**

queryStr - query string

**Returns:**

map of name value pairs

---

## splitPragmas

```
public static String[] splitPragmas(String str)
```

(continued from last page)

Split HTTP Pragma values at commas that separate values. It deals with internal commas in strings. Example:

```
no-cache, client-id=1485578017, features="seekable, stridable", timeout=6
```

Result:

```
no-cache  
client-id=1485578017  
features="seekable, stridable"  
timeout=6
```

**Parameters:**

str - Pragma value

**Returns:**

array of strings broken at commas

---

## splitCookie

```
public static java.util.List splitCookie(String str)
```

Breaks Cookies header value into a list of name/value pairs. The Cookie string: "name1=value1;name2;name1=value3" is returned as: List(item({"name1", "value1"}), item("name2", null), item("name1", "value3"))

**Parameters:**

str - input string

**Returns:**

List of name value pairs

---

## formatDeleteCookie

```
public static String formatDeleteCookie(String name,  
    String path,  
    String domain)
```

Formats a cookie header value that is in the past to delete a cookie

**Parameters:**

name - variable name  
path - path  
domain - domain

**Returns:**

formatted cookie string

---

## formatSetCookie

```
public static String formatSetCookie(String name,  
    String value,  
    int timeoffset,  
    String path,  
    String domain,  
    boolean isSecure)
```

Format a HTTP header Set-Cookie value

**Parameters:**

name - variable name  
value - variable value - null if no value  
timeoffset - expiration time in seconds  
path - cookie path  
domain - cookie domain  
isSecure - is cookie secure

**Returns:**

formatted cookie string

---

## statusCodeToStr

```
public static String statusCodeToStr(int statusCode)
```

Convert an HTTP status code to a string

**Parameters:**

statusCode - HTTP status code

**Returns:**

string

---

## com.wowza.util Interface IBandwidthThrottler

---

public interface **IBandwidthThrottler**  
extends

---

### Method Summary

long	<a href="#"><u>getBytesAllocation</u></a> (long request) Requests bytes from the bandwidth throttler interface.
------	--

---

### Methods

#### getBytesAllocation

public long **getBytesAllocation**(long request)

Requests bytes from the bandwidth throttler interface. Return value is the number of bytes allocated

**Parameters:**

request - request number of bytes

**Returns:**

allocated number of bytes



## com.wowza.util Interface IFileProcess

public interface **IFileProcess**  
extends

Used by FileUtils.traverseDirectory

### Method Summary

void	<a href="#">onFile</a> (java.io.File file) Triggered for each file encountered in FileUtils.traverseDirectory
------	--

### Methods

#### onFile

public void **onFile**(java.io.File file)

Triggered for each file encountered in FileUtils.traverseDirectory

**Parameters:**

file - file descriptor

## com.wowza.util Class IOPerformanceCounter

java.lang.Object

└─com.wowza.util.IOPerformanceCounter

public class **IOPerformanceCounter**  
extends Object

IOPerformanceCounter: data object that tracks the server performance of a particular component (client, vHost, server, stream). It tracks bytes and messages sent to and from the object being measured.

### Constructor Summary

public	<a href="#"><u>IOPerformanceCounter</u></a> ( ) Create an empty performance counter.
--------	---

### Method Summary

void	<a href="#"><u>add</u></a> ( <a href="#"><u>IOPerformanceCounter</u></a> value) Add (value) to this counter.
void	<a href="#"><u>addDifference</u></a> ( <a href="#"><u>IOPerformanceCounter</u></a> current, <a href="#"><u>IOPerformanceCounter</u></a> last) Add the result of (current-last) to this counter.
void	<a href="#"><u>clear</u></a> ( ) Clear or reset this counter back to zero.
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>clone</u></a> ( ) Create a deep clone (copy) if this object.
void	<a href="#"><u>doSet</u></a> ( <a href="#"><u>IOPerformanceCounter</u></a> value) Set this object to value.
void	<a href="#"><u>dummy</u></a> ( )
long	<a href="#"><u>getFileInBytes</u></a> ( ) Get file in bytes
double	<a href="#"><u>getFileInBytesRate</u></a> ( ) Get estimate of file byte-in byte rate.
long	<a href="#"><u>getFileOutBytes</u></a> ( ) Get file byte-out bytes (not implemented)
double	<a href="#"><u>getFileOutBytesRate</u></a> ( ) Get estimate of file byte-out message byte rate (not implemented).
long	<a href="#"><u>getMessagesInBytes</u></a> ( ) Get byte-in bytes
double	<a href="#"><u>getMessagesInBytesRate</u></a> ( ) Get estimate of byte-in message byte rate.

long	<a href="#"><u>getMessagesInCount</u></a> ( ) Get byte-in message count
long	<a href="#"><u>getMessagesInCountRate</u></a> ( ) Get estimate of byte-in message count rate.
long	<a href="#"><u>getMessagesLossBytes</u></a> ( ) Get byte-loss bytes
double	<a href="#"><u>getMessagesLossBytesRate</u></a> ( ) Get estimate of byte-loss message byte rate.
long	<a href="#"><u>getMessagesLossCount</u></a> ( ) Get byte-loss message count
long	<a href="#"><u>getMessagesLossCountRate</u></a> ( ) Get estimate of byte-loss message count rate.
long	<a href="#"><u>getMessagesOutBytes</u></a> ( ) Get byte-out bytes
double	<a href="#"><u>getMessagesOutBytesRate</u></a> ( ) Get estimate of byte-out message byte rate.
long	<a href="#"><u>getMessagesOutCount</u></a> ( ) Get byte-out message count
long	<a href="#"><u>getMessagesOutCountRate</u></a> ( ) Get estimate of byte-out message count rate.
long	<a href="#"><u>incrementBytesIn</u></a> (long bytes) Increment bytes-in by bytes and increment message count by 0.
long	<a href="#"><u>incrementBytesLoss</u></a> (long bytes) Increment bytes-loss by bytes and increment message count by 0.
long	<a href="#"><u>incrementBytesOut</u></a> (long bytes) Increment bytes-out by bytes and increment message count by 0.
long	<a href="#"><u>incrementFileIn</u></a> (long bytes) Increment file-bytes-in by bytes.
long	<a href="#"><u>incrementFileOut</u></a> (long bytes) Increment file bytes-out by bytes.
long	<a href="#"><u>incrementMessagesIn</u></a> ( ) Increment byte-in message count by 1.
long	<a href="#"><u>incrementMessagesIn</u></a> (long bytes) Increment bytes-in by bytes and increment message count by 1.
long	<a href="#"><u>incrementMessagesIn</u></a> (long bytes, long count) Increment bytes-in by bytes and message count by count.
long	<a href="#"><u>incrementMessagesLoss</u></a> ( ) Increment byte-loss message count by 1.
long	<a href="#"><u>incrementMessagesLoss</u></a> (long bytes) Increment bytes-loss by bytes and increment message count by 1.

long	<a href="#"><code>incrementMessagesLoss</code></a> (long bytes, long count) Increment bytes-loss by bytes and message count by count.
long	<a href="#"><code>incrementMessagesOut</code></a> () Increment byte-out message count by 1.
long	<a href="#"><code>incrementMessagesOut</code></a> (long bytes) Increment bytes-out by bytes and increment message count by 1.
long	<a href="#"><code>incrementMessagesOut</code></a> (long bytes, long count) Increment bytes-out by bytes and message count by count.
boolean	<a href="#"><code>isDebugLog</code></a> ()
void	<a href="#"><code>setDebugLog</code></a> (boolean debugLog)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### IOPerformanceCounter

```
public IOPerformanceCounter()
```

Create an empty performance counter.

## Methods

### clone

```
public IOPerformanceCounter clone()
```

Create a deep clone (copy) if this object.

### addDifference

```
public void addDifference(IOPerformanceCounter current,  
                          IOPerformanceCounter last)
```

Add the result of (current-last) to this counter. Used internally to efficiently track object performance on a timer.

#### Parameters:

current - current counter

last - last counter

### clear

```
public void clear()
```

Clear or reset this counter back to zero.

(continued from last page)

## add

```
public void add(IOPerformanceCounter value)
```

Add (value) to this counter.

**Parameters:**

value - value to add

---

## doSet

```
public void doSet(IOPerformanceCounter value)
```

Set this object to value.

**Parameters:**

value - value to set

---

## incrementMessagesIn

```
public long incrementMessagesIn(long bytes)
```

Increment bytes-in by bytes and increment message count by 1.

**Parameters:**

bytes - number of bytes

**Returns:**

bytes-in bytes

---

## incrementFileIn

```
public long incrementFileIn(long bytes)
```

Increment file-bytes-in by bytes.

**Parameters:**

bytes - number of bytes

**Returns:**

bytes-in bytes

---

## incrementMessagesIn

```
public long incrementMessagesIn(long bytes,  
                                long count)
```

Increment bytes-in by bytes and message count by count.

**Parameters:**

bytes - number of bytes  
count - number of messages

**Returns:**

bytes-in bytes

---

(continued from last page)

## incrementBytesIn

```
public long incrementBytesIn(long bytes)
```

Increment bytes-in by bytes and increment message count by 0.

**Parameters:**

bytes

**Returns:**

bytes-in bytes

---

## incrementMessagesIn

```
public long incrementMessagesIn()
```

Increment byte-in message count by 1.

**Returns:**

bytes-in message count

---

## incrementMessagesOut

```
public long incrementMessagesOut(long bytes)
```

Increment bytes-out by bytes and increment message count by 1.

**Parameters:**

bytes - number of bytes

**Returns:**

bytes-out bytes

---

## incrementFileOut

```
public long incrementFileOut(long bytes)
```

Increment file bytes-out by bytes.

**Parameters:**

bytes - number of bytes

**Returns:**

bytes-out bytes

---

## incrementMessagesLoss

```
public long incrementMessagesLoss(long bytes)
```

Increment bytes-loss by bytes and increment message count by 1.

**Parameters:**

bytes - number of bytes

**Returns:**

bytes-loss bytes

---

(continued from last page)

## incrementMessagesOut

```
public long incrementMessagesOut(long bytes,  
    long count)
```

Increment bytes-out by bytes and message count by count.

**Parameters:**

bytes - number of bytes  
count - number of messages

**Returns:**

bytes-out bytes

---

## incrementMessagesLoss

```
public long incrementMessagesLoss(long bytes,  
    long count)
```

Increment bytes-loss by bytes and message count by count.

**Parameters:**

bytes - number of bytes  
count - number of messages

**Returns:**

bytes-loss bytes

---

## incrementBytesOut

```
public long incrementBytesOut(long bytes)
```

Increment bytes-out by bytes and increment message count by 0.

**Parameters:**

bytes

**Returns:**

bytes-out bytes

---

## incrementBytesLoss

```
public long incrementBytesLoss(long bytes)
```

Increment bytes-loss by bytes and increment message count by 0.

**Parameters:**

bytes

**Returns:**

bytes-loss bytes

---

## incrementMessagesOut

```
public long incrementMessagesOut()
```

Increment byte-out message count by 1.

**Returns:**

(continued from last page)

bytes-out message count

---

## incrementMessagesLoss

```
public long incrementMessagesLoss()
```

Increment byte-loss message count by 1.

**Returns:**

bytes-loss message count

---

## getMessagesInCount

```
public long getMessagesInCount()
```

Get byte-in message count

**Returns:**

byte-in message count

---

## getMessagesOutCount

```
public long getMessagesOutCount()
```

Get byte-out message count

**Returns:**

byte-out message count

---

## getMessagesLossCount

```
public long getMessagesLossCount()
```

Get byte-loss message count

**Returns:**

byte-loss message count

---

## getMessagesInBytes

```
public long getMessagesInBytes()
```

Get byte-in bytes

**Returns:**

byte-in bytes

---

## getFileInBytes

```
public long getFileInBytes()
```

Get file in bytes

**Returns:**

file in bytes

---



(continued from last page)

## getMessagesOutBytes

```
public long getMessagesOutBytes()
```

Get byte-out bytes

**Returns:**

byte-out bytes

---

## getFileOutBytes

```
public long getFileOutBytes()
```

Get file byte-out bytes (not implemented)

**Returns:**

byte-out bytes

---

## getMessagesLossBytes

```
public long getMessagesLossBytes()
```

Get byte-loss bytes

**Returns:**

byte-loss bytes

---

## getMessagesInCountRate

```
public long getMessagesInCountRate()
```

Get estimate of byte-in message count rate.

**Returns:**

estimate of byte-in message count rate (messages per second)

---

## getMessagesOutCountRate

```
public long getMessagesOutCountRate()
```

Get estimate of byte-out message count rate.

**Returns:**

estimate of byte-out message count rate (messages per second)

---

## getMessagesLossCountRate

```
public long getMessagesLossCountRate()
```

Get estimate of byte-loss message count rate.

**Returns:**

estimate of byte-loss message count rate (messages per second)

---

## getMessagesInBytesRate

```
public double getMessagesInBytesRate()
```

(continued from last page)

Get estimate of byte-in message byte rate.

**Returns:**

estimate of byte-in message byte rate (bytes per second)

---

**getFileInBytesRate**

```
public double getFileInBytesRate()
```

Get estimate of file byte-in byte rate.

**Returns:**

estimate of file byte-in byte rate (bytes per second)

---

**getMessagesOutBytesRate**

```
public double getMessagesOutBytesRate()
```

Get estimate of byte-out message byte rate.

**Returns:**

estimate of byte-out message byte rate (bytes per second)

---

**getFileOutBytesRate**

```
public double getFileOutBytesRate()
```

Get estimate of file byte-out message byte rate (not implemented).

**Returns:**

estimate of file byte-out message byte rate (bytes per second)

---

**getMessagesLossBytesRate**

```
public double getMessagesLossBytesRate()
```

Get estimate of byte-loss message byte rate.

**Returns:**

estimate of byte-loss message byte rate (bytes per second)

---

**dummy**

```
public void dummy()
```

---

**isDebugLog**

```
public boolean isDebugLog()
```

---

**setDebugLog**

```
public void setDebugLog(boolean debugLog)
```

## com.wowza.util Class MD5DigestUtils

java.lang.Object

└─com.wowza.util.MD5DigestUtils

public class **MD5DigestUtils**  
extends Object

MD5DigestUtils: MD5 hash utilities.

### Field Summary

protected static	<a href="#">md5Digest</a>
protected static	<a href="#">md5Lock</a>

### Constructor Summary

public	<a href="#">MD5DigestUtils()</a>
--------	----------------------------------

### Method Summary

static String	<a href="#">generateAuth</a> (String method, String uri, String username, String password, String realm, String nonce) Generate an HTTP authorization response
static String	<a href="#">generateAuth</a> (String a2Hash, String alHash, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	<a href="#">generateAuth</a> (String method, String uri, String alHash, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	<a href="#">generateAuth</a> (String method, String uri, String username, String password, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	<a href="#">generateAuthHTTP</a> (String method, String uri, String username, String password, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	<a href="#">generateHash</a> (String value) Generate MD5 hash
static byte[]	<a href="#">generateHashBytes</a> (byte[] value) Generate MD5 hash
static byte[]	<a href="#">generateHashBytes</a> (String value) Generate MD5 hash

**Methods inherited from class** `java.lang.Object``clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

---

## Fields

### **md5Digest**

`protected static java.security.MessageDigest md5Digest`

---

### **md5Lock**

`protected static java.lang.Object md5Lock`

---

## Constructors

### **MD5DigestUtils**

`public MD5DigestUtils()`

---

## Methods

### **generateAuth**

```
public static String generateAuth(String method,
    String uri,
    String username,
    String password,
    String realm,
    String nonce)
```

Generate an HTTP authorization response

**Parameters:**

method - method  
uri - URI  
username - username  
password - password  
realm - realm  
nonce - nonce

**Returns:**

auth response

---

(continued from last page)

## generateAuth

```
public static String generateAuth(String method,  
    String uri,  
    String username,  
    String password,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

**Parameters:**

method - method  
uri - URI  
username - username  
password - password  
realm - realm  
nonce - nonce  
qop - qop  
nonceCount - nonceCount  
cnonce - cnonce

**Returns:**

auth response

---

## generateAuthHTTP

```
public static String generateAuthHTTP(String method,  
    String uri,  
    String username,  
    String password,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

**Parameters:**

method - method  
uri - URI  
username - username  
password - password  
realm - realm  
nonce - nonce  
qop - qop  
nonceCount - nonceCount  
cnonce - cnonce

**Returns:**

response

---

(continued from last page)

## generateAuth

```
public static String generateAuth(String method,  
    String uri,  
    String alHash,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

### Parameters:

method - method  
uri - URI  
alHash - alHash  
realm - realm  
nonce - nonce  
qop - qop  
nonceCount - nonceCount  
cnonce - cnonce

### Returns:

auth

---

## generateAuth

```
public static String generateAuth(String a2Hash,  
    String alHash,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

### Parameters:

a2Hash - a2Hash  
alHash - alHash  
realm - realm  
nonce - nonce  
qop - qop  
nonceCount - nonceCount  
cnonce - cnonce

### Returns:

auth

---

## generateHashBytes

```
public static byte[] generateHashBytes(byte[] value)
```

Generate MD5 hash

### Parameters:

value - byte array to hash

### Returns:

byte array result

## generateHashBytes

```
public static byte[] generateHashBytes(String value)
```

Generate MD5 hash

**Parameters:**

value - in string converted to byte array (UTF-8)

**Returns:**

byte array result

---

## generateHash

```
public static String generateHash(String value)
```

Generate MD5 hash

**Parameters:**

value - in string converted to byte array (UTF-8)

**Returns:**

hash as binhex string

---

## com.wowza.util Class MediaUtils

java.lang.Object

└─com.wowza.util.MediaUtils

public class **MediaUtils**  
extends Object

MediaUtils: Media utilities.

### Field Summary

public static final	<a href="#">CODECSTR_FORMAT_VIDEO_POSTIOS4</a> Value: <b>2</b>
public static final	<a href="#">CODECSTR_FORMAT_VIDEO_PREIOS4</a> Value: <b>1</b>
public static final	<a href="#">CODECSTR_FORMAT_VIDEO_UNKNOWN</a> Value: <b>0</b>

### Constructor Summary

public	<a href="#">MediaUtils()</a>
--------	------------------------------

### Method Summary

static String	<a href="#">audioCodecTypeToString</a> (int codecType) Audio codec ID to string.
static String	<a href="#">videoCodecTypeToString</a> (int codecType) Video codec ID to string.

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Fields

#### CODECSTR\_FORMAT\_VIDEO\_UNKNOWN

public static final int **CODECSTR\_FORMAT\_VIDEO\_UNKNOWN**

Constant value: **0**



---

## CODECSTR\_FORMAT\_VIDEO\_PREIOS4

```
public static final int CODECSTR_FORMAT_VIDEO_PREIOS4
```

Constant value: **1**

---

## CODECSTR\_FORMAT\_VIDEO\_POSTIOS4

```
public static final int CODECSTR_FORMAT_VIDEO_POSTIOS4
```

Constant value: **2**

---

## Constructors

### MediaUtils

```
public MediaUtils()
```

## Methods

### audioCodecTypeToString

```
public static String audioCodecTypeToString(int codecType)
```

Audio codec ID to string. See IVHost.CODEC\_AUDIO\_\*

**Parameters:**

codecType - codec id. See IVHost.CODEC\_AUDIO\_\*

**Returns:**

codec string

---

### videoCodecTypeToString

```
public static String videoCodecTypeToString(int codecType)
```

Video codec ID to string. See IVHost.CODEC\_VIDEO\_\*

**Parameters:**

codecType - codec id. See IVHost.CODEC\_VIDEO\_\*

**Returns:**

codec string

---

## com.wowza.util Class NetworkUtils

java.lang.Object

└─com.wowza.util.NetworkUtils

public class **NetworkUtils**  
extends Object

NetworkUtils: Networking utilities.

### Constructor Summary

public	<a href="#">NetworkUtils()</a>
--------	--------------------------------

### Method Summary

static boolean	<a href="#">isAddressMulticast(String IpAddress)</a> Returns true if IP address is multicast address
----------------	---

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### NetworkUtils

public **NetworkUtils()**

### Methods

#### isAddressMulticast

public static boolean **isAddressMulticast**(String IpAddress)

Returns true if IP address is multicast address

##### Parameters:

IpAddress - IP address

##### Returns:

true if IP address is multicast address

## com.wowza.util Interface NoMBean

---

public interface **NoMBean**  
extends Annotation

Annotation for excluding a method from the JMX interface. Below is an example of how it would be used

```
import com.wowza.util.NoMBean;
import com.wowza.wms.module.*;

class MyClass extends ModuleBase
{
    @NoMBean public void myMethod()
    {
    }
}
```

---

Methods inherited from interface <code>java.lang.annotation.Annotation</code>
---

<code>annotationType, equals, hashCode, toString</code>
---

---

## com.wowza.util Class StringUtils

java.lang.Object

└─com.wowza.util.StringUtils

public class **StringUtils**  
extends Object

StringUtils: utility class of String utilities.

### Constructor Summary

public	<a href="#">StringUtils()</a>
--------	-------------------------------

### Method Summary

static boolean	<a href="#">equals</a> (String s1, String s2) Checks if 2 strings are equals, accounting for null cases.
static String	<a href="#">intToHexStr</a> (int value, int strLen)
static String	<a href="#">intToStr</a> (int value, int strLen)
static boolean	<a href="#">isEmpty</a> (String s) Checks if string is empty, handling null String case.
static int	<a href="#">length</a> (String s) Returns string length, handling null String case as length of 0.
static String	<a href="#">longToHexStr</a> (long value, int strLen)
static String	<a href="#">longToStr</a> (long value, int strLen)
static String	<a href="#">stampToString</a> (long stamp) Convert a duration (milliseconds) to a formatted string.
static String	<a href="#">stampToStringNoUnits</a> (long stamp) Convert a duration (milliseconds) to a formatted string.
static long	<a href="#">stringToMilliseconds</a> (String stamp) Convert a hh:mm:ss.SSS string to milliseconds No validation that hh:mm:ss are valid ranges
static String	<a href="#">toStringList</a> (java.util.List strings) Convert list of Strings to comma-separated string
static String	<a href="#">toStringList</a> (String[] strings) Convert array of Strings to comma-separated string
static String	<a href="#">toStringList</a> ( <a href="#">WMSProperties</a> properties) Convert properties to comma-separated string

static String	<a href="#">valueOf</a> (String s) Returns string, handling null String case as "".
---------------	--

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### StringUtils

```
public StringUtils()
```

## Methods

### intToStr

```
public static String intToStr(int value,  
                               int strLen)
```

### intToHexStr

```
public static String intToHexStr(int value,  
                                  int strLen)
```

### longToStr

```
public static String longToStr(long value,  
                                int strLen)
```

### longToHexStr

```
public static String longToHexStr(long value,  
                                   int strLen)
```

### isEmpty

```
public static boolean isEmpty(String s)
```

Checks if string is empty, handling null String case.

**Parameters:**

s

**Returns:**

(continued from last page)

false if string is null or "", true otherwise

---

## length

```
public static int length(String s)
```

Returns string length, handling null String case as length of 0.

**Parameters:**

s

**Returns:**

0 if string is null, or length of string.

---

## valueOf

```
public static String valueOf(String s)
```

Returns string, handling null String case as "".

**Parameters:**

s

**Returns:**

"" if string is null, or string value.

---

## stampToString

```
public static String stampToString(long stamp)
```

Convert a duration (milliseconds) to a formatted string.

**Parameters:**

stamp - duration (milliseconds)

**Returns:**

formatted string (example: 3 days 4 minutes 1 seconds)

---

## stampToStringNoUnits

```
public static String stampToStringNoUnits(long stamp)
```

Convert a duration (milliseconds) to a formatted string.

**Parameters:**

stamp - duration (milliseconds)

**Returns:**

formatted string (example: 03:04:01.123 hours:minutes:seconds.milliseconds)

---

## stringToMilliseconds

```
public static long stringToMilliseconds(String stamp)
```

Convert a hh:mm:ss.SSS string to milliseconds No validation that hh:mm:ss are valid ranges

**Parameters:**

stamp - string (hours:minutes:seconds.milliseconds)

---

(continued from last page)

**Returns:**milliseconds, -1 is parse failed

---

**equals**

```
public static boolean equals(String s1,  
                             String s2)
```

Checks if 2 strings are equals, accounting for null cases. If both are null, they are considered equal.

**Parameters:**

s1 - string one

s2 - string 2

**Returns:**true is the strings are equal

---

**toStringList**

```
public static String toStringList(WMSPProperties properties)
```

Convert properties to comma-separated string

**Parameters:**

properties

**Returns:**comma-separated string

---

**toStringList**

```
public static String toStringList(java.util.List strings)
```

Convert list of Strings to comma-separated string

**Parameters:**

strings

**Returns:**comma-separated string

---

**toStringList**

```
public static String toStringList(String[] strings)
```

Convert array of Strings to comma-separated string

**Parameters:**

strings

**Returns:**comma-separated string

---

## com.wowza.util Class SystemUtils

java.lang.Object

└─com.wowza.util.SystemUtils

public class **SystemUtils**  
extends Object

### Nested Class Summary

class	<a href="#">SystemUtils.ReplaceItem</a> SystemUtils.ReplaceItem
-------	--

### Field Summary

public static final	<a href="#">defaultLocale</a>
public static final	<a href="#">defaultTimeZone</a>
public static final	<a href="#">gmtTimeZone</a>
protected static final	<a href="#">msb0baseTime</a> Value: <b>2085978496000</b>
protected static final	<a href="#">msblbaseTime</a> Value: <b>-2208988800000</b>

### Constructor Summary

public	<a href="#">SystemUtils()</a>
--------	-------------------------------

### Method Summary

static void	<a href="#">addBouncyCastleSecurityProvider()</a> Load bouncy castle providers, Internal use.
static String	<a href="#">expandEnvironmentVariables</a> (String inValue) Expand system level Java properties in a String in the form \${property-name}
static String	<a href="#">expandEnvironmentVariables</a> (String inValue, java.util.Map valueMap) Expand system level Java properties in a String in the form \${property-name}.
static long	<a href="#">getCpuTime</a> () Get CPU time in nanoseconds.
static byte[]	<a href="#">getMACAddress</a> () Get MAC address of localhost interface (only works on Java 6 or greater)



static long	<a href="#"><code>getSystemTime()</code></a> Get system time in nanoseconds.
static long	<a href="#"><code>getUserTime()</code></a> Get user time in nanoseconds.
static long	<a href="#"><code>toNTPTime(long t)</code></a> Convert a timecode value in milliseconds to NTP time

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Fields

### `defaultTimeZone`

`public static final java.util.TimeZone defaultTimeZone`

### `gmtTimeZone`

`public static final java.util.TimeZone gmtTimeZone`

### `defaultLocale`

`public static final java.util.Locale defaultLocale`

### `msb0baseTime`

`protected static final long msb0baseTime`

Constant value: **2085978496000**

### `msb1baseTime`

`protected static final long msb1baseTime`

Constant value: **-2208988800000**

## Constructors

### `SystemUtils`

`public SystemUtils()`

(continued from last page)

## Methods

### expandEnvironmentVariables

```
public static String expandEnvironmentVariables(String inValue)
```

Expand system level Java properties in a String in the form `${property-name}`

**Parameters:**

inValue - string with properties

**Returns:**

expanded string

---

### expandEnvironmentVariables

```
public static String expandEnvironmentVariables(String inValue,  
        java.util.Map valueMap)
```

Expand system level Java properties in a String in the form `${property-name}`. You can also pass in a map of name/value pairs that will expand the list of available properties

**Parameters:**

inValue - string with properties

valueMap - name/value pair map

**Returns:**

expanded string

---

### getMACAddress

```
public static byte[] getMACAddress()
```

Get MAC address of localhost interface (only works on Java 6 or greater)

**Returns:**

MAC address of localhost interface

---

### addBouncyCastleSecurityProvider

```
public static void addBouncyCastleSecurityProvider()
```

Load bouncy castle providers, Internal use.

---

### toNTPTime

```
public static long toNTPTime(long t)
```

Convert a timecode value in milliseconds to NTP time

**Parameters:**

t - timecode value in milliseconds

**Returns:**

NTP time

(continued from last page)

## **getCpuTime**

```
public static long getCpuTime()
```

Get CPU time in nanoseconds.

---

## **getUserTime**

```
public static long getUserTime()
```

Get user time in nanoseconds.

---

## **getSystemTime**

```
public static long getSystemTime()
```

Get system time in nanoseconds.

## com.wowza.util Class SystemUtils.ReplaceItem

java.lang.Object

└─com.wowza.util.SystemUtils.ReplaceItem

public static class **SystemUtils.ReplaceItem**  
extends Object

### Field Summary

public	<a href="#">end</a>
public	<a href="#">newValue</a>
public	<a href="#">start</a>

### Constructor Summary

public	<a href="#">SystemUtils.ReplaceItem</a> (int start, int stop, String newValue)
--------	--

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Fields

#### start

public int **start**

#### end

public int **end**

#### newValue

public java.lang.String **newValue**

### Constructors

(continued from last page)

## SystemUtils.ReplaceItem

```
public SystemUtils.ReplaceItem(int start,  
                               int stop,  
                               String newValue)
```

## com.wowza.util Class URLUtils

java.lang.Object

└─com.wowza.util.URLUtils

public final class **URLUtils**  
extends Object

Class to deal with URLs

### Constructor Summary

public	<a href="#">URLUtils()</a>
--------	----------------------------

### Method Summary

static String	<a href="#">appendParamsToUrl</a> (String url, String params) Convenience call to add parameters to a url.
static String	<a href="#">decodeValue</a> (String val) Wrapper for URLDecoder.decode(val, "UTF-8");
static String	<a href="#">encodeValue</a> (String val) Wrapper for URLEncoder.encode(val, "UTF-8");
static String	<a href="#">getParamValue</a> (java.util.Map params, String key) Helper funtion to get single value from multiple value parameter Map
static java.util.Map	<a href="#">parseQueryStr</a> (String queryString, boolean doDecode) Parse query string part of url into Map of Lists (to support multiple values) of query parameters
static String	<a href="#">pathToFileURL</a> (String basePath) Convert a path to a url (file://[path])
static String	<a href="#">urlToId</a> (java.net.URL url) Create a MD5 message digest hash of a url

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### URLUtils

public **URLUtils**()

(continued from last page)

## Methods

### pathToFileURL

```
public static String pathToFileURL(String basePath)
```

Convert a path to a url (file://[path])

**Parameters:**

basePath - path

**Returns:**

file url

### urlToId

```
public static String urlToId(java.net.URL url)
```

Create a MD5 message digest hash of a url

**Parameters:**

url - url to hash

**Returns:**

hashed url

### appendParamsToUrl

```
public static String appendParamsToUrl(String url,  
String params)
```

Convenience call to add parameters to a url. If already has ? add &.

**Parameters:**

url - input url

params - parameters in the form param1=val1&param2=val2

**Returns:**

appended url

### encodeValue

```
public static String encodeValue(String val)
```

Wrapper for URLEncoder.encode(val, "UTF-8");

**Parameters:**

val - value to encode

**Returns:**

encoded value

### decodeValue

```
public static String decodeValue(String val)
```

Wrapper for URLDecoder.decode(val, "UTF-8");

(continued from last page)

**Parameters:**

val - value to decode

**Returns:**decoded value

---

## parseQueryStr

```
public static java.util.Map parseQueryStr(String queryString,  
                                           boolean doDecode)
```

Parse query string part of url into Map of Lists (to support multiple values) of query parameters

**Parameters:**

queryString - query string

doDecode - true to use URLDecoder.decode() to decode parameters

**Returns:**Map of Lists

---

## getParamValue

```
public static String getParamValue(java.util.Map params,  
                                    String key)
```

Helper funtion to get single value from multiple value parameter Map

**Parameters:**

params - params Map

key - key string

**Returns:**first value

---



## com.wowza.util Class XMLUtils

java.lang.Object

└─com.wowza.util.XMLUtils

public class **XMLUtils**  
extends Object

XMLUtils: utility class for parsing XML files.

### Constructor Summary

public	<a href="#">XMLUtils()</a>
--------	----------------------------

### Method Summary

static org.w3c.dom.Node	<a href="#">getNodeByTagName</a> (org.w3c.dom.Element node, String name) Return a child Node by tag name.
static String	<a href="#">getNodeValue</a> (org.w3c.dom.Node node) Return the text value of a node.
static String	<a href="#">getNodeValueByTagName</a> (org.w3c.dom.Element node, String name) Get a child Node value by tag name.
static boolean	<a href="#">getXMLPropertyBool</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, boolean defaultVal) Get a boolean int value pointed to by xpath or defaultVal if not found.
static double	<a href="#">getXMLPropertyDouble</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, double defaultVal) Get a single double value pointed to by xpath or defaultVal if not found.
static boolean	<a href="#">getXMLPropertyExists</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root)
static int	<a href="#">getXMLPropertyInt</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, int defaultVal) Get a single int value pointed to by xpath or defaultVal if not found.
static int	<a href="#">getXMLPropertyIntSize</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, int defaultVal)
static long	<a href="#">getXMLPropertyLong</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, long defaultVal) Get a single long value pointed to by xpath or defaultVal if not found.
static long	<a href="#">getXMLPropertyLongSize</a> (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, long defaultVal)

static String	<a href="#">getXMLPropertyStr</a> ( javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root) Get a single string value pointed to by xpath or null if not found.
static String	<a href="#">getXMLPropertyStr</a> ( javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, String defaultVal) Get a single string value pointed to by xpath or defaultVal if not found.
static void	<a href="#">loadConfigProperties</a> (org.w3c.dom.Element root, String propertiesXPath, <a href="#">WMSProperties</a> properties) Loads <Properties> elemnt by xpath into properties object.
static void	<a href="#">loadConfigProperties</a> (org.w3c.dom.NodeList resultList, <a href="#">WMSProperties</a> properties) Given a nodeList load children as properties.
static javax.xml.xpath.XPath Factory	<a href="#">newXPathFactory</a> () Get a new XPath factory object.

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### XMLUtils

public **XMLUtils**()

## Methods

### getNodeValueByTagName

public static String **getNodeValueByTagName**(org.w3c.dom.Element node, String name)

Get a child Node value by tag name. Return null if does not exist.

#### Parameters:

node - parent node  
name - tag name

#### Returns:

node value or null if does not exist

### getNodeByTagName

public static org.w3c.dom.Node **getNodeByTagName**(org.w3c.dom.Element node, String name)

Return a child Node by tag name. Return null if does not exist.

#### Parameters:

node - parent node

(continued from last page)

name - tag name

**Returns:**

Node or null if does not exist

---

## getNodeValue

```
public static String getNodeValue(org.w3c.dom.Node node)
```

Return the text value of a node. Return concatenated value of all children nodes that are text nodes.

**Parameters:**

node - parent node

**Returns:**

concatenated text nodes or empty string if not found or no children

---

## loadConfigProperties

```
public static void loadConfigProperties(org.w3c.dom.Element root,  
    String propertiesXPath,  
    WMSProperties properties)
```

Loads <Properties> elemnt by xpath into properties object.

**Parameters:**

root - root node

propertiesXPath - xpath to search for <Properties> element

properties - properties to add values to

---

## loadConfigProperties

```
public static void loadConfigProperties(org.w3c.dom.NodeList resultList,  
    WMSProperties properties)
```

Given a nodeList load children as properties.

**Parameters:**

resultList - node list

properties - properties to add values to

---

## getXMLPropertyStr

```
public static String getXMLPropertyStr(javax.xml.xpath.XPath xpath,  
    String xpathStr,  
    org.w3c.dom.Element root)
```

Get a single string value pointed to by xpath or null if not found.

**Parameters:**

xpath - XPath interface

xpathStr - xpath string

root - root node to start search

**Returns:**

single string value pointed to by xpath or null if not found

(continued from last page)

## getXMLPropertyStr

```
public static String getXMLPropertyStr( javax.xml.xpath.XPath xpath,
    String xpathStr,
    org.w3c.dom.Element root,
    String defaultVal)
```

Get a single string value pointed to by xpath or defaultVal if not found.

### Parameters:

xpath - XPath interface  
xpathStr - xpath string  
root - node to start search  
defaultVal - default value

### Returns:

single string value pointed to by xpath or defaultVal if not found

---

## getXMLPropertyExists

```
public static boolean getXMLPropertyExists( javax.xml.xpath.XPath xpath,
    String xpathStr,
    org.w3c.dom.Element root)
```

---

## getXMLPropertyInt

```
public static int getXMLPropertyInt( javax.xml.xpath.XPath xpath,
    String xpathStr,
    org.w3c.dom.Element root,
    int defaultVal)
```

Get a single int value pointed to by xpath or defaultVal if not found.

### Parameters:

xpath - XPath interface  
xpathStr - xpath string  
root - node to start search  
defaultVal - default value

### Returns:

int value or defaultVal if not found

---

## getXMLPropertyIntSize

```
public static int getXMLPropertyIntSize( javax.xml.xpath.XPath xpath,
    String xpathStr,
    org.w3c.dom.Element root,
    int defaultVal)
```

---

## getXMLPropertyLong

```
public static long getXMLPropertyLong( javax.xml.xpath.XPath xpath,
    String xpathStr,
    org.w3c.dom.Element root,
    long defaultVal)
```

Get a single long value pointed to by xpath or defaultVal if not found.

---

(continued from last page)

**Parameters:**

xpath - XPath interface  
xpathStr - xpath string  
root - node to start search  
defaultVal - default value

**Returns:**

long value or defaultVal if not found

---

## getXMLPropertyLongSize

```
public static long getXMLPropertyLongSize( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root,
      long defaultVal)
```

---

## getXMLPropertyDouble

```
public static double getXMLPropertyDouble( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root,
      double defaultVal)
```

Get a single double value pointed to by xpath or defaultVal if not found.

**Parameters:**

xpath - XPath interface  
xpathStr - xpath string  
root - node to start search  
defaultVal - default value

**Returns:**

double value or defaultVal if not found

---

## getXMLPropertyBool

```
public static boolean getXMLPropertyBool( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root,
      boolean defaultVal)
```

Get a boolean int value pointed to by xpath or defaultVal if not found.

**Parameters:**

xpath - XPath interface  
xpathStr - xpath string  
root - node to start search  
defaultVal - default value

**Returns:**

boolean value or defaultVal if not found

---

## newXPathFactory

```
public static javax.xml.xpath.XPathFactory newXPathFactory()
```

(continued from last page)

Get a new XPath factory object. There is a bug in certain implementations of the Sun VM that forces an explicit creation of the "com.sun.org.apache.xpath.internal.jaxp.XPathFactoryImpl". This method will try the correct method for creation and if fails will directly create "com.sun.org.apache.xpath.internal.jaxp.XPathFactoryImpl" object.

**Returns:**

XPathFactory or null if not found

---

Package

**com.wowza.wms.amf**

## com.wowza.wms.amf

### Class AMF3Utils

java.lang.Object

└─com.wowza.wms.amf.AMF3Utils

public class **AMF3Utils**  
extends Object

AMF3 utilities

#### Constructor Summary

public	<a href="#">AMF3Utils()</a>
--------	-----------------------------

#### Method Summary

static java.util.Date	<a href="#">deserializeDate</a> (java.nio.ByteBuffer data) Deserialize date type
static int	<a href="#">deserializeInt</a> (java.nio.ByteBuffer data) Deserialize int
static String	<a href="#">deserializeString</a> (java.nio.ByteBuffer data) Deserialize string
static String	<a href="#">deserializeString</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Deserialize string
static String	<a href="#">deserializeString</a> (java.nio.ByteBuffer data, int utflen) Deserialize string
static int	<a href="#">serializeDate</a> (java.io.DataOutputStream out, java.util.Date date) Serialize a date object
static int	<a href="#">serializeInt</a> (java.io.DataOutputStream out, int val) Serialize int value
static int	<a href="#">serializeString</a> (java.io.DataOutputStream out, String str) Serialize a string value
static int	<a href="#">serializeStringNoLength</a> (java.io.DataOutputStream out, String str) Serialize string but do not write the length
static void	<a href="#">serializeZeroLengthString</a> (java.io.DataOutputStream out) Serialize empty string

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait



## Constructors

### AMF3Utils

```
public AMF3Utils()
```

## Methods

### deserializeDate

```
public static java.util.Date deserializeDate(java.nio.ByteBuffer data)
```

Deserialize date type

**Parameters:**

data - buffer

**Returns:**

date

---

### serializeDate

```
public static int serializeDate(java.io.DataOutputStream out,  
    java.util.Date date)
```

Serialize a date object

**Parameters:**

out - output stream

date - date

**Returns:**

number of bytes written

---

### deserializeInt

```
public static int deserializeInt(java.nio.ByteBuffer data)
```

Deserialize int

**Parameters:**

data - buffer

**Returns:**

int value

---

### serializeInt

```
public static int serializeInt(java.io.DataOutputStream out,  
    int val)
```

Serialize int value

**Parameters:**

(continued from last page)

out - output stream  
val - int value

**Returns:**

number of bytes written

---

## deserializeString

```
public static String deserializeString(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)  
    throws java.io.IOException
```

Deserialize string

**Parameters:**

data - data  
context - AMF context

**Returns:**

string value

**Throws:**

IOException

---

## deserializeString

```
public static String deserializeString(java.nio.ByteBuffer data)  
    throws java.io.IOException
```

Deserialize string

**Parameters:**

data - data

**Returns:**

string value

**Throws:**

IOException

---

## deserializeString

```
public static String deserializeString(java.nio.ByteBuffer data,  
    int utflen)  
    throws java.io.IOException
```

Deserialize string

**Parameters:**

data - data  
utflen - len of the string

**Returns:**

string value

**Throws:**

IOException

(continued from last page)

## serializeZeroLengthString

```
public static void serializeZeroLengthString(java.io.DataOutputStream out)
```

Serialize empty string

**Parameters:**

out - output stream

---

## serializeStringNoLength

```
public static int serializeStringNoLength(java.io.DataOutputStream out,  
    String str)  
throws java.io.IOException
```

Serialize string but do not write the length

**Parameters:**

out - output stream

str - string value

**Returns:**

number of bytes written

**Throws:**

IOException

---

## serializeString

```
public static int serializeString(java.io.DataOutputStream out,  
    String str)  
throws java.io.IOException
```

Serialize a string value

**Parameters:**

out - output stream

str - string value

**Returns:**

number of bytes written

**Throws:**

IOException

---

## com.wowza.wms.amf

### Class AMFData

java.lang.Object

└─com.wowza.wms.amf.AMFData

Direct Known Subclasses:

[AMFDataObj](#), [AMFDataList](#), [AMFDataItem](#), [AMFDataByteArray](#), [AMFDataArray](#)

public abstract class **AMFData**  
extends Object

Base abstract class for data in Action Message Format (AMF). Data is sent between the Flash client and the Wowza Media Server using the AMF format. This class cannot be instantiated. It serves as the base class for all AMFData objects.

#### Field Summary

public static final	<a href="#">AMF_LEVEL0</a> Value: <b>0</b>
public static final	<a href="#">AMF_LEVEL3</a> Value: <b>3</b>
public static final	<a href="#">DATA_TYPE_AMF3</a> Value: <b>17</b>
public static final	<a href="#">DATA_TYPE_AMF3_ARRAY</a> Value: <b>9</b>
public static final	<a href="#">DATA_TYPE_AMF3_BOOLEAN_FALSE</a> Value: <b>2</b>
public static final	<a href="#">DATA_TYPE_AMF3_BOOLEAN_TRUE</a> Value: <b>3</b>
public static final	<a href="#">DATA_TYPE_AMF3_BYTEARRAY</a> Value: <b>12</b>
public static final	<a href="#">DATA_TYPE_AMF3_DATE</a> Value: <b>8</b>
public static final	<a href="#">DATA_TYPE_AMF3_INTEGER</a> Value: <b>4</b>
public static final	<a href="#">DATA_TYPE_AMF3_NULL</a> Value: <b>1</b>

public static final	<a href="#"><u>DATA_TYPE_AMF3_NUMBER</u></a> Value: <b>5</b>
public static final	<a href="#"><u>DATA_TYPE_AMF3_OBJECT</u></a> Value: <b>10</b>
public static final	<a href="#"><u>DATA_TYPE_AMF3_STRING</u></a> Value: <b>6</b>
public static final	<a href="#"><u>DATA_TYPE_AMF3_UNDEFINED</u></a> Value: <b>0</b>
public static final	<a href="#"><u>DATA_TYPE_AMF3_XML_LEGACY</u></a> Value: <b>7</b>
public static final	<a href="#"><u>DATA_TYPE_AMF3_XML_TOP</u></a> Value: <b>11</b>
public static final	<a href="#"><u>DATA_TYPE_ARRAY</u></a> Value: <b>10</b>
public static final	<a href="#"><u>DATA_TYPE_AS_OBJECT</u></a> Value: <b>13</b>
public static final	<a href="#"><u>DATA_TYPE_BOOLEAN</u></a> Value: <b>1</b>
public static final	<a href="#"><u>DATA_TYPE_BYTEARRAY</u></a> Value: <b>33</b>
public static final	<a href="#"><u>DATA_TYPE_CUSTOM_CLASS</u></a> Value: <b>16</b>
public static final	<a href="#"><u>DATA_TYPE_DATE</u></a> Value: <b>11</b>
public static final	<a href="#"><u>DATA_TYPE_INTEGER</u></a> Value: <b>32</b>
public static final	<a href="#"><u>DATA_TYPE_LONG_STRING</u></a> Value: <b>12</b>
public static final	<a href="#"><u>DATA_TYPE_MIXED_ARRAY</u></a> Value: <b>8</b>
public static final	<a href="#"><u>DATA_TYPE_MOVIE_CLIP</u></a> Value: <b>4</b>

public static final	<a href="#">DATA_TYPE_NULL</a> Value: <b>5</b>
public static final	<a href="#">DATA_TYPE_NUMBER</a> Value: <b>0</b>
public static final	<a href="#">DATA_TYPE_OBJECT</a> Value: <b>3</b>
public static final	<a href="#">DATA_TYPE_OBJECT_END</a> Value: <b>9</b>
public static final	<a href="#">DATA_TYPE_RECORDSET</a> Value: <b>14</b>
public static final	<a href="#">DATA_TYPE_REFERENCE_OBJECT</a> Value: <b>7</b>
public static final	<a href="#">DATA_TYPE_STRING</a> Value: <b>2</b>
public static final	<a href="#">DATA_TYPE_UNDEFINED</a> Value: <b>6</b>
public static final	<a href="#">DATA_TYPE_UNKNOWN</a> Value: <b>-1</b>
public static final	<a href="#">DATA_TYPE_XML</a> Value: <b>15</b>
public static final	<a href="#">DATA_TYPE_XML_TOP</a> Value: <b>34</b>
public static final	<a href="#">MILLS_PER_HOUR</a> Number of milliseconds in an hour Value: <b>60000</b>
protected	<a href="#">type</a>

## Constructor Summary

public	<a href="#">AMFData()</a>
--------	---------------------------

## Method Summary

static <a href="#">AMFDataContextDeserialize</a> <a href="#">ize</a>	<a href="#">createContextDeserialize()</a> Create an AMF3 deserialization context
--	--

static <a href="#">AMFDataContextDeserialize</a>	<a href="#">createContextDeserialize</a> (int objectEncoding) Create an AMF3 deserialization context
static <a href="#">AMFDataContextSerialize</a>	<a href="#">createContextSerialize</a> () Create an AMF3 serialization context
static <a href="#">AMFDataContextSerialize</a>	<a href="#">createContextSerialize</a> (int objectEncoding) Create an AMF3 serialization context
abstract void	<a href="#">deserialize</a> (java.nio.ByteBuffer data) Deserialize data in byte buffer
abstract void	<a href="#">deserialize</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Deserialize data in byte buffer
static <a href="#">AMFData</a>	<a href="#">deserializeInnerObject</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Deserialize next item
static <a href="#">AMFData</a>	<a href="#">getReference</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Get AMF3 object reference
int	<a href="#">getType</a> () Returns the data type for this object
abstract Object	<a href="#">getValue</a> () Convert object to Java native class
static boolean	<a href="#">isAMF3Start</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Returns true if next byte in data is AMF3 start
static boolean	<a href="#">isArrayStart</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Returns true if next byte in data is an array start
static boolean	<a href="#">isByteArrayStart</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Returns true if next byte is ByteArray start
static boolean	<a href="#">isMixedArrayStart</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Returns true if next byte in data is mixed array start
static boolean	<a href="#">isObjEnd</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Returns true if next byte is object end
static boolean	<a href="#">isObjStart</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context) Returns true if next byte in data is object start
static int	<a href="#">peekByte</a> (java.nio.ByteBuffer data) Return the next byte in the buffer without incrementing the data position
abstract byte[]	<a href="#">serialize</a> () Serial object to byte array
abstract byte[]	<a href="#">serialize</a> ( <a href="#">AMFDataContextSerialize</a> context) Serial object to byte array

abstract void	<a href="#">serialize</a> (java.io.DataOutputStream out) Serialize object to output stream
abstract void	<a href="#">serialize</a> (java.io.DataOutputStream out, <a href="#">AMFDataContextSerialize</a> context) Serialize object to output stream
abstract void	<a href="#">serialize</a> (java.io.DataOutputStream out, int objectEncoding) Serialize object to output stream
abstract byte[]	<a href="#">serialize</a> (int objectEncoding) Serial object to byte array
void	<a href="#">setType</a> (int type) Sets the the data type for this object
static int	<a href="#">skipByte</a> (java.nio.ByteBuffer data) Skip forward one byte in the byte buffer
static boolean	<a href="#">testNextByte</a> (java.nio.ByteBuffer data, int test) Peek at the next value in data to see if its the test value
static boolean	<a href="#">triggerAMF3Switch</a> ( <a href="#">AMFData</a> data) Return true if the object is serialized differently in AMF3

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### DATA\_TYPE\_UNKNOWN

```
public static final byte DATA_TYPE_UNKNOWN
```

Constant value: **-1**

### DATA\_TYPE\_NUMBER

```
public static final byte DATA_TYPE_NUMBER
```

Constant value: **0**

### DATA\_TYPE\_BOOLEAN

```
public static final byte DATA_TYPE_BOOLEAN
```

Constant value: **1**

### DATA\_TYPE\_STRING

```
public static final byte DATA_TYPE_STRING
```



(continued from last page)

Constant value: **2**

---

## DATA\_TYPE\_OBJECT

```
public static final byte DATA_TYPE_OBJECT
```

Constant value: **3**

---

## DATA\_TYPE\_MOVIE\_CLIP

```
public static final byte DATA_TYPE_MOVIE_CLIP
```

Constant value: **4**

---

## DATA\_TYPE\_NULL

```
public static final byte DATA_TYPE_NULL
```

Constant value: **5**

---

## DATA\_TYPE\_UNDEFINED

```
public static final byte DATA_TYPE_UNDEFINED
```

Constant value: **6**

---

## DATA\_TYPE\_REFERENCE\_OBJECT

```
public static final byte DATA_TYPE_REFERENCE_OBJECT
```

Constant value: **7**

---

## DATA\_TYPE\_MIXED\_ARRAY

```
public static final byte DATA_TYPE_MIXED_ARRAY
```

Constant value: **8**

---

## DATA\_TYPE\_OBJECT\_END

```
public static final byte DATA_TYPE_OBJECT_END
```

Constant value: **9**

---

## DATA\_TYPE\_ARRAY

```
public static final byte DATA_TYPE_ARRAY
```

Constant value: **10**

(continued from last page)

---

## DATA\_TYPE\_DATE

```
public static final byte DATA_TYPE_DATE
```

Constant value: **11**

---

## DATA\_TYPE\_LONG\_STRING

```
public static final byte DATA_TYPE_LONG_STRING
```

Constant value: **12**

---

## DATA\_TYPE\_AS\_OBJECT

```
public static final byte DATA_TYPE_AS_OBJECT
```

Constant value: **13**

---

## DATA\_TYPE\_RECORDSET

```
public static final byte DATA_TYPE_RECORDSET
```

Constant value: **14**

---

## DATA\_TYPE\_XML

```
public static final byte DATA_TYPE_XML
```

Constant value: **15**

---

## DATA\_TYPE\_CUSTOM\_CLASS

```
public static final byte DATA_TYPE_CUSTOM_CLASS
```

Constant value: **16**

---

## DATA\_TYPE\_AMF3

```
public static final byte DATA_TYPE_AMF3
```

Constant value: **17**

---

## DATA\_TYPE\_INTEGER

```
public static final byte DATA_TYPE_INTEGER
```

Constant value: **32**

---

## DATA\_TYPE\_BYTEARRAY

```
public static final byte DATA_TYPE_BYTEARRAY
```

---

(continued from last page)

Constant value: **33**

---

## DATA\_TYPE\_XML\_TOP

```
public static final byte DATA_TYPE_XML_TOP
```

Constant value: **34**

---

## DATA\_TYPE\_AMF3\_UNDEFINED

```
public static final byte DATA_TYPE_AMF3_UNDEFINED
```

Constant value: **0**

---

## DATA\_TYPE\_AMF3\_NULL

```
public static final byte DATA_TYPE_AMF3_NULL
```

Constant value: **1**

---

## DATA\_TYPE\_AMF3\_BOOLEAN\_FALSE

```
public static final byte DATA_TYPE_AMF3_BOOLEAN_FALSE
```

Constant value: **2**

---

## DATA\_TYPE\_AMF3\_BOOLEAN\_TRUE

```
public static final byte DATA_TYPE_AMF3_BOOLEAN_TRUE
```

Constant value: **3**

---

## DATA\_TYPE\_AMF3\_INTEGER

```
public static final byte DATA_TYPE_AMF3_INTEGER
```

Constant value: **4**

---

## DATA\_TYPE\_AMF3\_NUMBER

```
public static final byte DATA_TYPE_AMF3_NUMBER
```

Constant value: **5**

---

## DATA\_TYPE\_AMF3\_STRING

```
public static final byte DATA_TYPE_AMF3_STRING
```

Constant value: **6**

---

## DATA\_TYPE\_AMF3\_XML\_LEGACY

public static final byte **DATA\_TYPE\_AMF3\_XML\_LEGACY**

Constant value: **7**

---

## DATA\_TYPE\_AMF3\_DATE

public static final byte **DATA\_TYPE\_AMF3\_DATE**

Constant value: **8**

---

## DATA\_TYPE\_AMF3\_ARRAY

public static final byte **DATA\_TYPE\_AMF3\_ARRAY**

Constant value: **9**

---

## DATA\_TYPE\_AMF3\_OBJECT

public static final byte **DATA\_TYPE\_AMF3\_OBJECT**

Constant value: **10**

---

## DATA\_TYPE\_AMF3\_XML\_TOP

public static final byte **DATA\_TYPE\_AMF3\_XML\_TOP**

Constant value: **11**

---

## DATA\_TYPE\_AMF3\_BYTEARRAY

public static final byte **DATA\_TYPE\_AMF3\_BYTEARRAY**

Constant value: **12**

---

## AMF\_LEVEL0

public static final byte **AMF\_LEVEL0**

Constant value: **0**

---

## AMF\_LEVEL3

public static final byte **AMF\_LEVEL3**

Constant value: **3**

---

(continued from last page)

## MILLS\_PER\_HOUR

```
public static final int MILLS_PER_HOUR
```

Number of milliseconds in an hour  
Constant value: **60000**

## type

```
protected int type
```

## Constructors

### AMFData

```
public AMFData()
```

## Methods

### getType

```
public int getType()
```

Returns the data type for this object

**Returns:**

object type DATA\_TYPE\_\*

### setType

```
public void setType(int type)
```

Sets the the data type for this object

**Parameters:**

type - type DATA\_TYPE\_\*

### testNextByte

```
public static boolean testNextByte(java.nio.ByteBuffer data,  
    int test)
```

Peek at the next value in data to see if its the test value

**Parameters:**

data - binary data being deserialized  
test - value being tested

**Returns:**

return true if the next byte in the buffer equals the test value

### peekByte

```
public static int peekByte(java.nio.ByteBuffer data)
```

(continued from last page)

Return the next byte in the buffer without incrementing the data position

**Parameters:**

data - binary data being deserialized

**Returns:**

next byte in buffer

---

## skipByte

```
public static int skipByte(java.nio.ByteBuffer data)
```

Skip forward one byte in the byte buffer

**Parameters:**

data - binary data being deserialized

**Returns:**

next byte in buffer

---

## isObjStart

```
public static boolean isObjStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is object start

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

Returns true if next byte in data is object start

---

## isAMF3Start

```
public static boolean isAMF3Start(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is AMF3 start

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

Returns true if next byte in data is object start

---

## isArrayStart

```
public static boolean isArrayStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is an array start

**Parameters:**

data - binary data being deserialized  
context - deserialization context

---

(continued from last page)

**Returns:**

Returns true if next byte in data is and array start

---

## isMixedArrayStart

```
public static boolean isMixedArrayStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is mixed array start

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

Returns true if next byte in data is mixed array start

---

## isObjEnd

```
public static boolean isObjEnd(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte is object end

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

Returns true if next byte in object end

---

## isByteArrayStart

```
public static boolean isByteArrayStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte is ByteArray start

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

true if next byte in object end

---

## getReference

```
public static AMFData getReference(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Get AMF3 object reference

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

null if not a reference else referenced object

## deserializeInnerObject

```
public static AMFData deserializeInnerObject(java.nio.ByteBuffer data,  
      AMFDataContextDeserialize context)  
    throws java.io.IOException
```

Deserialize next item

**Parameters:**

data - binary data being deserialized  
context - deserialization context

**Returns:**

deserialized object

**Throws:**

IOException

---

## createContextSerialize

```
public static AMFDataContextSerialize createContextSerialize()
```

Create an AMF3 serialization context

**Returns:**

AMF3 serialization context

---

## createContextSerialize

```
public static AMFDataContextSerialize createContextSerialize(int objectEncoding)
```

Create an AMF3 serialization context

**Parameters:**

objectEncoding - object encoding level (see AMF\_LEVEL\*)

**Returns:**

AMF3 serialization context

---

## createContextDeserialize

```
public static AMFDataContextDeserialize createContextDeserialize()
```

Create an AMF3 deserialization context

**Returns:**

AMF3 deserialization context

---

## createContextDeserialize

```
public static AMFDataContextDeserialize createContextDeserialize(int objectEncoding)
```

Create an AMF3 deserialization context

**Parameters:**

objectEncoding - object encoding level (see AMF\_LEVEL\*)

**Returns:**



(continued from last page)

## AMF3 deserialization context

---

**serialize**

```
public abstract void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

**Parameters:**

out - Output stream

---

**serialize**

```
public abstract void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

**Parameters:**

out - Output stream

objectEncoding - object encoding level (see AMF\_LEVEL\*)

---

**serialize**

```
public abstract void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

**Parameters:**

out - Output stream

context - serialization context used by AMF3

---

**serialize**

```
public abstract byte[] serialize()
```

Serial object to byte array

**Returns:**

serialized byte array

---

**serialize**

```
public abstract byte[] serialize(int objectEncoding)
```

Serial object to byte array

**Parameters:**

objectEncoding - object encoding level (see AMF\_LEVEL\*)

**Returns:**

serialized byte array

---

**serialize**

```
public abstract byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

---

(continued from last page)

**Parameters:**

context - serialization context used by AMF3

**Returns:**serialized byte array

---

**deserialize**

```
public abstract void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

**Parameters:**data - binary data

---

**deserialize**

```
public abstract void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

**Parameters:**

data - binary data

context - deserialization context used by AMF3

---

**getValue**

```
public abstract Object getValue()
```

Convert object to Java native class

**Returns:**java native class

---

**triggerAMF3Switch**

```
public static boolean triggerAMF3Switch(AMFData data)
```

Return true if the object is serialized differently in AMF3

**Parameters:**

data - AMF object

**Returns:**true if the object is serialized differently in AMF3

---

## com.wowza.wms.amf Class AMFDataArray

```
java.lang.Object
|
+-com.wowza.wms.amf.AMFData
|
+-com.wowza.wms.amf.AMFDataArray
```

```
public class AMFDataArray
extends AMFData
```

AMFDataArray: class for marshalling data between Wowza Pro server and Flash client. This class is a simple ordered array of items.

### Create Array of Strings

```
AMFDataArray amfDataArray = new AMFDataArray();

amfDataArray.add("item1");
amfDataArray.add("item2");
amfDataArray.add("item3");
```

### Iterate Items In Array

```
AMFDataArray amfDataArray;

for(int i=0;i<amfDataArray.size();i++)
{
    AMFData amfData = amfDataArray.get(i);
    WMSLoggerFactory.getLogger(null).debug("amfData.getType(): "+amfData.getType());
}
```

**NOTE:** There is a slight difference between this class and AMFDataList. This class when serialized/deserialized does include the DATA\_TYPE\_ARRAY header (byte) and array size (int).

**NOTE:** Simple arrays created in the Flash player client and sent to the Wowza Pro server are of type [AMFDataMixedArray](#).

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF\\_LEVEL0](#), [AMF\\_LEVEL3](#), [DATA\\_TYPE\\_AMF3](#), [DATA\\_TYPE\\_AMF3\\_ARRAY](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_FALSE](#),  
[DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_TRUE](#), [DATA\\_TYPE\\_AMF3\\_BYTEARRAY](#), [DATA\\_TYPE\\_AMF3\\_DATE](#),  
[DATA\\_TYPE\\_AMF3\\_INTEGER](#), [DATA\\_TYPE\\_AMF3\\_NULL](#), [DATA\\_TYPE\\_AMF3\\_NUMBER](#), [DATA\\_TYPE\\_AMF3\\_OBJECT](#),  
[DATA\\_TYPE\\_AMF3\\_STRING](#), [DATA\\_TYPE\\_AMF3\\_UNDEFINED](#), [DATA\\_TYPE\\_AMF3\\_XML\\_LEGACY](#),  
[DATA\\_TYPE\\_AMF3\\_XML\\_TOP](#), [DATA\\_TYPE\\_ARRAY](#), [DATA\\_TYPE\\_AS\\_OBJECT](#), [DATA\\_TYPE\\_BOOLEAN](#),  
[DATA\\_TYPE\\_BYTEARRAY](#), [DATA\\_TYPE\\_CUSTOM\\_CLASS](#), [DATA\\_TYPE\\_DATE](#), [DATA\\_TYPE\\_INTEGER](#),  
[DATA\\_TYPE\\_LONG\\_STRING](#), [DATA\\_TYPE\\_MIXED\\_ARRAY](#), [DATA\\_TYPE\\_MOVIE\\_CLIP](#), [DATA\\_TYPE\\_NULL](#),  
[DATA\\_TYPE\\_NUMBER](#), [DATA\\_TYPE\\_OBJECT](#), [DATA\\_TYPE\\_OBJECT\\_END](#), [DATA\\_TYPE\\_RECORDSET](#),  
[DATA\\_TYPE\\_REFERENCE\\_OBJECT](#), [DATA\\_TYPE\\_STRING](#), [DATA\\_TYPE\\_UNDEFINED](#), [DATA\\_TYPE\\_UNKNOWN](#),  
[DATA\\_TYPE\\_XML](#), [DATA\\_TYPE\\_XML\\_TOP](#), [MILLS\\_PER\\_HOUR](#), [type](#)

## Constructor Summary

public	<a href="#">AMFDataArray</a> () Create empty AMFDataArray object
public	<a href="#">AMFDataArray</a> (byte[] data) Deserialize entire data array and create AMFDataArray object
public	<a href="#">AMFDataArray</a> (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataArray object
public	<a href="#">AMFDataArray</a> (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataArray object
public	<a href="#">AMFDataArray</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)

## Method Summary

void	<a href="#">add</a> ( <a href="#">AMFData</a> data) Append a new item onto the array
void	<a href="#">add</a> (boolean data) Append a boolean (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (java.util.Date data) Append a date (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (double data) Append a double (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int data) Append a int (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, <a href="#">AMFData</a> data) Insert an item into the array
void	<a href="#">add</a> (int index, boolean data) Insert a boolean value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, java.util.Date data) Insert a date value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, double data) Insert a double value (will be wrapped in an AMFDataItem object)

void	<a href="#">add</a> (int index, int data) Insert a int value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, long data) Insert a long value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, String data) Insert a string value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (long data) Append a long (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (String data) Append a string (will be wrapped in an AMFDataItem object)
void	<a href="#">deserialize</a> (java.nio.ByteBuffer data)
void	<a href="#">deserialize</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)
<a href="#">AMFData</a>	<a href="#">get</a> (int index) Get item at index
boolean	<a href="#">getBoolean</a> (int index) Get item at index return as boolean
byte	<a href="#">getBytes</a> (int index) Get item at index return as byte
java.util.Date	<a href="#">getDate</a> (int index) Get item at index return as Date
double	<a href="#">getDouble</a> (int index) Get item at index return as double
float	<a href="#">getFloat</a> (int index) Get item at index return as float
int	<a href="#">getInt</a> (int index) Get item at index return as int
long	<a href="#">getLong</a> (int index) Get item at index return as long
<a href="#">AMFDataObj</a>	<a href="#">getObject</a> (int index) Get item at index return as AMFDataObj
short	<a href="#">getShort</a> (int index) Get item at index return as short
String	<a href="#">getString</a> (int index) Get item at index return as String
Object	<a href="#">getValue</a> ( )
<a href="#">AMFData</a>	<a href="#">remove</a> (int index) Remove an item from the array

byte[]	<a href="#">serialize()</a>
byte[]	<a href="#">serialize()</a> ( <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize()</a> (java.io.DataOutputStream out)
void	<a href="#">serialize()</a> (java.io.DataOutputStream out, <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize()</a> (java.io.DataOutputStream out, int objectEncoding)
byte[]	<a href="#">serialize()</a> (int objectEncoding)
void	<a href="#">set()</a> (int index, <a href="#">AMFData</a> data) Set an array item
void	<a href="#">set()</a> (int index, boolean data) Set an boolean value (will be wrapped in an AMFDataItem object)
void	<a href="#">set()</a> (int index, java.util.Date data) Set an date value (will be wrapped in an AMFDataItem object)
void	<a href="#">set()</a> (int index, double data) Set an double value (will be wrapped in an AMFDataItem object)
void	<a href="#">set()</a> (int index, int data) Set an int value (will be wrapped in an AMFDataItem object)
void	<a href="#">set()</a> (int index, long data) Set an long value (will be wrapped in an AMFDataItem object)
void	<a href="#">set()</a> (int index, String data) Set an string value (will be wrapped in an AMFDataItem object)
int	<a href="#">size()</a> Returns the number of items in array
String	<a href="#">toString()</a> Return object as formatted string

#### Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

#### Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

## Constructors

(continued from last page)

## AMFDataArray

```
public AMFDataArray()
```

Create empty AMFDataArray object

---

## AMFDataArray

```
public AMFDataArray(byte[] data)
```

Deserialize entire data array and create AMFDataArray object

**Parameters:**

data - binary data

---

## AMFDataArray

```
public AMFDataArray(byte[] data,  
                    int offset,  
                    int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataArray object

**Parameters:**

data - binary data

offset - starting offset into data

size - size of data to deserialize

---

## AMFDataArray

```
public AMFDataArray(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataArray object

**Parameters:**

data - binary data

---

## AMFDataArray

```
public AMFDataArray(java.nio.ByteBuffer data,  
                   AMFDataContextDeserialize context)
```

---

## Methods

### remove

```
public AMFData remove(int index)
```

Remove an item from the array

**Parameters:**

index - index

**Returns:**

delete item or null if not found

## size

```
public int size()
```

Returns the number of items in array

**Returns:**

number of items in array

---

## add

```
public void add(AMFData data)
```

Append a new item onto the array

**Parameters:**

data - AMFData object

---

## add

```
public void add(String data)
```

Append a string (will be wrapped in an AMFDataItem object)

**Parameters:**

data - string value

---

## add

```
public void add(double data)
```

Append a double (will be wrapped in an AMFDataItem object)

**Parameters:**

data - double value

---

## add

```
public void add(int data)
```

Append a int (will be wrapped in an AMFDataItem object)

**Parameters:**

data - int value

---

## add

```
public void add(long data)
```

Append a long (will be wrapped in an AMFDataItem object)

**Parameters:**

data - long value

---

## add

```
public void add(java.util.Date data)
```

---



(continued from last page)

Append a date (will be wrapped in an AMFDataItem object)

**Parameters:**

data - date value

---

**add**

```
public void add(boolean data)
```

Append a boolean (will be wrapped in an AMFDataItem object)

**Parameters:**

data - boolean value

---

**add**

```
public void add(int index,  
    AMFData data)
```

Insert an item into the array

**Parameters:**

index - index

data - AMFData object

---

**add**

```
public void add(int index,  
    String data)
```

Insert a string value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index

data - string value

---

**add**

```
public void add(int index,  
    double data)
```

Insert a double value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index

data - double value

---

**add**

```
public void add(int index,  
    int data)
```

Insert a int value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index

data - int value

---

## add

```
public void add(int index,  
               long data)
```

Insert a long value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - long value

---

## add

```
public void add(int index,  
               java.util.Date data)
```

Insert a date value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - date value

---

## add

```
public void add(int index,  
               boolean data)
```

Insert a boolean value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - boolean value

---

## set

```
public void set(int index,  
               AMFData data)
```

Set an array item

**Parameters:**

index - index  
data - AMFData object

---

## set

```
public void set(int index,  
               String data)
```

Set a string value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - string value

---

## set

```
public void set(int index,  
               double data)
```

---

(continued from last page)

Set an double value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - double value

---

**set**

```
public void set(int index,  
                int data)
```

Set an int value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - int value

---

**set**

```
public void set(int index,  
                long data)
```

Set an long value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - long value

---

**set**

```
public void set(int index,  
                java.util.Date data)
```

Set an date value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - date value

---

**set**

```
public void set(int index,  
                boolean data)
```

Set an boolean value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - boolean value

---

**get**

```
public AMFData get(int index)
```

Get item at index

**Parameters:**

index

---

(continued from last page)

**Returns:**

Returns AMFData object or null if out of bounds

---

## getString

```
public String getString(int index)
```

Get item at index return as String

**Parameters:**

index

**Returns:**

Return item as String or null if out of bounds

---

## getInt

```
public int getInt(int index)
```

Get item at index return as int

**Parameters:**

index

**Returns:**

Return item as int or 0 if out of bounds

---

## getLong

```
public long getLong(int index)
```

Get item at index return as long

**Parameters:**

index

**Returns:**

Return item as long or 0 if out of bounds

---

## getShort

```
public short getShort(int index)
```

Get item at index return as short

**Parameters:**

index

**Returns:**

Return item as short or 0 if out of bounds

---

## getByte

```
public byte getByte(int index)
```

Get item at index return as byte

**Parameters:**

(continued from last page)

index

**Returns:**

Return item as byte or 0 if out of bounds

---

## getBoolean

```
public boolean getBoolean(int index)
```

Get item at index return as boolean

**Parameters:**

index

**Returns:**

Return item as boolean or false if out of bounds

---

## getDate

```
public java.util.Date getDate(int index)
```

Get item at index return as Date

**Parameters:**

index

**Returns:**

Return item as Date or null if out of bounds

---

## getObject

```
public AMFDataObj getObject(int index)
```

Get item at index return as AMFDataObj

**Parameters:**

index

**Returns:**

Return item as AMFDataObj or null if out of bounds

---

## getDouble

```
public double getDouble(int index)
```

Get item at index return as double

**Parameters:**

index

**Returns:**

Return item as double or 0 if out of bounds

---

## getFloat

```
public float getFloat(int index)
```

Get item at index return as float

(continued from last page)

**Parameters:**

index

**Returns:**

Return item as float or 0 if out of bounds

---

**deserialize**

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

---

**deserialize**

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

---

**serialize**

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

---

**serialize**

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

---

**serialize**

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

---

**serialize**

```
public byte[] serialize()
```

Serial object to byte array

---

**serialize**

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

---

**serialize**

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

(continued from last page)

## **getValue**

```
public Object getValue()
```

Convert object to Java native class

---

## **toString**


```
public String toString()
```

Return object as formatted string

## com.wowza.wms.amf

### Class AMFDataByteArray

java.lang.Object



public class **AMFDataByteArray**  
 extends [AMFData](#)

AMFDataByteArray: class for marshalling data between Wowza Pro server and Flash client. This class is a simple byte array.

#### Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF\\_LEVEL0](#), [AMF\\_LEVEL3](#), [DATA\\_TYPE\\_AMF3](#), [DATA\\_TYPE\\_AMF3\\_ARRAY](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_FALSE](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_TRUE](#), [DATA\\_TYPE\\_AMF3\\_BYTEARRAY](#), [DATA\\_TYPE\\_AMF3\\_DATE](#), [DATA\\_TYPE\\_AMF3\\_INTEGER](#), [DATA\\_TYPE\\_AMF3\\_NULL](#), [DATA\\_TYPE\\_AMF3\\_NUMBER](#), [DATA\\_TYPE\\_AMF3\\_OBJECT](#), [DATA\\_TYPE\\_AMF3\\_STRING](#), [DATA\\_TYPE\\_AMF3\\_UNDEFINED](#), [DATA\\_TYPE\\_AMF3\\_XML\\_LEGACY](#), [DATA\\_TYPE\\_AMF3\\_XML\\_TOP](#), [DATA\\_TYPE\\_ARRAY](#), [DATA\\_TYPE\\_AS\\_OBJECT](#), [DATA\\_TYPE\\_BOOLEAN](#), [DATA\\_TYPE\\_BYTEARRAY](#), [DATA\\_TYPE\\_CUSTOM\\_CLASS](#), [DATA\\_TYPE\\_DATE](#), [DATA\\_TYPE\\_INTEGER](#), [DATA\\_TYPE\\_LONG\\_STRING](#), [DATA\\_TYPE\\_MIXED\\_ARRAY](#), [DATA\\_TYPE\\_MOVIE\\_CLIP](#), [DATA\\_TYPE\\_NULL](#), [DATA\\_TYPE\\_NUMBER](#), [DATA\\_TYPE\\_OBJECT](#), [DATA\\_TYPE\\_OBJECT\\_END](#), [DATA\\_TYPE\\_RECORDSET](#), [DATA\\_TYPE\\_REFERENCE\\_OBJECT](#), [DATA\\_TYPE\\_STRING](#), [DATA\\_TYPE\\_UNDEFINED](#), [DATA\\_TYPE\\_UNKNOWN](#), [DATA\\_TYPE\\_XML](#), [DATA\\_TYPE\\_XML\\_TOP](#), [MILLS\\_PER\\_HOUR](#), [type](#)

#### Constructor Summary

public	<a href="#">AMFDataByteArray()</a> Create empty AMFDataByteArray object
public	<a href="#">AMFDataByteArray(byte[] data)</a> Deserialize entire byte array and create AMFDataByteArray object.
public	<a href="#">AMFDataByteArray(byte[] data, int offset, int size)</a> Deserialize data array starting at offset for size bytes and create AMFDataByteArray object.
public	<a href="#">AMFDataByteArray(java.nio.ByteBuffer data)</a> Deserialize entire data array and create AMFDataByteArray object.
public	<a href="#">AMFDataByteArray(java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)</a> Deserialize entire data array and create AMFDataByteArray object.

#### Method Summary

int	<a href="#">compress()</a> Compress the internal buffer using the ZLIB compression library
int	<a href="#">decompress()</a> Decompress the internal buffer using the ZLIB compression library
void	<a href="#">deserialize(java.nio.ByteBuffer data)</a>



void	<a href="#">deserialize</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)
Object	<a href="#">getValue</a> () Returns the underlying byte[] data buffer
byte[]	<a href="#">serialize</a> ()
byte[]	<a href="#">serialize</a> ( <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize</a> (java.io.DataOutputStream out)
void	<a href="#">serialize</a> (java.io.DataOutputStream out, <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize</a> (java.io.DataOutputStream out, int objectEncoding)
byte[]	<a href="#">serialize</a> (int objectEncoding)
int	<a href="#">size</a> () Returns the number of bytes in the byte array
byte[]	<a href="#">toArray</a> () Returns the underlying data buffer (not a copy)
java.nio.ByteBuffer	<a href="#">toByteBuffer</a> () Wraps the underlying data buffer with a ByteBuffer object.
String	<a href="#">toString</a> () Return object as formatted string
static <a href="#">AMFDataByteArray</a>	<a href="#">wrap</a> (byte[] data) Wraps a byte[] into a AMFDataByteArray.
static <a href="#">AMFDataByteArray</a>	<a href="#">wrap</a> (java.nio.ByteBuffer data) Wraps a ByteBuffer into a AMFDataByteArray.

#### Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

(continued from last page)

## AMFDataByteArray

```
public AMFDataByteArray( )
```

Create empty AMFDataByteArray object

---

## AMFDataByteArray

```
public AMFDataByteArray(byte[] data)
```

Deserialize entire byte array and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMDDDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

**Parameters:**

data - binary data

---

## AMFDataByteArray

```
public AMFDataByteArray(byte[] data,  
                        int offset,  
                        int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMDDDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

**Parameters:**

data - binary data

offset - starting offset into data

size - size of data to deserialize

---

## AMFDataByteArray

```
public AMFDataByteArray(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMDDDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

**Parameters:**

data - binary data

---

## AMFDataByteArray

```
public AMFDataByteArray(java.nio.ByteBuffer data,  
                        AMFDataContextDeserialize context)
```

Deserialize entire data array and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMDDDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

**Parameters:**

data - binary data

context - deserialization context (used for AMF3 decoding)

## Methods

(continued from last page)

## size

```
public int size()
```

Returns the number of bytes in the byte array

**Returns:**

number of bytes in the array

---

## toArray

```
public byte[] toArray()
```

Returns the underlying data buffer (not a copy)

**Returns:**

data buffer (not a copy)

---

## toByteBuffer

```
public java.nio.ByteBuffer toByteBuffer()
```

Wraps the underlying data buffer with a ByteBuffer object.

**Returns:**

byte[] wrapped as ByteBuffer

---

## wrap

```
public static AMFDataByteArray wrap(byte[] data)
```

Wraps a byte[] into a AMFDataByteArray. Note: This method does not copy the array.

**Parameters:**

data - byte[] data

**Returns:**

wrapped byte[]

---

## wrap

```
public static AMFDataByteArray wrap(java.nio.ByteBuffer data)
```

Wraps a ByteBuffer into a AMFDataByteArray. Note: This method only copies the ByteBuffer data if the ByteBuffer.array() method fails.

**Parameters:**

data - ByteBuffer data

**Returns:**

wrapped ByteBuffer

---

## getValue

```
public Object getValue()
```

Returns the underlying byte[] data buffer

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

---

## serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

---

## serialize

```
public byte[] serialize()
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

---

## compress

```
public int compress()
```

Compress the internal buffer using the ZLIB compression library

**Returns:**

---

(continued from last page)

size of compressed buffer

---

## decompress

```
public int decompress()
```

Decompress the internal buffer using the ZLIB compression library

**Returns:**

size of decompressed buffer

---

## toString

```
public String toString()
```

Return object as formatted string

## com.wowza.wms.amf

### Class AMFDataContextDeserialize

java.lang.Object

└─com.wowza.wms.amf.AMFDataContextDeserialize

public class **AMFDataContextDeserialize**  
extends Object

AMF context used for deserialization

#### Constructor Summary

public	<a href="#">AMFDataContextDeserialize()</a> Constructor
public	<a href="#">AMFDataContextDeserialize(int objectEncoding)</a> Constructor with encoding

#### Method Summary

void	<a href="#">addObject(Object obj)</a> Add an object to the object cache
void	<a href="#">addString(String str)</a> Add a string to the string cache
void	<a href="#">addTrait(AMFDataTrait obj)</a> Add a trait to the trait cache
int	<a href="#">clearIntData()</a> Internal use, get and clear int data
int	<a href="#">getIntData()</a> Internal use, get int data
Object	<a href="#">getObject(int index)</a> Get an object from the object cache
int	<a href="#">getObjectEncoding()</a> Get object encoding, see AMFData.AMF_LEVEL*
String	<a href="#">getString(int index)</a> Get a string from the string cache
<a href="#">AMFDataTrait</a>	<a href="#">getTrait(int index)</a> Get a trait from the trait cache
boolean	<a href="#">isAMF0()</a> Is context AMF0
boolean	<a href="#">isAMF3()</a> Is context AMF3

boolean	<a href="#"><code>isIntData()</code></a> Internal use, get int data
void	<a href="#"><code>setIntData(int intData)</code></a> Internal use, set int data
void	<a href="#"><code>setObjectEncoding(int objectEncoding)</code></a> Set object encoding, see <code>AMFData.AMF_LEVEL*</code>

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### AMFDataContextDeserialize

```
public AMFDataContextDeserialize()
```

Constructor

### AMFDataContextDeserialize

```
public AMFDataContextDeserialize(int objectEncoding)
```

Constructor with encoding

#### Parameters:

`objectEncoding` - object encoding, see `AMFData.AMF_LEVEL*`

## Methods

### isIntData

```
public boolean isIntData()
```

Internal use, get int data

#### Returns:

returns true if pending int data

### setIntData

```
public void setIntData(int intData)
```

Internal use, set int data

#### Parameters:

`intData` - int data

### getIntData

```
public int getIntData()
```

Internal use, get int data

(continued from last page)

**Returns:**

int data

---

**clearIntData**

```
public int clearIntData()
```

Internal use, get and clear int data

**Returns:**

int data

---

**getObjectEncoding**

```
public int getObjectEncoding()
```

Get object encoding, see AMFData.AMF\_LEVEL\*

**Returns:**

object encoding, see AMFData.AMF\_LEVEL\*

---

**setObjectEncoding**

```
public void setObjectEncoding(int objectEncoding)
```

Set object encoding, see AMFData.AMF\_LEVEL\*

**Parameters:**

objectEncoding - object encoding, see AMFData.AMF\_LEVEL\*

---

**isAMF3**

```
public boolean isAMF3()
```

Is context AMF3

**Returns:**

true, if AMF3

---

**isAMF0**

```
public boolean isAMF0()
```

Is context AMF0

**Returns:**

true, if AMF0

---

**addString**

```
public void addString(String str)
```

Add a string to the string cache

**Parameters:**

str - string value



## getString

```
public String getString(int index)  
    throws IndexOutOfBoundsException
```

Get a string from the string cache

**Parameters:**

index - index

**Returns:**

string value

**Throws:**

IndexOutOfBoundsException

---

## addObject

```
public void addObject(Object obj)
```

Add an object to the object cache

**Parameters:**

obj - object value

---

## getObject

```
public Object getObject(int index)  
    throws IndexOutOfBoundsException
```

Get an object from the object cache

**Parameters:**

index - index

**Returns:**

object value

**Throws:**

IndexOutOfBoundsException

---

## addTrait

```
public void addTrait(AMFDataTrait obj)
```

Add a trait to the trait cache

**Parameters:**

obj - trait object

---

## getTrait

```
public AMFDataTrait getTrait(int index)  
    throws IndexOutOfBoundsException
```

Get a trait from the trait cache

**Parameters:**

---

(continued from last page)

index - index

**Returns:**

trait object

**Throws:**

IndexOutOfBoundsException

## com.wowza.wms.amf

### Class AMFDataContextSerialize

java.lang.Object

└─com.wowza.wms.amf.AMFDataContextSerialize

public class **AMFDataContextSerialize**  
extends Object

AMF context used for serialization

#### Constructor Summary

public	<a href="#">AMFDataContextSerialize()</a> Constructor
public	<a href="#">AMFDataContextSerialize(int objectEncoding)</a> Constructor with object encoding, see AMFData.AMF_LEVEL*

#### Method Summary

int	<a href="#">getObjectEncoding()</a> Get object encoding, see AMFData.AMF_LEVEL*
int	<a href="#">getObjectReference(Object obj)</a> Get index of object in object cache
int	<a href="#">getStringReference(String str)</a> Get index of string item in string cache
int	<a href="#">getTargetEncoding()</a> Get target encoding, see AMFData.AMF_LEVEL*
int	<a href="#">getTraitReference(AMFDataTrait obj)</a> Get index of trait object in trait cache
boolean	<a href="#">isAMF0()</a> Is context AMF0
boolean	<a href="#">isAMF3()</a> Is context AMF3
void	<a href="#">setObjectEncoding(int objectEncoding)</a> Set object encoding, see AMFData.AMF_LEVEL*
void	<a href="#">setTargetEncoding(int targetEncoding)</a> Set target encoding, , see AMFData.AMF_LEVEL*
void	<a href="#">writeString(java.io.DataOutputStream out, String str)</a> Write a stream to the output buffer

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

## Constructors

### AMFDataContextSerialize

```
public AMFDataContextSerialize()
```

Constructor

### AMFDataContextSerialize

```
public AMFDataContextSerialize(int objectEncoding)
```

Constructor with object encoding, see AMFData.AMF\_LEVEL\*

**Parameters:**

objectEncoding - object encoding, see AMFData.AMF\_LEVEL\*

## Methods

### getObjectEncoding

```
public int getObjectEncoding()
```

Get object encoding, see AMFData.AMF\_LEVEL\*

**Returns:**

object encoding, see AMFData.AMF\_LEVEL\*

### setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

Set object encoding, see AMFData.AMF\_LEVEL\*

**Parameters:**

objectEncoding - object encoding, see AMFData.AMF\_LEVEL\*

### getTargetEncoding

```
public int getTargetEncoding()
```

Get target encoding, see AMFData.AMF\_LEVEL\*

**Returns:**

target encoding, see AMFData.AMF\_LEVEL\*

### setTargetEncoding

```
public void setTargetEncoding(int targetEncoding)
```

Set target encoding, , see AMFData.AMF\_LEVEL\*

(continued from last page)

**Parameters:**

targetEncoding - target encoding, , see AMFData.AMF\_LEVEL\*

---

**isAMF3**

```
public boolean isAMF3()
```

Is context AMF3

**Returns:**

true, if AMF3

---

**isAMF0**

```
public boolean isAMF0()
```

Is context AMF0

**Returns:**

true, if AMF0

---

**getStringReference**

```
public int getStringReference(String str)
```

Get index of string item in string cache

**Parameters:**

str - string value

**Returns:**

index

---

**getObjectReference**

```
public int getObjectReference(Object obj)
```

Get index of object in object cache

**Parameters:**

obj - object value

**Returns:**

index

---

**getTraitReference**

```
public int getTraitReference(AMFDataTrait obj)
```

Get index of trait object in trait cache

**Parameters:**

obj - trait object

**Returns:**

index

(continued from last page)

## **writeString**

```
public void writeString(java.io.DataOutputStream out,  
    String str)
```

Write a stream to the output buffer

### **Parameters:**

out - output buffer

str - string value

## com.wowza.wms.amf Class AMFDataItem

```
java.lang.Object
  |
  +--com.wowza.wms.amf.AMFData
        |
        +--com.wowza.wms.amf.AMFDataItem
```

```
public class AMFDataItem
extends AMFData
```

AMFDataItem: class for marshalling data between Wowza Pro server and Flash client. The type wraps native Java data types.

- DATA\_TYPE\_NUMBER = int, long, short, double, float
- DATA\_TYPE\_STRING = String
- DATA\_TYPE\_BOOLEAN = boolean
- DATA\_TYPE\_DATE = Date
- DATA\_TYPE\_NULL = 'null'

### Create Native Java Types

```
AMFDataItem amfDataString = new AMFDataItem("here is my string"); // String
AMFDataItem amfDataLong = new AMFDataItem(1234L); // long
AMFDataItem amfDataDouble = new AMFDataItem(1.234); // double
AMFDataItem amfDataBoolean = new AMFDataItem(true); // boolean
AMFDataItem amfDataNull = new AMFDataItem(); // null
```

### Get Native Java Types

```
String dataString = amfDataString.getType()==AMFData.DATA_TYPE_LONG_STRING?
    amfDataString.toString():"";

long dataLong = amfDataLong.getType()==AMFData.DATA_TYPE_NUMBER?
    amfDataLong.longValue():0;

double dataDouble = amfDataDouble.getType()==AMFData.DATA_TYPE_NUMBER?
    amfDataLong.doubleValue():0.0;

boolean dataBoolean = amfDataBoolean.getType()==AMFData.DATA_TYPE_BOOLEAN?
    amfDataLong.booleanValue():false;

Object dataNull = amfDataNull.getType()==AMFData.DATA_TYPE_NULL?
    null:null;
```

## Field Summary

public static final	<a href="#">DATEFORMAT</a> Value: <b>EEE, dd MMM yyyy HH:mm:ss</b>
protected	<a href="#">fastDateFormat</a>

### Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF\\_LEVEL0](#), [AMF\\_LEVEL3](#), [DATA\\_TYPE\\_AMF3](#), [DATA\\_TYPE\\_AMF3\\_ARRAY](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_FALSE](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_TRUE](#), [DATA\\_TYPE\\_AMF3\\_BYTEARRAY](#), [DATA\\_TYPE\\_AMF3\\_DATE](#), [DATA\\_TYPE\\_AMF3\\_INTEGER](#), [DATA\\_TYPE\\_AMF3\\_NULL](#), [DATA\\_TYPE\\_AMF3\\_NUMBER](#), [DATA\\_TYPE\\_AMF3\\_OBJECT](#), [DATA\\_TYPE\\_AMF3\\_STRING](#), [DATA\\_TYPE\\_AMF3\\_UNDEFINED](#), [DATA\\_TYPE\\_AMF3\\_XML\\_LEGACY](#), [DATA\\_TYPE\\_AMF3\\_XML\\_TOP](#), [DATA\\_TYPE\\_ARRAY](#), [DATA\\_TYPE\\_AS\\_OBJECT](#), [DATA\\_TYPE\\_BOOLEAN](#), [DATA\\_TYPE\\_BYTEARRAY](#), [DATA\\_TYPE\\_CUSTOM\\_CLASS](#), [DATA\\_TYPE\\_DATE](#), [DATA\\_TYPE\\_INTEGER](#), [DATA\\_TYPE\\_LONG\\_STRING](#), [DATA\\_TYPE\\_MIXED\\_ARRAY](#), [DATA\\_TYPE\\_MOVIE\\_CLIP](#), [DATA\\_TYPE\\_NULL](#), [DATA\\_TYPE\\_NUMBER](#), [DATA\\_TYPE\\_OBJECT](#), [DATA\\_TYPE\\_OBJECT\\_END](#), [DATA\\_TYPE\\_RECORDSET](#), [DATA\\_TYPE\\_REFERENCE\\_OBJECT](#), [DATA\\_TYPE\\_STRING](#), [DATA\\_TYPE\\_UNDEFINED](#), [DATA\\_TYPE\\_UNKNOWN](#), [DATA\\_TYPE\\_XML](#), [DATA\\_TYPE\\_XML\\_TOP](#), [MILLS\\_PER\\_HOUR](#), [type](#)

## Constructor Summary

public	<a href="#">AMFDataItem</a> () Construct AMF type DATA_TYPE_NULL object
public	<a href="#">AMFDataItem</a> (String value) Construct AMF type DATA_TYPE_STRING object
public	<a href="#">AMFDataItem</a> (int value) Construct AMF type DATA_TYPE_NUMBER object
public	<a href="#">AMFDataItem</a> (long value) Construct AMF type DATA_TYPE_NUMBER object
public	<a href="#">AMFDataItem</a> (double value) Construct AMF type DATA_TYPE_NUMBER object
public	<a href="#">AMFDataItem</a> (boolean value) Construct AMF type DATA_TYPE_BOOLEAN
public	<a href="#">AMFDataItem</a> (java.util.Date value) Construct AMF type DATA_TYPE_DATE
public	<a href="#">AMFDataItem</a> (byte[] data) Deserialize entire data array and create AMFDataItem object
public	<a href="#">AMFDataItem</a> (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataItem object
public	<a href="#">AMFDataItem</a> (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataItem object
public	<a href="#">AMFDataItem</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)



## Method Summary

boolean	<a href="#">booleanValue()</a> Return object as boolean.
byte	<a href="#">byteValue()</a> Return object as byte.
java.util.Date	<a href="#">dateValue()</a> Return object as Date.
void	<a href="#">deserialize()</a> (java.nio.ByteBuffer data)
void	<a href="#">deserialize()</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)
double	<a href="#">doubleValue()</a> Return object as double.
float	<a href="#">floatValue()</a> Return object as float.
Object	<a href="#">getValue()</a> Return value as Java class
int	<a href="#">intValue()</a> Return object as int.
long	<a href="#">longValue()</a> Return object as long.
byte[]	<a href="#">serialize()</a>
byte[]	<a href="#">serialize()</a> ( <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize()</a> (java.io.DataOutputStream out)
void	<a href="#">serialize()</a> (java.io.DataOutputStream out, <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize()</a> (java.io.DataOutputStream out, int objectEncoding)
byte[]	<a href="#">serialize()</a> (int objectEncoding)
short	<a href="#">shortValue()</a> Return object as short.
String	<a href="#">toString()</a> Return object as formatted string

Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Fields

### DATEFORMAT

`public static final java.lang.String DATEFORMAT`

Constant value: **EEE, dd MMM yyyy HH:mm:ss**

### fastDateFormat

`protected org.apache.commons.lang.time.FastDateFormat fastDateFormat`

## Constructors

### AMFDataItem

`public AMFDataItem()`

Construct AMF type DATA\_TYPE\_NULL object

### AMFDataItem

`public AMFDataItem(String value)`

Construct AMF type DATA\_TYPE\_STRING object

#### Parameters:

value - String value

### AMFDataItem

`public AMFDataItem(int value)`

Construct AMF type DATA\_TYPE\_NUMBER object

#### Parameters:

value - int value

### AMFDataItem

`public AMFDataItem(long value)`

(continued from last page)

Construct AMF type DATA\_TYPE\_NUMBER object

**Parameters:**

value - long value

---

## AMFDataItem

```
public AMFDataItem(double value)
```

Construct AMF type DATA\_TYPE\_NUMBER object

**Parameters:**

value - double value

---

## AMFDataItem

```
public AMFDataItem(boolean value)
```

Construct AMF type DATA\_TYPE\_BOOLEAN

**Parameters:**

value - boolean value

---

## AMFDataItem

```
public AMFDataItem(java.util.Date value)
```

Construct AMF type DATA\_TYPE\_DATE

**Parameters:**

value - Date value

---

## AMFDataItem

```
public AMFDataItem(byte[] data)
```

Deserialize entire data array and create AMFDataItem object

**Parameters:**

data - binary data

---

## AMFDataItem

```
public AMFDataItem(byte[] data,  
                   int offset,  
                   int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataItem object

**Parameters:**

data - binary data

offset - starting offset into data

size - size of data to deserialize

---

## AMFDataItem

```
public AMFDataItem(java.nio.ByteBuffer data)
```

(continued from last page)

Deserialize entire data array and create AMFDataItem object

**Parameters:**

data - binary data

---

## AMFDataItem

```
public AMFDataItem(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

## Methods

### longValue

```
public long longValue()
```

Return object as long. Valid object types are DATA\_TYPE\_NUMBER and DATA\_TYPE\_STRING.

**Returns:**

long value or 0 if failure

---

### intValue

```
public int intValue()
```

Return object as int. Valid object types are DATA\_TYPE\_NUMBER and DATA\_TYPE\_STRING.

**Returns:**

int value or 0 if failure

---

### doubleValue

```
public double doubleValue()
```

Return object as double. Valid object types are DATA\_TYPE\_NUMBER and DATA\_TYPE\_STRING.

**Returns:**

double value or 0 if failure

---

### floatValue

```
public float floatValue()
```

Return object as float. Valid object types are DATA\_TYPE\_NUMBER and DATA\_TYPE\_STRING.

**Returns:**

float value or 0 if failure

---

### shortValue

```
public short shortValue()
```

Return object as short. Valid object types are DATA\_TYPE\_NUMBER and DATA\_TYPE\_STRING.

**Returns:**

short value or 0 if failure

## byteValue

```
public byte byteValue()
```

Return object as byte. Valid object types are DATA\_TYPE\_NUMBER and DATA\_TYPE\_STRING.

**Returns:**

byte value or 0 if failure

---

## dateValue

```
public java.util.Date dateValue()
```

Return object as Date. Valid object types are DATA\_TYPE\_DATE.

**Returns:**

Date value or null if failure

---

## booleanValue

```
public boolean booleanValue()
```

Return object as boolean. Valid object types are DATA\_TYPE\_BOOLEAN and DATA\_TYPE\_STRING.

**Returns:**

boolean value or false if failure

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

---

## getValue

```
public Object getValue()
```

Return value as Java class

---

## toString

```
public String toString()
```

Return object as formatted string

---

## serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

---

**serialize**

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

---

**serialize**

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

---

**serialize**

```
public byte[] serialize()
```

Serial object to byte array

---

**serialize**

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

---

**serialize**

```
public byte[] serialize(AMFDataContextSerialize context)
```


Serial object to byte array

---

## com.wowza.wms.amf

### Class AMFDataList

java.lang.Object



public class **AMFDataList**  
 extends [AMFData](#)

AMFDataItem: class for marshalling data between Wowza Pro server and Flash client. This class is for internal server marshalling of AMF event messages between the Flash client and Wowza Pro server.

**NOTE:** There is a slight difference between this class and AMFDataArray. This class when serialized/deserialized does NOT include the DATA\_TYPE\_ARRAY header (byte) and array size (int). AMF formatted functions use this class since they do not include these elements.

#### Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF\\_LEVEL0](#), [AMF\\_LEVEL3](#), [DATA\\_TYPE\\_AMF3](#), [DATA\\_TYPE\\_AMF3\\_ARRAY](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_FALSE](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_TRUE](#), [DATA\\_TYPE\\_AMF3\\_BYTEARRAY](#), [DATA\\_TYPE\\_AMF3\\_DATE](#), [DATA\\_TYPE\\_AMF3\\_INTEGER](#), [DATA\\_TYPE\\_AMF3\\_NULL](#), [DATA\\_TYPE\\_AMF3\\_NUMBER](#), [DATA\\_TYPE\\_AMF3\\_OBJECT](#), [DATA\\_TYPE\\_AMF3\\_STRING](#), [DATA\\_TYPE\\_AMF3\\_UNDEFINED](#), [DATA\\_TYPE\\_AMF3\\_XML\\_LEGACY](#), [DATA\\_TYPE\\_AMF3\\_XML\\_TOP](#), [DATA\\_TYPE\\_ARRAY](#), [DATA\\_TYPE\\_AS\\_OBJECT](#), [DATA\\_TYPE\\_BOOLEAN](#), [DATA\\_TYPE\\_BYTEARRAY](#), [DATA\\_TYPE\\_CUSTOM\\_CLASS](#), [DATA\\_TYPE\\_DATE](#), [DATA\\_TYPE\\_INTEGER](#), [DATA\\_TYPE\\_LONG\\_STRING](#), [DATA\\_TYPE\\_MIXED\\_ARRAY](#), [DATA\\_TYPE\\_MOVIE\\_CLIP](#), [DATA\\_TYPE\\_NULL](#), [DATA\\_TYPE\\_NUMBER](#), [DATA\\_TYPE\\_OBJECT](#), [DATA\\_TYPE\\_OBJECT\\_END](#), [DATA\\_TYPE\\_RECORDSET](#), [DATA\\_TYPE\\_REFERENCE\\_OBJECT](#), [DATA\\_TYPE\\_STRING](#), [DATA\\_TYPE\\_UNDEFINED](#), [DATA\\_TYPE\\_UNKNOWN](#), [DATA\\_TYPE\\_XML](#), [DATA\\_TYPE\\_XML\\_TOP](#), [MILLS\\_PER\\_HOUR](#), [type](#)

### Constructor Summary

public	<a href="#">AMFDataList</a> () Create empty AMFDataList object
public	<a href="#">AMFDataList</a> (byte[] data) Deserialize entire data array and create AMFDataList object
public	<a href="#">AMFDataList</a> (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataList object
public	<a href="#">AMFDataList</a> (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataList object
public	<a href="#">AMFDataList</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)

### Method Summary

void	<a href="#">add</a> ( <a href="#">AMFData</a> data) Append a new item onto the array
------	---

void	<a href="#">add</a> (boolean data) Append a boolean (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (java.util.Date data) Append a date (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (double data) Append a double (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int data) Append a int (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, <a href="#">AMFData</a> data) Insert an item into the array
void	<a href="#">add</a> (int index, boolean data) Insert a boolean value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, java.util.Date data) Insert a date value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, double data) Insert a double value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, int data) Insert a int value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, long data) Insert a long value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (int index, String data) Insert a string value (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (long data) Append a long (will be wrapped in an AMFDataItem object)
void	<a href="#">add</a> (String data) Append a string (will be wrapped in an AMFDataItem object)
void	<a href="#">deserialize</a> (java.nio.ByteBuffer data)
void	<a href="#">deserialize</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)
<a href="#">AMFData</a>	<a href="#">get</a> (int index) Get item at index
boolean	<a href="#">getBoolean</a> (int index) Get item at index return as boolean
byte	<a href="#">getBytes</a> (int index) Get item at index return as byte
java.util.Date	<a href="#">getDate</a> (int index) Get item at index return as Date
double	<a href="#">getDouble</a> (int index) Get item at index return as double



float	<a href="#"><code>getFloat(int index)</code></a> Get item at index return as float
int	<a href="#"><code>getInt(int index)</code></a> Get item at index return as int
long	<a href="#"><code>getLong(int index)</code></a> Get item at index return as long
<a href="#"><code>AMFDataObj</code></a>	<a href="#"><code>getObject(int index)</code></a> Get item at index return as AMFDataObj
short	<a href="#"><code>getShort(int index)</code></a> Get item at index return as short
String	<a href="#"><code>getString(int index)</code></a> Get item at index return as String
int	<a href="#"><code>getType(int index)</code></a> Get type of item at index.
Object	<a href="#"><code>getValue()</code></a>
<a href="#"><code>AMFData</code></a>	<a href="#"><code>remove(int index)</code></a> Remove an element from the AMFDataList object
byte[]	<a href="#"><code>serialize()</code></a>
byte[]	<a href="#"><code>serialize(AMFDataContextSerialize context)</code></a>
byte[]	<a href="#"><code>serialize(AMFDataContextSerialize context, byte[] prepend)</code></a>
void	<a href="#"><code>serialize(java.io.DataOutputStream out)</code></a>
void	<a href="#"><code>serialize(java.io.DataOutputStream out, AMFDataContextSerialize context)</code></a>
void	<a href="#"><code>serialize(java.io.DataOutputStream out, AMFDataContextSerialize context, byte[] prepend)</code></a>
void	<a href="#"><code>serialize(java.io.DataOutputStream out, int objectEncoding)</code></a>
byte[]	<a href="#"><code>serialize(int objectEncoding)</code></a>
void	<a href="#"><code>set(int index, AMFData data)</code></a> Set an array item
void	<a href="#"><code>set(int index, boolean data)</code></a> Set an boolean value (will be wrapped in an AMFDataItem object)
void	<a href="#"><code>set(int index, java.util.Date data)</code></a> Set an date value (will be wrapped in an AMFDataItem object)
void	<a href="#"><code>set(int index, double data)</code></a> Set an double value (will be wrapped in an AMFDataItem object)

void	<a href="#"><u>set</u></a> (int index, int data) Set an int value (will be wrapped in an AMFDataItem object)
void	<a href="#"><u>set</u></a> (int index, long data) Set an long value (will be wrapped in an AMFDataItem object)
void	<a href="#"><u>set</u></a> (int index, String data) Set an string value (will be wrapped in an AMFDataItem object)
int	<a href="#"><u>size</u></a> () Returns the number of items in array
String	<a href="#"><u>toString</u></a> () Return object as formatted string

#### Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

#### Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

## Constructors

### AMFDataList

```
public AMFDataList()
```

Create empty AMFDataList object

### AMFDataList

```
public AMFDataList(byte[] data)
```

Deserialize entire data array and create AMFDataList object

#### Parameters:

data - binary data

### AMFDataList

```
public AMFDataList(byte[] data,  
                   int offset,  
                   int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataList object

#### Parameters:

data - binary data

offset - starting offset into data

(continued from last page)

size - size of data to deserialize

---

## AMFDataList

```
public AMFDataList(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataList object

**Parameters:**

data - binary data

---

## AMFDataList

```
public AMFDataList(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

## Methods

### remove

```
public AMFData remove(int index)
```

Remove an element from the AMFDataList object

**Parameters:**

index - index

**Returns:**

removed element

---

### size

```
public int size()
```

Returns the number of items in array

**Returns:**

number of items in array

---

### add

```
public void add(AMFData data)
```

Append a new item onto the array

**Parameters:**

data - AMFData object

---

### add

```
public void add(String data)
```

Append a string (will be wrapped in an AMFDataItem object)

**Parameters:**

data - string value

---

## add

```
public void add(double data)
```

Append a double (will be wrapped in an AMFDataItem object)

**Parameters:**

data - double value

---

## add

```
public void add(int data)
```

Append a int (will be wrapped in an AMFDataItem object)

**Parameters:**

data - int value

---

## add

```
public void add(long data)
```

Append a long (will be wrapped in an AMFDataItem object)

**Parameters:**

data - long value

---

## add

```
public void add(java.util.Date data)
```

Append a date (will be wrapped in an AMFDataItem object)

**Parameters:**

data - date value

---

## add

```
public void add(boolean data)
```

Append a boolean (will be wrapped in an AMFDataItem object)

**Parameters:**

data - boolean value

---

## add

```
public void add(int index,  
    AMFData data)
```

Insert an item into the array

**Parameters:**

index - index

data - AMFData object

---

(continued from last page)

---

## add

```
public void add(int index,  
                String data)
```

Insert a string value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - string value

---

## add

```
public void add(int index,  
                double data)
```

Insert a double value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - double value

---

## add

```
public void add(int index,  
                int data)
```

Insert a int value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - int value

---

## add

```
public void add(int index,  
                long data)
```

Insert a long value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - long value

---

## add

```
public void add(int index,  
                java.util.Date data)
```

Insert a date value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - date value

---

## add

```
public void add(int index,  
                boolean data)
```

---

(continued from last page)

Insert a boolean value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - boolean value

---

**set**

```
public void set(int index,  
    AMFData data)
```

Set an array item

**Parameters:**

data - AMFData object

---

**set**

```
public void set(int index,  
    String data)
```

Set an string value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - string value

---

**set**

```
public void set(int index,  
    double data)
```

Set an double value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - double value

---

**set**

```
public void set(int index,  
    int data)
```

Set an int value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - int value

---

**set**

```
public void set(int index,  
    long data)
```

Set an long value (will be wrapped in an AMFDataItem object)

**Parameters:**

index - index  
data - long value

## set

```
public void set(int index,  
               java.util.Date data)
```

Set an date value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - date value

---

## set

```
public void set(int index,  
               boolean data)
```

Set an boolean value (will be wrapped in an AMFDataItem object)

### Parameters:

index - index  
data - boolean value

---

## getType

```
public int getType(int index)
```

Get type of item at index. Return AMFData.DATA\_TYPE\_UNKNOWN if item does not exist

### Parameters:

index

### Returns:

type of item at index

---

## get

```
public AMFData get(int index)
```

Get item at index

### Parameters:

index

### Returns:

Returns AMFData object or null if out of bounds

---

## getString

```
public String getString(int index)
```

Get item at index return as String

### Parameters:

index

### Returns:

Return item as String or null if out of bounds

---

---

## getInt

```
public int getInt(int index)
```

Get item at index return as int

**Parameters:**

index

**Returns:**

Return item as int or 0 if out of bounds

---

## getLong

```
public long getLong(int index)
```

Get item at index return as long

**Parameters:**

index

**Returns:**

Return item as long or 0 if out of bounds

---

## getDouble

```
public double getDouble(int index)
```

Get item at index return as double

**Parameters:**

index

**Returns:**

Return item as double or 0 if out of bounds

---

## getFloat

```
public float getFloat(int index)
```

Get item at index return as float

**Parameters:**

index

**Returns:**

Return item as float or 0 if out of bounds

---

## getShort

```
public short getShort(int index)
```

Get item at index return as short

**Parameters:**

index

---



(continued from last page)

**Returns:**

Return item as short or 0 if out of bounds

---

## getBytes

```
public byte getBytes(int index)
```

Get item at index return as byte

**Parameters:**

index

**Returns:**

Return item as byte or 0 if out of bounds

---

## getBoolean

```
public boolean getBoolean(int index)
```

Get item at index return as boolean

**Parameters:**

index

**Returns:**

Return item as boolean or false if out of bounds

---

## getDate

```
public java.util.Date getDate(int index)
```

Get item at index return as Date

**Parameters:**

index

**Returns:**

Return item as Date or null if out of bounds

---

## getObject

```
public AMFDataObj getObject(int index)
```

Get item at index return as AMFDataObj

**Parameters:**

index

**Returns:**

Return item as AMFDataObj or null if out of bounds

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

(continued from last page)

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

---

## serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context,  
    byte[] prepend)
```

---

## serialize

```
public byte[] serialize()
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(AMFDataContextSerialize context,  
    byte[] prepend)
```

---

## getValue

public Object **getValue()**

Convert object to Java native class

---

## toString

public String **toString()**

Return object as formatted string

## com.wowza.wms.amf

### Class AMFDataMixedArray

```

java.lang.Object
├── com.wowza.wms.amf.AMFData
│   ├── com.wowza.wms.amf.AMFDataObj
│   └── com.wowza.wms.amf.AMFDataMixedArray

```

All Implemented Interfaces:

[IAMFDataObj](#)

```

public class AMFDataMixedArray
extends AMFDataObj

```

AMFDataMixedArray: class for marshalling data between Wowza Pro server and Flash client. Array of mixed data types. An Array object created in the Flash client is wrapped in this data type when sent to the Wowza Pro server.

### Create Array of Strings

```

AMFDataMixedArray amfDataMixedArray = new AMFDataMixedArray();

amfDataMixedArray.put("0", "item1");
amfDataMixedArray.put("1", "item2");
amfDataMixedArray.put("2", "item3");

```

### Iterate Mixed Array

```

AMFDataMixedArray amfDataMixedArray;

int len = amfDataMixedArray.size();
for(int i=0;i<len;i++)
{
    String value = amfDataMixedArray.getString(i);
    int itemType = amfDataMixedArray.getType(i);
    WMSLoggerFactory.getLogger(null).debug("item:
["+i+": "+amfDataMixedArray.getKey(i)+"]="+value+" type:"+itemType);
}

```

**NOTE:** A AMFDataMixedArray is exactly the same as a AMFDataObj except its type is DATA\_TYPE\_MIXED\_ARRAY.

This objects acts like a Map and a List at the same time. As items are added by key the order and position of each object is recorded. Objects can be retrieved either by key or by index.

#### Fields inherited from class [com.wowza.wms.amf.AMFDataObj](#)

[DECODE\\_OBJ\\_REF](#), [DECODE\\_TRAITS](#), [DECODE\\_TRAITS\\_EXT](#), [DECODE\\_TRAITS\\_REF](#), [DECODE\\_UNDEFINED](#), [members](#), [order](#), [trait](#)

#### Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF\\_LEVEL0](#), [AMF\\_LEVEL3](#), [DATA\\_TYPE\\_AMF3](#), [DATA\\_TYPE\\_AMF3\\_ARRAY](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_FALSE](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_TRUE](#), [DATA\\_TYPE\\_AMF3\\_BYTEARRAY](#), [DATA\\_TYPE\\_AMF3\\_DATE](#), [DATA\\_TYPE\\_AMF3\\_INTEGER](#), [DATA\\_TYPE\\_AMF3\\_NULL](#), [DATA\\_TYPE\\_AMF3\\_NUMBER](#), [DATA\\_TYPE\\_AMF3\\_OBJECT](#), [DATA\\_TYPE\\_AMF3\\_STRING](#), [DATA\\_TYPE\\_AMF3\\_UNDEFINED](#), [DATA\\_TYPE\\_AMF3\\_XML\\_LEGACY](#), [DATA\\_TYPE\\_AMF3\\_XML\\_TOP](#), [DATA\\_TYPE\\_ARRAY](#), [DATA\\_TYPE\\_AS\\_OBJECT](#), [DATA\\_TYPE\\_BOOLEAN](#), [DATA\\_TYPE\\_BYTEARRAY](#), [DATA\\_TYPE\\_CUSTOM\\_CLASS](#), [DATA\\_TYPE\\_DATE](#), [DATA\\_TYPE\\_INTEGER](#), [DATA\\_TYPE\\_LONG\\_STRING](#), [DATA\\_TYPE\\_MIXED\\_ARRAY](#), [DATA\\_TYPE\\_MOVIE\\_CLIP](#), [DATA\\_TYPE\\_NULL](#), [DATA\\_TYPE\\_NUMBER](#), [DATA\\_TYPE\\_OBJECT](#), [DATA\\_TYPE\\_OBJECT\\_END](#), [DATA\\_TYPE\\_RECORDSET](#), [DATA\\_TYPE\\_REFERENCE\\_OBJECT](#), [DATA\\_TYPE\\_STRING](#), [DATA\\_TYPE\\_UNDEFINED](#), [DATA\\_TYPE\\_UNKNOWN](#), [DATA\\_TYPE\\_XML](#), [DATA\\_TYPE\\_XML\\_TOP](#), [MILLS\\_PER\\_HOUR](#), [type](#)

## Constructor Summary

public	<a href="#">AMFDataMixedArray()</a> Create empty AMFDataMixedArray object
public	<a href="#">AMFDataMixedArray</a> (byte[] data) Deserialize entire data array and create AMFDataMixedArray object
public	<a href="#">AMFDataMixedArray</a> (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataMixedArray object
public	<a href="#">AMFDataMixedArray</a> (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataMixedArray object
public	<a href="#">AMFDataMixedArray</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)

## Method Summary

void	<a href="#">deserialize</a> (java.nio.ByteBuffer data)
void	<a href="#">deserialize</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)
void	<a href="#">serialize</a> (java.io.DataOutputStream out)
void	<a href="#">serialize</a> (java.io.DataOutputStream out, <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize</a> (java.io.DataOutputStream out, int objectEncoding)
String	<a href="#">toString</a> () Return object as formatted string

**Methods inherited from class** [com.wowza.wms.amf.AMFDataObj](#)

[containsKey](#), [deserialize](#), [deserialize](#), [get](#), [get](#), [getBoolean](#), [getBoolean](#), [getBytes](#), [getBytes](#), [getClassName](#), [getDate](#), [getDate](#), [getDouble](#), [getDouble](#), [getFloat](#), [getFloat](#), [getInt](#), [getInt](#), [getKey](#), [getKeys](#), [getLong](#), [getLong](#), [getObject](#), [getObject](#), [getShort](#), [getShort](#), [getString](#), [getString](#), [getTrait](#), [getValue](#), [put](#), [put](#), [put](#), [put](#), [put](#), [put](#), [put](#), [remove](#), [remove](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setClassName](#), [size](#), [toString](#)

**Methods inherited from class** [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

**Methods inherited from class** [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

**Methods inherited from interface** [com.wowza.wms.amf.IAMFDataObj](#)

[containsKey](#), [get](#), [get](#), [getBoolean](#), [getBoolean](#), [getBytes](#), [getBytes](#), [getDate](#), [getDate](#), [getDouble](#), [getDouble](#), [getFloat](#), [getFloat](#), [getInt](#), [getInt](#), [getKey](#), [getKeys](#), [getLong](#), [getLong](#), [getObject](#), [getObject](#), [getShort](#), [getShort](#), [getString](#), [getString](#), [put](#), [put](#), [put](#), [put](#), [put](#), [put](#), [remove](#), [remove](#)

## Constructors

### AMFDataMixedArray

```
public AMFDataMixedArray()
```

Create empty AMFDataMixedArray object

### AMFDataMixedArray

```
public AMFDataMixedArray(byte[] data)
```

Deserialize entire data array and create AMFDataMixedArray object

**Parameters:**

data - binary data

### AMFDataMixedArray

```
public AMFDataMixedArray(byte[] data,  
                           int offset,  
                           int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataMixedArray object

**Parameters:**

data - binary data

(continued from last page)

offset - starting offset into data  
size - size of data to deserialize

---

## AMFDataMixedArray

```
public AMFDataMixedArray( java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataMixedArray object

### Parameters:

data - binary data

---

## AMFDataMixedArray

```
public AMFDataMixedArray( java.nio.ByteBuffer data,  
                           AMFDataContextDeserialize context)
```

---

## Methods

### deserialize

```
public void deserialize( java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

---

### deserialize

```
public void deserialize( java.nio.ByteBuffer data,  
                           AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

---

### serialize

```
public void serialize( java.io.DataOutputStream out)
```

Serialize object to output stream

---

### serialize

```
public void serialize( java.io.DataOutputStream out,  
                       int objectEncoding)
```

Serialize object to output stream

---

### serialize

```
public void serialize( java.io.DataOutputStream out,  
                           AMFDataContextSerialize context)
```

Serialize object to output stream

---

### toString

```
public String toString()
```

Return object as formatted string

---

## com.wowza.wms.amf

### Class AMFDataObj

```
java.lang.Object
|
+- com.wowza.wms.amf.AMFData
   |
   +- com.wowza.wms.amf.AMFDataObj
```

All Implemented Interfaces:

[IAMFDataObj](#)

Direct Known Subclasses:

[AMFDataMixedArray](#)

```
public class AMFDataObj
extends AMFData
implements IAMFDataObj
```

AMFDataObj: class for marshalling data between Wowza Pro server and Flash client. Object with attributes. Implementation is very similar to a java.util.Map. Each parameter is an item in the map.

### Create AMFDataObj

```
AMFDataObj amfDataObj = new AMFDataObj();

amfDataObj.put("key1", "item1");
amfDataObj.put("key2", "item2");
amfDataObj.put("key3", "item3");
```

### Iterate AMFDataObj

```
AMFDataObj amfDataObj;

List keys = amfDataObj.getKeys();
Iterator iter = keys.iterator();
while(iter.hasNext())
{
    String key = (String)iter.next();
    AMFData value = amfDataObj.get(key);
    int itemType = value.getType();
    WMSLoggerFactory.getLogger(null).debug(key+"="+value.toString()+"
(type:"+itemType+")");
}
```



## Direct Access To Attributes

```

AMFDataObj amfDataObj;

// If you know the type you can access it directly
String dataString = amfDataObj.getString("stringData");
long dataLong = amfDataObj.getLong("longData");
double dataDouble = amfDataObj.getDouble("doubleData");
boolean dataBoolean = amfDataObj.getBoolean("booleanData");

// This illustrate how to decode the value if
// you don't know the type
AMFData myItemKey1 = amfDataObj.get("theData");
switch (myItemKey1.getType())
{
default:
case AMFDataItem.DATA_TYPE_UNDEFINED:
case AMFDataItem.DATA_TYPE_UNKNOWN:
case AMFDataItem.DATA_TYPE_NULL:
    // the value is null or undefined
    break;
case AMFDataItem.DATA_TYPE_NUMBER:
    double amfDataDouble = ((AMFDataItem)myItemKey1).doubleValue();
    break;
case AMFDataItem.DATA_TYPE_BOOLEAN:
    boolean amfDataBoolean = ((AMFDataItem)myItemKey1).booleanValue();
    break;
case AMFDataItem.DATA_TYPE_STRING:
    String amfDataString = ((AMFDataItem)myItemKey1).toString();
    break;
case AMFDataItem.DATA_TYPE_DATE:
    Date amfDataDate = ((AMFDataItem)myItemKey1).dateValue();
    break;
case AMFDataItem.DATA_TYPE_OBJECT:
    AMFDataObj amfDataValObj = (AMFDataObj)myItemKey1;
    break;
case AMFDataItem.DATA_TYPE_MIXED_ARRAY:
    AMFDataMixedArray amfDataMixedArray = (AMFDataMixedArray)myItemKey1;
    break;
case AMFDataItem.DATA_TYPE_ARRAY:
    AMFDataArray amfDataArray = (AMFDataArray)myItemKey1;
    break;
}

```

**NOTE:** A AMFDataObj is exactly the same as a AMFDataMixedArray except its type is DATA\_TYPE\_OBJECT.

## Field Summary

public static final	<a href="#">DECODE_OBJ_REF</a> Value: <b>1</b>
public static final	<a href="#">DECODE_TRAITS</a> Value: <b>4</b>
public static final	<a href="#">DECODE_TRAITS_EXT</a> Value: <b>3</b>
public static final	<a href="#">DECODE_TRAITS_REF</a> Value: <b>2</b>
public static final	<a href="#">DECODE_UNDEFINED</a> Value: <b>0</b>
protected	<a href="#">members</a>
protected	<a href="#">order</a>
protected	<a href="#">trait</a>

### Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF\\_LEVEL0](#), [AMF\\_LEVEL3](#), [DATA\\_TYPE\\_AMF3](#), [DATA\\_TYPE\\_AMF3\\_ARRAY](#), [DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_FALSE](#),  
[DATA\\_TYPE\\_AMF3\\_BOOLEAN\\_TRUE](#), [DATA\\_TYPE\\_AMF3\\_BYTEARRAY](#), [DATA\\_TYPE\\_AMF3\\_DATE](#),  
[DATA\\_TYPE\\_AMF3\\_INTEGER](#), [DATA\\_TYPE\\_AMF3\\_NULL](#), [DATA\\_TYPE\\_AMF3\\_NUMBER](#), [DATA\\_TYPE\\_AMF3\\_OBJECT](#),  
[DATA\\_TYPE\\_AMF3\\_STRING](#), [DATA\\_TYPE\\_AMF3\\_UNDEFINED](#), [DATA\\_TYPE\\_AMF3\\_XML\\_LEGACY](#),  
[DATA\\_TYPE\\_AMF3\\_XML\\_TOP](#), [DATA\\_TYPE\\_ARRAY](#), [DATA\\_TYPE\\_AS\\_OBJECT](#), [DATA\\_TYPE\\_BOOLEAN](#),  
[DATA\\_TYPE\\_BYTEARRAY](#), [DATA\\_TYPE\\_CUSTOM\\_CLASS](#), [DATA\\_TYPE\\_DATE](#), [DATA\\_TYPE\\_INTEGER](#),  
[DATA\\_TYPE\\_LONG\\_STRING](#), [DATA\\_TYPE\\_MIXED\\_ARRAY](#), [DATA\\_TYPE\\_MOVIE\\_CLIP](#), [DATA\\_TYPE\\_NULL](#),  
[DATA\\_TYPE\\_NUMBER](#), [DATA\\_TYPE\\_OBJECT](#), [DATA\\_TYPE\\_OBJECT\\_END](#), [DATA\\_TYPE\\_RECORDSET](#),  
[DATA\\_TYPE\\_REFERENCE\\_OBJECT](#), [DATA\\_TYPE\\_STRING](#), [DATA\\_TYPE\\_UNDEFINED](#), [DATA\\_TYPE\\_UNKNOWN](#),  
[DATA\\_TYPE\\_XML](#), [DATA\\_TYPE\\_XML\\_TOP](#), [MILLS\\_PER\\_HOUR](#), [type](#)

## Constructor Summary

public	<a href="#">AMFDataObj</a> () Create empty AMFDataObj object
public	<a href="#">AMFDataObj</a> (byte[] data) Deserialize entire data array and create AMFDataObj object
public	<a href="#">AMFDataObj</a> (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataObj object
public	<a href="#">AMFDataObj</a> (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataObj object
public	<a href="#">AMFDataObj</a> (java.nio.ByteBuffer data, <a href="#">AMFDataContextDeserialize</a> context)

## Method Summary

boolean	<a href="#"><u>containsKey</u></a> (String name)
void	<a href="#"><u>deserialize</u></a> (java.nio.ByteBuffer data)
void	<a href="#"><u>deserialize</u></a> (java.nio.ByteBuffer data, <a href="#"><u>AMFDataContextDeserialize</u></a> context)
<a href="#"><u>AMFData</u></a>	<a href="#"><u>get</u></a> (int index)
<a href="#"><u>AMFData</u></a>	<a href="#"><u>get</u></a> (String name)
boolean	<a href="#"><u>getBoolean</u></a> (int index)
boolean	<a href="#"><u>getBoolean</u></a> (String name)
byte	<a href="#"><u>getBytes</u></a> (int index)
byte	<a href="#"><u>getBytes</u></a> (String name)
String	<a href="#"><u>getClassName</u></a> ()
java.util.Date	<a href="#"><u>getDate</u></a> (int index)
java.util.Date	<a href="#"><u>getDate</u></a> (String name)
double	<a href="#"><u>getDouble</u></a> (int index)
double	<a href="#"><u>getDouble</u></a> (String name)
float	<a href="#"><u>getFloat</u></a> (int index)
float	<a href="#"><u>getFloat</u></a> (String name)
int	<a href="#"><u>getInt</u></a> (int index)
int	<a href="#"><u>getInt</u></a> (String name)
String	<a href="#"><u>getKey</u></a> (int index)
java.util.List	<a href="#"><u>getKeys</u></a> ()
long	<a href="#"><u>getLong</u></a> (int index)
long	<a href="#"><u>getLong</u></a> (String name)
<a href="#"><u>AMFDataObj</u></a>	<a href="#"><u>getObject</u></a> (int index)

<a href="#">AMFDataObj</a>	<a href="#">getObject</a> (String name)
short	<a href="#">getShort</a> (int index)
short	<a href="#">getShort</a> (String name)
String	<a href="#">getString</a> (int index)
String	<a href="#">getString</a> (String name)
<a href="#">AMFDataTrait</a>	<a href="#">getTrait</a> ()
Object	<a href="#">getValue</a> ()
void	<a href="#">put</a> (String name, <a href="#">AMFData</a> data)
void	<a href="#">put</a> (String name, boolean data)
void	<a href="#">put</a> (String name, java.util.Date data)
void	<a href="#">put</a> (String name, double data)
void	<a href="#">put</a> (String name, int data)
void	<a href="#">put</a> (String name, long data)
void	<a href="#">put</a> (String name, String data)
<a href="#">AMFData</a>	<a href="#">remove</a> (int index)
<a href="#">AMFData</a>	<a href="#">remove</a> (String name)
byte[]	<a href="#">serialize</a> ()
byte[]	<a href="#">serialize</a> ( <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize</a> (java.io.DataOutputStream out)
void	<a href="#">serialize</a> (java.io.DataOutputStream out, <a href="#">AMFDataContextSerialize</a> context)
void	<a href="#">serialize</a> (java.io.DataOutputStream out, int objectEncoding)
byte[]	<a href="#">serialize</a> (int objectEncoding)
void	<a href="#">setClassName</a> (String className)
int	<a href="#">size</a> () Return the number of members of this object/array

String	<a href="#">toString()</a> Return object as formatted string
--------	---

Methods inherited from class <a href="#">com.wowza.wms.amf.AMFData</a>
<a href="#">createContextDeserialize</a> , <a href="#">createContextDeserialize</a> , <a href="#">createContextSerialize</a> , <a href="#">createContextSerialize</a> , <a href="#">deserialize</a> , <a href="#">deserialize</a> , <a href="#">deserializeInnerObject</a> , <a href="#">getReference</a> , <a href="#">getType</a> , <a href="#">getValue</a> , <a href="#">isAMF3Start</a> , <a href="#">isArrayStart</a> , <a href="#">isByteArrayStart</a> , <a href="#">isMixedArrayStart</a> , <a href="#">isObjEnd</a> , <a href="#">isObjStart</a> , <a href="#">peekByte</a> , <a href="#">serialize</a> , <a href="#">serialize</a> , <a href="#">serialize</a> , <a href="#">serialize</a> , <a href="#">serialize</a> , <a href="#">setType</a> , <a href="#">skipByte</a> , <a href="#">testNextByte</a> , <a href="#">triggerAMF3Switch</a>

Methods inherited from class java.lang.Object
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface <a href="#">com.wowza.wms.amf.IAMFDataObj</a>
<a href="#">containsKey</a> , <a href="#">get</a> , <a href="#">get</a> , <a href="#">getBoolean</a> , <a href="#">getBoolean</a> , <a href="#">getBytes</a> , <a href="#">getBytes</a> , <a href="#">getDate</a> , <a href="#">getDate</a> , <a href="#">getDouble</a> , <a href="#">getDouble</a> , <a href="#">getFloat</a> , <a href="#">getFloat</a> , <a href="#">getInt</a> , <a href="#">getInt</a> , <a href="#">getKey</a> , <a href="#">getKeys</a> , <a href="#">getLong</a> , <a href="#">getLong</a> , <a href="#">getObject</a> , <a href="#">getObject</a> , <a href="#">getShort</a> , <a href="#">getShort</a> , <a href="#">getString</a> , <a href="#">getString</a> , <a href="#">put</a> , <a href="#">put</a> , <a href="#">put</a> , <a href="#">put</a> , <a href="#">put</a> , <a href="#">put</a> , <a href="#">remove</a> , <a href="#">remove</a>

## Fields

### DECODE\_UNDEFINED

public static final int **DECODE\_UNDEFINED**

Constant value: 0

### DECODE\_OBJ\_REF

public static final int **DECODE\_OBJ\_REF**

Constant value: 1

### DECODE\_TRAITS\_REF

public static final int **DECODE\_TRAITS\_REF**

Constant value: 2

### DECODE\_TRAITS\_EXT

public static final int **DECODE\_TRAITS\_EXT**

Constant value: 3

### DECODE\_TRAITS

public static final int **DECODE\_TRAITS**

(continued from last page)

Constant value: **4**

---

## members

protected java.util.Map **members**

---

## order

protected java.util.List **order**

---

## trait

protected com.wowza.wms.amf.AMFDataTrait **trait**

---

## Constructors

### AMFDataObj

```
public AMFDataObj()
```

Create empty AMFDataObj object

---

### AMFDataObj

```
public AMFDataObj(byte[] data)
```

Deserialize entire data array and create AMFDataObj object

**Parameters:**

data - binary data

---

### AMFDataObj

```
public AMFDataObj(byte[] data,  
                  int offset,  
                  int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataObj object

**Parameters:**

data - binary data

offset - starting offset into data

size - size of data to deserialize

---

### AMFDataObj

```
public AMFDataObj(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataObj object

**Parameters:**

(continued from last page)

data - binary data

---

## AMFDataObj

```
public AMFDataObj(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

## Methods

### size

```
public int size()
```

Return the number of members of this object/array

**Returns:**

number of members

---

### containsKey

```
public boolean containsKey(String name)
```

---

### put

```
public void put(String name,  
    AMFData data)
```

---

### put

```
public void put(String name,  
    String data)
```

---

### put

```
public void put(String name,  
    double data)
```

---

### put

```
public void put(String name,  
    int data)
```

---

### put

```
public void put(String name,  
    long data)
```

---

(continued from last page)

---

**put**

```
public void put(String name,  
               java.util.Date data)
```

---

**put**

```
public void put(String name,  
               boolean data)
```

---

**getKeys**

```
public java.util.List getKeys()
```

---

**getKey**

```
public String getKey(int index)
```

---

**get**

```
public AMFData get(String name)
```

---

**get**

```
public AMFData get(int index)
```

---

**remove**

```
public AMFData remove(String name)
```

---

**remove**

```
public AMFData remove(int index)
```

---

**getString**

```
public String getString(String name)
```

---



## getInt

```
public int getInt(String name)
```

---

## getLong

```
public long getLong(String name)
```

---

## getShort

```
public short getShort(String name)
```

---

## getDouble

```
public double getDouble(String name)
```

---

## getFloat

```
public float getFloat(String name)
```

---

## getByte

```
public byte getByte(String name)
```

---

## getBoolean

```
public boolean getBoolean(String name)
```

---

## getDate

```
public java.util.Date getDate(String name)
```

---

## getObject

```
public AMFDataObj getObject(String name)
```

---

## getString

```
public String getString(int index)
```

---

(continued from last page)

---

### getInt

```
public int getInt(int index)
```

---

### getLong

```
public long getLong(int index)
```

---

### getShort

```
public short getShort(int index)
```

---

### getByte

```
public byte getByte(int index)
```

---

### getDouble

```
public double getDouble(int index)
```

---

### getFloat

```
public float getFloat(int index)
```

---

### getBoolean

```
public boolean getBoolean(int index)
```

---

### getDate

```
public java.util.Date getDate(int index)
```

---

### getObject

```
public AMFDataObj getObject(int index)
```

---

(continued from last page)

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

---

## deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

---

## serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

---

## serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

---

## serialize

```
public byte[] serialize()
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

---

## serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

---

## getValue

```
public Object getValue()
```

Convert object to Java native class

---

(continued from last page)

## toString

```
public String toString()
```

Return object as formatted string

---

## getClassName

```
public String getClassName()
```

---

## setClassName

```
public void setClassName(String className)
```

---

## getTrait

```
public AMFDataTrait getTrait()
```

## com.wowza.wms.amf

### Class AMFDataTrait

java.lang.Object

└─com.wowza.wms.amf.AMFDataTrait

public class **AMFDataTrait**  
extends Object

AMF trait used to describe an AMF class in AMF3

### Constructor Summary

public	<a href="#">AMFDataTrait</a> ( ) Constructor
--------	---

### Method Summary

void	<a href="#">addMember</a> (String member) Add a member
<a href="#">AMFDataTrait</a>	<a href="#">clone</a> ( ) clone the trait
String	<a href="#">getClassName</a> ( ) Get class name
<a href="#">AMFData</a>	<a href="#">getInnerObj</a> ( ) Get inner object
String	<a href="#">getMember</a> (int i) Get member by index
int	<a href="#">getMemberCount</a> ( ) Get the number of members
java.util.List	<a href="#">getMembers</a> ( ) Get a list of trait members
boolean	<a href="#">isDynamic</a> ( ) Is class dynamic
boolean	<a href="#">isMember</a> (String member) Return true if member of this trait
void	<a href="#">setClassName</a> (String className) Set class name
void	<a href="#">setDynamic</a> (boolean isDynamic) Set isDynamic
void	<a href="#">setInnerObj</a> ( <a href="#">AMFData</a> innerObj) Set inner object

**Methods inherited from class** `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

## Constructors

### AMFDataTrait

```
public AMFDataTrait()
```

Constructor

## Methods

### clone

```
public AMFDataTrait clone()
```

clone the trait

### addMember

```
public void addMember(String member)
```

Add a member

**Parameters:**

member - member name

### isMember

```
public boolean isMember(String member)
```

Return true if member of this trait

**Parameters:**

member - member name

**Returns:**

true, if member

### getMembers

```
public java.util.List getMembers()
```

Get a list of trait members

**Returns:**

list of trait members

### getMemberCount

```
public int getMemberCount()
```

(continued from last page)

Get the number of members

**Returns:**

number of members

---

## getMember

```
public String getMember(int i)
```

Get member by index

**Parameters:**

i - index

**Returns:**

member name

---

## getClassName

```
public String getClassName()
```

Get class name

**Returns:**

class name

---

## setClassName

```
public void setClassName(String className)
```

Set class name

**Parameters:**

className - class name

---

## isDynamic

```
public boolean isDynamic()
```

Is class dynamic

**Returns:**

true, if dynamic

---

## setDynamic

```
public void setDynamic(boolean isDynamic)
```

Set isDynamic

**Parameters:**

isDynamic - true, if dynamic

---

## getInnerObj

```
public AMFData getInnerObj()
```

Get inner object

---

(continued from last page)

**Returns:**

inner object

---

**setInnerObj**

```
public void setInnerObj(AMFData innerObj)
```

Set inner object

**Parameters:**

innerObj - inner object



## com.wowza.wms.amf

### Class AMFObj

java.lang.Object

└─com.wowza.wms.amf.AMFObj

public class **AMFObj**  
extends Object

AMFObj: class that stores the state of channel between the client and the server.

#### Field Summary

public static final	<a href="#">AMFDEBUGHEADERSIZE</a> Value: <b>false</b>
public static final	<a href="#">WOWZDEBUGHEADERSIZE</a> Value: <b>false</b>

#### Constructor Summary

public	<a href="#">AMFObj</a> (int id) Create new AMFObj for a given channel (id)
public	<a href="#">AMFObj</a> (int id, int objectEncoding) Create new AMFObj for a given channel (id)

#### Method Summary

void	<a href="#">addChunk</a> (byte[] buffer, int offset, int len) Add a chunk to the chunk list
void	<a href="#">clearByteContainer</a> () Clear the byte container
long	<a href="#">getAbsTimecode</a> () Get the absolute time code
int	<a href="#">getByteContainerLevel</a> () Fake container for processing
long	<a href="#">getChunkCounter</a> ()
java.util.List	<a href="#">getChunks</a> () Get the chunks that make up this packet
int	<a href="#">getId</a> () Get channel id
int	<a href="#">getObjectEncoding</a> ()

int	<a href="#"><u>getSize()</u></a> Get packet size
int	<a href="#"><u>getSrc()</u></a> Get stream id (0 if not stream data)
long	<a href="#"><u>getTimecode()</u></a> Get timecode (milliseconds) sometimes relative
int	<a href="#"><u>getType()</u></a> Get content type IVHost.CONTENTTYPE_*
long	<a href="#"><u>incAbsTimecode(long absTimecode)</u></a> Increment the absolute timecode
void	<a href="#"><u>incByteContainerLevel(int byteContainerLevel)</u></a> Fake container for processing
boolean	<a href="#"><u>isByteContainerEmpty()</u></a> Fake container for processing
boolean	<a href="#"><u>isByteContainerFull()</u></a> Fake container for processing
boolean	<a href="#"><u>isLastSentAbsTimecode()</u></a>
boolean	<a href="#"><u>isLongTimecode()</u></a> Get is a 32 bit timecode
boolean	<a href="#"><u>isNew()</u></a> Is this a new packet.
boolean	<a href="#"><u>isObjectEncodingAMF0()</u></a>
boolean	<a href="#"><u>isObjectEncodingAMF3()</u></a>
long	<a href="#"><u>setAbsTimecodeLong(long absTimecode)</u></a> Set the absolute timecode
long	<a href="#"><u>setAbsTimecodeShort(long absTimecode)</u></a> Set the absolute timecode
void	<a href="#"><u>setByteContainerLevel(int byteContainerLevel)</u></a> Fake container for processing
void	<a href="#"><u>setChunkCounter(long chunkCounter)</u></a>
void	<a href="#"><u>setId(int id)</u></a> Set channel id
void	<a href="#"><u>setLastSentAbsTimecode(boolean isLastSentAbsTimecode)</u></a>
void	<a href="#"><u>setLongTimecode(boolean isLongTimecode)</u></a> Set is a 32 bit timecode
void	<a href="#"><u>setNew(boolean isNew)</u></a> Set is new packet

void	<a href="#"><code>setObjectEncoding</code></a> (int objectEncoding)
void	<a href="#"><code>setSize</code></a> (int size) Set packet size
void	<a href="#"><code>setSrc</code></a> (int src) Set stream id (0 if not stream data)
void	<a href="#"><code>setTimecode</code></a> (long timecode) Set timecode (milliseconds) sometimes relative
void	<a href="#"><code>setType</code></a> (int type) Set content type IVHost.CONTENT_TYPE_*
String	<a href="#"><code>toString</code></a> () Return object as formatted string

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Fields

### AMFDEBUGHEADERSIZE

public static final boolean **AMFDEBUGHEADERSIZE**

Constant value: **false**

### WOWZDEBUGHEADERSIZE

public static final boolean **WOWZDEBUGHEADERSIZE**

Constant value: **false**

## Constructors

### AMFObj

public **AMFObj**(int id)

Create new AMFObj for a given channel (id)

#### Parameters:

id - channel id

### AMFObj

public **AMFObj**(int id,  
int objectEncoding)

Create new AMFObj for a given channel (id)

(continued from last page)

**Parameters:**

id - channel id  
objectEncoding - object encoding level (AMF0 or AMF3)

## Methods

### getChunks

```
public java.util.List getChunks()
```

Get the chunks that make up this packet

**Returns:**

chunks that make up this packet

### addChunk

```
public void addChunk(byte[] buffer,  
    int offset,  
    int len)
```

Add a chunk to the chunk list

**Parameters:**

buffer - buffer  
offset - offset  
len - length

### getId

```
public int getId()
```

Get channel id

**Returns:**

channel id

### setId

```
public void setId(int id)
```

Set channel id

**Parameters:**

id - channel id

### getSize

```
public int getSize()
```

Get packet size

**Returns:**

packet size

### setSize

```
public void setSize(int size)
```

(continued from last page)

Set packet size

**Parameters:**

size - packet size

---

## getType

```
public int getType()
```

Get content type IVHost.CONTENTTYPE\_\*

**Returns:**

content type

---

## setType

```
public void setType(int type)
```

Set content type IVHost.CONTENTTYPE\_\*

**Parameters:**

type - content type

---

## getSrc

```
public int getSrc()
```

Get stream id (0 if not stream data)

**Returns:**

stream id

---

## setSrc

```
public void setSrc(int src)
```

Set stream id (0 if not stream data)

**Parameters:**

src - stream id

---

## toString

```
public String toString()
```

Return object as formatted string

---

## getTimecode

```
public long getTimecode()
```

Get timecode (milliseconds) sometimes relative

**Returns:**

timecode (milliseconds)

---

(continued from last page)

## setTimecode

```
public void setTimecode(long timecode)
```

Set timecode (milliseconds) sometimes relative

**Parameters:**

timecode - timecode (milliseconds)

---

## isNew

```
public boolean isNew()
```

Is this a new packet. If new entire packet header needs to be sent

**Returns:**

is new packet

---

## setNew

```
public void setNew(boolean isNew)
```

Set is new packet

**Parameters:**

isNew - is new packet

---

## getAbsTimecode

```
public long getAbsTimecode()
```

Get the absolute time code

**Returns:**

absolute timecode

---

## setAbsTimecodeLong

```
public long setAbsTimecodeLong(long absTimecode)
```

Set the absolute timecode

**Parameters:**

absTimecode - absolute timecode

**Returns:**

absolute timecode

---

## setAbsTimecodeShort

```
public long setAbsTimecodeShort(long absTimecode)
```

Set the absolute timecode

**Parameters:**

absTimecode

**Returns:**

(continued from last page)

absolute timecode

---

## incAbsTimecode

```
public long incAbsTimecode(long absTimecode)
```

Increment the absolute timecode

**Parameters:**

absTimecode - absolute timecode

**Returns:**

absolute timecode

---

## getByteContainerLevel

```
public int getByteContainerLevel()
```

Fake container for processing

**Returns:**

current container level

---

## clearByteContainer

```
public void clearByteContainer()
```

Clear the byte container

---

## setByteContainerLevel

```
public void setByteContainerLevel(int byteContainerLevel)
```

Fake container for processing

**Parameters:**

byteContainerLevel - current container level

---

## incByteContainerLevel

```
public void incByteContainerLevel(int byteContainerLevel)
```

Fake container for processing

**Parameters:**

byteContainerLevel - current container level

---

## isByteContainerEmpty

```
public boolean isByteContainerEmpty()
```

Fake container for processing

**Returns:**

is container full

---

(continued from last page)

## isByteContainerFull

```
public boolean isByteContainerFull()
```

Fake container for processing

**Returns:**

is container full

---

## isLongTimecode

```
public boolean isLongTimecode()
```

Get is a 32 bit timecode

**Returns:**

true if 32 bit timecode

---

## setLongTimecode

```
public void setLongTimecode(boolean isLongTimecode)
```

Set is a 32 bit timecode

**Parameters:**

isLongTimecode - is a 32 bit timecode

---

## isLastSentAbsTimecode

```
public boolean isLastSentAbsTimecode()
```

---

## setLastSentAbsTimecode

```
public void setLastSentAbsTimecode(boolean isLastSentAbsTimecode)
```

---

## isObjectEncodingAMF3

```
public boolean isObjectEncodingAMF3()
```

---

## isObjectEncodingAMF0

```
public boolean isObjectEncodingAMF0()
```

---

## setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

---



(continued from last page)

**getObjectEncoding**

```
public int getObjectEncoding()
```

---

**getChunkCounter**

```
public long getChunkCounter()
```

---

**setChunkCounter**

```
public void setChunkCounter(long chunkCounter)
```

## com.wowza.wms.amf Class AMFObjChunk

java.lang.Object

└─com.wowza.wms.amf.AMFObjChunk

```
public class AMFObjChunk
extends Object
```

### Field Summary

public	<a href="#">buffer</a>
public	<a href="#">len</a>
public	<a href="#">offset</a>

### Constructor Summary

public	<a href="#">AMFObjChunk</a> (byte[] buffer, int offset, int len)
--------	--

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Fields

#### buffer

```
public byte buffer
```

#### offset

```
public int offset
```

#### len

```
public int len
```

### Constructors

(continued from last page)

## AMFObjChunk

```
public AMFObjChunk(byte[] buffer,  
                   int offset,  
                   int len)
```

## com.wowza.wms.amf

### Class AMPacket

java.lang.Object

└─com.wowza.wms.amf.AMPacket

```
public class AMPacket
extends Object
```

AMFPacket: data container for data being transferred to and from the server from the Flash client. AMPacket is also used to store data read/written to/from an flv file.

### Constructor Summary

public	<a href="#">AMPacket()</a> Create new empty packet
public	<a href="#">AMPacket(int type, int src, int size)</a> Create new packet with given values
public	<a href="#">AMPacket(int type, int src, byte[] data)</a> Create new packet with given values

### Method Summary

int	<a href="#">addData(byte[] data, int offset, int size)</a> Add data to the packet
int	<a href="#">addDataEx(byte[] srcData, int srcOffset, int destOffset, int srcBytes)</a> Add data to the packet
static int	<a href="#">calcTotalPacketSize(int packetSize, int headerSize, int chunkSize, int amfNumber, boolean isLongTimecode)</a> Calculate the total packet size for given packet parameters
<a href="#">AMPacket</a>	<a href="#">clone()</a>
<a href="#">AMPacket</a>	<a href="#">clone(boolean doCopy)</a>
long	<a href="#">getAbsTimecode()</a> Get absolute timecode (milliseconds)
byte[]	<a href="#">getData()</a> Get data as byte[]
java.nio.ByteBuffer	<a href="#">getDataBuffer()</a> Get data as ByteBuffer
int	<a href="#">getFirstByte()</a> Get first byte of data (used to peek into packet)
int	<a href="#">getMissing()</a> Get the number of bytes remaining unfilled in the packet

int	<a href="#"><u>getSecondByte()</u></a> Get second byte of data (used to peek into packet)
long	<a href="#"><u>getSeq()</u></a> Get packet sequence number.
int	<a href="#"><u>getSize()</u></a> Get packet size
int	<a href="#"><u>getSrc()</u></a> Get stream id (0 if not stream data)
long	<a href="#"><u>getTimecode()</u></a> Get timecode (milliseconds) relative to the <i>previous</i> packet.
int	<a href="#"><u>getType()</u></a> Get content type IVHost.CONTENTTYPE_*
boolean	<a href="#"><u>isAudio()</u></a> Is this an audio packet IVHost.CONTENTTYPE_AUDIO
boolean	<a href="#"><u>isVideo()</u></a> Is this an audio packet IVHost.CONTENTTYPE_VIDEO
void	<a href="#"><u>setAbsTimecode()</u></a> (long absTimecode) Set absolute timecode (milliseconds)
void	<a href="#"><u>setDataBuffer()</u></a> (byte[] data) Set the data buffer to a byte array
void	<a href="#"><u>setDataBuffer()</u></a> (java.nio.ByteBuffer data) Set the data for this packet
void	<a href="#"><u>setSeq()</u></a> (long seq) Set packet sequence.
void	<a href="#"><u>setSize()</u></a> (int size) Set packet size
void	<a href="#"><u>setSrc()</u></a> (int src) Set stream id (0 if not stream data)
void	<a href="#"><u>setTimecode()</u></a> (long timecode) Set timecode (milliseconds) relative,
void	<a href="#"><u>setTimecodes()</u></a> (long timecode, long absTimecode) Set both relative and absolute timecode in one call (milliseconds)
void	<a href="#"><u>setType()</u></a> (int type) Set content type IVHost.CONTENTTYPE_*
String	<a href="#"><u>toString()</u></a> Return object as formatted string
void	<a href="#"><u>truncatePacket()</u></a> (int newSize)

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

## Constructors

### AMFPacket

```
public AMFPacket()
```

Create new empty packet

### AMFPacket

```
public AMFPacket(int type,  
                 int src,  
                 int size)
```

Create new packet with given values

#### Parameters:

type - packet content type: IVHost.CONTENT\*TYPE\_\*

src - stream id

size - packet size (bytes)

### AMFPacket

```
public AMFPacket(int type,  
                 int src,  
                 byte[] data)
```

Create new packet with given values

#### Parameters:

type - packet content type: IVHost.CONTENT\*TYPE\_\*

src - stream id

data - data buffer

## Methods

### clone

```
public AMFPacket clone()
```

### clone

```
public AMFPacket clone(boolean doCopy)
```

### getSize

```
public int getSize()
```

Get packet size

(continued from last page)

**Returns:**

packet size

---

**setSize**

```
public void setSize(int size)
```

Set packet size

**Parameters:**

size - packet size

---

**truncatePacket**

```
public void truncatePacket(int newSize)
```

---

**getMissing**

```
public int getMissing()
```

Get the number of bytes remaining unfilled in the packet

**Returns:**

number of bytes unfilled in packet

---

**setDataBuffer**

```
public void setDataBuffer(java.nio.ByteBuffer data)
```

Set the data for this packet

**Parameters:**

data - byte buffer that holds packet data

---

**setDataBuffer**

```
public void setDataBuffer(byte[] data)
```

Set the data buffer to a byte array

**Parameters:**

data - data buffer byte array

---

**addData**

```
public int addData(byte[] data,  
                  int offset,  
                  int size)
```

Add data to the packet

**Parameters:**

data - byte buffer with data  
offset - offset in byte buffer  
size - size of data

(continued from last page)

**Returns:**

number of bytes unfilled in packet

---

## getType

```
public int getType()
```

Get content type IVHost.CONTENTTYPE\_\*

**Returns:**

content type

---

## setType

```
public void setType(int type)
```

Set content type IVHost.CONTENTTYPE\_\*

**Parameters:**

type - content type

---

## getSrc

```
public int getSrc()
```

Get stream id (0 if not stream data)

**Returns:**

stream id

---

## setSrc

```
public void setSrc(int src)
```

Set stream id (0 if not stream data)

**Parameters:**

src - stream id

---

## toString

```
public String toString()
```

Return object as formatted string

---

## getTimecode

```
public long getTimecode()
```

Get timecode (milliseconds) relative to the *previous* packet.**Returns:**

timecode (milliseconds)

---

## setTimecodes

```
public void setTimecodes(long timecode,  
                          long absTimecode)
```



(continued from last page)

Set both relative and absolute timecode in one call (milliseconds)

Note this time is relative to the *previous* packet.

**Parameters:**

timecode - relative timecode (milliseconds)

absTimecode - absolute timecode (milliseconds)

---

## setTimecode

```
public void setTimecode(long timecode)
```

Set timecode (milliseconds) relative,

Note this time is relative to the *previous* packet.

**Parameters:**

timecode - timecode (milliseconds)

---

## getAbsTimecode

```
public long getAbsTimecode()
```

Get absolute timecode (milliseconds)

**Returns:**

absolute timecode

---

## setAbsTimecode

```
public void setAbsTimecode(long absTimecode)
```

Set absolute timecode (milliseconds)

**Parameters:**

absTimecode - absolute timecode

---

## getSeq

```
public long getSeq()
```

Get packet sequence number. Used for live streams to keep track of packet ordering.

**Returns:**

packet sequence

---

## setSeq

```
public void setSeq(long seq)
```

Set packet sequence. Used for live streams to keep track of packet ordering.

**Parameters:**

seq - packet sequence

---

## isAudio

```
public boolean isAudio()
```

(continued from last page)

Is this an audio packet IVHost.CONTENTTYPE\_AUDIO

**Returns:**

true if audio packet

---

## isVideo

```
public boolean isVideo()
```

Is this an audio packet IVHost.CONTENTTYPE\_VIDEO

**Returns:**

true if video packet

---

## getDataBuffer

```
public java.nio.ByteBuffer getDataBuffer()
```

Get data as ByteBuffer

**Returns:**

data as ByteBuffer

---

## getData

```
public byte[] getData()
```

Get data as byte[]

**Returns:**

data as byte[] null if no data

---

## getFirstByte

```
public int getFirstByte()
```

Get first byte of data (used to peek into packet)

**Returns:**

first byte of data in packet

---

## getSecondByte

```
public int getSecondByte()
```

Get second byte of data (used to peek into packet)

**Returns:**

second byte of data in packet

---

## calcTotalPacketSize

```
public static int calcTotalPacketSize(int packetSize,  
    int headerSize,  
    int chunkSize,  
    int amfNumber,  
    boolean isLongTimecode)
```

Calculate the total packet size for given packet parameters

(continued from last page)

**Parameters:**

packetSize - data size  
headerSize - header size  
chunkSize - chunk size  
amfNumber - amf number  
isLongTimecode - is long timecode

**Returns:**

total bytes

---

**addDataEx**

```
public int addDataEx(byte[] srcData,  
    int srcOffset,  
    int destOffset,  
    int srcBytes)
```

Add data to the packet

**Parameters:**

srcData - - source byte buffer with data  
srcOffset - - start copying from source buffer at this offset  
destOffset - - copy into destination buffer from this offset  
srcBytes - - size of data to copy

**Returns:**

number of bytes unfilled in packet

## com.wowza.wms.amf Interface IAMFDataObj

All Known Implementing Classes:

[AMFDataObj](#)

public interface **IAMFDataObj**  
extends

### Method Summary

boolean	<a href="#"><code>containsKey</code></a> (String name) Return true if the object/array contains key
<a href="#">AMFData</a>	<a href="#"><code>get</code></a> (int index) Return the object at a particular index.
<a href="#">AMFData</a>	<a href="#"><code>get</code></a> (String name) Return the object at a particular key.
boolean	<a href="#"><code>getBoolean</code></a> (int index) Get item at index return as boolean
boolean	<a href="#"><code>getBoolean</code></a> (String name) Get item at key return as boolean
byte	<a href="#"><code>getByte</code></a> (int index) Get item at index return as byte
byte	<a href="#"><code>getByte</code></a> (String name) Get item at key return as byte
java.util.Date	<a href="#"><code>getDate</code></a> (int index) Get item at index return as Date
java.util.Date	<a href="#"><code>getDate</code></a> (String name) Get item at key return as Date
double	<a href="#"><code>getDouble</code></a> (int index) Get item at index return as double
double	<a href="#"><code>getDouble</code></a> (String name) Get item at key return as double
float	<a href="#"><code>getFloat</code></a> (int index) Get item at index return as float
float	<a href="#"><code>getFloat</code></a> (String name) Get item at key return as float
int	<a href="#"><code>getInt</code></a> (int index) Get item at index return as int
int	<a href="#"><code>getInt</code></a> (String name) Get item at key return as int

String	<a href="#"><u>getKey</u></a> (int index) Return the key at a particular index.
java.util.List	<a href="#"><u>getKeys</u></a> ( ) Return a list of all the keys (the list is a copy)
long	<a href="#"><u>getLong</u></a> (int index) Get item at index return as long
long	<a href="#"><u>getLong</u></a> (String name) Get item at key return as long
<a href="#"><u>AMFDataObj</u></a>	<a href="#"><u>getObject</u></a> (int index) Get item at index return as AMFDataObj
<a href="#"><u>AMFDataObj</u></a>	<a href="#"><u>getObject</u></a> (String name) Get item at key return as AMFDataObj
short	<a href="#"><u>getShort</u></a> (int index) Get item at index return as short
short	<a href="#"><u>getShort</u></a> (String name) Get item at key return as short
String	<a href="#"><u>getString</u></a> (int index) Get item at index return as String
String	<a href="#"><u>getString</u></a> (String name) Get item at key return as String
void	<a href="#"><u>put</u></a> (String name, <a href="#"><u>AMFData</u></a> data) Put or replace object at key
void	<a href="#"><u>put</u></a> (String name, boolean data) Put or replace boolean value at key (data will be wrapped in an AMFDataItem object)
void	<a href="#"><u>put</u></a> (String name, java.util.Date data) Put or replace date value at key (data will be wrapped in an AMFDataItem object)
void	<a href="#"><u>put</u></a> (String name, double data) Put or replace double value at key (data will be wrapped in an AMFDataItem object)
void	<a href="#"><u>put</u></a> (String name, int data) Put or replace int value at key (data will be wrapped in an AMFDataItem object)
void	<a href="#"><u>put</u></a> (String name, long data) Put or replace long value at key (data will be wrapped in an AMFDataItem object)
void	<a href="#"><u>put</u></a> (String name, String data) Put or replace string value at key (data will be wrapped in an AMFDataItem object)
<a href="#"><u>AMFData</u></a>	<a href="#"><u>remove</u></a> (int index) Remove element by index
<a href="#"><u>AMFData</u></a>	<a href="#"><u>remove</u></a> (String name) Remove element by key

(continued from last page)

## Methods

### containsKey

```
public boolean containsKey(String name)
```

Return true if the object/array contains key

**Parameters:**

name - key

**Returns:**

Return true the object/array contains key

---

### put

```
public void put(String name,  
    AMFData data)
```

Put or replace object at key

**Parameters:**

name - key

data - object

---

### put

```
public void put(String name,  
    String data)
```

Put or replace string value at key (data will be wrapped in an AMFDataItem object)

**Parameters:**

name - key

data - string value

---

### put

```
public void put(String name,  
    double data)
```

Put or replace double value at key (data will be wrapped in an AMFDataItem object)

**Parameters:**

name - key

data - double value

---

### put

```
public void put(String name,  
    int data)
```

Put or replace int value at key (data will be wrapped in an AMFDataItem object)

**Parameters:**

name - key

data - int value

## put

```
public void put(String name,  
                long data)
```

Put or replace long value at key (data will be wrapped in an AMFDataItem object)

**Parameters:**

name - key  
data - long value

---

## put

```
public void put(String name,  
                java.util.Date data)
```

Put or replace date value at key (data will be wrapped in an AMFDataItem object)

**Parameters:**

name - key  
data - date value

---

## put

```
public void put(String name,  
                boolean data)
```

Put or replace boolean value at key (data will be wrapped in an AMFDataItem object)

**Parameters:**

name - key  
data - boolean value

---

## getKeys

```
public java.util.List getKeys()
```

Return a list of all the keys (the list is a copy)

**Returns:**

new list that contains one entry for each key

---

## getKey

```
public String getKey(int index)
```

Return the key at a particular index.

**Parameters:**

index

**Returns:**

Return key at index or null if out of bounds

---

## get

```
public AMFData get(String name)
```

---

---

(continued from last page)

Return the object at a particular key.

**Parameters:**

name - key

**Returns:**

Return object or null if out of bounds

---

## get

public [AMFData](#) **get**(int index)

Return the object at a particular index.

**Parameters:**

index - index

**Returns:**

Return object or null if out of bounds

---

## remove

public [AMFData](#) **remove**(String name)

Remove element by key

**Parameters:**

name - key

**Returns:**

removed object or null if not found

---

## remove

public [AMFData](#) **remove**(int index)

Remove element by index

**Parameters:**

index - index

**Returns:**

removed object or null if not found

---

## getString

public String **getString**(String name)

Get item at key return as String

**Parameters:**

name - key

**Returns:**

Return item as String or null if out of bounds

---



(continued from last page)

## getInt

```
public int getInt(String name)
```

Get item at key return as int

**Parameters:**

name - key

**Returns:**

Return item as int or 0 if out of bounds

---

## getLong

```
public long getLong(String name)
```

Get item at key return as long

**Parameters:**

name - key

**Returns:**

Return item as long or 0 if out of bounds

---

## getShort

```
public short getShort(String name)
```

Get item at key return as short

**Parameters:**

name - key

**Returns:**

Return item as short or 0 if out of bounds

---

## getDouble

```
public double getDouble(String name)
```

Get item at key return as double

**Parameters:**

name - key

**Returns:**

Return item as double or 0 if out of bounds

---

## getFloat

```
public float getFloat(String name)
```

Get item at key return as float

**Parameters:**

name - key

**Returns:**

Return item as float or 0 if out of bounds

## getBytes

```
public byte getBytes(String name)
```

Get item at key return as byte

**Parameters:**

name - key

**Returns:**

Return item as byte or 0 if out of bounds

---

## getBoolean

```
public boolean getBoolean(String name)
```

Get item at key return as boolean

**Parameters:**

name - key

**Returns:**

Return item as boolean or false if out of bounds

---

## getDate

```
public java.util.Date getDate(String name)
```

Get item at key return as Date

**Parameters:**

name - key

**Returns:**

Return item as Date or null if out of bounds

---

## getObject

```
public AMFDataObj getObject(String name)
```

Get item at key return as AMFDataObj

**Parameters:**

name - key

**Returns:**

Return item as AMFDataObj or null if out of bounds

---

## getString

```
public String getString(int index)
```

Get item at index return as String

**Parameters:**

index - index

---

(continued from last page)

**Returns:**

Return item as String or null if out of bounds

---

## getInt

```
public int getInt(int index)
```

Get item at index return as int

**Parameters:**

index - index

**Returns:**

Return item as int or 0 if out of bounds

---

## getLong

```
public long getLong(int index)
```

Get item at index return as long

**Parameters:**

index - index

**Returns:**

Return item as long or 0 if out of bounds

---

## getShort

```
public short getShort(int index)
```

Get item at index return as short

**Parameters:**

index - index

**Returns:**

Return item as short or 0 if out of bounds

---

## getByte

```
public byte getByte(int index)
```

Get item at index return as byte

**Parameters:**

index - index

**Returns:**

Return item as byte or 0 if out of bounds

---

## getDouble

```
public double getDouble(int index)
```

Get item at index return as double

**Parameters:**

(continued from last page)

index - index

**Returns:**

Return item as double or 0 if out of bounds

---

## getFloat

```
public float getFloat(int index)
```

Get item at index return as float

**Parameters:**

index - index

**Returns:**

Return item as float or 0 if out of bounds

---

## getBoolean

```
public boolean getBoolean(int index)
```

Get item at index return as boolean

**Parameters:**

index - index

**Returns:**

Return item as boolean or false if out of bounds

---

## getDate

```
public java.util.Date getDate(int index)
```

Get item at index return as Date

**Parameters:**

index - index

**Returns:**

Return item as Date or null if out of bounds

---

## getObject

```
public AMFDataObj getObject(int index)
```

Get item at index return as AMFDataObj

**Parameters:**

index - index

**Returns:**

Return item as AMFDataObj or null if out of bounds

---

Package

**com.wowza.wms.application**

## com.wowza.wms.application Interface IApplication

public interface **IApplication**  
extends

IApplication: public interface to Application object

### Field Summary

public static final	<a href="#"><u>DEFAULT_APPLICATION_NAME</u></a> Value: <b>_defapp_</b>
---------------------	---

### Method Summary

void	<a href="#"><u>addApplicationInstanceListener</u></a> ( <a href="#"><u>IApplicationInstanceNotify</u></a> applicationInstanceListener) Add applicationInstance listener.
<a href="#"><u>IApplicationInstance</u></a>	<a href="#"><u>getAppInstance</u></a> (String name) Get applicationInstance object by name
java.util.List	<a href="#"><u>getAppInstanceNames</u></a> ( ) Get a list of application instance names
String	<a href="#"><u>getApplicationPath</u></a> ( ) Get the root path for application
String	<a href="#"><u>getConfigPath</u></a> ( ) Get full path to Application.xml file
<a href="#"><u>ConnectionCounter</u></a>	<a href="#"><u>getConnectionCounter</u></a> ( ) Get the connectionCounter for application
ConnectionCounterSimple	<a href="#"><u>getConnectionCounter</u></a> (int counterIndex) Get the connectionCounter for application for application for a specific technology (see IVHost.COUNTER_*)
String	<a href="#"><u>getDateStarted</u></a> ( ) Get date application started
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getIoPerformanceCounter</u></a> ( ) Get the performance counter for application
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getIoPerformanceCounter</u></a> (int counterIndex) Get the performance counter for application for a specific technology (see IVHost.COUNTER_*)
String	<a href="#"><u>getName</u></a> ( ) Get the name of application
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties</u></a> ( ) Get application properties

void	<a href="#"><u>getProtocolUsage</u></a> (boolean[] protocolsInUse) Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE_*)
String	<a href="#"><u>getTimeRunning</u></a> () Get time application running
double	<a href="#"><u>getTimeRunningSeconds</u></a> () Get time running in seconds
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost</u></a> () Get the parent vHost object
boolean	<a href="#"><u>isAppInstanceLoaded</u></a> (String name) Return true if application instance is loaded
String	<a href="#"><u>readAppConfig</u></a> (String sName) Method to read xml config file..
void	<a href="#"><u>removeAppInstance</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance) Disconnect all clients connected to an application instance and remove it from the IApplication application list.
void	<a href="#"><u>removeApplicationInstanceListener</u></a> ( <a href="#"><u>IApplicationInstanceNotify</u></a> applicationInstanceListener) Remove applicationInstance listener.
void	<a href="#"><u>setName</u></a> (String name) Set name of application
void	<a href="#"><u>shutdown</u></a> (boolean isServerShutdown) shutdown application
void	<a href="#"><u>shutdownAppInstance</u></a> (String appInstanceName) Shutdown an application instance by name.
boolean	<a href="#"><u>writeAppConfig</u></a> (String sName, String data) Method to write xml config file..

## Fields

### DEFAULT\_APPLICATION\_NAME

public static final java.lang.String **DEFAULT\_APPLICATION\_NAME**

Constant value: **\_defapp\_**

## Methods

### shutdown

public void **shutdown**(boolean isServerShutdown)

shutdown application

#### Parameters:

isServerShutdown - true if due to shutdown of server

## getApplicationPath

```
public String getApplicationPath()
```

Get the root path for application

**Returns:**

root path for application

---

## getConfigPath

```
public String getConfigPath()
```

Get full path to Application.xml file

**Returns:**

full path to Application.xml file

---

## getAppInstance

```
public IApplicationInstance getAppInstance(String name)
```

Get applicationInstance object by name

**Parameters:**

name - applicationInstance name

**Returns:**

appliationInstance object

---

## isAppInstanceLoaded

```
public boolean isAppInstanceLoaded(String name)
```

Return true if application instance is loaded

**Parameters:**

name - applicationInstance name

**Returns:**

true if application instance is loaded

---

## getName

```
public String getName()
```

Get the name of application

**Returns:**

name of application

---

## setName

```
public void setName(String name)
```

Set name of application

---



(continued from last page)

**Parameters:**

name - name of application

---

**getVHost**

```
public IVHost getVHost ( )
```

Get the parent vHost object

**Returns:**

parent vHost

---

**getProperties**

```
public WMSProperties getProperties ( )
```

Get application properties

**Returns:**

application properties

---

**addApplicationInstanceListener**

```
public void addApplicationInstanceListener ( IApplicationInstanceNotify  
applicationInstanceListener )
```

Add applicationInstance listener. Will be invoked each time applicationInstance created/deleted

**Parameters:**

applicationInstanceListener - applicationInstance listener

---

**removeApplicationInstanceListener**

```
public void removeApplicationInstanceListener ( IApplicationInstanceNotify  
applicationInstanceListener )
```

Remove applicationInstance listener. Will be invoked each time applicationInstance created/deleted

**Parameters:**

applicationInstanceListener - applicationInstance listener

---

**getConnectionCounter**

```
public ConnectionCounter getConnectionCounter ( )
```

Get the connectionCounter for application

**Returns:**

connectionCounter for application

---

**getConnectionCounter**

```
public ConnectionCounterSimple getConnectionCounter (int counterIndex)
```

Get the connectionCounter for application for application for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index (see IVHost.COUNTER\_\*)

(continued from last page)

**Returns:**

connection ocunter

---

## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter( )
```

Get the performance counter for application

**Returns:**

performance counter for application

---

## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

Get the performance counter for application for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index (see IVHost.COUNTER\_\*)

**Returns:**

performance counter

---

## getDateStarted

```
public String getDateStarted( )
```

Get date application started

**Returns:**

date application started

---

## getTimeRunning

```
public String getTimeRunning( )
```

Get time application running

**Returns:**

time application running

---

## getTimeRunningSeconds

```
public double getTimeRunningSeconds( )
```

Get time running in seconds

**Returns:**

time running in seconds

---

## getAppInstanceNames

```
public java.util.List getAppInstanceNames( )
```

Get a list of application instance names

**Returns:**

(continued from last page)

list of application instance names

---

## removeAppInstance

```
public void removeAppInstance(IApplicationInstance appInstance)
```

Disconnect all clients connected to an application instance and remove it from the IApplication application list. The proper way to call this is:

```
public void shutdownAppInstance(IApplicationInstance appInstance)
{
    IVHost vhost = appInstance.getVHost();
    IApplication app = appInstance.getApplication();

    WMSReadWriteLock appLock = vhost.getApplicationLock();
    appLock.writeLock().lock();
    try
    {
        app.removeAppInstance(appInstance);
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(Application.class).error("Application.shutdownAppInstance: "+
        e.toString());
    }
    finally
    {
        appLock.writeLock().unlock();
    }
}
```

### Parameters:

appInstance - application instance to remove

---

## shutdownAppInstance

```
public void shutdownAppInstance(String appInstanceName)
```

Shutdown an application instance by name. This will disconnect all clients connected to this application instance.

### Parameters:

appInstanceName - application instance name

---

## readAppConfig

```
public String readAppConfig(String sName)
```

Method to read xml config file..

---

## **writeAppConfig**

```
public boolean writeAppConfig(String sName,  
                               String data)
```

Method to write xml config file..

---

## **getProtocolUsage**

```
public void getProtocolUsage(boolean[] protocolsInUse)
```

Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE\_\*)

## com.wowza.wms.application Interface IApplicationInstance

public interface **IApplicationInstance**  
extends

IApplicationInstance: public interface to ApplicationInstance object

### Field Summary

public static final	<a href="#">DEFAULT_APPINSTANCE_NAME</a> Value: <b>_definst_</b>
public static final	<a href="#">PROTOCOLUSAGE_CUPERTINO</a> Value: <b>7</b>
public static final	<a href="#">PROTOCOLUSAGE_MPEGDASH</a> Value: <b>10</b>
public static final	<a href="#">PROTOCOLUSAGE_ORIGINCUPERTINO</a> Value: <b>15</b>
public static final	<a href="#">PROTOCOLUSAGE_ORIGINMPEGDASH</a> Value: <b>18</b>
public static final	<a href="#">PROTOCOLUSAGE_ORIGINSANJOSE</a> Value: <b>17</b>
public static final	<a href="#">PROTOCOLUSAGE_ORIGINSMOOTH</a> Value: <b>16</b>
public static final	<a href="#">PROTOCOLUSAGE_RTMP</a> Value: <b>0</b>
public static final	<a href="#">PROTOCOLUSAGE_RTMP_E</a> Value: <b>4</b>
public static final	<a href="#">PROTOCOLUSAGE_RTMP_S</a> Value: <b>2</b>
public static final	<a href="#">PROTOCOLUSAGE_RTMP_T</a> Value: <b>1</b>
public static final	<a href="#">PROTOCOLUSAGE_RTMP_T_E</a> Value: <b>5</b>

public static final	<a href="#">PROTOCOLUSAGE_RTPTS</a> Value: <b>3</b>
public static final	<a href="#">PROTOCOLUSAGE_RTP</a> Value: <b>6</b>
public static final	<a href="#">PROTOCOLUSAGE_SANJOSE</a> Value: <b>9</b>
public static final	<a href="#">PROTOCOLUSAGE_SMOOTH</a> Value: <b>8</b>
public static final	<a href="#">PROTOCOLUSAGE_TOTAL</a> Value: <b>19</b>
public static final	<a href="#">PROTOCOLUSAGE_WEBM</a> Value: <b>11</b>
public static final	<a href="#">PROTOCOLUSAGE_WOWZ</a> Value: <b>12</b>
public static final	<a href="#">PROTOCOLUSAGE_WOWZE</a> Value: <b>13</b>
public static final	<a href="#">PROTOCOLUSAGE_WOWZS</a> Value: <b>14</b>

## Method Summary

void	<a href="#">addClientListener</a> ( <a href="#">IClientNotify</a> clientListener) Add client listener.
void	<a href="#">addDvrRecorderListener</a> ( <a href="#">ILiveStreamDvrRecorderActionNotify</a> listener) Add a Dvr Recorder listener (see: <a href="#">ILiveStreamDvrRecorderActionNotify</a> )
void	<a href="#">addDvrStreamManagerListener</a> ( <a href="#">IDvrStreamManagerActionNotify</a> listener) Add a Dvr Application Store Manager listener (see: <a href="#">IDvrStoreActionNotify</a> )
void	<a href="#">addHTTPListener</a> ( <a href="#">IHTTPSessionNotify</a> httpListener) Add listener to be notified of HTTPSession create and destroy.
void	<a href="#">addHTTPStreamerSession</a> ( <a href="#">IHTTPStreamerSession</a> httpStreamerSession) Add a HTTPStreamerSession to this application instance
void	<a href="#">addLiveStreamPacketizerListener</a> ( <a href="#">ILiveStreamPacketizerActionNotify</a> liveStreamPacketizerListener) Add a Live Stream Packetizer listener (see: <a href="#">ILiveStreamPacketizerActionNotify</a> )
void	<a href="#">addLiveStreamTranscoderListener</a> ( <a href="#">ILiveStreamTranscoderNotify</a> liveStreamTranscoderListener) Add a live stream transcoder listener

void	<a href="#"><u>addMediaCasterListener</u></a> ( <a href="#"><u>IMediaCasterNotify</u></a> mediaCasterListener) Add mediaCaster listener.
void	<a href="#"><u>addMediaCasterListener</u></a> ( <a href="#"><u>IMediaCasterNotify2</u></a> mediaCasterListener) Add mediaCaster listener.
void	<a href="#"><u>addMediaReaderListener</u></a> ( <a href="#"><u>IMediaReaderActionNotify</u></a> mediaReaderListener) Add media reader listener.
void	<a href="#"><u>addMediaStreamListener</u></a> ( <a href="#"><u>IMediaStreamNotify</u></a> mediaStreamListener) Add mediaStream listener.
void	<a href="#"><u>addMediaWriterListener</u></a> ( <a href="#"><u>IMediaWriterActionNotify</u></a> listener) Add a MediaWriter listener class.
void	<a href="#"><u>addModuleListener</u></a> ( <a href="#"><u>IModuleNotify</u></a> moduleListener) Add module listener.
void	<a href="#"><u>addPlayStreamByName</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String name) Add a media stream to the list of streams that are listening for a published stream
void	<a href="#"><u>addPublisher</u></a> ( <a href="#"><u>Publisher</u></a> publisher) Add a server side publisher to this application instance
void	<a href="#"><u>addRTPIncomingDatagramPortAll</u></a> () Allow all incoming RTP UDP ports for this application instance
void	<a href="#"><u>addRTPIncomingDatagramPortRange</u></a> (int startPort, int endPort) Add a port range to the list of valid incoming RTP UDP ports
void	<a href="#"><u>addRTPListener</u></a> ( <a href="#"><u>IRTPSessionNotify</u></a> rtpListener) Add listener to be notified of RTPSession create and destroy.
void	<a href="#"><u>addRTPSession</u></a> ( <a href="#"><u>RTPSession</u></a> rtpSession) Add an RTP session to this application instance
void	<a href="#"><u>addSharedObjectListener</u></a> ( <a href="#"><u>ISharedObjectNotify</u></a> sharedObjectListener, boolean isPersistent) Add sharedObject listener.
void	<a href="#"><u>broadcastMsg</u></a> (java.util.List clientList, String handlerName) Broadcast a message to a specific list of clients connected to this application instance
void	<a href="#"><u>broadcastMsg</u></a> (java.util.List clientList, String handlerName, Object[] params) Broadcast a message to a specific list of clients connected to this application instance
void	<a href="#"><u>broadcastMsg</u></a> (String handlerName, Object[] params) Broadcast a message to all clients connected to this applicationInstance
boolean	<a href="#"><u>containsDvrRecorder</u></a> (String dvrRecorder) Does this application instance contain a references to this DVR recorder.
boolean	<a href="#"><u>containsHTTPStreamer</u></a> (String httpStreamer) Does this application instance allow streaming of a given HTTPStreamer
boolean	<a href="#"><u>containsLiveStreamPacketizer</u></a> (String liveStreamPacketizer) Does this application instance contain a references to this live stream packetizer.

boolean	<a href="#"><code>containsLiveStreamTranscoder</code></a> (String liveStreamTranscoder) Return true if this application instance contains the transcoder name
String	<a href="#"><code>decodeStorageDir</code></a> (String storageDir) This function will take a storage path that uses variables and expand the variables based on the context.
String[]	<a href="#"><code>getAllowDomains</code></a> () Get the list of domain names used to control access to this application.
<a href="#"><code>IApplication</code></a>	<a href="#"><code>getApplication</code></a> () Get parent application
int	<a href="#"><code>getApplicationInstanceTouchTimeout</code></a> () Get the application instance touch timeout (milliseconds).
int	<a href="#"><code>getApplicationTimeout</code></a> () Get application timeout (milliseconds)
<a href="#"><code>IClient</code></a>	<a href="#"><code>getClient</code></a> (int index) <b>Deprecated.</b> Get the client connection at index. This method is deprecated. It is best to use <code>getClient()</code> to return a List objects.
<a href="#"><code>IClient</code></a>	<a href="#"><code>getClientById</code></a> (int index) Get a client connection by the client Id
int	<a href="#"><code>getClientCount</code></a> () Get number of client connections currently connected to applicationInstance
int	<a href="#"><code>getClientCountTotal</code></a> () Get number of client connections in total that have connected to this applicationInstance
int	<a href="#"><code>getClientIdleFrequency</code></a> () Get default client idle frequency (milliseconds)
java.util.List	<a href="#"><code>getClients</code></a> () Get the set of clients currently connected to this application instance (replaces <code>getClient(index)</code> )
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<a href="#"><code>getClientsLockObj</code></a> () Get the read/write lock for this application instance
<a href="#"><code>ConnectionCounter</code></a>	<a href="#"><code>getConnectionCounter</code></a> () Get the connectionCounter for applicationInstance
ConnectionCounterSimple	<a href="#"><code>getConnectionCounter</code></a> (int counterIndex) Get the connectionCounter for applicationInstance for a specific technology (see <code>IVHost.COUNTER_*</code> )
String	<a href="#"><code>getContextStr</code></a> () Returns the application context string in the form [application]/[appInstance].
String	<a href="#"><code>getDateStarted</code></a> () Get date applicationInstance started
DvrApplicationContext	<a href="#"><code>getDvrApplicationContext</code></a> () Get live stream dvr application context
<a href="#"><code>WMSProperties</code></a>	<a href="#"><code>getDvrProperties</code></a> () Get the property collection of DVR settings that are specific to this application instance.



String	<a href="#"><u>getDvrRecorderList()</u></a> Get the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)
<a href="#"><u>IHTTPStreamerApplicationContext</u></a>	<a href="#"><u>getHTTPStreamerApplicationContext(String httpStreamName, boolean doCreate)</u></a> Get the HTTPStreamer application context for a given HTTPStreamer adapter
String	<a href="#"><u>getHTTPStreamerList()</u></a> Get the comma separated list of HTTPStreamers names being used by this application (see conf/HTTPStreamers.xml)
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getHTTPStreamerProperties()</u></a> Get the property collection of HTTPStreamer settings that are specific to this application instance
int	<a href="#"><u>getHTTPStreamerSessionCount()</u></a> Get the current number of HTTPStreamerSessions associated with this application instance
int	<a href="#"><u>getHTTPStreamerSessionCount(int protocol)</u></a> Get the current number of HTTPStreamerSessions associated with this application instance by protocol.
int	<a href="#"><u>getHTTPStreamerSessionCount(int protocol, String streamName)</u></a> Get the current number of HTTPStreamerSessions associated with this application instance and stream name by protocol .
int	<a href="#"><u>getHTTPStreamerSessionCount(String streamName)</u></a> Get the current number of HTTPStreamerSessions associated with this application instance and stream name
java.util.Map	<a href="#"><u>getHTTPStreamerSessionCountsByName(int protocol)</u></a> Get a map of session counts by name for a given protocol
java.util.List	<a href="#"><u>getHTTPStreamerSessions()</u></a> Get the HTTPStreamerSessions associated with this application instance
java.util.List	<a href="#"><u>getHTTPStreamerSessions(int protocol)</u></a> Get the HTTPStreamerSessions associated with this application instance by protocol.
java.util.List	<a href="#"><u>getHTTPStreamerSessions(int protocol, String streamName)</u></a> Get the HTTPStreamerSessions associated with this application instance for a stream name by protocol.
java.util.List	<a href="#"><u>getHTTPStreamerSessions(String streamName)</u></a> Get the HTTPStreamerSessions associated with this application instance for a stream name
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getIOPerformanceCounter()</u></a> Get the performance counter for applicationInstance
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getIOPerformanceCounter(int counterIndex)</u></a> Get the performance counter for applicationInstance for a specific technology (see IVHost.COUNTER_*)
long	<a href="#"><u>getLastTouchTime()</u></a> Get the last time the instance was touched (milliseconds)
<a href="#"><u>ILiveStreamDvrRecorderControl</u></a>	<a href="#"><u>getLiveStreamDvrRecorderControl()</u></a> Get the Live Stream DVR Recorder Controller.

<a href="#"><u>ILiveStreamPacketizerControl</u></a>	<a href="#"><u>getLiveStreamPacketizerControl()</u></a> Get the Live Stream Packetizer Controller.
String	<a href="#"><u>getLiveStreamPacketizerList()</u></a> Get the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getLiveStreamPacketizerProperties()</u></a> Get the property collection of LiveStreamPacketizer settings that are specific to this application instance
<a href="#"><u>ILiveStreamTranscoderControl</u></a>	<a href="#"><u>getLiveStreamTranscoderControl()</u></a> Get the Live Stream Transcoder Controller.
String	<a href="#"><u>getLiveStreamTranscoderList()</u></a> Get comma separated list of transcoders to use for this application instance
int	<a href="#"><u>getMaximumPendingReadBytes()</u></a> Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
int	<a href="#"><u>getMaximumPendingWriteBytes()</u></a> Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
int	<a href="#"><u>getMaximumSetBufferTime()</u></a> Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
int	<a href="#"><u>getMaxStorageDirDepth()</u></a> Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getMediaCasterProperties()</u></a> Get the property collection of media caster settings that are specific to this application instance
int	<a href="#"><u>getMediacasterRTPRTSPRTPTTransportMode()</u></a> RTP MediaCaster RTSP/RTP transport mode.
<a href="#"><u>MediaCasterStreamMap</u></a>	<a href="#"><u>getMediaCasterStreams()</u></a> Get the media caster streams attached to this application instance
<a href="#"><u>IMediaCasterValidateMediaCaster</u></a>	<a href="#"><u>getMediaCasterValidator()</u></a> Get the MediaCaster validator interface for this application instance
<a href="#"><u>IMediaListProvider</u></a>	<a href="#"><u>getMediaListProvider()</u></a> Get the current media list provider.
int	<a href="#"><u>getMediaReaderContentType()</u></a> (String mediaType) Get the content type of a media stream name prefix (see IMediaReader.CONTENT'TYPE_*)
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getMediaReaderProperties()</u></a> Get the property collection of media reader settings that are specific to this application instance
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getMediaWriterProperties()</u></a> Get the property collection of media reader settings that are specific to this application instance
ModuleFunctions	<a href="#"><u>getModFunctions()</u></a> Get list of application modules
Object	<a href="#"><u>getModuleInstance()</u></a> (String name) Get the instance of the module class for this application instance.

ModuleList	<a href="#"><u>getModuleList()</u></a> Get the list of loaded modules.
String	<a href="#"><u>getName()</u></a> Get applicationInstance name
int	<a href="#"><u>getPingTimeout()</u></a> Get ping timeout (milliseconds)
int	<a href="#"><u>getPlayStreamCount(String streamName)</u></a> Get the number of Flash players playing a given stream name
java.util.Map	<a href="#"><u>getPlayStreamCountsByName()</u></a> Get a map of stream names to number of Flash players playing the stream name
java.util.List	<a href="#"><u>getPlayStreamsByName(String name)</u></a> Get a list of media streams that are listening for published stream.
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties()</u></a> Get applicationInstance properties
boolean[]	<a href="#"><u>getProtocolUsage()</u></a> Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE_*)
void	<a href="#"><u>getProtocolUsage(boolean[] protocolsInUse)</u></a> Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE_*)
int	<a href="#"><u>getPublisherCount()</u></a> Get the current number of server side publishers
java.util.List	<a href="#"><u>getPublishers()</u></a> Get the set of server side publishers
java.util.List	<a href="#"><u>getPublishStreamNames()</u></a> Get the list of live stream names currently being published.
String	<a href="#"><u>getRepeaterOriginUrl()</u></a> Get the Repeater Origin URL used by the Live Stream Repeater
String	<a href="#"><u>getRepeaterQueryString()</u></a> Get the Repeater query string that is used to connect to the origin.
String	<a href="#"><u>getRsoStorageDir()</u></a> Get remote shared object storage path
String	<a href="#"><u>getRsoStoragePath()</u></a> Get the resolved storage path to the shared objects
int	<a href="#"><u>getRTPAVSyncMethod()</u></a> Get RTP audio/video sync method (RTPStream.AVSYNCMETHODS_SENDERREPORT, RTPStream.AVSYNCMETHODS_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS_RTPTIMECODE)
int	<a href="#"><u>getRTPIidleFrequency()</u></a> Set the default RTP idle frequency (milliseconds)
int	<a href="#"><u>getRTPMaxRTCPWaitTime()</u></a> Get the maximum time to wait for RTCP packets (milliseconds)

String	<a href="#"><u>getRTPPlayAuthenticationMethod()</u></a> Get the RTP play authentication method (as defined in conf/Authentication.xml)
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getRTPProperties()</u></a> Get the property collection of RTP settings that are specific to this application instance
String	<a href="#"><u>getRTPPublishAuthenticationMethod()</u></a> Get the RTP publish authentication method (as defined in conf/Authentication.xml)
int	<a href="#"><u>getRTPSessionCount()</u></a> Get the number of RTP sessions running under this application instance
int	<a href="#"><u>getRTPSessionCount(String streamName)</u></a> Get the number of RTP player streams playing a given stream name
java.util.Map	<a href="#"><u>getRTPSessionCountsByName()</u></a> Get a map of stream names and session counts of RTP sessions
java.util.List	<a href="#"><u>getRTPSessions()</u></a> Get a list of RTP sessions running under this application instance
java.util.List	<a href="#"><u>getRTPSessions(String streamName)</u></a> Get a list of RTP sessions running under this application instance playing a given stream name
String	<a href="#"><u>getRTSPBindIpAddress()</u></a> Set the IP address to which UDP ports will be bound for RTSP/RTP sessions
String	<a href="#"><u>getRTSPConnectionAddressType()</u></a> Get the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
String	<a href="#"><u>getRTSPConnectionIpAddress()</u></a> Get the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
int	<a href="#"><u>getRTSPMaximumPendingWriteBytes()</u></a> Get the maximum number of pending write bytes for an RTSP session
String	<a href="#"><u>getRTSPOriginAddressType()</u></a> Get the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
String	<a href="#"><u>getRTSPOriginIpAddress()</u></a> Get the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
int	<a href="#"><u>getRTSPSessionTimeout()</u></a> Get the RTSP session timeout (milliseconds)
String	<a href="#"><u>getSharedObjectReadAccess()</u></a> Get the default shared object read access
<a href="#"><u>ISharedObjects</u></a>	<a href="#"><u>getSharedObjects()</u></a> Get non-persistent shared object collection
<a href="#"><u>ISharedObjects</u></a>	<a href="#"><u>getSharedObjects(boolean isPersistent)</u></a> Get either persistent or non-persistent shared object collection
String	<a href="#"><u>getSharedObjectWriteAccess()</u></a> Get the default shared object write access

String	<a href="#"><u>getStreamAudioSampleAccess()</u></a> Get the default stream audio sample access
int	<a href="#"><u>getStreamCount()</u></a> Get the total number of open streams attached to this application instance
<a href="#"><u>IMediaStreamFileMapper</u></a>	<a href="#"><u>getStreamFileMapper()</u></a> Get the stream file mapper.
String	<a href="#"><u>getStreamKeyDir()</u></a> Get the stream key path
String	<a href="#"><u>getStreamKeyPath()</u></a> Get the resolved key path to the MediaStreams encryption keys
<a href="#"><u>IMediaStreamNameAliasProvider</u></a>	<a href="#"><u>getStreamNameAliasProvider()</u></a> Get the stream name alias provider
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getStreamProperties()</u></a> Get the property collection of stream settings that are specific to this application instance
String	<a href="#"><u>getStreamReadAccess()</u></a> Get the default stream read access
<a href="#"><u>MediaStreamMap</u></a>	<a href="#"><u>getStreams()</u></a> Get all the mediaStream objects attached to this applicationInstance
String	<a href="#"><u>getStreamStorageDir()</u></a> Get stream storage path
String	<a href="#"><u>getStreamStoragePath()</u></a> Get the resolved storage path to the MediaStreams
String	<a href="#"><u>getStreamType()</u></a> Get default streamType for application.
String	<a href="#"><u>getStreamVideoSampleAccess()</u></a> Get the default stream video sample access
String	<a href="#"><u>getStreamWriteAccess()</u></a> Get the default stream write access
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getTimedTextProperties()</u></a> Get the property collection of timed text settings that are specific to this application instance.
String	<a href="#"><u>getTimeRunning()</u></a> Get time applicationInstance running
double	<a href="#"><u>getTimeRunningSeconds()</u></a> Get time running in seconds
<a href="#"><u>LiveStreamTranscoderApplicationContext</u></a>	<a href="#"><u>getTranscoderApplicationContext()</u></a> Get live stream transcoder application context
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getTranscoderProperties()</u></a> Get the property collection of Transcoder settings that are specific to this application instance
int	<a href="#"><u>getValidationFrequency()</u></a> Get time between validation pings (milliseconds)

<a href="#">IVHost</a>	<a href="#">getVHost()</a> Get parent vHost
String	<a href="#">getVODTimedTextProviderList()</a> Get the comma separated list of VODTimedTextProvider names being used by this application (see conf/TimedTextProviders.xml)
java.util.List	<a href="#">getVODTimedTextProviderSet()</a>
void	<a href="#">incClientCountTotal()</a> Increment the total number of connected client counter by one
boolean	<a href="#">isAcceptConnection()</a> Is auto accept connection on/off
boolean	<a href="#">isDebugAppTimeout()</a> If true appTimeout processing will be logged.
boolean	<a href="#">isRTPIncomingDatagramPortValid(int port)</a> Check a port number to be sure it is a valid RTP UDP port for this application instance
boolean	<a href="#">isValidateFMLEConnections()</a> Returns true if validating FMLE connection (default is false)
void	<a href="#">notifyDvrStreamManagerCreate(IDvrStreamManager dvrStoreManager)</a> Notify listeners that Dvr Application Store Manager has been created.
void	<a href="#">notifyDvrStreamManagerDestroy(IDvrStreamManager dvrManager)</a> Notify listeners that Dvr Application Store Manager has been destroyed.
void	<a href="#">notifyDvrStreamManagerInit(IDvrStreamManager dvrStoreManager)</a> Notify listeners that Dvr Application Store Manager has been initialized.
void	<a href="#">notifyHTTPSessionCreate(IHTTPStreamerSession httpSession)</a> Notify HTTP session create
void	<a href="#">notifyHTTPSessionDestroy(IHTTPStreamerSession httpSession)</a> Notify HTTP session destroy
void	<a href="#">notifyLiveStreamDvrRecorderCreate(ILiveStreamDvrRecorder dvr, String streamName)</a> Notify Dvr Recorder Create
void	<a href="#">notifyLiveStreamDvrRecorderDestroy(ILiveStreamDvrRecorder dvr)</a> Notify DVR Recorder has been destroyed.
void	<a href="#">notifyLiveStreamDvrRecorderInit(ILiveStreamDvrRecorder dvr, String streamName)</a> Notify DVR Recorder has been initialized.
void	<a href="#">notifyLiveStreamPacketizerCreate(ILiveStreamPacketizer LiveStreamPacketizer, String streamName)</a> Notify Live Stream Packetizer Create
void	<a href="#">notifyLiveStreamPacketizerDestroy(ILiveStreamPacketizer LiveStreamPacketizer)</a> Notify Live Stream Packetizer Destory

void	<a href="#"><u>notifyLiveStreamPacketizerInit(ILiveStreamPacketizer liveStreamPacketizer, String streamName)</u></a> Notify Live Stream Packetizer Init
void	<a href="#"><u>notifyLiveStreamTranscoderCreate(ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream)</u></a> Notify live stream transcoder create
void	<a href="#"><u>notifyLiveStreamTranscoderDestroy(ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream)</u></a> Notify live stream transcoder destroy
void	<a href="#"><u>notifyLiveStreamTranscoderInit(ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream)</u></a> Notify live stream transcoder init
void	<a href="#"><u>notifyMediaReaderClose(IMediaReader mediaReader, IMediaStream stream)</u></a> Notify media reader notifyMediaReaderClose
void	<a href="#"><u>notifyMediaReaderCreate(IMediaReader mediaReader)</u></a> Notify media reader notifyMediaReaderCreate
void	<a href="#"><u>notifyMediaReaderExtractMetadata(IMediaReader mediaReader, IMediaStream stream)</u></a> Notify media reader notifyMediaReaderExtractMetadata
void	<a href="#"><u>notifyMediaReaderInit(IMediaReader mediaReader, IMediaStream stream)</u></a> Notify media reader notifyMediaReaderInit
void	<a href="#"><u>notifyMediaReaderOpen(IMediaReader mediaReader, IMediaStream stream)</u></a> Notify media reader notifyMediaReaderOpen
void	<a href="#"><u>notifyMediaWriterOnFLVAddMetadata(IMediaStream stream, java.util.Map extraMetadata)</u></a> Notify all MediaWriter listeners of onFLVAddMetadata
void	<a href="#"><u>notifyMediaWriterOnWriteComplete(IMediaStream stream, java.io.File file)</u></a> Notify all MediaWriter listeners of onWriteComplete
void	<a href="#"><u>notifyRTPSessionCreate(RTPSession rtpSession)</u></a> Notify RTP session create
void	<a href="#"><u>notifyRTPSessionDestroy(RTPSession rtpSession)</u></a> Notify RTP session destroy
void	<a href="#"><u>parseAllowDomains(String domainFilterStr)</u></a> Parse a comma delimited list of domain names used to control access to this application.
String	<a href="#"><u>readAppInstConfig(String sName)</u></a> Method to read xml config file..
void	<a href="#"><u>registerPlayRTPSession(RTPSession rtpSession)</u></a> Register an RTP session as a play session
void	<a href="#"><u>removeClientListener(IClientNotify clientListener)</u></a> Remove client listener.
void	<a href="#"><u>removeDvrRecorderListener(ILiveStreamDvrRecorderActionNotify listener)</u></a> Remove a Dvr Recorder listener (see: ILiveStreamDvrRecorderActionNotify)

void	<a href="#">removeDvrStreamManagerListener</a> ( <a href="#">IDvrStreamManagerActionNotify</a> listener) Remove a Dvr Application Store Manager listener (see: IDvrStoreActionNotify)
void	<a href="#">removeHTTPListener</a> ( <a href="#">IHTTPSessionNotify</a> httpListener) Remove listner to be notified of HTTPSession create and destroy.
void	<a href="#">removeHTTPStreamerSession</a> ( <a href="#">IHTTPStreamerSession</a> httpStreamerSession) Remove a HTTPStreamerSession from this application instance
void	<a href="#">removeLiveStreamPacketizerListener</a> ( <a href="#">ILiveStreamPacketizerActionNotify</a> liveStreamPacketizerListener) Remove a Live Stream Packetizer listener (see: ILiveStreamPacketizerActionNotify)
void	<a href="#">removeLiveStreamTranscoderListener</a> ( <a href="#">ILiveStreamTranscoderNotify</a> liveStreamTranscoderListener) Remove a live stream transcoder listener
void	<a href="#">removeMediaCasterListener</a> ( <a href="#">IMediaCasterNotify</a> mediaCasterListener) Remove mediaCaster listener.
void	<a href="#">removeMediaReaderListener</a> ( <a href="#">IMediaReaderActionNotify</a> mediaReaderListener) Remove media reader listener.
void	<a href="#">removeMediaStreamListener</a> ( <a href="#">IMediaStreamNotify</a> mediaStreamListener) Remove mediaStream listener.
void	<a href="#">removeMediaWriterListener</a> ( <a href="#">IMediaWriterActionNotify</a> listener) remove MediaWriter listener class.
void	<a href="#">removeModuleListener</a> ( <a href="#">IModuleNotify</a> moduleListener) Remove module listener
void	<a href="#">removePlayStreamByName</a> ( <a href="#">IMediaStream</a> stream) Remove media stream from the list of streams that are listening for a published stream
void	<a href="#">removePublisher</a> ( <a href="#">Publisher</a> publisher) Remove a server side publisher from this application instance
void	<a href="#">removeRTPListener</a> ( <a href="#">IRTPSessionNotify</a> rtpListener) Remove listner to be notified of RTPSession create and destroy.
void	<a href="#">removeRTPSession</a> ( <a href="#">RTPSession</a> rtpSession) Remove an RTP session from this application instance
void	<a href="#">removeSharedObjectListener</a> ( <a href="#">ISharedObjectNotify</a> sharedObjectListener, boolean isPersistent) Remove sharedObject listener.
boolean	<a href="#">resetMediaCasterStream</a> (String streamName) Reset a media caster stream
boolean	<a href="#">resetMediaCasterStream</a> (String streamName, String streamExt) Reset a media caster stream
void	<a href="#">setAcceptConnection</a> (boolean acceptConnection) Set is auto accept connection
void	<a href="#">setAllowDomains</a> (String[] domainFilter) Set the list of domain names used to control access to this application.



void	<a href="#"><u>setApplicationInstanceTouchTimeout</u></a> (int applicationInstanceTouchTimeout) Set the application instance touch timeout (milliseconds).
void	<a href="#"><u>setApplicationTimeout</u></a> (int applicationTimeout) Set application timeout (milliseconds)
void	<a href="#"><u>setClientIdleFrequency</u></a> (int clientIdleFrequency) Set default client idle frequency (milliseconds)
void	<a href="#"><u>setDebugAppTimeout</u></a> (boolean debugAppTimeout) If true appTimeout processing will be logged.
void	<a href="#"><u>setDvrRecorderList</u></a> (String recorderList) Set the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)
void	<a href="#"><u>setHTTPStreamerList</u></a> (String httpStreamerList) Set the comma separated list of HTTPStreamer names being used by this application (see conf/HTTPStreamers.xml)
void	<a href="#"><u>setLiveStreamDvrRecorderControl</u></a> ( <a href="#"><u>ILiveStreamDvrRecorderControl</u></a> controller) Set the Live Stream DVR Controller.
void	<a href="#"><u>setLiveStreamPacketizerControl</u></a> ( <a href="#"><u>ILiveStreamPacketizerControl</u></a> liveStreamPacketizerControl) Set the Live Stream Packetizer Contoller.
void	<a href="#"><u>setLiveStreamPacketizerList</u></a> (String liveStreamPacketizerList) Set the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)
void	<a href="#"><u>setLiveStreamTranscoderControl</u></a> ( <a href="#"><u>ILiveStreamTranscoderControl</u></a> liveStreamTranscoderControl) Set the Live Stream Transcoder Contoller.
void	<a href="#"><u>setLiveStreamTranscoderList</u></a> (String liveStreamTranscoderList) Set comma separated list of transcoders to use for this application instance
void	<a href="#"><u>setMaximumPendingReadBytes</u></a> (int maximumPendingReaderBytes) Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
void	<a href="#"><u>setMaximumPendingWriteBytes</u></a> (int maximumPendingWriteBytes) Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
void	<a href="#"><u>setMaximumSetBufferTime</u></a> (int maximumSetBufferTime) Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
void	<a href="#"><u>setMaxStorageDirDepth</u></a> (int maxStorageDirDepth) Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths
void	<a href="#"><u>setMediacasterRTPRTSPRTPTransportMode</u></a> (int mediacasterRTPRTSPRTPTransportMode) RTP MediaCaster RTSP/RTP transport mode.
void	<a href="#"><u>setMediaCasterValidator</u></a> ( <a href="#"><u>IMediaCasterValidateMediaCaster</u></a> mediaCasterValidator) Set the MediaCaster validator interface for this application instance

void	<a href="#"><u>setMediaListProvider</u></a> ( <a href="#"><u>IMediaListProvider</u></a> mediaListProvider) Set the current media list provider.
void	<a href="#"><u>setName</u></a> (String name) Set applicationInstance name
void	<a href="#"><u>setPingTimeout</u></a> (int pingTimeout) Set ping timeout (milliseconds)
void	<a href="#"><u>setRepeaterOriginUrl</u></a> (String repeaterOriginUrl) Set the Repeater Origin URL used by the Live Stream Repeater
void	<a href="#"><u>setRepeaterQueryString</u></a> (String repeaterQueryString) Set the Repeater query string that is used to connect to the origin.
void	<a href="#"><u>setRsoStorageDir</u></a> (String rsoStorageDir) Set remote shared object storage path
void	<a href="#"><u>setRTPAVSyncMethod</u></a> (int rtpAVSyncMethod) Set RTP audio/video sync method (RTPStream.AVSYNCMETHODS_SENDERREPORT, RTPStream.AVSYNCMETHODS_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS_RTPTIMECODE)
void	<a href="#"><u>setRTPIIdleFrequency</u></a> (int rtspIdleFrequency) Get the default RTP idle frequency (milliseconds)
void	<a href="#"><u>setRTPMaxRTCPWaitTime</u></a> (int rtpMaxRTCPWaitTime) Set the maximum time to wait for RTCP packets (milliseconds)
void	<a href="#"><u>setRTPPlayAuthenticationMethod</u></a> (String rtpPlayAuthenticationMethod) Set the RTP play authentication method (as defined in conf/Authentication.xml)
void	<a href="#"><u>setRTPPublishAuthenticationMethod</u></a> (String rtpPublishAuthenticationMethod) Set the RTP publish authentication method (as defined in conf/Authentication.xml)
void	<a href="#"><u>setRTSPBindIpAddress</u></a> (String rtspBindIpAddress) Get the IP address to which UDP ports will be bound for RTSP/RTP sessions
void	<a href="#"><u>setRTSPConnectionAddressType</u></a> (String rtspConnectionAddressType) Set the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<a href="#"><u>setRTSPConnectionIpAddress</u></a> (String rtspConnectionIpAddress) Set the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<a href="#"><u>setRTSPMaximumPendingWriteBytes</u></a> (int rtspMaximumPendingWriteBytes) Set the maximum number of pending write bytes for an RTSP session
void	<a href="#"><u>setRTSPOriginAddressType</u></a> (String rtspOriginAddressType) Set the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<a href="#"><u>setRTSPOriginIpAddress</u></a> (String rtspOriginIpAddress) Set the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<a href="#"><u>setRTSPSessionTimeout</u></a> (int rtspSessionTimeout) Set the RTSP session timeout (milliseconds)

void	<a href="#"><u>setSharedObjectReadAccess</u></a> (String sharedObjectReadAccess) Set the default shared object read access
void	<a href="#"><u>setSharedObjectWriteAccess</u></a> (String sharedObjectWriteAccess) Set the default shared object write access
void	<a href="#"><u>setStreamAudioSampleAccess</u></a> (String streamAudioSampleAccess) Set the default stream audio sample access
void	<a href="#"><u>setStreamFileMapper</u></a> ( <a href="#"><u>IMediaStreamFileMapper</u></a> streamFileMapper) Set the stream file mapper.
void	<a href="#"><u>setStreamKeyDir</u></a> (String keyStorageDir) Set the stream key path
void	<a href="#"><u>setStreamNameAliasProvider</u></a> ( <a href="#"><u>IMediaStreamNameAliasProvider</u></a> streamNameAliasProvider) Set the stream name alias provider
void	<a href="#"><u>setStreamReadAccess</u></a> (String streamReadAccess) Set the default stream read access
void	<a href="#"><u>setStreamStorageDir</u></a> (String streamStorageDir) Set stream storage path
void	<a href="#"><u>setStreamType</u></a> (String streamType) Set default stream type for application.
void	<a href="#"><u>setStreamVideoSampleAccess</u></a> (String streamVideoSampleAccess) Set the default stream video sample access
void	<a href="#"><u>setStreamWriteAccess</u></a> (String streamWriteAccess) Set the default stream write access
void	<a href="#"><u>setValidateFMLEConnections</u></a> (boolean validateFMLEConnections) Returns true if validating FMLE connection (default is false)
void	<a href="#"><u>setValidationFrequency</u></a> (int validationFrequency) Set time between validation pings (milliseconds)
void	<a href="#"><u>setVODTimedTextProviderList</u></a> (String timedTextProviderList) Set the comma separated list of VODTimedTextProvider names being used by this application (see conf/TimedTextProviders.xml)
void	<a href="#"><u>shutdown</u></a> (boolean isServerShutdown, boolean isAppShutdown) shutdown applicationInstance
void	<a href="#"><u>shutdownClient</u></a> ( <a href="#"><u>IClient</u></a> client) shutdown a client connection immediately
boolean	<a href="#"><u>startMediaCasterStream</u></a> (String streamName, String mediaCasterType) Start a media caster stream
boolean	<a href="#"><u>startMediaCasterStream</u></a> (String streamName, String streamExt, String mediaCasterType) Start a media caster stream
void	<a href="#"><u>stopMediaCasterStream</u></a> (String streamName) Stop a media caster stream

void	<a href="#">touch()</a> Touch the application instance so that it stays loaded for at least applicationInstanceTouchTimeout
boolean	<a href="#">writeAppInstConfig(String sName, String data)</a> Method to write xml config file..

## Fields

### PROTOCOLUSAGE\_RTMP

```
public static final int PROTOCOLUSAGE_RTMP
```

Constant value: **0**

### PROTOCOLUSAGE\_RTMPT

```
public static final int PROTOCOLUSAGE_RTMPT
```

Constant value: **1**

### PROTOCOLUSAGE\_RTMPS

```
public static final int PROTOCOLUSAGE_RTMPS
```

Constant value: **2**

### PROTOCOLUSAGE\_RTMPTS

```
public static final int PROTOCOLUSAGE_RTMPTS
```

Constant value: **3**

### PROTOCOLUSAGE\_RTMPE

```
public static final int PROTOCOLUSAGE_RTMPE
```

Constant value: **4**

### PROTOCOLUSAGE\_RTMPTE

```
public static final int PROTOCOLUSAGE_RTMPTE
```

Constant value: **5**

### PROTOCOLUSAGE\_RTP

```
public static final int PROTOCOLUSAGE_RTP
```

Constant value: **6**

---

## PROTOCOLUSAGE\_CUPERTINO

```
public static final int PROTOCOLUSAGE_CUPERTINO
```

Constant value: **7**

---

## PROTOCOLUSAGE\_SMOOTH

```
public static final int PROTOCOLUSAGE_SMOOTH
```

Constant value: **8**

---

## PROTOCOLUSAGE\_SANJOSE

```
public static final int PROTOCOLUSAGE_SANJOSE
```

Constant value: **9**

---

## PROTOCOLUSAGE\_MPEGDASH

```
public static final int PROTOCOLUSAGE_MPEGDASH
```

Constant value: **10**

---

## PROTOCOLUSAGE\_WEBM

```
public static final int PROTOCOLUSAGE_WEBM
```

Constant value: **11**

---

## PROTOCOLUSAGE\_WOWZ

```
public static final int PROTOCOLUSAGE_WOWZ
```

Constant value: **12**

---

## PROTOCOLUSAGE\_WOWZE

```
public static final int PROTOCOLUSAGE_WOWZE
```

Constant value: **13**

---

## PROTOCOLUSAGE\_WOWZS

```
public static final int PROTOCOLUSAGE_WOWZS
```

Constant value: **14**

---

(continued from last page)

---

## PROTOCOLUSAGE\_ORIGINCUPERTINO

```
public static final int PROTOCOLUSAGE_ORIGINCUPERTINO
```

Constant value: **15**

---

## PROTOCOLUSAGE\_ORIGINSMOOTH

```
public static final int PROTOCOLUSAGE_ORIGINSMOOTH
```

Constant value: **16**

---

## PROTOCOLUSAGE\_ORIGINSANJOSE

```
public static final int PROTOCOLUSAGE_ORIGINSANJOSE
```

Constant value: **17**

---

## PROTOCOLUSAGE\_ORIGINMPEGDASH

```
public static final int PROTOCOLUSAGE_ORIGINMPEGDASH
```

Constant value: **18**

---

## PROTOCOLUSAGE\_TOTAL

```
public static final int PROTOCOLUSAGE_TOTAL
```

Constant value: **19**

---

## DEFAULT\_APPINSTANCE\_NAME

```
public static final java.lang.String DEFAULT_APPINSTANCE_NAME
```

Constant value: **\_definst\_**

## Methods

### shutdownClient

```
public void shutdownClient(IClient client)
```

shutdown a client connection immediately

**Parameters:**

client - client connection

---

### shutdown

```
public void shutdown(boolean isServerShutdown,  
                     boolean isAppShutdown)
```

shutdown applicationInstance

---

(continued from last page)

**Parameters:**

isServerShutdown - true if due to shutdown of server  
isAppShutdown - true if due to shutdown of application

---

## getApplication

```
public IApplication getApplication()
```

Get parent application

**Returns:**

parent application

---

## getName

```
public String getName()
```

Get applicationInstance name

**Returns:**

applicationInstance name

---

## setName

```
public void setName(String name)
```

Set applicationInstance name

**Parameters:**

name - applicationInstance name

---

## getStreams

```
public MediaStreamMap getStreams()
```

Get all the mediaStream objects attached to this applicationInstance

## Get Stream By StreamId

```
IClient client;  
int streamId;  
  
MediaStreamMap streams = client.getAppInstance().getStreams();  
IMediaStream stream = streams.getStream((IClient)null, streamId);
```

**Returns:**

collection of mediaStream objects

## getVHost

```
public IVHost getVHost()
```

Get parent vHost

**Returns:**

parent vHost

---

## getProperties

```
public WMSProperties getProperties()
```

Get applicationInstance properties

**Returns:**

applicationInstance properties

---

## getStreamType

```
public String getStreamType()
```

Get default streamType for application.

**Returns:**

streamType name

---

## setStreamType

```
public void setStreamType(String streamType)
```

Set default stream type for application.

**Parameters:**

streamType - streamType name

---

## isAcceptConnection

```
public boolean isAcceptConnection()
```

Is auto accept connection on/off

**Returns:**

auto accept connection

---

## setAcceptConnection

```
public void setAcceptConnection(boolean acceptConnection)
```

Set is auto accept connection

**Parameters:**

acceptConnection - auto accept connection

---

## getClientCountTotal

```
public int getClientCountTotal()
```

---



(continued from last page)

Get number of client connections in total that have connected to this applicationInstance

**Returns:**

number of client connections

---

## incClientCountTotal

```
public void incClientCountTotal()
```

Increment the total number of connected client counter by one

---

## getClientCount

```
public int getClientCount()
```

Get number of client connections currently connected to applicationInstance

**Returns:**

number of client connections

---

## getClientById

```
public IClient getClientById(int index)
```

Get a client connection by the client Id

**Parameters:**

index - client Id

**Returns:**

client connection

---

## getClients

```
public java.util.List getClients()
```

Get the set of clients currently connected to this application instance (replaces getClient(index))

**Returns:**

set of clients

---

## getClient

```
public IClient getClient(int index)
```

**Deprecated.** *Get the client connection at index. This method is deprecated. It is best to use getClient() to return a List objects.*

**Parameters:**

index - index

**Returns:**

client connection

---

## getSharedObjects

```
public ISharedObjects getSharedObjects()
```

(continued from last page)

Get non-persistent shared object collection

**Returns:**

collection of non-persistent shared objects

---

## getSharedObjects

```
public ISharedObjects getSharedObjects(boolean isPersistent)
```

Get either persistent or non-persistent shared object collection

**Parameters:**

isPersistent

**Returns:**

collection of shared objects

---

## addClientListener

```
public void addClientListener(IClientNotify clientListener)
```

(continued from last page)

Add client listener. Listens for connects, disconnect, accepts and reject

## Add a Client Listener

```
IApplicationInstance appInstance;

class ClientListener implements IClientNotify
{
    public void onClientConnect(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientConnect: "+
            client.getClientId());
    }

    public void onClientDisconnect(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientDisconnect: "+
            client.getClientId());
    }

    public void onClientAccept(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientAccept: "+
            client.getClientId());
    }

    public void onClientReject(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientReject: "+
            client.getClientId());
    }
}

appInstance.addClientListener(new ClientListener());
```

### Parameters:

clientListener - client listener

---

## removeClientListener

```
public void removeClientListener(IClientNotify clientListener)
```

Remove client listener. Listens for connects, disconnect, accepts and reject

### Parameters:

clientListener - client listener

## addMediaStreamListener

public void **addMediaStreamListener**([IMediaStreamNotify](#) mediaStreamListener)

Add mediaStream listener. Listens for create and destroy

### Add a MediaStream Listener

```
IApplicationInstance appInstance;

class MediaStreamListener implements IMediaStreamNotify
{
    public void onMediaStreamCreate(IMediaStream stream)
    {
        WMSLoggerFactory.getLogger(null).debug("onMediaStreamCreate: "+
            stream.getSrc());
    }

    public void onMediaStreamDestroy(IMediaStream stream)
    {
        WMSLoggerFactory.getLogger(null).debug("onMediaStreamDestroy: "+
            stream.getSrc());
    }
}

appInstance.addMediaStreamListener(new MediaStreamListener());
```

#### Parameters:

mediaStreamListener - mediaStream listener

---

## removeMediaStreamListener

public void **removeMediaStreamListener**([IMediaStreamNotify](#) mediaStreamListener)

Remove mediaStream listener. Listens for create and destroy

#### Parameters:

mediaStreamListener - mediaStream listener

---

## addSharedObjectListener

public void **addSharedObjectListener**([ISharedObjectNotify](#) sharedObjectListener,  
boolean isPersistent)

(continued from last page)

Add sharedObject listener. Listens for create, destroy, clientConnect, clientDisconnect

## Add SharedObject Listener

```
IApplicationInstance appInstance;

class SharedObjectListener implements ISharedObjectNotify
{
    public void onSharedObjectCreate(ISharedObject sharedObject)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectCreate: "+
            sharedObject.getName());
    }

    public void onSharedObjectDestroy(ISharedObject sharedObject)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectDestroy: "+
            sharedObject.getName());
    }

    public void onSharedObjectConnect(ISharedObject sharedObject, IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectConnect: "+
            sharedObject.getName());
    }

    public void onSharedObjectDisconnect(ISharedObject sharedObject, IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectDisconnect: "+
            sharedObject.getName());
    }
}

appInstance.addSharedObjectListener(new SharedObjectListener(), false);
```

### Parameters:

sharedObjectListener - sharedObject listener  
isPersistent

## removeSharedObjectListener

```
public void removeSharedObjectListener(ISharedObjectNotify sharedObjectListener,
    boolean isPersistent)
```

Remove sharedObject listener. Listens for create, destroy, clientConnect, clientDisconnect

### Parameters:

(continued from last page)

sharedObjectListener - sharedObject listener  
isPersistent

---

## addMediaCasterListener

```
public void addMediaCasterListener(IMediaCasterNotify mediaCasterListener)
```

Add mediaCaster listener. Listens for create, destroy, registerPlayer, unregisterPlayer, setSourceStream

**Parameters:**

mediaCasterListener

---

## addMediaCasterListener

```
public void addMediaCasterListener(IMediaCasterNotify2 mediaCasterListener)
```

Add mediaCaster listener. Listens for create, destroy, registerPlayer, unregisterPlayer, setSourceStream

**Parameters:**

mediaCasterListener

---

## removeMediaCasterListener

```
public void removeMediaCasterListener(IMediaCasterNotify mediaCasterListener)
```

Remove mediaCaster listener. Listens for create, destroy, registerPlayer, unregisterPlayer, setSourceStream

**Parameters:**

mediaCasterListener

---

## getConnectionCounter

```
public ConnectionCounter getConnectionCounter( )
```

Get the connectionCounter for applicationInstance

**Returns:**

connection counter

---

## getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get the connectionCounter for applicationInstance for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index

**Returns:**

connection counter

---

## getDateStarted

```
public String getDateStarted( )
```

Get date applicationInstance started

**Returns:**

(continued from last page)

date applicationInstance started

---

## getTimeRunning

```
public String getTimeRunning()
```

Get time applicationInstance running

**Returns:**

time applicationInstance running

---

## getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

**Returns:**

time running in seconds

---

## broadcastMsg

```
public void broadcastMsg(java.util.List clientList,  
                          String handlerName)
```

Broadcast a message to a specific list of clients connected to this application instance

**Parameters:**

clientList - list of client

handlerName - handler name

---

## broadcastMsg

```
public void broadcastMsg(java.util.List clientList,  
                          String handlerName,  
                          Object[] params)
```

Broadcast a message to a specific list of clients connected to this application instance

**Parameters:**

clientList - list of client

handlerName - handler name

params - parameters

---

## broadcastMsg

```
public void broadcastMsg(String handlerName,  
                          Object[] params)
```

(continued from last page)

Broadcast a message to all clients connected to this applicationInstance

## Broadcast Message to All Clients

```
IApplicationInstance appInstance;
appInstance.broadcastMsg("onNotify", "Hello World", 1.2345, false, new Date());
```

### Parameters:

handlerName - handler name

params - variable list of arguments (Java primitive and Strings will be wrapped in AMFData objects)

---

## getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter()
```

Get the performance counter for applicationInstance

### Returns:

io performance counter

---

## getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter(int counterIndex)
```

Get the performance counter for applicationInstance for a specific technology (see IVHost.COUNTER\_\*)

### Parameters:

counterIndex - counter index (see IVHost.COUNTER\_\*)

### Returns:

connection counter

---

## addPlayStreamByName

```
public void addPlayStreamByName(IMediaStream stream,
    String name)
```

Add a media stream to the list of streams that are listening for a published stream

### Parameters:

stream - media stream

name - stream name

---

## removePlayStreamByName

```
public void removePlayStreamByName(IMediaStream stream)
```

Remove media stream from the list of streams that are listening for a published stream

### Parameters:



(continued from last page)

stream - media stream

---

## getPlayStreamCountsByName

```
public java.util.Map getPlayStreamCountsByName( )
```

Get a map of stream names to number of Flash players playing the stream name

**Returns:**

map of stream names to number of Flash players playing the stream name

---

## getPlayStreamCount

```
public int getPlayStreamCount(String streamName)
```

Get the number of Flash players playing a given stream name

**Parameters:**

streamName - stream name

**Returns:**

number of players

---

## getPlayStreamsByName

```
public java.util.List getPlayStreamsByName(String name)
```

Get a list of media streams that are listening for published stream.

**Parameters:**

name - stream name

**Returns:**

list of streams or null if no listeners

---

## getMediaCasterStreams

```
public MediaCasterStreamMap getMediaCasterStreams( )
```

Get the media caster streams attached to this application instance

**Returns:**

media caster streams attached to this application instance

---

## getStreamCount

```
public int getStreamCount( )
```

Get the total number of open streams attached to this application instance

**Returns:**

the total number of open streams attached to this application instance

---

## getModFunctions

```
public ModuleFunctions getModFunctions( )
```

Get list of application modules

---

(continued from last page)

**Returns:**

list of application modules

---

**addModuleListener**

```
public void addModuleListener(IModuleNotify moduleListener)
```

Add module listener. Listens for onModuleLoad and onModuleUnload events. See IModuleNotify.

**Parameters:**

moduleListener - module listener

---

**removeModuleListener**

```
public void removeModuleListener(IModuleNotify moduleListener)
```

Remove module listener

**Parameters:**

moduleListener - module listener

---

**getModuleList**

```
public ModuleList getModuleList()
```

Get the list of loaded modules.

**Returns:**

list of loaded modules

---

**getModuleInstance**

```
public Object getModuleInstance(String name)
```

Get the instance of the module class for this application instance.

**Parameters:**

name - module name as defined in Application.xml

**Returns:**

instance of class for this application instance

---

**getApplicationTimeout**

```
public int getApplicationTimeout()
```

Get application timeout (milliseconds)

**Returns:**

application timeout (milliseconds)

---

**setApplicationTimeout**

```
public void setApplicationTimeout(int applicationTimeout)
```

Set application timeout (milliseconds)

(continued from last page)

**Parameters:**

applicationTimeout - application timeout (milliseconds)

---

**getPingTimeout**

```
public int getPingTimeout()
```

Get ping timeout (milliseconds)

**Returns:**

ping timeout (milliseconds)

---

**setPingTimeout**

```
public void setPingTimeout(int pingTimeout)
```

Set ping timeout (milliseconds)

**Parameters:**

pingTimeout - ping timeout (milliseconds)

---

**getValidationFrequency**

```
public int getValidationFrequency()
```

Get time between validation pings (milliseconds)

**Returns:**

time between validation pings (milliseconds)

---

**setValidationFrequency**

```
public void setValidationFrequency(int validationFrequency)
```

Set time between validation pings (milliseconds)

**Parameters:**

validationFrequency - time between validation pings (milliseconds)

---

**getMaximumPendingWriteBytes**

```
public int getMaximumPendingWriteBytes()
```

Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

**Returns:**

maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

---

**setMaximumPendingWriteBytes**

```
public void setMaximumPendingWriteBytes(int maximumPendingWriteBytes)
```

Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

**Parameters:**

maximumPendingWriteBytes - maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

## getMaximumPendingReadBytes

```
public int getMaximumPendingReadBytes()
```

Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

**Returns:**

maximum number of bytes a client connection can have waiting to be written before the connection is terminated

---

## setMaximumPendingReadBytes

```
public void setMaximumPendingReadBytes(int maximumPendingReaderBytes)
```

Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

**Parameters:**

maximumPendingReaderBytes - maximum number of bytes a client connection can have waiting to be written before the connection is terminated

---

## setMaximumSetBufferTime

```
public void setMaximumSetBufferTime(int maximumSetBufferTime)
```

Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

**Parameters:**

maximumSetBufferTime - maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

---

## getMaximumSetBufferTime

```
public int getMaximumSetBufferTime()
```

Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

**Returns:**

maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

---

## getRepeaterOriginUrl

```
public String getRepeaterOriginUrl()
```

Get the Repeater Origin URL used by the Live Stream Repeater

**Returns:**

URL used by the Live Stream Repeater

---

## setRepeaterOriginUrl

```
public void setRepeaterOriginUrl(String repeaterOriginUrl)
```

Set the Repeater Origin URL used by the Live Stream Repeater

**Parameters:**

repeaterOriginUrl - URL used by the Live Stream Repeater

---

## getRepeaterQueryString

```
public String getRepeaterQueryString()
```

Get the Repeater query string that is used to connect to the origin. This value can be used to pass secure URL parameters to the origin for security validation.

**Returns:**

Repeater query string

---

## setRepeaterQueryString

```
public void setRepeaterQueryString(String repeaterQueryString)
```

Set the Repeater query string that is used to connect to the origin. This value can be used to pass secure URL parameters to the origin for security validation.

**Parameters:**

repeaterQueryString - Repeater query string

---

## getAllowDomains

```
public String[] getAllowDomains()
```

Get the list of domain names used to control access to this application. Upon connection, if this list is non-null the client.referrer value is checked to make sure the referrer is from a domain in this list.

**Returns:**

list of domain names used to control access to this application

---

## setAllowDomains

```
public void setAllowDomains(String[] domainFilter)
```

Set the list of domain names used to control access to this application. Upon connection, if this list is non-null the client.referrer value is checked to make sure the referrer is from a domain in this list.

**Parameters:**

domainFilter - list of domain names used to control access to this application

---

## parseAllowDomains

```
public void parseAllowDomains(String domainFilterStr)
```

Parse a comma delimited list of domain names used to control access to this application. Upon connection, if this list is non-null the client.referrer value is checked to make sure the referrer is from a domain in this list.

**Parameters:**

domainFilterStr - comma delimited list of domain names

---

## getClientIdleFrequency

```
public int getClientIdleFrequency()
```

Get default client idle frequency (milliseconds)

**Returns:**

default client idle frequency (milliseconds)

---

## setClientIdleFrequency

```
public void setClientIdleFrequency(int clientIdleFrequency)
```

Set default client idle frequency (milliseconds)

**Parameters:**

clientIdleFrequency - default client idle frequency (milliseconds)

---

## getRTPIdeFrequency

```
public int getRTPIdeFrequency( )
```

Set the default RTP idle frequency (milliseconds)

**Returns:**

default RTP idle frequency (milliseconds)

---

## setRTPIdeFrequency

```
public void setRTPIdeFrequency(int rtspIdleFrequency)
```

Get the default RTP idle frequency (milliseconds)

**Parameters:**

rtspIdleFrequency - default RTP idle frequency (milliseconds)

---

## getStreamStorageDir

```
public String getStreamStorageDir( )
```

Get stream storage path

**Returns:**

stream storage path

---

## setStreamStorageDir

```
public void setStreamStorageDir(String streamStorageDir)
```

Set stream storage path

**Parameters:**

streamStorageDir - stream storage path

---

## getStreamKeyDir

```
public String getStreamKeyDir( )
```

Get the stream key path

**Returns:**

stream key path

---

## setStreamKeyDir

```
public void setStreamKeyDir(String keyStorageDir)
```

---

(continued from last page)

Set the stream key path

**Parameters:**

keyStorageDir - stream key path

---

## getRsoStorageDir

```
public String getRsoStorageDir()
```

Get remote shared object storage path

**Returns:**

remote shared object storage path

---

## setRsoStorageDir

```
public void setRsoStorageDir(String rsoStorageDir)
```

Set remote shared object storage path

**Parameters:**

rsoStorageDir - remote shared object storage path

---

## getStreamKeyPath

```
public String getStreamKeyPath()
```

Get the resolved key path to the MediaStreams encryption keys

**Returns:**

resolved key path to the MediaStreams encryption keys

---

## getStreamStoragePath

```
public String getStreamStoragePath()
```

Get the resolved storage path to the MediaStreams

**Returns:**

resolved storage path to the MediaStreams

---

## getRsoStoragePath

```
public String getRsoStoragePath()
```

Get the resolved storage path to the shared objects

**Returns:**

resolved storage path to the shared objects

---

## getStreamVideoSampleAccess

```
public String getStreamVideoSampleAccess()
```

Get the default stream video sample access

**Returns:**

default stream video sample access

(continued from last page)

See Also:

[IClient.getStreamVideoSampleAccess\(\)](#)

---

## setStreamVideoSampleAccess

```
public void setStreamVideoSampleAccess(String streamVideoSampleAccess)
```

Set the default stream video sample access

**Parameters:**

streamVideoSampleAccess - default stream video sample access

See Also:

[IClient.setStreamVideoSampleAccess\(String\)](#)

---

## getStreamAudioSampleAccess

```
public String getStreamAudioSampleAccess()
```

Get the default stream audio sample access

**Returns:**

default stream audio sample access

See Also:

[IClient.getStreamAudioSampleAccess\(\)](#)

---

## setStreamAudioSampleAccess

```
public void setStreamAudioSampleAccess(String streamAudioSampleAccess)
```

Set the default stream audio sample access

**Parameters:**

streamAudioSampleAccess

See Also:

[IClient.setStreamAudioSampleAccess\(String\)](#)

---

## getStreamReadAccess

```
public String getStreamReadAccess()
```

Get the default stream read access

**Returns:**

default stream read access

See Also:

[IClient.getStreamReadAccess\(\)](#)

---

## setStreamReadAccess

```
public void setStreamReadAccess(String streamReadAccess)
```

Set the default stream read access



(continued from last page)

**Parameters:**

streamReadAccess - default stream read access

**See Also:**[IClient.setStreamReadAccess\(String\)](#)

---

## getStreamWriteAccess

```
public String getStreamWriteAccess()
```

Get the default stream write access

**Returns:**

default stream write access

**See Also:**[IClient.getStreamWriteAccess\(\)](#)

---

## setStreamWriteAccess

```
public void setStreamWriteAccess(String streamWriteAccess)
```

Set the default stream write access

**Parameters:**

streamWriteAccess - default stream write access

**See Also:**[IClient.setStreamWriteAccess\(String\)](#)

---

## getSharedObjectReadAccess

```
public String getSharedObjectReadAccess()
```

Get the default shared object read access

**Returns:**

default shared object read access

**See Also:**[IClient.getSharedObjectReadAccess\(\)](#)

---

## setSharedObjectReadAccess

```
public void setSharedObjectReadAccess(String sharedObjectReadAccess)
```

Set the default shared object read access

**Parameters:**

sharedObjectReadAccess - default shared object read access

**See Also:**[IClient.setSharedObjectReadAccess\(String\)](#)

---

## getSharedObjectWriteAccess

```
public String getSharedObjectWriteAccess()
```

(continued from last page)

Get the default shared object write access

**Returns:**

default shared object write access

**See Also:**

[IClient.getSharedObjectWriteAccess\(\)](#)

---

## setSharedObjectWriteAccess

```
public void setSharedObjectWriteAccess(String sharedObjectWriteAccess)
```

Set the default shared object write access

**Parameters:**

sharedObjectWriteAccess - default shared object write access

**See Also:**

[IClient.setSharedObjectWriteAccess\(String\)](#)

---

## getRTPPublishAuthenticationMethod

```
public String getRTPPublishAuthenticationMethod()
```

Get the RTP publish authentication method (as defined in conf/Authentication.xml)

**Returns:**

RTP publish authentication method

---

## setRTPPublishAuthenticationMethod

```
public void setRTPPublishAuthenticationMethod(String rtpPublishAuthenticationMethod)
```

Set the RTP publish authentication method (as defined in conf/Authentication.xml)

**Parameters:**

rtpPublishAuthenticationMethod - RTP publish authentication method

---

## getRTPPlayAuthenticationMethod

```
public String getRTPPlayAuthenticationMethod()
```

Get the RTP play authentication method (as defined in conf/Authentication.xml)

**Returns:**

RTP play authentication method

---

## setRTPPlayAuthenticationMethod

```
public void setRTPPlayAuthenticationMethod(String rtpPlayAuthenticationMethod)
```

Set the RTP play authentication method (as defined in conf/Authentication.xml)

**Parameters:**

rtpPlayAuthenticationMethod - RTP play authentication method

(continued from last page)

## getRTPAVSyncMethod

```
public int getRTPAVSyncMethod( )
```

Get RTP audio/video sync method (RTPStream.AVSYNCMETHODS\_SENDERREPORT, RTPStream.AVSYNCMETHODS\_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS\_RTPTIMECODE)

**Returns:**

RTP audio/video sync method

---

## setRTPAVSyncMethod

```
public void setRTPAVSyncMethod(int rtpAVSyncMethod)
```

Set RTP audio/video sync method (RTPStream.AVSYNCMETHODS\_SENDERREPORT, RTPStream.AVSYNCMETHODS\_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS\_RTPTIMECODE)

**Parameters:**

rtpAVSyncMethod - RTP audio/video sync method

---

## getRTPMaxRTCPWaitTime

```
public int getRTPMaxRTCPWaitTime( )
```

Get the maximum time to wait for RTCP packets (milliseconds)

**Returns:**

maximum time to wait for RTCP packets (milliseconds)

---

## setRTPMaxRTCPWaitTime

```
public void setRTPMaxRTCPWaitTime(int rtpMaxRTCPWaitTime)
```

Set the maximum time to wait for RTCP packets (milliseconds)

**Parameters:**

rtpMaxRTCPWaitTime - maximum time to wait for RTCP packets (milliseconds)

---

## getRTPSessions

```
public java.util.List getRTPSessions(String streamName)
```

Get a list of RTP sessions running under this application instance playing a given stream name

**Parameters:**

streamName - stream name

**Returns:**

list of RTP sessions running under this application instance playing a given stream name

---

## getRTPSessions

```
public java.util.List getRTPSessions( )
```

Get a list of RTP sessions running under this application instance

**Returns:**

list of RTP sessions running under this application instance

## getRTPSessionCountsByName

```
public java.util.Map getRTPSessionCountsByName()
```

Get a map of stream names and session counts of RTP sessions

**Returns:**

map of stream names and session counts

---

## getRTPSessionCount

```
public int getRTPSessionCount(String streamName)
```

Get the number of RTP player streams playing a given stream name

**Parameters:**

streamName - stream name

**Returns:**

the number of RTP sessions

---

## getRTPSessionCount

```
public int getRTPSessionCount()
```

Get the number of RTP sessions running under this application instance

**Returns:**

the number of RTP sessions running under this application instance

---

## addRTPSession

```
public void addRTPSession(RTPSession rtpSession)
```

Add an RTP session to this application instance

**Parameters:**

rtpSession - RTP session to add

---

## registerPlayRTPSession

```
public void registerPlayRTPSession(RTPSession rtpSession)
```

Register an RTP session as a play session

**Parameters:**

rtpSession - RTP session to register

---

## removeRTPSession

```
public void removeRTPSession(RTPSession rtpSession)
```

Remove an RTP session from this application instance

**Parameters:**

rtpSession - RTP session to remove

---

## getClientsLockObj

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
getClientsLockObj()
```

Get the read/write lock for this application instance

**Returns:**

read/write lock for this application instance

---

## getStreamProperties

```
public WMSProperties getStreamProperties()
```

Get the property collection of stream settings that are specific to this application instance

**Returns:**

property collection of stream settings

---

## getMediaCasterProperties

```
public WMSProperties getMediaCasterProperties()
```

Get the property collection of media caster settings that are specific to this application instance

**Returns:**

property collection of media caster settings

---

## getMediaReaderProperties

```
public WMSProperties getMediaReaderProperties()
```

Get the property collection of media reader settings that are specific to this application instance

**Returns:**

property collection of media reader settings

---

## getMediaWriterProperties

```
public WMSProperties getMediaWriterProperties()
```

Get the property collection of media reader settings that are specific to this application instance

**Returns:**

property collection of media reader settings

---

## getRTPProperties

```
public WMSProperties getRTPProperties()
```

Get the property collection of RTP settings that are specific to this application instance

**Returns:**

property collection of RTP settings

---

(continued from last page)

---

## getLiveStreamPacketizerProperties

```
public WMSProperties getLiveStreamPacketizerProperties()
```

Get the property collection of LiveStreamPacketizer settings that are specific to this application instance

**Returns:**

property collection of LiveStreamPacketizer settings

---

## getTranscoderProperties

```
public WMSProperties getTranscoderProperties()
```

Get the property collection of Transcoder settings that are specific to this application instance

**Returns:**

property collection of Transcoder settings

---

## getHTTPStreamerProperties

```
public WMSProperties getHTTPStreamerProperties()
```

Get the property collection of HTTPStreamer settings that are specific to this application instance

**Returns:**

property collection of HTTPStreamer settings

---

## getMaxStorageDirDepth

```
public int getMaxStorageDirDepth()
```

Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths

**Returns:**

folder depth

---

## setMaxStorageDirDepth

```
public void setMaxStorageDirDepth(int maxStorageDirDepth)
```

Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths

**Parameters:**

maxStorageDirDepth - folder depth

---

## getStreamFileMapper

```
public IMediaStreamFileMapper getStreamFileMapper()
```

Get the stream file mapper. See IMediaStreamFileMapper

**Returns:**

streamFileMapper stream file mapper

---

## setStreamFileMapper

```
public void setStreamFileMapper(IMediaStreamFileMapper streamFileMapper)
```

---

(continued from last page)

Set the stream file mapper. See IMediaStreamFileMapper

**Parameters:**

streamFileMapper - stream file mapper

---

## decodeStorageDir

```
public String decodeStorageDir(String storageDir)
```

This function will take a storage path that uses variables and expand the variables based on the context. It supports the following variables (as well as any system variables): `${com.wowza.wms.AppHome}`: Application home directory `${com.wowza.wms.ConfigHome}`: Configuration home directory `${com.wowza.wms.context.VHostConfigHome}`: Virtual configuration path `${com.wowza.wms.context.VHost}`: Virtual host name `${com.wowza.wms.context.Application}`: Application name `${com.wowza.wms.context.ApplicationInstance}`: Application instance name

---

## getLiveStreamPacketizerList

```
public String getLiveStreamPacketizerList()
```

Get the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)

**Returns:**

comma separated list of LiveStreamPacketizers names

---

## getHTTPStreamerList

```
public String getHTTPStreamerList()
```

Get the comma separated list of HTTPStreamers names being used by this application (see conf/HTTPStreamers.xml)

**Returns:**

comma separated list of HTTPStreamers names

---

## setLiveStreamPacketizerList

```
public void setLiveStreamPacketizerList(String liveStreamPacketizerList)
```

Set the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)

**Parameters:**

liveStreamPacketizerList - comma separated list of LiveStreamPacketizers names

---

## setHTTPStreamerList

```
public void setHTTPStreamerList(String httpStreamerList)
```

Set the comma separated list of HTTPStreamer names being used by this application (see conf/HTTPStreamers.xml)

**Parameters:**

httpStreamerList - comma separated list of HTTPStreamer names

---

## containsHTTPStreamer

```
public boolean containsHTTPStreamer(String httpStreamer)
```

Does this application instance allow streaming of a given HTTPStreamer

**Parameters:**

(continued from last page)

httpStreamer - HTTP Streamer name

**Returns:**

true is this type of streaming is allowed

---

## containsLiveStreamPacketizer

```
public boolean containsLiveStreamPacketizer(String liveStreamPacketizer)
```

Does this application instance contain a references to this live stream packetizer. If it is true we consider this a live stream source for the HTTP streamer. If false then we consider this a video on demand source.

**Parameters:**

liveStreamPacketizer - live stream packetizer name

**Returns:**

true if contains reference to it

---

## containsDvrRecorder

```
public boolean containsDvrRecorder(String dvrRecorder)
```

Does this application instance contain a references to this DVR recorder. If it is true we consider this a DVR source for the HTTP streamer.

**Parameters:**

dvrRecorder - DVR recorder name

**Returns:**

true if contains reference to it

---

## getVODTimedTextProviderList

```
public String getVODTimedTextProviderList()
```

Get the comma separated list of VODTimedTextProvider names being used by this application (see conf/TimedTextProviders.xml)

**Returns:**

comma separated list of VODTimedTextProvider names

---

## setVODTimedTextProviderList

```
public void setVODTimedTextProviderList(String timedTextProviderList)
```

Set the comma separated list of VODTimedTextProvider names being used by this application (see conf/TimedTextProviders.xml)

**Parameters:**

timedTextProviderList - comma separated list of VODTimedTextProvider names

---

## getVODTimedTextProviderSet

```
public java.util.List getVODTimedTextProviderSet()
```



(continued from last page)

---

## getTimedTextProperties

```
public WMSProperties getTimedTextProperties()
```

Get the property collection of timed text settings that are specific to this application instance. These are defined in Application/TimedText/Properties tag in Application.xml

**Returns:**

property collection of Timed Text settings

---

## getStreamNameAliasProvider

```
public IMediaStreamNameAliasProvider getStreamNameAliasProvider()
```

Get the stream name alias provider

**Returns:**

stream name alias provider

---

## setStreamNameAliasProvider

```
public void setStreamNameAliasProvider(IMediaStreamNameAliasProvider  
streamNameAliasProvider)
```

Set the stream name alias provider

**Parameters:**

streamNameAliasProvider - stream name alias provider

---

## getPublishers

```
public java.util.List getPublishers()
```

Get the set of server side publishers

**Returns:**

set of server side publishers

---

## getPublisherCount

```
public int getPublisherCount()
```

Get the current number of server side publishers

**Returns:**

number of server side publishers

---

## addPublisher

```
public void addPublisher(Publisher publisher)
```

Add a server side publisher to this application instance

**Parameters:**

publisher - server side publisher

---

(continued from last page)

---

## removePublisher

```
public void removePublisher(Publisher publisher)
```

Remove a server side publisher from this application instance

**Parameters:**

publisher - server side publisher

---

## getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions(int protocol,  
String streamName)
```

Get the HTTPStreamerSessions associated with this application instance for a stream name by protocol. See (IHTTPStreamerSession.SESSIONPROTOCOL\_\*) for protocols

**Parameters:**

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL\_\*)  
streamName - stream name

**Returns:**

HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions(String streamName)
```

Get the HTTPStreamerSessions associated with this application instance for a stream name

**Parameters:**

streamName - stream name

**Returns:**

HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessionCountsByName

```
public java.util.Map getHTTPStreamerSessionCountsByName(int protocol)
```

Get a map of session counts by name for a given protocol

**Parameters:**

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL\_\*)

**Returns:**

map of session counts by name

---

## getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount(String streamName)
```

Get the current number of HTTPStreamerSessions associated with this application instance and stream name

**Parameters:**

streamName - stream name

**Returns:**

number of HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount(int protocol,  
    String streamName)
```

Get the current number of HTTPStreamerSessions associated with this application instance and stream name by protocol . See (IHTTPStreamerSession.SESSIONPROTOCOL\_\*) for protocols

**Parameters:**

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL\_\*)  
streamName - stream name

**Returns:**

HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions()
```

Get the HTTPStreamerSessions associated with this application instance

**Returns:**

HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions(int protocol)
```

Get the HTTPStreamerSessions associated with this application instance by protocol. See (IHTTPStreamerSession.SESSIONPROTOCOL\_\*) for protocols

**Parameters:**

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL\_\*)

**Returns:**

HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount()
```

Get the current number of HTTPStreamerSessions associated with this application instance

**Returns:**

current number of HTTPStreamerSessions associated with this application instance

---

## getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount(int protocol)
```

Get the current number of HTTPStreamerSessions associated with this application instance by protocol. See (IHTTPStreamerSession.SESSIONPROTOCOL\_\*) for protocols

**Parameters:**

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL\_\*)

**Returns:**

current number of HTTPStreamerSessions associated with this application instance

---

## addHTTPStreamerSession

```
public void addHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Add a HTTPStreamerSession to this application instance

**Parameters:**

httpStreamerSession - HTTPStreamerSession

---

## removeHTTPStreamerSession

```
public void removeHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Remove a HTTPStreamerSession from this application instance

**Parameters:**

httpStreamerSession - HTTPStreamerSession

---

## getHTTPStreamerApplicationContext

```
public IHTTPStreamerApplicationContext getHTTPStreamerApplicationContext(String  
httpStreamName,  
boolean doCreate)
```

Get the HTTPStreamer application context for a given HTTPStreamer adapter

**Parameters:**

httpStreamName - HTTPStreamer adapter name  
doCreate - create if it does not exist

**Returns:**

HTTPStreamer application context

---

## addRTPIncomingDatagramPortRange

```
public void addRTPIncomingDatagramPortRange(int startPort,  
int endPort)
```

Add a port range to the list of valid incoming RTP UDP ports

**Parameters:**

startPort - starting port number  
endPort - end port number

---

## addRTPIncomingDatagramPortAll

```
public void addRTPIncomingDatagramPortAll()
```

Allow all incoming RTP UDP ports for this application instance

---

## isRTPIncomingDatagramPortValid

```
public boolean isRTPIncomingDatagramPortValid(int port)
```

Check a port number to be sure it is a valid RTP UDP port for this application instance

**Parameters:**

port - port number

---

(continued from last page)

**Returns:**

true if the port is valid

---

**readAppInstConfig**

```
public String readAppInstConfig(String sName)
```

Method to read xml config file..

---

**writeAppInstConfig**

```
public boolean writeAppInstConfig(String sName,  
    String data)
```

Method to write xml config file..

---

**getLiveStreamPacketizerControl**

```
public ILiveStreamPacketizerControl getLiveStreamPacketizerControl()
```

Get the Live Stream Packetizer Controller. This class will get called each time a stream is to be packetized using the LiveStreamPacketizer mechanism.

**Returns:**

Live Stream Packetizer Controller

---

**setLiveStreamPacketizerControl**

```
public void setLiveStreamPacketizerControl(ILiveStreamPacketizerControl  
liveStreamPacketizerControl)
```

Set the Live Stream Packetizer Controller. This class will get called each time a stream is to be packetized using the LiveStreamPacketizer mechanism.

**Parameters:**

liveStreamPacketizerControl - Live Stream Packetizer Controller

---

**resetMediaCasterStream**

```
public boolean resetMediaCasterStream(String streamName)
```

Reset a media caster stream

**Parameters:**

streamName - stream name

**Returns:**

true if successful

---

**resetMediaCasterStream**

```
public boolean resetMediaCasterStream(String streamName,  
    String streamExt)
```

Reset a media caster stream

**Parameters:**

streamName - stream name

(continued from last page)

streamExt - stream extension

**Returns:**

true if successful

---

## startMediaCasterStream

```
public boolean startMediaCasterStream(String streamName,  
    String streamExt,  
    String mediaCasterType)
```

Start a media caster stream

**Parameters:**

streamName - stream name

streamExt - stream extension

mediaCasterType - media caster stream type

**Returns:**

true if successful

---

## startMediaCasterStream

```
public boolean startMediaCasterStream(String streamName,  
    String mediaCasterType)
```

Start a media caster stream

**Parameters:**

streamName - stream name

mediaCasterType - media caster stream type

**Returns:**

true if successful

---

## stopMediaCasterStream

```
public void stopMediaCasterStream(String streamName)
```

Stop a media caster stream

**Parameters:**

streamName - stream name

---

## getContextStr

```
public String getContextStr()
```

Returns the application context string in the form [application]/[appInstance].

**Returns:**

application context string

---

## getPublishStreamNames

```
public java.util.List getPublishStreamNames()
```

Get the list of live stream names currently being published.

(continued from last page)

**Returns:**

list of live stream names currently being published

---

**addMediaWriterListener**

```
public void addMediaWriterListener(IMediaWriterActionNotify listener)
```

Add a MediaWriter listener class. See IMediaWriterActionNotify

**Parameters:**

listener - MediaWriter listener class

---

**removeMediaWriterListener**

```
public void removeMediaWriterListener(IMediaWriterActionNotify listener)
```

remove MediaWriter listener class. See IMediaWriterActionNotify

**Parameters:**

listener - MediaWriter listener class

---

**notifyMediaWriterOnWriteComplete**

```
public void notifyMediaWriterOnWriteComplete(IMediaStream stream,  
java.io.File file)
```

Notify all MediaWriter listeners of onWriteComplete

**Parameters:**

stream - media stream

file - file that was written

---

**notifyMediaWriterOnFLVAddMetadata**

```
public void notifyMediaWriterOnFLVAddMetadata(IMediaStream stream,  
java.util.Map extraMetadata)
```

Notify all MediaWriter listeners of onFLVAddMetadata

**Parameters:**

stream - media stream

extraMetadata - meta to add to the file

---

**getMediaCasterValidator**

```
public IMediaCasterValidateMediaCaster getMediaCasterValidator()
```

Get the MediaCaster validator interface for this application instance

**Returns:**

MediaCaster validator interface

---

**setMediaCasterValidator**

```
public void setMediaCasterValidator(IMediaCasterValidateMediaCaster  
mediaCasterValidator)
```

Set the MediaCaster validator interface for this application instance

(continued from last page)

**Parameters:**

mediaCasterValidator - MediaCaster validator interface

---

**touch**

```
public void touch()
```

Touch the application instance so that it stays loaded for at least applicationInstanceTouchTimeout

---

**getLastTouchTime**

```
public long getLastTouchTime()
```

Get the last time the instance was touched (milliseconds)

**Returns:**

last time the instance was touched (milliseconds)

---

**getApplicationInstanceTouchTimeout**

```
public int getApplicationInstanceTouchTimeout()
```

Get the application instance touch timeout (milliseconds). Default is 5000.

**Returns:**

application instance touch timeout (milliseconds)

---

**setApplicationInstanceTouchTimeout**

```
public void setApplicationInstanceTouchTimeout(int applicationInstanceTouchTimeout)
```

Set the application instance touch timeout (milliseconds). Default is 5000.

**Parameters:**

applicationInstanceTouchTimeout - application instance touch timeout (milliseconds)

---

**getRTSPSessionTimeout**

```
public int getRTSPSessionTimeout()
```

Get the RTSP session timeout (milliseconds)

**Returns:**

RTSP session timeout (milliseconds)

---

**setRTSPSessionTimeout**

```
public void setRTSPSessionTimeout(int rtspSessionTimeout)
```

Set the RTSP session timeout (milliseconds)

**Parameters:**

rtspSessionTimeout - RTSP session timeout (milliseconds)

---

**getRTSPMaximumPendingWriteBytes**

```
public int getRTSPMaximumPendingWriteBytes()
```



(continued from last page)

Get the maximum number of pending write bytes for an RTSP session

**Returns:**

maximum number of pending write bytes for an RTSP session

---

## setRTSPMaximumPendingWriteBytes

```
public void setRTSPMaximumPendingWriteBytes(int rtspMaximumPendingWriteBytes)
```

Set the maximum number of pending write bytes for an RTSP session

**Parameters:**

rtspMaximumPendingWriteBytes - maximum number of pending write bytes for an RTSP session

---

## addMediaReaderListener

```
public void addMediaReaderListener(IMediaReaderActionNotify mediaReaderListener)
```

Add media reader listener. see IMediaReaderActionNotify

**Parameters:**

mediaReaderListener - media reader listener

---

## removeMediaReaderListener

```
public void removeMediaReaderListener(IMediaReaderActionNotify mediaReaderListener)
```

Remove media reader listener. see IMediaReaderActionNotify

**Parameters:**

mediaReaderListener - media reader listener

---

## notifyMediaReaderCreate

```
public void notifyMediaReaderCreate(IMediaReader mediaReader)
```

Notify media reader notifyMediaReaderCreate

**Parameters:**

mediaReader - media reader

---

## notifyMediaReaderInit

```
public void notifyMediaReaderInit(IMediaReader mediaReader,  
    IMediaStream stream)
```

Notify media reader notifyMediaReaderInit

**Parameters:**

mediaReader - media reader

stream - media stream

---

## notifyMediaReaderOpen

```
public void notifyMediaReaderOpen(IMediaReader mediaReader,  
    IMediaStream stream)
```

Notify media reader notifyMediaReaderOpen

(continued from last page)

**Parameters:**

mediaReader - media reader  
stream - media stream

---

**notifyMediaReaderExtractMetaData**

```
public void notifyMediaReaderExtractMetaData(IMediaReader mediaReader,  
      IMediaStream stream)
```

Notify media reader notifyMediaReaderExtractMetaData

**Parameters:**

mediaReader - media reader  
stream - media stream

---

**notifyMediaReaderClose**

```
public void notifyMediaReaderClose(IMediaReader mediaReader,  
      IMediaStream stream)
```

Notify media reader notifyMediaReaderClose

**Parameters:**

mediaReader - media reader  
stream - media stream

---

**getRTSPBindIpAddress**

```
public String getRTSPBindIpAddress()
```

Set the IP address to which UDP ports will be bound for RTSP/RTP sessions

**Returns:**

IP address to which UDP ports will be bound for RTSP/RTP sessions

---

**setRTSPBindIpAddress**

```
public void setRTSPBindIpAddress(String rtspBindIpAddress)
```

Get the IP address to which UDP ports will be bound for RTSP/RTP sessions

**Parameters:**

rtspBindIpAddress - IP address to which UDP ports will be bound for RTSP/RTP sessions

---

**getRTSPConnectionIpAddress**

```
public String getRTSPConnectionIpAddress()
```

Get the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Returns:**

connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

**setRTSPConnectionIpAddress**

```
public void setRTSPConnectionIpAddress(String rtspConnectionIpAddress)
```

Set the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

(continued from last page)

**Parameters:**

rtspConnectionIpAddress - connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

## getRTSPConnectionAddressType

```
public String getRTSPConnectionAddressType()
```

Get the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Returns:**

the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

## setRTSPConnectionAddressType

```
public void setRTSPConnectionAddressType(String rtspConnectionAddressType)
```

Set the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Parameters:**

rtspConnectionAddressType

---

## getRTSPOriginIpAddress

```
public String getRTSPOriginIpAddress()
```

Get the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Returns:**

origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

## setRTSPOriginIpAddress

```
public void setRTSPOriginIpAddress(String rtspOriginIpAddress)
```

Set the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Parameters:**

rtspOriginIpAddress - origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

## getRTSPOriginAddressType

```
public String getRTSPOriginAddressType()
```

Get the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Returns:**

origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

## setRTSPOriginAddressType

```
public void setRTSPOriginAddressType(String rtspOriginAddressType)
```

Set the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

**Parameters:**

(continued from last page)

rtspOriginAddressType - origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

---

## addLiveStreamPacketizerListener

```
public void addLiveStreamPacketizerListener( ILiveStreamPacketizerActionNotify liveStreamPacketizerListener)
```

Add a Live Stream Packetizer listener (see: [ILiveStreamPacketizerActionNotify](#))

### Parameters:

liveStreamPacketizerListener - Live Stream Packetizer listener

---

## removeLiveStreamPacketizerListener

```
public void removeLiveStreamPacketizerListener( ILiveStreamPacketizerActionNotify liveStreamPacketizerListener)
```

Remove a Live Stream Packetizer listener (see: [ILiveStreamPacketizerActionNotify](#))

### Parameters:

liveStreamPacketizerListener - Live Stream Packetizer listener

---

## notifyLiveStreamPacketizerCreate

```
public void notifyLiveStreamPacketizerCreate( ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Notify Live Stream Packetizer Create

### Parameters:

liveStreamPacketizer - Live Stream Packetizer listener

---

## notifyLiveStreamPacketizerDestroy

```
public void notifyLiveStreamPacketizerDestroy( ILiveStreamPacketizer liveStreamPacketizer)
```

Notify Live Stream Packetizer Destroy

### Parameters:

liveStreamPacketizer - Live Stream Packetizer listener

---

## notifyLiveStreamPacketizerInit

```
public void notifyLiveStreamPacketizerInit( ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Notify Live Stream Packetizer Init

### Parameters:

liveStreamPacketizer - Live Stream Packetizer listener

---

## isValidFMLEConnections

```
public boolean isValidFMLEConnections()
```

Returns true if validating FMLE connection (default is false)

(continued from last page)

**Returns:**

true if validating FMLE connection

---

**setValidateFMLEConnections**

```
public void setValidateFMLEConnections(boolean validateFMLEConnections)
```

Returns true if validating FMLE connection (default is false)

**Parameters:**

validateFMLEConnections - true if validating FMLE connection

---

**addLiveStreamTranscoderListener**

```
public void addLiveStreamTranscoderListener(ILiveStreamTranscoderNotify  
liveStreamTranscoderListener)
```

Add a live stream transcoder listener

**Parameters:**

liveStreamTranscoderListener - live stream transcoder listener

---

**removeLiveStreamTranscoderListener**

```
public void removeLiveStreamTranscoderListener(ILiveStreamTranscoderNotify  
liveStreamTranscoderListener)
```

Remove a live stream transcoder listener

**Parameters:**

liveStreamTranscoderListener - live stream transcoder listener

---

**notifyLiveStreamTranscoderCreate**

```
public void notifyLiveStreamTranscoderCreate(ILiveStreamTranscoder  
liveStreamTranscoder,  
    IMediaStream stream)
```

Notify live stream transcoder create

**Parameters:**liveStreamTranscoder - live stream transcoder  
stream - stream

---

**notifyLiveStreamTranscoderDestroy**

```
public void notifyLiveStreamTranscoderDestroy(ILiveStreamTranscoder  
liveStreamTranscoder,  
    IMediaStream stream)
```

Notify live stream transcoder destroy

**Parameters:**liveStreamTranscoder - live stream transcoder  
stream - stream

(continued from last page)

## notifyLiveStreamTranscoderInit

```
public void notifyLiveStreamTranscoderInit(ILiveStreamTranscoder liveStreamTranscoder,  
IMediaStream stream)
```

Notify live stream transcoder init

### Parameters:

liveStreamTranscoder - live stream transcoder

stream - stream

---

## containsLiveStreamTranscoder

```
public boolean containsLiveStreamTranscoder(String liveStreamTranscoder)
```

Return true if this application instance contains the transcoder name

### Parameters:

liveStreamTranscoder - transcoder name

### Returns:

true if this application instance contains the transcoder name

---

## getLiveStreamTranscoderList

```
public String getLiveStreamTranscoderList()
```

Get comma separated list of transcoders to use for this application instance

### Returns:

comma separated list of transcoders

---

## setLiveStreamTranscoderList

```
public void setLiveStreamTranscoderList(String liveStreamTranscoderList)
```

Set comma separated list of transcoders to use for this application instance

### Parameters:

liveStreamTranscoderList - comma separated list of transcoders

---

## getLiveStreamTranscoderControl

```
public ILiveStreamTranscoderControl getLiveStreamTranscoderControl()
```

Get the Live Stream Transcoder Contoller. This class will get called each time a stream is to be transcoded using the LiveStreamTranscoder mechanism.

### Returns:

Live Stream Transcoder Contoller

---

## setLiveStreamTranscoderControl

```
public void setLiveStreamTranscoderControl(ILiveStreamTranscoderControl  
liveStreamTranscoderControl)
```

Set the Live Stream Transcoder Contoller. This class will get called each time a stream is to be transcoded using the LiveStreamTranscoder mechanism.

(continued from last page)

**Parameters:**

liveStreamTranscoderControl - Live Stream Transcoder Contoller

---

**getTranscoderApplicationContext**

```
public LiveStreamTranscoderApplicationContext getTranscoderApplicationContext()
```

Get live stream transcoder application context

**Returns:**

live stream transcoder application context

---

**getDvrProperties**

```
public WMSProperties getDvrProperties()
```

Get the property collection of DVR settings that are specific to this application instance. These are defined in Application/DVR/Properties tag in Application.xml

**Returns:**

property collection of DVR settings

---

**getDvrApplicationContext**

```
public DvrApplicationContext getDvrApplicationContext()
```

Get live stream dvr application context

**Returns:**

live stream dvr application context

---

**getLiveStreamDvrRecorderControl**

```
public ILiveStreamDvrRecorderControl getLiveStreamDvrRecorderControl()
```

Get the Live Stream DVR Recorder Controller. This class will get called each time a stream is to be DVR-ed.

**Returns:**

Live Stream DVR Controller

---

**setLiveStreamDvrRecorderControl**

```
public void setLiveStreamDvrRecorderControl(ILiveStreamDvrRecorderControl controller)
```

Set the Live Stream DVR Controller.

**Parameters:**

controller - Live Stream DVR Controller

---

**getDvrRecorderList**

```
public String getDvrRecorderList()
```

Get the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)

**Returns:**

comma separated list of Dvr Recorder names

## setDvrRecorderList

```
public void setDvrRecorderList(String recorderList)
```

Set the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)

**Parameters:**

recorderList - comma separated list of Dvr Recorder names

---

## addDvrRecorderListener

```
public void addDvrRecorderListener(ILiveStreamDvrRecorderActionNotify listener)
```

Add a Dvr Recorder listener (see: [ILiveStreamDvrRecorderActionNotify](#))

**Parameters:**

listener - Dvr Recorder listener

---

## removeDvrRecorderListener

```
public void removeDvrRecorderListener(ILiveStreamDvrRecorderActionNotify listener)
```

Remove a Dvr Recorder listener (see: [ILiveStreamDvrRecorderActionNotify](#))

**Parameters:**

listener - Dvr Recorder listener

---

## notifyLiveStreamDvrRecorderCreate

```
public void notifyLiveStreamDvrRecorderCreate(ILiveStreamDvrRecorder dvr,  
String streamName)
```

Notify Dvr Recorder Create

**Parameters:**

dvr - DVR Recorder listener  
streamName - stream Name

---

## notifyLiveStreamDvrRecorderInit

```
public void notifyLiveStreamDvrRecorderInit(ILiveStreamDvrRecorder dvr,  
String streamName)
```

Notify DVR Recorder has been initialized.

**Parameters:**

dvr - DVR Recorder listener \* @param streamName stream Name

---

## notifyLiveStreamDvrRecorderDestroy

```
public void notifyLiveStreamDvrRecorderDestroy(ILiveStreamDvrRecorder dvr)
```

Notify DVR Recorder has been destroyed.

**Parameters:**

dvr - DVR Recorder listener

---



(continued from last page)

---

## addDvrStreamManagerListener

```
public void addDvrStreamManagerListener(IDvrStreamManagerActionNotify listener)
```

Add a Dvr Application Store Manager listener (see: IDvrStoreActionNotify)

**Parameters:**

listener - Dvr Application Store Manager listener

---

## removeDvrStreamManagerListener

```
public void removeDvrStreamManagerListener(IDvrStreamManagerActionNotify listener)
```

Remove a Dvr Application Store Manager listener (see: IDvrStoreActionNotify)

**Parameters:**

listener - Dvr Application Store Manager listener

---

## notifyDvrStreamManagerCreate

```
public void notifyDvrStreamManagerCreate(IDvrStreamManager dvrStoreManager)
```

Notify listeners that Dvr Application Store Manager has been created.

**Parameters:**

dvrStoreManager - Dvr Application Store Manager

---

## notifyDvrStreamManagerInit

```
public void notifyDvrStreamManagerInit(IDvrStreamManager dvrStoreManager)
```

Notify listeners that Dvr Application Store Manager has been initialized.

**Parameters:**

dvrStoreManager - Dvr Application Store Manager

---

## notifyDvrStreamManagerDestroy

```
public void notifyDvrStreamManagerDestroy(IDvrStreamManager dvrManager)
```

Notify listeners that Dvr Application Store Manager has been destroyed.

**Parameters:**

dvrManager - Dvr Application Store Manager

---

## getMediaReaderContentType

```
public int getMediaReaderContentType(String mediaType)
```

Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE\_\*)

**Parameters:**

mediaType - mediaType (such as flv or smil)

**Returns:**

content type (see IMediaReader.CONTENTTYPE\_\*)

---

(continued from last page)

## getMediaListProvider

```
public IMediaListProvider getMediaListProvider( )
```

Get the current media list provider. The media list provider is used to resolve amlst:streamname requests to a media list (equivalent to a SMIL file).

**Returns:**

media list provider

---

## setMediaListProvider

```
public void setMediaListProvider(IMediaListProvider mediaListProvider)
```

Set the current media list provider. The media list provider is used to resolve amlst:streamname requests to a media list (equivalent to a SMIL file).

**Parameters:**

mediaListProvider - media list provider

---

## getMediacasterRTPRTSPRTPTransportMode

```
public int getMediacasterRTPRTSPRTPTransportMode( )
```

RTP MediaCaster RTSP/RTP transport mode. See RTPMediaCaster.RTSPTRANSPORTMODE\_\*

**Returns:**

RTP MediaCaster RTSP/RTP transport mode

---

## setMediacasterRTPRTSPRTPTransportMode

```
public void setMediacasterRTPRTSPRTPTransportMode(int  
mediacasterRTPRTSPRTPTransportMode)
```

RTP MediaCaster RTSP/RTP transport mode. See RTPMediaCaster.RTSPTRANSPORTMODE\_\*

**Parameters:**

mediacasterRTPRTSPRTPTransportMode - RTP MediaCaster RTSP/RTP transport mode

---

## getProtocolUsage

```
public boolean[] getProtocolUsage( )
```

Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE\_\*)

**Returns:**

protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE\_\*)

---

## getProtocolUsage

```
public void getProtocolUsage(boolean[] protocolsInUse)
```

Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE\_\*)

---

## isDebugAppTimeout

```
public boolean isDebugAppTimeout( )
```

If true appTimeout processing will be logged.

(continued from last page)

**Returns:**

true appTimeout processing will be logged

---

**setDebugAppTimeout**

```
public void setDebugAppTimeout(boolean debugAppTimeout)
```

If true appTimeout processing will be logged.

**Parameters:**

debugAppTimeout - true appTimeout processing will be logged

---

**addRTPListener**

```
public void addRTPListener(IRTPSessionNotify rtpListener)
```

Add listener to be notified of RTPSession create and destroy.

**Parameters:**

rtpListener - RTP listener

---

**removeRTPListener**

```
public void removeRTPListener(IRTPSessionNotify rtpListener)
```

Remove listener to be notified of RTPSession create and destroy.

**Parameters:**

rtpListener - RTP listener

---

**notifyRTPSessionCreate**

```
public void notifyRTPSessionCreate(RTPSession rtpSession)
```

Notify RTP session create

**Parameters:**

rtpSession - rtp session

---

**notifyRTPSessionDestroy**

```
public void notifyRTPSessionDestroy(RTPSession rtpSession)
```

Notify RTP session destroy

**Parameters:**

rtpSession - rtp session

---

**addHTTPListener**

```
public void addHTTPListener(IHTTPSessionNotify httpListener)
```

Add listener to be notified of HTTPSession create and destroy.

**Parameters:**

httpListener - http listener

---

## removeHTTPListener

```
public void removeHTTPListener(IHTTPSessionNotify httpListener)
```

Remove listner to be notified of HTTPSession create and destroy.

**Parameters:**

httpListener - http listener

---

## notifyHTTPSessionCreate

```
public void notifyHTTPSessionCreate(IHTTPStreamerSession httpSession)
```

Notify HTTP session create

**Parameters:**

httpSession - HTTP session

---

## notifyHTTPSessionDestroy

```
public void notifyHTTPSessionDestroy(IHTTPStreamerSession httpSession)
```

Notify HTTP session destroy

**Parameters:**

httpSession - HTTP session

---

## com.wowza.wms.application Interface IApplicationInstanceNotify

public interface **IApplicationInstanceNotify**  
extends

IApplicationInstanceNotify: listener interface used by IApplication addApplicationInstanceListener

### Method Summary

void	<a href="#">onApplicationInstanceCreate</a> ( <a href="#">IApplicationInstance</a> applicationInstance) Triggered when applicationInstance created
void	<a href="#">onApplicationInstanceDestroy</a> ( <a href="#">IApplicationInstance</a> applicationInstance) Triggered when applicationInstance destroyed

### Methods

#### onApplicationInstanceCreate

public void **onApplicationInstanceCreate**([IApplicationInstance](#) applicationInstance)

Triggered when applicationInstance created

**Parameters:**

applicationInstance - applicationInstance

#### onApplicationInstanceDestroy

public void **onApplicationInstanceDestroy**([IApplicationInstance](#) applicationInstance)

Triggered when applicationInstance destroyed

**Parameters:**

applicationInstance - applicationInstance

## com.wowza.wms.application Interface IApplicationNotify

public interface **IApplicationNotify**  
extends

IApplicationNotify: listener interface used by IVHost addApplicationListener

### Method Summary

void	<a href="#">onApplicationCreate</a> ( <a href="#">IApplication</a> application) Triggered when application created
void	<a href="#">onApplicationDestroy</a> ( <a href="#">IApplication</a> application) Triggered when application destroyed

### Methods

#### onApplicationCreate

public void **onApplicationCreate**([IApplication](#) application)

Triggered when application created

**Parameters:**

application - application

#### onApplicationDestroy

public void **onApplicationDestroy**([IApplication](#) application)

Triggered when application destroyed

**Parameters:**

application - application

## com.wowza.wms.application Class WMSProperties

```

java.lang.Object
  |-- java.util.AbstractMap
        |-- java.util.HashMap
              |-- com.wowza.wms.application.WMSProperties
  
```

### All Implemented Interfaces:

java.util.Map, java.io.Serializable, Cloneable, java.util.Map

```

public class WMSProperties
extends java.util.HashMap
  
```

WMSProperties: generic properties container used by many class to store extended property information. Acts like a simple Map with some simple utilities for performing type conversion.

## Constructor Summary

public	<a href="#">WMSProperties()</a>
--------	---------------------------------

## Method Summary

static void	<a href="#">cloneProperties</a> ( <a href="#">WMSProperties</a> from, <a href="#">WMSProperties</a> to) Copy all properties from "from" properties object to "to" properties object.
String[]	<a href="#">getAllAsStrings()</a> Return all properties as String[].
Object	<a href="#">getProperty</a> (String name) Get property value as generic object.
boolean	<a href="#">getPropertyBoolean</a> (String name, boolean defaultVal) Get property as boolean, return default value if does not exist.
double	<a href="#">getPropertyDouble</a> (String name, double defaultVal) Get property as double, return default value if does not exist.
int	<a href="#">getPropertyInt</a> (String name, int defaultVal) Get property as int, return default value if does not exist.
long	<a href="#">getPropertyLong</a> (String name, long defaultVal) Get property as long, return default value if does not exist.
String	<a href="#">getPropertyStr</a> (String name) Get property as String
String	<a href="#">getPropertyStr</a> (String name, String defaultVal) Get property as String, return default value if does not exist.
void	<a href="#">putAll</a> (java.util.Map m)

void	<a href="#">setProperty</a> (String name, Object value) Set property to generic object.
String	<a href="#">toString</a> ()

#### Methods inherited from class java.util.HashMap

clear, clone, containsKey, containsValue, entrySet, get, isEmpty, keySet, put, putAll, remove, size, values

#### Methods inherited from class java.util.AbstractMap

clear, clone, containsKey, containsValue, entrySet, equals, get, hashCode, isEmpty, keySet, put, putAll, remove, size, toString, values

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface java.util.Map

clear, containsKey, containsValue, entrySet, equals, get, hashCode, isEmpty, keySet, put, putAll, remove, size, values

#### Methods inherited from interface java.util.Map

clear, containsKey, containsValue, entrySet, equals, get, hashCode, isEmpty, keySet, put, putAll, remove, size, values

## Constructors

### WMSProperties

```
public WMSProperties()
```

## Methods

### putAll

```
public void putAll(java.util.Map m)
```

### cloneProperties

```
public static void cloneProperties(WMSProperties from, WMSProperties to)
```

Copy all properties from "from" properties object to "to" properties object.

#### Parameters:

from - source properties



(continued from last page)

to - destination properties

---

## setProperty

```
public void setProperty(String name,  
                        Object value)
```

Set property to generic object.

### Parameters:

name - property name  
value - value

---

## getProperty

```
public Object getProperty(String name)
```

Get property value as generic object.

### Parameters:

name - property name

### Returns:

value, null if does not exist

---

## getPropertyStr

```
public String getPropertyStr(String name)
```

Get property as String

### Parameters:

name - property name

### Returns:

value as String, null if does not exist

---

## getPropertyStr

```
public String getPropertyStr(String name,  
                             String defaultVal)
```

Get property as String, return default value if does not exist.

### Parameters:

name - property name  
defaultVal - default value

### Returns:

value as String, defaultVal if does not exist

---

## getPropertyBoolean

```
public boolean getPropertyBoolean(String name,  
                                   boolean defaultVal)
```

Get property as boolean, return default value if does not exist.

### Parameters:

(continued from last page)

name - property name  
defaultVal - default value

**Returns:**

value as boolean, defaultVal if does not exist

---

## getPropertyInt

```
public int getPropertyInt(String name,  
    int defaultVal)
```

Get property as int, return default value if does not exist.

**Parameters:**

name - property name  
defaultVal - default value

**Returns:**

value as boolean, defaultVal if does not exist

---

## getPropertyLong

```
public long getPropertyLong(String name,  
    long defaultVal)
```

Get property as long, return default value if does not exist.

**Parameters:**

name - property name  
defaultVal - default value

**Returns:**

value as long, defaultVal if does not exist

---

## getPropertyDouble

```
public double getPropertyDouble(String name,  
    double defaultVal)
```

Get property as double, return default value if does not exist.

**Parameters:**

name - property name  
defaultVal - default value

**Returns:**

value as double, defaultVal if does not exist

---

## getAllAsStrings

```
public String[] getAllAsStrings()
```

Return all properties as String[]. Format is "key=value".

**Returns:**

all properties as String[]

---

(continued from last page)

## **toString**

```
public String toString()
```

---

Package

**com.wowza.wms.authentication**

## com.wowza.wms.authentication

### Class AuthenticateUsernamePasswordProviderBase

java.lang.Object

└--com.wowza.wms.authentication.AuthenticateUsernamePasswordProviderBase

All Implemented Interfaces:

[IAuthenticateUsernamePasswordProvider](#)

public abstract class **AuthenticateUsernamePasswordProviderBase**

extends Object

implements [IAuthenticateUsernamePasswordProvider](#)

Base class for implementing HTTP and RTSP based custom authentication class.

#### Field Summary

protected	<a href="#">client</a>
protected	<a href="#">rtpSession</a>
protected	<a href="#">vhost</a>

#### Constructor Summary

public	<a href="#">AuthenticateUsernamePasswordProviderBase()</a>
--------	--

#### Method Summary

<a href="#">IClient</a>	<a href="#">getClient()</a> Get client
<a href="#">RTPSession</a>	<a href="#">getRTPSession()</a> Get RTP Session
<a href="#">IVHost</a>	<a href="#">getVHost()</a> Get vhost
void	<a href="#">setClient(<a href="#">IClient</a> client)</a> Set client
void	<a href="#">setRTPSession(<a href="#">RTPSession</a> rtpSession)</a> Set RTP Session
void	<a href="#">setVHost(<a href="#">IVHost</a> vhost)</a> Set vhost

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface**[com.wowza.wms.authentication.IAuthenticateUsernamePasswordProvider](#)[getClient](#), [getPassword](#), [getRTPSession](#), [getVHost](#), [setClient](#), [setRTPSession](#), [setVHost](#), [userExists](#)

## Fields

**vhost**protected com.wowza.wms.vhost.IVHost **vhost****client**protected com.wowza.wms.client.IClient **client****rtpSession**protected com.wowza.wms.rtp.model.RTPSession **rtpSession**

## Constructors

**AuthenticateUsernamePasswordProviderBase**public **AuthenticateUsernamePasswordProviderBase**()

## Methods

**getVHost**public [IVHost](#) **getVHost**()

Get vhost

**Returns:**

vhost

**setVHost**public void **setVHost**([IVHost](#) vhost)

Set vhost

**Parameters:**

vhost - vhost

(continued from last page)

## getRTPSession

```
public RTPSession getRTPSession()
```

Get RTP Session

**Returns:**

RTP Session

---

## setRTPSession

```
public void setRTPSession(RTPSession rtpSession)
```

Set RTP Session

**Parameters:**

rtpSession - RTP Session

---

## getClient

```
public IClient getClient()
```

Get client

**Returns:**

client

---

## setClient

```
public void setClient(IClient client)
```

Set client

**Parameters:**

client - client

## com.wowza.wms.authentication Interface IAuthenticate

public interface **IAuthenticate**  
extends

IAuthenticate: HTTP and RTSP authentication interface

### Field Summary

public static final	<a href="#">PASSWORDFILEFORMAT_CLEAR</a> Value: <b>1</b>
public static final	<a href="#">PASSWORDFILEFORMAT_UNKNOWN</a> Value: <b>0</b>

### Method Summary

void	<a href="#">init</a> ( <a href="#">IApplicationInstance</a> appInstance, AuthenticationItem authenticationItem) Initialize authentication class when instantiated as part of an application instance
void	<a href="#">init</a> ( <a href="#">IVHost</a> vhost, AuthenticationItem authenticationItem) Initialize authentication class when instantiated as part of a vhost

### Fields

#### PASSWORDFILEFORMAT\_UNKNOWN

public static final int **PASSWORDFILEFORMAT\_UNKNOWN**

Constant value: **0**

#### PASSWORDFILEFORMAT\_CLEAR

public static final int **PASSWORDFILEFORMAT\_CLEAR**

Constant value: **1**

### Methods

#### init

public void **init**([IApplicationInstance](#) appInstance,  
AuthenticationItem authenticationItem)

Initialize authentication class when instantiated as part of an application instance



(continued from last page)

**Parameters:**

appInstance - application instance  
authenticationItem - authentication item

---

**init**

```
public void init(IVHost vhost,  
                AuthenticationItem authenticationItem)
```

Initialize authentication class when instantiated as part of a vhost

**Parameters:**

vhost - vhost  
authenticationItem - authentication item

## com.wowza.wms.authentication Interface IAuthenticateHTTPProvider

public interface **IAuthenticateHTTPProvider**  
extends

IAuthenticateHTTPProvider: HTTP authentication provider

### Method Summary

boolean	<a href="#">authenticateHTTPProvider</a> ( <a href="#">IVHost</a> vhost, <a href="#">IHTTPRequest</a> req, <a href="#">IHTTPResponse</a> resp) Called for each HTTP authentication
---------	---

### Methods

#### authenticateHTTPProvider

```
public boolean authenticateHTTPProvider(IVHost vhost,  
    IHTTPRequest req,  
    IHTTPResponse resp)
```

Called for each HTTP authentication

**Parameters:**

vhost - virtual host  
req - HTTP request  
resp - HTTP response

**Returns:**

true if authentication was successful

## com.wowza.wms.authentication Interface IAuthenticateRTSP

public interface **IAuthenticateRTSP**  
extends

IAuthenticateRTSP: RTSP authentication provider

### Method Summary

boolean	<code><a href="#">authenticateRTSP</a>(<a href="#">RTPSession</a> rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</code> Called for each RTSP authentication
---------	---

### Methods

#### **authenticateRTSP**

```
public boolean authenticateRTSP(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Called for each RTSP authentication

#### **Parameters:**

`rtspSession` - RTP session  
`req` - RTSP request  
`resp` - RTSP response

#### **Returns:**

true if authentication was successful

## com.wowza.wms.authentication Interface IAuthenticateSIP

public interface **IAuthenticateSIP**  
extends

IAuthenticateRTSP: RTSP authentication provider

### Method Summary

boolean	<code><a href="#">authenticateSIP</a>(<a href="#">RTPSession</a> rtspSession, com.wowza.wms.sip.SIPRequestMessage req, com.wowza.wms.sip.SIPResponseMessages resp)</code> Called for each RTSP authentication
---------	--

### Methods

#### **authenticateSIP**

```
public boolean authenticateSIP(RTPSession rtspSession,  
    com.wowza.wms.sip.SIPRequestMessage req,  
    com.wowza.wms.sip.SIPResponseMessages resp)
```

Called for each RTSP authentication

##### **Parameters:**

`rtspSession` - RTP session  
`req` - RTSP request  
`resp` - RTSP response

##### **Returns:**

true if authentication was successful

## com.wowza.wms.authentication Interface IAuthenticateUsernamePasswordProvider

All Known Implementing Classes:

[AuthenticateUsernamePasswordProviderBase](#)

public interface **IAuthenticateUsernamePasswordProvider**  
extends

IAuthenticateUsernamePasswordProvider: HTTP and RTSP username/password validator interface

### Method Summary

<a href="#">IClient</a>	<a href="#">getClient()</a> Get client
String	<a href="#">getPassword(String username)</a> Get password for a given user
<a href="#">RTPSession</a>	<a href="#">getRTPSession()</a> Get RTP session
<a href="#">IVHost</a>	<a href="#">getVHost()</a> Get vhost
void	<a href="#">setClient(<a href="#">IClient</a> client)</a> Set client
void	<a href="#">setRTPSession(<a href="#">RTPSession</a> rtpSession)</a> Set RTP session
void	<a href="#">setVHost(<a href="#">IVHost</a> vhost)</a> Set vhost
boolean	<a href="#">userExists(String username)</a> Return true if user exists

### Methods

#### **userExists**

public boolean **userExists**(String username)

Return true if user exists

#### **Parameters:**

username - username

#### **Returns:**

true if user exists

(continued from last page)

## getPassword

```
public String getPassword(String username)
```

Get password for a given user

**Parameters:**

username - username

**Returns:**

password

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

**Returns:**

vhost

---

## setVHost

```
public void setVHost(IVHost vhost)
```

Set vhost

**Parameters:**

vhost - vhost

---

## getClient

```
public IClient getClient()
```

Get client

**Returns:**

client

---

## setClient

```
public void setClient(IClient client)
```

Set client

**Parameters:**

client - client

---

## getRTPSession

```
public RTPSession getRTPSession()
```

Get RTP session

**Returns:**

RTP session

---

(continued from last page)

## setRTPSession

```
public void setRTPSession(RTPSession rtpSession)
```

Set RTP session

**Parameters:**

rtpSession - RTP session

---

Package

**com.wowza.wms.client**



## com.wowza.wms.client Class ConnectionCounter

```
java.lang.Object
|
+-com.wowza.wms.client.ConnectionCounterBase
|
+-com.wowza.wms.client.ConnectionCounter
```

```
public class ConnectionCounter
extends ConnectionCounterBase
```

### Fields inherited from class com.wowza.wms.client.ConnectionCounterBase

DATEFORMATSTR, NEVERSTR, REJECTREASON\_APPLICATION, REJECTREASON\_COUNT, REJECTREASON\_LICENSE

### Constructor Summary

public	<a href="#">ConnectionCounter()</a> Create empty ConnectionCounter
--------	---

### Method Summary

void	<a href="#">acceptConnection</a> (ConnectionHolder connectionHolder, byte[] license) Accept a new connection.
void	<a href="#">addConnectionListener</a> (IConnectionNotify connectionNotify) Add a connection listener.
void	<a href="#">decrement</a> (ConnectionHolder connectionHolder, boolean isValid, java.util.Date date, long stamp, byte[] license) Decrement connection counters.
void	<a href="#">disconnect</a> (ConnectionHolder connectionHolder, byte[] license) Disconnect connection.
long	<a href="#">getCurrent</a> () Get total number of client currently conencted to this object.
long	<a href="#">getLastConnectAcceptedStamp</a> () Get time (milliseconds) of the last conenction to this object.
String	<a href="#">getLastConnectAcceptedStampString</a> () Get time (milliseconds) of the last conenction to this object as formatted string.
java.util.Date	<a href="#">getLastConnectAcceptedTime</a> () Get time (milliseconds) of the last accepted conenction to this object.
String	<a href="#">getLastConnectAcceptedTimeString</a> () Get time (milliseconds) of the last accepted conenction to this object as formatted string.
long	<a href="#">getLastConnectRejectedByReasonStamp</a> (int reason) Get time (milliseconds) of the last rejected conenction by reason to this object.

String	<a href="#"><u>getLastConnectRejectedByReasonStampString</u></a> (int reason) Get time (milliseconds) of the last rejected connection by reason to this object as formatted string.
java.util.Date	<a href="#"><u>getLastConnectRejectedByReasonTime</u></a> (int reason) Get date and time of last rejected connection by reason to this object as Date object.
String	<a href="#"><u>getLastConnectRejectedByReasonTimeString</u></a> (int reason) Get date and time of last rejected connection by reason to this object as formatted string.
long	<a href="#"><u>getLastConnectRejectedStamp</u></a> () Get time (milliseconds) of the last rejected connection to this object.
String	<a href="#"><u>getLastConnectRejectedStampString</u></a> () Get time (milliseconds) of the last rejected connection to this object as formatted string.
java.util.Date	<a href="#"><u>getLastConnectRejectedTime</u></a> () Get date and time of last rejected connection to this object as Date object.
String	<a href="#"><u>getLastConnectRejectedTimeString</u></a> () Get date and time of last rejected connection to this object as formatted string.
long	<a href="#"><u>getLastDisconnectStamp</u></a> () Get time (milliseconds) of the last disconnected connection to this object.
String	<a href="#"><u>getLastDisconnectStampString</u></a> () Get time (milliseconds) of the last disconnected connection to this object as formatted string.
java.util.Date	<a href="#"><u>getLastDisconnectTime</u></a> () Get date and time of last disconnected connection to this object as Date object.
String	<a href="#"><u>getLastDisconnectTimeString</u></a> () Get date and time of last disconnected connection to this object as Date object as formatted string.
long	<a href="#"><u>getTotal</u></a> () Get total number of connection attempts to this object.
long	<a href="#"><u>getTotalAccepted</u></a> () Get total number of accepted connections to this object.
long	<a href="#"><u>getTotalRejected</u></a> () Get total number of rejected connections to this object.
void	<a href="#"><u>incrementAccept</u></a> (ConnectionHolder connectionHolder, java.util.Date date, long stamp, byte[] license) Increment accepted connections.
void	<a href="#"><u>incrementReject</u></a> (ConnectionHolder connectionHolder, int reason, java.util.Date date, long stamp, byte[] license) Increment reject connection.
void	<a href="#"><u>rejectConnection</u></a> (ConnectionHolder connectionHolder, int reason, byte[] license) Reject connection.
void	<a href="#"><u>removeConnectionListener</u></a> (IConnectionNotify connectionNotify) Remove connection listener
void	<a href="#"><u>setConnectionValidator</u></a> (IConnectionValidator connectionValidator) Set the connection validator.

boolean

[validateNewConnection](#)(ConnectionHolder connectionHolder, byte[] license)

Validate a new connection.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### ConnectionCounter

```
public ConnectionCounter()
```

Create empty ConnectionCounter

## Methods

### addConnectionListener

```
public void addConnectionListener(IConnectionNotify connectionNotify)
```

Add a connection listener. Receives following events: onClientConnect, onClientDisconnect, onClientAccept and onClientReject.

**Parameters:**

connectionNotify - connection listener

### removeConnectionListener

```
public void removeConnectionListener(IConnectionNotify connectionNotify)
```

Remove connection listener

**Parameters:**

connectionNotify - connection listener

### setConnectionValidator

```
public void setConnectionValidator(IConnectionValidator connectionValidator)
```

Set the connection validator.

**Parameters:**

connectionValidator - connection validator

### validateNewConnection

```
public boolean validateNewConnection(ConnectionHolder connectionHolder,  
byte[] license)
```

Validate a new connection.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

(continued from last page)

**Parameters:**

connectionHolder - connection holder  
license - security data

**Returns:**

true if connection is accepted

---

## acceptConnection

```
public void acceptConnection(ConnectionHolder connectionHolder,  
    byte[] license)
```

Accept a new connection.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

**Parameters:**

connectionHolder - connection holder  
license - security data

---

## incrementAccept

```
public void incrementAccept(ConnectionHolder connectionHolder,  
    java.util.Date date,  
    long stamp,  
    byte[] license)
```

Increment accepted connections.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

**Parameters:**

connectionHolder - connection holder  
date - date the connection occurred  
stamp - time stamp connection occurred (milliseconds)  
license - security data

---

## rejectConnection

```
public void rejectConnection(ConnectionHolder connectionHolder,  
    int reason,  
    byte[] license)
```

Reject connection.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

**Parameters:**

connectionHolder - connection holder  
reason - reason the connection was refused. See REJECTREASON\_\*  
license - security data

---

(continued from last page)

## incrementReject

```
public void incrementReject(ConnectionHolder connectionHolder,  
    int reason,  
    java.util.Date date,  
    long stamp,  
    byte[] license)
```

Increment reject connection.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

**Parameters:**

connectionHolder - connection holder  
reason - reason the connection was refused. See REJECTREASON\_\*  
date - date the connection occurred  
stamp - time stamp connection occurred (milliseconds)  
license - security data

---

## disconnect

```
public void disconnect(ConnectionHolder connectionHolder,  
    byte[] license)
```

Disconnect connection.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

**Parameters:**

connectionHolder - connection holder  
license - security data

---

## decrement

```
public void decrement(ConnectionHolder connectionHolder,  
    boolean isValid,  
    java.util.Date date,  
    long stamp,  
    byte[] license)
```

Decrement connection counters.

**NOTE:** This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

**Parameters:**

connectionHolder - connection holder  
isValid - is a valid connection  
date - date the connection occurred  
stamp - time stamp connection occurred (milliseconds)  
license - security data

---

## getCurrent

```
public long getCurrent()
```

Get total number of client currently connected to this object.

**Returns:**

total number of client currently connected to this object

## getLastConnectAcceptedStamp

```
public long getLastConnectAcceptedStamp()
```

Get time (milliseconds) of the last conenction to this object.

**Returns:**

time (milliseconds) of the last conenction to this object

---

## getLastConnectAcceptedStampString

```
public String getLastConnectAcceptedStampString()
```

Get time (milliseconds) of the last conenction to this object as formatted string.

**Returns:**

time (milliseconds) of the last conenction to this object as formatted string

---

## getLastConnectAcceptedTime

```
public java.util.Date getLastConnectAcceptedTime()
```

Get time (milliseconds) of the last accepeted conenction to this object.

**Returns:**

time (milliseconds) of the last accepeted conenction to this object

---

## getLastConnectAcceptedTimeString

```
public String getLastConnectAcceptedTimeString()
```

Get time (milliseconds) of the last accepeted conenction to this object as formatted string.

**Returns:**

time (milliseconds) of the last accepeted conenction to this object as formatted string

---

## getLastConnectRejectedStamp

```
public long getLastConnectRejectedStamp()
```

Get time (milliseconds) of the last rejected conenction to this object.

**Returns:**

time (milliseconds) of the last rejected conenction to this object

---

## getLastConnectRejectedStampString

```
public String getLastConnectRejectedStampString()
```

Get time (milliseconds) of the last rejected conenction to this object as formatted string.

**Returns:**

time (milliseconds) of the last rejected conenction to this object as formatted string

---

## getLastConnectRejectedTime

```
public java.util.Date getLastConnectRejectedTime()
```

---

(continued from last page)

Get date and time of last rejected connection to this object as Date object.

**Returns:**

date and time of last reject connection to this object as Date object

---

## getLastConnectRejectedTimeString

```
public String getLastConnectRejectedTimeString()
```

Get date and time of last rejected connection to this object as formatted string.

**Returns:**

date and time of last reject connection to this object as formatted string

---

## getLastConnectRejectedByReasonStampString

```
public String getLastConnectRejectedByReasonStampString(int reason)
```

Get time (milliseconds) of the last rejected connection by reason to this object as formatted string.

**Parameters:**

reason - reason, see REJECTREASON\_\*

**Returns:**

time (milliseconds) of the last rejected connection by reason to this object as formatted string

---

## getLastConnectRejectedByReasonStamp

```
public long getLastConnectRejectedByReasonStamp(int reason)
```

Get time (milliseconds) of the last rejected connection by reason to this object.

**Parameters:**

reason - reason, see REJECTREASON\_\*

**Returns:**

time (milliseconds) of the last rejected connection by reason to this object

---

## getLastConnectRejectedByReasonTime

```
public java.util.Date getLastConnectRejectedByReasonTime(int reason)
```

Get date and time of last rejected connection by reason to this object as Date object.

**Parameters:**

reason - reason, see REJECTREASON\_\*

**Returns:**

date and time of last reject connection by reason to this object as Date object

---

## getLastConnectRejectedByReasonTimeString

```
public String getLastConnectRejectedByReasonTimeString(int reason)
```

Get date and time of last rejected connection by reason to this object as formatted string.

**Parameters:**

reason - reason, see REJECTREASON\_\*

(continued from last page)

**Returns:**

date and time of last rejected connection by reason to this object as formatted string

---

**getLastDisconnectStampString**

```
public String getLastDisconnectStampString( )
```

Get time (milliseconds) of the last disconnected connection to this object as formatted string.

**Returns:**

time (milliseconds) of the last disconnected connection to this object as formatted string

---

**getLastDisconnectStamp**

```
public long getLastDisconnectStamp( )
```

Get time (milliseconds) of the last disconnected connection to this object.

**Returns:**

time (milliseconds) of the last disconnected connection to this object

---

**getLastDisconnectTime**

```
public java.util.Date getLastDisconnectTime( )
```

Get date and time of last disconnected connection to this object as Date object.

**Returns:**

date and time of last disconnected connection to this object as Date object

---

**getLastDisconnectTimeString**

```
public String getLastDisconnectTimeString( )
```

Get date and time of last disconnected connection to this object as Date object as formatted string.

**Returns:**

date and time of last disconnected connection to this object as Date object as formatted string

---

**getTotal**

```
public long getTotal( )
```

Get total number of connection attempts to this object.

**Returns:**

total number of connection attempts to this object

---

**getTotalAccepted**

```
public long getTotalAccepted( )
```

Get total number of accepted connections to this object.

**Returns:**

total number of accepted connections to this object



## getTotalRejected

```
public long getTotalRejected()
```

Get total number of rejected connections to this object.

**Returns:**

total number of rejected connections to this object

## com.wowza.wms.client Interface IClient

public interface **IClient**  
extends

IClient: public interface to Client object.

### Field Summary

public static final	<a href="#">AUDIOSAMPLE_ACCESS_ALL</a> Value: *
public static final	<a href="#">AUDIOSAMPLE_ACCESS_NONE</a> Value:
public static final	<a href="#">READ_ACCESS_ALL</a> Value: *
public static final	<a href="#">READ_ACCESS_NONE</a> Value:
public static final	<a href="#">VIDEOSAMPLE_ACCESS_ALL</a> Value: *
public static final	<a href="#">VIDEOSAMPLE_ACCESS_NONE</a> Value:
public static final	<a href="#">WRITE_ACCESS_ALL</a> Value: *
public static final	<a href="#">WRITE_ACCESS_NONE</a> Value:

### Method Summary

void	<a href="#">acceptConnection</a> ( ) Accept connection
void	<a href="#">acceptConnection</a> ( <a href="#">AMFData</a> successObj) Accept connection
void	<a href="#">acceptConnection</a> (String successStr) Accept connection
void	<a href="#">addAcceptConnectionAttribute</a> (String key, <a href="#">AMFDataObj</a> item) Add and attribute to the resultObj that gets passed back to the client on successful connection

void	<a href="#"><u>addAcceptConnectionAttribute</u></a> (String key, String item) Add and attribute to the resultObj that gets passed back to the client on successful connection
void	<a href="#"><u>call</u></a> (String handlerName) Simplified call client method/handler call.
void	<a href="#"><u>call</u></a> (String handlerName, <a href="#"><u>IModuleCallResult</u></a> resultObj, Object[] params) Call client method/handler.
void	<a href="#"><u>clearFastPlaySettings</u></a> ( ) Force clear the fastPlay settings
void	<a href="#"><u>fcSubscribe</u></a> (String streamName) Subscribe to a live stream (for live stream repeater to start start from edge to origin)
void	<a href="#"><u>fcSubscribe</u></a> (String streamName, String mediaCasterType) Subscribe to a live stream (use a particular mediaCasterType)
void	<a href="#"><u>fcUnSubscribe</u></a> (String streamName) UnSubscribe from a stream
void	<a href="#"><u>fcUnSubscribeAll</u></a> ( ) UnSubscribe to all streams that this client is current subscribed to
<a href="#"><u>IApplicationInstance</u></a>	<a href="#"><u>getAppInstance</u></a> ( ) Get parent applicationInstance.
<a href="#"><u>IApplication</u></a>	<a href="#"><u>getApplication</u></a> ( ) Get parent application.
int	<a href="#"><u>getBufferTime</u></a> ( ) Get default buffer time for newly created mediaStream objects
int	<a href="#"><u>getClientId</u></a> ( ) Get client id.
long	<a href="#"><u>getConnectTime</u></a> ( ) Get time in milliseconds the client connected to the server.
String	<a href="#"><u>getDateStarted</u></a> ( ) Get date and time of client connection
<a href="#"><u>ElapsedTimer</u></a>	<a href="#"><u>getElapsedTime</u></a> ( ) Get elapsed time client has been connected.
<a href="#"><u>FastPlaySettings</u></a>	<a href="#"><u>getFastPlaySettings</u></a> ( ) Get the current fastPlay settings.
String	<a href="#"><u>getFlashVer</u></a> ( ) Get client flash version (same as FMS getAgent())
int	<a href="#"><u>getIdleFrequency</u></a> ( ) Get client idle frequency (milliseconds)
String	<a href="#"><u>getIp</u></a> ( ) Client ip address
long	<a href="#"><u>getLastValidateTime</u></a> ( ) Get last time (millisecond) the connection was validated with a ping

int	<a href="#"><u>getLiveRepeaterCapabilities()</u></a> Get the live repeater capabilities of this connection
String	<a href="#"><u>getLiveStreamPacketizerList()</u></a> Get the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)
String	<a href="#"><u>getLiveStreamTranscoderList()</u></a> Get the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)
int	<a href="#"><u>getMaximumPendingWriteBytes()</u></a> Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
int	<a href="#"><u>getMaximumSetBufferTime()</u></a> Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getMediaIOPerformanceCounter()</u></a> Get performance counter for media bytes transferred to this client.
int	<a href="#"><u>getObjectEncoding()</u></a> Get the object encoding level
String	<a href="#"><u>getPageUrl()</u></a> Get the pageUrl for this connection.
long	<a href="#"><u>getPingRoundTripTime()</u></a> Get turn around time (milliseconds) of last ping request
int	<a href="#"><u>getPingTimeout()</u></a> Get the ping timeout (milliseconds)
java.util.List	<a href="#"><u>getPlayStreams()</u></a> Get a collection of all play streams.
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties()</u></a> Get client properties
int	<a href="#"><u>getProtocol()</u></a> Get connection protocol (1 = RTMP, 3 = RTMPT)
java.util.List	<a href="#"><u>getPublishStreams()</u></a> Get a collection of publish streams.
String	<a href="#"><u>getQueryStr()</u></a> Get the query string part of the connection string.
String	<a href="#"><u>getReferrer()</u></a> Get the referrer data for this connection.
String	<a href="#"><u>getRepeaterOriginUrl()</u></a> Get the origin URL used by the Live Stream Repeater
<a href="#"><u>AMFObj</u></a>	<a href="#"><u>getRespAMFAudioObj(IMediaStream stream)</u></a> Get the audio response AMFObj for a given mediaStream
<a href="#"><u>AMFObj</u></a>	<a href="#"><u>getRespAMFDataObj(IMediaStream stream)</u></a> Get the data response AMFObj for a given mediaStream

<a href="#">AMFObj</a>	<a href="#">getRespAMFVideoObj</a> ( <a href="#">IMediaStream</a> stream) Get the video response AMFObj for a given mediaStream
<a href="#">ResponseFunctions</a>	<a href="#">getRespFunctions</a> () Get client responseFunctions object.
<a href="#">AMFObj</a>	<a href="#">getResponseAMFObj</a> (int index) Get the response channel AMFObj for channel index.
<a href="#">RTPStream</a>	<a href="#">getRTPStream</a> () If this client was created due to an RTP connection to the server return the underlying RTPStream object
<a href="#">HostPort</a>	<a href="#">getServerHostPort</a> () Get the hostPort object for the connection that is servicing this client
String	<a href="#">getSharedObjectReadAccess</a> () Get the shared object read access value.
String	<a href="#">getSharedObjectWriteAccess</a> () Get the shared object write access value.
String	<a href="#">getStreamAudioSampleAccess</a> () Get the audio sample access value.
java.io.File	<a href="#">getStreamFile</a> (String streamName) Get File object for stream with given name.
java.io.File	<a href="#">getStreamFile</a> (String streamName, String streamExt) Get File object for stream with given name and extension.
java.io.File	<a href="#">getStreamFile</a> (String streamName, String streamExt, boolean doCreateFolder) Get File object for stream with given name and extension.
String	<a href="#">getStreamReadAccess</a> () Get the stream read access value.
String	<a href="#">getStreamType</a> () Get default streamType
String	<a href="#">getStreamVideoSampleAccess</a> () Get the video sample access value.
String	<a href="#">getStreamWriteAccess</a> () Get the stream write access value.
String	<a href="#">getTimeRunning</a> () Get elapsed time of connection
double	<a href="#">getTimeRunningSeconds</a> () Get time running in seconds
<a href="#">IOPerformanceCounter</a>	<a href="#">getTotalIOPerformanceCounter</a> () Get performance counter for all bytes transferred to this client.
String	<a href="#">getUri</a> () Get the full URI of the connection string

<a href="#">IVHost</a>	<a href="#">getVHost()</a> Get parent vHost
com.wowza.wms.protocol.WOWZSession	<a href="#">getWowzSession()</a>
ClientWriteListener	<a href="#">getWriteListener()</a> Object that tracks write operations
boolean	<a href="#">isAcceptConnection()</a> Is auto accept connection
boolean	<a href="#">isConnected()</a> Is this client connected
boolean	<a href="#">isEncrypted()</a> Is this connection encrypted (RTMPE or RTMPTE)
boolean	<a href="#">isFlashMediaLiveEncoder()</a> Returns true if this connection is the Flash Media Live Encoder
boolean	<a href="#">isFlashVersion10()</a> Returns true if the Flash version is equal or greater than 10.x.x.x
boolean	<a href="#">isFlashVersion90115()</a> Returns true if the Flash version is equal or greater than 9.0.115.x
boolean	<a href="#">isFlashVersionH264Capable()</a> Returns true if the connected client is capable of playing H.264 video (Flash player 9.0.45.x or greater)
boolean	<a href="#">isLiveRepeater()</a> Returns true if this connection is from the live stream repeater
boolean	<a href="#">isObjectEncodingAMF0()</a> Is the object encoding for this client AMF0
boolean	<a href="#">isObjectEncodingAMF3()</a> Is the object encoding for this client AMF3
boolean	<a href="#">isSecure()</a> Is this connection protected by either SSL or encryption (RTMPE, RTMPTE, RTMPS)
boolean	<a href="#">isSSL()</a> Is this connection SSL (RTMPS)
boolean	<a href="#">isValidFMLEConnections()</a> Returns true if validating FMLE connection (default is false)
int	<a href="#">ping(IModulePingResult pingResult)</a> Ping client.
void	<a href="#">redirectConnection(String url)</a> Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)
void	<a href="#">redirectConnection(String url, String description)</a> Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

void	<a href="#"><u>redirectConnection</u></a> (String url, String description, <a href="#"><u>AMFData</u></a> errorObj) Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302).
void	<a href="#"><u>redirectConnection</u></a> (String url, String description, String errorStr) Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)
void	<a href="#"><u>rejectConnection</u></a> () Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<a href="#"><u>rejectConnection</u></a> ( <a href="#"><u>AMFData</u></a> errorObj) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<a href="#"><u>rejectConnection</u></a> (String errorStr) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<a href="#"><u>rejectConnection</u></a> (String description, <a href="#"><u>AMFData</u></a> errorObj) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<a href="#"><u>rejectConnection</u></a> (String description, String errorStr) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<a href="#"><u>reparentClient</u></a> ( <a href="#"><u>IVHost</u></a> vhost) Move a client object to a new vhost.
void	<a href="#"><u>setAcceptConnection</u></a> (boolean acceptConnection) Set the default for accept connection
void	<a href="#"><u>setAcceptConnectionDescription</u></a> (String description) Call this method from onConnect to set the info.description property returned in NetConnection onStatus handler
void	<a href="#"><u>setAcceptConnectionExObj</u></a> ( <a href="#"><u>AMFDataObj</u></a> acceptConnectionExObj) Call this method from onConnect to set the info.ex property returned in NetConnection onStatus handler
void	<a href="#"><u>setAcceptConnectionObj</u></a> ( <a href="#"><u>AMFData</u></a> acceptConnectionObj) Call this method from onConnect to add an "application" property to the info object that is passed back to the Flash client in the onStatus handler.
void	<a href="#"><u>setBufferTime</u></a> (int bufferTime) Set default buffer time for newly created mediaStream objects
void	<a href="#"><u>setFastPlaySettings</u></a> ( <a href="#"><u>FastPlaySettings</u></a> fastPlaySettings) Set fastPlay settings
void	<a href="#"><u>setFlashVer</u></a> (String flashVer) Set client flash version
void	<a href="#"><u>setIdleFrequency</u></a> (int idleFrequency) Set client idle frequency (milliseconds)
void	<a href="#"><u>setLastValidateTime</u></a> (long lastValidateTime) Set the last time (milliseconds) the connection was validated with ping

void	<a href="#"><u>setLiveRepeaterCapabilities</u></a> (int liveRepeaterCapabilities) Set the live repeater capabilities of this connection
void	<a href="#"><u>setLiveStreamPacketizerList</u></a> (String liveStreamPacketizerList) Set the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)
void	<a href="#"><u>setLiveStreamTranscoderList</u></a> (String liveStreamTranscoderList) Set the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)
void	<a href="#"><u>setObjectEncoding</u></a> (int objectEncoding) Set the object encoding level
void	<a href="#"><u>setRepeaterOriginUrl</u></a> (String repeaterOriginUrl) Set the origin URL used by the Live Stream Repeater
void	<a href="#"><u>setSharedObjectReadAccess</u></a> (String sharedObjectReadAccess) Set the shared object read access value.
void	<a href="#"><u>setSharedObjectWriteAccess</u></a> (String sharedObjectWriteAccess) Set the shared object write access value.
void	<a href="#"><u>setShutdownClient</u></a> (boolean shutdownClient) Gracefully and forcefully shutdown a client.
void	<a href="#"><u>setStreamAudioSampleAccess</u></a> (String audioSampleAccess) Set the stream audio sample access value.
void	<a href="#"><u>setStreamReadAccess</u></a> (String streamReadAccess) Set the stream object read access value.
void	<a href="#"><u>setStreamType</u></a> (String streamType) Set default streamType
void	<a href="#"><u>setStreamVideoSampleAccess</u></a> (String videoSampleAccess) Set the stream video sample access value.
void	<a href="#"><u>setStreamWriteAccess</u></a> (String streamWriteAccess) Set the stream object write access value.
void	<a href="#"><u>setThreadContext</u></a> ( ) Set the thread logging context to this client
void	<a href="#"><u>setValidateFMLEConnections</u></a> (boolean validateFMLEConnections) Returns true if validating FMLE connection (default is false)
void	<a href="#"><u>setWowzSession</u></a> (com.wowza.wms.protocol.wowz.WOWZSession wowzSession)
void	<a href="#"><u>shutdownClient</u></a> ( ) Gracefully shutdown a client.
int	<a href="#"><u>testFlashVersion</u></a> (int[] version) Test to see if the connected client flash version is equal to or greater than a given value.
void	<a href="#"><u>touch</u></a> ( ) Update the last touch time for client



(continued from last page)

## Fields

### VIDEOSAMPLE\_ACCESS\_ALL

```
public static final java.lang.String VIDEOSAMPLE_ACCESS_ALL
```

Constant value: \*

### VIDEOSAMPLE\_ACCESS\_NONE

```
public static final java.lang.String VIDEOSAMPLE_ACCESS_NONE
```

Constant value:

### AUDIOSAMPLE\_ACCESS\_ALL

```
public static final java.lang.String AUDIOSAMPLE_ACCESS_ALL
```

Constant value: \*

### AUDIOSAMPLE\_ACCESS\_NONE

```
public static final java.lang.String AUDIOSAMPLE_ACCESS_NONE
```

Constant value:

### READ\_ACCESS\_ALL

```
public static final java.lang.String READ_ACCESS_ALL
```

Constant value: \*

### READ\_ACCESS\_NONE

```
public static final java.lang.String READ_ACCESS_NONE
```

Constant value:

### WRITE\_ACCESS\_ALL

```
public static final java.lang.String WRITE_ACCESS_ALL
```

Constant value: \*

### WRITE\_ACCESS\_NONE

```
public static final java.lang.String WRITE_ACCESS_NONE
```

Constant value:

(continued from last page)

## Methods

### getClientId

```
public int getClientId()
```

Get client id. Assigned by server and connection time.

**Returns:**

client id

### getFlashVer

```
public String getFlashVer()
```

Get client flash version (same as FMS getAgent())

**Returns:**

client flash version string

### setFlashVer

```
public void setFlashVer(String flashVer)
```

Set client flash version

**Parameters:**

flashVer - client flash version string

### getTotalIOPerformanceCounter

```
public IOPerformanceCounter getTotalIOPerformanceCounter()
```

Get performance counter for all bytes transferred to this client. This includes function calls.

**Returns:**

performance counter

### getMediaIOPerformanceCounter

```
public IOPerformanceCounter getMediaIOPerformanceCounter()
```

Get performance counter for media bytes transferred to this client. Only includes bytes to mediaStream objects

**Returns:**

performance counter

### getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get parent applicationInstance. Is null if connection reject or before accepted.

**Returns:**

parent applicationInstance

(continued from last page)

## getApplication

```
public IApplication getApplication()
```

Get parent application. Is null if connection reject or before accepted.

**Returns:**

application

---

## getPlayStreams

```
public java.util.List getPlayStreams()
```

Get a collection of all play streams. Play streams are streams that are created due to a call to play.

## Iterate Play Streams

```
IClient client;

List playStreams = client.getPlayStreams();
Iterator iter = playStreams.iterator();
while(iter.hasNext())
{
    IMediaStream stream = (IMediaStream)iter.next();
    WMSLoggerFactory.getLogger(null).debug("stream: "+stream.getName());
}
```

**Returns:**

collection of play streams

---

## getPublishStreams

```
public java.util.List getPublishStreams()
```

(continued from last page)

Get a collection of publish streams. Publish streams are streams that are created due to a call to publish.

## Iterate Public Streams

```
IClient client;

List publishStreams = client.getPublishStreams();
Iterator iter = publishStreams.iterator();
while(iter.hasNext())
{
    IMediaStream stream = (IMediaStream)iter.next();
    WMSLoggerFactory.getLogger(null).debug("stream: "+stream.getName());
}
```

**Returns:**

collection of publish stream

---

## shutdownClient

```
public void shutdownClient()
```

Gracefully shutdown a client. Only use this method to shutdown a client if you know the client is connected to Wowza Pro. If the client may be disconnected from Wowza Pro, use `IClient.setShutdownClient(true)`

---

## touch

```
public void touch()
```

Update the last touch time for client

---

## isConnected

```
public boolean isConnected()
```

Is this client connected

**Returns:**

is connected

---

## getProperties

```
public WMSProperties getProperties()
```

Get client properties

**Returns:**

collection of client properties

---

(continued from last page)

## getStreamType

```
public String getStreamType()
```

Get default streamType

**Returns:**

streamType

---

## setStreamType

```
public void setStreamType(String streamType)
```

Set default streamType

**Parameters:**

streamType - streamType

---

## isAcceptConnection

```
public boolean isAcceptConnection()
```

Is auto accept connection

**Returns:**

auto accept connection

---

## acceptConnection

```
public void acceptConnection()
```

Accept connection

---

## acceptConnection

```
public void acceptConnection(String successStr)
```

Accept connection

**Parameters:**

successStr - application property value added to NetConnection.Connect.Success event object

---

## acceptConnection

```
public void acceptConnection(AMFData successObj)
```

Accept connection

**Parameters:**

successObj - application property value added to NetConnection.Connect.Success event object

---

## rejectConnection

```
public void rejectConnection()
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

(continued from last page)

## rejectConnection

```
public void rejectConnection(String errorStr)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

### Parameters:

errorStr - error (returned in onStatus handler in info.application parameter)

---

## rejectConnection

```
public void rejectConnection(AMFData errorObj)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

### Parameters:

errorObj - error AMFData (returned in onStatus handler in info.application parameter)

---

## rejectConnection

```
public void rejectConnection(String description,  
                             String errorStr)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

### Parameters:

description - description (returned in onStatus handler in info.description parameter)

errorStr - error (returned in onStatus handler in info.application parameter)

---

## rejectConnection

```
public void rejectConnection(String description,  
                             AMFData errorObj)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

### Parameters:

description - description (returned in onStatus handler in info.description parameter)

errorObj - error AMFData (returned in onStatus handler in info.application parameter)

---

## redirectConnection

```
public void redirectConnection(String url)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

### Parameters:

url - url (returned in onStatus handler in info.ex.redirect parameter)

---

## redirectConnection

```
public void redirectConnection(String url,  
                             String description)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

### Parameters:

(continued from last page)

url - url (returned in onStatus handler in info.ex.redirect parameter)

description - description (returned in onStatus handler in info.description parameter)

---

## redirectConnection

```
public void redirectConnection(String url,
    String description,
    String errorStr)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

**Parameters:**

url - url (returned in onStatus handler in info.ex.redirect parameter)

description - description (returned in onStatus handler in info.description parameter)

errorStr - error (returned in onStatus handler in info.application parameter)

---

## redirectConnection

```
public void redirectConnection(String url,
    String description,
    AMFData errorObj)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302). Code must be added client side to capture the NetConnection.Connect.Rejected message, look for the info.ex.code value of 302 and attempt a reconnect to the info.ex.redirect url. Client side example:

```
public function ncOnStatus(infoObject:NetStatusEvent)
{
    if (infoObject.info.code == "NetConnection.Connect.Rejected")
    {
        if (infoObject.info.ex.code == 302)
        {
            trace("Connection redirected: "+infoObject.info.ex.redirect);
            nc.connect(infoObject.info.ex.redirect);
        }
        else
            trace("Connection rejected");
    }
}
nc.addEventListener(NetStatusEvent.NET_STATUS, ncOnStatus);
```

**Parameters:**

url - url (returned in onStatus handler in info.ex.redirect parameter)

description - description (returned in onStatus handler in info.description parameter)

errorObj - error AMFData (returned in onStatus handler in info.application parameter)

---

## getVHost

```
public IVHost getVHost( )
```

Get parent vHost

(continued from last page)

**Returns:**

vHost object

---

**call**

```
public void call(String handlerName,  
    IModuleCallResult resultObj,  
    Object[] params)
```

Call client method/handler. You can call any method/handler attached to NetConnection object. Such as netConnection.myFunc

## Call Client Handler Method With Result Object

```
IClient client;  
  
class ReturnObj implements IModuleCallResult  
{  
    public void onResult(IClient client, RequestFunction function,  
        AMFDataList params)  
    {  
        WMSLoggerFactory.getLogger(null).debug("onResult");  
    }  
}  
  
client.call("onCustomMethod", new ReturnObj(), "param1", 1.2345, false, new Date());
```

**Parameters:**

handlerName - handler name

resultObj - if client method returns data this object will receive callback, null if don't care or no return on client method/handler.

params - variable list of argument. Will be automatically wrapped in AMFData objects

---

**call**

```
public void call(String handlerName)
```

Simplified call client method/handler call. No resultObj. No parameters

**Parameters:**

handlerName - handler name

---

**ping**

```
public int ping(IModulePingResult pingResult)
```



(continued from last page)

Ping client. Unlike FMS this ping is asynchronous. pingResult object will be notified of successful response by client or timeout.

## Ping Client and Kill Connection If Client Has Died

```
class PingResult implements IModulePingResult
{
    public void onResult(IClient client, long pingTime, int pingId, boolean result)
    {
        WMSLogger log = WMSLoggerFactory.getLogger(null);
        log.debug("onResult: result:"+result);
        if (!result)
        {
            // client has died lets kill it
            client.getAppInstance().shutdownClient(client);
        }
        else
            log.debug("lastPingTime: "+client.getPingRoundTripTime());
    }
}
client.ping(new PingResult());
```

### Parameters:

pingResult - ping result object. Will receive callback on result of ping or timeout. Can be null.

### Returns:

ping id

---

## getIp

```
public String getIp()
```

Client ip address

### Returns:

client ip address

---

## getFastPlaySettings

```
public FastPlaySettings getFastPlaySettings()
```

Get the current fastPlay settings. FastPlay settings when set from the client are immediately cleared on the next call to seek/unpause/play.

### Returns:

fastPlay settings

---

(continued from last page)

## setFastPlaySettings

```
public void setFastPlaySettings(FastPlaySettings fastPlaySettings)
```

Set fastPlay settings

### Parameters:

fastPlaySettings - fastPlay settings

---

## clearFastPlaySettings

```
public void clearFastPlaySettings()
```

Force clear the fastPlay settings

---

## getRespFunctions

```
public ResponseFunctions getRespFunctions()
```

Get client responseFunctions object. The responseFunctions object is the method by which events are sent to the client. This code snippet shows how to send an onStatus event for a mediaStream (stream) to the client.

## Send Status Message to Client

```
ResponseFunctions respFunctions = client.getRespFunctions();

ResponseFunction resp = new ResponseFunction();
resp.createDefaultMessage("onStatus", 0.0);
resp.setRetAMFObj(stream.getRespAMFDataObj());
resp.setSrc(stream.getSrc());

AMFDataObj data = new AMFDataObj();
data.put("level", new AMFDataItem("status"));
data.put("code", new AMFDataItem("NetStream.Publish.Success"));
data.put("description", new AMFDataItem(stream.getName()+" is now unpublished.));
data.put("clientId", new AMFDataItem(clientID));
resp.addBody(data);

respFunctions.add(resp);
```

### Returns:

responseFunctions object

---

## getConnectTime

```
public long getConnectTime()
```

(continued from last page)

Get time in milliseconds the client connected to the server. To get the duration of time in milliseconds that the client has been connected to the server us the following formula: `(System.currentTimeMillis() - client.getConnectTime())`

**Returns:**

duration connected (milliseconds)

---

## getPingRoundTripTime

```
public long getPingRoundTripTime()
```

Get turn around time (milliseconds) of last ping request

**Returns:**

time (milliseconds)

---

## getDateStarted

```
public String getDateStarted()
```

Get date and time of client connection

**Returns:**

date and time of connection

---

## getTimeRunning

```
public String getTimeRunning()
```

Get elapsed time of connection

**Returns:**

elapsed time of connection

---

## getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

**Returns:**

time running in seconds

---

## getStreamFile

```
public java.io.File getStreamFile(String streamName)
```

Get File object for stream with given name. Assumes file extension is .flv.

**Parameters:**

streamName - stream name

**Returns:**

file

---

## getStreamFile

```
public java.io.File getStreamFile(String streamName,  
    String streamExt)
```

(continued from last page)

Get File object for stream with given name and extension. For example test.flv would be `getStreamFile("test", "flv");`

## Get File Descriptor

```
IClient client;
File file = client.getStreamFile("test", "flv");
WMSLogger log = WMSLoggerFactory.getLogger(null);
if (file != null)
{
    if (file.exists())
        log.debug("getStreamFile: " + file.getPath());
}
```

### Parameters:

streamName - stream name  
streamExt - stream extension

### Returns:

file

---

## getStreamFile

```
public java.io.File getStreamFile(String streamName,
    String streamExt,
    boolean doCreateFolder)
```

Get File object for stream with given name and extension. If doCreateFolder is true, create folder necessary to make path exist. For example test.flv would be `getStreamFile("test", "flv");`

### Parameters:

streamName - stream name  
streamExt - stream extension  
doCreateFolder - create folders if needed

### Returns:

file

---

## getBufferTime

```
public int getBufferTime()
```

Get default buffer time for newly created mediaStream objects

### Returns:

default buffer time (milliseconds)

---

## setBufferTime

```
public void setBufferTime(int bufferTime)
```

---

(continued from last page)

Set default buffer time for newly created mediaStream objects

**Parameters:**

bufferTime - bufer time (milliseconds)

---

## getResponseAMFObj

```
public AMFObj getResponseAMFObj(int index)
```

Get the response channel AMFObj for channel index.

**Parameters:**

index - channel index

**Returns:**

AMFObj

---

## getRespAMFAudioObj

```
public AMFObj getRespAMFAudioObj(IMediaStream stream)
```

Get the audio response AMFObj for a given mediaStream

**Parameters:**

stream - mediaStream

**Returns:**

response channel AMFObj

---

## getRespAMFVideoObj

```
public AMFObj getRespAMFVideoObj(IMediaStream stream)
```

Get the video response AMFObj for a given mediaStream

**Parameters:**

stream - mediaStream

**Returns:**

response channel AMFObj

---

## getRespAMFDataObj

```
public AMFObj getRespAMFDataObj(IMediaStream stream)
```

Get the data response AMFObj for a given mediaStream

**Parameters:**

stream - mediaStream

**Returns:**

response channel AMFObj

---

## getQueryStr

```
public String getQueryStr()
```

(continued from last page)

Get the query string part of the connection string. If the connection string where:  
rtmp://localhost/app/appInst?data1=myData1&data2=myData2, then query string would be  
data1=myData1&data2=myData2

**Returns:**query string

---

## getReferrer

```
public String getReferrer()
```

Get the referrer data for this connection. The referrer in Wowza Media Server terms is the full url to the Flash movie that connected to the server. Checking referre upon connection is a great way to secure server connections and only allow your Flash movies to connect to the server.

## Only Allow Your .swf Files to Connect to Wowza Pro server

```
public class MyModule extends ModuleBase
{
    static public void onConnect(IClient client, RequestFunction function,
        AMFDataList params)
    {
        String referrer = client.getReferrer();

        if (referrer.indexOf("www.mycompany.com") >= 0 &&
            referrer.indexOf("mycoolflash.swf") >= 0)
            client.acceptConnection("valid referrer");
        else
            client.rejectConnection("invalid referrer: "+referrer);
    }
}
```

**Returns:**referrer

---

## getPageUrl

```
public String getPageUrl()
```

Get the pageUrl for this connection.

**Returns:**pageUrl for this connection

---

## getUri

```
public String getUri()
```

Get the full URI of the connection string

---

(continued from last page)

**Returns:**

URI of connection string

---

**getProtocol**

```
public int getProtocol()
```

Get connection protocol (1 = RTMP, 3 = RTMPT)

**Returns:**

connection protocol (1 = RTMP, 3 = RTMPT)

---

**getServerHostPort**

```
public HostPort getServerHostPort()
```

Get the hostPort object for the connection that is servicing this client

**Returns:**

vHost hostPort servicing request

---

**isSecure**

```
public boolean isSecure()
```

Is this connection protected by either SSL or encryption (RTMPE, RTMPTE, RTMPS)

**Returns:**

is connection protected by either SSL or encryption (RTMPE, RTMPTE, RTMPS)

---

**isSSL**

```
public boolean isSSL()
```

Is this connection SSL (RTMPS)

**Returns:**

is connection (RTMPS)

---

**isEncrypted**

```
public boolean isEncrypted()
```

Is this connection encrypted (RTMPE or RTMPTE)

**Returns:**

is connection encrypted (RTMPE or RTMPTE)

---

**getIdleFrequency**

```
public int getIdleFrequency()
```

Get client idle frequency (milliseconds)

**Returns:**

client idle frequency (milliseconds)

## setIdleFrequency

```
public void setIdleFrequency(int idleFrequency)
```

Set client idle frequency (milliseconds)

**Parameters:**

idleFrequency - client idle frequency (milliseconds)

---

## getSharedObjectReadAccess

```
public String getSharedObjectReadAccess()
```

Get the shared object read access value. see setSharedObjectReadAccess for more information.

**Returns:**

shared object read access value

---

## setSharedObjectReadAccess

```
public void setSharedObjectReadAccess(String sharedObjectReadAccess)
```

Set the shared object read access value. This list is a semi-colon delimited list of shared objects that this client has access to. By default the value is set to IClient.READ\_ACCESS\_ALL which indicates this client can read all shared objects. If you want to disable read access to all shared objects set this value to IClient.READ\_ACCESS\_NONE. If this value is set to anything other than IClient.READ\_ACCESS\_ALL or IClient.READ\_ACCESS\_NONE then each item in the semi-color delimited list is compared against incoming shared object read requests. If any item in the list completely matches the shared object name or the start of the shared object name, then access is allowed. For example, if the sharedObjectReadAccess list is set to "testa/testb;testc" then the following requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

**Parameters:**

sharedObjectReadAccess - shared object read access value

---

## getSharedObjectWriteAccess

```
public String getSharedObjectWriteAccess()
```

Get the shared object write access value. see setSharedObjectWriteAccess for more information.

**Returns:**

shared object write access value

---

## setSharedObjectWriteAccess

```
public void setSharedObjectWriteAccess(String sharedObjectWriteAccess)
```



(continued from last page)

Set the shared object write access value. This list is a semi-colon delimited list of shared objects that this client has access to. By default the value is set to IClient.WRITE\_ACCESS\_ALL which indicates this client can write all shared objects. If you want to disable write access to all shared objects set this value to IClient.WRITE\_ACCESS\_NONE. If this value is set to anything other than IClient.WRITE\_ACCESS\_ALL or IClient.WRITE\_ACCESS\_NONE then each item in the semi-color delimited list is compared against incoming shared object write requests. If any item in the list completely matches the shared object name or the start of the shared object name, then access is allowed. For example, if the sharedObjectWriteAccess list is set to "testa/testb;testc" then the following requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

**Parameters:**

sharedObjectWriteAccess

---

## getStreamVideoSampleAccess

```
public String getStreamVideoSampleAccess()
```

Get the video sample access value. see setVideoStreamAccess for more information.

**Returns:**

video sample access

---

## setStreamVideoSampleAccess

```
public void setStreamVideoSampleAccess(String videoSampleAccess)
```

Set the stream video sample access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.VIDEOSTREAM\_ACCESS\_NONE which indicates this client can access no stream data client side. If you want to enable access to all stream names set this value to IClient.VIDEOSTREAM\_ACCESS\_ALL. If this value is set to anything other than IClient.VIDEOSTREAM\_ACCESS\_ALL or IClient.VIDEOSTREAM\_ACCESS\_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamVideoSampleAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

**Parameters:**

videoSampleAccess

---

## getStreamAudioSampleAccess

```
public String getStreamAudioSampleAccess()
```

Get the audio sample access value. see setVideoStreamAccess for more information.

**Returns:**

(continued from last page)

audio sample access

---

## setStreamAudioSampleAccess

```
public void setStreamAudioSampleAccess(String audioSampleAccess)
```

Set the stream audio sample access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.AUDIOSTREAM\_ACCESS\_NONE which indicates this client can access no stream data client side. If you want to enable access to all stream names set this value to IClient.AUDIOSTREAM\_ACCESS\_ALL. If this value is set to anything other than IClient.AUDIOSTREAM\_ACCESS\_ALL or IClient.AUDIOSTREAM\_ACCESS\_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamAudioSampleAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

### Parameters:

audioSampleAccess

---

## getStreamReadAccess

```
public String getStreamReadAccess()
```

Get the stream read access value. see setStreamReadAccess for more information.

### Returns:

stream read access value

---

## setStreamReadAccess

```
public void setStreamReadAccess(String streamReadAccess)
```

Set the stream object read access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.READ\_ACCESS\_ALL which indicates this client can play all streams. If you want to disable read access to all stream names set this value to IClient.READ\_ACCESS\_NONE. If this value is set to anything other than IClient.READ\_ACCESS\_ALL or IClient.READ\_ACCESS\_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamReadAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

### Parameters:

streamReadAccess - shared object read access value

## getStreamWriteAccess

```
public String getStreamWriteAccess()
```

Get the stream write access value. see setStreamWriteAccess for more information.

**Returns:**

stream write access value

---

## setStreamWriteAccess

```
public void setStreamWriteAccess(String streamWriteAccess)
```

Set the stream object write access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.WRITE\_ACCESS\_ALL which indicates this client can play all streams. If you want to disable write access to all stream names set this value to IClient.WRITE\_ACCESS\_NONE. If this value is set to anything other than IClient.WRITE\_ACCESS\_ALL or IClient.WRITE\_ACCESS\_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamWriteAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

**Parameters:**

streamWriteAccess - shared object read access value

---

## getWriteListener

```
public ClientWriteListener getWriteListener()
```

Object that tracks write operations

**Returns:**

Object that tracks write operations

---

## addAcceptConnectionAttribute

```
public void addAcceptConnectionAttribute(String key,  
    AMFDataObj item)
```

Add and attribute to the resultObj that gets passed back to the client on successful connection

**Parameters:**

key - key  
item - item to add

---

## addAcceptConnectionAttribute

```
public void addAcceptConnectionAttribute(String key,  
    String item)
```

Add and attribute to the resultObj that gets passed back to the client on successful connection

---

(continued from last page)

**Parameters:**

key - key  
item - item to add

---

**getRepeaterOriginUrl**

```
public String getRepeaterOriginUrl()
```

Get the origin URL used by the Live Stream Repeater

**Returns:**

URL used by the Live Stream Repeater

---

**setRepeaterOriginUrl**

```
public void setRepeaterOriginUrl(String repeaterOriginUrl)
```

Set the origin URL used by the Live Stream Repeater

**Parameters:**

repeaterOriginUrl - URL used by the Live Stream Repeater

---

**getLastValidateTime**

```
public long getLastValidateTime()
```

Get last time (millisecond) the connection was validated with a ping

**Returns:**

last time (millisecond) the connection was validated with a ping

---

**setLastValidateTime**

```
public void setLastValidateTime(long lastValidateTime)
```

Set the last time (milliseconds) the connection was validated with ping

**Parameters:**

lastValidateTime - last time (milliseconds) the connection was validated with ping

---

**getPingTimeout**

```
public int getPingTimeout()
```

Get the ping timeout (milliseconds)

**Returns:**

ping timeout (milliseconds)

---

**isLiveRepeater**

```
public boolean isLiveRepeater()
```

Returns true if this connection is from the live stream repeater

**Returns:**

true if this connection is from the live stream repeater

## isFlashVersionH264Capable

```
public boolean isFlashVersionH264Capable()
```

Returns true if the connected client is capable of playing H.264 video (Flash player 9.0.45.x or greater)

**Returns:**

returns true if the connected client is capable of playing H.264 video (Flash player 9.0.45.x or greater)

---

## isFlashVersion90115

```
public boolean isFlashVersion90115()
```

Returns true if the Flash version is equal or greater than 9.0.115.x

**Returns:**

returns true if the Flash version is equal or greater than 9.0.115.x

---

## isFlashVersion10

```
public boolean isFlashVersion10()
```

Returns true if the Flash version is equal or greater than 10.x.x.x

**Returns:**

returns true if the Flash version is equal or greater than 10.x.x.x

---

## isFlashMediaLiveEncoder

```
public boolean isFlashMediaLiveEncoder()
```

Returns true if this connection is the Flash Media Live Encoder

**Returns:**

true if this connection is the Flash Media Live Encoder

---

## testFlashVersion

```
public int testFlashVersion(int[] version)
```

Test to see if the connected client flash version is equal to or greater than a given value. Example: int isGood = testFlashVersion( { 9, 0, 5, 12} );

**Parameters:**

version - array of version values

**Returns:**

1 if greater, 0 if equal, -1 if less than

---

## isObjectEncodingAMF3

```
public boolean isObjectEncodingAMF3()
```

Is the object encoding for this client AMF3

**Returns:**

true of the object encoding for this client is AMF3

---

## isObjectEncodingAMF0

```
public boolean isObjectEncodingAMF0()
```

Is the object encoding for this client AMF0

**Returns:**

true of the object encoding for this client is AMF0

---

## setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

Set the object encoding level

**Parameters:**

objectEncoding - object encoding level

---

## getObjectEncoding

```
public int getObjectEncoding()
```

Get the object encoding level

**Returns:**

object encoding level

---

## setAcceptConnectionObj

```
public void setAcceptConnectionObj(AMFData acceptConnectionObj)
```

Call this method from onConnect to add an "application" property to the info object that is passed back to the Flash client in the onStatus handler.

**Parameters:**

acceptConnectionObj - connection object

---

## setAcceptConnectionDescription

```
public void setAcceptConnectionDescription(String description)
```

Call this method from onConnect to set the info.description property returned in NetConnection onStatus handler

**Parameters:**

description - description

---

## setAcceptConnectionExObj

```
public void setAcceptConnectionExObj(AMFDataObj acceptConnectionExObj)
```

Call this method from onConnect to set the info.ex property returned in NetConnection onStatus handler

**Parameters:**

acceptConnectionExObj - exObj AMFData item return in info.ex property of NetConnection onStatus handler

---

(continued from last page)

---

## getRTPStream

```
public RTPStream getRTPStream( )
```

If this client was created due to an RTP connection to the server return the underlying RTPStream object

**Returns:**

underlying RTPStream object

---

## setAcceptConnection

```
public void setAcceptConnection(boolean acceptConnection)
```

Set the default for accept connection

**Parameters:**

acceptConnection - default for accept connection

---

## setShutdownClient

```
public void setShutdownClient(boolean shutdownClient)
```

Gracefully and forcefully shutdown a client.

**Parameters:**

shutdownClient - set to true to gracefully and forcefully shutdown a client

---

## reparentClient

```
public void reparentClient(IVHost vhost)
```

Move a client object to a new vhost. This can only be done right after the handshake process has completed. See IVHostNotify.onVHostClientConnect.

**Parameters:**

vhost - new vhost

---

## getMaximumSetBufferTime

```
public int getMaximumSetBufferTime( )
```

Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

**Returns:**

maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

---

## getMaximumPendingWriteBytes

```
public int getMaximumPendingWriteBytes( )
```

Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

**Returns:**

maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

---

(continued from last page)

---

## getLiveStreamPacketizerList

```
public String getLiveStreamPacketizerList()
```

Get the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)

**Returns:**

comma separated list of LiveStreamPacketizers names

---

## setLiveStreamPacketizerList

```
public void setLiveStreamPacketizerList(String liveStreamPacketizerList)
```

Set the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)

**Parameters:**

liveStreamPacketizerList - comma separated list of LiveStreamPacketizers names

---

## getLiveStreamTranscoderList

```
public String getLiveStreamTranscoderList()
```

Get the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)

**Returns:**

comma separated list of LiveStreamTranscoders names

---

## setLiveStreamTranscoderList

```
public void setLiveStreamTranscoderList(String liveStreamTranscoderList)
```

Set the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)

**Parameters:**

liveStreamTranscoderList - comma separated list of LiveStreamTranscoders names

---

## getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get elapsed time client has been connected.

**Returns:**

elapsed time client has been connected.

---

## getLiveRepeaterCapabilities

```
public int getLiveRepeaterCapabilities()
```

Get the live repeater capabilities of this connection

**Returns:**

live repeater capabilities of this connection

---

## setLiveRepeaterCapabilities

```
public void setLiveRepeaterCapabilities(int liveRepeaterCapabilities)
```

---



---

(continued from last page)

Set the live repeater capabilities of this connection

**Parameters:**

liveRepeaterCapabilities - live repeater capabilities of this connection

---

## fcSubscribe

```
public void fcSubscribe(String streamName)
```

Subscribe to a live stream (for live stream repeater to start start from edge to origin)

**Parameters:**

streamName - stream name

---

## fcSubscribe

```
public void fcSubscribe(String streamName,  
String mediaCasterType)
```

Subscribe to a live stream (use a particular mediaCasterType)

**Parameters:**

streamName - stream name

mediaCasterType - media caster type name

---

## fcUnSubscribeAll

```
public void fcUnSubscribeAll()
```

UnSubscribe to all streams that this client is current subscribed to

---

## fcUnSubscribe

```
public void fcUnSubscribe(String streamName)
```

UnSubscribe from a stream

**Parameters:**

streamName - stream name

---

## isValidateFMLEConnections

```
public boolean isValidateFMLEConnections()
```

Returns true if validating FMLE connection (default is false)

**Returns:**

true if validating FMLE connection

---

## setValidateFMLEConnections

```
public void setValidateFMLEConnections(boolean validateFMLEConnections)
```

Returns true if validating FMLE connection (default is false)

**Parameters:**

validateFMLEConnections - true if validating FMLE connection

---

(continued from last page)

## setThreadContext

```
public void setThreadContext()
```

Set the thread logging context to this client

---

## getWowzSession

```
public com.wowza.wms.protocol.wowz.WOWZSession getWowzSession()
```

---

## setWowzSession

```
public void setWowzSession(com.wowza.wms.protocol.wowz.WOWZSession wowzSession)
```

## com.wowza.wms.client Interface IClientNotify

public interface **IClientNotify**  
extends

IClientNotify: listener interface used by [IApplicationInstance.addClientListener\(IClientNotify\)](#)

See Also:

[IApplicationInstance.addClientListener\(IClientNotify\)](#)

### Method Summary

void	<a href="#">onClientAccept</a> ( <a href="#">IClient</a> client) Triggered when client connection accepted
void	<a href="#">onClientConnect</a> ( <a href="#">IClient</a> client) Triggered when client attempt connection
void	<a href="#">onClientDisconnect</a> ( <a href="#">IClient</a> client) Triggered when client disconnected
void	<a href="#">onClientReject</a> ( <a href="#">IClient</a> client) Triggered when client connection rejected

### Methods

#### onClientConnect

public void **onClientConnect**([IClient](#) client)

Triggered when client attempt connection

**Parameters:**

client - client

#### onClientDisconnect

public void **onClientDisconnect**([IClient](#) client)

Triggered when client disconnected

**Parameters:**

client - client

#### onClientAccept

public void **onClientAccept**([IClient](#) client)

Triggered when client connection accepted

**Parameters:**

client - client

## onClientReject

```
public void onClientReject(IClient client)
```

Triggered when client connection rejected

**Parameters:**

client - client

## com.wowza.wms.client Interface IConnectionNotify

public interface **IConnectionNotify**  
extends

IConnectionNotify: internal class to manage connection counting

### Method Summary

void	<a href="#">onAcceptConnection</a> ( <a href="#">ConnectionCounter</a> connectionCounter, <a href="#">ConnectionHolder</a> connectionHolder, java.util.Date date, long stamp) Triggered when client connection accepted
void	<a href="#">onDisconnect</a> ( <a href="#">ConnectionCounter</a> connectionCounter, <a href="#">ConnectionHolder</a> connectionHolder, boolean isValid, java.util.Date date, long stamp) Triggered when client disconnected
void	<a href="#">onRejectConnection</a> ( <a href="#">ConnectionCounter</a> connectionCounter, <a href="#">ConnectionHolder</a> connectionHolder, int reason, java.util.Date date, long stamp) Triggered when client connection rejected

### Methods

#### onAcceptConnection

```
public void onAcceptConnection(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    java.util.Date date,  
    long stamp)
```

Triggered when client connection accepted

**Parameters:**

connectionCounter  
connectionHolder  
date  
stamp

#### onRejectConnection

```
public void onRejectConnection(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    int reason,  
    java.util.Date date,  
    long stamp)
```

Triggered when client connection rejected

**Parameters:**

connectionCounter  
connectionHolder  
reason

(continued from last page)

date  
stamp

---

## onDisconnect

```
public void onDisconnect(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    boolean isValid,  
    java.util.Date date,  
    long stamp)
```

Triggered when client disconnected

### Parameters:

connectionCounter  
connectionHolder  
isValid  
date  
stamp

---

Package

**com.wowza.wms.closedcaption.cea608**

## com.wowza.wms.closedcaption.cea608

### Class ClosedCaptionCEA608Utils

java.lang.Object

└-com.wowza.wms.timedtext.cea608.CEA608Constants

└-[com.wowza.wms.timedtext.cea608.ClosedCaptionCEA608Utils](#)

└-com.wowza.wms.closedcaption.cea608.ClosedCaptionCEA608Utils

public class **ClosedCaptionCEA608Utils**

extends [ClosedCaptionCEA608Utils](#)

Fields inherited from class [com.wowza.wms.timedtext.cea608.ClosedCaptionCEA608Utils](#)



[CEA608\\_EXTENDED\\_FR\\_SP\\_MAP](#), [CEA608\\_EXTENDED\\_NA\\_MAP](#),  
[CEA608\\_EXTENDED\\_PORT\\_GERMAN\\_DANISH\\_MAP](#), [CEA608\\_MUSICAL\\_NOTE](#), [CEA608\\_SOLID\\_BLOCK](#), [CHANNEL1](#),  
[CHANNEL2](#), [COL\\_0](#), [COL\\_12](#), [COL\\_16](#), [COL\\_20](#), [COL\\_24](#), [COL\\_28](#), [COL\\_4](#), [COL\\_5](#), [COL0\\_BLUE](#), [COL0\\_CYAN](#),  
[COL0\\_GREEN](#), [COL0\\_HIBYTE](#), [COL0\\_LOWBYTE](#), [COL0\\_MAGENTA](#), [COL0\\_RED](#), [COL0\\_WHITE](#), [COL0\\_YELLOW](#),  
[COLN\\_LOWBYTE](#), [CONTROLCODES\\_AOF](#), [CONTROLCODES\\_AON](#), [CONTROLCODES\\_BAO](#), [CONTROLCODES\\_BAS](#),  
[CONTROLCODES\\_BBO](#), [CONTROLCODES\\_BBS](#), [CONTROLCODES\\_BCO](#), [CONTROLCODES\\_BCS](#), [CONTROLCODES\\_BGO](#),  
[CONTROLCODES\\_BGS](#), [CONTROLCODES\\_BMO](#), [CONTROLCODES\\_BMS](#), [CONTROLCODES BRO](#), [CONTROLCODES\\_BRS](#),  
[CONTROLCODES\\_BS](#), [CONTROLCODES\\_BT](#), [CONTROLCODES\\_BWO](#), [CONTROLCODES\\_BWS](#), [CONTROLCODES\\_BYO](#),  
[CONTROLCODES\\_BYS](#), [CONTROLCODES\\_CR](#), [CONTROLCODES\\_DER](#), [CONTROLCODES\\_EDM](#), [CONTROLCODES\\_ENM](#),  
[CONTROLCODES\\_EOC](#), [CONTROLCODES\\_FA](#), [CONTROLCODES\\_FAU](#), [CONTROLCODES\\_FON](#), [CONTROLCODES\\_RCL](#),  
[CONTROLCODES\\_RDC](#), [CONTROLCODES\\_RTD](#), [CONTROLCODES\\_RU2](#), [CONTROLCODES\\_RU3](#), [CONTROLCODES\\_RU4](#),  
[CONTROLCODES\\_TO1](#), [CONTROLCODES\\_TO2](#), [CONTROLCODES\\_TO3](#), [CONTROLCODES\\_TR](#), [COUNT\\_COLS](#),  
[COUNT\\_ROWS](#), [DONOTHING\\_BYTE](#), [DONOTHING\\_SHORT](#), [FORMAT\\_COLOR](#), [FORMAT\\_FLASH](#), [FORMAT\\_ITALICS](#),  
[FORMAT\\_ITALICS\\_UNDERLINE](#), [LANG\\_ASCII](#), [LANG\\_ASCII\\_DBL](#), [LANG\\_GB231280](#), [LANG\\_KSC56011987](#),  
[LANG\\_PRIV1](#), [LANG\\_PRIV2](#), [LANG\\_REG1](#), [MAX\\_CC\\_COUNT](#), [ODDPARITY](#), [SEI\\_PAYLOADTYPE](#), [SEI\\_STARTCODE](#),  
[SEI\\_USERDATATYPECODE](#), [UTF8\\_BRITISH\\_POUND](#), [UTF8\\_BULLET](#), [UTF8\\_CENTS](#),  
[UTF8\\_CLOSING\\_DOUBLE\\_QUOTE](#), [UTF8\\_CLOSING\\_GUILLEMETS](#), [UTF8\\_CONNECTING\\_VERTICAL\\_BAR](#),  
[UTF8\\_COPYRIGHT](#), [UTF8\\_CURRENCY](#), [UTF8\\_DASH](#), [UTF8\\_DEGREE](#), [UTF8\\_DOUBLEQUOTE](#), [UTF8\\_EM\\_DASH](#),  
[UTF8\\_EXCLAMATION](#), [UTF8\\_GREATERTHAN](#), [UTF8\\_INVERTED\\_EXCLAMATION](#), [UTF8\\_LEFT\\_SINGLE\\_QUOTATION](#),  
[UTF8\\_LEFTPAREN](#), [UTF8\\_LESSTHAN](#), [UTF8\\_LOWER\\_A](#), [UTF8\\_LOWER\\_A\\_WITH\\_CIRCUMFLEX](#),  
[UTF8\\_LOWER\\_A\\_WITH\\_DIAERESIS](#), [UTF8\\_LOWER\\_A\\_WITH\\_GRAVE](#), [UTF8\\_LOWER\\_A\\_WITH\\_RING](#),  
[UTF8\\_LOWER\\_A\\_WITH\\_TILDE](#), [UTF8\\_LOWER\\_B](#), [UTF8\\_LOWER\\_C](#), [UTF8\\_LOWER\\_D](#), [UTF8\\_LOWER\\_E](#),  
[UTF8\\_LOWER\\_E\\_WITH\\_CIRCUMFLEX](#), [UTF8\\_LOWER\\_E\\_WITH\\_DIAERESIS](#), [UTF8\\_LOWER\\_E\\_WITH\\_GRAVE](#),  
[UTF8\\_LOWER\\_F](#), [UTF8\\_LOWER\\_G](#), [UTF8\\_LOWER\\_H](#), [UTF8\\_LOWER\\_I](#), [UTF8\\_LOWER\\_I\\_WITH\\_CIRCUMFLEX](#),  
[UTF8\\_LOWER\\_I\\_WITH\\_DIAERESIS](#), [UTF8\\_LOWER\\_I\\_WITH\\_GRAVE](#), [UTF8\\_LOWER\\_J](#), [UTF8\\_LOWER\\_K](#),  
[UTF8\\_LOWER\\_L](#), [UTF8\\_LOWER\\_M](#), [UTF8\\_LOWER\\_N](#), [UTF8\\_LOWER\\_O](#), [UTF8\\_LOWER\\_O\\_WITH\\_CIRCUMFLEX](#),  
[UTF8\\_LOWER\\_O\\_WITH\\_DIAERESIS](#), [UTF8\\_LOWER\\_O\\_WITH\\_GRAVE](#), [UTF8\\_LOWER\\_O\\_WITH\\_STROKE](#),  
[UTF8\\_LOWER\\_O\\_WITH\\_TILDE](#), [UTF8\\_LOWER\\_P](#), [UTF8\\_LOWER\\_Q](#), [UTF8\\_LOWER\\_R](#), [UTF8\\_LOWER\\_S](#),  
[UTF8\\_LOWER\\_T](#), [UTF8\\_LOWER\\_U](#), [UTF8\\_LOWER\\_U\\_WITH\\_CIRCUMFLEX](#), [UTF8\\_LOWER\\_U\\_WITH\\_DIAERESIS](#),  
[UTF8\\_LOWER\\_U\\_WITH\\_GRAVE](#), [UTF8\\_LOWER\\_V](#), [UTF8\\_LOWER\\_W](#), [UTF8\\_LOWER\\_X](#), [UTF8\\_LOWER\\_Y](#),  
[UTF8\\_LOWER\\_Z](#), [UTF8\\_MINUSHYPHEN](#), [UTF8\\_MUSICAL\\_NOTE](#), [UTF8\\_NBSP](#), [UTF8\\_NOTMATCH](#), [UTF8\\_ONE\\_HALF](#),  
[UTF8\\_OPENING\\_DOUBLE\\_QUOTE](#), [UTF8\\_OPENING\\_GUILLEMETS](#), [UTF8\\_PERIOD](#), [UTF8\\_PIPE](#), [UTF8\\_QUESTION](#),  
[UTF8\\_REGISTERED\\_MARK](#), [UTF8\\_REVERSE\\_QUERY](#), [UTF8\\_RIGHTPAREN](#), [UTF8\\_SERVICE\\_MARK](#),  
[UTF8\\_SINGLEQUOTE](#), [UTF8\\_SPACE](#), [UTF8\\_TRADEMARK](#), [UTF8\\_UNDERSCORE](#), [UTF8\\_UPPER\\_A](#),  
[UTF8\\_UPPER\\_A\\_WITH\\_ACUTE](#), [UTF8\\_UPPER\\_A\\_WITH\\_CURCUMFLEX](#), [UTF8\\_UPPER\\_A\\_WITH\\_DIAERESIS](#),  
[UTF8\\_UPPER\\_A\\_WITH\\_GRAVE](#), [UTF8\\_UPPER\\_A\\_WITH\\_RING](#), [UTF8\\_UPPER\\_A\\_WITH\\_TILDE](#), [UTF8\\_UPPER\\_B](#),  
[UTF8\\_UPPER\\_C](#), [UTF8\\_UPPER\\_C\\_WITH\\_CEDILLA](#), [UTF8\\_UPPER\\_D](#), [UTF8\\_UPPER\\_E](#),  
[UTF8\\_UPPER\\_E\\_WITH\\_ACUTE](#), [UTF8\\_UPPER\\_E\\_WITH\\_CIRCUMFLEX](#), [UTF8\\_UPPER\\_E\\_WITH\\_DIAERESIS](#),  
[UTF8\\_UPPER\\_E\\_WITH\\_GRAVE](#), [UTF8\\_UPPER\\_F](#), [UTF8\\_UPPER\\_G](#), [UTF8\\_UPPER\\_H](#), [UTF8\\_UPPER\\_I](#),  
[UTF8\\_UPPER\\_I\\_WITH\\_CIRCUMFLEX](#), [UTF8\\_UPPER\\_I\\_WITH\\_DIAERESIS](#), [UTF8\\_UPPER\\_I\\_WITH\\_GRAVE](#),  
[UTF8\\_UPPER\\_I\\_WITH\\_TILDE](#), [UTF8\\_UPPER\\_J](#), [UTF8\\_UPPER\\_K](#), [UTF8\\_UPPER\\_L](#), [UTF8\\_UPPER\\_M](#),  
[UTF8\\_UPPER\\_N](#), [UTF8\\_UPPER\\_O](#), [UTF8\\_UPPER\\_O\\_WITH\\_ACUTE](#), [UTF8\\_UPPER\\_O\\_WITH\\_CIRCUMFLEX](#),  
[UTF8\\_UPPER\\_O\\_WITH\\_DIAERESIS](#), [UTF8\\_UPPER\\_O\\_WITH\\_GRAVE](#), [UTF8\\_UPPER\\_O\\_WITH\\_STROKE](#),  
[UTF8\\_UPPER\\_O\\_WITH\\_TILDE](#), [UTF8\\_UPPER\\_P](#), [UTF8\\_UPPER\\_Q](#), [UTF8\\_UPPER\\_R](#), [UTF8\\_UPPER\\_S](#),  
[UTF8\\_UPPER\\_T](#), [UTF8\\_UPPER\\_U](#), [UTF8\\_UPPER\\_U\\_WITH\\_ACUTE](#), [UTF8\\_UPPER\\_U\\_WITH\\_CIRCUMFLEX](#),  
[UTF8\\_UPPER\\_U\\_WITH\\_DIAERESIS](#), [UTF8\\_UPPER\\_U\\_WITH\\_GRAVE](#), [UTF8\\_UPPER\\_V](#), [UTF8\\_UPPER\\_W](#),  
[UTF8\\_UPPER\\_X](#), [UTF8\\_UPPER\\_Y](#), [UTF8\\_UPPER\\_Z](#), [UTF8\\_YEN](#), [UTF8MAP](#), [UTF8MAP\\_INDEX\\_OFFSET](#)

Fields inherited from class `com.wowza.wms.timedtext.cea608.CEA608Constants`

[CC\\_CHANNEL\\_CC1](#), [CC\\_CHANNEL\\_CC2](#), [CC\\_CHANNEL\\_CC3](#), [CC\\_CHANNEL\\_CC4](#), [CC\\_TYPE\\_DTVCC\\_PACKET\\_DATA](#),  
[CC\\_TYPE\\_DTVCC\\_PACKET\\_START](#), [CC\\_TYPE\\_NTSC\\_FIELD\\_1](#), [CC\\_TYPE\\_NTSC\\_FIELD\\_2](#)

## Constructor Summary

public [ClosedCaptionCEA608Utils\(\)](#)

---

Methods inherited from class [com.wowza.wms.timedtext.cea608.ClosedCaptionCEA608Utils](#)

[calcParity](#), [calcParity](#), [cea608CharToCharUTF8](#), [cea608ExtendedCharacterToUTF8](#),  
[charUTF8ToCAE608](#), [charUTF8ToCAE608](#), [checkParity](#), [checkParity](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`,  
`wait`

---

## Constructors

### ClosedCaptionCEA608Utils

```
public ClosedCaptionCEA608Utils()
```

---

Package

**com.wowza.wms.dvr**

## com.wowza.wms.dvr

# Class DefaultDvrStreamVersionHandler

java.lang.Object

└─com.wowza.wms.dvr.DefaultDvrStreamVersionHandler

All Implemented Interfaces:

[IDvrStreamVersionHandler](#)

public class **DefaultDvrStreamVersionHandler**  
 extends Object  
 implements [IDvrStreamVersionHandler](#)

Default stream Version Handler. May be sub-classed

## Constructor Summary

public	<a href="#">DefaultDvrStreamVersionHandler()</a>
--------	--

## Method Summary

<a href="#">IDvrStreamStore</a>	<a href="#">determineExistingStoreForPlaying</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, String baseStreamName)
<a href="#">IDvrStreamStore</a>	<a href="#">determineExistingStoreForRecording</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, String baseStreamName)
String	<a href="#">getArchiveStrategy</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, String baseStreamName)
boolean	<a href="#">handleArchivedStream</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, String baseStreamName, String vStreamName, java.util.SortedSet versions, DvrManifestHolder manifestHolder)
boolean	<a href="#">shouldDeleteArchivedStream</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, <a href="#">IDvrStreamStore</a> store)
boolean	<a href="#">shouldLoadArchivedStream</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, String baseStreamName, String vStreamName, java.util.SortedSet versions, DvrManifestHolder manifest)

## Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Methods inherited from interface [com.wowza.wms.dvr.IDvrStreamVersionHandler](#)

[determineExistingStoreForPlaying](#), [determineExistingStoreForRecording](#), [getArchiveStrategy](#), [handleArchivedStream](#), [shouldDeleteArchivedStream](#), [shouldLoadArchivedStream](#)

## Constructors

### DefaultDvrStreamVersionHandler

```
public DefaultDvrStreamVersionHandler()
```

## Methods

### getArchiveStrategy

```
public String getArchiveStrategy(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

### determineExistingStoreForRecording

```
public IDvrStreamStore determineExistingStoreForRecording(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

### determineExistingStoreForPlaying

```
public IDvrStreamStore determineExistingStoreForPlaying(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

### handleArchivedStream

```
public boolean handleArchivedStream(IDvrStreamManager dvrMgr,  
    String baseStreamName,  
    String vStreamName,  
    java.util.SortedSet versions,  
    DvrManifestHolder manifestHolder)
```

### shouldLoadArchivedStream

```
public boolean shouldLoadArchivedStream(IDvrStreamManager dvrMgr,  
    String baseStreamName,  
    String vStreamName,  
    java.util.SortedSet versions,  
    DvrManifestHolder manifest)
```


### shouldDeleteArchivedStream

```
public boolean shouldDeleteArchivedStream(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

## com.wowza.wms.dvr

### Class DvrManifestChunkEntry

java.lang.Object



public class **DvrManifestChunkEntry**  
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains an associated chunk.

#### Field Summary

protected	<a href="#">artifact</a>
protected	<a href="#">encryptions</a>

#### Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[dvrStart](#), [dvrStop](#), [index](#), [MANIFESTFILE\\_KEY\\_ARTIFACT](#), [MANIFESTFILE\\_KEY\\_AUDIO\\_CODEC](#), [MANIFESTFILE\\_KEY\\_CHUNKINDEX](#), [MANIFESTFILE\\_KEY\\_DVRTIME](#), [MANIFESTFILE\\_KEY\\_ENCRYPTIONS](#), [MANIFESTFILE\\_KEY\\_INDEX](#), [MANIFESTFILE\\_KEY\\_METADATA](#), [MANIFESTFILE\\_KEY\\_NAME](#), [MANIFESTFILE\\_KEY\\_PACKETTIME](#), [MANIFESTFILE\\_KEY\\_SIZE](#), [MANIFESTFILE\\_KEY\\_START](#), [MANIFESTFILE\\_KEY\\_STOP](#), [MANIFESTFILE\\_KEY\\_TYPE](#), [MANIFESTFILE\\_KEY\\_UTCTIME](#), [MANIFESTFILE\\_KEY\\_VIDEO\\_CODEC](#), [packetTime](#), [SERIALIZE\\_CURRENT\\_VERSION](#), [type](#), [utcTime](#)

#### Constructor Summary

public	<a href="#">DvrManifestChunkEntry</a> (int type, int index, long dvrStart, long dvrStop, long packetTime, long utcTime, DvrChunkArtifact artifact) Constructor
public	<a href="#">DvrManifestChunkEntry</a> (int type, int index, long dvrStart, long dvrStop, long packetTime, long utcTime, DvrChunkArtifact artifact, DvrEncryptionInfoHolder encryptions) Constructor

#### Method Summary

String	<a href="#">getArtifactsTextRepresentation</a> ()
DvrChunkArtifact	<a href="#">getDvrArtifact</a> () Get DVR artifact reference.
DvrEncryptionInfoHolder	<a href="#">getEncryptions</a> () Get associated encryptions.
String	<a href="#">getEncryptionsTextRepresentation</a> ()
String	<a href="#">getManifestRepresentation</a> ()

void	<a href="#">serialize</a> (java.io.DataOutputStream out)
void	<a href="#">setEncryptions</a> (DvrEncryptionInfoHolder encryptions) Set associated encryptions.
String	<a href="#">toString</a> ()

Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#),  
[getManifestRepresentation](#), [getPacketStartTime](#), [getStartTimecode](#), [getStopTimecode](#),  
[getType](#), [getUtcStartTime](#), [serialize](#), [serialize](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,  
wait

## Fields

### artifact

protected com.wowza.wms.dvr.DvrChunkArtifact **artifact**

### encryptions

protected com.wowza.wms.dvr.DvrEncryptionInfoHolder **encryptions**

## Constructors

### DvrManifestChunkEntry

```
public DvrManifestChunkEntry(int type,
                             int index,
                             long dvrStart,
                             long dvrStop,
                             long packetTime,
                             long utcTime,
                             DvrChunkArtifact artifact)
```

Constructor

#### Parameters:

type - type  
index - manifest index  
dvrStart - start time (ms in DVR time scale)  
dvrStop - stop time (ms in DVR time scale)  
utcTime  
packetTime  
artifact - reference to the chunk artifact

(continued from last page)

## DvrManifestChunkEntry

```
public DvrManifestChunkEntry(int type,
                             int index,
                             long dvrStart,
                             long dvrStop,
                             long packetTime,
                             long utcTime,
                             DvrChunkArtifact artifact,
                             DvrEncryptionInfoHolder encryptions)
```

Constructor

### Parameters:

type - type  
index - manifest index  
dvrStart - start time (ms in DVR time scale)  
dvrStop - stop time (ms in DVR time scale)  
utcTime  
packetTime  
artifact - reference to the chunk artifact  
encryptions - associated encryptions

## Methods

### getDvrArtifact

```
public DvrChunkArtifact getDvrArtifact()
```

Get DVR artifact reference.

### Returns:

DVR artifact reference.

### setEncryptions

```
public void setEncryptions(DvrEncryptionInfoHolder encryptions)
```

Set associated encryptions.

### Parameters:

encryptions - encryptions

### getEncryptions

```
public DvrEncryptionInfoHolder getEncryptions()
```

Get associated encryptions.

### Returns:

encryptions

### serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.



---

(continued from last page)

## **getManifestRepresentation**

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

---

## **getEncryptionsTextRepresentation**

```
protected String getEncryptionsTextRepresentation()
```

---

## **getArtifactsTextRepresentation**

```
protected String getArtifactsTextRepresentation()
```


---

## **toString**

```
public String toString()
```

## com.wowza.wms.dvr Class DvrManifestCodecEntry

java.lang.Object



public class **DvrManifestCodecEntry**  
extends [DvrManifestEntry](#)

Entry in DVR manifest that contains codec information

### Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[dvrStart](#), [dvrStop](#), [index](#), [MANIFESTFILE\\_KEY\\_ARTIFACT](#), [MANIFESTFILE\\_KEY\\_AUDIO\\_CODEC](#), [MANIFESTFILE\\_KEY\\_CHUNKINDEX](#), [MANIFESTFILE\\_KEY\\_DVRTIME](#), [MANIFESTFILE\\_KEY\\_ENCRYPTIONS](#), [MANIFESTFILE\\_KEY\\_INDEX](#), [MANIFESTFILE\\_KEY\\_METADATA](#), [MANIFESTFILE\\_KEY\\_NAME](#), [MANIFESTFILE\\_KEY\\_PACKETTIME](#), [MANIFESTFILE\\_KEY\\_SIZE](#), [MANIFESTFILE\\_KEY\\_START](#), [MANIFESTFILE\\_KEY\\_STOP](#), [MANIFESTFILE\\_KEY\\_TYPE](#), [MANIFESTFILE\\_KEY\\_UTCTIME](#), [MANIFESTFILE\\_KEY\\_VIDEO\\_CODEC](#), [packetTime](#), [SERIALIZE\\_CURRENT\\_VERSION](#), [type](#), [utcTime](#)

### Constructor Summary

public	<a href="#">DvrManifestCodecEntry</a> (int index, long dvrStart, long packetTime, long utcTime, com.wowza.wms.media.model.MediaCodecInfoAudio audioCodec, com.wowza.wms.media.model.MediaCodecInfoVideo videoCodec) Constructor
--------	--

### Method Summary

com.wowza.wms.media.model.MediaCodecInfoAudio	<a href="#">getAudioCodec</a> () Get audio codec information
String	<a href="#">getManifestRepresentation</a> ()
com.wowza.wms.media.model.MediaCodecInfoVideo	<a href="#">getVideoCodec</a> () Get video codec information
void	<a href="#">serialize</a> (java.io.DataOutputStream out)
String	<a href="#">toString</a> ()

### Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#), [getManifestRepresentation](#), [getPacketStartTime](#), [getStartTimecode](#), [getStopTimecode](#), [getType](#), [getUtcStartTime](#), [serialize](#), [serialize](#)

### Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

## Constructors

### DvrManifestCodecEntry

```
public DvrManifestCodecEntry(int index,
                             long dvrStart,
                             long packetTime,
                             long utcTime,
                             com.wowza.wms.media.model.MediaCodecInfoAudio audioCodec,
                             com.wowza.wms.media.model.MediaCodecInfoVideo videoCodec)
```

Constructor

**Parameters:**

index - manifest index  
dvrStart - start time (ms in DVR time scale)  
audioCodec - audio codec info  
videoCodec - video codec info

## Methods

### getVideoCodec

```
public com.wowza.wms.media.model.MediaCodecInfoVideo getVideoCodec()
```

Get video codec information

**Returns:**

video codec information

### getAudioCodec

```
public com.wowza.wms.media.model.MediaCodecInfoAudio getAudioCodec()
```

Get audio codec information

**Returns:**

audio codec information

### serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

### getManifestRepresentation

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

(continued from last page)

## **toString**

```
public String toString()
```

## com.wowza.wms.dvr

# Class DvrManifestEntry

java.lang.Object

└─com.wowza.wms.dvr.DvrManifestEntry

Direct Known Subclasses:

[DvrManifestTimeMapEntry](#), [DvrManifestOnMetadataEntry](#), [DvrManifestCodecEntry](#), [DvrManifestChunkEntry](#)

public abstract class **DvrManifestEntry**  
extends Object

Abstract class representing entry in DVR manifest.

### Field Summary

protected	<a href="#">dvrStart</a>
protected	<a href="#">dvrStop</a>
protected	<a href="#">index</a>
public static final	<a href="#">MANIFESTFILE_KEY_ARTIFACT</a> Value: <b>artifact</b>
public static final	<a href="#">MANIFESTFILE_KEY_AUDIO_CODEC</a> Value: <b>aCodec</b>
public static final	<a href="#">MANIFESTFILE_KEY_CHUNKINDEX</a> Value: <b>chunkIndex</b>
public static final	<a href="#">MANIFESTFILE_KEY_DVRTIME</a> Value: <b>dvrTime</b>
public static final	<a href="#">MANIFESTFILE_KEY_ENCRYPTIONS</a> Value: <b>enc</b>
public static final	<a href="#">MANIFESTFILE_KEY_INDEX</a> Value: <b>index</b>
public static final	<a href="#">MANIFESTFILE_KEY_METADATA</a> Value: <b>metadata</b>
public static final	<a href="#">MANIFESTFILE_KEY_NAME</a> Value: <b>name</b>

public static final	<a href="#">MANIFESTFILE_KEY_PACKETTIME</a> Value: <b>packetTime</b>
public static final	<a href="#">MANIFESTFILE_KEY_SIZE</a> Value: <b>size</b>
public static final	<a href="#">MANIFESTFILE_KEY_START</a> Value: <b>start</b>
public static final	<a href="#">MANIFESTFILE_KEY_STOP</a> Value: <b>stop</b>
public static final	<a href="#">MANIFESTFILE_KEY_TYPE</a> Value: <b>type</b>
public static final	<a href="#">MANIFESTFILE_KEY_UTCTIME</a> Value: <b>utcTime</b>
public static final	<a href="#">MANIFESTFILE_KEY_VIDEO_CODEC</a> Value: <b>vCodec</b>
protected	<a href="#">packetTime</a>
protected static final	<a href="#">SERIALIZE_CURRENT_VERSION</a> Value: <b>2</b>
protected	<a href="#">type</a>
protected	<a href="#">utcTime</a>

## Constructor Summary

public	<a href="#">DvrManifestEntry</a> (int type, int index, long dvrStart, long dvrStop, long packetTime, long utcTime) Constructor Valid types include: <a href="#">IVHost.CONTENTTYPE_AUDIO</a> , <a href="#">IVHost.CONTENTTYPE_VIDEO</a> , <a href="#">IVHost.CONTENTTYPE_DATA</a> , <a href="#">IDvrManifest.ON_METADATA_TYPE</a> , <a href="#">IDvrManifest.CODEC_TYPE</a> , or <a href="#">IDvrManifest.TIME_MAP_TYPE</a>
--------	--

## Method Summary

String	<a href="#">encodeBytes</a> (byte[] bytes) Encode string of bytes as Base64.
String	<a href="#">getCommonInitialTextRepString</a> ()
long	<a href="#">getDuration</a> () Get duration
int	<a href="#">getIndex</a> () Get manifest index.

abstract String	<a href="#"><code>getManifestRepresentation()</code></a> Get textual representation of record for textual manifest usage.
long	<a href="#"><code>getPacketStartTime()</code></a> Get chunk start timecode in packetTime units.
long	<a href="#"><code>getStartTimecode()</code></a> Get start timecode.
long	<a href="#"><code>getStopTimecode()</code></a> Get stop timecode.
int	<a href="#"><code>getType()</code></a> Get type of manifest record.
long	<a href="#"><code>getUtcStartTime()</code></a> Get chunk start timecode in UTC units.
byte[]	<a href="#"><code>serialize()</code></a> Serialize manifest record.
abstract void	<a href="#"><code>serialize(java.io.DataOutputStream out)</code></a> Serialize manifest record.

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Fields

### MANIFESTFILE\_KEY\_INDEX

```
public static final java.lang.String MANIFESTFILE_KEY_INDEX
```

Constant value: **index**

### MANIFESTFILE\_KEY\_TYPE

```
public static final java.lang.String MANIFESTFILE_KEY_TYPE
```

Constant value: **type**

### MANIFESTFILE\_KEY\_START

```
public static final java.lang.String MANIFESTFILE_KEY_START
```

Constant value: **start**

### MANIFESTFILE\_KEY\_STOP

```
public static final java.lang.String MANIFESTFILE_KEY_STOP
```

(continued from last page)

Constant value: **stop**

---

## MANIFESTFILE\_KEY\_SIZE

```
public static final java.lang.String MANIFESTFILE_KEY_SIZE
```

Constant value: **size**

---

## MANIFESTFILE\_KEY\_ARTIFACT

```
public static final java.lang.String MANIFESTFILE_KEY_ARTIFACT
```

Constant value: **artifact**

---

## MANIFESTFILE\_KEY\_DVRTIME

```
public static final java.lang.String MANIFESTFILE_KEY_DVRTIME
```

Constant value: **dvrTime**

---

## MANIFESTFILE\_KEY\_CHUNKINDEX

```
public static final java.lang.String MANIFESTFILE_KEY_CHUNKINDEX
```

Constant value: **chunkIndex**

---

## MANIFESTFILE\_KEY\_PACKETTIME

```
public static final java.lang.String MANIFESTFILE_KEY_PACKETTIME
```

Constant value: **packetTime**

---

## MANIFESTFILE\_KEY\_UTCTIME

```
public static final java.lang.String MANIFESTFILE_KEY_UTCTIME
```

Constant value: **utcTime**

---

## MANIFESTFILE\_KEY\_NAME

```
public static final java.lang.String MANIFESTFILE_KEY_NAME
```

Constant value: **name**

---

## MANIFESTFILE\_KEY\_AUDIO\_CODEC

```
public static final java.lang.String MANIFESTFILE_KEY_AUDIO_CODEC
```

Constant value: **aCodec**



(continued from last page)

---

## MANIFESTFILE\_KEY\_VIDEO\_CODEC

```
public static final java.lang.String MANIFESTFILE_KEY_VIDEO_CODEC
```

Constant value: **vCodec**

---

## MANIFESTFILE\_KEY\_ENCRYPTIONS

```
public static final java.lang.String MANIFESTFILE_KEY_ENCRYPTIONS
```

Constant value: **enc**

---

## MANIFESTFILE\_KEY\_METADATA

```
public static final java.lang.String MANIFESTFILE_KEY_METADATA
```

Constant value: **metadata**

---

## SERIALIZE\_CURRENT\_VERSION

```
protected static final byte SERIALIZE_CURRENT_VERSION
```

Constant value: **2**

---

## dvrStart

```
protected long dvrStart
```

---

## dvrStop

```
protected long dvrStop
```

---

## packetTime

```
protected long packetTime
```

---

## utcTime

```
protected long utcTime
```

---

## index

```
protected int index
```

---

(continued from last page)

## type

protected int **type**

## Constructors

### DvrManifestEntry

```
public DvrManifestEntry(int type,  
                        int index,  
                        long dvrStart,  
                        long dvrStop,  
                        long packetTime,  
                        long utcTime)
```

Constructor Valid types include: [IVHost.CONTENTTYPE\\_AUDIO](#), [IVHost.CONTENTTYPE\\_VIDEO](#), [IVHost.CONTENTTYPE\\_DATA](#), [IDvrManifest.ON\\_METADATA\\_TYPE](#), [IDvrManifest.CODEC\\_TYPE](#), or [IDvrManifest.TIME\\_MAP\\_TYPE](#)

#### Parameters:

type - type  
index - manifest index  
dvrStart - start time (ms in DVR time scale)  
dvrStop - stop time (ms in DVR time scale)  
packetTime  
utcTime

## Methods

### getStartTimecode

```
public long getStartTimecode()
```

Get start timecode. In milliseconds, DVR time base.

#### Returns:

start time

### getStopTimecode

```
public long getStopTimecode()
```

Get stop timecode. In milliseconds, DVR time base.

#### Returns:

stop time

### getPacketStartTime

```
public long getPacketStartTime()
```

Get chunk start timecode in packetTime units. In milliseconds.

#### Returns:

packet start time

(continued from last page)

---

## getUtcStartTime

```
public long getUtcStartTime()
```

Get chunk start timecode in UTC units. In milliseconds.

**Returns:**

UTC start time

---

## getDuration

```
public long getDuration()
```

Get duration

**Returns:**

duration in ms

---

## getType

```
public int getType()
```

Get type of manifest record. Valid types include: [IVHost.CONTENTTYPE\\_AUDIO](#), [IVHost.CONTENTTYPE\\_VIDEO](#), [IVHost.CONTENTTYPE\\_DATA](#), [IDvrManifest.ON\\_METADATA\\_TYPE](#), [IDvrManifest.CODEC\\_TYPE](#), or [IDvrManifest.TIME\\_MAP\\_TYPE](#)

**Returns:**

type

---

## getIndex

```
public int getIndex()
```

Get manifest index.

**Returns:**

index

---

## serialize

```
public abstract void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

**Parameters:**

out - output stream

---

## serialize

```
public byte[] serialize()
```

Serialize manifest record.

**Returns:**

serialized data

---

---

(continued from last page)

## getManifestRepresentation

```
public abstract String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

**Returns:**

textual representation of entry

---

## getCommonInitialTextRepString

```
protected String getCommonInitialTextRepString()
```

---

## encodeBytes

```
protected String encodeBytes(byte[] bytes)
```

Encode string of bytes as Base64. Provides check for null buffer or empty buffer.

**Parameters:**

bytes - buffer to encode.

**Returns:**

Base64 encoding or "".

com.wowza.wms.dvr

# Class DvrManifestEntryFactory



```
public class DvrManifestEntryFactory
extends Object
```

Deserialize manifest entry blobs.

## Constructor Summary

public	<a href="#">DvrManifestEntryFactory()</a>
--------	---

## Method Summary

static <a href="#">DvrManifestEntry</a>	<a href="#">deserialize</a> (byte[] data)
static <a href="#">DvrManifestEntry</a>	<a href="#">deserialize</a> (java.nio.ByteBuffer buffer)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

**DvrManifestEntryFactory**

```
public DvrManifestEntryFactory()
```

## Methods

**deserialize**

```
public static DvrManifestEntry deserialize(byte[] data)
```

**deserialize**

```
public static DvrManifestEntry deserialize(java.nio.ByteBuffer buffer)
```

## com.wowza.wms.dvr Class DvrManifestEntryRange

java.lang.Object

└─com.wowza.wms.dvr.DvrManifestEntryRange

public class **DvrManifestEntryRange**  
extends Object

Class that compactly represents a range of indices of a certain manifest type.

### Constructor Summary

public	<a href="#"><u>DvrManifestEntryRange</u></a> (int type, int startIndex, int endIndex) Construct a range of a given type.
--------	---

### Method Summary

void	<a href="#"><u>deserialize</u></a> (byte[] data) Deserialize.
int	<a href="#"><u>getEndIndex</u></a> () Get end index.
IndexRange	<a href="#"><u>getRange</u></a> () Get index range.
int	<a href="#"><u>getStartIndex</u></a> () Get start index.
int	<a href="#"><u>getType</u></a> () Get range type
boolean	<a href="#"><u>isEmpty</u></a> ()
boolean	<a href="#"><u>isInRange</u></a> (int index) Is index in range.
byte[]	<a href="#"><u>serialize</u></a> () Serialize range.
void	<a href="#"><u>setRange</u></a> (IndexRange range) Set index range.
String	<a href="#"><u>toString</u></a> ()

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

(continued from last page)

## Constructors

### DvrManifestEntryRange

```
public DvrManifestEntryRange(int type,  
                             int startIndex,  
                             int endIndex)
```

Construct a range of a given type.

**Parameters:**

type - manifest type

startIndex - initial member of range

endIndex - final member of range

## Methods

### getType

```
public int getType()
```

Get range type

**Returns:**

type.

### getRange

```
public IndexRange getRange()
```

Get index range.

**Returns:**

index range

### setRange

```
public void setRange(IndexRange range)
```

Set index range.

**Parameters:**

range - index range.

### getStartIndex

```
public int getStartIndex()
```

Get start index.

**Returns:**

start index (or -1 if undefined)

### getEndIndex

```
public int getEndIndex()
```

Get end index.

---

(continued from last page)

**Returns:**

end index (or -1 if undefined)

---

**isInRange**

```
public boolean isInRange(int index)
```

Is index in range.

**Parameters:**

index - index in question.

**Returns:**

true if part of range.

---

**serialize**

```
public byte[] serialize()
```

Serialize range.

**Returns:**

out buffer containing serialized range.

---

**deserialize**

```
public void deserialize(byte[] data)
```

Deserialize. Called after no-op constructor.

**Parameters:**

data - buffer to deserialize.

---

**isEmpty**

```
public boolean isEmpty()
```

---

**toString**

```
public String toString()
```

---



## com.wowza.wms.dvr Class DvrManifestEntryRangeGroup

java.lang.Object

└─com.wowza.wms.dvr.DvrManifestEntryRangeGroup

public class **DvrManifestEntryRangeGroup**  
extends Object

A group of Manifest Ranges. The group may contain ranges of different types.

### Field Summary

public	<a href="#">ranges</a>
--------	------------------------

### Constructor Summary

public	<a href="#">DvrManifestEntryRangeGroup()</a>
--------	--

### Method Summary

void	<a href="#">addRange(DvrManifestEntryRange range)</a> Add an index range to the group.
void	<a href="#">deserialize(byte[] data)</a> Deserialize.
boolean	<a href="#">isEmpty()</a> Determine if group of ranges is empty
boolean	<a href="#">isInRange(int type, int index)</a> Determine if index of given type is contained in the group of ranges.
byte[]	<a href="#">serialize()</a> Serialize range group
String	<a href="#">toString()</a>

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Fields

#### **ranges**

public java.util.List **ranges**

## Constructors

### DvrManifestEntryRangeGroup

```
public DvrManifestEntryRangeGroup()
```

## Methods

### addRange

```
public void addRange(DvrManifestEntryRange range)
```

Add an index range to the group.

**Parameters:**

range

---

### isInRange

```
public boolean isInRange(int type,  
    int index)
```

Determine if index of given type is contained in the group of ranges.

**Parameters:**

type - range type

index - index in question

**Returns:**

true iof in range.

---

### isEmpty

```
public boolean isEmpty()
```

Determine if group of ranges is empty

**Returns:**

true if empty

---

### serialize

```
public byte[] serialize()
```

Serialize range group

**Returns:**

bytes representing range group

---

### deserialize

```
public void deserialize(byte[] data)
```

Deserialize. Called after no-op constructor.

(continued from last page)

**Parameters:**

data - buffer to deserialize.

---


**toString**

```
public String toString()
```

## com.wowza.wms.dvr

### Class DvrManifestOnMetadataEntry

java.lang.Object



public class **DvrManifestOnMetadataEntry**  
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains onMetadata information and associated onMetadata chunk.

#### Field Summary

protected	<a href="#">artifact</a>
protected	<a href="#">data</a>

#### Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[dvrStart](#), [dvrStop](#), [index](#), [MANIFESTFILE\\_KEY\\_ARTIFACT](#), [MANIFESTFILE\\_KEY\\_AUDIO\\_CODEC](#), [MANIFESTFILE\\_KEY\\_CHUNKINDEX](#), [MANIFESTFILE\\_KEY\\_DVRTIME](#), [MANIFESTFILE\\_KEY\\_ENCRYPTIONS](#), [MANIFESTFILE\\_KEY\\_INDEX](#), [MANIFESTFILE\\_KEY\\_METADATA](#), [MANIFESTFILE\\_KEY\\_NAME](#), [MANIFESTFILE\\_KEY\\_PACKETTIME](#), [MANIFESTFILE\\_KEY\\_SIZE](#), [MANIFESTFILE\\_KEY\\_START](#), [MANIFESTFILE\\_KEY\\_STOP](#), [MANIFESTFILE\\_KEY\\_TYPE](#), [MANIFESTFILE\\_KEY\\_UTCTIME](#), [MANIFESTFILE\\_KEY\\_VIDEO\\_CODEC](#), [packetTime](#), [SERIALIZE\\_CURRENT\\_VERSION](#), [type](#), [utcTime](#)

#### Constructor Summary

public	<a href="#">DvrManifestOnMetadataEntry</a> (int index, long start, long packetTime, long utcTime, <a href="#">DvrChunkArtifact</a> artifact, byte[] data) Constructor
--------	--

#### Method Summary

String	<a href="#">getArtifactsTextRepresentation()</a>
byte[]	<a href="#">getData()</a> Get onMetadata information.
<a href="#">DvrChunkArtifact</a>	<a href="#">getDvrArtifact()</a>
String	<a href="#">getManifestRepresentation()</a>
void	<a href="#">serialize</a> (java.io.DataOutputStream out)
String	<a href="#">toString()</a>

#### Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[getBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#),  
[getManifestRepresentation](#), [getPacketStartTime](#), [getStartTimecode](#), [getStopTimecode](#),  
[getType](#), [getUtcStartTime](#), [serialize](#), [serialize](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`,  
`wait`

## Fields

### artifact

protected `com.wowza.wms.dvr.DvrChunkArtifact` **artifact**

### data

protected `byte` **data**

## Constructors

### DvrManifestOnMetadataEntry

```
public DvrManifestOnMetadataEntry(int index,
                                   long start,
                                   long packetTime,
                                   long utcTime,
                                   DvrChunkArtifact artifact,
                                   byte[] data)
```

Constructor

#### Parameters:

`index` - manifest index  
`start` - start time (ms in DVR time scale)  
`utcTime`  
`packetTime`  
`artifact` - reference to the chunk artifact  
`data` - buffer of onMetadata information

## Methods

### getDvrArtifact

```
public DvrChunkArtifact getDvrArtifact()
```

### getData

```
public byte[] getData()
```

---

(continued from last page)

Get onMetadata information.

**Returns:**

onMetadata information.

---

## **serialize**

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

---

## **getManifestRepresentation**

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

---

## **getArtifactsTextRepresentation**

```
protected String getArtifactsTextRepresentation()
```

---


## **toString**

```
public String toString()
```

## com.wowza.wms.dvr

# Class DvrManifestTimeMapEntry

java.lang.Object



public class **DvrManifestTimeMapEntry**  
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains time map information.

### Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[dvrStart](#), [dvrStop](#), [index](#), [MANIFESTFILE\\_KEY\\_ARTIFACT](#), [MANIFESTFILE\\_KEY\\_AUDIO\\_CODEC](#), [MANIFESTFILE\\_KEY\\_CHUNKINDEX](#), [MANIFESTFILE\\_KEY\\_DVRTIME](#), [MANIFESTFILE\\_KEY\\_ENCRYPTIONS](#), [MANIFESTFILE\\_KEY\\_INDEX](#), [MANIFESTFILE\\_KEY\\_METADATA](#), [MANIFESTFILE\\_KEY\\_NAME](#), [MANIFESTFILE\\_KEY\\_PACKETTIME](#), [MANIFESTFILE\\_KEY\\_SIZE](#), [MANIFESTFILE\\_KEY\\_START](#), [MANIFESTFILE\\_KEY\\_STOP](#), [MANIFESTFILE\\_KEY\\_TYPE](#), [MANIFESTFILE\\_KEY\\_UTCTIME](#), [MANIFESTFILE\\_KEY\\_VIDEO\\_CODEC](#), [packetTime](#), [SERIALIZE\\_CURRENT\\_VERSION](#), [type](#), [utcTime](#)

## Constructor Summary

public	<a href="#">DvrManifestTimeMapEntry</a> (int index, int chunkIndex, long start, long packetTime, long utcTime, TimeMapRecord timeMap) Constructor
--------	--

## Method Summary

int	<a href="#">getChunkIndex</a> () Get chunk index that correlates to this time mapping
String	<a href="#">getManifestRepresentation</a> ()
TimeMapRecord	<a href="#">getTimeMapping</a> () Get time map record.
void	<a href="#">serialize</a> (java.io.DataOutputStream out)
String	<a href="#">toString</a> ()

### Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#), [getManifestRepresentation](#), [getPacketStartTime](#), [getStartTimecode](#), [getStopTimecode](#), [getType](#), [getUtcStartTime](#), [serialize](#), [serialize](#)

### Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

---

## Constructors

### DvrManifestTimeMapEntry

```
public DvrManifestTimeMapEntry(int index,
                               int chunkIndex,
                               long start,
                               long packetTime,
                               long utcTime,
                               TimeMapRecord timeMap)
```

Constructor

**Parameters:**

index - manifest index  
start - start time (ms in DVR time scale)  
timeMap - time map record

---

## Methods

### getTimeMapping

```
public TimeMapRecord getTimeMapping()
```

Get time map record.

**Returns:**

time map record

---

### getChunkIndex

```
public int getChunkIndex()
```

Get chunk index that correlates to this time mapping

**Returns:**

chunk index

---

### getManifestRepresentation

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

---

### serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

---

### toString

```
public String toString()
```



## com.wowza.wms.dvr Interface IDvrChannelManifest

All Subinterfaces:

[IDvrTimeMap](#)

public interface **IDvrChannelManifest**  
extends

### Method Summary

long	<a href="#">expandEndTime</a> (long dvrEndTime)
long	<a href="#">expandStartTime</a> (long dvrStartTime)
long	<a href="#">getClosestStartTime</a> (long t)
<a href="#">DvrManifestEntry</a>	<a href="#">getFirstEntry</a> ()
int	<a href="#">getFirstIndex</a> ()
java.util.Map	<a href="#">getIndexMap</a> ()
<a href="#">DvrManifestEntry</a>	<a href="#">getLastLiveEntry</a> ()
<a href="#">DvrManifestEntry</a>	<a href="#">getLastRecordedEntry</a> ()
int	<a href="#">getLastRecordedIndex</a> ()
long	<a href="#">getLiveDuration</a> ()
java.util.List	<a href="#">getLiveEntries</a> ()
java.util.List	<a href="#">getLiveEntries</a> (long startTime)
java.util.List	<a href="#">getLiveEntriesWithLimit</a> (long t, int limit)
<a href="#">DvrManifestEntryRange</a>	<a href="#">getLiveRangeEndingBeforeTime</a> (long time)
<a href="#">DvrManifestEntryRange</a>	<a href="#">getLiveRangeEndingBeforeTime</a> (long time, boolean skipFirst)
java.util.List	<a href="#">getLiveTailEntries</a> (int index)
int	<a href="#">getNumberLiveEntries</a> (long dvrStart)
int	<a href="#">getNumberLiveEntries</a> (long dvrStart, long dvrEnd)

int	<a href="#"><u>getNumberRecordedEntries</u></a> (long dvrStart)
int	<a href="#"><u>getNumberRecordedEntries</u></a> (long dvrStart, long dvrEnd)
long	<a href="#"><u>getRecordedDuration</u></a> ()
java.util.List	<a href="#"><u>getRecordedEntries</u></a> ()
java.util.List	<a href="#"><u>getRecordedEntries</u></a> (long dvrStartTime)
java.util.List	<a href="#"><u>getRecordedEntries</u></a> (long dvrStartTime, long dvrEndTime)
java.util.List	<a href="#"><u>getRecordedEntriesInRange</u></a> (int startIndex, int endIndex)
java.util.List	<a href="#"><u>getRecordedEntriesWithLimit</u></a> (long t, int limit)
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryByIndex</u></a> (int index)
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryByTimeKey</u></a> (long t)
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryStartingBeforeTime</u></a> (long t, boolean inclusive)
int	<a href="#"><u>getType</u></a> ()
boolean	<a href="#"><u>isEmpty</u></a> ()

## Methods

### isEmpty

```
public boolean isEmpty()
```

### getType

```
public int getType()
```

### getLastRecordedIndex

```
public int getLastRecordedIndex()
```

### getRecordedEntries

```
public java.util.List getRecordedEntries()
```

(continued from last page)

---

### getRecordedEntriesInRange

```
public java.util.List getRecordedEntriesInRange(int startIndex,  
int endIndex)
```

---

### getIndexMap

```
public java.util.Map getIndexMap()
```

---

### getRecordedEntryByTimeKey

```
public DvrManifestEntry getRecordedEntryByTimeKey(long t)
```

---

### getRecordedEntryByIndex

```
public DvrManifestEntry getRecordedEntryByIndex(int index)
```

---

### getRecordedEntryStartingBeforeTime

```
public DvrManifestEntry getRecordedEntryStartingBeforeTime(long t,  
boolean inclusive)
```

---

### getRecordedEntries

```
public java.util.List getRecordedEntries(long dvrStartTime)
```

---

### getRecordedEntries

```
public java.util.List getRecordedEntries(long dvrStartTime,  
long dvrEndTime)
```

---

### getRecordedEntriesWithLimit

```
public java.util.List getRecordedEntriesWithLimit(long t,  
int limit)
```

---

### getRecordedDuration

```
public long getRecordedDuration()
```

---

### getLiveDuration

```
public long getLiveDuration()
```

---

---

### getClosestStartTime

```
public long getClosestStartTime(long t)
```

---

---

### getLiveEntries

```
public java.util.List getLiveEntries()
```

---

---

### getLiveTailEntries

```
public java.util.List getLiveTailEntries(int index)
```

---

---

### getNumberLiveEntries

```
public int getNumberLiveEntries(long dvrStart)
```

---

---

### getNumberLiveEntries

```
public int getNumberLiveEntries(long dvrStart,  
                                long dvrEnd)
```

---

---

### getNumberRecordedEntries

```
public int getNumberRecordedEntries(long dvrStart)
```

---

---

### getNumberRecordedEntries

```
public int getNumberRecordedEntries(long dvrStart,  
                                long dvrEnd)
```

---

---

### getLiveEntries

```
public java.util.List getLiveEntries(long startTime)
```

---

(continued from last page)

---

## getLiveEntriesWithLimit

```
public java.util.List getLiveEntriesWithLimit(long t,  
                                              int limit)
```

---

## getFirstIndex

```
public int getFirstIndex()
```

---

## getFirstEntry

```
public DvrManifestEntry getFirstEntry()
```

---

## getLastLiveEntry

```
public DvrManifestEntry getLastLiveEntry()
```

---

## getLastRecordedEntry

```
public DvrManifestEntry getLastRecordedEntry()
```

---

## getLiveRangeEndingBeforeTime

```
public DvrManifestEntryRange getLiveRangeEndingBeforeTime(long time)
```

---

## getLiveRangeEndingBeforeTime

```
public DvrManifestEntryRange getLiveRangeEndingBeforeTime(long time,  
                  boolean skipFirst)
```

---

## expandStartTime

```
public long expandStartTime(long dvrStartTime)
```

---

## expandEndTime

```
public long expandEndTime(long dvrEndTime)
```

## com.wowza.wms.dvr Interface IDvrChunker

public interface **IDvrChunker**  
extends

### Method Summary

long	<a href="#"><code>calculateChunkGroupTime</code></a> (long dvrTime)
String	<a href="#"><code>determineChunkGroupIdentifier</code></a> (long dvrTime)
int	<a href="#"><code>getChunkGroupDuration</code></a> ()
void	<a href="#"><code>setChunkGroupDuration</code></a> (int chunkGrouping)

### Methods

#### `getChunkGroupDuration`

public int **getChunkGroupDuration**()

#### `determineChunkGroupIdentifier`

public String **determineChunkGroupIdentifier**(long dvrTime)

#### `calculateChunkGroupTime`

public long **calculateChunkGroupTime**(long dvrTime)

#### `setChunkGroupDuration`

public void **setChunkGroupDuration**(int chunkGrouping)

## com.wowza.wms.dvr Interface IDvrChunkMemoryCache

All Superinterfaces:

[IDvrRawChunkProvider](#)

public interface **IDvrChunkMemoryCache**

extends [IDvrRawChunkProvider](#)

Interface for managing in-memory cache of chunks. The implementor is responsible for implementing the desired algorithm for keeping DVR chunks in memory.

### Method Summary

void	<a href="#">addToCache</a> ( <a href="#">DvrManifestChunkEntry</a> entry, DvrChunk chunk) Provide in-memory cache the opportunity to add the DVR chunk to its cache.
void	<a href="#">init</a> ( <a href="#">IDvrStreamStore</a> store) Called to initialize the in-memory cache.
DvrChunk	<a href="#">retrieveRawChunk</a> ( <a href="#">DvrManifestChunkEntry</a> entry)

Methods inherited from interface [com.wowza.wms.dvr.IDvrRawChunkProvider](#)

[retrieveRawChunk](#)

### Methods

#### **init**

public void **init**([IDvrStreamStore](#) store)

Called to initialize the in-memory cache.

**Parameters:**

store - The DVR stream store associated with this cache.

#### **retrieveRawChunk**

public DvrChunk **retrieveRawChunk**([DvrManifestChunkEntry](#) entry)

#### **addToCache**

public void **addToCache**([DvrManifestChunkEntry](#) entry,  
DvrChunk chunk)

Provide in-memory cache the opportunity to add the DVR chunk to its cache. The implementation may choose to cache the chunk or ignore it.

**Parameters:**

(continued from last page)

entry - DVR manifest entry  
chunk - the chunk.



## com.wowza.wms.dvr Interface IDvrChunkUtcDelegate

public interface **IDvrChunkUtcDelegate**  
extends

Delegate class for determining utc time of DVR chunk.

### Method Summary

long	<a href="#">determineUtcTime</a> (long currentUtc, long aChunkStartUtc, long aFirstPacketUtc, <a href="#">AMFPacket</a> aFirstPacket, long vChunkStartUtc, long vFirstPacketUtc, <a href="#">AMFPacket</a> vFirstPacket)
void	<a href="#">init</a> ( <a href="#">IDvrStreamStore</a> store)

### Methods

#### **init**

public void **init**([IDvrStreamStore](#) store)

#### **determineUtcTime**

```
public long determineUtcTime(long currentUtc,  
    long aChunkStartUtc,  
    long aFirstPacketUtc,  
    AMFPacket aFirstPacket,  
    long vChunkStartUtc,  
    long vFirstPacketUtc,  
    AMFPacket vFirstPacket)
```

## com.wowza.wms.dvr Interface IDvrConstants

public interface **IDvrConstants**  
extends IDvrPrivateConstants

### Nested Class Summary

class	<a href="#">IDvrConstants.DvrTimeScale</a> IDvrConstants.DvrTimeScale
-------	--

### Field Summary

public static final	<a href="#">ARCHIVE_STRATEGY_APPEND</a> Value: <b>append</b>
public static final	<a href="#">ARCHIVE_STRATEGY_DELETE</a> Value: <b>delete</b>
public static final	<a href="#">ARCHIVE_STRATEGY_VERSION</a> Value: <b>version</b>
public static final	<a href="#">DEFAULT_CHUNK_MEMORY_CACHESIZE</a> Default value for DVR Property "chunkMemoryCacheSize". Value: <b>10</b>
public static final	<a href="#">DEFAULT_CUPERTINO_PLAYLIST_GZIP_THRESHOLD</a> Default value for property "dvrCupertinoPlaylistGzipThreshold" #see <a href="#">PROPERTY_CUPERTINO_PLAYLIST_GZIP_THRESHOLD</a> Value: <b>4000</b>
public static final	<a href="#">DEFAULT_PROPERTY_ALLOWABLE_AV_PACKET_DELTA</a> Default value for DVR Property "dvrAllowableAVPacketDelta". Value: <b>2000</b>
public static final	<a href="#">DEFAULT_PROPERTY_APPEND_DISCONTINUITY_DELTA</a> Default value for DVR Property "dvrAppendDiscontinuityDelta". Value: <b>0</b>
public static final	<a href="#">DEFAULT_PROPERTY_AUDIO_ONLY_CHUNK_TARGET_DURATION</a> Default value for DVR Property "dvrAudioOnlyChunkTargetDuration". Value: <b>2000</b>
public static final	<a href="#">DEFAULT_PROPERTY_BREAK_ON_PTS</a> Default value for DVR Property "dvrChunkBreakOnPTS". Value: <b>true</b>
public static final	<a href="#">DEFAULT_PROPERTY_CHUNK_CACHE_CLASS</a> Default value for DVR Property "dvrChunkMemoryCacheClass". Value: <b>com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache</b>

public static final	<a href="#">DEFAULT_PROPERTY_CHUNK_DURATION_MINIMUM</a> Default value for DVR Property "dvrChunkDurationMinimum". Value: <b>1500</b>
public static final	<a href="#">DEFAULT_PROPERTY_CHUNK_GROUPING_SECONDS</a> Default value for DVR Property "dvrChunkGroupingSeconds". Value: <b>600</b>
public static final	<a href="#">DEFAULT_PROPERTY_CHUNK_READER_CLASS</a> Default value for DVR Property "dvrChunkReaderClass". Value: <b>com.wowza.wms.dvr.impl.io.DvrFileChunkReader</b>
public static final	<a href="#">DEFAULT_PROPERTY_CHUNK_WRITER_CLASS</a> Default value for DVR Property "dvrChunkWriterClass". Value: <b>com.wowza.wms.dvr.impl.io.DvrFileChunkWriter</b>
public static final	<a href="#">DEFAULT_PROPERTY_DEBUG_MAX_INVALID_CHUNKS_LOGGED</a> Default value for DVR Property "dvrMaxInvalidChunksLogged". Value: <b>10</b>
public static final	<a href="#">DEFAULT_PROPERTY_DEBUG_MAX_RAW_PACKETS</a> Default value for DVR Property "dvrDebugMaximumRawPackets". Value: <b>200</b>
public static final	<a href="#">DEFAULT_PROPERTY_DEBUG_MAX_VALID_CHUNKS_LOGGED</a> Default value for DVR Property "dvrMaxValidChunksLogged". Value: <b>10</b>
public static final	<a href="#">DEFAULT_PROPERTY_DEBUG_RAW_PACKETS</a> Default value for DVR Property "dvrDebugRawPackets". Value: <b>false</b>
public static final	<a href="#">DEFAULT_PROPERTY_DVR_MAX_CHUNK_LOG</a> Default value for DVR Property "dvrMaxChunkLogCount". Value: <b>10</b>
public static final	<a href="#">DEFAULT_PROPERTY_FILE_SYSTEM_CLASS</a> Default value for DVR Property "dvrFileSystemClass". Value: <b>com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem</b>
public static final	<a href="#">DEFAULT_PROPERTY_MANIFEST_PERSISTER_CLASS</a> Default value for DVR Property "dvrManifestPersisterClass". Value: <b>com.wowza.wms.dvr.impl.DvrManifestPersister</b>
public static final	<a href="#">DEFAULT_PROPERTY_MAX_RECALC_DURATION_LOG</a> Default value for DVR Property "dvrMaxRecountDurationLogCount". Value: <b>30</b>
public static final	<a href="#">DEFAULT_PROPERTY_MAX_RECORDING_LENGTH</a> Default value for DVR Property "dvrMaximumRecordingLength". Value: <b>108000</b>
public static final	<a href="#">DEFAULT_PROPERTY_MBR_ALTERNATIVE_MATCH_DELTA</a> Default value for DVR Property "dvrMbrAlternateMatchDelta". Value: <b>1000</b>

public static final	<a href="#">DEFAULT_PROPERTY_MBR_MINIMUM_PACKETTIME_GAP_SIZE</a> Default value for DVR Property "dvrMbrMinimumPacketTimeGapSize". Value: <b>100</b>
public static final	<a href="#">DEFAULT_PROPERTY_MBR_MINIMUM_UTCTIME_GAP_SIZE</a> Default value for DVR Property "dvrMbrMinimumPacketTimeGapSize". Value: <b>750</b>
public static final	<a href="#">DEFAULT_PROPERTY_MEDIACACHE_READER_CLASS</a> Default value for DVR Property "dvrMediaCacheReaderClass". Value: <b>com.wowza.wms.plugin.mediacache.impl.MediaCacheRandomAccessReader</b>
public static final	<a href="#">DEFAULT_PROPERTY_PACKET_DELTA_TO_NOTIFY</a> Value: <b>200</b>
public static final	<a href="#">DEFAULT_PROPERTY_PACKET_DELTA_TO_RESET_TIME</a> Default value for DVR Property "dvrResetTimePacketDelta". Value: <b>200</b>
public static final	<a href="#">DEFAULT_PROPERTY_PACKET_DURATION_MAXIMUM</a> Default value for DVR Property "dvrChunkDurationMinimum". Value: <b>5000</b>
public static final	<a href="#">DEFAULT_PROPERTY_PACKET_SORT_TIME</a> Default value for DVR Property "dvrPacketSortTime". Value: <b>0</b>
public static final	<a href="#">DEFAULT_PROPERTY_RECORDINGS_LOADER_CLASS</a> Default value for DVR Property "dvrRecordingsLoaderClass". Value: <b>com.wowza.wms.dvr.DvrRecordingsLoader</b>
public static final	<a href="#">DEFAULT_PROPERTY_REPEATER_HEARTBEAT_DURATION</a> Value: <b>4000</b>
public static final	<a href="#">DEFAULT_PROPERTY_SANJOSE_ABST_DURATION_TOLERANCE</a> Default value for property "dvrSanJosePlaylistAbstDurationTolerance" #see <a href="#">PROPERTY_SANJOSE_ABST_DURATION_TOLERANCE</a> Value: <b>50</b>
public static final	<a href="#">DEFAULT_PROPERTY_SANJOSE_ABST_TIMESCALE</a> Default value for property "dvrSanJosePlaylistAbstTimescale" #see <a href="#">PROPERTY_SANJOSE_ABST_TIMESCALE</a> Value: <b>1000</b>
public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_PAUSE</a> Value: <b>true</b>
public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_SEEK</a> Value: <b>true</b>
public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_MAJOR_VERSION</a> Value: <b>2</b>

public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_MINOR_VERSION</a> Value: <b>1</b>
public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_PAUSE</a> Value: <b>true</b>
public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_SEEK</a> Value: <b>true</b>
public static final	<a href="#">DEFAULT_PROPERTY_SMOOTH_MANIFEST_RECORDED_SPECIFY_DURATION</a> Value: <b>true</b>
public static final	<a href="#">DEFAULT_PROPERTY_STORAGE_DIRECTORY</a> Default value for DVR Property "dvrStorageDirectory". Value: <b>\${com.wowza.wms.context.VHostConfigHome}/dvr</b>
public static final	<a href="#">DEFAULT_PROPERTY_TEXT_READER_CLASS</a> Default value for DVR Property "dvrTextReaderClass". Value: <b>com.wowza.wms.dvr.impl.io.DvrTextFileReader</b>
public static final	<a href="#">DEFAULT_PROPERTY_TEXT_WRITER_CLASS</a> Default value for DVR Property "dvrTextWriterClass". Value: <b>com.wowza.wms.dvr.impl.io.DvrTextFileWriter</b>
public static final	<a href="#">DVR_DEFAULT_FILESTORE</a> The default DVR store ID: "dvrfilestorage". Value: <b>dvrfilestorage</b>
public static final	<a href="#">DVR_DEFAULT_RECORDER_ID</a> The default DVR recorder ID: "dvrrecorder". Value: <b>dvrrecorder</b>
public static final	<a href="#">DVR_REPEATER_PACKETIZER_ID</a> The default DVR streaming repeater ID: "dvrstreamingrepeater". Value: <b>dvrstreamingrepeater</b>
public static final	<a href="#">DVR_STREAMING_PACKETIZER_ID</a> The default DVR streaming packetizer ID: "dvrstreamingpacketizer". Value: <b>dvrstreamingpacketizer</b>
public static final	<a href="#">DVR_WINDOW_DURATION_UNLIMITED</a> Value: <b>0</b>
public static final	<a href="#">MEDIACACHE_PREFIX</a> The MediaCache prefix for dvr repeater Value: <b>dvrorigin</b>
public static final	<a href="#">MIMETYPE_VIDEO_MP4</a> Constant for mime type "video/mp4" Value: <b>video/mp4</b>

public static final	<a href="#"><u>PROPERTY_ALLOWABLE_AV_PACKET_DELTA</u></a> DVR Property "dvrAllowableAVPacketDelta": for specifying how much audio and video packets may diverge before triggering an error. Value: <b>dvrAllowableAVPacketDelta</b>
public static final	<a href="#"><u>PROPERTY_APPEND_DISCONTINUITY_DELTA</u></a> DVR Property "dvrAppendDiscontinuityDelta": for specifying how many milliseconds of empty space are put between individual recordings that when in append mode. Value: <b>dvrAppendDiscontinuityDelta</b>
public static final	<a href="#"><u>PROPERTY_ARCHIVE_STRATEGY</u></a> DVR Property "dvrArchiveStrategy": for specifying the DVR archive strategy. Value: <b>dvrArchiveStrategy</b>
public static final	<a href="#"><u>PROPERTY_AUDIO_ONLY_CHUNK_TARGET_DURATION</u></a> DVR Property "dvrAudioOnlyChunkTargetDuration": for target duration when recording audio-only. Value: <b>dvrAudioOnlyChunkTargetDuration</b>
public static final	<a href="#"><u>PROPERTY_BREAK_ON_PTS</u></a> DVR Property "dvrChunkBreakOnPTS": for specifying that DVR should be broken on PTS. Value: <b>dvrChunkBreakOnPTS</b>
public static final	<a href="#"><u>PROPERTY_CHUNK_CACHE_CLASS</u></a> DVR Property "dvrChunkMemoryCacheClass": for controlling the class responsible for caching DVR chunks in memory. Value: <b>dvrChunkMemoryCacheClass</b>
public static final	<a href="#"><u>PROPERTY_CHUNK_DURATION_MINIMUM</u></a> DVR Property "dvrChunkDurationMinimum": for minimum chunk duration, in milliseconds. Value: <b>dvrChunkDurationMinimum</b>
public static final	<a href="#"><u>PROPERTY_CHUNK_GROUPING_SECONDS</u></a> DVR Property "dvrChunkGroupingSeconds": for determining how many seconds of DVR are stored in each stores sub-folder. Value: <b>dvrChunkGroupingSeconds</b>
public static final	<a href="#"><u>PROPERTY_CHUNK_MEMORY_CACHESIZE</u></a> DVR Property "chunkMemoryCacheSize": used by DvrDefaultChunkMemoryCache to set number of chunks stored in DVR in-memory cache. Value: <b>chunkMemoryCacheSize</b>
public static final	<a href="#"><u>PROPERTY_CHUNK_READER_CLASS</u></a> DVR Property "dvrChunkReaderClass": for controlling the class responsible for reading DVR Chunks. Value: <b>dvrChunkReaderClass</b>
public static final	<a href="#"><u>PROPERTY_CHUNK_WRITER_CLASS</u></a> DVR Property "dvrChunkWriterClass": for controlling the class responsible for writing DVR Chunks. Value: <b>dvrChunkWriterClass</b>
public static final	<a href="#"><u>PROPERTY_CUPERTINO_ON_CHUNK_START_RESET_COUNTER</u></a> DVR Property "dvrCupertinoOnChunkStartResetCounter": when a new chunk starts, reset internal tsPacketizer counters Value: <b>dvrCupertinoOnChunkStartResetCounter</b>

public static final	<a href="#"><u>PROPERTY_CUPERTINO_PLAYLIST_ALLOW_CACHING</u></a> DVR Property "dvrCupertinoPlaylistAllowCaching": used to force Cupertino playlist to set #EXT-X-ALLOW-CACHE: value Value: <b>dvrCupertinoPlaylistAllowCaching</b>
public static final	<a href="#"><u>PROPERTY_CUPERTINO_PLAYLIST_FORCE_LIVE</u></a> DVR Property "dvrCupertinoPlaylistForceLive": used to override playlist request delegate logic that determines if playlist is live. Value: <b>dvrCupertinoPlaylistForceLive</b>
public static final	<a href="#"><u>PROPERTY_CUPERTINO_PLAYLIST_FORCE_NONLIVE</u></a> DVR Property "dvrCupertinoPlaylistForceLive": used to override playlist request delegate logic that determines if playlist is live versus non-live. Value: <b>dvrCupertinoPlaylistForceNonLive</b>
public static final	<a href="#"><u>PROPERTY_CUPERTINO_PLAYLIST_GZIP_THRESHOLD</u></a> DVR Property "dvrCupertinoPlaylistGzipThreshold": when playlist is larger than this number of bytes, and gzip is enabled and accepted, the playlist will be compressed Value: <b>dvrCupertinoPlaylistGzipThreshold</b>
public static final	<a href="#"><u>PROPERTY_CUPERTINO_PLAYLIST_USE_GZIP</u></a> DVR Property "dvrCupertinoPlaylistUseGzip": used to force Cupertino playlist to use gzip if it is accepted Value: <b>dvrCupertinoPlaylistUseGzip</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_CHUNK_RETRIEVALS</u></a> DVR Property "dvrDebugChunkRetrievals": for logging each chunk retrieval Value: <b>dvrDebugChunkRetrievals</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_CUPERTINO_PLAYER_ADAPTER</u></a> HTTP Streamer Property "dvrDebugCupertinoPlayerAdapter": for turning on DVR Player Cupertino Adapter debug logging. Value: <b>dvrDebugCupertinoPlayerAdapter</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_FAILED_CHUNK_RETRIEVALS</u></a> DVR Property "dvrDebugFailedChunkRetrievals": for logging info about each failed chunk retrieval Value: <b>dvrDebugFailedChunkRetrievals</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_LOG_INVALID_CHUNK_DETAILS</u></a> DVR Property "dvrLogInvalidChunkDetails": to control detailed logging information of DVR invalid chunks Value: <b>dvrLogInvalidChunkDetails</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_LOG_INVALID_CHUNK_MATCHER</u></a> DVR Property "dvrLogInvalidChunkMatcher": for matching stream names that will log chunk packets Value: <b>dvrLogInvalidChunkMatcher</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_LOG_VALID_CHUNK_DETAILS</u></a> DVR Property "dvrLogValidChunkDetails": to control detailed logging information of DVR valid chunks Value: <b>dvrLogValidChunkDetails</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_LOG_VALID_CHUNK_MATCHER</u></a> DVR Property "dvrLogValidChunkMatcher": for matching stream names that will log chunk packets Value: <b>dvrLogValidChunkMatcher</b>

public static final	<a href="#"><u>PROPERTY_DEBUG_MAX_INVALID_CHUNKS_LOGGED</u></a> DVR Property "dvrMaxInvalidChunksLogged": for controlling maximum number of invalid DVR chunks logged. Value: <b>dvrMaxInvalidChunksLogged</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MAX_VALID_CHUNKS_LOGGED</u></a> DVR Property "dvrMaxValidChunksLogged": for controlling maximum number of valid DVR chunks logged. Value: <b>dvrMaxValidChunksLogged</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MAXIMUM_RAW_PACKETS</u></a> DVR Property "dvrDebugMaximumRawPackets": for setting maximum number of logged raw packets. Value: <b>dvrDebugMaximumRawPackets</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MBR_ALIGNMENT</u></a> HTTP Streamer or DVR Property "dvrDebugMbrAlignment": for turning on logging of mbr alignment Value: <b>dvrDebugMbrAlignment</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MBR_ALIGNMENT_RESOLUTION</u></a> DVR Property "dvrDebugMbrAlignmentResolution": for turning on logging of mbr alignment resolution (requested to actual) Value: <b>dvrDebugMbrAlignmentResolution</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MBR_DETAILS_WHEN_RECORD_DNE</u></a> HTTP Streamer or DVR Property "dvrDebugMbrDetailsWhenRecordDNE": for turning on DVR MBR Player Adapter debug logging. Value: <b>dvrDebugMbrDetailsWhenRecordDNE</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MBR_PLAYER_ADAPTER</u></a> HTTP Streamer or DVR Property "dvrDebugMbrPlayerAdapter": for turning on DVR MBR Player Adapter debug logging. Value: <b>dvrDebugMbrPlayerAdapter</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_MBR_PLAYER_ADAPTER_IF_SHIFTED_EMPTY</u></a> HTTP Streamer or DVR Property "dvrDebugMbrPlayerAdapter": for turning on DVR MBR Player Adapter debug logging when null shifted entries is returned. Value: <b>dvrDebugMbrPlayerAdapterWhenShiftedEmpty</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_METHODS</u></a> DVR Property "dvrDebugManagerLogMethods": for turning on DVR Manager debug logging. Value: <b>dvrDebugManagerLogMethods</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_PLAYER_ADAPTER</u></a> HTTP Streamer Property "dvrDebugPlayerAdapter": for turning on DVR Player Adapter debug logging for all streamer types. Value: <b>dvrDebugPlayerAdapter</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_PLAYLIST_REQUEST</u></a> DVR Property "dvrDebugPlaylistRequest": for turning on logging of DVR playlist requests. Value: <b>dvrDebugPlaylistRequest</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_RAW_PACKETS</u></a> DVR Property "dvrDebugRawPackets": for turning on logging of incoming raw packets. Value: <b>dvrDebugRawPackets</b>



public static final	<a href="#"><u>PROPERTY_DEBUG_RAW_PACKETS_MATCHER</u></a> DVR Property "dvrDebugRawPacketsMatcher": for matching stream names that will dump raw packet. Value: <b>dvrDebugRawPacketsMatcher</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_REPEATER</u></a> DVR Property "dvrDebugRepeater": for turning on logging of DVR repeater Value: <b>dvrDebugRepeater</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_SANJOSE_PLAYER_ADAPTER</u></a> HTTP Streamer Property "dvrDebugSanJosePlayerAdapter": for turning on DVR Player San Jose Adapter debug logging. Value: <b>dvrDebugSanJosePlayerAdapter</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_SMOOTH_PLAYER_ADAPTER</u></a> HTTP Streamer Property "dvrDebugSmoothPlayerAdapter": for turning on DVR Player Smooth Adapter debug logging. Value: <b>dvrDebugSmoothPlayerAdapter</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_STATE_CHANGE</u></a> DVR Property "dvrDebugStateChange": for logging state changes of DVR store. Value: <b>dvrDebugStateChange</b>
public static final	<a href="#"><u>PROPERTY_DEBUG_TOSSED_HOLDERS</u></a> DVR Property "dvrDebugTossedHolders": for turning on logging of packets that are being tossed. Value: <b>dvrDebugTossedHolders</b>
public static final	<a href="#"><u>PROPERTY_ENCRYPTION_INFO_DELEGATE</u></a> DVR Property "dvrPlaylistEncryptionInfoDelegate": used to over-ride the encryption info on the playback side. Value: <b>dvrPlaylistEncryptionInfoDelegate</b>
public static final	<a href="#"><u>PROPERTY_FILE_SYSTEM_CLASS</u></a> DVR Property "dvrFileSystemClass": for controlling the class responsible for managing the DVR File System. Value: <b>dvrFileSystemClass</b>
public static final	<a href="#"><u>PROPERTY_MANIFEST_PERSISTER_CLASS</u></a> DVR Property "dvrManifestPersisterClass": for controlling the class responsible for persisting the manifest files. Value: <b>dvrManifestPersisterClass</b>
public static final	<a href="#"><u>PROPERTY_MAX_CHUNK_LOG</u></a> DVR Property "dvrMaxChunkLogCount": for maximum number of DVR chunks to log. Value: <b>dvrMaxChunkLogCount</b>
public static final	<a href="#"><u>PROPERTY_MAX_RECALC_DURATION_LOG</u></a> DVR Property "dvrMaxRecountDurationLogCount": for maximum number of messages to log regarding recalculating DVR chunk duration Value: <b>dvrMaxRecountDurationLogCount</b>
public static final	<a href="#"><u>PROPERTY_MAX_RECORDING_LENGTH</u></a> DVR Property "dvrMaximumRecordingLength": The maximum recording length in seconds. Value: <b>dvrMaximumRecordingLength</b>

public static final	<a href="#">PROPERTY_MBR_ALTERNATIVE_MATCH_DELTA</a> DVR Property "dvrMbrAlternateMatchDelta": when finding alternative for a MBR gap, an alternate is considered a match is within this many ms of the gap in question. Value: <b>dvrMbrAlternateMatchDelta</b>
public static final	<a href="#">PROPERTY_MBR_MINIMUM_PACKETTIME_GAP_SIZE</a> DVR Property "dvrMbrMinimumPacketTimeGapSize": when doing mbr alignment gaps smaller than this are ignored. Value: <b>dvrMbrMinimumPacketTimeGapSize</b>
public static final	<a href="#">PROPERTY_MBR_MINIMUM_UTCTIME_GAP_SIZE</a> DVR Property "dvrMbrMinimumUtcTimeGapSize": when doing mbr alignment gaps smaller than this are ignored. Value: <b>dvrMbrMinimumUtcTimeGapSize</b>
public static final	<a href="#">PROPERTY_MBR_USE_UTC_FOR_ALIGNMENT</a> DVR Property "dvrMbrUseUtcForAlignment": when doing mbr alignment use utc time for alignment Value: <b>dvrMbrUseUtcForAlignment</b>
public static final	<a href="#">PROPERTY_MEDIACACHE_ENABLED</a> DVR Property "dvrMediaCacheEnabled" Value: <b>dvrMediaCacheEnabled</b>
public static final	<a href="#">PROPERTY_MEDIACACHE_READER_CLASS</a> DVR Property "dvrMediaCacheReaderClass" Value: <b>dvrMediaCacheReaderClass</b>
public static final	<a href="#">PROPERTY_PACKET_DELTA_TO_NOTIFY</a> Value: <b>dvrPacketDeltaToNotify</b>
public static final	<a href="#">PROPERTY_PACKET_DELTA_TO_RESET_TIME</a> DVR Property "dvrResetTimePacketDelta": for controlling how much Chunk start times must diverge from last chunk's end time before the DVR time gets reset. Value: <b>dvrResetTimePacketDelta</b>
public static final	<a href="#">PROPERTY_PACKET_DURATION_MAXIMUM</a> DVR Property "dvrPacketDurationMaximum": for maximum packet duration, in milliseconds. Value: <b>dvrPacketDurationMaximum</b>
public static final	<a href="#">PROPERTY_PACKET_SORT_TIME</a> DVR Property "dvrPacketSortTime": for sorting incoming packets. Value: <b>dvrPacketSortTime</b>
public static final	<a href="#">PROPERTY_PLAYLIST_REQUEST_DELEGATE</a> DVR Property "dvrPlaylistRequestDelegate": used to over-ride the class that generates a playlist request. Value: <b>dvrPlaylistRequestDelegate</b>
public static final	<a href="#">PROPERTY_RECORD_AUDIO</a> DVR Property "recordAudio": for determining if audio should be recorded. Value: <b>recordAudio</b>
public static final	<a href="#">PROPERTY_RECORD_DATA</a> DVR Property "recordData": for determining if data should be recorded. Value: <b>recordData</b>

public static final	<a href="#"><u>PROPERTY_RECORD_VIDEO</u></a> DVR Property "recordVideo": for determining if video should be recorded. Value: <b>recordVideo</b>
public static final	<a href="#"><u>PROPERTY_RECORDINGS_LOADER_CLASS</u></a> DVR Property "dvrRecordingsLoaderClass": for controlling the class responsible for loading DVR recordings. Value: <b>dvrRecordingsLoaderClass</b>
public static final	<a href="#"><u>PROPERTY_REPEATER_HEARTBEAT_DURATION</u></a> DVR Property "dvrRepeaterHeartbeatDuration": for time in ms that origin pings edges Value: <b>dvrRepeaterHeartbeatDuration</b>
public static final	<a href="#"><u>PROPERTY_REPEATER_SHARED_SECRET</u></a> DVR Property "dvrEncryptionSharedSecret": for encryption shared secret between origins and edges. Value: <b>dvrEncryptionSharedSecret</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_ABST_DURATION_TOLERANCE</u></a> DVR Property "dvrSanJosePlaylistAbstDurationEqualityTolerance": used to over-ride the tolerance when determining equal chunks lengths. Value: <b>dvrSanJosePlaylistAbstDurationTolerance</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_ABST_TIMESCALE</u></a> DVR Property "dvrSanJosePlaylistAbstTimescale": used to over-ride the time-scale for abst files. Value: <b>dvrSanJosePlaylistAbstTimescale</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_PLAYLIST_DELIVERYTYPE</u></a> DVR Property "dvrSanJosePlaylistDeliveryType": used to over-ride the mime type for DVR San Jose F4m playlists. Value: <b>dvrSanJosePlaylistDeliveryType</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_PLAYLIST_LIVE_STREAMTYPE</u></a> DVR Property "dvrSanJosePlaylistLiveStreamType": used to over-ride the stream type for live DVR in San Jose f4m playlists. Value: <b>dvrSanJosePlaylistLiveStreamType</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_PLAYLIST_MIMETYPE</u></a> DVR Property "dvrSanJosePlaylistMimeType": used to over-ride the mime type for DVR San Jose F4m playlists. Value: <b>dvrSanJosePlaylistMimeType</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_PLAYLIST_RECORDED_STREAMTYPE</u></a> DVR Property "dvrSanJosePlaylistRecordedStreamType": used to over-ride the stream type for non-live (recorded) DVR in San Jose f4m playlists. Value: <b>dvrSanJosePlaylistRecordedStreamType</b>
public static final	<a href="#"><u>PROPERTY_SANJOSE_PLAYLIST_VERSION</u></a> DVR Property "dvrSanJosePlaylistVersion": used to over-ride the version of the San Jose f4m playlist. Value: <b>dvrSanJosePlaylistVersion</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_H264_CODEC</u></a> DVR Property "dvrSmoothManifestH264Codec": used to force Smooth Manifest to use this as its FourCC H264 codec info. Value: <b>dvrSmoothManifestH264Codec</b>

public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_PAUSE</u></a> DVR Property "dvrSmoothManifestLiveCanPause": used to determine is CanPause is enabled in smooth Manifest. Value: <b>dvrSmoothManifestLiveCanPause</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_SEEK</u></a> DVR Property "dvrSmoothManifestLiveCanSeek": used to determine is CanSeek is enabled in smooth Manifest. Value: <b>dvrSmoothManifestLiveCanSeek</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_MAJOR_VERSION</u></a> DVR Property "dvrSmoothManifestMajorVersion": used to determine Smooth manifest major version Value: <b>dvrSmoothManifestMajorVersion</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_MINOR_VERSION</u></a> DVR Property "dvrSmoothManifestMinorVersion": used to determine Smooth manifest major version Value: <b>dvrSmoothManifestMinorVersion</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_PAUSE</u></a> DVR Property "dvrSmoothManifestRecordedCanPause": used to determine is CanPause is enabled in smooth Manifest. Value: <b>dvrSmoothManifestRecordedCanPause</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_SEEK</u></a> DVR Property "dvrSmoothManifestRecordedCanSeek": used to determine is CanSeek is enabled in smooth Manifest. Value: <b>dvrSmoothManifestRecordedCanSeek</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_RECORDED_SPECIFY_DURATION</u></a> DVR Property "dvrSmoothManifestRecordedSpecifyDuration": used to determine if duration is specified. Value: <b>dvrSmoothManifestRecordedSpecifyDuration</b>
public static final	<a href="#"><u>PROPERTY_SMOOTH_MANIFEST_VERBOSE_DURATION</u></a> DVR Property "dvrSmoothManifestVerboseDuration": used to force Smooth Manifest to include durations for each record Value: <b>dvrSmoothManifestVerboseDuration</b>
public static final	<a href="#"><u>PROPERTY_START_RECORDING_ON_STARTUP</u></a> DVR Property "startRecordingOnStartup": for determining if DVR recorder should start recording immediately. Value: <b>startRecordingOnStartup</b>
public static final	<a href="#"><u>PROPERTY_STORAGE_DIRECTORY</u></a> DVR Property "dvrStorageDirectory": for overriding the DVR storage directory location Typically this is defined application-wide in Application.xml under Application/DVR/StorageDirectory. Value: <b>dvrStorageDirectory</b>
public static final	<a href="#"><u>PROPERTY_STREAM_DATA</u></a> Value: <b>dvrStreamRecordedData</b>
public static final	<a href="#"><u>PROPERTY_TEXT_READER_CLASS</u></a> DVR Property "dvrTextReaderClass": for controlling the class responsible for reading DVR text files. Value: <b>dvrTextReaderClass</b>

public static final	<a href="#">PROPERTY_TEXT_WRITER_CLASS</a> DVR Property "dvrTextWriterClass": for controlling the class responsible for writing DVR text files. Value: <b>dvrTextWriterClass</b>
public static final	<a href="#">PROPERTY_WINDOW_DURATION</a> DVR Property "dvrWindowDuration": for specifying the DVR window duration, in seconds. Value: <b>dvrWindowDuration</b>
public static final	<a href="#">SANJOSE_F4M_STREAMINGTYPE_STREAMING</a> Constant for San Jose streaming type "streaming" Value: <b>streaming</b>
public static final	<a href="#">SANJOSE_F4M_STREAMTYPE_DVR</a> Constant for San Jose stream type "dvr". Value: <b>dvr</b>
public static final	<a href="#">SANJOSE_F4M_STREAMTYPE_LIVE</a> Constant for San Jose stream type "live". Value: <b>live</b>
public static final	<a href="#">SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED</a> Constant for San Jose stream type "liveOrRecorded". Value: <b>liveOrRecorded</b>
public static final	<a href="#">SANJOSE_F4M_STREAMTYPE_RECORDED</a> Constant for San Jose stream type "recorded". Value: <b>recorded</b>
public static final	<a href="#">SANJOSE_F4M_VERSION_1_0</a> Constant for San Jose f4m version "1.0". Value: <b>1.0</b>
public static final	<a href="#">SANJOSE_F4M_VERSION_2_0</a> Constant for San Jose f4m version "2.0". Value: <b>2.0</b>

Fields inherited from interface `com.wowza.wms.dvr.IDvrPrivateConstants`

```

CHUNK_FILENAME_FORMAT_AUDIO,CHUNK_FILENAME_FORMAT_DATA,CHUNK_FILENAME_FORMAT_METADATA,
CHUNK_FILENAME_FORMAT_VIDEO,CHUNK_FOLDER_FORMAT,DEFAULT_PROPERTY_AUDIO_GROUP_COUNT,
DEFAULT_PROPERTY_MANIFEST_PURGE_SIZE,DEFAULT_PROPERTY_MAX_ALLOWABLE_CHUNK_DURATION,
DEFAULT_PROPERTY_MAX_SAVE_HOLDER_SIZE,DEFAULT_PROPERTY_MINIMUM_AVAILABLE_CHUNKS,
DEFAULT_PROPERTY_PURGE_CONTROL_CLASS,
DEFAULT_PROPERTY_RECALC_DURATION_MAX_AV_DIFFERENCE_TRIGGER,
DEFAULT_PROPERTY_RECALC_DURATION_TRIGGER_SIZE,DEFAULT_PROPERTY_STREAM_IDLE_TIMEOUT,
DEFAULT_PROPERTY_STREAM_STARTUP_TIMEOUT,DEFAULT_PROPERTY_UTC_ALIGN_TO_AUDIO,
DEFAULT_PROPERTY_UTC_USE_WOWZA_PACKET_ARRIVAL,DEFAULT_PROPERTY_WAIT_FOR_CODEC_TIME,
PROPERTY_AUDIO_GROUP_COUNT,PROPERTY_DEBUG_MBR_RESOLVER,
PROPERTY_DEBUG_MBR_RESOLVER_GAP_DETAILS,
PROPERTY_DEBUG_MBR_RESOLVER_INTERSECTION_DETAILS,PROPERTY_INTERCEPTOR_CHUNK_DELEGATE,
PROPERTY_MANIFEST_PURGE_CACHE_SIZE,PROPERTY_MAX_ALLOWABLE_CHUNK_DURATION,
PROPERTY_MAX_SAVE_HOLDER_SIZE,PROPERTY_MBR_USE_SIMPLEALIGNMENT,
PROPERTY_MINIMUM_AVAILABLE_CHUNKS,PROPERTY_PURGE_CONTROL_CLASS,
PROPERTY_RECALC_DURATION_MAX_AV_DIFFERENCE_TRIGGER,
PROPERTY_RECALC_DURATION_TRIGGER_SIZE,PROPERTY_UTC_ALIGN_TO_AUDIO,
PROPERTY_UTC_DELEGATE_CLASS,PROPERTY_UTC_USE_WOWZA_PACKET_ARRIVAL,
PROPERTY_VERIFY_CHUNK_EXISTENCE_ON_MANIFEST_LOAD,PROPERTY_WAIT_FOR_CODEC_TIME

```

## Fields

### DVR\_STREAMING\_PACKETIZER\_ID

```
public static final java.lang.String DVR_STREAMING_PACKETIZER_ID
```

The default DVR streaming packetizer ID: "dvrstreamingpacketizer".

See DVR.xml and Application.xml.

Constant value: **dvrstreamingpacketizer**

### DVR\_REPEATER\_PACKETIZER\_ID

```
public static final java.lang.String DVR_REPEATER_PACKETIZER_ID
```

The default DVR streaming repeater ID: "dvrstreamingrepeater".

See DVR.xml and Application.xml.

Constant value: **dvrstreamingrepeater**

### DVR\_DEFAULT\_RECORDER\_ID

```
public static final java.lang.String DVR_DEFAULT_RECORDER_ID
```

The default DVR recorder ID: "dvrrecorder".

See DVR.xml and Application.xml.

Constant value: **dvrrecorder**

### DVR\_DEFAULT\_FILESTORE

```
public static final java.lang.String DVR_DEFAULT_FILESTORE
```

The default DVR store ID: "dvrfilestorage".

See DVR.xml and Application.xml.

Constant value: **dvrfilestorage**

## MEDIACACHE\_PREFIX

```
public static final java.lang.String MEDIACACHE_PREFIX
```

The MediaCache prefix for dvr repeater

See MediaCache.xml

Constant value: **dvrorigin**

---

## PROPERTY\_CHUNK\_GROUPING\_SECONDS

```
public static final java.lang.String PROPERTY_CHUNK_GROUPING_SECONDS
```

DVR Property "dvrChunkGroupingSeconds": for determining how many seconds of DVR are stored in each stores sub-folder.

The directory naming convention is HHHH\_MM\_SS with H = hours, M = minutes, S = seconds. Using the defaults, first directory would be named 0000\_00\_00 and the second directory would be named 0000\_10\_00, etc.

Valid values are integers greater than 60. Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrChunkGroupingSeconds**

See Also:

[DEFAULT\\_PROPERTY\\_CHUNK\\_GROUPING\\_SECONDS](#)

---

## DEFAULT\_PROPERTY\_CHUNK\_GROUPING\_SECONDS

```
public static final int DEFAULT_PROPERTY_CHUNK_GROUPING_SECONDS
```

Default value for DVR Property "dvrChunkGroupingSeconds".

Default value is 600 seconds (10 minutes).

Constant value: **600**

See Also:

[PROPERTY\\_CHUNK\\_GROUPING\\_SECONDS](#)

---

## PROPERTY\_APPEND\_DISCONTINUITY\_DELTA

```
public static final java.lang.String PROPERTY_APPEND_DISCONTINUITY_DELTA
```

DVR Property "dvrAppendDiscontinuityDelta": for specifying how many milliseconds of empty space are put between individual recordings that when in append mode.

Valid values are integers greater than or equal to 0. Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrAppendDiscontinuityDelta**

See Also:

[DEFAULT\\_PROPERTY\\_APPEND\\_DISCONTINUITY\\_DELTA](#)

---

## DEFAULT\_PROPERTY\_APPEND\_DISCONTINUITY\_DELTA

```
public static final int DEFAULT_PROPERTY_APPEND_DISCONTINUITY_DELTA
```

Default value for DVR Property "dvrAppendDiscontinuityDelta".

Default value is 0.

Constant value: **0**

See Also:

---

(continued from last page)

[PROPERTY\\_APPEND\\_DISCONTINUITY\\_DELTA](#)

---

## PROPERTY\_WINDOW\_DURATION

```
public static final java.lang.String PROPERTY_WINDOW_DURATION
```

DVR Property "dvrWindowDuration": for specifying the DVR window duration, in seconds.

Typically this is defined application-wide in Application.xml under Application/DVR/WindowDuration. However, to override this on a per stream basis, the property may be set on the IDvrStreamManager after creation and before initialization. Valid values are integers greater than or equal to 0. Add the property to Application/DVR/Properties section of Application.xml. The default is 0, meaning the window size is unlimited.

Constant value: **dvrWindowDuration**

See Also:

[DVR\\_WINDOW\\_DURATION\\_UNLIMITED](#)

---

## DVR\_WINDOW\_DURATION\_UNLIMITED

```
public static final int DVR_WINDOW_DURATION_UNLIMITED
```

Constant value: **0**

---

## PROPERTY\_STORAGE\_DIRECTORY

```
public static final java.lang.String PROPERTY_STORAGE_DIRECTORY
```

DVR Property "dvrStorageDirectory": for overriding the DVR storage directory location. Typically this is defined application-wide in Application.xml under Application/DVR/StorageDirectory. However, to override this on a per stream basis, the property may be set on the IDvrStreamManager after creation and before initialization.

Constant value: **dvrStorageDirectory**

See Also:

[DEFAULT\\_PROPERTY\\_STORAGE\\_DIRECTORY](#)

---

## DEFAULT\_PROPERTY\_STORAGE\_DIRECTORY

```
public static final java.lang.String DEFAULT_PROPERTY_STORAGE_DIRECTORY
```

Default value for DVR Property "dvrStorageDirectory".

Default value is "\${com.wowza.wms.context.VHostConfigHome}/dvr".

Constant value: **\${com.wowza.wms.context.VHostConfigHome}/dvr**

See Also:

[PROPERTY\\_STORAGE\\_DIRECTORY](#)

---

## PROPERTY\_ARCHIVE\_STRATEGY

```
public static final java.lang.String PROPERTY_ARCHIVE_STRATEGY
```

DVR Property "dvrArchiveStrategy": for specifying the DVR archive strategy.

Typically this is defined application-wide in Application.xml under Application/DVR/ArchiveStrategy. However, to override this on a per stream basis, the property may be set on the IDvrStreamManager after creation and before initialization. Valid values are:

Constant value: **dvrArchiveStrategy**

See Also:

[ARCHIVE\\_STRATEGY\\_APPEND](#)



(continued from last page)

[ARCHIVE\\_STRATEGY\\_VERSION](#)[ARCHIVE\\_STRATEGY\\_APPEND](#)

---

## ARCHIVE\_STRATEGY\_DELETE

```
public static final java.lang.String ARCHIVE_STRATEGY_DELETE
```

Constant value: **delete**

---

## ARCHIVE\_STRATEGY\_VERSION

```
public static final java.lang.String ARCHIVE_STRATEGY_VERSION
```

Constant value: **version**

---

## ARCHIVE\_STRATEGY\_APPEND

```
public static final java.lang.String ARCHIVE_STRATEGY_APPEND
```

Constant value: **append**

---

## PROPERTY\_CHUNK\_READER\_CLASS

```
public static final java.lang.String PROPERTY_CHUNK_READER_CLASS
```

DVR Property "dvrChunkReaderClass": for controlling the class responsible for reading DVR Chunks.

The class must implement IDvrChunkReader

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrChunkReaderClass**

### See Also:

`com.wowza.wms.dvr.io.IDvrChunkReader`

[DEFAULT\\_PROPERTY\\_CHUNK\\_READER\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_CHUNK\_READER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_CHUNK_READER_CLASS
```

Default value for DVR Property "dvrChunkReaderClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrFileChunkReader".

Constant value: **com.wowza.wms.dvr.impl.io.DvrFileChunkReader**

### See Also:

[PROPERTY\\_CHUNK\\_READER\\_CLASS](#)

---

## PROPERTY\_CHUNK\_WRITER\_CLASS

```
public static final java.lang.String PROPERTY_CHUNK_WRITER_CLASS
```

DVR Property "dvrChunkWriterClass": for controlling the class responsible for writing DVR Chunks.

The class must implement IDvrChunkWriter

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrChunkWriterClass**

---

(continued from last page)

**See Also:**

com.wowza.wms.dvr.io.IDvrChunkWriter  
[DEFAULT\\_PROPERTY\\_CHUNK\\_WRITER\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_CHUNK\_WRITER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_CHUNK_WRITER_CLASS
```

Default value for DVR Property "dvrChunkWriterClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrFileChunkWriter".

Constant value: **com.wowza.wms.dvr.impl.io.DvrFileChunkWriter**

**See Also:**

[PROPERTY\\_CHUNK\\_WRITER\\_CLASS](#)

---

## PROPERTY\_FILE\_SYSTEM\_CLASS

```
public static final java.lang.String PROPERTY_FILE_SYSTEM_CLASS
```

DVR Property "dvrFileSystemClass": for controlling the class responsible for managing the DVR File System.

The class must implement com.wowza.wms.dvr.io.IDvrFileSystem and may sub-class com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrFileSystemClass**

**See Also:**

com.wowza.wms.dvr.io.IDvrFileSystem  
[DEFAULT\\_PROPERTY\\_FILE\\_SYSTEM\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_FILE\_SYSTEM\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_FILE_SYSTEM_CLASS
```

Default value for DVR Property "dvrFileSystemClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem".

Constant value: **com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem**

**See Also:**

[PROPERTY\\_FILE\\_SYSTEM\\_CLASS](#)

---

## PROPERTY\_MANIFEST\_PERSISTER\_CLASS

```
public static final java.lang.String PROPERTY_MANIFEST_PERSISTER_CLASS
```

DVR Property "dvrManifestPersisterClass": for controlling the class responsible for persisting the manifest files.

The class must implement com.wowza.wms.dvr.io.IDvrManifestPersister

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrManifestPersisterClass**

**See Also:**

com.wowza.wms.dvr.io.IDvrManifestPersister  
[DEFAULT\\_PROPERTY\\_MANIFEST\\_PERSISTER\\_CLASS](#)

(continued from last page)

---

## DEFAULT\_PROPERTY\_MANIFEST\_PERSISTER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_MANIFEST_PERSISTER_CLASS
```

Default value for DVR Property "dvrManifestPersisterClass".

Default value is "com.wowza.wms.dvr.impl.DvrManifestPersister".

Constant value: **com.wowza.wms.dvr.impl.DvrManifestPersister**

See Also:

[PROPERTY\\_MANIFEST\\_PERSISTER\\_CLASS](#)

---

## PROPERTY\_CHUNK\_CACHE\_CLASS

```
public static final java.lang.String PROPERTY_CHUNK_CACHE_CLASS
```

DVR Property "dvrChunkMemoryCacheClass": for controlling the class responsible for caching DVR chunks in memory.

The class must implement [IDvrChunkMemoryCache](#) and may sub-class `com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache`

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrChunkMemoryCacheClass**

See Also:

[IDvrChunkMemoryCache](#)

[DEFAULT\\_PROPERTY\\_CHUNK\\_CACHE\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_CHUNK\_CACHE\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_CHUNK_CACHE_CLASS
```

Default value for DVR Property "dvrChunkMemoryCacheClass".

Default value is "com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache".

Constant value: **com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache**

See Also:

[PROPERTY\\_CHUNK\\_CACHE\\_CLASS](#)

---

## PROPERTY\_RECORDINGS\_LOADER\_CLASS

```
public static final java.lang.String PROPERTY_RECORDINGS_LOADER_CLASS
```

DVR Property "dvrRecordingsLoaderClass": for controlling the class responsible for loading DVR recordings.

The class must implement [IDvrRecordingsLoader](#)

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrRecordingsLoaderClass**

See Also:

[IDvrRecordingsLoader](#)

[DEFAULT\\_PROPERTY\\_RECORDINGS\\_LOADER\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_RECORDINGS\_LOADER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_RECORDINGS_LOADER_CLASS
```

Default value for DVR Property "dvrRecordingsLoaderClass".

Default value is "com.wowza.wms.dvr.DvrRecordingsLoader".

---

(continued from last page)

Constant value: **com.wowza.wms.dvr.DvrRecordingsLoader**

See Also:

[PROPERTY\\_RECORDINGS\\_LOADER\\_CLASS](#)

---

## PROPERTY\_TEXT\_WRITER\_CLASS

```
public static final java.lang.String PROPERTY_TEXT_WRITER_CLASS
```

DVR Property "dvrTextWriterClass": for controlling the class responsible for writing DVR text files.

The class must implement [IDvrTextWriter](#)

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrTextWriterClass**

See Also:

[IDvrTextWriter](#)

[DEFAULT\\_PROPERTY\\_TEXT\\_WRITER\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_TEXT\_WRITER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_TEXT_WRITER_CLASS
```

Default value for DVR Property "dvrTextWriterClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrTextFileWriter".

Constant value: **com.wowza.wms.dvr.impl.io.DvrTextFileWriter**

See Also:

[PROPERTY\\_TEXT\\_WRITER\\_CLASS](#)

---

## PROPERTY\_TEXT\_READER\_CLASS

```
public static final java.lang.String PROPERTY_TEXT_READER_CLASS
```

DVR Property "dvrTextReaderClass": for controlling the class responsible for reading DVR text files.

The class must implement [IDvrTextReader](#)

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrTextReaderClass**

See Also:

[IDvrTextReader](#)

[DEFAULT\\_PROPERTY\\_TEXT\\_READER\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_TEXT\_READER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_TEXT_READER_CLASS
```

Default value for DVR Property "dvrTextReaderClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrTextFileReader".

Constant value: **com.wowza.wms.dvr.impl.io.DvrTextFileReader**

See Also:

[PROPERTY\\_TEXT\\_READER\\_CLASS](#)

---

(continued from last page)

---

## PROPERTY\_ALLOWABLE\_AV\_PACKET\_DELTA

```
public static final java.lang.String PROPERTY_ALLOWABLE_AV_PACKET_DELTA
```

DVR Property "dvrAllowableAVPacketDelta": for specifying how much audio and video packets may diverge before triggering an error.

Wowza nDVR expects the incoming audio and video to be aligned. Through this parameter, Wowza nDVR will try to compensate for out of alignment issues, but it cannot resolve them. This setting safeguards against audio and data video packets that are not closely aligned. The units are in ms. The default value is 2000 ms. If audio and video are out of alignment by more than this value, the audio and video chunks will be ignored in an attempt to get the streams back into alignment. If you already have an out of alignment issue, increasing the default value is likely to cause more problems. Increasing this value will increase the number of chunks not recorded which may cause the overall quality to be unacceptable.

Add the property to Application/DVR/Properties section of Application.xml.  
Constant value: **dvrAllowableAVPacketDelta**

See Also:

[DEFAULT\\_PROPERTY\\_ALLOWABLE\\_AV\\_PACKET\\_DELTA](#)

---

## DEFAULT\_PROPERTY\_ALLOWABLE\_AV\_PACKET\_DELTA

```
public static final int DEFAULT_PROPERTY_ALLOWABLE_AV_PACKET_DELTA
```

Default value for DVR Property "dvrAllowableAVPacketDelta".

Default value is 2000 ms.  
Constant value: **2000**

See Also:

[PROPERTY\\_ALLOWABLE\\_AV\\_PACKET\\_DELTA](#)

---

## PROPERTY\_PACKET\_DELTA\_TO\_RESET\_TIME

```
public static final java.lang.String PROPERTY_PACKET_DELTA_TO_RESET_TIME
```

DVR Property "dvrResetTimePacketDelta": for controlling how much Chunk start times must diverge from last chunk's end time before the DVR time gets reset.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrResetTimePacketDelta**

See Also:

[DEFAULT\\_PROPERTY\\_PACKET\\_DELTA\\_TO\\_RESET\\_TIME](#)

---

## DEFAULT\_PROPERTY\_PACKET\_DELTA\_TO\_RESET\_TIME

```
public static final int DEFAULT_PROPERTY_PACKET_DELTA_TO_RESET_TIME
```

Default value for DVR Property "dvrResetTimePacketDelta".

Default value is 200 ms.  
Constant value: **200**

See Also:

[PROPERTY\\_PACKET\\_DELTA\\_TO\\_RESET\\_TIME](#)

---

## PROPERTY\_PACKET\_DELTA\_TO\_NOTIFY

```
public static final java.lang.String PROPERTY_PACKET_DELTA_TO_NOTIFY
```

(continued from last page)

Constant value: **dvrPacketDeltaToNotify**

---

## DEFAULT\_PROPERTY\_PACKET\_DELTA\_TO\_NOTIFY

```
public static final int DEFAULT_PROPERTY_PACKET_DELTA_TO_NOTIFY
```

Constant value: **200**

---

## PROPERTY\_RECORD\_DATA

```
public static final java.lang.String PROPERTY_RECORD_DATA
```

DVR Property "recordData": for determining if data should be recorded.

Set property to: true to record data of incoming stream. Default is true. Set property to: false to ignore data packets during recording.

Constant value: **recordData**

---

## PROPERTY\_RECORD\_VIDEO

```
public static final java.lang.String PROPERTY_RECORD_VIDEO
```

DVR Property "recordVideo": for determining if video should be recorded.

Set property to: true to record video of incoming stream. Default is true. Set property to: false to ignore video packets during recording. Either recordVideo or recordAudio property must be set to: true

Constant value: **recordVideo**

---

## PROPERTY\_RECORD\_AUDIO

```
public static final java.lang.String PROPERTY_RECORD_AUDIO
```

DVR Property "recordAudio": for determining if audio should be recorded.

Set property to: true to record audio of incoming stream. Default is true. Set property to: false to ignore audio packets during recording. Either recordVideo or recordAudio property must be set to: true

Constant value: **recordAudio**

---

## PROPERTY\_START\_RECORDING\_ON\_STARTUP

```
public static final java.lang.String PROPERTY_START_RECORDING_ON_STARTUP
```

DVR Property "startRecordingOnStartup": for determining if DVR recorder should start recording immediately.

Set property to: true (default) to start recording immediately when stream is detected. Set property to: false to init the DVR recorder but to not start recording immediately when stream starts.

Constant value: **startRecordingOnStartup**

---

## PROPERTY\_AUDIO\_ONLY\_CHUNK\_TARGET\_DURATION

```
public static final java.lang.String PROPERTY_AUDIO_ONLY_CHUNK_TARGET_DURATION
```

DVR Property "dvrAudioOnlyChunkTargetDuration": for target duration when recording audio-only.

Applies to recording an audio-only stream and is the target chunk duration. The unit is in ms. The default value is 2000 ms. This setting is ignored if the stream contains video and audio, in which case the keyframe determines the chunk size.

Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrAudioOnlyChunkTargetDuration**

**See Also:**

(continued from last page)

[DEFAULT\\_PROPERTY\\_AUDIO\\_ONLY\\_CHUNK\\_TARGET\\_DURATION](#)

---

## DEFAULT\_PROPERTY\_AUDIO\_ONLY\_CHUNK\_TARGET\_DURATION

```
public static final int DEFAULT_PROPERTY_AUDIO_ONLY_CHUNK_TARGET_DURATION
```

Default value for DVR Property "dvrAudioOnlyChunkTargetDuration".

Default value is 2000 ms.

Constant value: **2000**

See Also:

[PROPERTY\\_AUDIO\\_ONLY\\_CHUNK\\_TARGET\\_DURATION](#)

---

## PROPERTY\_PACKET\_SORT\_TIME

```
public static final java.lang.String PROPERTY_PACKET_SORT_TIME
```

DVR Property "dvrPacketSortTime": for sorting incoming packets. Specified in milliseconds.

Valid values are a integer greater than equal to 0. Zero means no sorting occurs. Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrPacketSortTime**

See Also:

[DEFAULT\\_PROPERTY\\_PACKET\\_SORT\\_TIME](#)

---

## DEFAULT\_PROPERTY\_PACKET\_SORT\_TIME

```
public static final int DEFAULT_PROPERTY_PACKET_SORT_TIME
```

Default value for DVR Property "dvrPacketSortTime".

Default value is 0 ms (i.e. no sorting).

Constant value: **0**

See Also:

[PROPERTY\\_PACKET\\_SORT\\_TIME](#)

---

## PROPERTY\_BREAK\_ON\_PTS

```
public static final java.lang.String PROPERTY_BREAK_ON_PTS
```

DVR Property "dvrChunkBreakOnPTS": for specifying that DVR should be broken on PTS.

Valid values are "true" or "false" Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrChunkBreakOnPTS**

See Also:

[DEFAULT\\_PROPERTY\\_BREAK\\_ON\\_PTS](#)

---

## DEFAULT\_PROPERTY\_BREAK\_ON\_PTS

```
public static final boolean DEFAULT_PROPERTY_BREAK_ON_PTS
```

Default value for DVR Property "dvrChunkBreakOnPTS".

Default value is true.

Constant value: **true**

See Also:

(continued from last page)

[PROPERTY\\_BREAK\\_ON\\_PTS](#)

---

## PROPERTY\_REPEATER\_SHARED\_SECRET

```
public static final java.lang.String PROPERTY_REPEATER_SHARED_SECRET
```

DVR Property "dvrEncryptionSharedSecret": for encryption shared secret between origins and edges. In Origin-Edge scenarios when Wowza is using encryption, a shared secret must be defined for both origin and edges to encrypt the information sent between origin and edge so that encryption information is not revealed.

A String values.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrEncryptionSharedSecret**

---

## PROPERTY\_REPEATER\_HEARTBEAT\_DURATION

```
public static final java.lang.String PROPERTY_REPEATER_HEARTBEAT_DURATION
```

DVR Property "dvrRepeaterHeartbeatDuration": for time in ms that origin pings edges

A Integer Value.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrRepeaterHeartbeatDuration**

---

## DEFAULT\_PROPERTY\_REPEATER\_HEARTBEAT\_DURATION

```
public static final int DEFAULT_PROPERTY_REPEATER_HEARTBEAT_DURATION
```

Constant value: **4000**

---

## PROPERTY\_CHUNK\_DURATION\_MINIMUM

```
public static final java.lang.String PROPERTY_CHUNK_DURATION_MINIMUM
```

DVR Property "dvrChunkDurationMinimum": for minimum chunk duration, in milliseconds.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrChunkDurationMinimum**

See Also:

[DEFAULT\\_PROPERTY\\_CHUNK\\_DURATION\\_MINIMUM](#)

---

## DEFAULT\_PROPERTY\_CHUNK\_DURATION\_MINIMUM

```
public static final int DEFAULT_PROPERTY_CHUNK_DURATION_MINIMUM
```

Default value for DVR Property "dvrChunkDurationMinimum".

Default value is 1500 ms.  
Constant value: **1500**

See Also:

[PROPERTY\\_CHUNK\\_DURATION\\_MINIMUM](#)

---

## PROPERTY\_CHUNK\_MEMORY\_CACHESIZE

```
public static final java.lang.String PROPERTY_CHUNK_MEMORY_CACHESIZE
```



---

(continued from last page)

DVR Property "chunkMemoryCacheSize": used by DvrDefaultChunkMemoryCache to set number of chunks stored in DVR in-memory cache.

Default value is [DEFAULT\\_CHUNK\\_MEMORY\\_CACHESIZE](#)

Add this to Application/DVR/Properties section of Application.xml  
Constant value: **chunkMemoryCacheSize**

---

## DEFAULT\_CHUNK\_MEMORY\_CACHESIZE

```
public static final int DEFAULT_CHUNK_MEMORY_CACHESIZE
```

Default value for DVR Property "chunkMemoryCacheSize".

Default value is 10 chunks.  
Constant value: **10**

See Also:

[PROPERTY\\_CHUNK\\_MEMORY\\_CACHESIZE](#)

---

## PROPERTY\_MBR\_USE\_UTC\_FOR\_ALIGNMENT

```
public static final java.lang.String PROPERTY_MBR_USE_UTC_FOR_ALIGNMENT
```

DVR Property "dvrMbrUseUtcForAlignment": when doing mbr alignment use utc time for alignment

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMbrUseUtcForAlignment**

---

## PROPERTY\_MBR\_MINIMUM\_PACKETTIME\_GAP\_SIZE

```
public static final java.lang.String PROPERTY_MBR_MINIMUM_PACKETTIME_GAP_SIZE
```

DVR Property "dvrMbrMinimumPacketTimeGapSize": when doing mbr alignment gaps smaller than this are ignored.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMbrMinimumPacketTimeGapSize**

See Also:

[DEFAULT\\_PROPERTY\\_MBR\\_MINIMUM\\_PACKETTIME\\_GAP\\_SIZE](#)

---

## PROPERTY\_MBR\_ALTERNATIVE\_MATCH\_DELTA

```
public static final java.lang.String PROPERTY_MBR_ALTERNATIVE_MATCH_DELTA
```

DVR Property "dvrMbrAlternateMatchDelta": when finding alternative for a MBR gap, an alternate is considered a match is within this many ms of the gap in question.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMbrAlternateMatchDelta**

See Also:

[DEFAULT\\_PROPERTY\\_MBR\\_ALTERNATIVE\\_MATCH\\_DELTA](#)

---

## DEFAULT\_PROPERTY\_MBR\_ALTERNATIVE\_MATCH\_DELTA

```
public static final int DEFAULT_PROPERTY_MBR_ALTERNATIVE_MATCH_DELTA
```

Default value for DVR Property "dvrMbrAlternateMatchDelta".

Default value is 1000 ms.  
Constant value: **1000**

---

(continued from last page)

See Also:

[PROPERTY\\_MBR\\_ALTERNATIVE\\_MATCH\\_DELTA](#)

---

## PROPERTY\_PACKET\_DURATION\_MAXIMUM

```
public static final java.lang.String PROPERTY_PACKET_DURATION_MAXIMUM
```

DVR Property "dvrPacketDurationMaximum": for maximum packet duration, in milliseconds.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrPacketDurationMaximum**

See Also:

[DEFAULT\\_PROPERTY\\_PACKET\\_DURATION\\_MAXIMUM](#)

---

## DEFAULT\_PROPERTY\_PACKET\_DURATION\_MAXIMUM

```
public static final int DEFAULT_PROPERTY_PACKET_DURATION_MAXIMUM
```

Default value for DVR Property "dvrChunkDurationMinimum".

Default value is 5000 ms.  
Constant value: **5000**

See Also:

[PROPERTY\\_PACKET\\_DURATION\\_MAXIMUM](#)

---

## DEFAULT\_PROPERTY\_MBR\_MINIMUM\_PACKETTIME\_GAP\_SIZE

```
public static final int DEFAULT_PROPERTY_MBR_MINIMUM_PACKETTIME_GAP_SIZE
```

Default value for DVR Property "dvrMbrMinimumPacketTimeGapSize".

Default value is 100 ms.  
Constant value: **100**

See Also:

[PROPERTY\\_MBR\\_MINIMUM\\_PACKETTIME\\_GAP\\_SIZE](#)

---

## PROPERTY\_MBR\_MINIMUM\_UTCTIME\_GAP\_SIZE

```
public static final java.lang.String PROPERTY_MBR_MINIMUM_UTCTIME_GAP_SIZE
```

DVR Property "dvrMbrMinimumUtcTimeGapSize": when doing mbr alignment gaps smaller than this are ignored.

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMbrMinimumUtcTimeGapSize**

See Also:

[DEFAULT\\_PROPERTY\\_MBR\\_MINIMUM\\_UTCTIME\\_GAP\\_SIZE](#)

---

## DEFAULT\_PROPERTY\_MBR\_MINIMUM\_UTCTIME\_GAP\_SIZE

```
public static final int DEFAULT_PROPERTY_MBR_MINIMUM_UTCTIME_GAP_SIZE
```

Default value for DVR Property "dvrMbrMinimumPacketTimeGapSize".

Default value is 750 ms.  
Constant value: **750**

(continued from last page)

See Also:

[PROPERTY\\_MBR\\_MINIMUM\\_UTCTIME\\_GAP\\_SIZE](#)

---

## PROPERTY\_MAX\_RECORDING\_LENGTH

```
public static final java.lang.String PROPERTY_MAX_RECORDING_LENGTH
```

DVR Property "dvrMaximumRecordingLength": The maximum recording length in seconds. Recording stops when it reaches this value.

Add the property to Application/DVR/Properties section of Application.xml A value of zero means no maximum recording length is enforced. If used in conjunction with DVRWindow, should be slightly larger (1-2%) than DVRWindow.  
Constant value: **dvrMaximumRecordingLength**

See Also:

[DEFAULT\\_PROPERTY\\_MAX\\_RECORDING\\_LENGTH](#)

---

## DEFAULT\_PROPERTY\_MAX\_RECORDING\_LENGTH

```
public static final long DEFAULT_PROPERTY_MAX_RECORDING_LENGTH
```

Default value for DVR Property "dvrMaximumRecordingLength".

Default value is 108000 (30 hours)  
Constant value: **108000**

See Also:

[PROPERTY\\_MAX\\_RECORDING\\_LENGTH](#)

---

## PROPERTY\_MEDIACACHE\_ENABLED

```
public static final java.lang.String PROPERTY_MEDIACACHE_ENABLED
```

DVR Property "dvrMediaCacheEnabled"

Add the property to Application/DVR/Properties section of Application.xml Default is false.  
Constant value: **dvrMediaCacheEnabled**

---

## PROPERTY\_MEDIACACHE\_READER\_CLASS

```
public static final java.lang.String PROPERTY_MEDIACACHE_READER_CLASS
```

DVR Property "dvrMediaCacheReaderClass"

Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMediaCacheReaderClass**

See Also:

[DEFAULT\\_PROPERTY\\_MEDIACACHE\\_READER\\_CLASS](#)

---

## DEFAULT\_PROPERTY\_MEDIACACHE\_READER\_CLASS

```
public static final java.lang.String DEFAULT_PROPERTY_MEDIACACHE_READER_CLASS
```

Default value for DVR Property "dvrMediaCacheReaderClass".  
Constant value: **com.wowza.wms.plugin.mediache.impl.MediaCacheRandomAccessReader**

See Also:

[PROPERTY\\_MEDIACACHE\\_READER\\_CLASS](#)

(continued from last page)

---

## PROPERTY\_DEBUG\_LOG\_INVALID\_CHUNK\_DETAILS

```
public static final java.lang.String PROPERTY_DEBUG_LOG_INVALID_CHUNK_DETAILS
```

DVR Property "dvrLogInvalidChunkDetails": to control detailed logging information of DVR invalid chunks

The default is false, meaning do not log invalid chunks. Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrLogInvalidChunkDetails**

See Also:

[PROPERTY\\_DEBUG\\_MAX\\_INVALID\\_CHUNKS\\_LOGGED](#)

---

## PROPERTY\_DEBUG\_LOG\_INVALID\_CHUNK\_MATCHER

```
public static final java.lang.String PROPERTY_DEBUG_LOG_INVALID_CHUNK_MATCHER
```

DVR Property "dvrLogInvalidChunkMatcher": for matching stream names that will log chunk packets

Only affects logging if [PROPERTY\\_DEBUG\\_MAX\\_INVALID\\_CHUNKS\\_LOGGED](#) is true.

Constant value: **dvrLogInvalidChunkMatcher**

See Also:

[PROPERTY\\_DEBUG\\_MAX\\_INVALID\\_CHUNKS\\_LOGGED](#)

---

## PROPERTY\_DEBUG\_MAX\_INVALID\_CHUNKS\_LOGGED

```
public static final java.lang.String PROPERTY_DEBUG_MAX_INVALID_CHUNKS_LOGGED
```

DVR Property "dvrMaxInvalidChunksLogged": for controlling maximum number of invalid DVR chunks logged.

The default is 10. Logging only occurs if property [PROPERTY\\_DEBUG\\_LOG\\_INVALID\\_CHUNK\\_DETAILS](#) is true. Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrMaxInvalidChunksLogged**

See Also:

[DEFAULT\\_PROPERTY\\_DEBUG\\_MAX\\_INVALID\\_CHUNKS\\_LOGGED](#)

[PROPERTY\\_DEBUG\\_LOG\\_INVALID\\_CHUNK\\_DETAILS](#)

---

## DEFAULT\_PROPERTY\_DEBUG\_MAX\_INVALID\_CHUNKS\_LOGGED

```
public static final int DEFAULT_PROPERTY_DEBUG_MAX_INVALID_CHUNKS_LOGGED
```

Default value for DVR Property "dvrMaxInvalidChunksLogged".

Default value is 10.

Constant value: **10**

See Also:

[PROPERTY\\_DEBUG\\_LOG\\_INVALID\\_CHUNK\\_DETAILS](#)

[PROPERTY\\_DEBUG\\_MAX\\_INVALID\\_CHUNKS\\_LOGGED](#)

---

## PROPERTY\_DEBUG\_LOG\_VALID\_CHUNK\_DETAILS

```
public static final java.lang.String PROPERTY_DEBUG_LOG_VALID_CHUNK_DETAILS
```

DVR Property "dvrLogValidChunkDetails": to control detailed logging information of DVR valid chunks

The default is false, meaning do not log valid chunks. Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrLogValidChunkDetails**

---

(continued from last page)

**See Also:**[PROPERTY\\_DEBUG\\_MAX\\_VALID\\_CHUNKS\\_LOGGED](#)

---

## PROPERTY\_DEBUG\_MAX\_VALID\_CHUNKS\_LOGGED

```
public static final java.lang.String PROPERTY_DEBUG_MAX_VALID_CHUNKS_LOGGED
```

DVR Property "dvrMaxValidChunksLogged": for controlling maximum number of valid DVR chunks logged.

The default is 10. Logging only occurs if property [PROPERTY\\_DEBUG\\_LOG\\_VALID\\_CHUNK\\_DETAILS](#) is true. Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMaxValidChunksLogged**

**See Also:**[DEFAULT\\_PROPERTY\\_DEBUG\\_MAX\\_VALID\\_CHUNKS\\_LOGGED](#)[PROPERTY\\_DEBUG\\_LOG\\_VALID\\_CHUNK\\_DETAILS](#)

---

## DEFAULT\_PROPERTY\_DEBUG\_MAX\_VALID\_CHUNKS\_LOGGED

```
public static final int DEFAULT_PROPERTY_DEBUG_MAX_VALID_CHUNKS_LOGGED
```

Default value for DVR Property "dvrMaxValidChunksLogged".

Default value is 10.  
Constant value: **10**

**See Also:**[PROPERTY\\_DEBUG\\_LOG\\_VALID\\_CHUNK\\_DETAILS](#)[PROPERTY\\_DEBUG\\_MAX\\_VALID\\_CHUNKS\\_LOGGED](#)

---

## PROPERTY\_DEBUG\_LOG\_VALID\_CHUNK\_MATCHER

```
public static final java.lang.String PROPERTY_DEBUG_LOG_VALID_CHUNK_MATCHER
```

DVR Property "dvrLogValidChunkMatcher": for matching stream names that will log chunk packets

Only affects logging if [PROPERTY\\_DEBUG\\_MAX\\_VALID\\_CHUNKS\\_LOGGED](#) is true.  
Constant value: **dvrLogValidChunkMatcher**

**See Also:**[PROPERTY\\_DEBUG\\_MAX\\_VALID\\_CHUNKS\\_LOGGED](#)

---

## PROPERTY\_DEBUG\_TOSSED\_HOLDERS

```
public static final java.lang.String PROPERTY_DEBUG_TOSSED_HOLDERS
```

DVR Property "dvrDebugTossedHolders": for turning on logging of packets that are being tossed.

Valid values are "true" or "false". Default is false.  
Constant value: **dvrDebugTossedHolders**

---

## PROPERTY\_DEBUG\_RAW\_PACKETS

```
public static final java.lang.String PROPERTY_DEBUG_RAW_PACKETS
```

DVR Property "dvrDebugRawPackets": for turning on logging of incoming raw packets.

Valid values are "true" or "false".  
Constant value: **dvrDebugRawPackets**

**See Also:**

(continued from last page)

---

[PROPERTY\\_DEBUG\\_MAXIMUM\\_RAW\\_PACKETS](#)

---

---

## DEFAULT\_PROPERTY\_DEBUG\_RAW\_PACKETS

```
public static final boolean DEFAULT_PROPERTY_DEBUG_RAW_PACKETS
```

Default value for DVR Property "dvrDebugRawPackets".

Default value is false.

Constant value: **false**

See Also:

[PROPERTY\\_DEBUG\\_RAW\\_PACKETS](#)

[PROPERTY\\_DEBUG\\_RAW\\_PACKETS\\_MATCHER](#)

---

## PROPERTY\_DEBUG\_RAW\_PACKETS\_MATCHER

```
public static final java.lang.String PROPERTY_DEBUG_RAW_PACKETS_MATCHER
```

DVR Property "dvrDebugRawPacketsMatcher": for matching stream names that will dump raw packet.

Only affects logging if [PROPERTY\\_DEBUG\\_RAW\\_PACKETS](#) is true.

Constant value: **dvrDebugRawPacketsMatcher**

See Also:

[PROPERTY\\_DEBUG\\_RAW\\_PACKETS](#)

---

## PROPERTY\_DEBUG\_MAXIMUM\_RAW\_PACKETS

```
public static final java.lang.String PROPERTY_DEBUG_MAXIMUM_RAW_PACKETS
```

DVR Property "dvrDebugMaximumRawPackets": for setting maximum number of logged raw packets.

Valid values is an integer. 0 means there is no limit.

Only affects logging if [PROPERTY\\_DEBUG\\_RAW\\_PACKETS](#) is true.

Constant value: **dvrDebugMaximumRawPackets**

See Also:

[PROPERTY\\_DEBUG\\_RAW\\_PACKETS](#)

---

## DEFAULT\_PROPERTY\_DEBUG\_MAX\_RAW\_PACKETS

```
public static final int DEFAULT_PROPERTY_DEBUG_MAX_RAW_PACKETS
```

Default value for DVR Property "dvrDebugMaximumRawPackets".

Default value is 200 log statements.

Constant value: **200**

See Also:

[PROPERTY\\_DEBUG\\_MAXIMUM\\_RAW\\_PACKETS](#)

---

## PROPERTY\_DEBUG\_STATE\_CHANGE

```
public static final java.lang.String PROPERTY_DEBUG_STATE_CHANGE
```

DVR Property "dvrDebugStateChange": for logging state changes of DVR store.

Constant value: **dvrDebugStateChange**

---

(continued from last page)

---

## PROPERTY\_DEBUG\_CHUNK\_RETRIEVALS

```
public static final java.lang.String PROPERTY_DEBUG_CHUNK_RETRIEVALS
```

DVR Property "dvrDebugChunkRetrievals": for logging each chunk retrieval  
Constant value: **dvrDebugChunkRetrievals**

---

## PROPERTY\_DEBUG\_FAILED\_CHUNK\_RETRIEVALS

```
public static final java.lang.String PROPERTY_DEBUG_FAILED_CHUNK_RETRIEVALS
```

DVR Property "dvrDebugFailedChunkRetrievals": for logging info about each failed chunk retrieval  
Constant value: **dvrDebugFailedChunkRetrievals**

---

## PROPERTY\_MAX\_CHUNK\_LOG

```
public static final java.lang.String PROPERTY_MAX_CHUNK_LOG
```

DVR Property "dvrMaxChunkLogCount": for maximum number of DVR chunks to log.

Maximum number of chunks to log recording information about in the wowzamedia\_access.log file. As recording is continued past this value, there is no feedback for normal operation in the log. View directories and files created in [install-dir]/dvr for on-going feedback that recording is occurring. Add the property to Application/DVR/Properties section of Application.xml  
Constant value: **dvrMaxChunkLogCount**

See Also:

[DEFAULT\\_PROPERTY\\_DVR\\_MAX\\_CHUNK\\_LOG](#)

---

## DEFAULT\_PROPERTY\_DVR\_MAX\_CHUNK\_LOG

```
public static final int DEFAULT_PROPERTY_DVR_MAX_CHUNK_LOG
```

Default value for DVR Property "dvrMaxChunkLogCount".

Default value is 10 logging statements.  
Constant value: **10**

See Also:

[PROPERTY\\_MAX\\_CHUNK\\_LOG](#)

---

## PROPERTY\_MAX\_RECALC\_DURATION\_LOG

```
public static final java.lang.String PROPERTY_MAX_RECALC_DURATION_LOG
```

DVR Property "dvrMaxRecountDurationLogCount": for maximum number of messages to log regarding recalculating DVR chunk duration

Maximum number of log statements recorded regarding chunk duration being recalculated. A value less than 0 means all statements will be logged with no limit.  
Constant value: **dvrMaxRecountDurationLogCount**

See Also:

[DEFAULT\\_PROPERTY\\_MAX\\_RECALC\\_DURATION\\_LOG](#)

---

## DEFAULT\_PROPERTY\_MAX\_RECALC\_DURATION\_LOG

```
public static final int DEFAULT_PROPERTY_MAX_RECALC_DURATION_LOG
```

Default value for DVR Property "dvrMaxRecountDurationLogCount".

Default value is 30 logging statements.

---

(continued from last page)

Constant value: **30**

See Also:

[PROPERTY\\_MAX\\_RECALC\\_DURATION\\_LOG](#)

---

## PROPERTY\_DEBUG\_METHODS

```
public static final java.lang.String PROPERTY_DEBUG_METHODS
```

DVR Property "dvrDebugManagerLogMethods": for turning on DVR Manager debug logging.

Valid values are "true" or "false".

Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrDebugManagerLogMethods**

---

## PROPERTY\_DEBUG\_REPEATER

```
public static final java.lang.String PROPERTY_DEBUG_REPEATER
```

DVR Property "dvrDebugRepeater": for turning on logging of DVR repeater

Valid values are "true" or "false".

Constant value: **dvrDebugRepeater**

---

## PROPERTY\_DEBUG\_PLAYER\_ADAPTER

```
public static final java.lang.String PROPERTY_DEBUG_PLAYER_ADAPTER
```

HTTP Streamer Property "dvrDebugPlayerAdapter": for turning on DVR Player Adapter debug logging for all streamer types.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.

Constant value: **dvrDebugPlayerAdapter**

---

## PROPERTY\_DEBUG\_SMOOTH\_PLAYER\_ADAPTER

```
public static final java.lang.String PROPERTY_DEBUG_SMOOTH_PLAYER_ADAPTER
```

HTTP Streamer Property "dvrDebugSmoothPlayerAdapter": for turning on DVR Player Smooth Adapter debug logging.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.

Constant value: **dvrDebugSmoothPlayerAdapter**

---

## PROPERTY\_DEBUG\_SANJOSE\_PLAYER\_ADAPTER

```
public static final java.lang.String PROPERTY_DEBUG_SANJOSE_PLAYER_ADAPTER
```

HTTP Streamer Property "dvrDebugSanJosePlayerAdapter": for turning on DVR Player San Jose Adapter debug logging.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.

Constant value: **dvrDebugSanJosePlayerAdapter**



(continued from last page)

---

## PROPERTY\_DEBUG\_CUPERTINO\_PLAYER\_ADAPTER

```
public static final java.lang.String PROPERTY_DEBUG_CUPERTINO_PLAYER_ADAPTER
```

HTTP Streamer Property "dvrDebugCupertinoPlayerAdapter": for turning on DVR Player Cupertino Adapter debug logging.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.  
Constant value: **dvrDebugCupertinoPlayerAdapter**

---

## PROPERTY\_DEBUG\_MBR\_PLAYER\_ADAPTER

```
public static final java.lang.String PROPERTY_DEBUG_MBR_PLAYER_ADAPTER
```

HTTP Streamer or DVR Property "dvrDebugMbrPlayerAdapter": for turning on DVR MBR Player Adapter debug logging.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.  
Constant value: **dvrDebugMbrPlayerAdapter**

---

## PROPERTY\_DEBUG\_MBR\_PLAYER\_ADAPTER\_IF\_SHIFTED\_EMPTY

```
public static final java.lang.String  
PROPERTY_DEBUG_MBR_PLAYER_ADAPTER_IF_SHIFTED_EMPTY
```

HTTP Streamer or DVR Property "dvrDebugMbrPlayerAdapter": for turning on DVR MBR Player Adapter debug logging when null shifted entries is returned.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.  
Constant value: **dvrDebugMbrPlayerAdapterWhenShiftedEmpty**

---

## PROPERTY\_DEBUG\_MBR\_DETAILS\_WHEN\_RECORD\_DNE

```
public static final java.lang.String PROPERTY_DEBUG_MBR_DETAILS_WHEN_RECORD_DNE
```

HTTP Streamer or DVR Property "dvrDebugMbrDetailsWhenRecordDNE": for turning on DVR MBR Player Adapter debug logging.

Valid values are "true" or "false". (Default is false)

Add this property to Application/HTTPStreamer/Properties.  
Constant value: **dvrDebugMbrDetailsWhenRecordDNE**

---

## PROPERTY\_DEBUG\_MBR\_ALIGNMENT

```
public static final java.lang.String PROPERTY_DEBUG_MBR_ALIGNMENT
```

HTTP Streamer or DVR Property "dvrDebugMbrAlignment": for turning on logging of mbr alignment

Valid values are "true" or "false". Default is false.  
Constant value: **dvrDebugMbrAlignment**

---

## PROPERTY\_DEBUG\_MBR\_ALIGNMENT\_RESOLUTION

```
public static final java.lang.String PROPERTY_DEBUG_MBR_ALIGNMENT_RESOLUTION
```

---

(continued from last page)

DVR Property "dvrDebugMbrAlignmentResolution": for turning on logging of mbr alignment resolution (requested to actual)

Valid values are "true" or "false". Default is false.

Constant value: **dvrDebugMbrAlignmentResolution**

---

## PROPERTY\_DEBUG\_PLAYLIST\_REQUEST

```
public static final java.lang.String PROPERTY_DEBUG_PLAYLIST_REQUEST
```

DVR Property "dvrDebugPlaylistRequest": for turning on logging of DVR playlist requests.

Valid values are "true" or "false". Default is false.

Constant value: **dvrDebugPlaylistRequest**

---

## PROPERTY\_PLAYLIST\_REQUEST\_DELEGATE

```
public static final java.lang.String PROPERTY_PLAYLIST_REQUEST_DELEGATE
```

DVR Property "dvrPlaylistRequestDelegate": used to over-ride the class that generates a playlist request.

The delegate should extend DvrBasePlaylistRequestFactory

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrPlaylistRequestDelegate**

---

## PROPERTY\_ENCRYPTION\_INFO\_DELEGATE

```
public static final java.lang.String PROPERTY_ENCRYPTION_INFO_DELEGATE
```

DVR Property "dvrPlaylistEncryptionInfoDelegate": used to over-ride the encryption info on the playback side.

The specified delegate should extend com.wowza.wms.dvr.DvrBaseEncryptionInfoDelegate

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrPlaylistEncryptionInfoDelegate**

---

## PROPERTY\_SANJOSE\_PLAYLIST\_MIMETYPE

```
public static final java.lang.String PROPERTY_SANJOSE_PLAYLIST_MIMETYPE
```

DVR Property "dvrSanJosePlaylistMimeType": used to over-ride the mime type for DVR San Jose F4m playlists.

Default value is "video/mp4"

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSanJosePlaylistMimeType**

---

## PROPERTY\_SANJOSE\_PLAYLIST\_DELIVERYTYPE

```
public static final java.lang.String PROPERTY_SANJOSE_PLAYLIST_DELIVERYTYPE
```

DVR Property "dvrSanJosePlaylistDeliveryType": used to over-ride the mime type for DVR San Jose F4m playlists.

Default value is "streaming"

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSanJosePlaylistDeliveryType**

---

## PROPERTY\_SANJOSE\_PLAYLIST\_VERSION

```
public static final java.lang.String PROPERTY_SANJOSE_PLAYLIST_VERSION
```

(continued from last page)

DVR Property "dvrSanJosePlaylistVersion": used to over-ride the version of the San Jose f4m playlist.

Default value is "2.0". Valid values are "1.0" and "2.0".

Constant value: **dvrSanJosePlaylistVersion**

See Also:

[SANJOSE\\_F4M\\_VERSION\\_1\\_0](#)

[Add this to Application/DVR/Properties section of Application.xml](#)

---

## PROPERTY\_SANJOSE\_PLAYLIST\_RECORDED\_STREAMTYPE

```
public static final java.lang.String PROPERTY_SANJOSE_PLAYLIST_RECORDED_STREAMTYPE
```

DVR Property "dvrSanJosePlaylistRecordedStreamType": used to over-ride the stream type for non-live (recorded) DVR in San Jose f4m playlists.

Default value is #SANJOSE\_F4M\_STREAMTYPE\_RECORDED.\*

Constant value: **dvrSanJosePlaylistRecordedStreamType**

See Also:

[SANJOSE\\_F4M\\_STREAMTYPE\\_DVR](#)

[SANJOSE\\_F4M\\_STREAMTYPE\\_LIVE](#)

[SANJOSE\\_F4M\\_STREAMTYPE\\_LIVEORRECORDED](#)

Add this to Application/DVR/Properties section of Application.xml

---

## PROPERTY\_SANJOSE\_PLAYLIST\_LIVE\_STREAMTYPE

```
public static final java.lang.String PROPERTY_SANJOSE_PLAYLIST_LIVE_STREAMTYPE
```

DVR Property "dvrSanJosePlaylistLiveStreamType": used to over-ride the stream type for live DVR in San Jose f4m playlists.

Default value is #SANJOSE\_F4M\_STREAMTYPE\_DVR.

Constant value: **dvrSanJosePlaylistLiveStreamType**

See Also:

[SANJOSE\\_F4M\\_STREAMTYPE\\_DVR](#)

[SANJOSE\\_F4M\\_STREAMTYPE\\_LIVE](#)

[SANJOSE\\_F4M\\_STREAMTYPE\\_LIVEORRECORDED](#)

Add this to Application/DVR/Properties section of Application.xml

---

## SANJOSE\_F4M\_STREAMTYPE\_DVR

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_DVR
```

Constant for San Jose stream type "dvr".

Constant value: **dvr**

---

## SANJOSE\_F4M\_STREAMTYPE\_RECORDED

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_RECORDED
```

Constant for San Jose stream type "recorded".

Constant value: **recorded**

---

(continued from last page)

---

## SANJOSE\_F4M\_STREAMTYPE\_LIVE

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_LIVE
```

Constant for San Jose stream type "live".  
Constant value: **live**

---

## SANJOSE\_F4M\_STREAMTYPE\_LIVEORRECORDED

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED
```

Constant for San Jose stream type "liveOrRecorded".  
Constant value: **liveOrRecorded**

---

## SANJOSE\_F4M\_VERSION\_1\_0

```
public static final java.lang.String SANJOSE_F4M_VERSION_1_0
```

Constant for San Jose f4m version "1.0".  
Constant value: **1.0**

---

## SANJOSE\_F4M\_VERSION\_2\_0

```
public static final java.lang.String SANJOSE_F4M_VERSION_2_0
```

Constant for San Jose f4m version "2.0".  
Constant value: **2.0**

---

## SANJOSE\_F4M\_STREAMINGTYPE\_STREAMING

```
public static final java.lang.String SANJOSE_F4M_STREAMINGTYPE_STREAMING
```

Constant for San Jose streaming type "streaming".  
Constant value: **streaming**

---

## MIMETYPE\_VIDEO\_MP4

```
public static final java.lang.String MIMETYPE_VIDEO_MP4
```

Constant for mime type "video/mp4".  
Constant value: **video/mp4**

---

## PROPERTY\_SANJOSE\_ABST\_TIMESCALE

```
public static final java.lang.String PROPERTY_SANJOSE_ABST_TIMESCALE
```

DVR Property "dvrSanJosePlaylistAbstTimescale": used to over-ride the time-scale for abst files.

Default value is #SANJOSE\_ABST\_DEFAULT\_TIMESCALE (1000), which means milliseconds.

Add this to Application/DVR/Properties section of Application.xml  
Constant value: **dvrSanJosePlaylistAbstTimescale**

---

## PROPERTY\_SANJOSE\_ABST\_DURATION\_TOLERANCE

```
public static final java.lang.String PROPERTY_SANJOSE_ABST_DURATION_TOLERANCE
```

(continued from last page)

DVR Property "dvrSanJosePlaylistAbstDurationEqualityTolerance": used to over-ride the tolerance when determining equal chunks lengths.

Default value is #SANJOSE\_ABST\_DEFAULT\_DURATION\_EQUALITY\_TOLERANCE (50), which means 50 milliseconds.

Add this to Application/DVR/Properties section of Application.xml  
Constant value: **dvrSanJosePlaylistAbstDurationTolerance**

---

## DEFAULT\_PROPERTY\_SANJOSE\_ABST\_TIMESCALE

```
public static final int DEFAULT_PROPERTY_SANJOSE_ABST_TIMESCALE
```

Default value for property "dvrSanJosePlaylistAbstTimescale" #see [PROPERTY\\_SANJOSE\\_ABST\\_TIMESCALE](#)  
Constant value: **1000**

---

## DEFAULT\_PROPERTY\_SANJOSE\_ABST\_DURATION\_TOLERANCE

```
public static final int DEFAULT_PROPERTY_SANJOSE_ABST_DURATION_TOLERANCE
```

Default value for property "dvrSanJosePlaylistAbstDurationTolerance" #see [PROPERTY\\_SANJOSE\\_ABST\\_DURATION\\_TOLERANCE](#)  
Constant value: **50**

---

## PROPERTY\_CUPERTINO\_PLAYLIST\_FORCE\_LIVE

```
public static final java.lang.String PROPERTY_CUPERTINO_PLAYLIST_FORCE_LIVE
```

DVR Property "dvrCupertinoPlaylistForceLive": used to override playlist request delegate logic that determines if playlist is live.

Default value is false

Add this to Application/DVR/Properties section of Application.xml  
Constant value: **dvrCupertinoPlaylistForceLive**

---

## PROPERTY\_CUPERTINO\_PLAYLIST\_FORCE\_NONLIVE

```
public static final java.lang.String PROPERTY_CUPERTINO_PLAYLIST_FORCE_NONLIVE
```

DVR Property "dvrCupertinoPlaylistForceLive": used to override playlist request delegate logic that determines if playlist is live versus non-live.

Default value is false

Add this to Application/DVR/Properties section of Application.xml  
Constant value: **dvrCupertinoPlaylistForceNonLive**

---

## PROPERTY\_CUPERTINO\_PLAYLIST\_USE\_GZIP

```
public static final java.lang.String PROPERTY_CUPERTINO_PLAYLIST_USE_GZIP
```

DVR Property "dvrCupertinoPlaylistUseGzip": used to force Cupertino playlist to use gzip if it is accepted

Default value is true

Add this to Application/DVR/Properties section of Application.xml  
Constant value: **dvrCupertinoPlaylistUseGzip**

---

## PROPERTY\_CUPERTINO\_PLAYLIST\_GZIP\_THRESHOLD

```
public static final java.lang.String PROPERTY_CUPERTINO_PLAYLIST_GZIP_THRESHOLD
```

(continued from last page)

DVR Property "dvrCupertinoPlaylistGzipThreshold": when playlist is larger than this number of bytes, and gzip is enabled and accepted, the playlist will be compressed

Default value is [DEFAULT\\_CUPERTINO\\_PLAYLIST\\_GZIP\\_THRESHOLD](#)

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrCupertinoPlaylistGzipThreshold**

---

## DEFAULT\_CUPERTINO\_PLAYLIST\_GZIP\_THRESHOLD

```
public static final int DEFAULT_CUPERTINO_PLAYLIST_GZIP_THRESHOLD
```

Default value for property "dvrCupertinoPlaylistGzipThreshold" #see

[PROPERTY\\_CUPERTINO\\_PLAYLIST\\_GZIP\\_THRESHOLD](#)

Constant value: **4000**

---

## PROPERTY\_CUPERTINO\_ON\_CHUNK\_START\_RESET\_COUNTER

```
public static final java.lang.String PROPERTY_CUPERTINO_ON_CHUNK_START_RESET_COUNTER
```

DVR Property "dvrCupertinoOnChunkStartResetCounter": when a new chunk starts, reset internal tsPacketizer counters

Default value is false

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrCupertinoOnChunkStartResetCounter**

---

## PROPERTY\_CUPERTINO\_PLAYLIST\_ALLOW\_CACHING

```
public static final java.lang.String PROPERTY_CUPERTINO_PLAYLIST_ALLOW_CACHING
```

DVR Property "dvrCupertinoPlaylistAllowCaching": used to force Cupertino playlist to set #EXT-X-ALLOW-CACHE: value

Default value is false

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrCupertinoPlaylistAllowCaching**

---

## PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_SEEK

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_SEEK
```

DVR Property "dvrSmoothManifestLiveCanSeek": used to determine is CanSeek is enabled in smooth Manifest.

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_LIVE\_CAN\_SEEK, which is set to true.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestLiveCanSeek**

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_SEEK

```
public static final boolean DEFAULT_PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_SEEK
```

Constant value: **true**

---

## PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_PAUSE

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_PAUSE
```

---

(continued from last page)

DVR Property "dvrSmoothManifestLiveCanPause": used to determine is CanPause is enabled in smooth Manifest.

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_PAUSE, which is set to true.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestLiveCanPause**

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_PAUSE

```
public static final boolean DEFAULT_PROPERTY_SMOOTH_MANIFEST_LIVE_CAN_PAUSE
```

Constant value: **true**

---

## PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_SEEK

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_SEEK
```

DVR Property "dvrSmoothManifestRecordedCanSeek": used to determine is CanSeek is enabled in smooth Manifest.

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_SEEK, which is set to true.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestRecordedCanSeek**

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_SEEK

```
public static final boolean DEFAULT_PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_SEEK
```

Constant value: **true**

---

## PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_PAUSE

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_PAUSE
```

DVR Property "dvrSmoothManifestRecordedCanPause": used to determine is CanPause is enabled in smooth Manifest.

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_PAUSE, which is set to true.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestRecordedCanPause**

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_PAUSE

```
public static final boolean DEFAULT_PROPERTY_SMOOTH_MANIFEST_RECORDED_CAN_PAUSE
```

Constant value: **true**

---

## PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_SPECIFY\_DURATION

```
public static final java.lang.String  
PROPERTY_SMOOTH_MANIFEST_RECORDED_SPECIFY_DURATION
```

DVR Property "dvrSmoothManifestRecordedSpecifyDuration": used to determine if duration is specified. If not duration of zero is shown.

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_SPECIFY\_DURATION, which is set to true.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestRecordedSpecifyDuration**

---

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_SPECIFY\_DURATION

```
public static final boolean DEFAULT_PROPERTY_SMOOTH_MANIFEST_RECORDED_SPECIFY_DURATION
```

Constant value: **true**

---

## PROPERTY\_SMOOTH\_MANIFEST\_MAJOR\_VERSION

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_MAJOR_VERSION
```

DVR Property "dvrSmoothManifestMajorVersion": used to determine Smooth manifest major version

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_MAJOR\_VERSION.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestMajorVersion**

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_MAJOR\_VERSION

```
public static final int DEFAULT_PROPERTY_SMOOTH_MANIFEST_MAJOR_VERSION
```

Constant value: **2**

---

## PROPERTY\_SMOOTH\_MANIFEST\_MINOR\_VERSION

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_MINOR_VERSION
```

DVR Property "dvrSmoothManifestMinorVersion": used to determine Smooth manifest major version

Default value is #DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_MINOR\_VERSION.

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestMinorVersion**

---

## DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_MINOR\_VERSION

```
public static final int DEFAULT_PROPERTY_SMOOTH_MANIFEST_MINOR_VERSION
```

Constant value: **1**

---

## PROPERTY\_SMOOTH\_MANIFEST\_VERBOSE\_DURATION

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_VERBOSE_DURATION
```

DVR Property "dvrSmoothManifestVerboseDuration": used to force Smooth Manifest to include durations for each record

Default value is false

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestVerboseDuration**

---

## PROPERTY\_SMOOTH\_MANIFEST\_H264\_CODEC

```
public static final java.lang.String PROPERTY_SMOOTH_MANIFEST_H264_CODEC
```

---



(continued from last page)

DVR Property "dvrSmoothManifestH264Codec": used to force Smooth Manifest to use this as its FourCC H264 codec info.

Default value is set by Smooth Streaming

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSmoothManifestH264Codec**


---

## PROPERTY\_STREAM\_DATA

```
public static final java.lang.String PROPERTY_STREAM_DATA
```

Constant value: **dvrStreamRecordedData**

com.wowza.wms.dvr  
Class IDvrConstants.DvrTimeScale



All Implemented Interfaces:  
java.io.Serializable, Comparable

public static final class IDvrConstants.DvrTimeScale  
extends Enum

Field Summary

public static final	<a href="#">DVR_TIME</a>
public static final	<a href="#">PACKET_TIME</a>
public static final	<a href="#">UTC_TIME</a>

Method Summary

static <a href="#">IDvrConstants.DvrTimeScale</a>	<a href="#">valueOf</a> (String name)
static <a href="#">IDvrConstants.DvrTimeScale[]</a>	<a href="#">values</a> ()

Methods inherited from class java.lang.Enum
clone, compareTo, equals, getDeclaringClass, hashCode, name, ordinal, toString, valueOf

Methods inherited from class java.lang.Object
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.lang.Comparable
compareTo

Fields

(continued from last page)

---

## DVR\_TIME

```
public static final com.wowza.wms.dvr.IDvrConstants.DvrTimeScale DVR_TIME
```

---

## PACKET\_TIME

```
public static final com.wowza.wms.dvr.IDvrConstants.DvrTimeScale PACKET_TIME
```

---

## UTC\_TIME

```
public static final com.wowza.wms.dvr.IDvrConstants.DvrTimeScale UTC_TIME
```

## Methods

### values

```
public final static IDvrConstants.DvrTimeScale\[\] values()
```

---

### valueOf

```
public static IDvrConstants.DvrTimeScale valueOf(String name)
```

## com.wowza.wms.dvr Interface IDvrEncryptionInfo

public interface **IDvrEncryptionInfo**  
extends Cloneable

Interface for persisting encryption information for DVR.

### Field Summary

public static final	<a href="#">ENCRYPTION_TYPE_CUPERTINO</a> Cupertino AES encryption type. Value: <b>1</b>
public static final	<a href="#">ENCRYPTION_TYPE_MPEGDASH</a> MPEGDash encryption type. Value: <b>3</b>
public static final	<a href="#">ENCRYPTION_TYPE_PLAYREADY</a> Playready encryption type. Value: <b>2</b>

### Method Summary

Object	<a href="#">clone()</a>
int	<a href="#">getEncryptionType()</a> Serialize encryption info.
int	<a href="#">getSerializeSize()</a> Return number of bytes required to serialize this encryption info.
byte[]	<a href="#">serialize()</a> Serialize the encryption info, returning a byte buffer containing the serialized data.
int	<a href="#">serialize(byte[] buffer, int pos)</a> Serialize the encryption info into buffer starting at position 'pos'.

### Fields

#### ENCRYPTION\_TYPE\_CUPERTINO

public static final int **ENCRYPTION\_TYPE\_CUPERTINO**

Cupertino AES encryption type.  
Constant value: **1**

#### ENCRYPTION\_TYPE\_PLAYREADY

public static final int **ENCRYPTION\_TYPE\_PLAYREADY**

Playready encryption type.

(continued from last page)

Constant value: **2**

---

## ENCRYPTION\_TYPE\_MPEGDASH

```
public static final int ENCRYPTION_TYPE_MPEGDASH
```

MPEGDash encryption type.  
Constant value: **3**

## Methods

### getSerializeSize

```
public int getSerializeSize()
```

Return number of bytes required to serialize this encryption info.

**Returns:**

number of bytes to serialize.

---

### getEncryptionType

```
public int getEncryptionType()
```

Serialize encryption info.

The encryption should consist of the following:

- version (1 byte)
- encryption type (1 byte)
- length of 'blob' (2 bytes)
- byte blob (n bytes)

**Returns:**

encryption type (constants defined in this class)

---

### serialize

```
public int serialize(byte[] buffer,  
                    int pos)
```

Serialize the encryption info into buffer starting at position 'pos'.

**Parameters:**

`buffer` - buffer to serialize to  
`pos` - position to start serializing

**Returns:**

new position into buffer

---

### serialize

```
public byte[] serialize()
```

Serialize the encryption info, returning a byte buffer containing the serialized data.

**Returns:**

(continued from last page)

byte buffer of serialized data

---

## **clone**

```
public Object clone()  
    throws CloneNotSupportedException
```

## com.wowza.wms.dvr Interface IDvrManifest

public interface **IDvrManifest**  
extends

Interface for a DVR Store manifest. A DVR manifest collects type-specific manifest info, including:

- Audio manifest
- Video manifest
- data manifest
- time map manifest, to map DVR, packet and real time
- codec manifest to track codec information
- onMetadata manifest

The difference between retrieving 'recorded entries' and 'live entries' is an important one. Recorded Entries means every current manifest entry. Live Entries refers to a subset of these because a playlist will not include the very last entries, as some chunks must be available for buffering.

Field Summary	
public static final	<a href="#">CODEC_TYPE</a> Constant for codec manifest type. Value: <b>999</b>
public static final	<a href="#">MANIFEST_TAGNAME_CAN_PLAY</a> Value: <b>CanPlay</b>
public static final	<a href="#">MANIFEST_TAGNAME_CAN_RECORD</a> Value: <b>CanRecord</b>
public static final	<a href="#">MANIFEST_TAGNAME_CHUNK_GROUPING</a> Value: <b>ChunkGrouping</b>
public static final	<a href="#">MANIFEST_TAGNAME_CURRENT_TIME</a> Value: <b>CurrentTime</b>
public static final	<a href="#">MANIFEST_TAGNAME_HAS_ENCRYPTION</a> Value: <b>HasEncryption</b>
public static final	<a href="#">MANIFEST_TAGNAME_PURGE_TIME</a> Value: <b>PurgeTime</b>
public static final	<a href="#">ON_METADATA_TYPE</a> Constant for 'onMetadata' manifest type. Value: <b>0</b>
public static final	<a href="#">TIME_MAP_TYPE</a> Constant for time map manifest type. Value: <b>998</b>

## Method Summary

void	<a href="#"><code>addToManifest</code></a> (java.util.List entries) Add manifest entries to the manifest
void	<a href="#"><code>deserialize</code></a> (byte[] bytes) Deserialize the manifest.
long	<a href="#"><code>expandEndTime</code></a> (int type, long dvrEndTime)
long	<a href="#"><code>expandStartTime</code></a> (int type, long dvrStartTime)
long	<a href="#"><code>getClosestStartTime</code></a> (int type, long dvrTime) Given a dvrTime and a manifest type, find the closest chunk starting time.
<a href="#"><code>DvrManifestCodecEntry</code></a>	<a href="#"><code>getCodecEntryForTime</code></a> (long dvrTime) Return most recent codec entry for a given DVR time.
long	<a href="#"><code>getDvrTime</code></a> (int type)
<a href="#"><code>DvrManifestEntryRangeGroup</code></a>	<a href="#"><code>getEntriesToPurge</code></a> (long purgeTime) Given a purge time, return a group of manifest ranges to purge.
<a href="#"><code>DvrManifestEntry</code></a>	<a href="#"><code>getFirstEntry</code></a> (int type) Given manifest type, get the first playlist manifest entry.
<a href="#"><code>DvrManifestEntry</code></a>	<a href="#"><code>getLastLiveEntry</code></a> (int type) Given manifest type, get the last playlist manifest entry.
<a href="#"><code>DvrManifestEntry</code></a>	<a href="#"><code>getLastRecordedEntry</code></a> (int type) Given manifest type and DVR time, get last entry.
int	<a href="#"><code>getLastRecordedIndex</code></a> (int type) Return last index of DVR entry for given type.
long	<a href="#"><code>getLiveDuration</code></a> (int type) Given manifest type, return DVR live duration in seconds
java.util.List	<a href="#"><code>getLiveEntries</code></a> (int type, long dvrStart) Given manifest type and DVR time, get a list of the live entries.
java.util.List	<a href="#"><code>getLiveEntriesWithLimit</code></a> (int type, long dvrTime, int limit) Given manifest type and DVR time, get a list of the live entries limiting number of returned items.
DvrChannelManifest	<a href="#"><code>getManifestChannel</code></a> (int type) For a given manifest type, return the channel manifest.
<a href="#"><code>DvrManifestOnMetadataEntry</code></a>	<a href="#"><code>getMetadataEntryForTime</code></a> (long dvrTime) Return most recent metadataEntry for a given DVR time.
int	<a href="#"><code>getNextChunkIndex</code></a> ()
int	<a href="#"><code>getNextCodecIndex</code></a> ()
int	<a href="#"><code>getNextMetadataIndex</code></a> ()



int	<a href="#"><u>getNextTimeMapIndex()</u></a>
int	<a href="#"><u>getNumberLiveEntries</u></a> (int type, long dvrStart) Given manifest type and DVR time, get the number of live entries at the given time.
int	<a href="#"><u>getNumberLiveEntries</u></a> (int type, long dvrStart, long dvrEnd) Given manifest type and DVR time, get the number of live entries at the given time.
int	<a href="#"><u>getNumberRecordedEntries</u></a> (int type, long dvrStart) Given manifest type and DVR time, get the number of entries at the given time.
int	<a href="#"><u>getNumberRecordedEntries</u></a> (int type, long dvrStart, long dvrEnd) Given manifest type and DVR time, get the number of live entries at the given time.
long	<a href="#"><u>getRecordedDuration</u></a> (int type) Given manifest type, return DVR recorded duration in seconds
java.util.List	<a href="#"><u>getRecordedEntries</u></a> (int type) Get a copy of all manifest entries of a given type.
java.util.List	<a href="#"><u>getRecordedEntries</u></a> (int type, long dvrStartTime) Given manifest type and DVR time, get a list of recorded entries.
java.util.List	<a href="#"><u>getRecordedEntries</u></a> (int type, long dvrStartTime, long dvrEndTime) Given manifest type and DVR time, get a list of recorded entries.
java.util.List	<a href="#"><u>getRecordedEntriesInRange</u></a> ( <a href="#"><u>DvrManifestEntryRange</u></a> range) Given a DvrManifestEntryRange, get a list of recorded entries in this range.
java.util.Map	<a href="#"><u>getRecordedEntriesMap</u></a> (int type) Get a copy of all manifest entries of a given type as a Map of indices.
java.util.List	<a href="#"><u>getRecordedEntriesWithLimit</u></a> (int type, long dvrTime, int limit) Given manifest type and DVR time, get a list of recorded entries limiting number of returned items.
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryByIndex</u></a> (int type, int index) Get the manifest entry given a manifest type and an index.
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryByTimeKey</u></a> (int type, long dvrTime) Get the manifest entry given a manifest type and a time (in DVR units)
<a href="#"><u>IDvrTimeMap</u></a>	<a href="#"><u>getTimeMap</u></a> ()
boolean	<a href="#"><u>hasAudio</u></a> () Does manifest contain audio.
boolean	<a href="#"><u>hasCodecData</u></a> () Does manifest contain codec data.
boolean	<a href="#"><u>hasData</u></a> () Does manifest contain data.
boolean	<a href="#"><u>hasOnMetadata</u></a> () Does manifest contain onMetadata.
boolean	<a href="#"><u>hasTimeMapData</u></a> () Does manifest contain time map info.

boolean	<a href="#"><code>hasVideo()</code></a> Does manifest contain video.
void	<a href="#"><code>importManifest(IDvrManifest manifest, boolean persist)</code></a> Import the specified manifest into this manifest
void	<a href="#"><code>initialize()</code></a> Initialize the manifest.
java.util.List	<a href="#"><code>purgeEntries(DvrManifestEntryRangeGroup ranges)</code></a> Given a group of ranges, purge the manifest entries.
void	<a href="#"><code>refreshManifest()</code></a> Refresh the manifest.
byte[]	<a href="#"><code>serialize(boolean ignoreEntries)</code></a> Serialize the manifest.

## Fields

### ON\_METADATA\_TYPE

public static final int **ON\_METADATA\_TYPE**

Constant for 'onMetadata' manifest type.  
Constant value: **0**

### CODEC\_TYPE

public static final int **CODEC\_TYPE**

Constant for codec manifest type.  
Constant value: **999**

### TIME\_MAP\_TYPE

public static final int **TIME\_MAP\_TYPE**

Constant for time map manifest type.  
Constant value: **998**

### MANIFEST\_TAGNAME\_CAN\_RECORD

public static final java.lang.String **MANIFEST\_TAGNAME\_CAN\_RECORD**

Constant value: **CanRecord**

### MANIFEST\_TAGNAME\_CAN\_PLAY

public static final java.lang.String **MANIFEST\_TAGNAME\_CAN\_PLAY**

Constant value: **CanPlay**

(continued from last page)

---

## MANIFEST\_TAGNAME\_HAS\_ENCRYPTION

```
public static final java.lang.String MANIFEST_TAGNAME_HAS_ENCRYPTION
```

Constant value: **HasEncryption**

---

## MANIFEST\_TAGNAME\_CHUNK\_GROUPING

```
public static final java.lang.String MANIFEST_TAGNAME_CHUNK_GROUPING
```

Constant value: **ChunkGrouping**

---

## MANIFEST\_TAGNAME\_PURGE\_TIME

```
public static final java.lang.String MANIFEST_TAGNAME_PURGE_TIME
```

Constant value: **PurgeTime**

---

## MANIFEST\_TAGNAME\_CURRENT\_TIME

```
public static final java.lang.String MANIFEST_TAGNAME_CURRENT_TIME
```

Constant value: **CurrentTime**

## Methods

### initialize

```
public void initialize()
```

Initialize the manifest. Called after the previous storage has been loaded but before any chunks are added.

---

### refreshManifest

```
public void refreshManifest()
```

Refresh the manifest.

---

### addToManifest

```
public void addToManifest(java.util.List entries)
```

Add manifest entries to the manifest

**Parameters:**

entries - list of entries.

---

### getRecordedEntries

```
public java.util.List getRecordedEntries(int type)
```

Get a copy of all manifest entries of a given type. Valid types include: [IVHost.CONTENTTYPE\\_AUDIO](#), [IVHost.CONTENTTYPE\\_VIDEO](#), [IVHost.CONTENTTYPE\\_DATA](#), [ON\\_METADATA\\_TYPE](#), [CODEC\\_TYPE](#), or [TIME\\_MAP\\_TYPE](#)

**Parameters:**

(continued from last page)

type - The manifest type.

**Returns:**

list of entries

---

## getRecordedEntriesMap

```
public java.util.Map getRecordedEntriesMap(int type)
```

Get a copy of all manifest entries of a given type as a Map of indices. Valid types include: [IVHost.CONTENTTYPE\\_AUDIO](#), [IVHost.CONTENTTYPE\\_VIDEO](#), [IVHost.CONTENTTYPE\\_DATA](#), [ON\\_METADATA\\_TYPE](#), [CODEC\\_TYPE](#), or [TIME\\_MAP\\_TYPE](#)

**Parameters:**

type - the manifest type.

**Returns:**

map of entries

---

## getRecordedEntriesInRange

```
public java.util.List getRecordedEntriesInRange(DvrManifestEntryRange range)
```

Given a DvrManifestEntryRange, get a list of recorded entries in this range.

**Parameters:**

range - a range (which consists of a manifest type and a start and end index)

**Returns:**

list of entries

---

## getLastRecordedEntry

```
public DvrManifestEntry getLastRecordedEntry(int type)
```

Given manifest type and DVR time, get last entry.

"Recorded Entries" includes those entries after the end of the playlist.

**Parameters:**

type - the manifest type.

**Returns:**

manifest entry

---

## getRecordedEntryByTimeKey

```
public DvrManifestEntry getRecordedEntryByTimeKey(int type,  
long dvrTime)
```

Get the manifest entry given a manifest type and a time (in DVR units)

**Parameters:**

type - the manifest type.  
dvrTime - DVR time

**Returns:**

manifest entry

---

(continued from last page)

## getRecordedEntryByIndex

```
public DvrManifestEntry getRecordedEntryByIndex(int type,  
int index)
```

Get the manifest entry given a manifest type and an index.

**Parameters:**

type - the manifest type.  
index - the index into the manifest

**Returns:**

manifest entry

---

## getEntriesToPurge

```
public DvrManifestEntryRangeGroup getEntriesToPurge(long purgeTime)
```

Given a purge time, return a group of manifest ranges to purge. This method ensures that the purge entries are aligned by index so that audio and video always remain index aligned.

**Parameters:**

purgeTime - The DVR time to purge

**Returns:**

a group of ranges.

---

## purgeEntries

```
public java.util.List purgeEntries(DvrManifestEntryRangeGroup ranges)
```

Given a group of ranges, purge the manifest entries.

**Parameters:**

ranges - Group of ranges

**Returns:**

A list of the purged items.

---

## getMetadataEntryForTime

```
public DvrManifestOnMetadataEntry getMetadataEntryForTime(long dvrTime)
```

Return most recent metadataEntry for a given DVR time. The manifest for metadata entries is sparse-- it only stores items periodically. So for a given time t, the returned entry will exist at or before time t.

**Parameters:**

dvrTime - DVR time

**Returns:**

onMetadata Entry

---

## getCodecEntryForTime

```
public DvrManifestCodecEntry getCodecEntryForTime(long dvrTime)
```

Return most recent codec entry for a given DVR time. The manifest for codec entries is sparse-- it only stores items periodically. So for a given time t, the returned entry will exist at or before time t.

(continued from last page)

**Parameters:**

dvrTime - DVR time

**Returns:**

Codec Entry

---

## getNumberLiveEntries

```
public int getNumberLiveEntries(int type,  
                                long dvrStart)
```

Given manifest type and DVR time, get the number of live entries at the given time.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

**Parameters:**

type - the manifest type.  
dvrStart - DVR time

**Returns:**

number of entries.

---

## getNumberLiveEntries

```
public int getNumberLiveEntries(int type,  
                                long dvrStart,  
                                long dvrEnd)
```

Given manifest type and DVR time, get the number of live entries at the given time.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

**Parameters:**

type - the manifest type.  
dvrStart - DVR time  
dvrEnd - end DVR time

**Returns:**

number of entries.

---

## getNumberRecordedEntries

```
public int getNumberRecordedEntries(int type,  
                                    long dvrStart)
```

Given manifest type and DVR time, get the number of entries at the given time.

"Recorded Entries" includes those entries after the end of the playlist.

**Parameters:**

type - the manifest type.  
dvrStart - DVR time

**Returns:**

number of entries.

(continued from last page)

## getNumberRecordedEntries

```
public int getNumberRecordedEntries(int type,  
    long dvrStart,  
    long dvrEnd)
```

Given manifest type and DVR time, get the number of live entries at the given time.

"Recorded Entries" includes those entries after the end of the playlist.

### Parameters:

type - the manifest type.  
dvrStart - DVR time  
dvrEnd - end DVR time

### Returns:

number of entries.

---

## getFirstEntry

```
public DvrManifestEntry getFirstEntry(int type)
```

Given manifest type, get the first playlist manifest entry.

### Parameters:

type - the manifest type.

### Returns:

manifest entry

---

## getLastLiveEntry

```
public DvrManifestEntry getLastLiveEntry(int type)
```

Given manifest type, get the last playlist manifest entry.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

### Parameters:

type - the manifest type.

### Returns:

manifest entry

---

## getLiveEntries

```
public java.util.List getLiveEntries(int type,  
    long dvrStart)
```

Given manifest type and DVR time, get a list of the live entries.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

### Parameters:

type - the manifest type.  
dvrStart - DVR time

### Returns:

(continued from last page)

list of entries.

---

## **getLiveEntriesWithLimit**

```
public java.util.List getLiveEntriesWithLimit(int type,  
        long dvrTime,  
        int limit)
```

Given manifest type and DVR time, get a list of the live entries limiting number of returned items.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

### **Parameters:**

type - the manifest type.  
dvrTime - DVR time  
limit - maximum number of returned items

### **Returns:**

list of entries.

---

## **getRecordedEntriesWithLimit**

```
public java.util.List getRecordedEntriesWithLimit(int type,  
        long dvrTime,  
        int limit)
```

Given manifest type and DVR time, get a list of recorded entries limiting number of returned items.

"Recorded Entries" includes those entries after the end of the playlist.

### **Parameters:**

type - the manifest type.  
dvrTime - DVR time  
limit - maximum number of returned items

### **Returns:**

list of entries.

---

## **getRecordedEntries**

```
public java.util.List getRecordedEntries(int type,  
        long dvrStartTime)
```

Given manifest type and DVR time, get a list of recorded entries.

"Recorded Entries" includes those entries after the end of the playlist.

### **Parameters:**

type - the manifest type.  
dvrStartTime - DVR time

### **Returns:**

list of entries.

---

## **getRecordedEntries**

```
public java.util.List getRecordedEntries(int type,  
        long dvrStartTime,  
        long dvrEndTime)
```



(continued from last page)

Given manifest type and DVR time, get a list of recorded entries.

"Recorded Entries" includes those entries after the end of the playlist.

**Parameters:**

type - the manifest type.  
dvrStartTime - DVR time  
dvrEndTime - DVR end time

**Returns:**

list of entries.

---

## getRecordedDuration

```
public long getRecordedDuration(int type)
```

Given manifest type, return DVR recorded duration in seconds

"Recorded Entries" includes those entries after the end of the "live" playlist.

**Parameters:**

type - the manifest type.

**Returns:**

duration in seconds

---

## getLiveDuration

```
public long getLiveDuration(int type)
```

Given manifest type, return DVR live duration in seconds

"Recorded Entries" includes those entries after the end of the "live" playlist.

**Parameters:**

type - the manifest type.

**Returns:**

duration in seconds

---

## getDvrTime

```
public long getDvrTime(int type)
```

---

## getLastRecordedIndex

```
public int getLastRecordedIndex(int type)
```

Return last index of DVR entry for given type.

**Parameters:**

type

**Returns:**

index, or -1 if type does not exist

---

(continued from last page)

---

## getNextChunkIndex

```
public int getNextChunkIndex()
```

---

## getNextMetadataIndex

```
public int getNextMetadataIndex()
```

---

## getNextCodecIndex

```
public int getNextCodecIndex()
```

---

## getNextTimeMapIndex

```
public int getNextTimeMapIndex()
```

---

## getManifestChannel

```
public DvrChannelManifest getManifestChannel(int type)
```

For a given manifest type, return the channel manifest.

**Parameters:**

type

**Returns:**

channel manifest

---

## importManifest

```
public void importManifest(IDvrManifest manifest,  
    boolean persist)
```

Import the specified manifest into this manifest

**Parameters:**

manifest

persist

---

## getClosestStartTime

```
public long getClosestStartTime(int type,  
    long dvrTime)
```

Given a dvrTime and a manifest type, find the closest chunk starting time.

**Parameters:**

type - manifest type

dvrTime - DVR time

**Returns:**

(continued from last page)

time that corresponds to the closest start time of the given manifest type

---

## expandEndTime

```
public long expandEndTime(int type,  
                           long dvrEndTime)
```

---

## expandStartTime

```
public long expandStartTime(int type,  
                             long dvrStartTime)
```

---

## hasVideo

```
public boolean hasVideo()
```

Does manifest contain video.

**Returns:**

true if it contains video.

---

## hasAudio

```
public boolean hasAudio()
```

Does manifest contain audio.

**Returns:**

true if it contains audio.

---

## hasData

```
public boolean hasData()
```

Does manifest contain data.

**Returns:**

true if it contains data.

---

## hasOnMetadata

```
public boolean hasOnMetadata()
```

Does manifest contain onMetadata.

**Returns:**

true if it contains onMetadata.

---

## hasCodecData

```
public boolean hasCodecData()
```

Does manifest contain codec data.

**Returns:**

---

(continued from last page)

true if it contains codec data

---

## hasTimeMapData

```
public boolean hasTimeMapData( )
```

Does manifest contain time map info.

**Returns:**

true if it contains time map info.

---

## serialize

```
public byte[] serialize(boolean ignoreEntries)
```

Serialize the manifest.

**Parameters:**

`ignoreEntries` - If true, the individual manifest entries are not serialized.

**Returns:**

byte array of serialized data

---

## deserialize

```
public void deserialize(byte[] bytes)
```

Deserialize the manifest. Should be called after default constructor for manifest has been called.

**Parameters:**

`bytes` - buffer of bytes to deserialize

---

## getTimeMap

```
public IDvrTimeMap getTimeMap( )
```

## com.wowza.wms.dvr Interface IDvrPacketConverter

public interface **IDvrPacketConverter**  
extends

Interface for creating DVR chunks from a set of packets.

### Method Summary

DvrChunk	<a href="#">createDvrAudioChunk</a> (long dvrTime, int index, int duration, <a href="#">DvrPacketHolder</a> holder) Create audio chunk from set of packets.
DvrChunk	<a href="#">createDvrDataChunk</a> (long dvrTime, int index, int duration, <a href="#">DvrPacketHolder</a> holder) Create data chunk from set of packets.
DvrChunk	<a href="#">createDvrOnMetadataChunk</a> (long dvrTime, long pt, <a href="#">AMFPacket</a> metaPacket) Create onMetadata chunk from set of packets.
DvrChunk	<a href="#">createDvrVideoChunk</a> (long dvrTime, int index, int duration, <a href="#">DvrPacketHolder</a> holder) Create video chunk from set of packets.

### Methods

#### createDvrAudioChunk

```
public DvrChunk createDvrAudioChunk(long dvrTime,  
    int index,  
    int duration,  
    DvrPacketHolder holder)
```

Create audio chunk from set of packets.

**Parameters:**

dvrTime - DVR start time in milliseconds  
index - index of DVR chunk  
duration - Duration in milliseconds  
holder - packet holder

**Returns:**

the created chunk or null if chunk not created.

#### createDvrVideoChunk

```
public DvrChunk createDvrVideoChunk(long dvrTime,  
    int index,  
    int duration,  
    DvrPacketHolder holder)
```

Create video chunk from set of packets.

**Parameters:**

---

(continued from last page)

dvrTime - DVR start time in milliseconds  
index - index of DVR chunk  
duration - Duration in milliseconds  
holder - packet holder

**Returns:**

the created chunk or null if chunk not created.

---

## createDvrDataChunk

```
public DvrChunk createDvrDataChunk(long dvrTime,  
    int index,  
    int duration,  
    DvrPacketHolder holder)
```

Create data chunk from set of packets.

**Parameters:**

dvrTime - DVR start time in milliseconds  
index - index of DVR chunk  
duration - Duration in milliseconds  
holder - packet holder

**Returns:**

the created chunk or null if chunk not created.

---

## createDvrOnMetadataChunk

```
public DvrChunk createDvrOnMetadataChunk(long dvrTime,  
    long pt,  
    AMFPacket metaPacket)
```

Create onMetadata chunk from set of packets.

**Parameters:**

dvrTime - DVR start time in milliseconds  
pt - Packet time  
metaPacket - metadata packet

**Returns:**

the created chunk or null if chunk not created.

---

## com.wowza.wms.dvr Interface IDvrPacketWriter

public interface **IDvrPacketWriter**  
extends

Interface for chunking and storing packets for DVR.

### Method Summary

void	<a href="#"><u>addToChunk</u></a> (DvrPacketHolder holder)
boolean	<a href="#"><u>canRecordAudio</u></a> ()
boolean	<a href="#"><u>canRecordData</u></a> ()
boolean	<a href="#"><u>canRecordVideo</u></a> ()
void	<a href="#"><u>endChunk</u></a> (long videoEndTime, long audioEndTime)
void	<a href="#"><u>resetStream</u></a> ()
void	<a href="#"><u>sendOnMetadata</u></a> (long pt, <a href="#"><u>AMFPacket</u></a> metaPacket)
void	<a href="#"><u>setCodecInfoAudio</u></a> (com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
void	<a href="#"><u>setCodecInfoVideo</u></a> (com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
void	<a href="#"><u>startChunk</u></a> (int streamMode, int videoCodecId, int audioCodecId, long timecode, long utcTimecode)

### Methods

#### sendOnMetadata

```
public void sendOnMetadata(long pt,
    AMFPacket metaPacket)
```

#### startChunk

```
public void startChunk(int streamMode,
    int videoCodecId,
    int audioCodecId,
    long timecode,
    long utcTimecode)
```

(continued from last page)

---

## **addToChunk**

```
public void addToChunk(DvrPacketHolder holder)
```

---

## **endChunk**

```
public void endChunk(long videoEndTime,  
    long audioEndTime)
```

---

## **setCodecInfoAudio**

```
public void setCodecInfoAudio(com.wowza.wms.media.model.MediaCodecInfoAudio  
    codecInfoAudio)
```

---

## **setCodecInfoVideo**

```
public void setCodecInfoVideo(com.wowza.wms.media.model.MediaCodecInfoVideo  
    codecInfoVideo)
```

---

## **resetStream**

```
public void resetStream()
```

---

## **canRecordAudio**

```
public boolean canRecordAudio()
```

---

## **canRecordVideo**

```
public boolean canRecordVideo()
```

---

## **canRecordData**

```
public boolean canRecordData()
```



## com.wowza.wms.dvr Interface IDvrPlayerAdapter

public interface **IDvrPlayerAdapter**  
extends

### Field Summary

public static final	<a href="#"><u>QUERY_PARAM_DVR</u></a> Value: <b>DVR</b>
---------------------	---

### Method Summary

int	<a href="#"><u>calcBitrate</u></a> ( <a href="#"><u>IDvrStreamStore</u></a> store, int type, long t)
String	<a href="#"><u>determineStreamVersion</u></a> ( <a href="#"><u>IDvrStreamManager</u></a> dvrMgr, String baseStreamName)
DvrPlaylistRequest	<a href="#"><u>getDvrPlaylistRequest</u></a> ( <a href="#"><u>IHTTPStreamerApplicationContext</u></a> appContext, <a href="#"><u>IDvrStreamStore</u></a> store, java.util.Map queryMap)
DvrPlaylistRequest	<a href="#"><u>getDvrPlaylistRequest</u></a> ( <a href="#"><u>IHTTPStreamerApplicationContext</u></a> appContext, java.util.List stores, java.util.Map queryMap)
IDvrMbrPlaylistAlignment	<a href="#"><u>getPlaylistAlignment</u></a> ( <a href="#"><u>IHTTPStreamerSession</u></a> httpStreamerSession)
boolean	<a href="#"><u>isPlaylistReady</u></a> ( <a href="#"><u>IDvrStreamStore</u></a> store, DvrPlaylistRequest playlistRequest)
boolean	<a href="#"><u>isPlaylistReady</u></a> (java.util.List stores, DvrPlaylistRequest dvrPlaylistRequest)

### Fields

#### QUERY\_PARAM\_DVR

public static final java.lang.String **QUERY\_PARAM\_DVR**

Constant value: **DVR**

### Methods

#### isPlaylistReady

public boolean **isPlaylistReady**([IDvrStreamStore](#) store, DvrPlaylistRequest playlistRequest)

## isPlaylistReady

```
public boolean isPlaylistReady(java.util.List stores,  
    DvrPlaylistRequest dvrPlaylistRequest)
```

---

## determineStreamVersion

```
public String determineStreamVersion(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

---

## calcBitrate

```
public int calcBitrate(IDvrStreamStore store,  
    int type,  
    long t)
```

---

## getDvrPlaylistRequest

```
public DvrPlaylistRequest getDvrPlaylistRequest(IHTTPStreamerApplicationContext  
appContext,  
    IDvrStreamStore store,  
    java.util.Map queryMap)
```

---

## getDvrPlaylistRequest

```
public DvrPlaylistRequest getDvrPlaylistRequest(IHTTPStreamerApplicationContext  
appContext,  
    java.util.List stores,  
    java.util.Map queryMap)
```

---

## getPlaylistAlignment

```
public IDvrMbrPlaylistAlignment getPlaylistAlignment(IHTTPStreamerSession  
httpStreamerSession)
```

---

## com.wowza.wms.dvr Interface IDvrPurgeController

public interface **IDvrPurgeController**  
extends

Interface for controlling DVR chunk purging. The purge controller is instantiated using a factory class DvrPurgeControllerFactory.  
**See Also:**

`com.wowza.wms.dvr.impl.DvrPurgeControllerFactory,`  
`IDvrPrivateConstants.PROPERTY_PURGE_CONTROL_CLASS`

### Method Summary

long	<a href="#"><code>getCurrentTime()</code></a> Get current DVR time.
long	<a href="#"><code>getLastPurgeTime()</code></a> Get the DVR time when the last purge occurred.
void	<a href="#"><code>init(IDvrStreamStore store)</code></a> Initialize the controller.
boolean	<a href="#"><code>isPurgingEnabled()</code></a> Is Purging enabled for this controller.
void	<a href="#"><code>setCurrentDvrTime(long newDvrTime)</code></a> Set the current DVR time and perform purge if necessary.

### Methods

#### **init**

public void **init**([`IDvrStreamStore`](#) store)

Initialize the controller.

**Parameters:**

store - the DVR stream store

#### **isPurgingEnabled**

public boolean **isPurgingEnabled**()

Is Purging enabled for this controller.

**Returns:**

true if purging is active, false otherwise.

#### **setCurrentDvrTime**

public void **setCurrentDvrTime**(long newDvrTime)

Set the current DVR time and perform purge if necessary. This method checks the DVR time against its internal rules for purging and performs the purge. It is also responsible for setting the last purge time and the next purge time.

(continued from last page)

**Parameters:**newDvrTime

---

**getCurrentTime**

```
public long getCurrentTime()
```

Get current DVR time. The store is responsible for setting the DVR time via setCurrentDvrTime.

**Returns:**

current DVR time.

---

**getLastPurgeTime**

```
public long getLastPurgeTime()
```

Get the DVR time when the last purge occurred.

**Returns:**

DVR time of last purge

## com.wowza.wms.dvr Interface IDvrRawChunkProvider

All Subinterfaces:

[IDvrChunkMemoryCache](#)

public interface **IDvrRawChunkProvider**  
extends

Interface for providing raw DVR chunks based on a DVR manifest entry.

### Method Summary

DvrChunk	<a href="#">retrieveRawChunk</a> ( <a href="#">DvrManifestChunkEntry</a> entry) Given the specified manifest entry, return the raw DVR chunk.
----------	--

### Methods

#### **retrieveRawChunk**

public DvrChunk **retrieveRawChunk**([DvrManifestChunkEntry](#) entry)

Given the specified manifest entry, return the raw DVR chunk.

**Parameters:**

entry - The DVR manifest entry

**Returns:**

the DVR chunk or null if not able to return the chunk.

## com.wowza.wms.dvr Interface IDvrRecordingListener

public interface **IDvrRecordingListener**  
extends

Listener for DVR Recording events.

See Also:

[IDvrStreamManager.addDvrRecordingListener\(IDvrRecordingListener\)](#),  
[IDvrStreamManager.removeDvrRecordingListener\(IDvrRecordingListener\)](#)

### Method Summary

void	<a href="#">recordingPaused</a> ( <a href="#">IDvrStreamStore</a> store) Callback when DVR moves to paused state.
void	<a href="#">recordingReset</a> ( <a href="#">IDvrStreamStore</a> store) Callback when DVR gets reset.
void	<a href="#">recordingResumed</a> ( <a href="#">IDvrStreamStore</a> store) Callback when DVR moves out of paused state.
void	<a href="#">recordingStarted</a> ( <a href="#">IDvrStreamStore</a> store) Callback when DVR moves to recording state.
void	<a href="#">recordingStopped</a> ( <a href="#">IDvrStreamStore</a> store) Callback when DVR recording stops
void	<a href="#">timeReset</a> ( <a href="#">IDvrStreamStore</a> store, long oldDvrTime, long oldPacketTime, TimeMapRecord newTime) Callback when DVR time is adjusted.

### Methods

#### recordingStarted

public void **recordingStarted**([IDvrStreamStore](#) store)

Callback when DVR moves to recording state.

**Parameters:**

store - stream store

#### recordingPaused

public void **recordingPaused**([IDvrStreamStore](#) store)

Callback when DVR moves to paused state.

**Parameters:**

store - stream store

(continued from last page)

---

## recordingResumed

```
public void recordingResumed(IDvrStreamStore store)
```

Callback when DVR moves out of paused state.

**Parameters:**

store - stream store

---

## recordingReset

```
public void recordingReset(IDvrStreamStore store)
```

Callback when DVR gets reset. For example, if the incoming stream resets.

**Parameters:**

store - stream store

---

## recordingStopped

```
public void recordingStopped(IDvrStreamStore store)
```

Callback when DVR recording stops

**Parameters:**

store - stream store

---

## timeReset

```
public void timeReset(IDvrStreamStore store,  
    long oldDvrTime,  
    long oldPacketTime,  
    TimeMapRecord newTime)
```

Callback when DVR time is adjusted.

**Parameters:**

store - stream store

oldDvrTime

oldPacketTime - old packet time associated to oldDvrTime

newTime

## com.wowza.wms.dvr Interface IDvrRecordingsLoader

public interface **IDvrRecordingsLoader**  
extends

Interface for loading recordings during DVR Stream Manager initialization.

**See Also:**

[com.wowza.wms.dvr.impl.DvrRecordingsLoaderFactory](#),  
[IDvrConstants.PROPERTY\\_RECORDINGS\\_LOADER\\_CLASS](#)

### Method Summary

void	<a href="#">init</a> ( <a href="#">IDvrStreamManager</a> dvrMgr) Initialize recordings loader
void	<a href="#">loadArchivedRecordings</a> () Discover and load archived recording
boolean	<a href="#">shouldLoadStream</a> (String streamName, java.util.SortedSet versions) Should the given archived streams be laoded.
boolean	<a href="#">shouldLoadStreamVersion</a> (String streamName, Integer version, java.util.SortedSet versions) Should the given archived stream of specific version be laoded.

### Methods

#### init

public void **init**([IDvrStreamManager](#) dvrMgr)

Initialize recordings loader

**Parameters:**

dvrMgr - the DVR Stream Manager

#### loadArchivedRecordings

public void **loadArchivedRecordings**()

Discover and load archived recording

#### shouldLoadStream

public boolean **shouldLoadStream**(String streamName,  
java.util.SortedSet versions)

Should the given archived streams be laoded. The method contains logic which determines if all versions of the given stream Name should be loaded or not.

**Parameters:**

streamName - Stream name (unversioned)

versions - sorted set of available versions of this stream



(continued from last page)

**Returns:**

true if one or more of the streams should be loaded, false otherwise.

---

**shouldLoadStreamVersion**

```
public boolean shouldLoadStreamVersion(String streamName,  
    Integer version,  
    java.util.SortedSet versions)
```

Should the given archived stream of specific version be loaded. The method contains logic which determines if all versions of the given stream Name should be loaded or not.

**Parameters:**

streamName - Stream name (unversioned)

version - the specific version of the stream we are determining if we should load

versions - sorted set of all available versions of this stream

**Returns:**

true if one or more of the streams should be loaded, false otherwise.

## com.wowza.wms.dvr Interface IDvrStoreChunkListener

public interface **IDvrStoreChunkListener**  
extends

Listener for DVR Store chunk events.

Note that this listener traffic is very high.

**See Also:**

[IDvrStreamStore.addDvrChunkListener\(IDvrStoreChunkListener\)](#),  
[IDvrStreamStore.removeDvrChunkListener\(IDvrStoreChunkListener\)](#)

### Method Summary

void	<a href="#">postChunkAdded</a> ( <a href="#">IDvrStreamStore</a> store) Callback after a chunk is written to DVR store
void	<a href="#">postChunksPurged</a> ( <a href="#">IDvrStreamStore</a> store, <a href="#">DvrManifestEntryRangeGroup</a> entries, java.util.List deletedEntries) Callback after DVR store performs a purge
void	<a href="#">preChunkAdded</a> ( <a href="#">IDvrStreamStore</a> store) Callback before a chunk is written to DVR store
void	<a href="#">preChunksPurged</a> ( <a href="#">IDvrStreamStore</a> store, <a href="#">DvrManifestEntryRangeGroup</a> entries) Callback before DVR store performs a purge

### Methods

#### preChunkAdded

public void **preChunkAdded**([IDvrStreamStore](#) store)

Callback before a chunk is written to DVR store

**Parameters:**

store - the stream store

#### postChunkAdded

public void **postChunkAdded**([IDvrStreamStore](#) store)

Callback after a chunk is written to DVR store

**Parameters:**

store - the stream store

#### preChunksPurged

public void **preChunksPurged**([IDvrStreamStore](#) store,  
[DvrManifestEntryRangeGroup](#) entries)

(continued from last page)

Callback before DVR store performs a purge

**Parameters:**

store - the stream store

entries - list of DVR chunks to be purged

---

## postChunksPurged

```
public void postChunksPurged(IDvrStreamStore store,  
    DvrManifestEntryRangeGroup entries,  
    java.util.List deletedEntries)
```

Callback after DVR store performs a purge

**Parameters:**

store - the stream store

entries - list of DVR chunks purged

deletedEntries - list of entries deleted

## com.wowza.wms.dvr Interface IDvrStoreListener

public interface **IDvrStoreListener**  
extends

Listener for DVR Store lifecycle events.

See Also:

[IDvrStreamManager.addDvrStoreListener\(IDvrStoreListener\)](#),  
[IDvrStreamManager.removeDvrStoreListener\(IDvrStoreListener\)](#)

### Method Summary

void	<a href="#">dvrStreamStorageDeleted</a> ( <a href="#">IDvrStreamStore</a> store, <a href="#">IDvrFileSystem</a> <a href="#">FileSystem</a> , boolean success) Callback after DVR store is deleted from disk.
void	<a href="#">dvrStreamStorageLoaded</a> ( <a href="#">IDvrStreamManager</a> dvrMgr, <a href="#">IDvrStreamStore</a> store) Callback after DVR store is loaded from disk.
void	<a href="#">dvrStreamStoreCreate</a> ( <a href="#">IDvrStreamStore</a> store) Callback after DVR stream store is created.
void	<a href="#">dvrStreamStoreDestroy</a> ( <a href="#">IDvrStreamStore</a> store) Callback after DVR stream store is destroyed.
void	<a href="#">dvrStreamStoreInit</a> ( <a href="#">IDvrStreamStore</a> store) Callback after DVR stream store is initialized.

### Methods

#### dvrStreamStoreCreate

public void **dvrStreamStoreCreate**([IDvrStreamStore](#) store)

Callback after DVR stream store is created.

**Parameters:**

store - stream store

#### dvrStreamStoreInit

public void **dvrStreamStoreInit**([IDvrStreamStore](#) store)

Callback after DVR stream store is initialized.

**Parameters:**

store - stream store

#### dvrStreamStoreDestroy

public void **dvrStreamStoreDestroy**([IDvrStreamStore](#) store)

Callback after DVR stream store is destroyed.

---

(continued from last page)

**Parameters:**

store - stream store

---

## dvrStreamStorageLoaded

```
public void dvrStreamStorageLoaded(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback after DVR store is loaded from disk.

**Parameters:**

dvrMgr - DVR Application Store Manager

store - stream store

---

## dvrStreamStorageDeleted

```
public void dvrStreamStorageDeleted(IDvrStreamStore store,  
    IDvrFileSystem fileSystem,  
    boolean success)
```

Callback after DVR store is deleted from disk.

**Parameters:**

store

fileSystem - stream store file system

success - whether delete succeeded or failed

## com.wowza.wms.dvr Interface IDvrStreamManager

All Superinterfaces:

[ILiveStreamPacketizer](#)

public interface **IDvrStreamManager**

extends [ILiveStreamPacketizer](#)

DVR Stream manager. Manages a live stream and associated DVR stores.

### Method Summary

void	<a href="#">addDvrRecordingListener</a> ( <a href="#">IDvrRecordingListener</a> listener)	Add listener to DVR recording events.
void	<a href="#">addDvrStoreListener</a> ( <a href="#">IDvrStoreListener</a> listener)	Add listener to DVR store lifecycle events.
void	<a href="#">addManifestEntries</a> (String vStreamName, java.util.List entries)	Add to stream stores manifest.
void	<a href="#">addRepeaterHeartBeatItem</a> ()	
boolean	<a href="#">canRecord</a> ()	Is this stream able to record.
void	<a href="#">deleteArchivedStore</a> (String vStreamName)	Delete archived stream store.
String	<a href="#">getArchiveStrategy</a> ()	Get the DVR archive strategy.
String	<a href="#">getContextStr</a> ()	Get stream context string, useful for logging.
<a href="#">IDvrStreamStore</a>	<a href="#">getDefaultStreamingStore</a> ()	Get the store to be used for streaming.
String	<a href="#">getDvrFileSystemClass</a> ()	Get the class used for the DVR file system.
String	<a href="#">getDvrStorageDir</a> ()	Get the storage directory.
int	<a href="#">getDvrStorageWindowSeconds</a> ()	Get DVR window size.
DvrBaseEncryptionInfo Delegate	<a href="#">getEncryptionDelegate</a> ()	Get the encryption delegate for providing streaming side encryption info objects.
String	<a href="#">getEncryptionRepeaterSharedSecret</a> ()	Get the DVR encryption shared secret.

<a href="#">IDvrStreamStore</a>	<a href="#">getHighestVersionedStore()</a> Return stream store that is highest known version.
void	<a href="#">getInitialRepeaterItems</a> (java.util.List items) Get initial repeater items to send to repeater receiver.
int	<a href="#">getMinimumAvailableChunks()</a> Return number of chunks that must be available to stream.
String	<a href="#">getPacketizerName()</a> Get live stream packetizer name.
<a href="#">IDvrStreamStore</a>	<a href="#">getRecordingStreamStore()</a> Get current recording store
void	<a href="#">getRepeaterItemsDvr</a> (java.util.List items, long lastSeq)
String	<a href="#">getStreamBaseName()</a> Get input streamName (no version info).
<a href="#">IDvrStreamStore</a>	<a href="#">getStreamStore</a> (String vStreamName) Given a stream name containing version info, return the associated stream store.
java.util.List	<a href="#">getStreamStores()</a> Get list of all stream stores known to this stream manager.
<a href="#">IDvrStreamVersionHandler</a>	<a href="#">getStreamVersionHandler()</a> Get the stream version handler object.
void	<a href="#">initialAttributes</a> (String vStreamName, int dvrWindow)
void	<a href="#">initialManifest</a> (String vStreamName, <a href="#">IDvrManifest</a> manifest)
void	<a href="#">initialManifestEnd</a> (String vStreamName)
boolean	<a href="#">isRecording()</a> Is this stream currently recording.
boolean	<a href="#">isRecordingPaused()</a> Is this stream currently paused from recording.
<a href="#">IDvrStreamStore</a>	<a href="#">loadArchivedStore</a> (String vStreamName, DvrManifestHolder manifestHolder) Load archived stream store.
void	<a href="#">notifyDvrStreamStorageDeleted</a> ( <a href="#">IDvrStreamStore</a> store, IDvrFileSystem fileSystem, boolean success)
void	<a href="#">notifyDvrStreamStoreCreate</a> ( <a href="#">IDvrStreamStore</a> store)
void	<a href="#">notifyDvrStreamStoreDestroy</a> ( <a href="#">IDvrStreamStore</a> store)
void	<a href="#">notifyDvrStreamStoreInit</a> ( <a href="#">IDvrStreamStore</a> store)
void	<a href="#">notifyDvrStreamStoreLoaded</a> ( <a href="#">IDvrStreamStore</a> store)

void	<a href="#"><u>notifyTimeReset</u></a> ( <a href="#"><u>IDvrStreamStore</u></a> store, long oldDvrTime, long oldPacketTime, <a href="#"><u>TimeMapRecord</u></a> newTimeMapRecord)
<a href="#"><u>IDvrStreamStore</u></a>	<a href="#"><u>pauseRecording</u></a> () Request that stream recording pause.
void	<a href="#"><u>purgeManifestEntries</u></a> (String vStreamName, <a href="#"><u>DvrManifestEntryRangeGroup</u></a> rangeGroup) Purge entries from store
void	<a href="#"><u>removeDvrRecordingListener</u></a> ( <a href="#"><u>IDvrRecordingListener</u></a> listener) Remove listener to DVR recording events.
void	<a href="#"><u>removeDvrStoreListener</u></a> ( <a href="#"><u>IDvrStoreListener</u></a> listener) Remove listener of DVR store lifecycle events.
void	<a href="#"><u>resetStream</u></a> () Reset the stream.
<a href="#"><u>IDvrStreamStore</u></a>	<a href="#"><u>resumeRecording</u></a> () Request that stream recording resume.
void	<a href="#"><u>setDefaultStreamingStore</u></a> ( <a href="#"><u>IDvrStreamStore</u></a> store) Set the store to be used for streaming.
void	<a href="#"><u>setRecordingStreamStore</u></a> ( <a href="#"><u>IDvrStreamStore</u></a> store) Set the store used for recording.
void	<a href="#"><u>setStreamVersionHandler</u></a> ( <a href="#"><u>IDvrStreamVersionHandler</u></a> handler) Set the stream version handler object.
<a href="#"><u>IDvrStreamStore</u></a>	<a href="#"><u>startRecording</u></a> () Request that stream recording start.
void	<a href="#"><u>stateChange</u></a> (String vStreamName, <a href="#"><u>DvrStreamStoreState</u></a> state)
<a href="#"><u>IDvrStreamStore</u></a>	<a href="#"><u>stopRecording</u></a> () Request that stream recording stop.
DvrChunkStorageInfo	<a href="#"><u>storeChunks</u></a> (int vDuration, <a href="#"><u>DvrPacketHolder</u></a> vPackets, int aDuration, <a href="#"><u>DvrPacketHolder</u></a> aPackets, int dDuration, <a href="#"><u>DvrPacketHolder</u></a> dPackets)
boolean	<a href="#"><u>storeOnMetadata</u></a> (long pt, long utc, <a href="#"><u>AMFPacket</u></a> metaPacket)

Methods inherited from interface [com.wowza.wms.stream.livepacketizer.ILiveStreamPacketizer](#)

[getAndSetStartStream](#), [getApplicationInstance](#), [getLiveStreamPacketizerId](#), [getProperties](#), [getRepeaterLastSequence](#), [handlePacket](#), [init](#), [isActive](#), [isPacketizeAudio](#), [isPacketizeData](#), [isPacketizeVideo](#), [isRepeaterEdge](#), [resetStream](#), [setLiveStreamPacketizerId](#), [setPacketizeAudio](#), [setPacketizeData](#), [setPacketizeVideo](#), [setRepeaterEdge](#), [shutdown](#), [startStream](#), [touch](#)

## Methods



(continued from last page)

## getContextStr

```
public String getContextStr()
```

Get stream context string, useful for logging.

**Returns:**

stream context string

---

## getStreamBaseName

```
public String getStreamBaseName()
```

Get input streamName (no version info).

**Returns:**

unversioned incoming stream name

---

## getStreamStore

```
public IDvrStreamStore getStreamStore(String vStreamName)
```

Given a stream name containing version info, return the associated stream store.

**Parameters:**

vStreamName - versioned stream name

**Returns:**

store or null

---

## getPacketizerName

```
public String getPacketizerName()
```

Get live stream packetizer name.

**Returns:**

live stream packetizer name

---

## getStreamStores

```
public java.util.List getStreamStores()
```

Get list of all stream stores known to this stream manager.

**Returns:**

list of stream stores.

---

## getHighestVersionedStore

```
public IDvrStreamStore getHighestVersionedStore()
```

Return stream store that is highest known version.

**Returns:**

stream store

---

## getMinimumAvailableChunks

```
public int getMinimumAvailableChunks()
```

Return number of chunks that must be available to stream.

**Returns:**

minimum available chunks

---

## setRecordingStreamStore

```
public void setRecordingStreamStore(IDvrStreamStore store)
```

Set the store used for recording.

**Parameters:**

store - stream store, or null

---

## getRecordingStreamStore

```
public IDvrStreamStore getRecordingStreamStore()
```

Get current recording store

**Returns:**

current recording store (may be null)

---

## setDefaultStreamingStore

```
public void setDefaultStreamingStore(IDvrStreamStore store)
```

Set the store to be used for streaming.

**Parameters:**

store - store to stream.

---

## getDefaultStreamingStore

```
public IDvrStreamStore getDefaultStreamingStore()
```

Get the store to be used for streaming.

**Returns:**

store to stream.

---

## getDvrStorageWindowSeconds

```
public int getDvrStorageWindowSeconds()
```

Get DVR window size.

**Returns:**

window size in seconds (0 means infinite window size)

---

## getDvrStorageDir

```
public String getDvrStorageDir()
```

---

(continued from last page)

Get the storage directory.

**Returns:**

storage directory

---

## getDvrFileSystemClass

```
public String getDvrFileSystemClass()
```

Get the class used for the DVR file system.

**Returns:**

fully qualified class name

---

## getArchiveStrategy

```
public String getArchiveStrategy()
```

Get the DVR archive strategy.

**Returns:**

The archive strategy

---

## getEncryptionRepeaterSharedSecret

```
public String getEncryptionRepeaterSharedSecret()
```

Get the DVR encryption shared secret.

**Returns:**

shared secret.

---

## getEncryptionDelegate

```
public DvrBaseEncryptionInfoDelegate getEncryptionDelegate()
```

Get the encryption delegate for providing streaming side encryption info objects.

**Returns:**

delegate

---

## getStreamVersionHandler

```
public IDvrStreamVersionHandler getStreamVersionHandler()
```

Get the stream version handler object.

**Returns:**

stream version handler object.

---

## setStreamVersionHandler

```
public void setStreamVersionHandler(IDvrStreamVersionHandler handler)
```

Set the stream version handler object. Must be called after the stream manager is created and before it is initialized.

**Parameters:**

handler - stream version handler object.

## resetStream

```
public void resetStream()
```

Reset the stream.

---

## canRecord

```
public boolean canRecord()
```

Is this stream able to record.

**Returns:**

true if this stream is recordable.

---

## isRecording

```
public boolean isRecording()
```

Is this stream currently recording. If this stream is not recordable, the method returns false.

**Returns:**

true if has a recording stream and it is recording.

---

## isRecordingPaused

```
public boolean isRecordingPaused()
```

Is this stream currently paused from recording. If this stream is not recording and not paused, the method returns false.

**Returns:**

true if has a recording is paused.

---

## startRecording

```
public IDvrStreamStore startRecording()
```

Request that stream recording start.

Used internally. Clients should call [ILiveStreamDvrRecorder.startRecording\(\)](#). Note that this call places the DVR stream store in the recording state. If the stream store is in the paused state, DVR recording will not occur.

If there is not currently a stream store for recording, one will attempt to be created. A successful start will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingStarted\(IDvrStreamStore\)](#) method called.

Success only occurs if the stream canRecord [IDvrStreamStore.canRecord\(\)](#) and the stream is not already in the recording state.

**Returns:**

store if successful. null otherwise.

---

## stopRecording

```
public IDvrStreamStore stopRecording()
```

---

(continued from last page)

Request that stream recording stop.

Used internally. Clients should call [ILiveStreamDvrRecorder.stopRecording\(\)](#). Note that this call places the DVR stream in the *not* recording state.

A successful stop will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingStopped\(IDvrStreamStore\)](#) method called.

Success only occurs if the stream is already in the recording state [IDvrStreamStore.isRecording\(\)](#).

**Returns:**

store if successful. null otherwise.

---

## pauseRecording

```
public IDvrStreamStore pauseRecording()
```

Request that stream recording pause.

Used internally. Clients should call [ILiveStreamDvrRecorder.pauseRecording\(\)](#). The stream does not have to be actively recording to be paused. For example, it could be paused before packets start flowing.

A successful pause will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingPaused\(IDvrStreamStore\)](#) method called.

**Returns:**

store if successful. null otherwise.

---

## resumeRecording

```
public IDvrStreamStore resumeRecording()
```

Request that stream recording resume.

Used internally. Clients should call [ILiveStreamDvrRecorder.resumeRecording\(\)](#). The stream does not have to be actively recording to be resumed. For example, it could have been paused before the stream started, and this call would move it out of the paused state.

A successful resume will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingResumed\(IDvrStreamStore\)](#) method called.

**Returns:**

store if successful. null otherwise.

---

## loadArchivedStore

```
public IDvrStreamStore loadArchivedStore(String vStreamName,  
DvrManifestHolder manifestHolder)
```

Load archived stream store.

**Parameters:**

vStreamName - versioned stream Name (e.g. myStream.0)

manifestHolder - manifest holder containing list of manifest properties

**Returns:**

stream store

---

## deleteArchivedStore

```
public void deleteArchivedStore(String vStreamName)
```

(continued from last page)

Delete archived stream store.

**Parameters:**

vStreamName - versioned stream Name (e.g. myStream.0)

---

## addManifestEntries

```
public void addManifestEntries(String vStreamName,  
    java.util.List entries)
```

Add to stream stores manifest.

**Parameters:**

vStreamName - versioned stream Name (e.g. myStream.0)

entries - list of manifest entries.

---

## purgeManifestEntries

```
public void purgeManifestEntries(String vStreamName,  
    DvrManifestEntryRangeGroup rangeGroup)
```

Purge entries from store

**Parameters:**

vStreamName - versioned stream Name (e.g. myStream.0)

rangeGroup - set of ranges for purging

---

## storeChunks

```
public DvrChunkStorageInfo storeChunks(int vDuration,  
    DvrPacketHolder vPackets,  
    int aDuration,  
    DvrPacketHolder aPackets,  
    int dDuration,  
    DvrPacketHolder dPackets)
```

---

## storeOnMetadata

```
public boolean storeOnMetadata(long pt,  
    long utc,  
    AMFPacket metaPacket)
```

---

## addDvrStoreListener

```
public void addDvrStoreListener(IDvrStoreListener listener)
```

Add listener to DVR store lifecycle events.

**Parameters:**

listener - listener

---

## removeDvrStoreListener

```
public void removeDvrStoreListener(IDvrStoreListener listener)
```

Remove listener of DVR store lifecycle events.

---

(continued from last page)

**Parameters:**

listener - listener

---

**addDvrRecordingListener**

```
public void addDvrRecordingListener(IDvrRecordingListener listener)
```

Add listener to DVR recording events.

**Parameters:**

listener - listener

---

**removeDvrRecordingListener**

```
public void removeDvrRecordingListener(IDvrRecordingListener listener)
```

Remove listener to DVR recording events.

**Parameters:**

listener - listener

---

**notifyDvrStreamStoreCreate**

```
public void notifyDvrStreamStoreCreate(IDvrStreamStore store)
```

---

**notifyDvrStreamStoreInit**

```
public void notifyDvrStreamStoreInit(IDvrStreamStore store)
```

---

**notifyDvrStreamStoreDestroy**

```
public void notifyDvrStreamStoreDestroy(IDvrStreamStore store)
```

---

**notifyDvrStreamStoreLoaded**

```
public void notifyDvrStreamStoreLoaded(IDvrStreamStore store)
```

---

**notifyDvrStreamStorageDeleted**

```
public void notifyDvrStreamStorageDeleted(IDvrStreamStore store,  
    IDvrFileSystem fileSystem,  
    boolean success)
```

(continued from last page)

## notifyTimeReset

```
public void notifyTimeReset(IDvrStreamStore store,
    long oldDvrTime,
    long oldPacketTime,
    TimeMapRecord newTimeMapRecord)
```

---

## getInitialRepeaterItems

```
public void getInitialRepeaterItems(java.util.List items)
```

Get initial repeater items to send to repeater receiver.

When an edge initially requests the items, instead of sending the entire manifest and all repeater items up until that point, the player sends a `DvrRepeaterHolder.REPEATER_INITIAL_MANIFEST` event followed by several `DvrRepeaterHolder.REPEATER_ADD_MANIFEST_ENTRIES` events.

This allows us to not bother sending any purged manifest entries.

### Parameters:

items

---

## getRepeaterItemsDvr

```
public void getRepeaterItemsDvr(java.util.List items,
    long lastSeq)
```

---

## initialManifest

```
public void initialManifest(String vStreamName,
    IDvrManifest manifest)
```

---

## initialManifestEnd

```
public void initialManifestEnd(String vStreamName)
```

---

## initialAttributes

```
public void initialAttributes(String vStreamName,
    int dvrWindow)
```

---

## stateChange

```
public void stateChange(String vStreamName,
    DvrStreamStoreState state)
```

---



(continued from last page)

## **addRepeaterHeartBeatItem**

```
public void addRepeaterHeartBeatItem( )
```

## com.wowza.wms.dvr Interface IDvrStreamStore

public interface **IDvrStreamStore**  
extends

### Method Summary

void	<a href="#"><u>addDvrChunkListener</u></a> ( <a href="#"><u>IDvrStoreChunkListener</u></a> listener) Add (very fine) listener for chunk events.
void	<a href="#"><u>addManifestEntries</u></a> (java.util.List entries)
boolean	<a href="#"><u>canPlay</u></a> () Is this store capable of playing.
boolean	<a href="#"><u>canRecord</u></a> () Is this store capable of recording.
<a href="#"><u>IApplicationInstance</u></a>	<a href="#"><u>getAppInstance</u></a> () Get associated application instance.
<a href="#"><u>IDvrChunker</u></a>	<a href="#"><u>getChunker</u></a> ()
long	<a href="#"><u>getClosestStartTime</u></a> (int type, long t)
String	<a href="#"><u>getContextStr</u></a> () Get stream context string, useful for logging.
DvrChunk	<a href="#"><u>getDvrChunkAtTime</u></a> (int fragmentType, long t)
DvrChunk	<a href="#"><u>getDvrChunkByIndex</u></a> (int fragmentType, int index)
DvrChunk	<a href="#"><u>getDvrChunkNearTime</u></a> (int fragmentType, long t, long delta)
<a href="#"><u>IDvrStreamManager</u></a>	<a href="#"><u>getDvrManager</u></a> () Get DVR Stream Manager
int	<a href="#"><u>getDvrStorageWindowSeconds</u></a> () Get DVR window size.
IDvrFileSystem	<a href="#"><u>getFileSystem</u></a> ()
<a href="#"><u>IDvrManifest</u></a>	<a href="#"><u>getManifest</u></a> () Get manifest
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties</u></a> () Get stream store properties.
<a href="#"><u>IDvrPurgeController</u></a>	<a href="#"><u>getPurgeController</u></a> () Get purge controller for stream store.

java.util.List	<a href="#"><u>getRecordedEntriesWithLimit</u></a> (int fragmentType, long t, int limit)
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryByIndex</u></a> (int fragmentType, int index)
<a href="#"><u>DvrManifestEntry</u></a>	<a href="#"><u>getRecordedEntryByTime</u></a> (int fragmentType, long t)
String	<a href="#"><u>getStreamName</u></a> () Get versioned stream name.
DvrTimeMapper	<a href="#"><u>getTimeMapper</u></a> () Get time mapper, which maps between DVR, real and packet time.
boolean	<a href="#"><u>hasAudio</u></a> () Does this store have audio.
boolean	<a href="#"><u>hasData</u></a> () Does this store have data.
boolean	<a href="#"><u>hasEncryption</u></a> () Does this store contain encryption information
boolean	<a href="#"><u>hasOnMetadata</u></a> () Does this store have on metadata.
boolean	<a href="#"><u>hasVideo</u></a> () Does this store have video.
void	<a href="#"><u>init</u></a> () Initialize DVR stream store.
boolean	<a href="#"><u>isLive</u></a> () Is store currently live For an origin, <a href="#"><u>isRecording()</u></a> and <a href="#"><u>isLive()</u></a> will typically return the same result.
boolean	<a href="#"><u>isLoading</u></a> ()
boolean	<a href="#"><u>isRecording</u></a> () Is store currently recording.
boolean	<a href="#"><u>isRecordingPaused</u></a> () Is store currently paused while recording.
boolean	<a href="#"><u>pauseRecording</u></a> () Request that stream recording pause.
void	<a href="#"><u>purgeEntries</u></a> ( <a href="#"><u>DvrManifestEntryRangeGroup</u></a> rangeGroup) Purge entries from store
void	<a href="#"><u>removeDvrChunkListener</u></a> ( <a href="#"><u>IDvrStoreChunkListener</u></a> listener) Remove (very fine) listener for chunk events.
void	<a href="#"><u>reset</u></a> ()
boolean	<a href="#"><u>resumeRecording</u></a> () Request that stream recording resume.

void	<a href="#">setCanPlay</a> (boolean canPlay) Set the Stream Stores ability to play.
void	<a href="#">setCanRecord</a> (boolean canRecord) Set the Stream Stores ability to record.
void	<a href="#">setHasEncryption</a> (boolean hasEncryption) Set whether the store has encryption.
void	<a href="#">shutdown</a> ( )
boolean	<a href="#">startRecording</a> ( ) Request that recording start.
boolean	<a href="#">stopRecording</a> ( ) Request that stream recording stop.
DvrChunkStorageInfo	<a href="#">storeChunks</a> (int vDuration, DvrPacketHolder vPackets, int aDuration, DvrPacketHolder aPackets, int dDuration, DvrPacketHolder dPackets)
boolean	<a href="#">storeOnMetadata</a> (long pt, long utc, <a href="#">AMFPacket</a> metaPacket)

## Methods

### init

```
public void init()
```

Initialize DVR stream store.

### reset

```
public void reset()
```

### shutdown

```
public void shutdown()
```

### getProperties

```
public WMSProperties getProperties()
```

Get stream store properties.

**Returns:**

properties

### getDvrStorageWindowSeconds

```
public int getDvrStorageWindowSeconds()
```

(continued from last page)

Get DVR window size. This may be set by setting the IDvrStreamStore's property [IDvrConstants.PROPERTY\\_WINDOW\\_DURATION](#) after the store is created and before it is initialized by using the [IDvrStoreListener.dvrStreamStoreCreate\(IDvrStreamStore\)](#)

**Returns:**

window size in seconds (0 means infinite window size)

---

## getStreamName

```
public String getStreamName()
```

Get versioned stream name.

**Returns:**

(versioned) stream name

---

## getContextStr

```
public String getContextStr()
```

Get stream context string, useful for logging.

**Returns:**

stream context string

---

## getDvrManager

```
public IDvrStreamManager getDvrManager()
```

Get DVR Stream Manager

**Returns:**

DVR Stream Manager

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get associated application instance.

**Returns:**

application instance.

---

## getManifest

```
public IDvrManifest getManifest()
```

Get manifest

**Returns:**

manifest

---

## getTimeMapper

```
public DvrTimeMapper getTimeMapper()
```

Get time mapper, which maps between DVR, real and packet time.

**Returns:**

(continued from last page)

time mapper

---

## getPurgeController

```
public IDvrPurgeController getPurgeController()
```

Get purge controller for stream store.

**Returns:**

purge controller

---

## getFileSystem

```
public IDvrFileSystem getFileSystem()
```

---

## getChunker

```
public IDvrChunker getChunker()
```

---

## canRecord

```
public boolean canRecord()
```

Is this store capable of recording.

**Returns:**

true if store can record

---

## isLoaded

```
public boolean isLoaded()
```

---

## setCanRecord

```
public void setCanRecord(boolean canRecord)
```

Set the Stream Stores ability to record.

Note: Must be called when stream is not recording.

**Parameters:**

canRecord

---

## canPlay

```
public boolean canPlay()
```

Is this store capable of playing.

**Returns:**

true if store can play

---

## setCanPlay

```
public void setCanPlay(boolean canPlay)
```

Set the Stream Stores ability to play.

Note: Must be called when stream is not playing.

**Parameters:**

canPlay

---

## setHasEncryption

```
public void setHasEncryption(boolean hasEncryption)
```

Set whether the store has encryption. Used internally.

Note: Must be called when stream is not playing.

**Parameters:**

hasEncryption - if store has encryption

---

## hasEncryption

```
public boolean hasEncryption()
```

Does this store contain encryption information

**Returns:**

true if store contains encryption

---

## hasVideo

```
public boolean hasVideo()
```

Does this store have video.

**Returns:**

true if store contains video, false otherwise.

---

## hasAudio

```
public boolean hasAudio()
```

Does this store have audio.

**Returns:**

true if store contains audio, false otherwise.

---

## hasData

```
public boolean hasData()
```

Does this store have data.

**Returns:**

true if store contains data, false otherwise.

---

(continued from last page)

## hasOnMetadata

```
public boolean hasOnMetadata( )
```

Does this store have on metadata.

**Returns:**

true if store contains on metadata, false otherwise.

---

## startRecording

```
public boolean startRecording( )
```

Request that recording start.

Used internally. Clients should call [ILiveStreamDvrRecorder.startRecording\(\)](#).

Success occurs if the stream canRecord [canRecord\(\)](#) and the stream is not already in the recording state [isRecording\(\)](#).

**Returns:**

true if successful.

---

## pauseRecording

```
public boolean pauseRecording( )
```

Request that stream recording pause.

Used internally. Clients should call [ILiveStreamDvrRecorder.pauseRecording\(\)](#).

Success occurs if the stream is not already paused.

**Returns:**

true if successful.

---

## resumeRecording

```
public boolean resumeRecording( )
```

Request that stream recording resume.

Used internally. Clients should call [ILiveStreamDvrRecorder.resumeRecording\(\)](#).

Success occurs if the stream was previously paused.

**Returns:**

true if successful.

---

## stopRecording

```
public boolean stopRecording( )
```

Request that stream recording stop. This shuts down saving of chunks

Used internally. Clients should call [ILiveStreamDvrRecorder.stopRecording\(\)](#).

Success only occurs if the stream is already in the recording state [isRecording\(\)](#).

**Returns:**

true if successful.

---



## isRecordingPaused

```
public boolean isRecordingPaused()
```

Is store currently paused while recording.

**Returns:**

true if recording is paused.

---

## isRecording

```
public boolean isRecording()
```

Is store currently recording. This will always be false for an edge.

**Returns:**

true if recording

---

## isLive

```
public boolean isLive()
```

Is store currently live For an origin, [isRecording\(\)](#) and [isLive\(\)](#) will typically return the same result. On an origin, [isRecording\(\)](#) will always be false. But [isLive\(\)](#) will reflect the status of the repeated stream.

**Returns:**

true if live

---

## storeChunks

```
public DvrChunkStorageInfo storeChunks(int vDuration,  
    DvrPacketHolder vPackets,  
    int aDuration,  
    DvrPacketHolder aPackets,  
    int dDuration,  
    DvrPacketHolder dPackets)
```

---

## storeOnMetadata

```
public boolean storeOnMetadata(long pt,  
    long utc,  
    AMFPacket metaPacket)
```

---

## purgeEntries

```
public void purgeEntries(DvrManifestEntryRangeGroup rangeGroup)
```

Purge entries from store

**Parameters:**

rangeGroup - s set of ranges for purging

---

(continued from last page)

---

## addManifestEntries

```
public void addManifestEntries(java.util.List entries)
```

---

## addDvrChunkListener

```
public void addDvrChunkListener(IDvrStoreChunkListener listener)
```

Add (very fine) listener for chunk events.

**Parameters:**

listener - listener

---

## removeDvrChunkListener

```
public void removeDvrChunkListener(IDvrStoreChunkListener listener)
```

Remove (very fine) listener for chunk events.

**Parameters:**

listener - listener

---

## getRecordedEntriesWithLimit

```
public java.util.List getRecordedEntriesWithLimit(int fragmentType,  
    long t,  
    int limit)
```

---

## getRecordedEntryByIndex

```
public DvrManifestEntry getRecordedEntryByIndex(int fragmentType,  
    int index)
```

---

## getRecordedEntryByTime

```
public DvrManifestEntry getRecordedEntryByTime(int fragmentType,  
    long t)
```

---

## getDvrChunkByIndex

```
public DvrChunk getDvrChunkByIndex(int fragmentType,  
    int index)
```

---

## getDvrChunkAtTime

```
public DvrChunk getDvrChunkAtTime(int fragmentType,  
    long t)
```

---

---

### **getDvrChunkNearTime**

```
public DvrChunk getDvrChunkNearTime(int fragmentType,  
    long t,  
    long delta)
```

---

### **getClosestStartTime**

```
public long getClosestStartTime(int type,  
    long t)
```

## com.wowza.wms.dvr Interface IDvrStreamVersionHandler

All Known Implementing Classes:  
[DefaultDvrStreamVersionHandler](#)

public interface **IDvrStreamVersionHandler**  
 extends

Callback to manage (archival) versions of DVR stream stores

### Method Summary

<a href="#">IDvrStreamStore</a>	<a href="#">determineExistingStoreForPlaying</a> ( <a href="#">IDvrStreamManager</a> dvrManager, String baseStreamName) When a session requests a stream store w/o specifying the version, we need gto determine the version of the stream to store.
<a href="#">IDvrStreamStore</a>	<a href="#">determineExistingStoreForRecording</a> ( <a href="#">IDvrStreamManager</a> dvrManager, String baseStreamName) After a set of versioned streams are loaded from disk, one of them may be designated the stream that will be recorded to (i.e.
String	<a href="#">getArchiveStrategy</a> ( <a href="#">IDvrStreamManager</a> dvrManager, String baseStreamName) Determine the archive strategy for a given set of streams.
boolean	<a href="#">handleArchivedStream</a> ( <a href="#">IDvrStreamManager</a> dvrManager, String baseStreamName, String version, java.util.SortedSet versions, DvrManifestHolder manifest) When a stream group inits, the file system is checked for older versions of the streams.
boolean	<a href="#">shouldDeleteArchivedStream</a> ( <a href="#">IDvrStreamManager</a> dvrManager, <a href="#">IDvrStreamStore</a> store) Determine if a given stream store version should be deleted.
boolean	<a href="#">shouldLoadArchivedStream</a> ( <a href="#">IDvrStreamManager</a> dvrManager, String baseStreamName, String version, java.util.SortedSet versions, DvrManifestHolder manifest) Determine if a given stream store version should be loaded into WMS.

### Methods

#### determineExistingStoreForRecording

```
public IDvrStreamStore determineExistingStoreForRecording(IDvrStreamManager
dvrManager,
    String baseStreamName)
```

After a set of versioned streams are loaded from disk, one of them may be designated the stream that will be recorded to (i.e. append mode).

The default implementation says that if append mode, then the highest versioned stream that has canRecord set to true is used. But this API, allows for a more detailed logic.

#### Parameters:

dvrManager - The DVR Stream Manager

(continued from last page)

baseStreamName - The base stream name (no version info). e.g. myStream

**Returns:**

stream store to append to, null if no stream in the stream group is to be appended to.

**See Also:**

[DefaultDvrStreamVersionHandler](#)

## determineExistingStoreForPlaying

```
public IDvrStreamStore determineExistingStoreForPlaying(IDvrStreamManager dvrManager,
String baseStreamName)
```

When a session requests a stream store w/o specifying the version, we need to determine the version of the stream to store.

The default implementation first checks the recording stream. If it 'canPlay()', it is returned. Otherwise, the highest versioned stream that canRecord set to true is used.

**Parameters:**

dvrManager - The DVR Stream Manager

baseStreamName - The base stream name (no version info). e.g. myStream

**Returns:**

stream store to stream, null if no stream in the stream group can be played.

**See Also:**

[DefaultDvrStreamVersionHandler](#)

## getArchiveStrategy

```
public String getArchiveStrategy(IDvrStreamManager dvrManager,
String baseStreamName)
```

Determine the archive strategy for a given set of streams.

Typically, this returns the archive strategy as specified in Application.xml, but this API provides a hook for more detailed logic in determining the strategy.

**Parameters:**

dvrManager - The DVR App Instance Manager

baseStreamName - The base stream name (no version info). e.g. myStream

**Returns:**

the archive strategy

**See Also:**

[DefaultDvrStreamVersionHandler](#)

[IDvrConstants.ARCHIVE\\_STRATEGY\\_APPEND](#)

[IDvrConstants.ARCHIVE\\_STRATEGY\\_DELETE](#)

[IDvrConstants.ARCHIVE\\_STRATEGY\\_VERSION](#)

## handleArchivedStream

```
public boolean handleArchivedStream(IDvrStreamManager dvrManager,
String baseStreamName,
String version,
java.util.SortedSet versions,
DvrManifestHolder manifest)
```

(continued from last page)

When a stream group inits, the file system is checked for older versions of the streams. This method is called to handle the streams.

Typically, 3 things can happen: The stream is ignored, loaded, or deleted.

**Parameters:**

dvrManager - The DVR Stream Manager  
baseStreamName - The base stream name (no version info). e.g. myStream  
version - The version of the stream to be loaded.  
versions - A sorted set of all the versions that are attempting to be loaded  
manifest - The main manifest info of the stream

**Returns:**

true if handled in some manner, false if ignored (unhandled)

**See Also:**

[DefaultDvrStreamVersionHandler](#)

---

## shouldLoadArchivedStream

```
public boolean shouldLoadArchivedStream(IDvrStreamManager dvrManager,  
    String baseStreamName,  
    String version,  
    java.util.SortedSet versions,  
    DvrManifestHolder manifest)
```

Determine if a given stream store version should be loaded into WMS.

**Parameters:**

dvrManager - The DVR Stream Manager  
baseStreamName - The base stream name (no version info). e.g. myStream  
version - The version of the stream to be loaded.  
versions - A sorted set of all the versions that are attempting to be loaded  
manifest - The main manifest info of the stream

**Returns:**

true if should be loaded. false if not.

**See Also:**

[DefaultDvrStreamVersionHandler](#)

---

## shouldDeleteArchivedStream

```
public boolean shouldDeleteArchivedStream(IDvrStreamManager dvrManager,  
    IDvrStreamStore store)
```

Determine if a given stream store version should be deleted.

**Parameters:**

dvrManager - The DVR Stream Manager  
store - The DVR store

**Returns:**

true if should be deleted. false if not.

**See Also:**

[DefaultDvrStreamVersionHandler](#)

## com.wowza.wms.dvr Interface IDvrTextReader

public interface **IDvrTextReader**  
extends [ITextReader](#)

### Method Summary

void	<a href="#">init</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaStream</a> stream, <a href="#">IDvrFileSystem</a> fileSystem, String artifactName)
------	---

#### Methods inherited from interface [com.wowza.io.ITextReader](#)

[close](#), [exists](#), [getBasePath](#), [getMediaName](#), [getPath](#), [init](#), [isOpen](#), [lastModified](#), [length](#), [open](#), [read](#), [ready](#)

### Methods

#### **init**

```
public void init(IApplicationInstance appInstance,  
                IMediaStream stream,  
                IDvrFileSystem fileSystem,  
                String artifactName)
```

## com.wowza.wms.dvr Interface IDvrTextWriter

public interface **IDvrTextWriter**  
extends `ITextWriter`

### Method Summary

void	<code><a href="#">init</a>(<a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaStream</a> stream, <a href="#">IDvrFileSystem</a> fileSystem, String artifactName)</code>
------	--

#### Methods inherited from interface `com.wowza.io.ITextWriter`

`close`, `exists`, `getBasePath`, `getMediaName`, `getPath`, `init`, `isAppend`, `isOpen`, `lastModified`, `length`, `open`, `setAppend`, `write`, `write`, `write`, `write`

### Methods

#### **init**

```
public void init(IApplicationInstance appInstance,  
                 IMediaStream stream,  
                 IDvrFileSystem fileSystem,  
                 String artifactName)
```



## com.wowza.wms.dvr Interface IDvrTimeMap

All Superinterfaces:

[IDvrChannelManifest](#)

public interface **IDvrTimeMap**

extends [IDvrChannelManifest](#)

### Method Summary

boolean	<a href="#">containsTime</a> (long startTime, <a href="#">IDvrConstants.DvrTimeScale</a> timeScale)
long	<a href="#">dvrToPt</a> (long dt)
long	<a href="#">dvrToUtc</a> (long dt)
java.util.List	<a href="#">getTimeMap</a> ()
java.util.List	<a href="#">getTimeMapEntries</a> ()
long	<a href="#">ptToDvr</a> (long pt)
long	<a href="#">toDvr</a> (long t, <a href="#">IDvrConstants.DvrTimeScale</a> timeScale)
long	<a href="#">utcToDvr</a> (long utc)

### Methods inherited from interface [com.wowza.wms.dvr.IDvrChannelManifest](#)

[expandEndTime](#), [expandStartTime](#), [getClosestStartTime](#), [getFirstEntry](#), [getFirstIndex](#), [getIndexMap](#), [getLastLiveEntry](#), [getLastRecordedEntry](#), [getLastRecordedIndex](#), [getLiveDuration](#), [getLiveEntries](#), [getLiveEntries](#), [getLiveEntriesWithLimit](#), [getLiveRangeEndingBeforeTime](#), [getLiveRangeEndingBeforeTime](#), [getLiveTailEntries](#), [getNumberLiveEntries](#), [getNumberLiveEntries](#), [getNumberRecordedEntries](#), [getNumberRecordedEntries](#), [getRecordedDuration](#), [getRecordedEntries](#), [getRecordedEntries](#), [getRecordedEntries](#), [getRecordedEntriesInRange](#), [getRecordedEntriesWithLimit](#), [getRecordedEntryByIndex](#), [getRecordedEntryByTimeKey](#), [getRecordedEntryStartingBeforeTime](#), [getType](#), [isEmpty](#)

### Methods

#### getTimeMap

public java.util.List **getTimeMap**()

(continued from last page)

---

## getTimeMapEntries

```
public java.util.List getTimeMapEntries()
```

---

## dvrToUtc

```
public long dvrToUtc(long dt)
```

---

## dvrToPt

```
public long dvrToPt(long dt)
```

---

## ptToDvr

```
public long ptToDvr(long pt)
```

---

## utcToDvr

```
public long utcToDvr(long utc)
```

---

## toDvr

```
public long toDvr(long t,  
    IDvrConstants.DvrTimeScale timeScale)
```

---

## containsTime

```
public boolean containsTime(long startTime,  
    IDvrConstants.DvrTimeScale timeScale)
```

---

---

Package

**com.wowza.wms.http**

## com.wowza.wms.http Class HTTPProvider2Base

java.lang.Object

└─com.wowza.wms.http.HTTPProvider2Base

All Implemented Interfaces:

[IHTTPProvider2](#)

Direct Known Subclasses:

[HTTPLiveStreamRecord](#)

---

public abstract class **HTTPProvider2Base**  
extends Object  
implements [IHTTPProvider2](#)

HTTPProvider2Base: base class for implementing HTTP Providers.

### Simple HTTPProvider class

```
public class HTTPHelloWowza extends HTTPProvider2Base
{
    public void onHTTPRequest(IVHost vhost, IHTTPRequest req, IHTTPResponse resp)
    {
        if (!doHTTPAuthentication(vhost, req, resp))
            return;

        String retStr = "<head><title>Hello Wowza</title></head><body>Hello
Wowza</body>";
        try
        {
            OutputStream out = resp.getOutputStream();
            byte[] outBytes = retStr.getBytes();
            out.write(outBytes);
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(HTTPHelloWowza.class).error("HTTPHelloWowza: "+e.toString());
        }
    }
}
```

---

## Field Summary

protected	<a href="#">authenticateHandler</a>
protected	<a href="#">authenticateHTTPProviderHandler</a>
protected	<a href="#">authenticationMethod</a>
protected	<a href="#">filters</a>
protected	<a href="#">properties</a>
protected	<a href="#">requestFilters</a>

## Constructor Summary

public	<a href="#">HTTPProvider2Base()</a>
--------	-------------------------------------

## Method Summary

boolean	<a href="#">canHandle</a> (String path) Return true if can handle the request
boolean	<a href="#">doHTTPAuthentication</a> ( <a href="#">IVHost</a> vhost, <a href="#">IHTTPRequest</a> req, <a href="#">IHTTPResponse</a> resp) Handle authentication request
String	<a href="#">getAuthenticationMethod</a> () Get the authentication method: digest, basic, none...
String	<a href="#">getPath</a> ( <a href="#">IHTTPRequest</a> req, boolean removeFilter) Get the request path
String	<a href="#">getRequestFilters</a> () Get the request filter
void	<a href="#">init</a> () Initialize the HTTPProvider
void	<a href="#">onBind</a> ( <a href="#">IVHost</a> vhost, <a href="#">HostPort</a> hostPort) Called when bind is called on port
void	<a href="#">onUnbind</a> ( <a href="#">IVHost</a> vhost, <a href="#">HostPort</a> hostPort) Called when unbind is called on port
void	<a href="#">setAuthenticationMethod</a> (String authenticationMethod) Set authentication method: digest, basic, none...
void	<a href="#">setProperties</a> ( <a href="#">WMSProperties</a> properties) Set properties
void	<a href="#">setRequestFilters</a> (String requestFilters) Set the request filter

Methods inherited from class `java.lang.Object`

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.http.IHTTPProvider2](#)

[canHandle](#), [getAuthenticationMethod](#), [getRequestFilters](#), [init](#), [setAuthenticationMethod](#), [setRequestFilters](#)

Methods inherited from interface [com.wowza.wms.http.IHTTPProvider](#)

[onBind](#), [onHTTPRequest](#), [onUnbind](#), [setProperties](#)

## Fields

### properties

protected com.wowza.wms.application.WMSProperties **properties**

### filters

protected java.util.List **filters**

### requestFilters

protected java.lang.String **requestFilters**

### authenticateHandler

protected com.wowza.wms.authentication.IAuthenticate **authenticateHandler**

### authenticateHTTPProviderHandler

protected com.wowza.wms.authentication.IAuthenticateHTTPProvider  
**authenticateHTTPProviderHandler**

### authenticationMethod

protected java.lang.String **authenticationMethod**

## Constructors

(continued from last page)

## HTTPProvider2Base

```
public HTTPProvider2Base()
```

## Methods

### init

```
public void init()
```

Initialize the HTTPProvider

### canHandle

```
public boolean canHandle(String path)
```

Return true if can handle the request

**Parameters:**

path - request path

**Returns:**

true, if can handle the request

### getPath

```
public String getPath(IHTTPRequest req,  
    boolean removeFilter)
```

Get the request path

**Parameters:**

req - request

removeFilter - set to true to remove filter part of URL

**Returns:**

path

### setRequestFilters

```
public void setRequestFilters(String requestFilters)
```

Set the request filter

**Parameters:**

requestFilters - request filter

### getRequestFilters

```
public String getRequestFilters()
```

Get the request filter

**Returns:**

request filter

## setProperty

```
public void setProperty(WMSProperties properties)
```

Set properties

**Parameters:**

properties - properties

---

## onBind

```
public void onBind(IVHost vhost,  
    HostPort hostPort)
```

Called when bind is called on port

**Parameters:**

vhost - vhost

hostPort - host port

---

## onUnbind

```
public void onUnbind(IVHost vhost,  
    HostPort hostPort)
```

Called when unbind is called on port

**Parameters:**

vhost - vhost

hostPort - host port

---

## getAuthenticationMethod

```
public String getAuthenticationMethod()
```

Get the authentication method: digest, basic, none...

**Returns:**

authentication method

---

## setAuthenticationMethod

```
public void setAuthenticationMethod(String authenticationMethod)
```

Set authentication method: digest, basic, none...

**Parameters:**

authenticationMethod - authentication method

---

## doHTTPAuthentication

```
public boolean doHTTPAuthentication(IVHost vhost,  
    HttpRequest req,  
    HttpResponse resp)
```

Handle authentication request

**Parameters:**

---



(continued from last page)

vhost - vhost  
req - request  
resp - response

**Returns:**

true, if request should be handled by the HTTPProvider subclass

## com.wowza.wms.http Interface IHTTPProvider

All Subinterfaces:

[IHTTPProvider2](#)

public interface **IHTTPProvider**  
extends

IHTTPProvider: HTTP provider class for a given HostPort definition. Receive all HTTP requests that are not RTMPT requests. See IHTTPProvider2 for the extended version of this interface.

### Method Summary

void	<a href="#">onBind</a> ( <a href="#">IVHost</a> vhost, <a href="#">HostPort</a> hostPort) Triggered after hostPort binds to socket
void	<a href="#">onHTTPRequest</a> ( <a href="#">IVHost</a> vhost, <a href="#">IHTTPRequest</a> req, <a href="#">IHTTPResponse</a> resp) Triggered for each HTTP request to the given hostPort that is not an RTMPT request.
void	<a href="#">onUnbind</a> ( <a href="#">IVHost</a> vhost, <a href="#">HostPort</a> hostPort) Triggered after hostPort unbinds
void	<a href="#">setProperties</a> ( <a href="#">WMSProperties</a> properties) Called to provide properties set in configuration files

### Methods

#### onBind

```
public void onBind(IVHost vhost,  
                   HostPort hostPort)
```

Triggered after hostPort binds to socket

**Parameters:**

vhost - parent vhost  
hostPort - host port definition

#### onHTTPRequest

```
public void onHTTPRequest(IVHost vhost,  
                           IHTTPRequest req,  
                           IHTTPResponse resp)
```

Triggered for each HTTP request to the given hostPort that is not an RTMPT request.

**Parameters:**

vhost - parent vhost  
req - HTML request object  
resp - HTML response object

---

## onUnbind

```
public void onUnbind(IVHost vhost,  
    HostPort hostPort)
```

Triggered after hostPort unbinds

### Parameters:

vhost - parent vhost

hostPort - host port definition

---

## setProperties

```
public void setProperties(WMSProperties properties)
```

Called to provide properties set in configuration files

## com.wowza.wms.http Interface IHTTPProvider2

All Superinterfaces:

[IHTTPProvider](#)

All Known Implementing Classes:

[HTTPProvider2Base](#)

---

public interface **IHTTPProvider2**  
extends [IHTTPProvider](#)

IHTTPProvider2: Extension of IHTTPProvider that adds support for multiple HTTPProviders attached to a single HostPort along with authentication. Multiple HTTPProviders can be added to a HostPort definition. They are configured as follows:

```
<HTTPProvider>
  <BaseClass>com.wowza.wms.http.HTTPServerVersion</BaseClass>
  <RequestFilters>*serverversion</RequestFilters>
  <AuthenticationMethod>none</AuthenticationMethod>
</HTTPProvider>
```

Below is an sample implementation of the HTTPServerVersion provider:

```

import java.io.*;

import com.wowza.wms.server.*;
import com.wowza.wms.stream.*;
import com.wowza.wms.vhost.*;
import com.wowza.wms.logging.*;

public class HTTPServerVersion extends HTTPProvider2Base
{
    public void onHTTPRequest(IVHost vhost, IHTTPRequest req, IHTTPResponse resp)
    {
        if (!doHTTPAuthentication(vhost, req, resp))
            return;

        String version = MediaStreamBase.p+" "+ReleaseInfo.getVersion()+"
build"+ReleaseInfo.getBuildNumber();
        String retStr =
"<html><head><title>"+version+"</title></head><body>"+version+"</body></html>";
        try
        {
            OutputStream out = resp.getOutputStream();
            byte[] outBytes = retStr.getBytes();
            out.write(outBytes);
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(HTTPServerVersion.class).error("HTMLServerVersion:
"+e.toString());
        }
    }
}

```

## Method Summary

boolean	<a href="#">canHandle</a> (String path)
String	<a href="#">getAuthenticationMethod</a> ()
String	<a href="#">getRequestFilters</a> ()
void	<a href="#">init</a> ()
void	<a href="#">setAuthenticationMethod</a> (String authenticationMethod)
void	<a href="#">setRequestFilters</a> (String requestFilters)

---

Methods inherited from interface [com.wowza.wms.http.IHTTPProvider](#)

[onBind](#), [onHTTPRequest](#), [onUnbind](#), [setProperties](#)

---

## Methods

### canHandle

```
public boolean canHandle(String path)
```

---

### setRequestFilters

```
public void setRequestFilters(String requestFilters)
```

---

### getRequestFilters

```
public String getRequestFilters()
```

---

### init

```
public void init()
```

---

### getAuthenticationMethod

```
public String getAuthenticationMethod()
```

---

### setAuthenticationMethod

```
public void setAuthenticationMethod(String authenticationMethod)
```

---

## com.wowza.wms.http Interface IHTTPRequest

public interface **IHTTPRequest**  
extends

### Method Summary

int	<a href="#"><u>getContentLength()</u></a> Get the content length of the body of the message
String	<a href="#"><u>getContentType()</u></a> Get the request content type
String	<a href="#"><u>getHeader(String name)</u></a> Get a HTTP header value such as 'Content-Length'
byte[]	<a href="#"><u>getHeaderBytes()</u></a> Returns the header as bytes
java.util.Map	<a href="#"><u>getHeaderMap()</u></a> Get a copy of the HTTP request header map
java.util.Set	<a href="#"><u>getHeaderNames()</u></a> Get a Set of the header names
java.io.InputStream	<a href="#"><u>getInputStream()</u></a> Get the body of the message as an input stream
int	<a href="#"><u>getIntHeader(String name)</u></a> Get a HTTP header value such as 'Content-Length' and return as int
java.util.Locale	<a href="#"><u>getLocale()</u></a> Get locale of request (Example: en-us)
String	<a href="#"><u>getMethod()</u></a> Get the method invocation method: GET, POST, HEAD
byte[]	<a href="#"><u>getMsgBytes()</u></a> Return the message bytes
String	<a href="#"><u>getParameter(String name)</u></a> Get a parameter value
java.util.Map	<a href="#"><u>getParameterMap()</u></a> Get the entire parameter Map
java.util.Set	<a href="#"><u>getParameterNames()</u></a> Get a Set of parameter names
String[]	<a href="#"><u>getParameterValues(String name)</u></a> Get a multi-value parameter as an array of String
String	<a href="#"><u>getPath()</u></a> Returns the HTTP path element of the request

String	<a href="#"><code>getProtocol()</code></a> Get the request protocol (example: HTTP/1.1)
String	<a href="#"><code>getQueryString()</code></a> Get the query string part of the url (everything after the ?)
String	<a href="#"><code>getRemoteAddr()</code></a> Get the remote ip address of the request
String	<a href="#"><code>getRemoteHost()</code></a> Get the remote host name (if known) if not return ip address
String	<a href="#"><code>getRequestURI()</code></a> Get the full request URI
String	<a href="#"><code>getRequestURL()</code></a> Get the request url (same as URI minus the query string)
String	<a href="#"><code>getScheme()</code></a> Get the request scheme (Example "http")
String	<a href="#"><code>getServerName()</code></a> Get the name of the server (Example: "Wowza Media Server Pro")
int	<a href="#"><code>getServerPort()</code></a> Get the port this request was received on
boolean	<a href="#"><code>isHeadRequest()</code></a> Returns true if the request is a HEAD request
boolean	<a href="#"><code>isSecure()</code></a> Returns true is the request is protected by SSL
void	<a href="#"><code>parseBodyForParams()</code></a> If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.
void	<a href="#"><code>parseBodyForParams(boolean doDecode)</code></a> If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.

## Methods

### getHeaderMap

```
public java.util.Map getHeaderMap()
```

Get a copy of the HTTP request header map

**Returns:**

copy of the HTTP request header map

### getHeader

```
public String getHeader(String name)
```

Get a HTTP header value such as 'Content-Length'



(continued from last page)

**Parameters:**

name - header name

**Returns:**

header value

---

## getIntHeader

```
public int getIntHeader(String name)
```

Get a HTTP header value such as 'Content-Length' and return as int

**Parameters:**

name - header name

**Returns:**

header value

---

## getHeaderNames

```
public java.util.Set getHeaderNames()
```

Get a Set of the header names

**Returns:**

Set of header names

---

## getMethod

```
public String getMethod()
```

Get the method invocation method: GET, POST, HEAD

**Returns:**

method

---

## getQueryString

```
public String getQueryString()
```

Get the query string part of the url (everything after the ?)

**Returns:**

query string

---

## getContentLength

```
public int getContentLength()
```

Get the content length of the body of the message

**Returns:**

content length of the body of the message

---

## getRequestURI

```
public String getRequestURI()
```

(continued from last page)

Get the full request URI

**Returns:**

full request URI

---

## getRequestURL

```
public String getRequestURL()
```

Get the request url (same as URI minus the query string)

**Returns:**

request url

---

## getContentType

```
public String getContentType()
```

Get the request content type

**Returns:**

request content type

---

## parseBodyForParams

```
public void parseBodyForParams(boolean doDecode)
```

If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.

**Parameters:**

doDecode - true to decode the params as though they are url params

---

## parseBodyForParams

```
public void parseBodyForParams()
```

If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.

---

## getParameter

```
public String getParameter(String name)
```

Get a parameter value

**Parameters:**

name - parameter name

**Returns:**

parameter value

---

## getParameterNames

```
public java.util.Set getParameterNames()
```

Get a Set of parameter names

(continued from last page)

**Returns:**

Set of parameter names

---

## getParameterValues

```
public String[] getParameterValues(String name)
```

Get a multi-value parameter as an array of String

**Parameters:**

name - parameter name

**Returns:**

multi-value parameter as an array of String

---

## getParameterMap

```
public java.util.Map getParameterMap()
```

Get the entire parameter Map

**Returns:**

parameter Map

---

## getInputStream

```
public java.io.InputStream getInputStream()
```

Get the body of the message as an input stream

**Returns:**

body of the message as an input stream

---

## getProtocol

```
public String getProtocol()
```

Get the request protocol (example: HTTP/1.1)

**Returns:**

request protocol

---

## getScheme

```
public String getScheme()
```

Get the request scheme (Example "http")

**Returns:**

request scheme

---

## getServerName

```
public String getServerName()
```

Get the name of the server (Example: "Wowza Media Server Pro")

**Returns:**

(continued from last page)

name of the server

---

## getServerPort

```
public int getServerPort()
```

Get the port this request was received on

**Returns:**

the port this request was received on

---

## getRemoteAddr

```
public String getRemoteAddr()
```

Get the remote ip address of the request

**Returns:**

remote ip address of the request

---

## getRemoteHost

```
public String getRemoteHost()
```

Get the remote host name (if known) if not return ip address

**Returns:**

remote host name

---

## getLocale

```
public java.util.Locale getLocale()
```

Get locale of request (Example: en-us)

**Returns:**

locale of request

---

## isSecure

```
public boolean isSecure()
```

Returns true is the request is protected by SSL

**Returns:**

true is the request is protected by SSL

---

## getPath

```
public String getPath()
```

Returns the HTTP path element of the request

**Returns:**

HTTP path element of the request

---

(continued from last page)

## getHeaderBytes

```
public byte[] getHeaderBytes()
```

Returns the header as bytes

**Returns:**

header as bytes

---

## getMsgBytes

```
public byte[] getMsgBytes()
```

Return the message bytes

**Returns:**

message bytes

---

## isHeadRequest

```
public boolean isHeadRequest()
```

Returns true if the request is a HEAD request

**Returns:**

true if the request is a HEAD request

---

## com.wowza.wms.http Interface IHTTPResponse

public interface **IHTTPResponse**  
extends

### Method Summary

boolean	<a href="#"><code>containsHeader</code></a> (String name) Returns true if response header contains parameter name
String	<a href="#"><code>getHeader</code></a> (String name) Get header value
java.util.Map	<a href="#"><code>getHeaders</code></a> () Get the current response headers as a map
int	<a href="#"><code>getHeaderSize</code></a> () Get the size in bytes of the HTTP header
int	<a href="#"><code>getIntHeader</code></a> (String name) Get header value as int
java.io.OutputStream	<a href="#"><code>getOutputStream</code></a> () Get the output stream for the response.
boolean	<a href="#"><code>isHeadResponse</code></a> () returns true if the response is due to a HEAD request
void	<a href="#"><code>removeHeader</code></a> (String name) Remove header value
void	<a href="#"><code>setHeader</code></a> (String name, String value) Set header value
void	<a href="#"><code>setHeadResponse</code></a> (boolean isHeadResponse) indicates if the response is a response to a HEAD request
void	<a href="#"><code>setIntHeader</code></a> (String name, int value) Set header value as int
void	<a href="#"><code>setResponseCode</code></a> (int responseCode) Set the HTTP response code

### Methods

#### **getOutputStream**

public java.io.OutputStream **getOutputStream**()

Get the output stream for the response. You can then write directly into the output stream.

(continued from last page)

**Returns:**output stream for the response

---

**containsHeader**

```
public boolean containsHeader(String name)
```

Returns true if response header contains parameter name

**Parameters:**

name - header parameter name

**Returns:**true if header contains value

---

**setHeader**

```
public void setHeader(String name,  
                      String value)
```

Set header value

**Parameters:**

name - header parameter name

value - parameter value

---

**removeHeader**

```
public void removeHeader(String name)
```

Remove header value

**Parameters:**name - name

---

**setIntHeader**

```
public void setIntHeader(String name,  
                        int value)
```

Set header value as int

**Parameters:**

name - header parameter name

value - parameter value

---

**getHeaders**

```
public java.util.Map getHeaders()
```

Get the current response headers as a map

**Returns:**current response headers as a map

---

**getHeader**

```
public String getHeader(String name)
```

---

(continued from last page)

Get header value

**Parameters:**

name - header parameter name

**Returns:**

parameter value

---

## getIntHeader

```
public int getIntHeader(String name)
```

Get header value as int

**Parameters:**

name - header parameter name

**Returns:**

parameter value

---

## setResponseCode

```
public void setResponseCode(int responseCode)
```

Set the HTTP response code

**Parameters:**

responseCode - HTTP response code

---

## getHeaderSize

```
public int getHeaderSize()
```

Get the size in bytes of the HTTP header

**Returns:**

header size in bytes

---

## setHeadResponse

```
public void setHeadResponse(boolean isHeadResponse)
```

indicates if the response is a response to a HEAD request

**Parameters:**

isHeadResponse - indicating if this is a response to a HEAD request

---

## isHeadResponse

```
public boolean isHeadResponse()
```

returns true if the response is due to a HEAD request

**Returns:**

true if the response is due to a HEAD request

---



---

Package

**com.wowza.wms.httpstreamer.cupertinostrea  
ming.httpstreamer**

## com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer Class HTTPStreamerSessionCupertino

java.lang.Object

└─ com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer.HTTPStreamerSessionCupertino

All Implemented Interfaces:

[IHTTPSessionNotify](#), [IHTTPStreamerSession](#)

public class **HTTPStreamerSessionCupertino**  
 extends HTTPStreamerSessionBase  
 implements [IHTTPStreamerSession](#), [IHTTPSessionNotify](#)

### Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isHTTPOrigin, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, notifyCreate, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, transcoderVODIndex, transcoderVODIndexDestinationsMap, transcoderVODIndexDestinationsOrder, transcoderVODSession, uri, userAgent, userHTTPHeaders, userQueryStr, vhost, vodTranscodeNGRP

### Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL\\_COUNT](#), [SESSIONPROTOCOL\\_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL\\_DIRECTSTREAMING](#), [SESSIONPROTOCOL\\_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL\\_MPEGDASHSTREAMING](#), [SESSIONPROTOCOL\\_SANJOSESTREAMING](#), [SESSIONPROTOCOL\\_SMOOTHSTREAMING](#), [SESSIONPROTOCOL\\_UNKNOWN](#), [SESSIONPROTOCOL\\_WEBMSTREAMING](#), [SESSIONTYPE\\_LIVE](#), [SESSIONTYPE\\_LIVEDVR](#), [SESSIONTYPE\\_UNKNOWN](#), [SESSIONTYPE\\_VOD](#)

## Constructor Summary

public	<a href="#">HTTPStreamerSessionCupertino()</a>
--------	--

## Method Summary

void	<a href="#">clearLoggingValues()</a>
boolean	<a href="#">containsIndex</a> (String streamName)
IHTTPStreamerCupertinoIndex	<a href="#">getIndex</a> ( <a href="#">IHTTPStreamerApplicationContext</a> appContext, <a href="#">IHTTPStreamerSession</a> httpStreamerSession, String rawStreamName, String streamExt, String streamName, long playStart, long playDuration, TimedTextRequest captionRequest, String vodTranscodeNGRP)

void	<a href="#">indexTranscoderVOD</a> ( <a href="#">IHTTPStreamerApplicationContext</a> appContext, String vodTranscodeNGRP)
void	<a href="#">logLiveChunk</a> (LiveStreamPacketizerCupertinoChunk chunk)
void	<a href="#">logVODChunk</a> (LiveStreamPacketizerCupertinoChunk chunk)
void	<a href="#">notifyHTTPSessionCreate</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IHTTPStreamerSession</a> httpStreamerSession)
void	<a href="#">notifyHTTPSessionDestroy</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IHTTPStreamerSession</a> httpStreamerSession)
void	<a href="#">shutdown</a> ()
void	<a href="#">updateLoggingValues</a> ()

#### Methods inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr, addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues, containsStreamDomainStr, containsStreamNameParts, doSessionRedirect, doSessionRedirect, extractHTTPRequestInfo, getAndClearNotifyCreate, getAppInstance, getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo, getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader, getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest, getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties, getQueryStr, getRedirectSessionBody, getRedirectSessionCode, getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp, getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType, getStream, getStreamDomainStr, getStreamDomainStrList, getStreamExt, getStreamName, getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds, getTranscoderVODIndex, getTranscoderVODIndex, getTranscoderVODIndexDestinationsMap, getTranscoderVODIndexDestinationsOrder, getTranscoderVODSession, getUri, getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, getVODTranscodeNGRP, indexTranscoderVOD, isAcceptSession, isActive, isFileInfo, isHTTPOrigin, isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated, isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts, redirectSession, redirectSession, rejectSession, removeStreamDomainStr, setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo, setHTTPOrigin, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer, setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession, setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType, setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId, setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt, setStreamName, setStreamPosition, setThreadContext, setTimeoutSession, setTranscoderVODIndex, setTranscoderVODSession, setUri, setUserAgent, setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, setVODTranscodeNGRP, shutdown, shutdownLocked, touch, updateLoggingValues, validStreamDomainToString

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),  
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),  
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),  
[doSessionRedirect](#), [extractHTTPRequestInfo](#), [getAndClearNotifyCreate](#), [getAppInstance](#),  
[getConnectionHolder](#), [getCookieStr](#), [getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#),  
[getHTTPHeader](#), [getHTTPHeaderMap](#), [getHTTPHeaderNames](#), [getHTTPIntHeader](#),  
[getHTTPStreamerAdapter](#), [getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#),  
[getLiveStreamingPacketizer](#), [getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#),  
[getQueryStr](#), [getRedirectSessionBody](#), [getRedirectSessionCode](#),  
[getRedirectSessionContentType](#), [getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#),  
[getServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[getStream](#), [getStreamExt](#), [getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#),  
[getTimeRunning](#), [getTimeRunningSeconds](#), [getTranscoderVODIndex](#), [getTranscoderVODIndex](#),  
[getTranscoderVODIndexDestinationsMap](#), [getTranscoderVODIndexDestinationsOrder](#),  
[getTranscoderVODSession](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),  
[getVHost](#), [getVODTranscodeNGRP](#), [indexTranscoderVOD](#), [isAcceptSession](#), [isActive](#),  
[isFileInfo](#), [isHTTPOrigin](#), [isPlayLogged](#), [isRedirectSession](#), [isTimeout](#),  
[isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#), [lockRepeaterStreams](#),  
[putFileInfo](#), [putStreamNameParts](#), [redirectSession](#), [redirectSession](#), [rejectSession](#),  
[removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#), [setAppInstance](#), [setCookieStr](#),  
[setDvrSessionInfo](#), [setHTTPOrigin](#), [setHTTPStreamerAdapter](#), [setIpAddress](#),  
[setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#), [setPlayStart](#),  
[setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#), [setRedirectSessionCode](#),  
[setRedirectSessionContentType](#), [setRedirectSessionURL](#), [setReferrer](#), [setServerIp](#),  
[setServerPort](#), [setSessionId](#), [setSessionProtocol](#), [setSessionTimeout](#), [setSessionType](#),  
[setStream](#), [setStreamExt](#), [setStreamName](#), [setStreamPosition](#), [setTimeoutSession](#),  
[setTranscoderVODIndex](#), [setTranscoderVODSession](#), [setUri](#), [setUserAgent](#),  
[setUserHTTPHeader](#), [setUserQueryStr](#), [setVHost](#), [setVODTranscodeNGRP](#), [shutdown](#), [touch](#),  
[updateLoggingValues](#), [validStreamDomainToString](#)

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPSessionNotify](#)

[notifyHTTPSessionCreate](#), [notifyHTTPSessionDestroy](#)

## Constructors

**HTTPStreamerSessionCupertino**

```
public HTTPStreamerSessionCupertino()
```

## Methods

**shutdown**

```
public void shutdown()
```

**containsIndex**

```
public boolean containsIndex(String streamName)
```

(continued from last page)

---

## getIndex

```
public IHTTPStreamerCupertinoIndex getIndex(IHTTPStreamerApplicationContext
appContext,
IHTTPStreamerSession httpStreamerSession,
String rawStreamName,
String streamExt,
String streamName,
long playStart,
long playDuration,
TimedTextRequest captionRequest,
String vodTranscodeNGRP)
```

---

## updateLoggingValues

```
public void updateLoggingValues()
```

---

## clearLoggingValues

```
public void clearLoggingValues()
```

---

## logLiveChunk

```
public void logLiveChunk(LiveStreamPacketizerCupertinoChunk chunk)
```

---

## logVODChunk

```
public void logVODChunk(LiveStreamPacketizerCupertinoChunk chunk)
```

---

## notifyHTTPSessionCreate

```
public void notifyHTTPSessionCreate(IApplicationInstance appInstance,
IHTTPStreamerSession httpStreamerSession)
```

---

## notifyHTTPSessionDestroy

```
public void notifyHTTPSessionDestroy(IApplicationInstance appInstance,
IHTTPStreamerSession httpStreamerSession)
```

---

## indexTranscoderVOD

```
public void indexTranscoderVOD(IHTTPStreamerApplicationContext appContext,
String vodTranscodeNGRP)
```

(continued from last page)

## com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer Interface IHTTPStreamerCupertinoVODActionNotify

All Subinterfaces:

[IHTTPStreamerCupertinoVODActionNotify2](#)

public interface **IHTTPStreamerCupertinoVODActionNotify**

extends

IHTTPStreamerCupertinoVODActionNotify: listener interface for video on demand iOS streaming. See

HTTPStreamerApplicationContextCupertinoStreamer.addVODActionListener(IHTTPStreamerCupertinoVODActionNotify listener)

### Method Summary

void	<a href="#">onCreate</a> (IHTTPStreamerCupertinoIndex fileIndex, <a href="#">IHTTPStreamerApplicationContext</a> appContext, <a href="#">IHTTPStreamerSession</a> httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called when file index created
void	<a href="#">onDestroy</a> (IHTTPStreamerCupertinoIndex fileIndex) Called after file index is destroyed
void	<a href="#">onFillChunkEnd</a> (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerCupertinoIndexItem item, LiveStreamPacketizerCupertinoChunk chunk, boolean audioOnly) Called after each chunk is filled.
void	<a href="#">onFillChunkStart</a> (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerCupertinoIndexItem item, LiveStreamPacketizerCupertinoChunk chunk, boolean audioOnly) Called each time a chunk is filled.
void	<a href="#">onIndex</a> (IHTTPStreamerCupertinoIndex fileIndex, <a href="#">IHTTPStreamerApplicationContext</a> appContext, <a href="#">IHTTPStreamerSession</a> httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called after file is indexed
void	<a href="#">onInit</a> (IHTTPStreamerCupertinoIndex fileIndex, <a href="#">IHTTPStreamerApplicationContext</a> appContext, <a href="#">IHTTPStreamerSession</a> httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called after initialized
void	<a href="#">onOpen</a> (IHTTPStreamerCupertinoIndex fileIndex, <a href="#">IHTTPStreamerApplicationContext</a> appContext, <a href="#">IHTTPStreamerSession</a> httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called after open

### Methods

(continued from last page)

## onCreate

```
public void onCreate(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called when file index created

### Parameters:

fileIndex - file index  
appContext - HTTP application context  
httpStreamerSession - HTTP streaming session  
rawStreamName - stream name  
streamExt - stream extension  
streamName - adjusted stream name

---

## onInit

```
public void onInit(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called after initialized

### Parameters:

fileIndex - file index  
appContext - HTTP application context  
httpStreamerSession - HTTP streaming session  
rawStreamName - stream name  
streamExt - stream extension  
streamName - adjusted stream name

---

## onOpen

```
public void onOpen(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called after open

### Parameters:

fileIndex - file index  
appContext - HTTP application context  
httpStreamerSession - HTTP streaming session  
rawStreamName - stream name  
streamExt - stream extension  
streamName - adjusted stream name

---



(continued from last page)

## onIndex

```
public void onIndex(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called after file is indexed

### Parameters:

fileIndex - file index  
appContext - HTTP application context  
httpStreamerSession - HTTP streaming session  
rawStreamName - stream name  
streamExt - stream extension  
streamName - adjusted stream name

---

## onFillChunkStart

```
public void onFillChunkStart(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerCupertinoIndexItem item,  
    LiveStreamPacketizerCupertinoChunk chunk,  
    boolean audioOnly)
```

Called each time a chunk is filled. Can be used to add ID3 data to the header of a chunk.

### Parameters:

fileIndex - file index  
item - index item  
chunk - chunk being filled  
audioOnly - is audio-only chunk

---

## onFillChunkEnd

```
public void onFillChunkEnd(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerCupertinoIndexItem item,  
    LiveStreamPacketizerCupertinoChunk chunk,  
    boolean audioOnly)
```

Called after each chunk is filled. Can be used to add ID3 data to the end of a chunk.

### Parameters:

fileIndex - file index  
item - index item  
chunk - chunk being filled  
audioOnly - is audio-only chunk

---

## onDestroy

```
public void onDestroy(IHTTPStreamerCupertinoIndex fileIndex)
```

Called after file index is destroyed

### Parameters:

fileIndex - file index

---

## com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer Interface IHTTPStreamerCupertinoVODActionNotify2

All Superinterfaces:

[IHTTPStreamerCupertinoVODActionNotify](#)

public interface **IHTTPStreamerCupertinoVODActionNotify2**

extends [IHTTPStreamerCupertinoVODActionNotify](#)

### Method Summary

void	<a href="#">onFillChunkDataPacket</a> (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerCupertinoIndexItem item, LiveStreamPacketizerCupertinoChunk chunk, boolean audioOnly, <a href="#">AMFPacket</a> packet, <a href="#">ID3Frames</a> id3Frames) Called when data packet is encountered.
------	--

#### Methods inherited from interface

[com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer.IHTTPStreamerCupertinoVODActionNotify](#)

[onCreate](#), [onDestroy](#), [onFillChunkEnd](#), [onFillChunkStart](#), [onIndex](#), [onInit](#), [onOpen](#)

### Methods

#### onFillChunkDataPacket

```
public void onFillChunkDataPacket(IHTTPStreamerCupertinoIndex fileIndex,
    IHTTPStreamerCupertinoIndexItem item,
    LiveStreamPacketizerCupertinoChunk chunk,
    boolean audioOnly,
    AMFPacket packet,
    ID3Frames id3Frames)
```

Called when data packet is encountered. Used to convert AMF events into ID3 tags for iOS streaming

#### Parameters:

fileIndex - file index  
item - item  
chunk - chunk  
audioOnly - is audio-only chunk  
packet - amf packet  
id3Frames - ID3 frames

---

Package

**com.wowza.wms.httpstreamer.directstreamin  
g.httpstreamer**

## com.wowza.wms.httpstreamer.directstreaming.httpstreamer Class HTTPStreamerSessionDirect

java.lang.Object

└─ com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.directstreaming.httpstreamer.HTTPStreamerSessionDirect

All Implemented Interfaces:

[IHTTPStreamerSession](#)

public class **HTTPStreamerSessionDirect**  
extends HTTPStreamerSessionBase

### Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isHTTPOrigin, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, notifyCreate, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, transcoderVODIndex, transcoderVODIndexDestinationsMap, transcoderVODIndexDestinationsOrder, transcoderVODSession, uri, userAgent, userHTTPHeaders, userQueryStr, vhost, vodTranscodeNGRP

### Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL\\_COUNT](#), [SESSIONPROTOCOL\\_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL\\_DIRECTSTREAMING](#), [SESSIONPROTOCOL\\_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL\\_MPEGDASHSTREAMING](#), [SESSIONPROTOCOL\\_SANJOSESTREAMING](#), [SESSIONPROTOCOL\\_SMOOTHSTREAMING](#), [SESSIONPROTOCOL\\_UNKNOWN](#), [SESSIONPROTOCOL\\_WEBMSTREAMING](#), [SESSIONTYPE\\_LIVE](#), [SESSIONTYPE\\_LIVEDVR](#), [SESSIONTYPE\\_UNKNOWN](#), [SESSIONTYPE\\_VOD](#)

## Constructor Summary

public [HTTPStreamerSessionDirect](#)()

### Methods inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

```

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr,
addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues,
containsStreamDomainStr, containsStreamNameParts, doSessionRedirect,
doSessionRedirect, extractHTTPRequestInfo, getAndClearNotifyCreate, getAppInstance,
getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo,
getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader,
getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest,
getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties,
getQueryStr, getRedirectSessionBody, getRedirectSessionCode,
getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp,
getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType,
getStream, getStreamDomainStr, getStreamDomainStrList, getStreamExt, getStreamName,
getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds,
getTranscoderVODIndex, getTranscoderVODIndex, getTranscoderVODIndexDestinationsMap,
getTranscoderVODIndexDestinationsOrder, getTranscoderVODSession, getUri,
getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, getVODTranscodeNGRP,
indexTranscoderVOD, isAcceptSession, isActive, isFileInfo, isHTTPOrigin,
isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated,
isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts,
redirectSession, redirectSession, rejectSession, removeStreamDomainStr,
setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo,
setHTTPOrigin, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer,
setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession,
setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType,
setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId,
setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt,
setStreamName, setStreamPosition, setThreadContext, setTimeoutSession,
setTranscoderVODIndex, setTranscoderVODSession, setUri, setUserAgent,
setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, setVODTranscodeNGRP,
shutdown, shutdownLocked, touch, updateLoggingValues, validStreamDomainToString

```

#### Methods inherited from class java.lang.Object

```

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

```

#### Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),  
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),  
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),  
[doSessionRedirect](#), [extractHTTPRequestInfo](#), [getAndClearNotifyCreate](#), [getAppInstance](#),  
[getConnectionHolder](#), [getCookieStr](#), [getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#),  
[getHTTPHeader](#), [getHTTPHeaderMap](#), [getHTTPHeaderNames](#), [getHTTPIntHeader](#),  
[getHTTPStreamerAdapter](#), [getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#),  
[getLiveStreamingPacketizer](#), [getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#),  
[getQueryStr](#), [getRedirectSessionBody](#), [getRedirectSessionCode](#),  
[getRedirectSessionContentType](#), [getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#),  
[getServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[getStream](#), [getStreamExt](#), [getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#),  
[getTimeRunning](#), [getTimeRunningSeconds](#), [getTranscoderVODIndex](#), [getTranscoderVODIndex](#),  
[getTranscoderVODIndexDestinationsMap](#), [getTranscoderVODIndexDestinationsOrder](#),  
[getTranscoderVODSession](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),  
[getVHost](#), [getVODTranscodeNGRP](#), [indexTranscoderVOD](#), [isAcceptSession](#), [isActive](#),  
[isFileInfo](#), [isHTTPOrigin](#), [isPlayLogged](#), [isRedirectSession](#), [isTimeout](#),  
[isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#), [lockRepeaterStreams](#),  
[putFileInfo](#), [putStreamNameParts](#), [redirectSession](#), [redirectSession](#), [rejectSession](#),  
[removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#), [setAppInstance](#), [setCookieStr](#),  
[setDvrSessionInfo](#), [setHTTPOrigin](#), [setHTTPStreamerAdapter](#), [setIpAddress](#),  
[setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#), [setPlayStart](#),  
[setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#), [setRedirectSessionCode](#),  
[setRedirectSessionContentType](#), [setRedirectSessionURL](#), [setReferrer](#), [setServerIp](#),  
[setServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [setSessionType](#),  
[setStream](#), [setStreamExt](#), [setStreamName](#), [setStreamPosition](#), [setTimeoutSession](#),  
[setTranscoderVODIndex](#), [setTranscoderVODSession](#), [setUri](#), [setUserAgent](#),  
[setUserHTTPHeader](#), [setUserQueryStr](#), [setVHost](#), [setVODTranscodeNGRP](#), [shutdown](#), [touch](#),  
[updateLoggingValues](#), [validStreamDomainToString](#)

## Constructors

### HTTPStreamerSessionDirect

```
public HTTPStreamerSessionDirect()
```

---

Package

**com.wowza.wms.httpstreamer.model**

## com.wowza.wms.httpstreamer.model Interface IHTTPCryptoHolder

public interface IHTTPCryptoHolder  
extends

### Method Summary

byte[]	<a href="#">getBuffer()</a>
int	<a href="#">getOffset()</a>
int	<a href="#">getPacketType()</a>
long	<a href="#">getSample()</a>
int	<a href="#">getSize()</a>
void	<a href="#">setBuffer</a> (byte[] buffer)
void	<a href="#">setOffset</a> (int offset)
void	<a href="#">setPacketType</a> (int packetType)
void	<a href="#">setSample</a> (long sample)
void	<a href="#">setSize</a> (int size)

### Methods

#### getBuffer

public byte[] **getBuffer**()

#### setBuffer

public void **setBuffer**(byte[] buffer)

#### getOffset

public int **getOffset**()



---

**setOffset**

```
public void setOffset(int offset)
```

---

---

**getSize**

```
public int getSize()
```

---

---

**setSize**

```
public void setSize(int size)
```

---

---

**getPacketType**

```
public int getPacketType()
```

---

---

**setPacketType**

```
public void setPacketType(int packetType)
```

---

---

**getSample**

```
public long getSample()
```

---

---

**setSample**

```
public void setSample(long sample)
```

---

---

## com.wowza.wms.httpstreamer.model Interface IHTTPSessionFactory

---

public interface **IHTTPSessionFactory**  
extends

---

### Method Summary

<a href="#">IHTTPStreamerSession</a>	<a href="#">createHTTPSessionInstance()</a>
--------------------------------------	---

---

### Methods

#### **createHTTPSessionInstance**

public [IHTTPStreamerSession](#) **createHTTPSessionInstance()**

com.wowza.wms.httpstreamer.model

Interface IHTTPSessionNotify

All Known Implementing Classes:  
[HTTPStreamerSessionSmoothStreamer](#), [HTTPStreamerSessionSanJose](#), [HTTPStreamerSessionCupertino](#)

public interface IHTTPSessionNotify  
extends

Method Summary	
void	<a href="#">notifyHTTPSessionCreate(IApplicationInstance</a> appInstance, <a href="#">IHTTPStreamerSession</a> httpStreamerSession)
void	<a href="#">notifyHTTPSessionDestroy(IApplicationInstance</a> appInstance, <a href="#">IHTTPStreamerSession</a> httpStreamerSession)

Methods

notifyHTTPSessionCreate

public void **notifyHTTPSessionCreate**([IApplicationInstance](#) appInstance, [IHTTPStreamerSession](#) httpStreamerSession)

notifyHTTPSessionDestroy

public void **notifyHTTPSessionDestroy**([IApplicationInstance](#) appInstance, [IHTTPStreamerSession](#) httpStreamerSession)

## com.wowza.wms.httpstreamer.model Interface IHTTPStreamerAdapter

public interface **IHTTPStreamerAdapter**  
extends

IHTTPStreamerAdapter: HTTP streaming adapter interface

### Method Summary

boolean	<a href="#"><u>canHandle</u></a> (String path) Return true if can handle request
String	<a href="#"><u>getAdapterName</u></a> ( ) Get the name of this adapter
HTTPStreamerItem	<a href="#"><u>getHTTPStreamerItem</u></a> ( ) Get the HTTP streamer item associated with this adapter
String	<a href="#"><u>getID</u></a> ( ) Get the id of this adapter
int	<a href="#"><u>getIdleFrequency</u></a> ( ) Get the idle frequency (milliseconds) for HTTP requests.
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties</u></a> ( ) Get properties
int	<a href="#"><u>getSessionProtocol</u></a> ( ) Set the adapter session protocol.
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost</u></a> ( ) Get the vhost associated with this adapter
void	<a href="#"><u>init</u></a> ( ) Initialize the HTTP streaming adapter
void	<a href="#"><u>service</u></a> (org.apache.mina.common.io.Session session, RtmpRequestMessage req, RtmpResponseMessage resp) Called to service each request
void	<a href="#"><u>setHTTPStreamerItem</u></a> (HTTPStreamerItem httpStreamerItem) Set the HTTP streamer item associated with this adapter
void	<a href="#"><u>setID</u></a> (String id) Set the id of this adapter
void	<a href="#"><u>setProperties</u></a> ( <a href="#"><u>WMSProperties</u></a> properties) Set properties
void	<a href="#"><u>setSessionProtocol</u></a> (int sessionProtocol) Get the adapter session protocol.
void	<a href="#"><u>setVHost</u></a> ( <a href="#"><u>IVHost</u></a> vhost) Set the vhost associated with this adapter

void

[shutdownSession](#)([IApplicationInstance](#) appInstance, [IHTTPStreamerSession](#) session)

Called when an HTTP streaming session is shutdown

## Methods

### canHandle

```
public boolean canHandle(String path)
```

Return true if can handle request

**Parameters:**

path - request path

**Returns:**

true if can handle request

### service

```
public void service(org.apache.mina.common.Session session,  
    RtmpRequestMessage req,  
    RtmpResponseMessage resp)
```

Called to service each request

**Parameters:**

session - io session

req - request

resp - response

### getProperties

```
public WMSPProperties getProperties()
```

Get properties

**Returns:**

properties

### setProperties

```
public void setProperties(WMSPProperties properties)
```

Set properties

**Parameters:**

properties - properties

### getHTTPStreamerItem

```
public HTTPStreamerItem getHTTPStreamerItem()
```

Get the HTTP streamer item associated with this adapter

**Returns:**

(continued from last page)

HTTP streamer item

---

## setHTTPStreamerItem

```
public void setHTTPStreamerItem(HTTPStreamerItem httpStreamerItem)
```

Set the HTTP streamer item associated with this adapter

**Parameters:**

httpStreamerItem - HTTP streamer item

---

## getVHost

```
public IVHost getVHost()
```

Get the vhost associated with this adapter

**Returns:**

vhost

---

## setVHost

```
public void setVHost(IVHost vhost)
```

Set the vhost associated with this adapter

**Parameters:**

vhost - vhost

---

## init

```
public void init()
```

Initialize the HTTP streaming adapter

---

## shutdownSession

```
public void shutdownSession(IApplicationInstance appInstance,  
    IHTTPStreamerSession session)
```

Called when an HTTP streaming session is shutdown

**Parameters:**

session - HTTP streaming session

---

## getIdleFrequency

```
public int getIdleFrequency()
```

Get the idle frequency (milliseconds) for HTTP requests. This is how often the session is called back while active.

**Returns:**

idle frequency (milliseconds)

---

## getAdapterName

```
public String getAdapterName()
```

---

(continued from last page)

Get the name of this adapter

**Returns:**

name of this adapter

---

**getID**

```
public String getID()
```

Get the id of this adapter

**Returns:**

id of this adapter

---

**setID**

```
public void setID(String id)
```

Set the id of this adapter

**Parameters:**

id - id of this adapter

---

**getSessionProtocol**

```
public int getSessionProtocol()
```

Set the adapter session protocol. See IHTTPStreamerSession.SESSIONPROTOCOL\_\*

**Returns:**

adapter session protocol

---

**setSessionProtocol**

```
public void setSessionProtocol(int sessionProtocol)
```

Get the adapter session protocol. See IHTTPStreamerSession.SESSIONPROTOCOL\_\*

**Parameters:**

sessionProtocol - adapter session protocol

---

## com.wowza.wms.httpstreamer.model Interface IHTTPStreamerApplicationContext

public interface **IHTTPStreamerApplicationContext**  
extends

IHTTPStreamerApplicationContext: HTTP streamer application context interface. Used by HTTP streaming adapter to store per-application information.

### Field Summary

public static final	<a href="#">HTTPOIGINMODE_AUTO</a> Value: <b>1</b>
public static final	<a href="#">HTTPOIGINMODE_OFF</a> Value: <b>0</b>
public static final	<a href="#">HTTPOIGINMODE_ON</a> Value: <b>2</b>

### Method Summary

void	<a href="#">addQueryStrRemoveList</a> (String name) Add a name to the list of query string parameters that will not be copied to the media URLs for HTTP streaming
java.util.Map	<a href="#">filterQueryStr</a> (java.util.Map map) Internal
<a href="#">IApplicationInstance</a>	<a href="#">getAppInstance</a> () Get application instance
int	<a href="#">getHTTPOriginMode</a> () Get current HTTP origin mode.
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> () Get properties
<a href="#">MediaCasterItem</a>	<a href="#">getRepeaterMediaCasterDef</a> () Get the live repeater media caster definition
String	<a href="#">getStreamTypeStr</a> () Get stream type
java.util.Map	<a href="#">getUserHTTPHeaders</a> () Get user HTTP headers.
<a href="#">IVHost</a>	<a href="#">getVHost</a> () Get vhost



void	<a href="#"><code>init(IApplicationInstance appInstance, HTTPStreamerItem httpStreamerItem)</code></a> Initialize context
boolean	<a href="#"><code>isHTTPOriginOn()</code></a> Returns true if HTTP origin mode is set to ON.
boolean	<a href="#"><code>isStreamDomainProtectionActive()</code></a> Return true if stream domain protection is on
void	<a href="#"><code>setHTTPOriginMode(int httpOriginMode)</code></a> Set current HTTP origin mode.
void	<a href="#"><code>setRepeaterMediaCasterDef(MediaCasterItem repeaterMediaCasterDef)</code></a> Set the live repeater media caster definition
void	<a href="#"><code>setStreamDomainProtectionActive(boolean streamDomainProtectionActive)</code></a> Turn on/off stream domain protection
void	<a href="#"><code>setStreamTypeStr(String streamTypeStr)</code></a> Set stream type
void	<a href="#"><code>setUserHTTPHeader(String name, String value)</code></a> Add a user HTTP header to the header map.

## Fields

### HTTPORIGINMODE\_OFF

```
public static final int HTTPORIGINMODE_OFF
```

Constant value: **0**

### HTTPORIGINMODE\_AUTO

```
public static final int HTTPORIGINMODE_AUTO
```

Constant value: **1**

### HTTPORIGINMODE\_ON

```
public static final int HTTPORIGINMODE_ON
```

Constant value: **2**

## Methods

### init

```
public void init(IApplicationInstance appInstance,
    HTTPStreamerItem httpStreamerItem)
```

Initialize context

(continued from last page)

**Parameters:**

appInstance - application instance  
httpStreamerItem - HTTP streamer

---

## getProperties

```
public WMSProperties getProperties()
```

Get properties

**Returns:**

properties

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get application instance

**Returns:**

application instance

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

**Returns:**

vhost

---

## getRepeaterMediaCasterDef

```
public MediaCasterItem getRepeaterMediaCasterDef()
```

Get the live repeater media caster definition

**Returns:**

live repeater media caster definition

---

## setRepeaterMediaCasterDef

```
public void setRepeaterMediaCasterDef(MediaCasterItem repeaterMediaCasterDef)
```

Set the live repeater media caster definition

**Parameters:**

repeaterMediaCasterDef - live repeater media caster definition

---

## getStreamTypeStr

```
public String getStreamTypeStr()
```

Get stream type

**Returns:**

stream type

## setStreamTypeStr

```
public void setStreamTypeStr(String streamTypeStr)
```

Set stream type

**Parameters:**

streamTypeStr - stream type

---

## isStreamDomainProtectionActive

```
public boolean isStreamDomainProtectionActive()
```

Return true if stream domain protection is on

**Returns:**

true if stream domain protection is on

---

## setStreamDomainProtectionActive

```
public void setStreamDomainProtectionActive(boolean streamDomainProtectionActive)
```

Turn on/off stream domain protection

**Parameters:**

streamDomainProtectionActive - true if stream domain protection is on

---

## getHTTPOriginMode

```
public int getHTTPOriginMode()
```

Get current HTTP origin mode. See HTTPORIGINMODE\_ (auto is currently not supported)

**Returns:**

HTTP origin mode

---

## setHTTPOriginMode

```
public void setHTTPOriginMode(int httpOriginMode)
```

Set current HTTP origin mode. See HTTPORIGINMODE\_ (auto is currently not supported)

**Parameters:**

httpOriginMode - HTTP origin mode

---

## isHTTPOriginOn

```
public boolean isHTTPOriginOn()
```

Returns true if HTTP origin mode is set to ON.

**Returns:**

true if HTTP origin mode is set to ON.

---

(continued from last page)

## setUserHTTPHeader

```
public void setUserHTTPHeader(String name,  
                               String value)
```

Add a user HTTP header to the header map. These headers will be added to every HTTP response.

**Parameters:**

name - name

value - value (null if no value)

---

## getUserHTTPHeaders

```
public java.util.Map getUserHTTPHeaders()
```

Get user HTTP headers.

**Returns:**

header map

---

## addQueryStringRemoveList

```
public void addQueryStringRemoveList(String name)
```

Add a name to the list of query string parameters that will not be copied to the media URLs for HTTP streaming

**Parameters:**

name - query name

---

## filterQueryString

```
public java.util.Map filterQueryString(java.util.Map map)
```

Internal

**Parameters:**

map - query map

**Returns:**

query map

---

# com.wowza.wms.httpstreamer.model

## Interface IHTTPStreamerRepeater

public interface IHTTPStreamerRepeater  
extends

IHTTPStreamerRepeater: stream switching constants

Field Summary	
public static final	<a href="#">MSG_STARTSTREAM</a> Value: <b>startStream</b>
public static final	<a href="#">MSG_SWITCHSTREAM</a> Value: <b>switchStream</b>

### Fields

#### MSG\_STARTSTREAM

public static final java.lang.String MSG\_STARTSTREAM

Constant value: **startStream**

#### MSG\_SWITCHSTREAM

public static final java.lang.String MSG\_SWITCHSTREAM

Constant value: **switchStream**

## com.wowza.wms.httpstreamer.model Interface IHTTPStreamerSession

public interface **IHTTPStreamerSession**  
extends

IHTTPStreamerSession: HTTP streaming session interface

### Field Summary

public static final	<a href="#">SESSIONPROTOCOL_COUNT</a> Value: <b>7</b>
public static final	<a href="#">SESSIONPROTOCOL_CUPERTINOSTREAMING</a> Value: <b>1</b>
public static final	<a href="#">SESSIONPROTOCOL_DIRECTSTREAMING</a> Value: <b>6</b>
public static final	<a href="#">SESSIONPROTOCOL_DVRCHUNKSTREAMING</a> Value: <b>5</b>
public static final	<a href="#">SESSIONPROTOCOL_MPEGDASHSTREAMING</a> Value: <b>4</b>
public static final	<a href="#">SESSIONPROTOCOL_SANJOSESTREAMING</a> Value: <b>2</b>
public static final	<a href="#">SESSIONPROTOCOL_SMOOTHSTREAMING</a> Value: <b>0</b>
public static final	<a href="#">SESSIONPROTOCOL_UNKNOWN</a> Value: <b>-1</b>
public static final	<a href="#">SESSIONPROTOCOL_WEBMSTREAMING</a> Value: <b>3</b>
public static final	<a href="#">SESSIONTYPE_LIVE</a> Value: <b>1</b>
public static final	<a href="#">SESSIONTYPE_LIVEDVR</a> Value: <b>3</b>
public static final	<a href="#">SESSIONTYPE_UNKNOWN</a> Value: <b>0</b>

public static final	<a href="#">SESSIONTYPE_VOD</a> Value: <b>2</b>
---------------------	--

## Method Summary

void	<a href="#">acceptSession()</a> Accept the HTTP session.
void	<a href="#">addIOPerformance()</a> ( <a href="#">IOPerformanceCounter</a> totalIOPerformanceResult) Internal user, keep track of IO performance
void	<a href="#">addIOPerformance2()</a> ( <a href="#">IOPerformanceCounter</a> totalIOPerformanceResult) Internal user, keep track of IO performance
void	<a href="#">addStreamDomainStr()</a> (String streamDomainStr) Internal user, add stream name
void	<a href="#">addStreamDomainStrs()</a> (java.util.List streamNames) Internal user, add stream names
void	<a href="#">addUserHTTPHeaders()</a> ( <a href="#">IHTTPResponse</a> resp) Internal
boolean	<a href="#">checkAndSetPlayLogged()</a> If play has not been logged return false, else returns true, sets play has been logged
void	<a href="#">clearLoggingValues()</a> Internal user, clear logging values
boolean	<a href="#">containsStreamDomainStr()</a> (String streamDomainStr) Internal user, test stream name
boolean	<a href="#">containsStreamNameParts()</a> (String streamName) Return true if stream name in stream name parts
void	<a href="#">doSessionRedirect()</a> ( <a href="#">IHTTPResponse</a> resp) Internal
void	<a href="#">doSessionRedirect()</a> ( <a href="#">IHTTPResponse</a> resp, String redirectSessionURL, String redirectSessionContentType, int redirectSessionCode) Internal
void	<a href="#">extractHTTPRequestInfo()</a> ( <a href="#">IHTTPRequest</a> req) Extract information from HTTP request
boolean	<a href="#">getAndClearNotifyCreate()</a>
<a href="#">IApplicationInstance</a>	<a href="#">getAppInstance()</a> Get the application instance associated with this HTTP session
ConnectionHolder	<a href="#">getConnectionHolder()</a> Connection holder for this session
String	<a href="#">getCookieStr()</a> Get cookie string
DvrSessionInfo	<a href="#">getDvrSessionInfo()</a> This information is used to manage the connection to the DVR store.

<a href="#">ElapsedTimer</a>	<a href="#">getElapsedTime()</a> Get the elapsed timer to see how long this session has been running
HTTPStreamerFileInfo	<a href="#">getFileInfo(String streamName)</a> Get the file information if video on demand streaming
String	<a href="#">getHTTPHeader(String name)</a> Get a HTTP header value such as 'Content-Length'
java.util.Map	<a href="#">getHTTPHeaderMap()</a> Get a copy of the HTTP request header map
java.util.Set	<a href="#">getHTTPHeaderNames()</a> Get a Set of the header names
int	<a href="#">getHTTPIntHeader(String name)</a> Get a HTTP header value such as 'Content-Length' and return as int
<a href="#">IHTTPStreamerAdapter</a>	<a href="#">getHTTPStreamerAdapter()</a> Get the HTTP streaming adapter associated with this HTTP session
<a href="#">IOPerformanceCounter</a>	<a href="#">getIOPerformanceCounter()</a> Get IO performance counter
String	<a href="#">getIpAddress()</a> Get the IP address
long	<a href="#">getLastRequest()</a> Get the last timestamp of the last Io request
String	<a href="#">getLiveStreamingPacketizer()</a> Get the live stream packetizer name
Object	<a href="#">getLock()</a> Get the synchronization lock for this HTTP session
long	<a href="#">getPlayDuration()</a> Get the play duration (milliseconds) for video on demand playback.
long	<a href="#">getPlayStart()</a> Get the play start time offset (milliseconds) for video on demand playback.
<a href="#">WMSProperties</a>	<a href="#">getProperties()</a> Get the properties associated with this session
String	<a href="#">getQueryStr()</a> Get query string
byte[]	<a href="#">getRedirectSessionBody()</a> Get redirect session body
int	<a href="#">getRedirectSessionCode()</a> Get session redirect HTTP response code (default 302)
String	<a href="#">getRedirectSessionContentType()</a> Get redirect session HTTP Content-Type
String	<a href="#">getRedirectSessionURL()</a> Get redirect session URL



String	<a href="#"><u>getReferrer()</u></a> Get referrer
String	<a href="#"><u>getServerIp()</u></a> Get server IP address
int	<a href="#"><u>getServerPort()</u></a> Get server port
String	<a href="#"><u>getSessionId()</u></a> Get session id
int	<a href="#"><u>getSessionProtocol()</u></a> Get protocol, see SESSIONPROTOCOL_*
int	<a href="#"><u>getSessionTimeout()</u></a> Get the session timeout for this session (milliseconds)
int	<a href="#"><u>getSessionType()</u></a> Get session type: see SESSIONTYPE_*
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream()</u></a> Get the IMediaStream associated with this HTTP session
String	<a href="#"><u>getStreamExt()</u></a> Get stream extension
String	<a href="#"><u>getStreamName()</u></a> Get stream name
HTTPStreamerStreamNameParts	<a href="#"><u>getStreamNameParts()</u></a> (String streamName) Break the stream name into parts
long	<a href="#"><u>getStreamPosition()</u></a> Get stream position
String	<a href="#"><u>getTimeRunning()</u></a> Get the time this session has been running (milliseconds)
double	<a href="#"><u>getTimeRunningSeconds()</u></a> Get the time this session has been running (seconds)
<a href="#"><u>IHTTPStreamerTranscoderVODIndex</u></a>	<a href="#"><u>getTranscoderVODIndex()</u></a> Get the VOD Transcoder index information
<a href="#"><u>IHTTPStreamerTranscoderVODDestinationIndex</u></a>	<a href="#"><u>getTranscoderVODIndex()</u></a> (String bitrateStr) Get VOD transcoder index for given bitrate
java.util.Map	<a href="#"><u>getTranscoderVODIndexDestinationsMap()</u></a> Get the VOD Transcoder destination map
java.util.List	<a href="#"><u>getTranscoderVODIndexDestinationsOrder()</u></a> Get the list of VOD Transcoder destinations in playlist order
com.wowza.wms.transcoder.vod.TranscoderVODSession	<a href="#"><u>getTranscoderVODSession()</u></a> Get the vod transcoder session associated with this HTTP session
String	<a href="#"><u>getUri()</u></a> Get the URI associated with initial request

String	<a href="#"><u>getUserAgent()</u></a> Get user agent
java.util.Map	<a href="#"><u>getUserHTTPHeaders()</u></a> Get user HTTP header.
String	<a href="#"><u>getUserQueryStr()</u></a> This query string will be added to URLs used in HTTP streaming
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost()</u></a> Get vhost
String	<a href="#"><u>getVODTranscodeNGRP()</u></a> Get the VOD Transcoder NGRP name
void	<a href="#"><u>indexTranscoderVOD(IHTTPStreamerApplicationContext appContext, String vodTranscodeNGRP)</u></a> Index the HTTP session for VOD transcoder streaming
boolean	<a href="#"><u>isAcceptSession()</u></a> Return true if this session has not been rejected
boolean	<a href="#"><u>isActive()</u></a> Is this session active, false after shutdown
boolean	<a href="#"><u>isFileInfo(String streamName)</u></a> Return true if the is file information for a given stream name
boolean	<a href="#"><u>isHTTPOrigin()</u></a> Return true if session in an HTTP origin session
boolean	<a href="#"><u>isPlayLogged()</u></a> true, if play has been logged
boolean	<a href="#"><u>isRedirectSession()</u></a> Is session redirect
boolean	<a href="#"><u>isTimeout(long timecode)</u></a> Return true if this session is timed out.
boolean	<a href="#"><u>isTimeoutSession()</u></a> Get is session timeout.
boolean	<a href="#"><u>isValidated()</u></a> Has this session been validated
boolean	<a href="#"><u>isValidStreamDomainStr(String streamDomainStr)</u></a> Internal user, is stream name valid for HTTP session
void	<a href="#"><u>lockRepeaterStreams(java.util.List streamNames, String liveStreamPacketizer, String liveStreamRepeater, String streamTypeStr)</u></a> Internal user, lock in reapter streams
void	<a href="#"><u>putFileInfo(String streamName, HTTPStreamerFileInfo fileInfo)</u></a> Set the file information
void	<a href="#"><u>putStreamNameParts(String streamName, HTTPStreamerStreamNameParts streamNameParts)</u></a> Add stream name to stream name parts

void	<a href="#"><u>redirectSession</u></a> (String redirectSessionURL) Redirect session
void	<a href="#"><u>redirectSession</u></a> (String redirectSessionURL, int redirectSessionCode) Redirect session
void	<a href="#"><u>rejectSession</u></a> () Reject this HTTP session.
void	<a href="#"><u>removeStreamDomainStr</u></a> (String streamDomainStr) Internal user, remove stream name
void	<a href="#"><u>setAcceptSession</u></a> (boolean acceptSession) Set to false to reject session
void	<a href="#"><u>setActive</u></a> (boolean isActive) Set session active
void	<a href="#"><u>setAppInstance</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance) Set the application instance associated with this HTTP session
void	<a href="#"><u>setCookieStr</u></a> (String cookieStr) Set cookie string
void	<a href="#"><u>setDvrSessionInfo</u></a> (DvrSessionInfo dvr) This information is used to manage the connection to the DVR store.
void	<a href="#"><u>setHTTPOrigin</u></a> (boolean isHTTPOrigin) Set to true if HTTP origin session
void	<a href="#"><u>setHTTPStreamerAdapter</u></a> ( <a href="#"><u>IHTTPStreamerAdapter</u></a> httpStreamerAdapter) Set the HTTP streaming adapter associated with this HTTP session
void	<a href="#"><u>setIpAddress</u></a> (String ipAddress) Set the IP address
void	<a href="#"><u>setLiveStreamingPacketizer</u></a> (String liveStreamingPacketizer) Set the live stream packetizer name
void	<a href="#"><u>setPlayDuration</u></a> (long playDuration) Set the play duration (milliseconds) for video on demand playback.
void	<a href="#"><u>setPlayLogged</u></a> (boolean isPlayLogged) true, if play has been logged
void	<a href="#"><u>setPlayStart</u></a> (long playStart) Set the play start time offset (milliseconds) for video on demand playback.
void	<a href="#"><u>setQueryStr</u></a> (String queryStr) Set query string
void	<a href="#"><u>setRedirectSession</u></a> (boolean redirectSession) Set session redirect
void	<a href="#"><u>setRedirectSessionBody</u></a> (byte[] redirectSessionBody) Set redirect session body
void	<a href="#"><u>setRedirectSessionCode</u></a> (int redirectSessionCode) Set session redirect HTTP response code (default 302)

void	<a href="#"><u>setRedirectSessionContentType</u></a> (String redirectSessionContentType) Set redirect session HTTP Content-Type
void	<a href="#"><u>setRedirectSessionURL</u></a> (String redirectSessionURL) Set redirect session URL
void	<a href="#"><u>setReferrer</u></a> (String referrer) Set referrer
void	<a href="#"><u>setServerIp</u></a> (String serverIp) Set server IP address
void	<a href="#"><u>setServerPort</u></a> (int serverPort) Set server port
void	<a href="#"><u>setSessionId</u></a> (String sessionId) Set session id
void	<a href="#"><u>setSessionProtocol</u></a> (int sessionProtocol) Set protocol, see SESSIONPROTOCOL_*
void	<a href="#"><u>setSessionTimeout</u></a> (int sessionTimeout) Set the session timeout for this session (milliseconds)
void	<a href="#"><u>setSessionType</u></a> (int sessionType) Set session type: see SESSIONTYPE_*
void	<a href="#"><u>setStream</u></a> (IMediaStream stream) Set the IMediaStream associated with this HTTP session
void	<a href="#"><u>setStreamExt</u></a> (String streamExt) Set stream extension
void	<a href="#"><u>setStreamName</u></a> (String streamName) Set stream name
void	<a href="#"><u>setStreamPosition</u></a> (long streamPosition) Set stream position (will not cause seek)
void	<a href="#"><u>setTimeoutSession</u></a> (boolean timeoutSession) Set is session timeout.
void	<a href="#"><u>setTranscoderVODIndex</u></a> (IHTTPStreamerTranscoderVODIndex transcoderVODIndex) Set the VOD Transcoder index information
void	<a href="#"><u>setTranscoderVODSession</u></a> (com.wowza.wms.transcoder.vod.TranscoderVODSession transcoderVODSession) Set the vod transcoder session associated with this HTTP session
void	<a href="#"><u>setUri</u></a> (String uri) Set the URI associated with initial request
void	<a href="#"><u>setUserAgent</u></a> (String userAgent) Set user agent
void	<a href="#"><u>setUserHTTPHeader</u></a> (String name, String value) Set user HTTP header.

void	<a href="#"><code>setUserQueryStr</code></a> (String userQueryStr) This query string will be added to URLs used in HTTP streaming
void	<a href="#"><code>setVHost</code></a> ( <a href="#"><code>IVHost</code></a> vhost) Set vhost
void	<a href="#"><code>setVODTranscodeNGRP</code></a> (String vodTranscodeNGRP) Set the VOD Transcoder NGRP name
void	<a href="#"><code>shutdown</code></a> () Called then the HTTP session is shutting down
void	<a href="#"><code>touch</code></a> (long timecode) Touch this session to keep it active.
void	<a href="#"><code>updateLoggingValues</code></a> () Internal user, update logging values
String	<a href="#"><code>validStreamDomainToString</code></a> () Return the valid domain strings as a string

## Fields

### SESSIONTYPE\_UNKNOWN

```
public static final int SESSIONTYPE_UNKNOWN
```

Constant value: **0**

### SESSIONTYPE\_LIVE

```
public static final int SESSIONTYPE_LIVE
```

Constant value: **1**

### SESSIONTYPE\_VOD

```
public static final int SESSIONTYPE_VOD
```

Constant value: **2**

### SESSIONTYPE\_LIVEDVR

```
public static final int SESSIONTYPE_LIVEDVR
```

Constant value: **3**

### SESSIONPROTOCOL\_UNKNOWN

```
public static final int SESSIONPROTOCOL_UNKNOWN
```

Constant value: **-1**

---

## SESSIONPROTOCOL\_SMOOTHSTREAMING

```
public static final int SESSIONPROTOCOL_SMOOTHSTREAMING
```

Constant value: **0**

---

## SESSIONPROTOCOL\_CUPERTINOSTREAMING

```
public static final int SESSIONPROTOCOL_CUPERTINOSTREAMING
```

Constant value: **1**

---

## SESSIONPROTOCOL\_SANJOSESTREAMING

```
public static final int SESSIONPROTOCOL_SANJOSESTREAMING
```

Constant value: **2**

---

## SESSIONPROTOCOL\_WEBMSTREAMING

```
public static final int SESSIONPROTOCOL_WEBMSTREAMING
```

Constant value: **3**

---

## SESSIONPROTOCOL\_MPEGDASHSTREAMING

```
public static final int SESSIONPROTOCOL_MPEGDASHSTREAMING
```

Constant value: **4**

---

## SESSIONPROTOCOL\_DVRCHUNKSTREAMING

```
public static final int SESSIONPROTOCOL_DVRCHUNKSTREAMING
```

Constant value: **5**

---

## SESSIONPROTOCOL\_DIRECTSTREAMING

```
public static final int SESSIONPROTOCOL_DIRECTSTREAMING
```

Constant value: **6**

---

## SESSIONPROTOCOL\_COUNT

```
public static final int SESSIONPROTOCOL_COUNT
```

Constant value: **7**

## Methods

(continued from last page)

## getSessionId

```
public String getSessionId()
```

Get session id

**Returns:**

session id

---

## setSessionId

```
public void setSessionId(String sessionId)
```

Set session id

**Parameters:**

sessionId - session id

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

**Returns:**

vhost

---

## setVHost

```
public void setVHost(IVHost vhost)
```

Set vhost

**Parameters:**

vhost - vhost

---

## touch

```
public void touch(long timecode)
```

Touch this session to keep it active.

**Parameters:**

timecode - timecode of touch - System.currentTimeMillis();

---

## isTimeout

```
public boolean isTimeout(long timecode)
```

Return true if this session is timed out.

**Parameters:**

timecode - last touch - System.currentTimeMillis();

**Returns:**

true, if timed out

---

## getLock

```
public Object getLock()
```

Get the synchronization lock for this HTTP session

**Returns:**

synchronization lock

---

## shutdown

```
public void shutdown()
```

Called then the HTTP session is shutting down

---

## isActive

```
public boolean isActive()
```

Is this session active, false after shutdown

**Returns:**

true if session is active

---

## setActive

```
public void setActive(boolean isActive)
```

Set session active

**Parameters:**

isActive - session active

---

## getStream

```
public IMediaStream getStream()
```

Get the IMediaStream associated with this HTTP session

**Returns:**

IMediaStream associated with this HTTP session

---

## setStream

```
public void setStream(IMediaStream stream)
```

Set the IMediaStream associated with this HTTP session

**Parameters:**

stream - IMediaStream associated with this HTTP session

---

## isTimeoutSession

```
public boolean isTimeoutSession()
```

Get is session timeout.

**Returns:**

---



(continued from last page)

true if this session is timed out

---

## setTimeoutSession

```
public void setTimeoutSession(boolean timeoutSession)
```

Set is session timeout.

### Parameters:

timeoutSession - true if this session is timed out

---

## getSessionTimeout

```
public int getSessionTimeout()
```

Get the session timeout for this session (milliseconds)

### Returns:

session timeout for this session (milliseconds)

---

## setSessionTimeout

```
public void setSessionTimeout(int sessionTimeout)
```

Set the session timeout for this session (milliseconds)

### Parameters:

sessionTimeout - session timeout for this session (milliseconds)

---

## isValidated

```
public boolean isValidated()
```

Has this session been validated

### Returns:

true, if validated

---

## checkAndSetPlayLogged

```
public boolean checkAndSetPlayLogged()
```

If play has not been logged return false, else returns true, sets play has been logged

### Returns:

true, if play has been logged

---

## isPlayLogged

```
public boolean isPlayLogged()
```

true, if play has been logged

### Returns:

true, if play has been logged

(continued from last page)

## setPlayLogged

```
public void setPlayLogged(boolean isPlayLogged)
```

true, if play has been logged

### Parameters:

isPlayLogged - true, if play has been logged

---

## addIOPerformance

```
public void addIOPerformance(IOPerformanceCounter totalIOPerformanceResult)
```

Internal user, keep track of IO performance

### Parameters:

totalIOPerformanceResult - IO performance

---

## addIOPerformance2

```
public void addIOPerformance2(IOPerformanceCounter totalIOPerformanceResult)
```

Internal user, keep track of IO performance

### Parameters:

totalIOPerformanceResult - IO performance

---

## getConnectionHolder

```
public ConnectionHolder getConnectionHolder()
```

Connection holder for this session

### Returns:

connection holder

---

## getHTTPStreamerAdapter

```
public IHTTPStreamerAdapter getHTTPStreamerAdapter()
```

Get the HTTP streaming adapter associated with this HTTP session

### Returns:

HTTP streaming adapter

---

## setHTTPStreamerAdapter

```
public void setHTTPStreamerAdapter(IHTTPStreamerAdapter httpStreamerAdapter)
```

Set the HTTP streaming adapter associated with this HTTP session

### Parameters:

httpStreamerAdapter - HTTP streaming adapter

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

(continued from last page)

Get the application instance associated with this HTTP session

**Returns:**

application instance associated with this HTTP session

---

## setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set the application instance associated with this HTTP session

**Parameters:**

appInstance - application instance associated with this HTTP session

---

## getSessionType

```
public int getSessionType()
```

Get session type: see SESSIONTYPE\_\*

**Returns:**

session type: see SESSIONTYPE\_\*

---

## setSessionType

```
public void setSessionType(int sessionType)
```

Set session type: see SESSIONTYPE\_\*

**Parameters:**

sessionType - session type: see SESSIONTYPE\_\*

---

## getLiveStreamingPacketizer

```
public String getLiveStreamingPacketizer()
```

Get the live stream packetizer name

**Returns:**

live stream packetizer name

---

## setLiveStreamingPacketizer

```
public void setLiveStreamingPacketizer(String liveStreamingPacketizer)
```

Set the live stream packetizer name

**Parameters:**

liveStreamingPacketizer - live stream packetizer name

---

## getIpAddress

```
public String getIpAddress()
```

Get the IP address

**Returns:**

IP address

## setIpAddress

```
public void setIpAddress(String ipAddress)
```

Set the IP address

**Parameters:**

ipAddress - IP address

---

## updateLoggingValues

```
public void updateLoggingValues()
```

Internal user, update logging values

---

## clearLoggingValues

```
public void clearLoggingValues()
```

Internal user, clear logging values

---

## getSessionProtocol

```
public int getSessionProtocol()
```

Get protocol, see SESSIONPROTOCOL\_\*

**Returns:**

protocol, see SESSIONPROTOCOL\_\*

---

## setSessionProtocol

```
public void setSessionProtocol(int sessionProtocol)
```

Set protocol, see SESSIONPROTOCOL\_\*

**Parameters:**

sessionProtocol - protocol, see SESSIONPROTOCOL\_\*

---

## getServerIp

```
public String getServerIp()
```

Get server IP address

**Returns:**

server IP address

---

## setServerIp

```
public void setServerIp(String serverIp)
```

Set server IP address

**Parameters:**

serverIp - server IP address

---

---

## getServerPort

```
public int getServerPort()
```

Get server port

**Returns:**

server port

---

## setServerPort

```
public void setServerPort(int serverPort)
```

Set server port

**Parameters:**

serverPort - server port

---

## getUserAgent

```
public String getUserAgent()
```

Get user agent

**Returns:**

user agent

---

## setUserAgent

```
public void setUserAgent(String userAgent)
```

Set user agent

**Parameters:**

userAgent - user agent

---

## getUri

```
public String getUri()
```

Get the URI associated with initial request

**Returns:**

URI associated with initial request

---

## setUri

```
public void setUri(String uri)
```

Set the URI associated with initial request

**Parameters:**

uri - URI associated with initial request

---

## getReferrer

```
public String getReferrer()
```

---

(continued from last page)

Get referrer

**Returns:**

referrer

---

**setReferrer**

```
public void setReferrer(String referrer)
```

Set referrer

**Parameters:**

referrer - referrer

---

**getQueryStr**

```
public String getQueryStr()
```

Get query string

**Returns:**

query string

---

**setQueryStr**

```
public void setQueryStr(String queryStr)
```

Set query string

**Parameters:**

queryStr - query string

---

**lockRepeaterStreams**

```
public void lockRepeaterStreams(java.util.List streamNames,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    String streamTypeStr)
```

Internal user, lock in reapter streams

**Parameters:**

streamNames - list of stream names

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live repeater name

streamTypeStr - stream type

---

**rejectSession**

```
public void rejectSession()
```

Reject this HTTP session. No further processing should occur

---

**acceptSession**

```
public void acceptSession()
```

Accept the HTTP session.

## isAcceptSession

```
public boolean isAcceptSession()
```

Return true if this session has not been rejected

**Returns:**

true if this session has not been rejected

---

## setAcceptSession

```
public void setAcceptSession(boolean acceptSession)
```

Set to false to reject session

**Parameters:**

acceptSession - false to reject session

---

## getCookieStr

```
public String getCookieStr()
```

Get cookie string

**Returns:**

cookie string

---

## setCookieStr

```
public void setCookieStr(String cookieStr)
```

Set cookie string

**Parameters:**

cookieStr - cookie string

---

## getStreamName

```
public String getStreamName()
```

Get stream name

**Returns:**

stream name

---

## setStreamName

```
public void setStreamName(String streamName)
```

Set stream name

**Parameters:**

streamName - stream name

---

## getStreamExt

```
public String getStreamExt()
```

---

(continued from last page)

Get stream extension

**Returns:**

stream extension

---

## setStreamExt

```
public void setStreamExt(String streamExt)
```

Set stream extension

**Parameters:**

streamExt - stream extension

---

## getStreamNameParts

```
public HTTPStreamerStreamNameParts getStreamNameParts(String streamName)
```

Break the stream name into parts

**Parameters:**

streamName - stream name

**Returns:**

stream name parts

---

## containsStreamNameParts

```
public boolean containsStreamNameParts(String streamName)
```

Return true if stream name in stream name parts

**Parameters:**

streamName - stream name

**Returns:**

true if stream name in stream name parts

---

## putStreamNameParts

```
public void putStreamNameParts(String streamName,  
    HTTPStreamerStreamNameParts streamNameParts)
```

Add stream name to stream name parts

**Parameters:**

streamName - stream name

streamNameParts - stream name parts

---

## getStreamPosition

```
public long getStreamPosition()
```

Get stream position

**Returns:**

stream position



## setStreamPosition

```
public void setStreamPosition(long streamPosition)
```

Set stream position (will not cause seek)

**Parameters:**

streamPosition - stream position

---

## getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter()
```

Get IO performance counter

**Returns:**

IO performance counter

---

## getFileInfo

```
public HTTPStreamerFileInfo getFileInfo(String streamName)
```

Get the file information if video on demand streaming

**Parameters:**

streamName - stream name

**Returns:**

file information

---

## putFileInfo

```
public void putFileInfo(String streamName,  
    HTTPStreamerFileInfo fileInfo)
```

Set the file information

**Parameters:**

streamName - stream name

fileInfo - file information

---

## isFileInfo

```
public boolean isFileInfo(String streamName)
```

Return true if the is file information for a given stream name

**Parameters:**

streamName - stream name

**Returns:**

true if the is file information for a given stream name

---

## isValidStreamDomainStr

```
public boolean isValidStreamDomainStr(String streamDomainStr)
```

Internal user, is stream name valid for HTTP session

---

(continued from last page)

**Parameters:**

streamDomainStr - stream name

**Returns:**

true if valid

---

## validStreamDomainToString

```
public String validStreamDomainToString()
```

Return the valid domain strings as a string

**Returns:**

valid domain strings as a string

---

## containsStreamDomainStr

```
public boolean containsStreamDomainStr(String streamDomainStr)
```

Internal user, test stream name

**Parameters:**

streamDomainStr - stream name

**Returns:**

true if valid

---

## removeStreamDomainStr

```
public void removeStreamDomainStr(String streamDomainStr)
```

Internal user, remove stream name

**Parameters:**

streamDomainStr - stream name

---

## addStreamDomainStr

```
public void addStreamDomainStr(String streamDomainStr)
```

Internal user, add stream name

**Parameters:**

streamDomainStr - stream name

---

## addStreamDomainStrs

```
public void addStreamDomainStrs(java.util.List streamNames)
```

Internal user, add stream names

**Parameters:**

streamNames - stream names

---

## getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

(continued from last page)

Get the elapsed timer to see how long this session has been running

**Returns:**

elapsed timer (milliseconds)

---

## getTimeRunning

```
public String getTimeRunning()
```

Get the time this session has been running (milliseconds)

**Returns:**

time this session has been running (milliseconds)

---

## getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get the time this session has been running (seconds)

**Returns:**

time this session has been running (seconds)

---

## getProperties

```
public WMSProperties getProperties()
```

Get the properties associated with this session

**Returns:**

properties

---

## getUserQueryStr

```
public String getUserQueryStr()
```

This query string will be added to URLs used in HTTP streaming

**Returns:**

user query string

---

## setUserQueryStr

```
public void setUserQueryStr(String userQueryStr)
```

This query string will be added to URLs used in HTTP streaming

**Parameters:**

userQueryStr - user query string

---

## setDvrSessionInfo

```
public void setDvrSessionInfo(DvrSessionInfo dvr)
```

This information is used to manage the connection to the DVR store.

**Parameters:**

dvr - The DVR session info.

## getDvrSessionInfo

```
public DvrSessionInfo getDvrSessionInfo()
```

This information is used to manage the connection to the DVR store.

**Returns:**

DVR session info.

---

## extractHTTPRequestInfo

```
public void extractHTTPRequestInfo(IHttpRequest req)
```

Extract information from HTTP request

**Parameters:**

req - HTTP request

---

## getHTTPHeaderMap

```
public java.util.Map getHTTPHeaderMap()
```

Get a copy of the HTTP request header map

**Returns:**

copy of the HTTP request header map

---

## getHTTPHeader

```
public String getHTTPHeader(String name)
```

Get a HTTP header value such as 'Content-Length'

**Parameters:**

name - header name

**Returns:**

header value

---

## getHTTPIntHeader

```
public int getHTTPIntHeader(String name)
```

Get a HTTP header value such as 'Content-Length' and return as int

**Parameters:**

name - header name

**Returns:**

header value

---

## getHTTPHeaderNames

```
public java.util.Set getHTTPHeaderNames()
```

Get a Set of the header names

---

(continued from last page)

**Returns:**

Set of header names

---

**getPlayStart**

```
public long getPlayStart()
```

Get the play start time offset (milliseconds) for video on demand playback.

**Returns:**

play start time offset (milliseconds)

---

**setPlayStart**

```
public void setPlayStart(long playStart)
```

Set the play start time offset (milliseconds) for video on demand playback.

**Parameters:**

playStart - play start time offset (milliseconds)

---

**getPlayDuration**

```
public long getPlayDuration()
```

Get the play duration (milliseconds) for video on demand playback. A values of -1 means play to end.

**Returns:**

play duration (milliseconds)

---

**setPlayDuration**

```
public void setPlayDuration(long playDuration)
```

Set the play duration (milliseconds) for video on demand playback. A values of -1 means play to end.

**Parameters:**

playDuration - play duration (milliseconds)

---

**setUserHTTPHeader**

```
public void setUserHTTPHeader(String name,  
                               String value)
```

Set user HTTP header. This header value will be added to all HTTP responses

**Parameters:**

name - name

value - value

---

**getUserHTTPHeaders**

```
public java.util.Map getUserHTTPHeaders()
```

Get user HTTP header. This header value will be added to all HTTP responses

**Returns:**

header map

## addUserHTTPHeaders

```
public void addUserHTTPHeaders(IHTTPResponse resp)
```

Internal

### Parameters:

resp - response

---

## doSessionRedirect

```
public void doSessionRedirect(IHTTPResponse resp)
```

Internal

### Parameters:

resp - response

---

## doSessionRedirect

```
public void doSessionRedirect(IHTTPResponse resp,  
    String redirectSessionURL,  
    String redirectSessionContentType,  
    int redirectSessionCode)
```

Internal

### Parameters:

resp - response

redirectSessionURL - redirect session URL

redirectSessionContentType

redirectSessionCode - redirect session response code (default 302)

---

## isRedirectSession

```
public boolean isRedirectSession()
```

Is session redirect

### Returns:

session redirect

---

## setRedirectSession

```
public void setRedirectSession(boolean redirectSession)
```

Set session redirect

### Parameters:

redirectSession - session redirect

---

## getRedirectSessionCode

```
public int getRedirectSessionCode()
```

Get session redirect HTTP response code (default 302)

### Returns:

(continued from last page)

session redirect HTTP response code

---

## setRedirectSessionCode

```
public void setRedirectSessionCode(int redirectSessionCode)
```

Set session redirect HTTP response code (default 302)

**Parameters:**

redirectSessionCode - session redirect HTTP response code

---

## getRedirectSessionURL

```
public String getRedirectSessionURL()
```

Get redirect session URL

**Returns:**

redirect session URL

---

## setRedirectSessionURL

```
public void setRedirectSessionURL(String redirectSessionURL)
```

Set redirect session URL

**Parameters:**

redirectSessionURL - redirect session URL

---

## redirectSession

```
public void redirectSession(String redirectSessionURL)
```

Redirect session

**Parameters:**

redirectSessionURL - redirect session URL

---

## redirectSession

```
public void redirectSession(String redirectSessionURL,  
    int redirectSessionCode)
```

Redirect session

**Parameters:**

redirectSessionURL - redirect session URL

redirectSessionCode - redirect session response code (default 302)

---

## getRedirectSessionBody

```
public byte[] getRedirectSessionBody()
```

Get redirect session body

**Returns:**

redirect session body

---

## setRedirectSessionBody

```
public void setRedirectSessionBody(byte[] redirectSessionBody)
```

Set redirect session body

**Parameters:**

redirectSessionBody - redirect session body

---

## getRedirectSessionContentType

```
public String getRedirectSessionContentType()
```

Get redirect session HTTP Content-Type

**Returns:**

redirect session HTTP Content-Type

---

## setRedirectSessionContentType

```
public void setRedirectSessionContentType(String redirectSessionContentType)
```

Set redirect session HTTP Content-Type

**Parameters:**

redirectSessionContentType

---

## getLastRequest

```
public long getLastRequest()
```

Get the last timestamp of the last Io request

**Returns:**

last timestamp of the last Io request (milliseconds)

---

## isHTTPOrigin

```
public boolean isHTTPOrigin()
```

Return true if session in an HTTP origin session

**Returns:**

true if session in an HTTP origin session

---

## setHTTPOrigin

```
public void setHTTPOrigin(boolean isHTTPOrigin)
```

Set to true if HTTP origin session

**Parameters:**

isHTTPOrigin - true if HTTP origin session

---

## getAndClearNotifyCreate

```
public boolean getAndClearNotifyCreate()
```

---



(continued from last page)

---

## getTranscoderVODSession

```
public com.wowza.wms.transcoder.vod.TranscoderVODSession getTranscoderVODSession()
```

Get the vod transcoder session associated with this HTTP session

**Returns:**

vod transcoder session

---

## setTranscoderVODSession

```
public void setTranscoderVODSession(com.wowza.wms.transcoder.vod.TranscoderVODSession  
transcoderVODSession)
```

Set the vod transcoder session associated with this HTTP session

**Parameters:**

transcoderVODSession - vod transcoder session

---

## getVODTranscodeNGRP

```
public String getVODTranscodeNGRP()
```

Get the VOD Transcoder NGRP name

**Returns:**

VOD Transcoder NGRP name

---

## setVODTranscodeNGRP

```
public void setVODTranscodeNGRP(String vodTranscodeNGRP)
```

Set the VOD Transcoder NGRP name

**Parameters:**

vodTranscodeNGRP - VOD Transcoder NGRP name

---

## getTranscoderVODIndex

```
public IHTTPStreamerTranscoderVODIndex getTranscoderVODIndex()
```

Get the VOD Transcoder index information

**Returns:**

VOD Transcoder index

---

## setTranscoderVODIndex

```
public void setTranscoderVODIndex(IHTTPStreamerTranscoderVODIndex transcoderVODIndex)
```

Set the VOD Transcoder index information

**Parameters:**

transcoderVODIndex - VOD Transcoder index

---

(continued from last page)

## getTranscoderVODIndexDestinationsOrder

```
public java.util.List getTranscoderVODIndexDestinationsOrder()
```

Get the list of VOD Transcoder destinations in playlist order

**Returns:**

list of VOD Transcoder destinations

---

## getTranscoderVODIndexDestinationsMap

```
public java.util.Map getTranscoderVODIndexDestinationsMap()
```

Get the VOD Transcoder destination map

**Returns:**

VOD Transcoder destination map

---

## indexTranscoderVOD

```
public void indexTranscoderVOD(IHTTPStreamerApplicationContext appContext,  
String vodTranscodeNGRP)
```

Index the HTTP session for VOD transcoder streaming

**Parameters:**

appContext - application context

vodTranscodeNGRP - transcoder name group

---

## getTranscoderVODIndex

```
public IHTTPStreamerTranscoderVODDestinationIndex getTranscoderVODIndex(String  
bitrateStr)
```

Get VOD transcoder index for given bitrate

**Parameters:**

bitrateStr - bitrate string

**Returns:**

VOD transcoder index

## com.wowza.wms.httpstreamer.model Interface IHTTPStreamerSessionNotify

public interface IHTTPStreamerSessionNotify  
extends

IHTTPStreamerSessionNotify: HTTP session create/destroy interface

### Method Summary

void	<a href="#">onHTTPStreamerSessionCreate</a> ( <a href="#">IHTTPStreamerSession</a> httpStreamerSession) Called when an HTTP streaming session is created
void	<a href="#">onHTTPStreamerSessionDestroy</a> ( <a href="#">IHTTPStreamerSession</a> httpStreamerSession) Called when an HTTP streaming session is destroyed

### Methods

#### onHTTPStreamerSessionCreate

public void **onHTTPStreamerSessionCreate**([IHTTPStreamerSession](#) httpStreamerSession)

Called when an HTTP streaming session is created

**Parameters:**

httpStreamerSession - HTTP streaming session

#### onHTTPStreamerSessionDestroy

public void **onHTTPStreamerSessionDestroy**([IHTTPStreamerSession](#) httpStreamerSession)

Called when an HTTP streaming session is destroyed

**Parameters:**

httpStreamerSession - HTTP streaming session

## com.wowza.wms.httpstreamer.model Interface IHTTPStreamerTranscoderVODDestinationIndex

public interface IHTTPStreamerTranscoderVODDestinationIndex  
extends

### Method Summary

int	<a href="#">getBitrate()</a>
com.wowza.wms.transcoder.vod.TranscoderVODDestination	<a href="#">getTranscoderVODDestination()</a>
void	<a href="#">setBitrate</a> (int bitrate)
void	<a href="#">setTranscoderVODDestination</a> (com.wowza.wms.transcoder.vod.TranscoderVODDestination transcoderVODDestination)

### Methods

#### getTranscoderVODDestination

```
public com.wowza.wms.transcoder.vod.TranscoderVODDestination  
getTranscoderVODDestination()
```

#### setTranscoderVODDestination

```
public void  
setTranscoderVODDestination(com.wowza.wms.transcoder.vod.TranscoderVODDestination  
transcoderVODDestination)
```

#### getBitrate

```
public int getBitrate()
```

#### setBitrate

```
public void setBitrate(int bitrate)
```

## com.wowza.wms.httpstreamer.model Interface IHTTPStreamerTranscoderVODIndex

---

public interface IHTTPStreamerTranscoderVODIndex  
extends

---

---

## com.wowza.wms.httpstreamer.model Interface **ILiveStreamPacketizerChunkWriter**

public interface **ILiveStreamPacketizerChunkWriter**  
extends

### Method Summary

void	<a href="#"><u>addToChunk</u></a> (LiveStreamPacketizerPacketHolder holder)
void	<a href="#"><u>endChunk</u></a> (long timecode)
boolean	<a href="#"><u>isPacketizeAudio</u></a> ()
boolean	<a href="#"><u>isPacketizeData</u></a> ()
boolean	<a href="#"><u>isPacketizeVideo</u></a> ()
boolean	<a href="#"><u>isValidAudioCodec</u></a> (int codec)
boolean	<a href="#"><u>isValidVideoCodec</u></a> (int codec)
void	<a href="#"><u>resetStream</u></a> ()
void	<a href="#"><u>setCodecInfoAudio</u></a> (com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
void	<a href="#"><u>setCodecInfoVideo</u></a> (com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
void	<a href="#"><u>startChunk</u></a> (int streamMode, int videoCodecId, int audioCodecId, long timecode)

### Methods

#### **startChunk**

```
public void startChunk(int streamMode,  
    int videoCodecId,  
    int audioCodecId,  
    long timecode)
```

#### **endChunk**

```
public void endChunk(long timecode)
```

(continued from last page)

---

## addToChunk

```
public void addToChunk(LiveStreamPacketizerPacketHolder holder)
```

---

## setCodecInfoAudio

```
public void setCodecInfoAudio(com.wowza.wms.media.model.MediaCodecInfoAudio  
codecInfoAudio)
```

---

## setCodecInfoVideo

```
public void setCodecInfoVideo(com.wowza.wms.media.model.MediaCodecInfoVideo  
codecInfoVideo)
```

---

## resetStream

```
public void resetStream()
```

---

## isPacketizeAudio

```
public boolean isPacketizeAudio()
```

---

## isPacketizeVideo

```
public boolean isPacketizeVideo()
```

---

## isPacketizeData

```
public boolean isPacketizeData()
```

---

## isValidAudioCodec

```
public boolean isValidAudioCodec(int codec)
```

---

## isValidVideoCodec

```
public boolean isValidVideoCodec(int codec)
```

---

Package

**com.wowza.wms.httpstreamer.mpegdashstreaming.httpstreamer**



## com.wowza.wms.httpstreamer.mpegdashstreaming.httpstreamer Class HTTPStreamerSessionMPGEDash

java.lang.Object

└─com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.mpegdashstreaming.httpstreamer.HTTPStreamerSessionMPGEDash

All Implemented Interfaces:

[IHTTPStreamerSession](#)

public class **HTTPStreamerSessionMPGEDash**  
extends HTTPStreamerSessionBase

### Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isHTTPOrigin, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, notifyCreate, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, transcoderVODIndex, transcoderVODIndexDestinationsMap, transcoderVODIndexDestinationsOrder, transcoderVODSession, uri, userAgent, userHTTPHeaders, userQueryStr, vhost, vodTranscodeNGRP

### Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL\\_COUNT](#), [SESSIONPROTOCOL\\_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL\\_DIRECTSTREAMING](#), [SESSIONPROTOCOL\\_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL\\_MPEGDASHSTREAMING](#), [SESSIONPROTOCOL\\_SANJOSESTREAMING](#), [SESSIONPROTOCOL\\_SMOOTHSTREAMING](#), [SESSIONPROTOCOL\\_UNKNOWN](#), [SESSIONPROTOCOL\\_WEBMSTREAMING](#), [SESSIONTYPE\\_LIVE](#), [SESSIONTYPE\\_LIVEDVR](#), [SESSIONTYPE\\_UNKNOWN](#), [SESSIONTYPE\\_VOD](#)

## Constructor Summary

public	<a href="#">HTTPStreamerSessionMPGEDash()</a>
--------	---

## Method Summary

void	<a href="#">clearLoggingValues()</a>
boolean	<a href="#">containsIndex</a> (String streamName)
static IHTTPStreamerMPGEDash Index	<a href="#">createIndexLive</a> ( <a href="#">IHTTPStreamerApplicationContext</a> appContext, <a href="#">IHTTPStreamerSession</a> httpStreamerSession, String rawStreamName, String streamExt, String streamName)

IHTTPStreamerMPEGDash Index	<a href="#">getIndex(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName, long playStart, long playDuration, TimedTextRequest captionRequest, String vodTranscodeNGRP)</a>
IHTTPStreamerMPEGDash Index	<a href="#">getIndexLive(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName)</a>
void	<a href="#">indexTranscoderVOD(IHTTPStreamerApplicationContext appContext, String vodTranscodeNGRP)</a>
void	<a href="#">logLiveChunk</a> (MPEGDashDashChunk chunk)
void	<a href="#">logVODChunk</a> (MPEGDashDashChunk chunk)
void	<a href="#">notifyHTTPSessionCreate(IApplicationInstance appInstance, IHTTPStreamerSession httpStreamerSession)</a>
void	<a href="#">notifyHTTPSessionDestroy(IApplicationInstance appInstance, IHTTPStreamerSession httpStreamerSession)</a>
void	<a href="#">shutdown()</a>
void	<a href="#">updateLoggingValues()</a>

Methods inherited from class `com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase`

```

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr,
addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues,
containsStreamDomainStr, containsStreamNameParts, doSessionRedirect,
doSessionRedirect, extractHTTPRequestInfo, getAndClearNotifyCreate, getAppInstance,
getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo,
getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader,
getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest,
getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties,
getQueryStr, getRedirectSessionBody, getRedirectSessionCode,
getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp,
getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType,
getStream, getStreamDomainStr, getStreamDomainStrList, getStreamExt, getStreamName,
getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds,
getTranscoderVODIndex, getTranscoderVODIndex, getTranscoderVODIndexDestinationsMap,
getTranscoderVODIndexDestinationsOrder, getTranscoderVODSession, getUri,
getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, getVODTranscodeNGRP,
indexTranscoderVOD, isAcceptSession, isActive, isFileInfo, isHTTPOrigin,
isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated,
isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts,
redirectSession, redirectSession, rejectSession, removeStreamDomainStr,
setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo,
setHTTPOrigin, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer,
setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession,
setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType,
setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId,
setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt,
setStreamName, setStreamPosition, setThreadContext, setTimeoutSession,
setTranscoderVODIndex, setTranscoderVODSession, setUri, setUserAgent,
setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, setVODTranscodeNGRP,
shutdown, shutdownLocked, touch, updateLoggingValues, validStreamDomainToString

```

#### Methods inherited from class java.lang.Object

```

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

```

#### Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),  
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),  
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),  
[doSessionRedirect](#), [extractHTTPRequestInfo](#), [getAndClearNotifyCreate](#), [getAppInstance](#),  
[getConnectionHolder](#), [getCookieStr](#), [getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#),  
[getHTTPHeader](#), [getHTTPHeaderMap](#), [getHTTPHeaderNames](#), [getHTTPIntHeader](#),  
[getHTTPStreamerAdapter](#), [getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#),  
[getLiveStreamingPacketizer](#), [getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#),  
[getQueryStr](#), [getRedirectSessionBody](#), [getRedirectSessionCode](#),  
[getRedirectSessionContentType](#), [getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#),  
[getServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[getStream](#), [getStreamExt](#), [getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#),  
[getTimeRunning](#), [getTimeRunningSeconds](#), [getTranscoderVODIndex](#), [getTranscoderVODIndex](#),  
[getTranscoderVODIndexDestinationsMap](#), [getTranscoderVODIndexDestinationsOrder](#),  
[getTranscoderVODSession](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),  
[getVHost](#), [getVODTranscodeNGRP](#), [indexTranscoderVOD](#), [isAcceptSession](#), [isActive](#),  
[isFileInfo](#), [isHTTPOrigin](#), [isPlayLogged](#), [isRedirectSession](#), [isTimeout](#),  
[isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#), [lockRepeaterStreams](#),  
[putFileInfo](#), [putStreamNameParts](#), [redirectSession](#), [redirectSession](#), [rejectSession](#),  
[removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#), [setAppInstance](#), [setCookieStr](#),  
[setDvrSessionInfo](#), [setHTTPOrigin](#), [setHTTPStreamerAdapter](#), [setIpAddress](#),  
[setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#), [setPlayStart](#),  
[setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#), [setRedirectSessionCode](#),  
[setRedirectSessionContentType](#), [setRedirectSessionURL](#), [setReferrer](#), [setServerIp](#),  
[setServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[setStream](#), [setStreamExt](#), [setStreamName](#), [setStreamPosition](#), [setTimeoutSession](#),  
[setTranscoderVODIndex](#), [setTranscoderVODSession](#), [setUri](#), [setUserAgent](#),  
[setUserHTTPHeader](#), [setUserQueryStr](#), [setVHost](#), [setVODTranscodeNGRP](#), [shutdown](#), [touch](#),  
[updateLoggingValues](#), [validStreamDomainToString](#)

## Constructors

### HTTPStreamerSessionMPEGDash

```
public HTTPStreamerSessionMPEGDash()
```

## Methods

### shutdown

```
public void shutdown()
```

### containsIndex

```
public boolean containsIndex(String streamName)
```

(continued from last page)

---

## createIndexLive

```
public static IHTTPStreamerMPEGDashIndex
createIndexLive(IHTTPStreamerApplicationContext appContext,
IHTTPStreamerSession httpStreamerSession,
    String rawStreamName,
    String streamExt,
    String streamName)
```

---

## getIndexLive

```
public IHTTPStreamerMPEGDashIndex getIndexLive(IHTTPStreamerApplicationContext
appContext,
IHTTPStreamerSession httpStreamerSession,
    String rawStreamName,
    String streamExt,
    String streamName)
```

---

## getIndex

```
public IHTTPStreamerMPEGDashIndex getIndex(IHTTPStreamerApplicationContext appContext,
IHTTPStreamerSession httpStreamerSession,
    String rawStreamName,
    String streamExt,
    String streamName,
    long playStart,
    long playDuration,
    TimedTextRequest captionRequest,
    String vodTranscodeNGRP)
```

---

## updateLoggingValues

```
public void updateLoggingValues()
```

---

## clearLoggingValues

```
public void clearLoggingValues()
```

---

## logLiveChunk

```
public void logLiveChunk(MPEGDashDashChunk chunk)
```

---

## logVODChunk

```
public void logVODChunk(MPEGDashDashChunk chunk)
```

---

(continued from last page)

## **notifyHTTPSessionCreate**

```
public void notifyHTTPSessionCreate(IApplicationInstance appInstance,  
    IHTTPStreamerSession httpStreamerSession)
```

---

## **notifyHTTPSessionDestroy**

```
public void notifyHTTPSessionDestroy(IApplicationInstance appInstance,  
    IHTTPStreamerSession httpStreamerSession)
```

---

## **indexTranscoderVOD**

```
public void indexTranscoderVOD(IHTTPStreamerApplicationContext appContext,  
    String vodTranscodeNGRP)
```

---

Package

**com.wowza.wms.httpstreamer.sanjoestream  
ing.httpstreamer**

## com.wowza.wms.httpstreamer.sanjosestreaming.httpstreamer Class HTTPStreamerSessionSanJose

java.lang.Object

└─com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.sanjosestreaming.httpstreamer.HTTPStreamerSessionSanJose

All Implemented Interfaces:

[IHTTPSessionNotify](#), [IHTTPStreamerSession](#)

public class **HTTPStreamerSessionSanJose**  
 extends HTTPStreamerSessionBase  
 implements [IHTTPStreamerSession](#), [IHTTPSessionNotify](#)

### Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isHTTPOrigin, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, notifyCreate, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, transcoderVODIndex, transcoderVODIndexDestinationsMap, transcoderVODIndexDestinationsOrder, transcoderVODSession, uri, userAgent, userHTTPHeaders, userQueryStr, vhost, vodTranscodeNGRP

### Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL\\_COUNT](#), [SESSIONPROTOCOL\\_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL\\_DIRECTSTREAMING](#), [SESSIONPROTOCOL\\_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL\\_MPEGDASHSTREAMING](#), [SESSIONPROTOCOL\\_SANJOSESTREAMING](#), [SESSIONPROTOCOL\\_SMOOTHSTREAMING](#), [SESSIONPROTOCOL\\_UNKNOWN](#), [SESSIONPROTOCOL\\_WEBMSTREAMING](#), [SESSIONTYPE\\_LIVE](#), [SESSIONTYPE\\_LIVEDVR](#), [SESSIONTYPE\\_UNKNOWN](#), [SESSIONTYPE\\_VOD](#)

## Constructor Summary

public	<a href="#">HTTPStreamerSessionSanJose()</a>
--------	--

## Method Summary

void	<a href="#">addFirstABSTRequest</a> (String streamName)
------	---

void	<a href="#">clearLoggingValues</a> ()
------	---------------------------------------

boolean	<a href="#">containsIndex</a> (String streamName)
---------	---



static IHTTPStreamerSanJoseIndex	<a href="#">createIndexLive(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName)</a>
IHTTPStreamerSanJoseIndex	<a href="#">getIndex(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName, long playStart, long playDuration, TimedTextRequest captionRequest, String vodTranscodeNGRP)</a>
IHTTPStreamerSanJoseIndex	<a href="#">getIndexLive(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName)</a>
void	<a href="#">indexTranscoderVOD(IHTTPStreamerApplicationContext appContext, String vodTranscodeNGRP)</a>
boolean	<a href="#">isFirstABSTRequest(String streamName)</a>
void	<a href="#">logLiveChunk(LiveStreamPacketizerSanJoseChunk chunk)</a>
void	<a href="#">logVODChunk(LiveStreamPacketizerSanJoseChunk chunk)</a>
void	<a href="#">notifyHTTPSessionCreate(IApplicationInstance appInstance, IHTTPStreamerSession httpStreamerSession)</a>
void	<a href="#">notifyHTTPSessionDestroy(IApplicationInstance appInstance, IHTTPStreamerSession httpStreamerSession)</a>
void	<a href="#">shutdown()</a>
void	<a href="#">updateLoggingValues()</a>

Methods inherited from class `com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase`

```

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr,
addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues,
containsStreamDomainStr, containsStreamNameParts, doSessionRedirect,
doSessionRedirect, extractHTTPRequestInfo, getAndClearNotifyCreate, getAppInstance,
getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo,
getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader,
getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest,
getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties,
getQueryStr, getRedirectSessionBody, getRedirectSessionCode,
getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp,
getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType,
getStream, getStreamDomainStr, getStreamDomainStrList, getStreamExt, getStreamName,
getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds,
getTranscoderVODIndex, getTranscoderVODIndex, getTranscoderVODIndexDestinationsMap,
getTranscoderVODIndexDestinationsOrder, getTranscoderVODSession, getUri,
getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, getVODTranscodeNGRP,
indexTranscoderVOD, isAcceptSession, isActive, isFileInfo, isHTTPOrigin,
isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated,
isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts,
redirectSession, redirectSession, rejectSession, removeStreamDomainStr,
setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo,
setHTTPOrigin, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer,
setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession,
setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType,
setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId,
setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt,
setStreamName, setStreamPosition, setThreadContext, setTimeoutSession,
setTranscoderVODIndex, setTranscoderVODSession, setUri, setUserAgent,
setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, setVODTranscodeNGRP,
shutdown, shutdownLocked, touch, updateLoggingValues, validStreamDomainToString

```

#### Methods inherited from class java.lang.Object

```

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

```

#### Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),  
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),  
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),  
[doSessionRedirect](#), [extractHTTPRequestInfo](#), [getAndClearNotifyCreate](#), [getAppInstance](#),  
[getConnectionHolder](#), [getCookieStr](#), [getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#),  
[getHTTPHeader](#), [getHTTPHeaderMap](#), [getHTTPHeaderNames](#), [getHTTPIntHeader](#),  
[getHTTPStreamerAdapter](#), [getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#),  
[getLiveStreamingPacketizer](#), [getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#),  
[getQueryStr](#), [getRedirectSessionBody](#), [getRedirectSessionCode](#),  
[getRedirectSessionContentType](#), [getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#),  
[getServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[getStream](#), [getStreamExt](#), [getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#),  
[getTimeRunning](#), [getTimeRunningSeconds](#), [getTranscoderVODIndex](#), [getTranscoderVODIndex](#),  
[getTranscoderVODIndexDestinationsMap](#), [getTranscoderVODIndexDestinationsOrder](#),  
[getTranscoderVODSession](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),  
[getVHost](#), [getVODTranscodeNGRP](#), [indexTranscoderVOD](#), [isAcceptSession](#), [isActive](#),  
[isFileInfo](#), [isHTTPOrigin](#), [isPlayLogged](#), [isRedirectSession](#), [isTimeout](#),  
[isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#), [lockRepeaterStreams](#),  
[putFileInfo](#), [putStreamNameParts](#), [redirectSession](#), [redirectSession](#), [rejectSession](#),  
[removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#), [setAppInstance](#), [setCookieStr](#),  
[setDvrSessionInfo](#), [setHTTPOrigin](#), [setHTTPStreamerAdapter](#), [setIpAddress](#),  
[setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#), [setPlayStart](#),  
[setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#), [setRedirectSessionCode](#),  
[setRedirectSessionContentType](#), [setRedirectSessionURL](#), [setReferrer](#), [setServerIp](#),  
[setServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[setStream](#), [setStreamExt](#), [setStreamName](#), [setStreamPosition](#), [setTimeoutSession](#),  
[setTranscoderVODIndex](#), [setTranscoderVODSession](#), [setUri](#), [setUserAgent](#),  
[setUserHTTPHeader](#), [setUserQueryStr](#), [setVHost](#), [setVODTranscodeNGRP](#), [shutdown](#), [touch](#),  
[updateLoggingValues](#), [validStreamDomainToString](#)

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPSessionNotify](#)

[notifyHTTPSessionCreate](#), [notifyHTTPSessionDestroy](#)

## Constructors

### HTTPStreamerSessionSanJose

```
public HTTPStreamerSessionSanJose()
```

## Methods

### shutdown

```
public void shutdown()
```

### containsIndex

```
public boolean containsIndex(String streamName)
```

## createIndexLive

```
public static IHTTPStreamerSanJoseIndex  
createIndexLive(IHTTPStreamerApplicationContext appContext,  
                IHTTPStreamerSession httpStreamerSession,  
                String rawStreamName,  
                String streamExt,  
                String streamName)
```

---

## getIndexLive

```
public IHTTPStreamerSanJoseIndex getIndexLive(IHTTPStreamerApplicationContext  
appContext,  
        IHTTPStreamerSession httpStreamerSession,  
        String rawStreamName,  
        String streamExt,  
        String streamName)
```

---

## getIndex

```
public IHTTPStreamerSanJoseIndex getIndex(IHTTPStreamerApplicationContext appContext,  
        IHTTPStreamerSession httpStreamerSession,  
        String rawStreamName,  
        String streamExt,  
        String streamName,  
        long playStart,  
        long playDuration,  
        TimedTextRequest captionRequest,  
        String vodTranscodeNGRP)
```

---

## updateLoggingValues

```
public void updateLoggingValues()
```

---

## clearLoggingValues

```
public void clearLoggingValues()
```

---

## logLiveChunk

```
public void logLiveChunk(LiveStreamPacketizerSanJoseChunk chunk)
```

---

## logVODChunk

```
public void logVODChunk(LiveStreamPacketizerSanJoseChunk chunk)
```

---

---

### isFirstABSTRequest

```
public boolean isFirstABSTRequest(String streamName)
```

---

### addFirstABSTRequest

```
public void addFirstABSTRequest(String streamName)
```

---

### notifyHTTPSessionCreate

```
public void notifyHTTPSessionCreate(IApplicationInstance appInstance,  
    IHTTPStreamerSession httpStreamerSession)
```

---

### notifyHTTPSessionDestroy

```
public void notifyHTTPSessionDestroy(IApplicationInstance appInstance,  
    IHTTPStreamerSession httpStreamerSession)
```

---

### indexTranscoderVOD

```
public void indexTranscoderVOD(IHTTPStreamerApplicationContext appContext,  
    String vodTranscodeNGRP)
```

---

---

Package

**com.wowza.wms.httpstreamer.smoothstream  
ing.httpstreamer**

## com.wowza.wms.httpstreamer.smoothstreaming.httpstreamer Class HTTPStreamerSessionSmoothStreamer

java.lang.Object

└─com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.smoothstreaming.httpstreamer.HTTPStreamerSessionSmoothStreamer

All Implemented Interfaces:

[IHTTPSessionNotify](#), [IHTTPStreamerSession](#)

public class **HTTPStreamerSessionSmoothStreamer**  
 extends HTTPStreamerSessionBase  
 implements [IHTTPStreamerSession](#), [IHTTPSessionNotify](#)

### Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isHTTPOrigin, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, notifyCreate, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, transcoderVODIndex, transcoderVODIndexDestinationsMap, transcoderVODIndexDestinationsOrder, transcoderVODSession, uri, userAgent, userHTTPHeaders, userQueryStr, vhost, vodTranscodeNGRP

### Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL\\_COUNT](#), [SESSIONPROTOCOL\\_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL\\_DIRECTSTREAMING](#), [SESSIONPROTOCOL\\_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL\\_MPEGDASHSTREAMING](#), [SESSIONPROTOCOL\\_SANJOSESTREAMING](#), [SESSIONPROTOCOL\\_SMOOTHSTREAMING](#), [SESSIONPROTOCOL\\_UNKNOWN](#), [SESSIONPROTOCOL\\_WEBMSTREAMING](#), [SESSIONTYPE\\_LIVE](#), [SESSIONTYPE\\_LIVEDVR](#), [SESSIONTYPE\\_UNKNOWN](#), [SESSIONTYPE\\_VOD](#)

## Constructor Summary

public	<a href="#">HTTPStreamerSessionSmoothStreamer()</a>
--------	---

## Method Summary

void	<a href="#">clearLoggingValues()</a>
------	--------------------------------------

boolean	<a href="#">containsIndex</a> (String streamName)
---------	---

IHTTPStreamerSmoothStreamerIndex	<a href="#">getIndex</a> ( <a href="#">IHTTPStreamerSession</a> httpStreamerSession, <a href="#">IHTTPStreamerApplicationContext</a> appContext, String streamExt, String streamName, long playStart, long playDuration, String vodTranscodeNGRP)
----------------------------------	---

SmoothStreamingLivePlaylist	<a href="#">getLivePlaylist()</a>
void	<a href="#">indexTranscoderVOD(IHTTPStreamerApplicationContext appContext, String vodTranscodeNGRP)</a>
void	<a href="#">logLiveFragment</a> (SmoothStreamerFragmentId fragmentId, PacketFragmentList fragmentData)
void	<a href="#">logVODFragment</a> (SmoothStreamerFragmentId fragmentId, PacketFragmentList fragmentData)
void	<a href="#">notifyHTTPSessionCreate(IApplicationInstance appInstance, IHTTPStreamerSession httpStreamerSession)</a>
void	<a href="#">notifyHTTPSessionDestroy(IApplicationInstance appInstance, IHTTPStreamerSession httpStreamerSession)</a>
void	<a href="#">setLivePlaylist</a> (SmoothStreamingLivePlaylist livePlaylist)
void	<a href="#">shutdown()</a>
void	<a href="#">updateLoggingValues()</a>

#### Methods inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr, addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues, containsStreamDomainStr, containsStreamNameParts, doSessionRedirect, doSessionRedirect, extractHTTPRequestInfo, getAndClearNotifyCreate, getAppInstance, getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo, getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader, getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest, getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties, getQueryStr, getRedirectSessionBody, getRedirectSessionCode, getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp, getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType, getStream, getStreamDomainStr, getStreamDomainStrList, getStreamExt, getStreamName, getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds, getTranscoderVODIndex, getTranscoderVODIndex, getTranscoderVODIndexDestinationsMap, getTranscoderVODIndexDestinationsOrder, getTranscoderVODSession, getUri, getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, getVODTranscodeNGRP, indexTranscoderVOD, isAcceptSession, isActive, isFileInfo, isHTTPOrigin, isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated, isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts, redirectSession, redirectSession, rejectSession, removeStreamDomainStr, setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo, setHTTPOrigin, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer, setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession, setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType, setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId, setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt, setStreamName, setStreamPosition, setThreadContext, setTimeoutSession, setTranscoderVODIndex, setTranscoderVODSession, setUri, setUserAgent, setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, setVODTranscodeNGRP, shutdown, shutdownLocked, touch, updateLoggingValues, validStreamDomainToString



**Methods inherited from class `java.lang.Object`**

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

**Methods inherited from interface `com.wowza.wms.httpstreamer.model.IHTTPStreamerSession`**

[`acceptSession`](#), [`addIOPerformance`](#), [`addIOPerformance2`](#), [`addStreamDomainStr`](#), [`addStreamDomainStrs`](#), [`addUserHTTPHeaders`](#), [`checkAndSetPlayLogged`](#), [`clearLoggingValues`](#), [`containsStreamDomainStr`](#), [`containsStreamNameParts`](#), [`doSessionRedirect`](#), [`doSessionRedirect`](#), [`extractHTTPRequestInfo`](#), [`getAndClearNotifyCreate`](#), [`getAppInstance`](#), [`getConnectionHolder`](#), [`getCookieStr`](#), [`getDvrSessionInfo`](#), [`getElapsedTime`](#), [`getFileInfo`](#), [`getHTTPHeader`](#), [`getHTTPHeaderMap`](#), [`getHTTPHeaderNames`](#), [`getHTTPIntHeader`](#), [`getHTTPStreamerAdapter`](#), [`getIOPerformanceCounter`](#), [`getIpAddress`](#), [`getLastRequest`](#), [`getLiveStreamingPacketizer`](#), [`getLock`](#), [`getPlayDuration`](#), [`getPlayStart`](#), [`getProperties`](#), [`getQueryStr`](#), [`getRedirectSessionBody`](#), [`getRedirectSessionCode`](#), [`getRedirectSessionContentType`](#), [`getRedirectSessionURL`](#), [`getReferrer`](#), [`getServerIp`](#), [`getServerPort`](#), [`getSessionId`](#), [`getSessionProtocol`](#), [`getSessionTimeout`](#), [`getSessionType`](#), [`getStream`](#), [`getStreamExt`](#), [`getStreamName`](#), [`getStreamNameParts`](#), [`getStreamPosition`](#), [`getTimeRunning`](#), [`getTimeRunningSeconds`](#), [`getTranscoderVODIndex`](#), [`getTranscoderVODIndex`](#), [`getTranscoderVODIndexDestinationsMap`](#), [`getTranscoderVODIndexDestinationsOrder`](#), [`getTranscoderVODSession`](#), [`getUri`](#), [`getUserAgent`](#), [`getUserHTTPHeaders`](#), [`getUserQueryStr`](#), [`getVHost`](#), [`getVODTranscodeNGRP`](#), [`indexTranscoderVOD`](#), [`isAcceptSession`](#), [`isActive`](#), [`isFileInfo`](#), [`isHTTPOrigin`](#), [`isPlayLogged`](#), [`isRedirectSession`](#), [`isTimeout`](#), [`isTimeoutSession`](#), [`isValidated`](#), [`isValidStreamDomainStr`](#), [`lockRepeaterStreams`](#), [`putFileInfo`](#), [`putStreamNameParts`](#), [`redirectSession`](#), [`redirectSession`](#), [`rejectSession`](#), [`removeStreamDomainStr`](#), [`setAcceptSession`](#), [`setActive`](#), [`setAppInstance`](#), [`setCookieStr`](#), [`setDvrSessionInfo`](#), [`setHTTPOrigin`](#), [`setHTTPStreamerAdapter`](#), [`setIpAddress`](#), [`setLiveStreamingPacketizer`](#), [`setPlayDuration`](#), [`setPlayLogged`](#), [`setPlayStart`](#), [`setQueryStr`](#), [`setRedirectSession`](#), [`setRedirectSessionBody`](#), [`setRedirectSessionCode`](#), [`setRedirectSessionContentType`](#), [`setRedirectSessionURL`](#), [`setReferrer`](#), [`setServerIp`](#), [`setServerPort`](#), [`getSessionId`](#), [`getSessionProtocol`](#), [`getSessionTimeout`](#), [`getSessionType`](#), [`setStream`](#), [`setStreamExt`](#), [`setStreamName`](#), [`setStreamPosition`](#), [`setTimeoutSession`](#), [`setTranscoderVODIndex`](#), [`setTranscoderVODSession`](#), [`setUri`](#), [`setUserAgent`](#), [`setUserHTTPHeader`](#), [`setUserQueryStr`](#), [`setVHost`](#), [`setVODTranscodeNGRP`](#), [`shutdown`](#), [`touch`](#), [`updateLoggingValues`](#), [`validStreamDomainToString`](#)

**Methods inherited from interface `com.wowza.wms.httpstreamer.model.IHTTPSessionNotify`**

[`notifyHTTPSessionCreate`](#), [`notifyHTTPSessionDestroy`](#)

## Constructors

### `HTTPStreamerSessionSmoothStreamer`

```
public HTTPStreamerSessionSmoothStreamer()
```

## Methods

### `shutdown`

```
public void shutdown()
```

(continued from last page)

---

## containsIndex

```
public boolean containsIndex(String streamName)
```

---

## getIndex

```
public IHTTPStreamerSmoothStreamerIndex getIndex(IHTTPStreamerSession  
httpStreamerSession,  
    IHTTPStreamerApplicationContext appContext,  
    String streamExt,  
    String streamName,  
    long playStart,  
    long playDuration,  
    String vodTranscodeNGRP)
```

---

## updateLoggingValues

```
public void updateLoggingValues()
```

---

## clearLoggingValues

```
public void clearLoggingValues()
```

---

## getLivePlaylist

```
public SmoothStreamingLivePlaylist getLivePlaylist()
```

---

## setLivePlaylist

```
public void setLivePlaylist(SmoothStreamingLivePlaylist livePlaylist)
```

---

## logLiveFragment

```
public void logLiveFragment(SmoothStreamerFragmentId fragmentId,  
    PacketFragmentList fragmentData)
```

---

## logVODFragment

```
public void logVODFragment(SmoothStreamerFragmentId fragmentId,  
    PacketFragmentList fragmentData)
```

---

(continued from last page)

## **notifyHTTPSessionCreate**

```
public void notifyHTTPSessionCreate(IApplicationInstance appInstance,  
    IHTTPStreamerSession httpStreamerSession)
```

---

## **notifyHTTPSessionDestroy**

```
public void notifyHTTPSessionDestroy(IApplicationInstance appInstance,  
    IHTTPStreamerSession httpStreamerSession)
```

---

## **indexTranscoderVOD**

```
public void indexTranscoderVOD(IHTTPStreamerApplicationContext appContext,  
    String vodTranscodeNGRP)
```

---

Package

**com.wowza.wms.httpstreamer.webmstreami  
ng.httpstreamer**

## com.wowza.wms.httpstreamer.webmstreaming.httpstreamer

### Class HTTPStreamerSessionWebM

java.lang.Object

└─com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─com.wowza.wms.httpstreamer.webmstreaming.httpstreamer.HTTPStreamerSessionWebM

All Implemented Interfaces:

[IHTTPStreamerSession](#)

public class **HTTPStreamerSessionWebM**  
extends HTTPStreamerSessionBase

#### Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isHTTPOrigin, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, notifyCreate, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, transcoderVODIndex, transcoderVODIndexDestinationsMap, transcoderVODIndexDestinationsOrder, transcoderVODSession, uri, userAgent, userHTTPHeaders, userQueryStr, vhost, vodTranscodeNGRP

#### Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL\\_COUNT](#), [SESSIONPROTOCOL\\_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL\\_DIRECTSTREAMING](#), [SESSIONPROTOCOL\\_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL\\_MPEGDASHSTREAMING](#), [SESSIONPROTOCOL\\_SANJOSESTREAMING](#), [SESSIONPROTOCOL\\_SMOOTHSTREAMING](#), [SESSIONPROTOCOL\\_UNKNOWN](#), [SESSIONPROTOCOL\\_WEBMSTREAMING](#), [SESSIONTYPE\\_LIVE](#), [SESSIONTYPE\\_LIVEDVR](#), [SESSIONTYPE\\_UNKNOWN](#), [SESSIONTYPE\\_VOD](#)

### Constructor Summary

public	<a href="#">HTTPStreamerSessionWebM()</a>
--------	---

### Method Summary

WebMPacketizerSessionTracker	<a href="#">getSessionTracker()</a>
void	<a href="#">setSessionTracker</a> (WebMPacketizerSessionTracker sessionTracker)
void	<a href="#">shutdown()</a>

#### Methods inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

```

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr,
addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues,
containsStreamDomainStr, containsStreamNameParts, doSessionRedirect,
doSessionRedirect, extractHTTPRequestInfo, getAndClearNotifyCreate, getAppInstance,
getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo,
getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader,
getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest,
getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties,
getQueryStr, getRedirectSessionBody, getRedirectSessionCode,
getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp,
getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType,
getStream, getStreamDomainStr, getStreamDomainStrList, getStreamExt, getStreamName,
getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds,
getTranscoderVODIndex, getTranscoderVODIndex, getTranscoderVODIndexDestinationsMap,
getTranscoderVODIndexDestinationsOrder, getTranscoderVODSession, getUri,
getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, getVODTranscodeNGRP,
indexTranscoderVOD, isAcceptSession, isActive, isFileInfo, isHTTPOrigin,
isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated,
isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts,
redirectSession, redirectSession, rejectSession, removeStreamDomainStr,
setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo,
setHTTPOrigin, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer,
setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession,
setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType,
setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId,
setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt,
setStreamName, setStreamPosition, setThreadContext, setTimeoutSession,
setTranscoderVODIndex, setTranscoderVODSession, setUri, setUserAgent,
setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, setVODTranscodeNGRP,
shutdown, shutdownLocked, touch, updateLoggingValues, validStreamDomainToString

```

#### Methods inherited from class java.lang.Object

```

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

```

#### Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),  
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),  
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),  
[doSessionRedirect](#), [extractHTTPRequestInfo](#), [getAndClearNotifyCreate](#), [getAppInstance](#),  
[getConnectionHolder](#), [getCookieStr](#), [getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#),  
[getHTTPHeader](#), [getHTTPHeaderMap](#), [getHTTPHeaderNames](#), [getHTTPIntHeader](#),  
[getHTTPStreamerAdapter](#), [getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#),  
[getLiveStreamingPacketizer](#), [getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#),  
[getQueryStr](#), [getRedirectSessionBody](#), [getRedirectSessionCode](#),  
[getRedirectSessionContentType](#), [getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#),  
[getServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[getStream](#), [getStreamExt](#), [getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#),  
[getTimeRunning](#), [getTimeRunningSeconds](#), [getTranscoderVODIndex](#), [getTranscoderVODIndex](#),  
[getTranscoderVODIndexDestinationsMap](#), [getTranscoderVODIndexDestinationsOrder](#),  
[getTranscoderVODSession](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),  
[getVHost](#), [getVODTranscodeNGRP](#), [indexTranscoderVOD](#), [isAcceptSession](#), [isActive](#),  
[isFileInfo](#), [isHTTPOrigin](#), [isPlayLogged](#), [isRedirectSession](#), [isTimeout](#),  
[isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#), [lockRepeaterStreams](#),  
[putFileInfo](#), [putStreamNameParts](#), [redirectSession](#), [redirectSession](#), [rejectSession](#),  
[removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#), [setAppInstance](#), [setCookieStr](#),  
[setDvrSessionInfo](#), [setHTTPOrigin](#), [setHTTPStreamerAdapter](#), [setIpAddress](#),  
[setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#), [setPlayStart](#),  
[setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#), [setRedirectSessionCode](#),  
[setRedirectSessionContentType](#), [setRedirectSessionURL](#), [setReferrer](#), [setServerIp](#),  
[setServerPort](#), [getSessionId](#), [getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#),  
[setStream](#), [setStreamExt](#), [setStreamName](#), [setStreamPosition](#), [setTimeoutSession](#),  
[setTranscoderVODIndex](#), [setTranscoderVODSession](#), [setUri](#), [setUserAgent](#),  
[setUserHTTPHeader](#), [setUserQueryStr](#), [setVHost](#), [setVODTranscodeNGRP](#), [shutdown](#), [touch](#),  
[updateLoggingValues](#), [validStreamDomainToString](#)

## Constructors

### HTTPStreamerSessionWebM

```
public HTTPStreamerSessionWebM()
```

## Methods

### getSessionTracker

```
public WebMPacketizerSessionTracker getSessionTracker()
```

### setSessionTracker

```
public void setSessionTracker(WebMPacketizerSessionTracker sessionTracker)
```

### shutdown

```
public void shutdown()
```

(continued from last page)




---

Package

**com.wowza.wms.livestreamrecord.http**

## com.wowza.wms.livestreamrecord.http Class HTTPLiveStreamRecord

java.lang.Object



### All Implemented Interfaces:

com.wowza.wms.livestreamrecord.streamnamerecorder.ILiveStreamRecordStreamNameRecorderActionNotify,  
[IHTTPProvider2](#)

public class **HTTPLiveStreamRecord**

extends [HTTPProvider2Base](#)

implements [IHTTPProvider2](#),

com.wowza.wms.livestreamrecord.streamnamerecorder.ILiveStreamRecordStreamNameRecorderActionNotify

### Field Summary

public static final	<a href="#">FORMAT_FLV</a> Value: <b>1</b>
public static final	<a href="#">FORMAT_MP4</a> Value: <b>2</b>
public static final	<a href="#">FORMAT_UNKNOWN</a> Value: <b>0</b>

### Fields inherited from class [com.wowza.wms.http.HTTPProvider2Base](#)

[authenticateHandler](#), [authenticateHTTPProviderHandler](#), [authenticationMethod](#), [filters](#),  
[properties](#), [requestFilters](#)

### Constructor Summary

public	<a href="#">HTTPLiveStreamRecord()</a>
--------	--

### Method Summary

static String	<a href="#">HTMLEncode</a> (String s)
void	<a href="#">init</a> ()
void	<a href="#">onBind</a> ( <a href="#">IVHost</a> vhost, <a href="#">HostPort</a> hostPort)
void	<a href="#">onHTTPRequest</a> ( <a href="#">IVHost</a> vhost, <a href="#">IHTTPRequest</a> req, <a href="#">IHTTPResponse</a> resp)

void	<a href="#">onStartRecord(IApplicationInstance</a> appInstance, <a href="#">IMediaStream</a> stream, String streamName, Object opaque)
void	<a href="#">onStopRecord(IApplicationInstance</a> appInstance, <a href="#">IMediaStream</a> stream, String streamName, Object opaque)
void	<a href="#">onSwitchRecord(IApplicationInstance</a> appInstance, <a href="#">IMediaStream</a> streamOld, <a href="#">IMediaStream</a> streamNew, String streamName, Object opaque)

#### Methods inherited from class [com.wowza.wms.http.HTTPProvider2Base](#)

[canHandle](#), [doHTTPAuthentication](#), [getAuthenticationMethod](#), [getPath](#), [getRequestFilters](#), [init](#), [onBind](#), [onUnbind](#), [setAuthenticationMethod](#), [setProperties](#), [setRequestFilters](#)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface [com.wowza.wms.http.IHTTPProvider2](#)

[canHandle](#), [getAuthenticationMethod](#), [getRequestFilters](#), [init](#), [setAuthenticationMethod](#), [setRequestFilters](#)

#### Methods inherited from interface [com.wowza.wms.http.IHTTPProvider](#)

[onBind](#), [onHTTPRequest](#), [onUnbind](#), [setProperties](#)

#### Methods inherited from interface

com.wowza.wms.livestreamrecord.streamnamerecorder.ILiveStreamRecordStreamNameRecorderActionNotify

onStartRecord, onStopRecord, onSwitchRecord

## Fields

### FORMAT\_UNKNOWN

```
public static final int FORMAT_UNKNOWN
```

Constant value: **0**

### FORMAT\_FLV

```
public static final int FORMAT_FLV
```

Constant value: **1**

### FORMAT\_MP4

```
public static final int FORMAT_MP4
```

Constant value: **2**

## Constructors

### HTTPLiveStreamRecord

```
public HTTPLiveStreamRecord()
```

## Methods

### HTMLEncode

```
public static String HTMLEncode(String s)
```

---

### init

```
public void init()
```

Initialize the HTTPProvider

---

### onBind

```
public void onBind(IVHost vhost,  
                  HostPort hostPort)
```

Called when bind is called on port

---

### onHTTPRequest

```
public void onHTTPRequest(IVHost vhost,  
                          IHTTPRequest req,  
                          IHTTPResponse resp)
```

---

### onStartRecord

```
public void onStartRecord(IApplicationInstance appInstance,  
                          IMediaStream stream,  
                          String streamName,  
                          Object opaque)
```

---

### onSwitchRecord

```
public void onSwitchRecord(IApplicationInstance appInstance,  
                           IMediaStream streamOld,  
                           IMediaStream streamNew,  
                           String streamName,  
                           Object opaque)
```

---

(continued from last page)

## onStopRecord

```
public void onStopRecord(IApplicationInstance appInstance,  
    IMediaStream stream,  
    String streamName,  
    Object opaque)
```

---

Package

**com.wowza.wms.livestreamrecord.model**

## com.wowza.wms.livestreamrecord.model Interface **ILiveStreamRecord**

All Known Implementing Classes:  
[LiveStreamRecorderBase](#)

public interface **ILiveStreamRecord**  
 extends

### Field Summary

public static final	<a href="#">SPLIT_ON_DISCONTINUITY_ALWAYS</a> Value: <b>1</b>
public static final	<a href="#">SPLIT_ON_DISCONTINUITY_DEFAULT</a> Value: <b>0</b>
public static final	<a href="#">SPLIT_ON_DISCONTINUITY_NEVER</a> Value: <b>2</b>
public static final	<a href="#">SPLIT_TYPE_BY_DURATION</a> Value: <b>3</b>
public static final	<a href="#">SPLIT_TYPE_BY_SCHEDULE</a> Value: <b>1</b>
public static final	<a href="#">SPLIT_TYPE_BY_SIZE</a> Value: <b>2</b>
public static final	<a href="#">SPLIT_TYPE_NONE</a> Value: <b>0</b>

### Method Summary

<a href="#">ILiveStreamRecordNotify</a>	<a href="#">addListener()</a> ( <a href="#">ILiveStreamRecordNotify</a> listener)
String	<a href="#">getBaseFilePath()</a>
long	<a href="#">getCurrentDuration()</a>
String	<a href="#">getCurrentFile()</a>
long	<a href="#">getCurrentSize()</a>
String	<a href="#">getFilePath()</a>

<a href="#"><u>ILiveStreamRecordFileVersionDelegate</u></a>	<a href="#"><u>getFileVersionDelegate()</u></a>
long	<a href="#"><u>getSegmentDuration()</u></a>
int	<a href="#"><u>getSegmentNumber()</u></a>
<a href="#"><u>CrontabEvent</u></a>	<a href="#"><u>getSegmentSchedule()</u></a>
long	<a href="#"><u>getSegmentSize()</u></a>
int	<a href="#"><u>getSplitType()</u></a>
org.joda.time.DateTim e	<a href="#"><u>getStartTime()</u></a>
String	<a href="#"><u>getStreamName()</u></a>
Object	<a href="#"><u>getWriteLock()</u></a>
void	<a href="#"><u>init()</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance)
boolean	<a href="#"><u>isAppendFile()</u></a>
boolean	<a href="#"><u>isMoveFirstVideoFrameToZero()</u></a>
boolean	<a href="#"><u>isRecordData()</u></a>
boolean	<a href="#"><u>isStartOnKeyFrame()</u></a>
boolean	<a href="#"><u>isVersionFile()</u></a>
void	<a href="#"><u>onPublish()</u></a>
void	<a href="#"><u>onUnPublish()</u></a>
boolean	<a href="#"><u>removeListener()</u></a> ( <a href="#"><u>ILiveStreamRecordNotify</u></a> listener)
void	<a href="#"><u>setFileVersionDelegate()</u></a> ( <a href="#"><u>ILiveStreamRecordFileVersionDelegate</u></a> delegate)
void	<a href="#"><u>setMoveFirstVideoFrameToZero()</u></a> (boolean moveFirstVideoFrameToZero)
void	<a href="#"><u>setRecordData()</u></a> (boolean recordData)
void	<a href="#"><u>setSegmentDuration()</u></a> (long duration)
void	<a href="#"><u>setSegmentSize()</u></a> (long size)
void	<a href="#"><u>setStartOnKeyFrame()</u></a> (boolean startOnKeyFrame)



void	<a href="#"><u>setVersionFile</u></a> (boolean versionFile)
void	<a href="#"><u>splitRecordingNow</u></a> ()
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, boolean append)
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, boolean append)
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, boolean append, java.util.Map extraMetadata)
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, boolean append, java.util.Map extraMetadata, int splitOnTcDiscontinuity)
void	<a href="#"><u>startRecordingSegmentByDuration</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, java.util.Map extraMetadata, long duration)
void	<a href="#"><u>startRecordingSegmentBySchedule</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, java.util.Map extraMetadata, String schedule)
void	<a href="#"><u>startRecordingSegmentBySize</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, java.util.Map extraMetadata, long size)
void	<a href="#"><u>stopRecording</u></a> ()
void	<a href="#"><u>work</u></a> ()
void	<a href="#"><u>workStop</u></a> ()

## Fields

### SPLIT\_TYPE\_NONE

```
public static final int SPLIT_TYPE_NONE
```

Constant value: **0**

### SPLIT\_TYPE\_BY\_SCHEDULE

```
public static final int SPLIT_TYPE_BY_SCHEDULE
```

Constant value: **1**

### SPLIT\_TYPE\_BY\_SIZE

```
public static final int SPLIT_TYPE_BY_SIZE
```

Constant value: **2**

---

## SPLIT\_TYPE\_BY\_DURATION

```
public static final int SPLIT_TYPE_BY_DURATION
```

Constant value: **3**

---

## SPLIT\_ON\_DISCONTINUITY\_DEFAULT

```
public static final int SPLIT_ON_DISCONTINUITY_DEFAULT
```

Constant value: **0**

---

## SPLIT\_ON\_DISCONTINUITY\_ALWAYS

```
public static final int SPLIT_ON_DISCONTINUITY_ALWAYS
```

Constant value: **1**

---

## SPLIT\_ON\_DISCONTINUITY\_NEVER

```
public static final int SPLIT_ON_DISCONTINUITY_NEVER
```

Constant value: **2**

## Methods

### init

```
public void init(IApplicationInstance appInstance)
```

---

### startRecording

```
public void startRecording(IMediaStream stream,  
    boolean append)
```

---

### startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append)
```

---

### getFilePath

```
public String getFilePath()
```

---

(continued from last page)

---

## isStartOnKeyFrame

```
public boolean isStartOnKeyFrame()
```

---

## setStartOnKeyFrame

```
public void setStartOnKeyFrame(boolean startOnKeyFrame)
```

---

## startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata)
```

---

## startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata,  
    int splitOnTcDiscontinuity)
```

---

## startRecordingSegmentBySize

```
public void startRecordingSegmentBySize(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long size)
```

---

## startRecordingSegmentByDuration

```
public void startRecordingSegmentByDuration(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long duration)
```

---

## startRecordingSegmentBySchedule

```
public void startRecordingSegmentBySchedule(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    String schedule)
```

---

(continued from last page)

## **stopRecording**

```
public void stopRecording()
```

---

## **onPublish**

```
public void onPublish()
```

---

## **onUnPublish**

```
public void onUnPublish()
```

---

## **workStop**

```
public void workStop()
```

---

## **work**

```
public void work()
```

---

## **isRecordData**

```
public boolean isRecordData()
```

---

## **setRecordData**

```
public void setRecordData(boolean recordData)
```

---

## **isVersionFile**

```
public boolean isVersionFile()
```

---

## **setVersionFile**

```
public void setVersionFile(boolean versionFile)
```

---

## **isAppendFile**

```
public boolean isAppendFile()
```

---

(continued from last page)

---

**getWriteLock**

```
public Object getWriteLock()
```

---

**isMoveFirstVideoFrameToZero**

```
public boolean isMoveFirstVideoFrameToZero()
```

---

**setMoveFirstVideoFrameToZero**

```
public void setMoveFirstVideoFrameToZero(boolean moveFirstVideoFrameToZero)
```

---

**setFileVersionDelegate**

```
public void setFileVersionDelegate(ILiveStreamRecordFileVersionDelegate delegate)
```

---

**getFileVersionDelegate**

```
public ILiveStreamRecordFileVersionDelegate getFileVersionDelegate()
```

---

**splitRecordingNow**

```
public void splitRecordingNow()
```

---

**getSplitType**

```
public int getSplitType()
```

---

**getSegmentSize**

```
public long getSegmentSize()
```

---

**getSegmentDuration**

```
public long getSegmentDuration()
```

---

(continued from last page)

### getCurrentSize

```
public long getCurrentSize()
```

---

### getCurrentDuration

```
public long getCurrentDuration()
```

---

### setSegmentSize

```
public void setSegmentSize(long size)
```

---

### setSegmentDuration

```
public void setSegmentDuration(long duration)
```

---

### getBaseFilePath

```
public String getBaseFilePath()
```

---

### getCurrentFile

```
public String getCurrentFile()
```

---

### getSegmentSchedule

```
public CrontabEvent getSegmentSchedule()
```

---

### getStreamName

```
public String getStreamName()
```

---

### getSegmentNumber

```
public int getSegmentNumber()
```

---

### getStartTime

```
public org.joda.time.DateTime getStartTime()
```

---

(continued from last page)

---

## **addListener**

```
public ILiveStreamRecordNotify addListener(ILiveStreamRecordNotify listener)
```

---

## **removeListener**

```
public boolean removeListener(ILiveStreamRecordNotify listener)
```

## com.wowza.wms.livestreamrecord.model

# Interface ILiveStreamRecordFileVersionDelegate

All Known Implementing Classes:

[LiveStreamRecordFileVersionDelegate](#)

---

public interface **ILiveStreamRecordFileVersionDelegate**  
extends

---

## Method Summary

String	<a href="#">getFilename</a> ( <a href="#">ILiveStreamRecord</a> recorder)
--------	---

---

## Methods

### getFilename

public String **getFilename**([ILiveStreamRecord](#) recorder)



---

## com.wowza.wms.livestreamrecord.model Interface **ILiveStreamRecordNotify**

---

public interface **ILiveStreamRecordNotify**  
extends

---

### Method Summary

void	<a href="#">onSegmentEnd</a> ( <a href="#">ILiveStreamRecord</a> recorder)
void	<a href="#">onSegmentStart</a> ( <a href="#">ILiveStreamRecord</a> recorder)

---

### Methods

#### **onSegmentStart**

public void **onSegmentStart**([ILiveStreamRecord](#) recorder)

---

#### **onSegmentEnd**

public void **onSegmentEnd**([ILiveStreamRecord](#) recorder)

## com.wowza.wms.livestreamrecord.model Class LiveStreamRecordActionNotifier

java.lang.Object

└─com.wowza.wms.livestreamrecord.model.LiveStreamRecordActionNotifier

All Implemented Interfaces:

[IMediaStreamActionNotify](#)

public class **LiveStreamRecordActionNotifier**  
extends Object  
implements [IMediaStreamActionNotify](#)

### Method Summary

void	<a href="#">onPause</a> ( <a href="#">IMediaStream</a> stream, boolean isPause, double location)
void	<a href="#">onPlay</a> ( <a href="#">IMediaStream</a> stream, String streamName, double playStart, double playLen, int playReset)
void	<a href="#">onPublish</a> ( <a href="#">IMediaStream</a> stream, String streamName, boolean isRecord, boolean isAppend)
void	<a href="#">onSeek</a> ( <a href="#">IMediaStream</a> stream, double location)
void	<a href="#">onStop</a> ( <a href="#">IMediaStream</a> stream)
void	<a href="#">onUnPublish</a> ( <a href="#">IMediaStream</a> stream, String streamName, boolean isRecord, boolean isAppend)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify](#)

[onPause](#), [onPlay](#), [onPublish](#), [onSeek](#), [onStop](#), [onUnPublish](#)

### Methods

#### onPause

```
public void onPause(IMediaStream stream,
                    boolean isPause,
                    double location)
```

## onPlay

```
public void onPlay(IMediaStream stream,  
    String streamName,  
    double playStart,  
    double playLen,  
    int playReset)
```

---

## onPublish

```
public void onPublish(IMediaStream stream,  
    String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

---

## onSeek

```
public void onSeek(IMediaStream stream,  
    double location)
```

---

## onStop

```
public void onStop(IMediaStream stream)
```

---

## onUnPublish

```
public void onUnPublish(IMediaStream stream,  
    String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

---

## com.wowza.wms.livestreamrecord.model Class LiveStreamRecorderBase

java.lang.Object

└-com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase

All Implemented Interfaces:

[ICrontabEventHandler](#), [ILiveStreamRecord](#)

Direct Known Subclasses:

[LiveStreamRecorderMediaWriter](#), [LiveStreamRecorderMP4](#), [LiveStreamRecorderFLV](#)

public class **LiveStreamRecorderBase**

extends Object

implements [ILiveStreamRecord](#), [ICrontabEventHandler](#)

### Field Summary

protected	<a href="#">appInstance</a>
protected	<a href="#">baseFilePath</a>
protected	<a href="#">contextStr</a>
protected	<a href="#">cronEventWorker</a>
protected	<a href="#">currentDuration</a>
protected	<a href="#">currentOutputFile</a>
protected	<a href="#">currentSize</a>
protected	<a href="#">debugLog</a>
protected	<a href="#">file</a>
protected	<a href="#">fileVersionDelegate</a>
protected	<a href="#">listeners</a>
protected	<a href="#">moveFirstVideoFrameToZero</a>
protected	<a href="#">recordStartTime</a>
protected	<a href="#">segmentNumber</a>

protected	<a href="#">splitNow</a>
protected	<a href="#">splitOnTcDiscontinuity</a>
protected	<a href="#">splitType</a>
protected	<a href="#">stream</a>
protected	<a href="#">streamNotifier</a>
protected	<a href="#">useSimpleFileVersionNaming</a>
protected	<a href="#">worker</a>
protected	<a href="#">writeLock</a>

Fields inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[SPLIT\\_ON\\_DISCONTINUITY\\_ALWAYS](#), [SPLIT\\_ON\\_DISCONTINUITY\\_DEFAULT](#),  
[SPLIT\\_ON\\_DISCONTINUITY\\_NEVER](#), [SPLIT\\_TYPE\\_BY\\_DURATION](#), [SPLIT\\_TYPE\\_BY\\_SCHEDULE](#),  
[SPLIT\\_TYPE\\_BY\\_SIZE](#), [SPLIT\\_TYPE\\_NONE](#)

## Constructor Summary

public	<a href="#">LiveStreamRecorderBase()</a>
--------	--

## Method Summary

<a href="#">ILiveStreamRecordNotify</a>	<a href="#">addListener(<a href="#">ILiveStreamRecordNotify</a> listener)</a> Add ILiveStreamRecordNotify listener
<a href="#">CrontabEvent</a>	<a href="#">createSegmentSchedule</a> (String schedule, <a href="#">ICrontabEventHandler</a> handler, boolean debug)
void	<a href="#">debug</a> (Class c, String string)
String	<a href="#">getBaseFilePath()</a>
long	<a href="#">getCurrentDuration()</a>
String	<a href="#">getCurrentFile()</a>
long	<a href="#">getCurrentSize()</a>
String	<a href="#">getFilePath()</a>
<a href="#">ILiveStreamRecordFileVersionDelegate</a>	<a href="#">getFileVersionDelegate()</a>
java.util.List	<a href="#">getLocalListeners()</a> Get a list of ILiveStreamRecordNotify listeners

long	<a href="#">getSegmentDuration()</a>
int	<a href="#">getSegmentNumber()</a>
<a href="#">CrontabEvent</a>	<a href="#">getSegmentSchedule()</a>
long	<a href="#">getSegmentSize()</a>
int	<a href="#">getSplitType()</a>
org.joda.time.DateTim e	<a href="#">getStartTime()</a>
String	<a href="#">getStreamName()</a>
Object	<a href="#">getWriteLock()</a>
void	<a href="#">init()</a> ( <a href="#">IApplicationInstance</a> appInstance)
boolean	<a href="#">isAppendFile()</a>
boolean	<a href="#">isMoveFirstVideoFrameToZero()</a>
boolean	<a href="#">isRecordData()</a>
boolean	<a href="#">isStartOnKeyFrame()</a>
boolean	<a href="#">isVersionFile()</a>
void	<a href="#">notifySegmentEnd()</a> ( <a href="#">ILiveStreamRecord</a> recorder) Notify segment end
void	<a href="#">notifySegmentStart()</a> ( <a href="#">ILiveStreamRecord</a> recorder) Notify segment start
void	<a href="#">onCronEvent()</a> ( <a href="#">CrontabEvent</a> event) handles segmentBySchedule timer events
void	<a href="#">onPublish()</a>
void	<a href="#">onUnPublish()</a>
boolean	<a href="#">removeListener()</a> ( <a href="#">ILiveStreamRecordNotify</a> listener) remove ILiveStreamRecordNotify listener
void	<a href="#">setAppendFile()</a> (boolean appendFile)
void	<a href="#">setBaseFilePath()</a> (String filePath)
void	<a href="#">setFilePath()</a> (String filePath)

void	<a href="#"><u>setFileVersionDelegate</u></a> ( <a href="#"><u>ILiveStreamRecordFileVersionDelegate</u></a> delegate)
void	<a href="#"><u>setMoveFirstVideoFrameToZero</u></a> (boolean moveFirstVideoFrameToZero)
void	<a href="#"><u>setRecordData</u></a> (boolean recordData)
void	<a href="#"><u>setSegmentDuration</u></a> (long duration) Allows the changing of the segmentDuration without the need to stop an active recording
void	<a href="#"><u>setSegmentSize</u></a> (long size) Allows the changing of the segmentSize without the need to stop an active recording
void	<a href="#"><u>setStartOnKeyFrame</u></a> (boolean startOnKeyFrame)
void	<a href="#"><u>setVersionFile</u></a> (boolean versionFile)
void	<a href="#"><u>splitRecordingNow</u></a> ()
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, boolean append)
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, boolean append)
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, boolean append, java.util.Map extraMetadata)
void	<a href="#"><u>startRecording</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, boolean append, java.util.Map extraMetadata, int splitOnTcDiscontinuity)
void	<a href="#"><u>startRecordingSegmentByDuration</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, java.util.Map extraMetadata, long duration)
void	<a href="#"><u>startRecordingSegmentBySchedule</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, java.util.Map extraMetadata, String schedule)
void	<a href="#"><u>startRecordingSegmentBySize</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String filePath, java.util.Map extraMetadata, long size)
void	<a href="#"><u>stopRecording</u></a> ()
void	<a href="#"><u>work</u></a> ()
void	<a href="#"><u>workStop</u></a> ()

**Methods inherited from class** [java.lang.Object](#)

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface** [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[addListener](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#),  
[getFilePath](#), [getFileVersionDelegate](#), [getSegmentDuration](#), [getSegmentNumber](#),  
[getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#),  
[getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#),  
[isStartOnKeyFrame](#), [isVersionFile](#), [onPublish](#), [onUnPublish](#), [removeListener](#),  
[setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#),  
[setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#),  
[splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#),  
[startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#),  
[startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

Methods inherited from interface [com.wowza.wms.util.crontab.ICrontabEventHandler](#)

[onCronEvent](#)

## Fields

### worker

protected com.wowza.wms.livestreamrecord.model.LiveStreamRecorderWorker **worker**

### stream

protected com.wowza.wms.stream.IMediaStream **stream**

### appInstance

protected com.wowza.wms.application.IApplicationInstance **appInstance**

### streamNotifier

protected com.wowza.wms.livestreamrecord.model.LiveStreamRecordActionNotifier  
**streamNotifier**

### writeLock

protected java.lang.Object **writeLock**

### moveFirstVideoFrameToZero

protected boolean **moveFirstVideoFrameToZero**



(continued from last page)

---

## fileVersionDelegate

protected com.wowza.wms.livestreamrecord.model.ILiveStreamRecordFileVersionDelegate  
**fileVersionDelegate**

---

## baseFilePath

protected java.lang.String **baseFilePath**

---

## splitType

protected int **splitType**

---

## splitNow

protected boolean **splitNow**

---

## currentSize

protected long **currentSize**

---

## currentDuration

protected long **currentDuration**

---

## cronEventWorker

protected com.wowza.wms.livestreamrecord.model.LiveStreamRecordCronEventWorker  
**cronEventWorker**

---

## listeners

protected java.util.List **listeners**

---

## file

protected java.io.File **file**

---

(continued from last page)

---

## segmentNumber

protected int **segmentNumber**

---

---

## recordStartTime

protected org.joda.time.DateTime **recordStartTime**

---

---

## debugLog

protected boolean **debugLog**

---

---

## contextStr

protected java.lang.String **contextStr**

---

---

## currentOutputFile

protected java.lang.String **currentOutputFile**

---

---

## splitOnTcDiscontinuity

protected boolean **splitOnTcDiscontinuity**

---

---

## useSimpleFileVersionNaming

protected boolean **useSimpleFileVersionNaming**

---

## Constructors

### LiveStreamRecorderBase

public **LiveStreamRecorderBase**()

## Methods

### init

public void **init**([IApplicationInstance](#) appInstance)

---

## getSplitType

```
public int getSplitType()
```

---

## getSegmentSize

```
public long getSegmentSize()
```

---

## getSegmentDuration

```
public long getSegmentDuration()
```

---

## getCurrentSize

```
public long getCurrentSize()
```

---

## getCurrentDuration

```
public long getCurrentDuration()
```

---

## setSegmentSize

```
public void setSegmentSize(long size)
```

Allows the changing of the segmentSize without the need to stop an active recording

**Parameters:**

size - long new maximum size for recording segments

---

## setSegmentDuration

```
public void setSegmentDuration(long duration)
```

Allows the changing of the segmentDuration without the need to stop an active recording

**Parameters:**

duration - long new maximum duration for recording segments

---

## createSegmentSchedule

```
public CrontabEvent createSegmentSchedule(String schedule,  
    ICrontabEventHandler handler,  
    boolean debug)
```

---

(continued from last page)

---

## getSegmentSchedule

```
public CrontabEvent getSegmentSchedule()
```

---

---

## getSegmentNumber

```
public int getSegmentNumber()
```

---

---

## getBaseFilePath

```
public String getBaseFilePath()
```

---

---

## setBaseFilePath

```
public void setBaseFilePath(String filePath)
```

---

---

## getCurrentFile

```
public String getCurrentFile()
```

---

---

## setFileVersionDelegate

```
public void setFileVersionDelegate(ILiveStreamRecordFileVersionDelegate delegate)
```

---

---

## getFileVersionDelegate

```
public ILiveStreamRecordFileVersionDelegate getFileVersionDelegate()
```

---

---

## getFilePath

```
public String getFilePath()
```

---

---

## setFilePath

```
public void setFilePath(String filePath)
```

---

---

## getStreamName

```
public String getStreamName()
```

---

(continued from last page)

---

### getStartTime

```
public org.joda.time.DateTime getStartTime()
```

---

### isStartOnKeyFrame

```
public boolean isStartOnKeyFrame()
```

---

### setStartOnKeyFrame

```
public void setStartOnKeyFrame(boolean startOnKeyFrame)
```

---

### isRecordData

```
public boolean isRecordData()
```

---

### setRecordData

```
public void setRecordData(boolean recordData)
```

---

### isVersionFile

```
public boolean isVersionFile()
```

---

### setVersionFile

```
public void setVersionFile(boolean versionFile)
```

---

### isAppendFile

```
public boolean isAppendFile()
```

---

### setAppendFile

```
public void setAppendFile(boolean appendFile)
```

---

(continued from last page)

---

## getWriteLock

```
public Object getWriteLock()
```

---

---

## isMoveFirstVideoFrameToZero

```
public boolean isMoveFirstVideoFrameToZero()
```

---

---

## setMoveFirstVideoFrameToZero

```
public void setMoveFirstVideoFrameToZero(boolean moveFirstVideoFrameToZero)
```

---

---

## splitRecordingNow

```
public void splitRecordingNow()
```

---

---

## addListener

```
public ILiveStreamRecordNotify addListener(ILiveStreamRecordNotify listener)
```

Add ILiveStreamRecordNotify listener

**Parameters:**

listener - ILiveStreamRecordNotify listener

---

---

## removeListener

```
public boolean removeListener(ILiveStreamRecordNotify listener)
```

remove ILiveStreamRecordNotify listener

**Parameters:**

listener - ILiveStreamRecordNotify listener

**Returns:**

true if removed

---

---

## onCronEvent

```
public void onCronEvent(CrontabEvent event)
```

handles segmentBySchedule timer events

**Parameters:**

event - CrontabEvent which caused the timer to fire

---

---

## getLocalListeners

```
protected java.util.List getLocalListeners()
```

---

(continued from last page)

Get a list of `ILiveStreamRecordNotify` listeners

**Returns:**

list of `ILiveStreamRecordNotify` listeners

---

**notifySegmentStart**

```
protected void notifySegmentStart(ILiveStreamRecord recorder)
```

Notify segment start

**Parameters:**

recorder - `liveStreamRecord` instance

---

**notifySegmentEnd**

```
protected void notifySegmentEnd(ILiveStreamRecord recorder)
```

Notify segment end

**Parameters:**

recorder - `liveStreamRecord` instance

---

**debug**

```
protected void debug(Class c,  
    String string)
```

---

**startRecording**

```
public void startRecording(IMediaStream stream,  
    boolean append)
```

---

**startRecording**

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append)
```

---

**startRecording**

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata)
```

---

(continued from last page)

---

## startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata,  
    int splitOnTcDiscontinuity)
```

---

## startRecordingSegmentBySize

```
public void startRecordingSegmentBySize(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long size)
```

---

## startRecordingSegmentByDuration

```
public void startRecordingSegmentByDuration(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long duration)
```

---

## startRecordingSegmentBySchedule

```
public void startRecordingSegmentBySchedule(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    String schedule)
```

---

## stopRecording

```
public void stopRecording()
```

---

## onPublish

```
public void onPublish()
```

---

## onUnPublish

```
public void onUnPublish()
```

---

## workStop

```
public void workStop()
```

---



---


## **work**

```
public void work()
```

## com.wowza.wms.livestreamrecord.model

### Class LiveStreamRecorderFLV

java.lang.Object



All Implemented Interfaces:

[ICrontabEventHandler](#), [ILiveStreamRecord](#)

public class **LiveStreamRecorderFLV**  
 extends [LiveStreamRecorderBase](#)

Fields inherited from class [com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase](#)

[appInstance](#), [baseFilePath](#), [contextStr](#), [cronEventWorker](#), [currentDuration](#), [currentOutputFile](#), [currentSize](#), [debugLog](#), [file](#), [fileVersionDelegate](#), [listeners](#), [moveFirstVideoFrameToZero](#), [recordStartTime](#), [segmentNumber](#), [splitNow](#), [splitOnTcDiscontinuity](#), [splitType](#), [stream](#), [streamNotifier](#), [useSimpleFileVersionNaming](#), [worker](#), [writeLock](#)

Fields inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[SPLIT\\_ON\\_DISCONTINUITY\\_ALWAYS](#), [SPLIT\\_ON\\_DISCONTINUITY\\_DEFAULT](#), [SPLIT\\_ON\\_DISCONTINUITY\\_NEVER](#), [SPLIT\\_TYPE\\_BY\\_DURATION](#), [SPLIT\\_TYPE\\_BY\\_SCHEDULE](#), [SPLIT\\_TYPE\\_BY\\_SIZE](#), [SPLIT\\_TYPE\\_NONE](#)

## Constructor Summary

public	<a href="#">LiveStreamRecorderFLV()</a>
--------	---

## Method Summary

java.util.List	<a href="#">getPlayPackets()</a>
----------------	----------------------------------

void	<a href="#">onPublish()</a>
------	-----------------------------

void	<a href="#">onUnPublish()</a>
------	-------------------------------

void	<a href="#">startRecording(<a href="#">IMediaStream</a> stream, boolean append)</a>
------	---

void	<a href="#">startRecording(<a href="#">IMediaStream</a> stream, String filePath, boolean append)</a>
------	--

void	<a href="#">startRecording(<a href="#">IMediaStream</a> stream, String filePath, boolean append, java.util.Map extraMetadata)</a>
------	---

void	<a href="#">startRecording(<a href="#">IMediaStream</a> stream, String filePath, boolean append, java.util.Map extraMetadata, int splitOnTcDiscontinuity)</a>
------	---

void	<a href="#"><u>startRecordingSegmentByDuration(IMediaStream stream, String filePath, java.util.Map extraMetadata, long duration)</u></a>
void	<a href="#"><u>startRecordingSegmentBySchedule(IMediaStream stream, String filePath, java.util.Map extraMetadata, String schedule)</u></a>
void	<a href="#"><u>startRecordingSegmentBySize(IMediaStream stream, String filePath, java.util.Map extraMetadata, long size)</u></a>
void	<a href="#"><u>stopRecording()</u></a>
void	<a href="#"><u>work()</u></a>
void	<a href="#"><u>workStop()</u></a>

#### Methods inherited from class [com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase](#)

[addListener](#), [createSegmentSchedule](#), [debug](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#), [getFilePath](#), [getFileVersionDelegate](#), [getLocalListeners](#), [getSegmentDuration](#), [getSegmentNumber](#), [getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#), [getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#), [isStartOnKeyFrame](#), [isVersionFile](#), [notifySegmentEnd](#), [notifySegmentStart](#), [onCronEvent](#), [onPublish](#), [onUnPublish](#), [removeListener](#), [setAppendFile](#), [setBaseFilePath](#), [setFilePath](#), [setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#), [setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#), [splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#), [startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

#### Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

#### Methods inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[addListener](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#), [getFilePath](#), [getFileVersionDelegate](#), [getSegmentDuration](#), [getSegmentNumber](#), [getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#), [getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#), [isStartOnKeyFrame](#), [isVersionFile](#), [onPublish](#), [onUnPublish](#), [removeListener](#), [setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#), [setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#), [splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#), [startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

#### Methods inherited from interface [com.wowza.wms.util.crontab.ICrontabEventHandler](#)

[onCronEvent](#)

## Constructors

(continued from last page)

## LiveStreamRecorderFLV

```
public LiveStreamRecorderFLV()
```

## Methods

### startRecording

```
public void startRecording(IMediaStream stream,  
    boolean append)
```

### startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append)
```

### startRecordingSegmentBySize

```
public void startRecordingSegmentBySize(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long size)
```

### startRecordingSegmentByDuration

```
public void startRecordingSegmentByDuration(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long duration)
```

### startRecordingSegmentBySchedule

```
public void startRecordingSegmentBySchedule(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    String schedule)
```

### startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata)
```

(continued from last page)

## startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata,  
    int splitOnTcDiscontinuity)
```

---

## stopRecording

```
public void stopRecording()
```

---

## onPublish

```
public void onPublish()
```

---

## onUnPublish

```
public void onUnPublish()
```

---

## workStop

```
public void workStop()
```

---

## getPlayPackets

```
protected java.util.List getPlayPackets()
```

---

## work


```
public void work()
```

---

## com.wowza.wms.livestreamrecord.model

### Class LiveStreamRecorderMediaWriter

java.lang.Object



All Implemented Interfaces:

[ICrontabEventHandler](#), [ILiveStreamRecord](#)

public class **LiveStreamRecorderMediaWriter**  
 extends [LiveStreamRecorderBase](#)

Fields inherited from class [com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase](#)

[appInstance](#), [baseFilePath](#), [contextStr](#), [cronEventWorker](#), [currentDuration](#), [currentOutputFile](#), [currentSize](#), [debugLog](#), [file](#), [fileVersionDelegate](#), [listeners](#), [moveFirstVideoFrameToZero](#), [recordStartTime](#), [segmentNumber](#), [splitNow](#), [splitOnTcDiscontinuity](#), [splitType](#), [stream](#), [streamNotifier](#), [useSimpleFileVersionNaming](#), [worker](#), [writeLock](#)

Fields inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[SPLIT\\_ON\\_DISCONTINUITY\\_ALWAYS](#), [SPLIT\\_ON\\_DISCONTINUITY\\_DEFAULT](#), [SPLIT\\_ON\\_DISCONTINUITY\\_NEVER](#), [SPLIT\\_TYPE\\_BY\\_DURATION](#), [SPLIT\\_TYPE\\_BY\\_SCHEDULE](#), [SPLIT\\_TYPE\\_BY\\_SIZE](#), [SPLIT\\_TYPE\\_NONE](#)

## Constructor Summary

public	<a href="#">LiveStreamRecorderMediaWriter()</a>
--------	---

## Method Summary

java.util.List	<a href="#">getPlayPackets()</a>
----------------	----------------------------------

void	<a href="#">onPublish()</a>
------	-----------------------------

void	<a href="#">onUnPublish()</a>
------	-------------------------------

void	<a href="#">setMediaWriterType</a> (String mediaWriterType)
------	---

void	<a href="#">splitRecordingNow()</a>
------	-------------------------------------

void	<a href="#">startRecording</a> ( <a href="#">IMediaStream</a> stream, boolean append)
------	---

void	<a href="#">startRecording</a> ( <a href="#">IMediaStream</a> stream, String filePath, boolean append)
------	--

void	<a href="#">startRecording</a> ( <a href="#">IMediaStream</a> stream, String filePath, boolean append, java.util.Map extraMetadata)
------	---

void	<a href="#"><u>startRecording(IMediaStream stream, String filePath, boolean append, java.util.Map extraMetadata, int splitOnTcDiscontinuity)</u></a>
void	<a href="#"><u>startRecordingSegmentByDuration(IMediaStream stream, String filePath, java.util.Map extraMetadata, long duration)</u></a>
void	<a href="#"><u>startRecordingSegmentBySchedule(IMediaStream stream, String filePath, java.util.Map extraMetadata, String schedule)</u></a>
void	<a href="#"><u>startRecordingSegmentBySize(IMediaStream stream, String filePath, java.util.Map extraMetadata, long size)</u></a>
void	<a href="#"><u>stopRecording()</u></a>
void	<a href="#"><u>work()</u></a>
void	<a href="#"><u>workStop()</u></a>

#### Methods inherited from class [com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase](#)

[addListener](#), [createSegmentSchedule](#), [debug](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#), [getFilePath](#), [getFileVersionDelegate](#), [getLocalListeners](#), [getSegmentDuration](#), [getSegmentNumber](#), [getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#), [getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#), [isStartOnKeyFrame](#), [isVersionFile](#), [notifySegmentEnd](#), [notifySegmentStart](#), [onCronEvent](#), [onPublish](#), [onUnPublish](#), [removeListener](#), [setAppendFile](#), [setBaseFilePath](#), [setFilePath](#), [setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#), [setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#), [splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#), [startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

#### Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

#### Methods inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[addListener](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#), [getFilePath](#), [getFileVersionDelegate](#), [getSegmentDuration](#), [getSegmentNumber](#), [getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#), [getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#), [isStartOnKeyFrame](#), [isVersionFile](#), [onPublish](#), [onUnPublish](#), [removeListener](#), [setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#), [setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#), [splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#), [startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

#### Methods inherited from interface [com.wowza.wms.util.crontab.ICrontabEventHandler](#)

[onCronEvent](#)

---

## Constructors

### LiveStreamRecorderMediaWriter

```
public LiveStreamRecorderMediaWriter()
```

---

## Methods

### setMediaWriterType

```
public void setMediaWriterType(String mediaWriterType)
```

---

### startRecording

```
public void startRecording(IMediaStream stream,  
    boolean append)
```

---

### startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append)
```

---

### startRecordingSegmentBySize

```
public void startRecordingSegmentBySize(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long size)
```

---

### startRecordingSegmentByDuration

```
public void startRecordingSegmentByDuration(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    long duration)
```

---

### startRecordingSegmentBySchedule

```
public void startRecordingSegmentBySchedule(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    String schedule)
```



---

## startRecording

```
public void startRecording(IMediaStream stream,
    String filePath,
    boolean append,
    java.util.Map extraMetadata,
    int splitOnTcDiscontinuity)
```

---

## startRecording

```
public void startRecording(IMediaStream stream,
    String filePath,
    boolean append,
    java.util.Map extraMetadata)
```

---

## stopRecording

```
public void stopRecording()
```

---

## splitRecordingNow

```
public void splitRecordingNow()
```

---

## onPublish

```
public void onPublish()
```

---

## onUnPublish

```
public void onUnPublish()
```

---

## workStop

```
public void workStop()
```

---

## getPlayPackets

```
protected java.util.List getPlayPackets()
```

---

## work

```
public void work()
```


---

(continued from last page)

## com.wowza.wms.livestreamrecord.model

### Class LiveStreamRecorderMP4

java.lang.Object



All Implemented Interfaces:

[ICrontabEventHandler](#), [ILiveStreamRecord](#)

public class **LiveStreamRecorderMP4**  
 extends [LiveStreamRecorderBase](#)

Fields inherited from class [com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase](#)

[appInstance](#), [baseFilePath](#), [contextStr](#), [cronEventWorker](#), [currentDuration](#), [currentOutputFile](#), [currentSize](#), [debugLog](#), [file](#), [fileVersionDelegate](#), [listeners](#), [moveFirstVideoFrameToZero](#), [recordStartTime](#), [segmentNumber](#), [splitNow](#), [splitOnTcDiscontinuity](#), [splitType](#), [stream](#), [streamNotifier](#), [useSimpleFileVersionNaming](#), [worker](#), [writeLock](#)

Fields inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[SPLIT\\_ON\\_DISCONTINUITY\\_ALWAYS](#), [SPLIT\\_ON\\_DISCONTINUITY\\_DEFAULT](#), [SPLIT\\_ON\\_DISCONTINUITY\\_NEVER](#), [SPLIT\\_TYPE\\_BY\\_DURATION](#), [SPLIT\\_TYPE\\_BY\\_SCHEDULE](#), [SPLIT\\_TYPE\\_BY\\_SIZE](#), [SPLIT\\_TYPE\\_NONE](#)

## Constructor Summary

public	<a href="#">LiveStreamRecorderMP4()</a>
--------	---

## Method Summary

java.util.List	<a href="#">getPlayPackets()</a>
----------------	----------------------------------

boolean	<a href="#">isRecordOnMetaData()</a>
---------	--------------------------------------

void	<a href="#">onPublish()</a>
------	-----------------------------

void	<a href="#">onUnPublish()</a>
------	-------------------------------

void	<a href="#">setRecordOnMetaData</a> (boolean recordOnMetaData)
------	--

void	<a href="#">startRecording</a> ( <a href="#">IMediaStream</a> stream, boolean append)
------	---

void	<a href="#">startRecording</a> ( <a href="#">IMediaStream</a> stream, String filePath, boolean append)
------	--

void	<a href="#">startRecording</a> ( <a href="#">IMediaStream</a> stream, String filePath, boolean append, java.util.Map extraMetadata)
------	---

void	<a href="#"><u>startRecording(IMediaStream stream, String filePath, boolean append, java.util.Map extraMetadata, int splitOnTcDiscontinuity)</u></a>
void	<a href="#"><u>startRecordingSegmentByDuration(IMediaStream stream, String filePath, java.util.Map extraMetadata, long duration)</u></a>
void	<a href="#"><u>startRecordingSegmentBySchedule(IMediaStream stream, String filePath, java.util.Map extraMetadata, String schedule)</u></a>
void	<a href="#"><u>startRecordingSegmentBySize(IMediaStream stream, String filePath, java.util.Map extraMetadata, long size)</u></a>
void	<a href="#"><u>stopRecording()</u></a>
void	<a href="#"><u>work()</u></a>
void	<a href="#"><u>workStop()</u></a>

#### Methods inherited from class [com.wowza.wms.livestreamrecord.model.LiveStreamRecorderBase](#)

[addListener](#), [createSegmentSchedule](#), [debug](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#), [getFilePath](#), [getFileVersionDelegate](#), [getLocalListeners](#), [getSegmentDuration](#), [getSegmentNumber](#), [getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#), [getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#), [isStartOnKeyFrame](#), [isVersionFile](#), [notifySegmentEnd](#), [notifySegmentStart](#), [onCronEvent](#), [onPublish](#), [onUnPublish](#), [removeListener](#), [setAppendFile](#), [setBaseFilePath](#), [setFilePath](#), [setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#), [setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#), [splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#), [startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

#### Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

#### Methods inherited from interface [com.wowza.wms.livestreamrecord.model.ILiveStreamRecord](#)

[addListener](#), [getBaseFilePath](#), [getCurrentDuration](#), [getCurrentFile](#), [getCurrentSize](#), [getFilePath](#), [getFileVersionDelegate](#), [getSegmentDuration](#), [getSegmentNumber](#), [getSegmentSchedule](#), [getSegmentSize](#), [getSplitType](#), [getStartTime](#), [getStreamName](#), [getWriteLock](#), [init](#), [isAppendFile](#), [isMoveFirstVideoFrameToZero](#), [isRecordData](#), [isStartOnKeyFrame](#), [isVersionFile](#), [onPublish](#), [onUnPublish](#), [removeListener](#), [setFileVersionDelegate](#), [setMoveFirstVideoFrameToZero](#), [setRecordData](#), [setSegmentDuration](#), [setSegmentSize](#), [setStartOnKeyFrame](#), [setVersionFile](#), [splitRecordingNow](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecording](#), [startRecordingSegmentByDuration](#), [startRecordingSegmentBySchedule](#), [startRecordingSegmentBySize](#), [stopRecording](#), [work](#), [workStop](#)

#### Methods inherited from interface [com.wowza.wms.util.crontab.ICrontabEventHandler](#)

[onCronEvent](#)

## Constructors

### LiveStreamRecorderMP4

```
public LiveStreamRecorderMP4()
```

## Methods

### onPublish

```
public void onPublish()
```

---

### onUnPublish

```
public void onUnPublish()
```

---

### startRecording

```
public void startRecording(IMediaStream stream,  
                           boolean append)
```

---

### startRecording

```
public void startRecording(IMediaStream stream,  
                           String filePath,  
                           boolean append)
```

---

### startRecordingSegmentBySize

```
public void startRecordingSegmentBySize(IMediaStream stream,  
                                         String filePath,  
                                         java.util.Map extraMetadata,  
                                         long size)
```

---

### startRecordingSegmentByDuration

```
public void startRecordingSegmentByDuration(IMediaStream stream,  
                                             String filePath,  
                                             java.util.Map extraMetadata,  
                                             long duration)
```

---

(continued from last page)

---

## startRecordingSegmentBySchedule

```
public void startRecordingSegmentBySchedule(IMediaStream stream,  
    String filePath,  
    java.util.Map extraMetadata,  
    String schedule)
```

---

## startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata)
```

---

## startRecording

```
public void startRecording(IMediaStream stream,  
    String filePath,  
    boolean append,  
    java.util.Map extraMetadata,  
    int splitOnTcDiscontinuity)
```

---

## stopRecording

```
public void stopRecording()
```

---

## workStop

```
public void workStop()
```

---

## getPlayPackets

```
protected java.util.List getPlayPackets()
```

---

## work

```
public void work()
```

---

## isRecordOnMetaData

```
public boolean isRecordOnMetaData()
```

---

(continued from last page)

## **setRecordOnMetaData**

```
public void setRecordOnMetaData(boolean recordOnMetaData)
```

## com.wowza.wms.livestreamrecord.model Class LiveStreamRecordFileVersionDelegate

java.lang.Object

└─com.wowza.wms.livestreamrecord.model.LiveStreamRecordFileVersionDelegate

All Implemented Interfaces:

[ILiveStreamRecordFileVersionDelegate](#)

```
public class LiveStreamRecordFileVersionDelegate
extends Object
implements ILiveStreamRecordFileVersionDelegate
```

Default FileVersionDelegate class

This delegate allows the configuration of a custom FileName using a template string. The tags in the template string are replaced with their associated values, to generate a filename.

Valid template tags are;

`${SourceStreamName}` - The name of the stream

`${SegmentNumber}` - An incrementing value representing the current number of segments which have been created for this recording, starting at 0

`${RecordingStartTime}` - The time at which the recording was started

`${SegmentTime}` - Time time at which the segment was created

### Field Summary

public static final	<a href="#">BASE_NAME_TAG</a> Value: <code>\${BaseFileName}</code>
public static final	<a href="#">DATETIME_FORMAT</a>
public static final	<a href="#">SEGMENT_NUMBER_TAG</a> Value: <code>\${SegmentNumber}</code>
public static final	<a href="#">SEGMENT_TIME_TAG</a> Value: <code>\${SegmentTime}</code>
public static final	<a href="#">START_TIME_TAG</a> Value: <code>\${RecordingStartTime}</code>
public static final	<a href="#">STREAM_NAME_TAG</a> Value: <code>\${SourceStreamName}</code>

### Constructor Summary

public	<a href="#">LiveStreamRecordFileVersionDelegate()</a>
--------	---

### Method Summary



String	<a href="#"><code>getFilename(ILiveStreamRecord recContext)</code></a> Creates a new filename using the default template string,
String	<a href="#"><code>getFileTemplate()</code></a> Returns the current template string
void	<a href="#"><code>setFileTemplate(String template)</code></a> Sets the template string for creating the versioned file name.

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

#### Methods inherited from interface

[`com.wowza.wms.livestreamrecord.model.ILiveStreamRecordFileVersionDelegate`](#)

[`getFilename`](#)

## Fields

### DATETIME\_FORMAT

```
public static final org.joda.time.format.DateTimeFormatter DATETIME_FORMAT
```

### STREAM\_NAME\_TAG

```
public static final java.lang.String STREAM_NAME_TAG
```

Constant value: `${SourceStreamName}`

### BASE\_NAME\_TAG

```
public static final java.lang.String BASE_NAME_TAG
```

Constant value: `${BaseFileName}`

### SEGMENT\_NUMBER\_TAG

```
public static final java.lang.String SEGMENT_NUMBER_TAG
```

Constant value: `${SegmentNumber}`

### START\_TIME\_TAG

```
public static final java.lang.String START_TIME_TAG
```

Constant value: `${RecordingStartTime}`

(continued from last page)

## SEGMENT\_TIME\_TAG

```
public static final java.lang.String SEGMENT_TIME_TAG
```

Constant value: `${SegmentTime}`

## Constructors

### LiveStreamRecordFileVersionDelegate

```
public LiveStreamRecordFileVersionDelegate()
```

## Methods

### getFilename

```
public String getFilename(ILiveStreamRecord recContext)
```

Creates a new filename using the default template string,

**Parameters:**

recContext - The LiveStreamRecord context

**Returns:**

String The versioned file name

### setFileTemplate

```
public void setFileTemplate(String template)
```

Sets the template string for creating the versioned file name. If null is passed in, the template string reverts to the default template string

**Parameters:**

template - new template String

### getFileTemplate

```
public String getFileTemplate()
```

Returns the current template string

**Returns:**

String current template string

---

Package

**com.wowza.wms.logging**

## com.wowza.wms.logging Interface Constants

public interface **Constants**  
extends

Constants used internally throughout log4j.

### Field Summary

public static final	<a href="#"><u>ABSOLUTE_FORMAT</u></a> ABSOLUTE string literal. Value: <b>ABSOLUTE</b>
public static final	<a href="#"><u>ABSOLUTE_TIME_PATTERN</u></a> SimpleTimePattern for ABSOLUTE. Value: <b>HH:mm:ss,SSS</b>
public static final	<a href="#"><u>APPLICATION_KEY</u></a> application string literal. Value: <b>application</b>
public static final	<a href="#"><u>CODES_HREF</u></a> Codes URL string literal. Value: <b>http://logging.apache.org/log4j/docs/codes.html</b>
public static final	<a href="#"><u>CONFIGURATOR_CLASS_KEY</u></a> log4j.configuratorClass string literal. Value: <b>log4j.configuratorClass</b>
public static final	<a href="#"><u>DATE_AND_TIME_FORMAT</u></a> DATE string literal. Value: <b>DATE</b>
public static final	<a href="#"><u>DATE_AND_TIME_PATTERN</u></a> SimpleTimePattern for DATE. Value: <b>dd MMM yyyy HH:mm:ss,SSS</b>
public static final	<a href="#"><u>DEFAULT_CONFIGURATION_FILE</u></a> The default property file name for automatic configuration. Value: <b>log4j.properties</b>
public static final	<a href="#"><u>DEFAULT_CONFIGURATION_KEY</u></a> log4j.configuration string literal. Value: <b>log4j.configuration</b>
public static final	<a href="#"><u>DEFAULT_REPOSITORY_NAME</u></a> The name of the default repository is "default" (without the quotes). Value: <b>default</b>
public static final	<a href="#"><u>DEFAULT_XML_CONFIGURATION_FILE</u></a> The default XML configuration file name for automatic configuration. Value: <b>log4j.xml</b>

public static final	<a href="#">HOSTNAME_KEY</a> hostname string literal. Value: <b>hostname</b>
public static final	<a href="#">ISO8601_FORMAT</a> ISO8601 string literal. Value: <b>ISO8601</b>
public static final	<a href="#">ISO8601_PATTERN</a> SimpleTimePattern for ISO8601. Value: <b>yyyy-MM-dd HH:mm:ss,SSS</b>
public static final	<a href="#">JNDI_CONTEXT_NAME</a> JNDI context name string literal. Value: <b>java:comp/env/log4j/context-name</b>
public static final	<a href="#">LOG4J_ID_KEY</a> log4jid string literal. Value: <b>log4jid</b>
public static final	<a href="#">LOG4J_PACKAGE_NAME</a> log4j package name string literal. Value: <b>org.apache.log4j</b>
public static final	<a href="#">RECEIVER_NAME_KEY</a> receiver string literal. Value: <b>receiver</b>
public static final	<a href="#">TEMP_CONSOLE_APPENDER_NAME</a> TEMP_CONSOLE_APPENDER string literal. Value: <b>TEMP_CONSOLE_APPENDER</b>
public static final	<a href="#">TEMP_LIST_APPENDER_NAME</a> TEMP_LIST_APPENDER string literal. Value: <b>TEMP_LIST_APPENDER</b>
public static final	<a href="#">TIMESTAMP_RULE_FORMAT</a> time stamp pattern string literal. Value: <b>yyyy/MM/dd HH:mm:ss</b>

## Fields

### LOG4J\_PACKAGE\_NAME

public static final java.lang.String **LOG4J\_PACKAGE\_NAME**

log4j package name string literal.  
Constant value: **org.apache.log4j**

### DEFAULT\_REPOSITORY\_NAME

public static final java.lang.String **DEFAULT\_REPOSITORY\_NAME**

The name of the default repository is "default" (without the quotes).  
Constant value: **default**

## APPLICATION\_KEY

```
public static final java.lang.String APPLICATION_KEY
```

application string literal.

Constant value: **application**

---

## HOSTNAME\_KEY

```
public static final java.lang.String HOSTNAME_KEY
```

hostname string literal.

Constant value: **hostname**

---

## RECEIVER\_NAME\_KEY

```
public static final java.lang.String RECEIVER_NAME_KEY
```

receiver string literal.

Constant value: **receiver**

---

## LOG4J\_ID\_KEY

```
public static final java.lang.String LOG4J_ID_KEY
```

log4jid string literal.

Constant value: **log4jid**

---

## TIMESTAMP\_RULE\_FORMAT

```
public static final java.lang.String TIMESTAMP_RULE_FORMAT
```

time stamp pattern string literal.

Constant value: **yyyy/MM/dd HH:mm:ss**

---

## DEFAULT\_CONFIGURATION\_FILE

```
public static final java.lang.String DEFAULT_CONFIGURATION_FILE
```

The default property file name for automatic configuration.

Constant value: **log4j.properties**

---

## DEFAULT\_XML\_CONFIGURATION\_FILE

```
public static final java.lang.String DEFAULT_XML_CONFIGURATION_FILE
```

The default XML configuration file name for automatic configuration.

Constant value: **log4j.xml**

---

## DEFAULT\_CONFIGURATION\_KEY

```
public static final java.lang.String DEFAULT_CONFIGURATION_KEY
```

log4j.configuration string literal.

Constant value: **log4j.configuration**

---

(continued from last page)

---

## CONFIGURATOR\_CLASS\_KEY

```
public static final java.lang.String CONFIGURATOR_CLASS_KEY
```

log4j.configuratorClass string literal.

Constant value: **log4j.configuratorClass**

---

## JNDI\_CONTEXT\_NAME

```
public static final java.lang.String JNDI_CONTEXT_NAME
```

JNDI context name string literal.

Constant value: **java:comp/env/log4j/context-name**

---

## TEMP\_LIST\_APPENDER\_NAME

```
public static final java.lang.String TEMP_LIST_APPENDER_NAME
```

TEMP\_LIST\_APPENDER string literal.

Constant value: **TEMP\_LIST\_APPENDER**

---

## TEMP\_CONSOLE\_APPENDER\_NAME

```
public static final java.lang.String TEMP_CONSOLE_APPENDER_NAME
```

TEMP\_CONSOLE\_APPENDER string literal.

Constant value: **TEMP\_CONSOLE\_APPENDER**

---

## CODES\_HREF

```
public static final java.lang.String CODES_HREF
```

Codes URL string literal.

Constant value: **http://logging.apache.org/log4j/docs/codes.html**

---

## ABSOLUTE\_FORMAT

```
public static final java.lang.String ABSOLUTE_FORMAT
```

ABSOLUTE string literal.

Constant value: **ABSOLUTE**

---

## ABSOLUTE\_TIME\_PATTERN

```
public static final java.lang.String ABSOLUTE_TIME_PATTERN
```

SimpleTimePattern for ABSOLUTE.

Constant value: **HH:mm:ss,SSS**

---

## DATE\_AND\_TIME\_FORMAT

```
public static final java.lang.String DATE_AND_TIME_FORMAT
```

DATE string literal.

Constant value: **DATE**

---

## DATE\_AND\_TIME\_PATTERN

```
public static final java.lang.String DATE_AND_TIME_PATTERN
```

---

(continued from last page)

SimpleTimePattern for DATE.

Constant value: **dd MMM yyyy HH:mm:ss,SSS**

---

## ISO8601\_FORMAT

```
public static final java.lang.String ISO8601_FORMAT
```

ISO8601 string literal.

Constant value: **ISO8601**

---

## ISO8601\_PATTERN

```
public static final java.lang.String ISO8601_PATTERN
```

SimpleTimePattern for ISO8601.

Constant value: **yyyy-MM-dd HH:mm:ss,SSS**



## com.wowza.wms.logging Interface ILogNotify

All Known Implementing Classes:

[LogNotifyCalculateIncremental](#)

---

public interface **ILogNotify**  
extends

ILogNotify: Interface to add custom fields to the Wowza Pro log files. To add your own custom log fields, define a class that implements this interface. The onLog method will be called each time the Wowza Pro server logs a message. Here is an example of a simple ILogNotify class that logs the current system time in milliseconds as a Long (systime-long) and as a String (systime-string).

```
package com.wowza.wms.plugin.newlogfields;

import org.apache.log4j.*;

import com.wowza.wms.logging.*;
import com.wowza.wms.stream.*;

public class LogNotifyDocs implements ILogNotify
{
    public void onLog(Level level, String comment, IMediaStream stream, String category,
String event, int status, String context)
    {
        long systime = System.currentTimeMillis();
        WMSLoggerFactory.putGlobalLogValue("systime-long", new Long(systime));
        WMSLoggerFactory.putGlobalLogValue("systime-string", systime+"");
    }
}
```

*Note: To get any of the values currently being logged use the logging API  
WMSLoggerFactory.getGlobalLogValue(WMSLoggerIDs.FD\_\*)*

To add your class to Wowza Pro, compile your class into a .class file, bind the class into a .jar file and copy the .jar file into the Wowza Pro server /lib folder. Next, edit:

- [install-dir]/bin/setenv.bat (Windows)
- [install-dir]/bin/setenv.sh (Linux, OSX, Solaris)

Add **-Dcom.wowza.wms.logging.LogNotify=[full-path-to-your-ILogNotify-class]** to the **JAVA\_OPTS**. For example for the class above the JAVA\_OPTS would look like:

Linux/OSX

JAVA\_OPTS="-Xmx768M -

Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.plugin.newlogfields.NewLogFields"

Windows

JAVA\_OPTS=-Xmx768M -

Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.plugin.newlogfields.NewLogFields

If on Windows, also edit `[install-dir]/bin/WowzaMediaServerPro-Service.conf` and add `wrapper.java.additional.[n]=-Dcom.wowza.wms.logging.LogNotify=[full-path-to-your-ILogNotify-class]` to the **Java Additional Parameters** section where **[n]** is the next number in the list of active parameters. For example for the class above if the last active additional parameter is 6, the entry would look like this:

wrapper.java.additional.7=-

Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.plugin.newlogfields.NewLogFields

Next, edit `[install-dir]/conf/log4j.properties` and add the new field names to any `log4j.appender.[appender-name].layout.Fields` fields lists to which you want to log these values. For example:

log4j.appender.stdout.layout.Fields=x-severity,x-category,x-event,x-ctx,x-comment,systemtime-long,systemtime-string

## Method Summary

void	<code>onLog(org.apache.log4j.Level level, String comment, <a href="#">IMediaStream</a> stream, String category, String event, int status, String context)</code> Called each time the server logs a message.
------	---

## Methods

### onLog

```
public void onLog(org.apache.log4j.Level level,
    String comment,
    IMediaStream stream,
    String category,
    String event,
    int status,
    String context)
```

Called each time the server logs a message.

#### Parameters:

level - log level as defined by (org.apache.log4j.Level)  
comment - comment part of the log statement  
stream - if stream category log message it's the source stream

(continued from last page)

category - log category as defined by WMSLoggerIDs.CAT\_\*

event - log event as defined by WMSLoggerIDs.EVT\_\*

status - log status (same as HTTP status field) as defined by WMSLoggerIDs.STAT\_\*

context - log context value like stream name, vhost name, application name

## com.wowza.wms.logging Class LogNotifyCalculateIncremental

java.lang.Object

└─com.wowza.wms.logging.LogNotifyCalculateIncremental

All Implemented Interfaces:

[ILogNotify](#)

public class **LogNotifyCalculateIncremental**  
extends Object  
implements [ILogNotify](#)

LogNotifyCalculateIncremental: pre-built implementation of ILogNotify that adds 5 new log fields:

- cs-bytes-inc (client to server bytes streamed since last log entry)
- sc-bytes-inc (server to client bytesstreamed since last log entry)
- cs-stream-bytes-inc (client to server stream bytesstreamed since last log entry)
- sc-stream-bytes-inc (server to client stream bytesstreamed since last log entry)
- x-duration-inc (time in seconds that have passed since the last log event)

These are incremental versions of the regular log values. To add this to Wowza Pro edit:

- [install-dir]/bin/setenv.bat (Windows)
- [install-dir]/bin/setenv.sh (Linux, OSX)

Add **-Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.logging.LogNotifyCalculateIncremental** to the **JAVA\_OPTS**. Also, edit [install-dir]/conf/log4j.properties and add these field names to any log4j.appender.[appender-name].layout.Fields fields lists to which you want to log these values.

*NOTE: These new log values are only accurate if all the events are included for the **session** and **stream** log categories.*

### Field Summary

public static final	<a href="#">FD_cs_bytes_inc</a> Value: <b>cs-bytes-inc</b>
public static final	<a href="#">FD_cs_stream_bytes_inc</a> Value: <b>cs-stream-bytes-inc</b>
public static final	<a href="#">FD_sc_bytes_inc</a> Value: <b>sc-bytes-inc</b>
public static final	<a href="#">FD_sc_stream_bytes_inc</a> Value: <b>sc-stream-bytes-inc</b>
public static final	<a href="#">FD_x_duration_inc</a> Value: <b>x-duration-inc</b>

### Constructor Summary

public	<a href="#">LogNotifyCalculateIncremental()</a>
--------	---

Method Summary

void	<a href="#">onLog</a> (org.apache.log4j.Level level, String comment, <a href="#">IMediaStream</a> stream, String category, String event, int status, String context)
------	--

Methods inherited from class java.lang.Object	
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait	

Methods inherited from interface <a href="#">com.wowza.wms.logging.ILogNotify</a>	
<a href="#">onLog</a>	

Fields

FD\_cs\_bytes\_inc

public static final java.lang.String **FD\_cs\_bytes\_inc**

Constant value: **cs-bytes-inc**

FD\_sc\_bytes\_inc

public static final java.lang.String **FD\_sc\_bytes\_inc**

Constant value: **sc-bytes-inc**

FD\_cs\_stream\_bytes\_inc

public static final java.lang.String **FD\_cs\_stream\_bytes\_inc**

Constant value: **cs-stream-bytes-inc**

FD\_sc\_stream\_bytes\_inc

public static final java.lang.String **FD\_sc\_stream\_bytes\_inc**

Constant value: **sc-stream-bytes-inc**

FD\_x\_duration\_inc

public static final java.lang.String **FD\_x\_duration\_inc**

Constant value: **x-duration-inc**

Constructors

(continued from last page)

## LogNotifyCalculateIncremental

```
public LogNotifyCalculateIncremental()
```

## Methods

### onLog

```
public void onLog(org.apache.log4j.Level level,  
    String comment,  
    IMediaStream stream,  
    String category,  
    String event,  
    int status,  
    String context)
```

## com.wowza.wms.logging Class UDPAppender

```

java.lang.Object
|
|--org.apache.log4j.AppenderSkeleton
|   |
|   |--com.wowza.wms.logging.UDPAppender

```

### All Implemented Interfaces:

PortBased, org.apache.log4j.spi.OptionHandler, org.apache.log4j.Appender

```

public class UDPAppender
extends org.apache.log4j.AppenderSkeleton
implements org.apache.log4j.Appender, org.apache.log4j.spi.OptionHandler, PortBased

```

Sends log information as a UDP datagrams.

The UDPAppender is meant to be used as a diagnostic logging tool so that logging can be monitored by a simple UDP client.

Messages are not sent as LoggingEvent objects but as text after applying the designated Layout.

The port and remoteHost properties can be set in configuration properties. By setting the remoteHost to a broadcast address any number of clients can listen for log messages.

This was inspired and really extended/copied from SocketAppender. Please see the docs for the proper credit to the authors of that class.

## Field Summary

public static final	<a href="#">DEFAULT_PORT</a> The default port number for the UDP packets, 9991. Value: <b>9991</b>
---------------------	--

## Fields inherited from class org.apache.log4j.AppenderSkeleton

closed, errorHandler, headFilter, layout, name, tailFilter, threshold

## Constructor Summary

public	<a href="#">UDPAppender</a> ()
public	<a href="#">UDPAppender</a> (java.net.InetAddress address, int port) Sends UDP packets to the address and port.
public	<a href="#">UDPAppender</a> (String host, int port) Sends UDP packets to the address and port.

## Method Summary

void	<a href="#">activateOptions</a> () Open the UDP sender for the <b>RemoteHost</b> and <b>Port</b> .
void	<a href="#">append</a> (org.apache.log4j.spi.LoggingEvent event)

void	<a href="#"><code>cleanUp()</code></a> Close the UDP Socket and release the underlying connector thread if it has been created
void	<a href="#"><code>close()</code></a> Close this appender.
String	<a href="#"><code>getApplication()</code></a> Returns value of the <b>App</b> option.
String	<a href="#"><code>getEncoding()</code></a> Returns value of the <b>Encoding</b> option.
int	<a href="#"><code>getPort()</code></a> Returns value of the <b>Port</b> option.
String	<a href="#"><code>getRemoteHost()</code></a> Returns value of the <b>RemoteHost</b> option.
boolean	<a href="#"><code>isActive()</code></a>
boolean	<a href="#"><code>requiresLayout()</code></a> The UDPAppender uses layouts.
void	<a href="#"><code>setApplication(String app)</code></a> The <b>App</b> option takes a string value which should be the name of the application getting logged.
void	<a href="#"><code>setEncoding(String encoding)</code></a> The <b>Encoding</b> option specifies how the bytes are encoded.
void	<a href="#"><code>setPort(int port)</code></a> The <b>Port</b> option takes a positive integer representing the port where UDP packets will be sent.
void	<a href="#"><code>setRemoteHost(String host)</code></a> The <b>RemoteHost</b> option takes a string value which should be the host name or ipaddress to send the UDP packets.

**Methods inherited from class org.apache.log4j.AppenderSkeleton**

activateOptions, addFilter, append, clearFilters, doAppend, finalize, getErrorHandler, getFilter, getFirstFilter, getLayout, getName, getThreshold, isAsSevereAsThreshold, setErrorHandler, setLayout, setName, setThreshold

**Methods inherited from class java.lang.Object**

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface org.apache.log4j.Appender**

addFilter, clearFilters, close, doAppend, getErrorHandler, getFilter, getLayout, getName, requiresLayout, setErrorHandler, setLayout, setName

**Methods inherited from interface org.apache.log4j.spi.OptionHandler**

activateOptions

**Methods inherited from interface com.wowza.wms.logging.PortBased**



```
getPort
```

Methods inherited from interface `com.wowza.wms.logging.NetworkBased`

```
getName, isActive
```

## Fields

### DEFAULT\_PORT

```
public static final int DEFAULT_PORT
```

The default port number for the UDP packets, 9991.  
Constant value: **9991**

## Constructors

### UDPAppender

```
public UDPAppender()
```

### UDPAppender

```
public UDPAppender(java.net.InetAddress address,  
                    int port)
```

Sends UDP packets to the address and port.

### UDPAppender

```
public UDPAppender(String host,  
                    int port)
```

Sends UDP packets to the address and port.

## Methods

### activateOptions

```
public void activateOptions()
```

Open the UDP sender for the **RemoteHost** and **Port**.

### close

```
public void close()
```

Close this appender.

This will mark the appender as closed and call then [cleanUp\(\)](#) method.

(continued from last page)

## cleanUp

```
public void cleanUp()
```

Close the UDP Socket and release the underlying connector thread if it has been created

---

## append

```
public void append(org.apache.log4j.spi.LoggingEvent event)
```

---

## isActive

```
public boolean isActive()
```

---

## requiresLayout

```
public boolean requiresLayout()
```

The **UDPAppender** uses layouts. Hence, this method returns true.

---

## setRemoteHost

```
public void setRemoteHost(String host)
```

The **RemoteHost** option takes a string value which should be the host name or ipaddress to send the UDP packets.

---

## getRemoteHost

```
public String getRemoteHost()
```

Returns value of the **RemoteHost** option.

---

## setApplication

```
public void setApplication(String app)
```

The **App** option takes a string value which should be the name of the application getting logged. If property was already set (via system property), don't set here.

---

## getApplication

```
public String getApplication()
```

Returns value of the **App** option.

---

## setEncoding

```
public void setEncoding(String encoding)
```

The **Encoding** option specifies how the bytes are encoded. If this option is not specified, the System encoding is used.

---

## getEncoding

```
public String getEncoding()
```

---

(continued from last page)

Returns value of the **Encoding** option.

---

## setPort

```
public void setPort(int port)
```

The **Port** option takes a positive integer representing the port where UDP packets will be sent.

---

## getPort

```
public int getPort()
```

Returns value of the **Port** option.

## com.wowza.wms.logging Class WMSLogger

```

java.lang.Object
  |
  +-org.apache.log4j.Category
    |
    +-org.apache.log4j.Logger
      |
      +-com.wowza.wms.logging.WMSLogger
  
```

### All Implemented Interfaces:

org.apache.log4j.spi.AppenderAttachable

```

public class WMSLogger
extends org.apache.log4j.Logger
  
```

### Fields inherited from class org.apache.log4j.Category

additive, level, name, parent, repository, resourceBundle

## Constructor Summary

public	<a href="#">WMSLogger</a> (String name, org.apache.log4j.Logger tmpLogger)
public	<a href="#">WMSLogger</a> (String name)

## Method Summary

void	<a href="#">debug</a> (Object o)
void	<a href="#">debug</a> (Object o, Throwable e)
void	<a href="#">debug</a> (String comment)
void	<a href="#">debug</a> (String comment, <a href="#">IMediaStream</a> stream)
void	<a href="#">debug</a> (String comment, <a href="#">IMediaStream</a> stream, String category, String event, int status, String context)
void	<a href="#">debug</a> (String comment, String category, String event)
void	<a href="#">debug</a> (String comment, String category, String event, int status, String context)
void	<a href="#">debug</a> (String comment, Throwable e)
void	<a href="#">error</a> (Object o)
void	<a href="#">error</a> (Object o, Throwable e)

void	<a href="#"><u>error</u></a> (String comment)
void	<a href="#"><u>error</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream)
void	<a href="#"><u>error</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event, int status, String context)
void	<a href="#"><u>error</u></a> (String comment, String category, String event)
void	<a href="#"><u>error</u></a> (String comment, String category, String event, int status, String context)
void	<a href="#"><u>error</u></a> (String comment, Throwable e)
void	<a href="#"><u>fatal</u></a> (Object o)
void	<a href="#"><u>fatal</u></a> (Object o, Throwable e)
void	<a href="#"><u>fatal</u></a> (String comment)
void	<a href="#"><u>fatal</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream)
void	<a href="#"><u>fatal</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event, int status, String context)
void	<a href="#"><u>fatal</u></a> (String comment, String category, String event)
void	<a href="#"><u>fatal</u></a> (String comment, String category, String event, int status, String context)
void	<a href="#"><u>fatal</u></a> (String comment, Throwable e)
static <a href="#"><u>WMSLogger</u></a>	<a href="#"><u>getLogger</u></a> (String name)
void	<a href="#"><u>info</u></a> (Object o)
void	<a href="#"><u>info</u></a> (Object o, Throwable e)
void	<a href="#"><u>info</u></a> (String comment)
void	<a href="#"><u>info</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream)
void	<a href="#"><u>info</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event, int status, String context)
void	<a href="#"><u>info</u></a> (String comment, String category, String event)
void	<a href="#"><u>info</u></a> (String comment, String category, String event, int status, String context)

void	<a href="#"><u>info</u></a> (String comment, Throwable e)
boolean	<a href="#"><u>isDebugEnabled</u></a> ()
boolean	<a href="#"><u>isEnabledFor</u></a> (org.apache.log4j.Priority level)
boolean	<a href="#"><u>isErrorEnabled</u></a> ()
boolean	<a href="#"><u>isInfoEnabled</u></a> ()
boolean	<a href="#"><u>isTraceEnabled</u></a> ()
boolean	<a href="#"><u>isWarnEnabled</u></a> ()
void	<a href="#"><u>log</u></a> (org.apache.log4j.Level level, String comment)
void	<a href="#"><u>log</u></a> (org.apache.log4j.Level level, String comment, <a href="#"><u>IMediaStream</u></a> stream)
void	<a href="#"><u>log</u></a> (org.apache.log4j.Level level, String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event)
void	<a href="#"><u>log</u></a> (org.apache.log4j.Level level, String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event, int status, String context)
void	<a href="#"><u>log</u></a> (org.apache.log4j.Level level, String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event, int status, String context, Throwable e)
void	<a href="#"><u>log</u></a> (org.apache.log4j.Level level, String comment, String category, String event)
void	<a href="#"><u>warn</u></a> (Object o)
void	<a href="#"><u>warn</u></a> (Object o, Throwable e)
void	<a href="#"><u>warn</u></a> (String comment)
void	<a href="#"><u>warn</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream)
void	<a href="#"><u>warn</u></a> (String comment, <a href="#"><u>IMediaStream</u></a> stream, String category, String event, int status, String context)
void	<a href="#"><u>warn</u></a> (String comment, String category, String event)
void	<a href="#"><u>warn</u></a> (String comment, String category, String event, int status, String context)
void	<a href="#"><u>warn</u></a> (String comment, Throwable e)

#### Methods inherited from class org.apache.log4j.Logger

getLogger, getLogger, getLogger, getLogger, getRootLogger, isTraceEnabled, trace, trace

**Methods inherited from class** org.apache.log4j.Category

addAppender, assertLog, callAppenders, debug, debug, error, error, exists, fatal, fatal, forcedLog, getAdditivity, getAllAppenders, getAppender, getChainedPriority, getCurrentCategories, getDefaultHierarchy, getEffectiveLevel, getHierarchy, getInstance, getInstance, getLevel, getLoggerRepository, getName, getParent, getPriority, getResourceBundle, getResourceBundleString, getRoot, info, info, isAttached, isDebugEnabled, isEnabledFor, isInfoEnabled, l7dlog, l7dlog, log, log, log, removeAllAppenders, removeAppender, removeAppender, setAdditivity, setLevel, setPriority, setResourceBundle, shutdown, warn, warn

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface** org.apache.log4j.spi.AppenderAttachable

addAppender, getAllAppenders, getAppender, isAttached, removeAllAppenders, removeAppender, removeAppender

## Constructors

### WMSLogger

```
public WMSLogger(String name,  
                 org.apache.log4j.Logger tmpLogger)
```

### WMSLogger

```
public WMSLogger(String name)
```

## Methods

### getLogger

```
public static WMSLogger getLogger(String name)
```

### isWarnEnabled

```
public boolean isWarnEnabled()
```

### isErrorEnabled

```
public boolean isErrorEnabled()
```

---

## isTraceEnabled

```
public boolean isTraceEnabled()
```

---

---

## isDebugEnabled

```
public boolean isDebugEnabled()
```

---

---

## isInfoEnabled

```
public boolean isInfoEnabled()
```

---

---

## isEnabledFor

```
public boolean isEnabledFor(org.apache.log4j.Priority level)
```

---

---

## log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               IMediaStream stream,  
               String category,  
               String event,  
               int status,  
               String context,  
               Throwable e)
```

---

---

## log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               IMediaStream stream,  
               String category,  
               String event,  
               int status,  
               String context)
```

---

---

## log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               IMediaStream stream,  
               String category,  
               String event)
```

---



(continued from last page)

**log**

```
public void log(org.apache.log4j.Level level,
               String comment,
               String category,
               String event)
```

---

**log**

```
public void log(org.apache.log4j.Level level,
               String comment)
```

---

**log**

```
public void log(org.apache.log4j.Level level,
               String comment,
               IMediaStream stream)
```

---

**info**

```
public void info(Object o)
```

---

**info**

```
public void info(Object o,
               Throwable e)
```

---

**info**

```
public void info(String comment)
```

---

**info**

```
public void info(String comment,
               Throwable e)
```

---

**info**

```
public void info(String comment,
               IMediaStream stream)
```

---

(continued from last page)

**info**

```
public void info(String comment,  
                String category,  
                String event)
```

---

**info**

```
public void info(String comment,  
                String category,  
                String event,  
                int status,  
                String context)
```

---

**info**

```
public void info(String comment,  
                IMediaStream stream,  
                String category,  
                String event,  
                int status,  
                String context)
```

---

**error**

```
public void error(Object o)
```

---

**error**

```
public void error(Object o,  
                Throwable e)
```

---

**error**

```
public void error(String comment)
```

---

**error**

```
public void error(String comment,  
                Throwable e)
```

---

**error**

```
public void error(String comment,  
                IMediaStream stream)
```

---

**error**

```
public void error(String comment,
                  String category,
                  String event)
```

---

**error**

```
public void error(String comment,
                  String category,
                  String event,
                  int status,
                  String context)
```

---

**error**

```
public void error(String comment,
                  IMediaStream stream,
                  String category,
                  String event,
                  int status,
                  String context)
```

---

**fatal**

```
public void fatal(Object o)
```

---

**fatal**

```
public void fatal(Object o,
                  Throwable e)
```

---

**fatal**

```
public void fatal(String comment)
```

---

**fatal**

```
public void fatal(String comment,
                  Throwable e)
```

---

**fatal**

```
public void fatal(String comment,
                  IMediaStream stream)
```

---

(continued from last page)

---

**fatal**

```
public void fatal(String comment,  
                  String category,  
                  String event)
```

---

**fatal**

```
public void fatal(String comment,  
                  String category,  
                  String event,  
                  int status,  
                  String context)
```

---

**fatal**

```
public void fatal(String comment,  
                  IMediaStream stream,  
                  String category,  
                  String event,  
                  int status,  
                  String context)
```

---

**debug**

```
public void debug(Object o)
```

---

**debug**

```
public void debug(Object o,  
                  Throwable e)
```

---

**debug**

```
public void debug(String comment)
```

---

**debug**

```
public void debug(String comment,  
                  Throwable e)
```

---

(continued from last page)

## debug

```
public void debug(String comment,  
    IMediaStream stream)
```

---

## debug

```
public void debug(String comment,  
    String category,  
    String event)
```

---

## debug

```
public void debug(String comment,  
    String category,  
    String event,  
    int status,  
    String context)
```

---

## debug

```
public void debug(String comment,  
    IMediaStream stream,  
    String category,  
    String event,  
    int status,  
    String context)
```

---

## warn

```
public void warn(Object o)
```

---

## warn

```
public void warn(Object o,  
    Throwable e)
```

---

## warn

```
public void warn(String comment)
```

---

## warn

```
public void warn(String comment,  
    Throwable e)
```

---

**warn**

```
public void warn(String comment,  
    IMediaStream stream)
```

---

**warn**

```
public void warn(String comment,  
    String category,  
    String event)
```

---

**warn**

```
public void warn(String comment,  
    String category,  
    String event,  
    int status,  
    String context)
```

---

**warn**

```
public void warn(String comment,  
    IMediaStream stream,  
    String category,  
    String event,  
    int status,  
    String context)
```

## com.wowza.wms.logging Class WMSLoggerFactory

java.lang.Object

└-com.wowza.wms.logging.WMSLoggerFactory

### All Implemented Interfaces:

org.apache.log4j.spi.LoggerFactory

public class **WMSLoggerFactory**  
 extends Object  
 implements org.apache.log4j.spi.LoggerFactory

### Field Summary

public static final	<a href="#">LOGGERNAME_SERVER</a> Value: <b>_Server_</b>
---------------------	---

### Constructor Summary

public	<a href="#">WMSLoggerFactory()</a>
--------	------------------------------------

### Method Summary

<a href="#">WMSLogger</a>	<a href="#">forceNewLoggerInstance</a> (String name, org.apache.log4j.Logger tmpLogger)
static Object	<a href="#">getGlobalLogValue</a> (String key)
static <a href="#">WMSLoggerFactory</a>	<a href="#">getInstance</a> ()
static <a href="#">WMSLogger</a>	<a href="#">getLogger</a> (Class classObj)
static <a href="#">WMSLogger</a>	<a href="#">getLoggerObj</a> ( <a href="#">IApplication</a> application)
static <a href="#">WMSLogger</a>	<a href="#">getLoggerObj</a> ( <a href="#">IApplicationInstance</a> appInstance)
static <a href="#">WMSLogger</a>	<a href="#">getLoggerObj</a> ( <a href="#">IVHost</a> vhost)
<a href="#">WMSLogger</a>	<a href="#">getLoggerObj</a> (String name)
static void	<a href="#">initContextLogging</a> ( <a href="#">IApplication</a> application)
static void	<a href="#">initContextLogging</a> ( <a href="#">IApplicationInstance</a> appInstance)
static void	<a href="#">initContextLogging</a> ( <a href="#">IVHost</a> vhost)

static <a href="#">WMSLogger</a>	<a href="#">initializeLogging</a> (String loggingConfigURL)
static <a href="#">WMSLogger</a>	<a href="#">initializeLogging</a> (String loggingConfigURL, <a href="#">IVHost</a> vhost)
static boolean	<a href="#">isGlobalLogValueSet</a> (String key)
org.apache.log4j.Logger	<a href="#">makeNewLoggerInstance</a> (String name)
static void	<a href="#">putGlobalLogValue</a> (String key, Object obj)
static void	<a href="#">removeGlobalLogValue</a> (String key)
static void	<a href="#">removeGlobalLogValues</a> ()
static void	<a href="#">resetMDC</a> ()

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface org.apache.log4j.spi.LoggerFactory

makeNewLoggerInstance

## Fields

### LOGGERNAME\_SERVER

```
public static final java.lang.String LOGGERNAME_SERVER
```

Constant value: **\_Server\_**

## Constructors

### WMSLoggerFactory

```
public WMSLoggerFactory()
```

## Methods

### getLoggerObj

```
public WMSLogger getLoggerObj(String name)
```



(continued from last page)

## forceNewLoggerInstance

```
public WMSLogger forceNewLoggerInstance(String name,  
    org.apache.log4j.Logger tmpLogger)
```

---

## getInstance

```
public static WMSLoggerFactory getInstance()
```

---

## initContextLogging

```
public static void initContextLogging(IVHost vhost)
```

---

## initContextLogging

```
public static void initContextLogging(IApplication application)
```

---

## initContextLogging

```
public static void initContextLogging(IApplicationInstance appInstance)
```

---

## initializeLogging

```
public static WMSLogger initializeLogging(String loggingConfigURL)
```

---

## initializeLogging

```
public static WMSLogger initializeLogging(String loggingConfigURL,  
    IVHost vhost)
```

---

## makeNewLoggerInstance

```
public org.apache.log4j.Logger makeNewLoggerInstance(String name)
```

---

## resetMDC

```
public static void resetMDC()
```

---

(continued from last page)

---

## removeGlobalLogValues

```
public static void removeGlobalLogValues()
```

---

## removeGlobalLogValue

```
public static void removeGlobalLogValue(String key)
```

---

## isGlobalLogValueSet

```
public static boolean isGlobalLogValueSet(String key)
```

---

## putGlobalLogValue

```
public static void putGlobalLogValue(String key,  
                                     Object obj)
```

---

## getGlobalLogValue

```
public static Object getGlobalLogValue(String key)
```

---

## getLoggerObj

```
public static WMSLogger getLoggerObj(IVHost vhost)
```

---

## getLoggerObj

```
public static WMSLogger getLoggerObj(IApplication application)
```

---

## getLoggerObj

```
public static WMSLogger getLoggerObj(IApplicationInstance appInstance)
```

---

## getLogger

```
public static WMSLogger getLogger(Class classObj)
```

---

## com.wowza.wms.logging

### Class WMSLoggerIDs

java.lang.Object

└-com.wowza.wms.logging.WMSLoggerIDs

public class **WMSLoggerIDs**  
extends Object

#### Field Summary

public static final	<a href="#">CAT_ALL</a>
public static final	<a href="#">CAT_application</a> Value: <b>application</b>
public static final	<a href="#">CAT_cupertino</a> Value: <b>cupertino</b>
public static final	<a href="#">CAT_dvrchunk</a> Value: <b>dvrchunk</b>
public static final	<a href="#">CAT_mpegdash</a> Value: <b>mpegdash</b>
public static final	<a href="#">CAT_rtsp</a> Value: <b>rtsp</b>
public static final	<a href="#">CAT_sanjose</a> Value: <b>sanjose</b>
public static final	<a href="#">CAT_server</a> Value: <b>server</b>
public static final	<a href="#">CAT_session</a> Value: <b>session</b>
public static final	<a href="#">CAT_smoothstreaming</a> Value: <b>smoothstreaming</b>
public static final	<a href="#">CAT_stream</a> Value: <b>stream</b>
public static final	<a href="#">CAT_transcoder</a> Value: <b>transcoder</b>

public static final	<a href="#">CAT_vhost</a> Value: <b>vhost</b>
public static final	<a href="#">CAT_webm</a> Value: <b>webm</b>
public static final	<a href="#">CTRL_playlist_node</a> Value: <b>CTRL-playlist-node</b>
public static final	<a href="#">EVT_ALL</a>
public static final	<a href="#">EVT_announce</a> Value: <b>announce</b>
public static final	<a href="#">EVT_app_start</a> Value: <b>app-start</b>
public static final	<a href="#">EVT_app_stop</a> Value: <b>app-stop</b>
public static final	<a href="#">EVT_comment</a> Value: <b>comment</b>
public static final	<a href="#">EVT_connect</a> Value: <b>connect</b>
public static final	<a href="#">EVT_connect_burst</a> Value: <b>connect-burst</b>
public static final	<a href="#">EVT_connect_pending</a> Value: <b>connect-pending</b>
public static final	<a href="#">EVT_create</a> Value: <b>create</b>
public static final	<a href="#">EVT_decoderaudiostart</a> Value: <b>decoder-audio-start</b>
public static final	<a href="#">EVT_decoderaudiostop</a> Value: <b>decoder-audio-stop</b>
public static final	<a href="#">EVT_decodervideostart</a> Value: <b>decoder-video-start</b>
public static final	<a href="#">EVT_decodervideostop</a> Value: <b>decoder-video-stop</b>

public static final	<a href="#">EVT_describe</a> Value: <b>describe</b>
public static final	<a href="#">EVT_destroy</a> Value: <b>destroy</b>
public static final	<a href="#">EVT_disconnect</a> Value: <b>disconnect</b>
public static final	<a href="#">EVT_encoderaudiostart</a> Value: <b>encoder-audio-start</b>
public static final	<a href="#">EVT_encoderaudiostop</a> Value: <b>encoder-audio-stop</b>
public static final	<a href="#">EVT_encodervideostart</a> Value: <b>encoder-video-start</b>
public static final	<a href="#">EVT_encodervideostop</a> Value: <b>encoder-video-stop</b>
public static final	<a href="#">EVT_pause</a> Value: <b>pause</b>
public static final	<a href="#">EVT_play</a> Value: <b>play</b>
public static final	<a href="#">EVT_publish</a> Value: <b>publish</b>
public static final	<a href="#">EVT_record</a> Value: <b>record</b>
public static final	<a href="#">EVT_recordstop</a> Value: <b>recordstop</b>
public static final	<a href="#">EVT_seek</a> Value: <b>seek</b>
public static final	<a href="#">EVT_server_start</a> Value: <b>server-start</b>
public static final	<a href="#">EVT_server_stop</a> Value: <b>server-stop</b>
public static final	<a href="#">EVT_setbuffertime</a> Value: <b>setbuffertime</b>

public static final	<a href="#">EVT_setstreamtype</a> Value: <b>setstreamtype</b>
public static final	<a href="#">EVT_stop</a> Value: <b>stop</b>
public static final	<a href="#">EVT_unpause</a> Value: <b>unpause</b>
public static final	<a href="#">EVT_unpublish</a> Value: <b>unpublish</b>
public static final	<a href="#">EVT_vhost_start</a> Value: <b>vhost-start</b>
public static final	<a href="#">EVT_vhost_stop</a> Value: <b>vhost-stop</b>
public static final	<a href="#">FD_ALL</a>
public static final	<a href="#">FD_c_client_id</a> Value: <b>c-client-id</b>
public static final	<a href="#">FD_c_ip</a> Value: <b>c-ip</b>
public static final	<a href="#">FD_c_proto</a> Value: <b>c-proto</b>
public static final	<a href="#">FD_c_referrer</a> Value: <b>c-referrer</b>
public static final	<a href="#">FD_c_user_agent</a> Value: <b>c-user-agent</b>
public static final	<a href="#">FD_cs_bytes</a> Value: <b>cs-bytes</b>
public static final	<a href="#">FD_cs_stream_bytes</a> Value: <b>cs-stream-bytes</b>
public static final	<a href="#">FD_cs_uri_query</a> Value: <b>cs-uri-query</b>
public static final	<a href="#">FD_cs_uri_stem</a> Value: <b>cs-uri-stem</b>

public static final	<a href="#">FD_date</a> Value: <b>date</b>
public static final	<a href="#">FD_s_ip</a> Value: <b>s-ip</b>
public static final	<a href="#">FD_s_port</a> Value: <b>s-port</b>
public static final	<a href="#">FD_s_uri</a> Value: <b>s-uri</b>
public static final	<a href="#">FD_sc_bytes</a> Value: <b>sc-bytes</b>
public static final	<a href="#">FD_sc_stream_bytes</a> Value: <b>sc-stream-bytes</b>
public static final	<a href="#">FD_time</a> Value: <b>time</b>
public static final	<a href="#">FD_tz</a> Value: <b>tz</b>
public static final	<a href="#">FD_x_app</a> Value: <b>x-app</b>
public static final	<a href="#">FD_x_appinst</a> Value: <b>x-appinst</b>
public static final	<a href="#">FD_x_category</a> Value: <b>x-category</b>
public static final	<a href="#">FD_x_comment</a> Value: <b>x-comment</b>
public static final	<a href="#">FD_x_ctx</a> Value: <b>x-ctx</b>
public static final	<a href="#">FD_x_ctx_override</a> Value: <b>x-ctx-override</b>
public static final	<a href="#">FD_x_duration</a> Value: <b>x-duration</b>
public static final	<a href="#">FD_x_event</a> Value: <b>x-event</b>

public static final	<a href="#">FD_x_file_ext</a> Value: <b>x-file-ext</b>
public static final	<a href="#">FD_x_file_length</a> Value: <b>x-file-length</b>
public static final	<a href="#">FD_x_file_name</a> Value: <b>x-file-name</b>
public static final	<a href="#">FD_x_file_size</a> Value: <b>x-file-size</b>
public static final	<a href="#">FD_x_severity</a> Value: <b>x-severity</b>
public static final	<a href="#">FD_x_sname</a> Value: <b>x-sname</b>
public static final	<a href="#">FD_x_sname_query</a> Value: <b>x-sname-query</b>
public static final	<a href="#">FD_x_spos</a> Value: <b>x-spos</b>
public static final	<a href="#">FD_x_status</a> Value: <b>x-status</b>
public static final	<a href="#">FD_x_stream_id</a> Value: <b>x-stream-id</b>
public static final	<a href="#">FD_x_suri</a> Value: <b>x-suri</b>
public static final	<a href="#">FD_x_suri_query</a> Value: <b>x-suri-query</b>
public static final	<a href="#">FD_x_suri_stem</a> Value: <b>x-suri-stem</b>
public static final	<a href="#">FD_x_vhost</a> Value: <b>x-vhost</b>
public static final	<a href="#">PROTO_HTTPCUPERTINO</a> Value: <b>http (cupertino)</b>
public static final	<a href="#">PROTO_HTTPDVRCHUNK</a> Value: <b>http (dvr)</b>



public static final	<a href="#">PROTO_HTTPMPEGDASH</a> Value: <b>http (mpegdash)</b>
public static final	<a href="#">PROTO_HTTPSANJOSE</a> Value: <b>http (sanjose)</b>
public static final	<a href="#">PROTO_HTTPSCUPERTINO</a> Value: <b>https (cupertino)</b>
public static final	<a href="#">PROTO_HTTPSDVRCHUNK</a> Value: <b>https (dvr)</b>
public static final	<a href="#">PROTO_HTTPSMOOTH</a> Value: <b>http (smooth)</b>
public static final	<a href="#">PROTO_HTTPSSANJOSE</a> Value: <b>https (sanjose)</b>
public static final	<a href="#">PROTO_HTTPSSMOOTH</a> Value: <b>https (smooth)</b>
public static final	<a href="#">PROTO_HTTPSSTREAMER</a> Value: <b>https (streamer)</b>
public static final	<a href="#">PROTO_HTTPSTREAMER</a> Value: <b>http (streamer)</b>
public static final	<a href="#">PROTO_RTMP</a> Value: <b>rtmp</b>
public static final	<a href="#">PROTO_RTMPE</a> Value: <b>rtmpe</b>
public static final	<a href="#">PROTO_RTMPs</a> Value: <b>rtmps</b>
public static final	<a href="#">PROTO_RTMPt</a> Value: <b>rtmpt (HTTP-1.1)</b>
public static final	<a href="#">PROTO_RTMPtE</a> Value: <b>rtmpte (HTTP-1.1)</b>
public static final	<a href="#">PROTO_RTMPts</a> Value: <b>rtmpts (HTTP-1.1)</b>
public static final	<a href="#">PROTO_RTSP</a> Value: <b>rtsp</b>

public static final	<a href="#">PROTO_WOWZ</a> Value: <b>wowz</b>
public static final	<a href="#">PROTO_WOWZE</a> Value: <b>wowze</b>
public static final	<a href="#">PROTO_WOWZS</a> Value: <b>wowzs</b>
public static final	<a href="#">STAT_connect_application_not_available</a> Value: <b>302</b>
public static final	<a href="#">STAT_connect_application_not_found</a> Value: <b>404</b>
public static final	<a href="#">STAT_connect_bad_gateway</a> Value: <b>502</b>
public static final	<a href="#">STAT_connect_internal_error</a> Value: <b>500</b>
public static final	<a href="#">STAT_connect_license_limit</a> Value: <b>413</b>
public static final	<a href="#">STAT_connect_pending_wating</a> Value: <b>100</b>
public static final	<a href="#">STAT_connect_redirect</a> Value: <b>302</b>
public static final	<a href="#">STAT_connect_rejected_by_application</a> Value: <b>401</b>
public static final	<a href="#">STAT_connect_rejected_by_module</a> Value: <b>403</b>
public static final	<a href="#">STAT_connect_resource_limit</a> Value: <b>409</b>
public static final	<a href="#">STAT_connect_service_unavailable</a> Value: <b>503</b>
public static final	<a href="#">STAT_connect_successful</a> Value: <b>200</b>
public static final	<a href="#">STAT_connect_unknown_protocol</a> Value: <b>400</b>

public static final	<a href="#"><u>STAT_general_internal_error</u></a> Value: <b>500</b>
public static final	<a href="#"><u>STAT_general_successful</u></a> Value: <b>200</b>
public static final	<a href="#"><u>STAT_play_bad_request</u></a> Value: <b>400</b>
public static final	<a href="#"><u>STAT_play_internal_error</u></a> Value: <b>500</b>
public static final	<a href="#"><u>STAT_play_rejected_by_application</u></a> Value: <b>401</b>
public static final	<a href="#"><u>STAT_play_rejected_by_module</u></a> Value: <b>403</b>
public static final	<a href="#"><u>STAT_play_stream_not_found</u></a> Value: <b>404</b>
public static final	<a href="#"><u>STAT_play_successful</u></a> Value: <b>200</b>
public static final	<a href="#"><u>STAT_play_unsupported_media_type</u></a> Value: <b>415</b>
public static final	<a href="#"><u>STAT_publish_bad_request</u></a> Value: <b>400</b>
public static final	<a href="#"><u>STAT_publish_in_use</u></a> Value: <b>409</b>
public static final	<a href="#"><u>STAT_publish_internal_error</u></a> Value: <b>500</b>
public static final	<a href="#"><u>STAT_publish_rejected_by_application</u></a> Value: <b>401</b>
public static final	<a href="#"><u>STAT_publish_successful</u></a> Value: <b>200</b>
public static final	<a href="#"><u>STAT_publish_unsupported_media_type</u></a> Value: <b>415</b>
public static final	<a href="#"><u>STAT_stop_client_disconnect</u></a> Value: <b>408</b>

```
public static final
```

```
STAT\_stop\_successful
```

```
Value: 200
```

## Constructor Summary

```
public
```

```
WMSLoggerIDs( )
```

Methods inherited from class `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

## Fields

### FD\_x\_event

```
public static final java.lang.String FD_x_event
```

Constant value: **x-event**

### FD\_x\_category

```
public static final java.lang.String FD_x_category
```

Constant value: **x-category**

### FD\_date

```
public static final java.lang.String FD_date
```

Constant value: **date**

### FD\_time

```
public static final java.lang.String FD_time
```

Constant value: **time**

### FD\_tz

```
public static final java.lang.String FD_tz
```

Constant value: **tz**

### FD\_x\_ctx

```
public static final java.lang.String FD_x_ctx
```

Constant value: **x-ctx**

---

## FD\_x\_ctx\_override

```
public static final java.lang.String FD_x_ctx_override
```

Constant value: **x-ctx-override**

---

## FD\_x\_vhost

```
public static final java.lang.String FD_x_vhost
```

Constant value: **x-vhost**

---

## FD\_x\_app

```
public static final java.lang.String FD_x_app
```

Constant value: **x-app**

---

## FD\_x\_appinst

```
public static final java.lang.String FD_x_appinst
```

Constant value: **x-appinst**

---

## FD\_c\_ip

```
public static final java.lang.String FD_c_ip
```

Constant value: **c-ip**

---

## FD\_c\_proto

```
public static final java.lang.String FD_c_proto
```

Constant value: **c-proto**

---

## FD\_s\_uri

```
public static final java.lang.String FD_s_uri
```

Constant value: **s-uri**

---

## FD\_c\_referrer

```
public static final java.lang.String FD_c_referrer
```

Constant value: **c-referrer**

---

(continued from last page)

---

## FD\_c\_user\_agent

```
public static final java.lang.String FD_c_user_agent
```

Constant value: **c-user-agent**

---

## FD\_c\_client\_id

```
public static final java.lang.String FD_c_client_id
```

Constant value: **c-client-id**

---

## FD\_cs\_bytes

```
public static final java.lang.String FD_cs_bytes
```

Constant value: **cs-bytes**

---

## FD\_sc\_bytes

```
public static final java.lang.String FD_sc_bytes
```

Constant value: **sc-bytes**

---

## FD\_x\_sname

```
public static final java.lang.String FD_x_sname
```

Constant value: **x-sname**

---

## FD\_x\_file\_size

```
public static final java.lang.String FD_x_file_size
```

Constant value: **x-file-size**

---

## FD\_x\_file\_length

```
public static final java.lang.String FD_x_file_length
```

Constant value: **x-file-length**

---

## FD\_x\_spos

```
public static final java.lang.String FD_x_spos
```

Constant value: **x-spos**

---

## FD\_cs\_stream\_bytes

```
public static final java.lang.String FD_cs_stream_bytes
```

---

(continued from last page)

---

Constant value: **cs-stream-bytes**

---

## FD\_sc\_stream\_bytes

```
public static final java.lang.String FD_sc_stream_bytes
```

---

Constant value: **sc-stream-bytes**

---

## FD\_s\_ip

```
public static final java.lang.String FD_s_ip
```

---

Constant value: **s-ip**

---

## FD\_x\_duration

```
public static final java.lang.String FD_x_duration
```

---

Constant value: **x-duration**

---

## FD\_x\_status

```
public static final java.lang.String FD_x_status
```

---

Constant value: **x-status**

---

## FD\_cs\_uri\_stem

```
public static final java.lang.String FD_cs_uri_stem
```

---

Constant value: **cs-uri-stem**

---

## FD\_cs\_uri\_query

```
public static final java.lang.String FD_cs_uri_query
```

---

Constant value: **cs-uri-query**

---

## FD\_x\_sname\_query

```
public static final java.lang.String FD_x_sname_query
```

---

Constant value: **x-sname-query**

---

## FD\_x\_file\_name

```
public static final java.lang.String FD_x_file_name
```

---

Constant value: **x-file-name**

---

---

## FD\_x\_file\_ext

```
public static final java.lang.String FD_x_file_ext
```

Constant value: **x-file-ext**

---

## FD\_x\_suri\_query

```
public static final java.lang.String FD_x_suri_query
```

Constant value: **x-suri-query**

---

## FD\_x\_suri\_stem

```
public static final java.lang.String FD_x_suri_stem
```

Constant value: **x-suri-stem**

---

## FD\_x\_suri

```
public static final java.lang.String FD_x_suri
```

Constant value: **x-suri**

---

## FD\_x\_severity

```
public static final java.lang.String FD_x_severity
```

Constant value: **x-severity**

---

## FD\_x\_comment

```
public static final java.lang.String FD_x_comment
```

Constant value: **x-comment**

---

## FD\_s\_port

```
public static final java.lang.String FD_s_port
```

Constant value: **s-port**

---

## FD\_x\_stream\_id

```
public static final java.lang.String FD_x_stream_id
```

Constant value: **x-stream-id**

---



(continued from last page)

---

## CAT\_server

```
public static final java.lang.String CAT_server
```

Constant value: **server**

---

## CAT\_vhost

```
public static final java.lang.String CAT_vhost
```

Constant value: **vhost**

---

## CAT\_application

```
public static final java.lang.String CAT_application
```

Constant value: **application**

---

## CAT\_session

```
public static final java.lang.String CAT_session
```

Constant value: **session**

---

## CAT\_stream

```
public static final java.lang.String CAT_stream
```

Constant value: **stream**

---

## CAT\_rtsp

```
public static final java.lang.String CAT_rtsp
```

Constant value: **rtsp**

---

## CAT\_cupertino

```
public static final java.lang.String CAT_cupertino
```

Constant value: **cupertino**

---

## CAT\_sanjose

```
public static final java.lang.String CAT_sanjose
```

Constant value: **sanjose**

---

## CAT\_smoothstreaming

```
public static final java.lang.String CAT_smoothstreaming
```

(continued from last page)

---

Constant value: **smoothstreaming**

---

## CAT\_dvrchunk

```
public static final java.lang.String CAT_dvrchunk
```

Constant value: **dvrchunk**

---

## CAT\_webm

```
public static final java.lang.String CAT_webm
```

Constant value: **webm**

---

## CAT\_transcoder

```
public static final java.lang.String CAT_transcoder
```

Constant value: **transcoder**

---

## CAT\_mpegdash

```
public static final java.lang.String CAT_mpegdash
```

Constant value: **mpegdash**

---

## EVT\_connect\_pending

```
public static final java.lang.String EVT_connect_pending
```

Constant value: **connect-pending**

---

## EVT\_connect

```
public static final java.lang.String EVT_connect
```

Constant value: **connect**

---

## EVT\_connect\_burst

```
public static final java.lang.String EVT_connect_burst
```

Constant value: **connect-burst**

---

## EVT\_disconnect

```
public static final java.lang.String EVT_disconnect
```

Constant value: **disconnect**

---

## EVT\_publish

```
public static final java.lang.String EVT_publish
```

Constant value: **publish**

---

## EVT\_unpublish

```
public static final java.lang.String EVT_unpublish
```

Constant value: **unpublish**

---

## EVT\_play

```
public static final java.lang.String EVT_play
```

Constant value: **play**

---

## EVT\_pause

```
public static final java.lang.String EVT_pause
```

Constant value: **pause**

---

## EVT\_setbuffertime

```
public static final java.lang.String EVT_setbuffertime
```

Constant value: **setbuffertime**

---

## EVT\_create

```
public static final java.lang.String EVT_create
```

Constant value: **create**

---

## EVT\_destroy

```
public static final java.lang.String EVT_destroy
```

Constant value: **destroy**

---

## EVT\_setstreamtype

```
public static final java.lang.String EVT_setstreamtype
```

Constant value: **setstreamtype**

---

(continued from last page)

---

## EVT\_unpause

```
public static final java.lang.String EVT_unpause
```

Constant value: **unpause**

---

## EVT\_seek

```
public static final java.lang.String EVT_seek
```

Constant value: **seek**

---

## EVT\_stop

```
public static final java.lang.String EVT_stop
```

Constant value: **stop**

---

## EVT\_record

```
public static final java.lang.String EVT_record
```

Constant value: **record**

---

## EVT\_recordstop

```
public static final java.lang.String EVT_recordstop
```

Constant value: **recordstop**

---

## EVT\_server\_start

```
public static final java.lang.String EVT_server_start
```

Constant value: **server-start**

---

## EVT\_server\_stop

```
public static final java.lang.String EVT_server_stop
```

Constant value: **server-stop**

---

## EVT\_vhost\_start

```
public static final java.lang.String EVT_vhost_start
```

Constant value: **vhost-start**

---

## EVT\_vhost\_stop

```
public static final java.lang.String EVT_vhost_stop
```

---

(continued from last page)

---

Constant value: **vhost-stop**

---

## EVT\_app\_start

```
public static final java.lang.String EVT_app_start
```

---

Constant value: **app-start**

---

## EVT\_app\_stop

```
public static final java.lang.String EVT_app_stop
```

---

Constant value: **app-stop**

---

## EVT\_comment

```
public static final java.lang.String EVT_comment
```

---

Constant value: **comment**

---

## EVT\_announce

```
public static final java.lang.String EVT_announce
```

---

Constant value: **announce**

---

## EVT\_describe

```
public static final java.lang.String EVT_describe
```

---

Constant value: **describe**

---

## EVT\_decoderaudiostart

```
public static final java.lang.String EVT_decoderaudiostart
```

---

Constant value: **decoder-audio-start**

---

## EVT\_decoderaudiostop

```
public static final java.lang.String EVT_decoderaudiostop
```

---

Constant value: **decoder-audio-stop**

---

## EVT\_decodervideostart

```
public static final java.lang.String EVT_decodervideostart
```

---

Constant value: **decoder-video-start**

---

## EVT\_decodervideostop

```
public static final java.lang.String EVT_decodervideostop
```

Constant value: **decoder-video-stop**

---

## EVT\_encoderaudiostart

```
public static final java.lang.String EVT_encoderaudiostart
```

Constant value: **encoder-audio-start**

---

## EVT\_encoderaudiostop

```
public static final java.lang.String EVT_encoderaudiostop
```

Constant value: **encoder-audio-stop**

---

## EVT\_encodervideostart

```
public static final java.lang.String EVT_encodervideostart
```

Constant value: **encoder-video-start**

---

## EVT\_encodervideostop

```
public static final java.lang.String EVT_encodervideostop
```

Constant value: **encoder-video-stop**

---

## CTRL\_playlist\_node

```
public static final java.lang.String CTRL_playlist_node
```

Constant value: **CTRL-playlist-node**

---

## STAT\_connect\_pending\_wating

```
public static final int STAT_connect_pending_wating
```

Constant value: **100**

---

## STAT\_connect\_successful

```
public static final int STAT_connect_successful
```

Constant value: **200**

---

(continued from last page)

---

**STAT\_connect\_application\_not\_available**

```
public static final int STAT_connect_application_not_available
```

Constant value: **302**

---

**STAT\_connect\_unknown\_protocol**

```
public static final int STAT_connect_unknown_protocol
```

Constant value: **400**

---

**STAT\_connect\_rejected\_by\_application**

```
public static final int STAT_connect_rejected_by_application
```

Constant value: **401**

---

**STAT\_connect\_rejected\_by\_module**

```
public static final int STAT_connect_rejected_by_module
```

Constant value: **403**

---

**STAT\_connect\_application\_not\_found**

```
public static final int STAT_connect_application_not_found
```

Constant value: **404**

---

**STAT\_connect\_resource\_limit**

```
public static final int STAT_connect_resource_limit
```

Constant value: **409**

---

**STAT\_connect\_license\_limit**

```
public static final int STAT_connect_license_limit
```

Constant value: **413**

---

**STAT\_connect\_redirect**

```
public static final int STAT_connect_redirect
```

Constant value: **302**

---

**STAT\_connect\_internal\_error**

```
public static final int STAT_connect_internal_error
```

---

(continued from last page)

---

Constant value: **500**

---

**STAT\_connect\_bad\_gateway**

```
public static final int STAT_connect_bad_gateway
```

---

Constant value: **502**

---

**STAT\_connect\_service\_unavailable**

```
public static final int STAT_connect_service_unavailable
```

---

Constant value: **503**

---

**STAT\_play\_successful**

```
public static final int STAT_play_successful
```

---

Constant value: **200**

---

**STAT\_play\_bad\_request**

```
public static final int STAT_play_bad_request
```

---

Constant value: **400**

---

**STAT\_play\_rejected\_by\_application**

```
public static final int STAT_play_rejected_by_application
```

---

Constant value: **401**

---

**STAT\_play\_rejected\_by\_module**

```
public static final int STAT_play_rejected_by_module
```

---

Constant value: **403**

---

**STAT\_play\_stream\_not\_found**

```
public static final int STAT_play_stream_not_found
```

---

Constant value: **404**

---

**STAT\_play\_unsupported\_media\_type**

```
public static final int STAT_play_unsupported_media_type
```

---

Constant value: **415**



---

## STAT\_play\_internal\_error

public static final int **STAT\_play\_internal\_error**

Constant value: **500**

---

## STAT\_publish\_successful

public static final int **STAT\_publish\_successful**

Constant value: **200**

---

## STAT\_publish\_bad\_request

public static final int **STAT\_publish\_bad\_request**

Constant value: **400**

---

## STAT\_publish\_rejected\_by\_application

public static final int **STAT\_publish\_rejected\_by\_application**

Constant value: **401**

---

## STAT\_publish\_in\_use

public static final int **STAT\_publish\_in\_use**

Constant value: **409**

---

## STAT\_publish\_unsupported\_media\_type

public static final int **STAT\_publish\_unsupported\_media\_type**

Constant value: **415**

---

## STAT\_publish\_internal\_error

public static final int **STAT\_publish\_internal\_error**

Constant value: **500**

---

## STAT\_stop\_successful

public static final int **STAT\_stop\_successful**

Constant value: **200**

---

(continued from last page)

---

## STAT\_stop\_client\_disconnect

```
public static final int STAT_stop_client_disconnect
```

Constant value: **408**

---

## STAT\_general\_successful

```
public static final int STAT_general_successful
```

Constant value: **200**

---

## STAT\_general\_internal\_error

```
public static final int STAT_general_internal_error
```

Constant value: **500**

---

## PROTO\_RTMP

```
public static final java.lang.String PROTO_RTMP
```

Constant value: **rtmp**

---

## PROTO\_RTMPs

```
public static final java.lang.String PROTO_RTMPs
```

Constant value: **rtmps**

---

## PROTO\_RTMPT

```
public static final java.lang.String PROTO_RTMPT
```

Constant value: **rtmpt (HTTP-1.1)**

---

## PROTO\_RTMPTs

```
public static final java.lang.String PROTO_RTMPTs
```

Constant value: **rtmpts (HTTP-1.1)**

---

## PROTO\_RTMPE

```
public static final java.lang.String PROTO_RTMPE
```

Constant value: **rtmpe**

---

## PROTO\_RTMPTE

```
public static final java.lang.String PROTO_RTMPTE
```

---

(continued from last page)

---

Constant value: **rtmpte (HTTP-1.1)**

---

## PROTO\_WOWZ

```
public static final java.lang.String PROTO_WOWZ
```

---

Constant value: **wowz**

---

## PROTO\_WOWZE

```
public static final java.lang.String PROTO_WOWZE
```

---

Constant value: **wowze**

---

## PROTO\_WOWZS

```
public static final java.lang.String PROTO_WOWZS
```

---

Constant value: **wowzs**

---

## PROTO\_RTSP

```
public static final java.lang.String PROTO_RTSP
```

---

Constant value: **rtsp**

---

## PROTO\_HTTPSTREAMER

```
public static final java.lang.String PROTO_HTTPSTREAMER
```

---

Constant value: **http (streamer)**

---

## PROTO\_HTTPCUPERTINO

```
public static final java.lang.String PROTO_HTTPCUPERTINO
```

---

Constant value: **http (cupertino)**

---

## PROTO\_HTTPSMOOTH

```
public static final java.lang.String PROTO_HTTPSMOOTH
```

---

Constant value: **http (smooth)**

---

## PROTO\_HTTPSANJOSE

```
public static final java.lang.String PROTO_HTTPSANJOSE
```

---

Constant value: **http (sanjose)**

---

---

## PROTO\_HTTPDVARCHUNK

```
public static final java.lang.String PROTO_HTTPDVARCHUNK
```

Constant value: **http (dvr)**

---

## PROTO\_HTTPMPEGDASH

```
public static final java.lang.String PROTO_HTTPMPEGDASH
```

Constant value: **http (mpegdash)**

---

## PROTO\_HTTPSSTREAMER

```
public static final java.lang.String PROTO_HTTPSSTREAMER
```

Constant value: **https (streamer)**

---

## PROTO\_HTTPSCUPERTINO

```
public static final java.lang.String PROTO_HTTPSCUPERTINO
```

Constant value: **https (cupertino)**

---

## PROTO\_HTTPSSMOOTH

```
public static final java.lang.String PROTO_HTTPSSMOOTH
```

Constant value: **https (smooth)**

---

## PROTO\_HTTPSSANJOSE

```
public static final java.lang.String PROTO_HTTPSSANJOSE
```

Constant value: **https (sanjose)**

---

## PROTO\_HTTPSDVARCHUNK

```
public static final java.lang.String PROTO_HTTPSDVARCHUNK
```

Constant value: **https (dvr)**

---

## FD\_ALL

```
public static final java.lang.String FD_ALL
```

---

## CAT\_ALL

```
public static final java.lang.String CAT_ALL
```

---

(continued from last page)

---

## EVT\_ALL

```
public static final java.lang.String EVT_ALL
```

## Constructors

### WMSLoggerIDs

```
public WMSLoggerIDs()
```

---

Package

**com.wowza.wms.media.mp3.model.idtags**

## com.wowza.wms.media.mp3.model.idtags Class ID3Frames

java.lang.Object

└--com.wowza.wms.media.mp3.model.idtags.ID3Frames

public class **ID3Frames**  
extends Object

### Field Summary

public static final	<a href="#"><u>ID3FOOTER_SIZE</u></a> Value: <b>10</b>
public static final	<a href="#"><u>ID3HEADER_SIZE</u></a> Value: <b>10</b>
public static final	<a href="#"><u>ID3HEADER_VERSION</u></a> Value: <b>1024</b>
public static final	<a href="#"><u>ID3HEADERFLAGS_DEFAULT</u></a> Value: <b>0</b>
public static final	<a href="#"><u>ID3HEADERFLAGS_EXPERIMENTAL</u></a> Value: <b>32</b>
public static final	<a href="#"><u>ID3HEADERFLAGS_EXTENDED</u></a> Value: <b>64</b>
public static final	<a href="#"><u>ID3HEADERFLAGS_FOOTERPRESENT</u></a> Value: <b>16</b>
public static final	<a href="#"><u>ID3HEADERFLAGS_UNSYNC</u></a> Value: <b>128</b>

### Constructor Summary

public	<a href="#"><u>ID3Frames</u></a> ( )
--------	--------------------------------------

### Method Summary

void	<a href="#"><u>clear</u></a> ( )
java.util.List	<a href="#"><u>getFrameMapIds</u></a> ( )

java.util.List	<a href="#">getFrames()</a>
Object	<a href="#">getLock()</a>
int	<a href="#">getSize()</a>
boolean	<a href="#">isEmpty()</a>
void	<a href="#">putFrame</a> ( <a href="#">IID3V2Frame</a> frame)
<a href="#">IID3V2Frame</a>	<a href="#">removeFrame</a> ( <a href="#">IID3V2Frame</a> frame)
byte[]	<a href="#">serialize()</a>
byte[]	<a href="#">serialize</a> (boolean includeHeader, boolean includeFooter, int flags)
static int	<a href="#">serializeFooter</a> (byte[] buffer, int offset, int flags, int size)
static int	<a href="#">serializeHeader</a> (byte[] buffer, int offset, int flags, int size)
int	<a href="#">serializeTags</a> (byte[] buffer, int offset)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### ID3HEADER\_VERSION

```
public static final int ID3HEADER_VERSION
```

Constant value: **1024**

### ID3HEADER\_SIZE

```
public static final int ID3HEADER_SIZE
```

Constant value: **10**

### ID3FOOTER\_SIZE

```
public static final int ID3FOOTER_SIZE
```

Constant value: **10**



(continued from last page)

---

## ID3HEADERFLAGS\_DEFAULT

```
public static final int ID3HEADERFLAGS_DEFAULT
```

Constant value: **0**

---

## ID3HEADERFLAGS\_UNSYNC

```
public static final int ID3HEADERFLAGS_UNSYNC
```

Constant value: **128**

---

## ID3HEADERFLAGS\_EXTENDED

```
public static final int ID3HEADERFLAGS_EXTENDED
```

Constant value: **64**

---

## ID3HEADERFLAGS\_EXPERIMENTAL

```
public static final int ID3HEADERFLAGS_EXPERIMENTAL
```

Constant value: **32**

---

## ID3HEADERFLAGS\_FOOTERPRESENT

```
public static final int ID3HEADERFLAGS_FOOTERPRESENT
```

Constant value: **16**

## Constructors

### ID3Frames

```
public ID3Frames()
```

## Methods

### getLock

```
public Object getLock()
```

---

### clear

```
public void clear()
```

---

(continued from last page)

---

## isEmpty

```
public boolean isEmpty()
```

---

## putFrame

```
public void putFrame(IID3V2Frame frame)
```

---

## removeFrame

```
public IID3V2Frame removeFrame(IID3V2Frame frame)
```

---

## getFrames

```
public java.util.List getFrames()
```

---

## getFrameMapIds

```
public java.util.List getFrameMapIds()
```

---

## getSize

```
public int getSize()
```

---

## serializeTags

```
public int serializeTags(byte[] buffer,  
    int offset)
```

---

## serializeHeader

```
public static int serializeHeader(byte[] buffer,  
    int offset,  
    int flags,  
    int size)
```

---

## serializeFooter

```
public static int serializeFooter(byte[] buffer,  
    int offset,  
    int flags,  
    int size)
```

---

(continued from last page)

---

**serialize**

```
public byte[] serialize()
```

---

**serialize**

```
public byte[] serialize(boolean includeHeader,  
                        boolean includeFooter,  
                        int flags)
```

## com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameAttachedPicture

java.lang.Object

└- [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)  
└- [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameAttachedPicture](#)

All Implemented Interfaces:

[IID3V2Frame](#)

```
public class ID3V2FrameAttachedPicture
extends ID3V2FrameBase
```

### Field Summary

public static final	<a href="#">MIMETYPES_JPEG</a> Value: <b>image/jpeg</b>
public static final	<a href="#">MIMETYPES_PNG</a> Value: <b>image/png</b>
public static final	<a href="#">MIMETYPES_URL</a> Value: <b>--&gt;</b>
public static	<a href="#">PICTUREMAXFILESIZE</a>
public static final	<a href="#">PICTURETYPE_ARTISTLOGO</a> Value: <b>19</b>
public static final	<a href="#">PICTURETYPE_COVERBACK</a> Value: <b>4</b>
public static final	<a href="#">PICTURETYPE_COVERFRONT</a> Value: <b>3</b>
public static final	<a href="#">PICTURETYPE_FILEICON</a> Value: <b>1</b>
public static final	<a href="#">PICTURETYPE_ILLUSTRATION</a> Value: <b>18</b>
public static final	<a href="#">PICTURETYPE_MOVIESCREENCAPTURE</a> Value: <b>16</b>
public static final	<a href="#">PICTURETYPE_OTHER</a> Value: <b>0</b>

public static final	<a href="#">PICTURETYPE_OTHERFILEICON</a> Value: <b>2</b>
public static final	<a href="#">PICTURETYPE_PUBLISHERLOGO</a> Value: <b>20</b>

#### Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOP](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

## Constructor Summary

public	<a href="#">ID3V2FrameAttachedPicture</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameAttachedPicture</a> ()

## Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
String	<a href="#">getDescription</a> ()
String	<a href="#">getMapIdStr</a> ()
String	<a href="#">getMimeType</a> ()
byte[]	<a href="#">getPictureData</a> ()
int	<a href="#">getPictureType</a> ()
int	<a href="#">getTextEncoding</a> ()
boolean	<a href="#">loadFile</a> (java.io.File file)
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)
void	<a href="#">setDescription</a> (String description)
void	<a href="#">setMimeType</a> (String mimeType)

void	<a href="#">setPictureData</a> (byte[] pictureData)
void	<a href="#">setPictureDataAsURL</a> (String urlStr)
void	<a href="#">setPictureType</a> (int pictureType)
void	<a href="#">setTextEncoding</a> (int textEncoding)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Fields

### PICTURETYPE\_OTHER

```
public static final int PICTURETYPE_OTHER
```

Constant value: **0**

### PICTURETYPE\_FILEICON

```
public static final int PICTURETYPE_FILEICON
```

Constant value: **1**

### PICTURETYPE\_OTHERFILEICON

```
public static final int PICTURETYPE_OTHERFILEICON
```

Constant value: **2**

### PICTURETYPE\_COVERFRONT

```
public static final int PICTURETYPE_COVERFRONT
```

Constant value: **3**

---

## PICTURETYPE\_COVERBACK

```
public static final int PICTURETYPE_COVERBACK
```

Constant value: **4**

---

## PICTURETYPE\_MOVIESCREENCAPTURE

```
public static final int PICTURETYPE_MOVIESCREENCAPTURE
```

Constant value: **16**

---

## PICTURETYPE\_ILLUSTRATION

```
public static final int PICTURETYPE_ILLUSTRATION
```

Constant value: **18**

---

## PICTURETYPE\_ARTISTLOGO

```
public static final int PICTURETYPE_ARTISTLOGO
```

Constant value: **19**

---

## PICTURETYPE\_PUBLISHERLOGO

```
public static final int PICTURETYPE_PUBLISHERLOGO
```

Constant value: **20**

---

## MIMETYPES\_JPEG

```
public static final java.lang.String MIMETYPES_JPEG
```

Constant value: **image/jpeg**

---

## MIMETYPES\_PNG

```
public static final java.lang.String MIMETYPES_PNG
```

Constant value: **image/png**

---

## MIMETYPES\_URL

```
public static final java.lang.String MIMETYPES_URL
```

Constant value: **-->**

---

(continued from last page)

## PICTUREMAXFILESIZE

```
public static long PICTUREMAXFILESIZE
```

## Constructors

### ID3V2FrameAttachedPicture

```
public ID3V2FrameAttachedPicture(String idStr,  
                                int flags)
```

### ID3V2FrameAttachedPicture

```
public ID3V2FrameAttachedPicture()
```

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,  
                        int offset)
```

### deserializeBody

```
public void deserializeBody(byte[] buffer,  
                          int offset,  
                          int len)
```

### getMapIdStr

```
public String getMapIdStr()
```

### getBodySize

```
public int getBodySize()
```

### getTextEncoding

```
public int getTextEncoding()
```



(continued from last page)

## setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

---

## getMimeType

```
public String getMimeType()
```

---

## setMimeType

```
public void setMimeType(String mimeType)
```

---

## getPictureType

```
public int getPictureType()
```

---

## setPictureType

```
public void setPictureType(int pictureType)
```

---

## getDescription

```
public String getDescription()
```

---

## setDescription

```
public void setDescription(String description)
```

---

## getPictureData

```
public byte[] getPictureData()
```

---

## setPictureData

```
public void setPictureData(byte[] pictureData)
```

---

## setPictureDataAsURL

```
public void setPictureDataAsURL(String urlStr)
```

---

(continued from last page)

---

## loadFile

```
public boolean loadFile(java.io.File file)
```

## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FrameBase

java.lang.Object

└─com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase

All Implemented Interfaces:

[IID3V2Frame](#)

Direct Known Subclasses:

[ID3V2FrameURLLink](#), [ID3V2FrameTextInformation](#), [ID3V2FrameSynchronizedText](#),  
[ID3V2FrameRecommendedBufferSize](#), [ID3V2FrameRawBytes](#), [ID3V2FramePrivate](#), [ID3V2FrameLinkedInformation](#),  
[ID3V2FrameComment](#), [ID3V2FrameAttachedPicture](#)

public abstract class **ID3V2FrameBase**

extends Object

implements [IID3V2Frame](#)

#### Field Summary

public static final	<a href="#">FLAGS_DEFAULT</a> Value: <b>0</b>
public static final	<a href="#">HEADERSIZE</a> Value: <b>10</b>
public static final	<a href="#">TAG_APIC</a> Value: <b>APIC</b>
public static final	<a href="#">TAG_COMM</a> Value: <b>COMM</b>
public static final	<a href="#">TAG_LINK</a> Value: <b>LINK</b>
public static final	<a href="#">TAG_PRIV</a> Value: <b>PRIV</b>
public static final	<a href="#">TAG_RBUF</a> Value: <b>RBUF</b>
public static final	<a href="#">TAG_SYLT</a> Value: <b>SYLT</b>
public static final	<a href="#">TAG_TALB</a> Value: <b>TALB</b>

public static final	<a href="#">TAG_TBPM</a> Value: <b>TBPM</b>
public static final	<a href="#">TAG_TCOM</a> Value: <b>TCOM</b>
public static final	<a href="#">TAG_TCON</a> Value: <b>TCON</b>
public static final	<a href="#">TAG_TCOP</a> Value: <b>TCOP</b>
public static final	<a href="#">TAG_TDEN</a> Value: <b>TDEN</b>
public static final	<a href="#">TAG_TDLY</a> Value: <b>TDLY</b>
public static final	<a href="#">TAG_TDOR</a> Value: <b>TDOR</b>
public static final	<a href="#">TAG_TDRC</a> Value: <b>TDRC</b>
public static final	<a href="#">TAG_TDRL</a> Value: <b>TDRL</b>
public static final	<a href="#">TAG_TDTG</a> Value: <b>TDTG</b>
public static final	<a href="#">TAG_TENC</a> Value: <b>TENC</b>
public static final	<a href="#">TAG_TEXT</a> Value: <b>TEXT</b>
public static final	<a href="#">TAG_TFLT</a> Value: <b>TFLT</b>
public static final	<a href="#">TAG_TIPL</a> Value: <b>TIPL</b>
public static final	<a href="#">TAG_TIT1</a> Value: <b>TIT1</b>
public static final	<a href="#">TAG_TIT2</a> Value: <b>TIT2</b>

public static final	<a href="#">TAG_TIT3</a> Value: <b>TIT3</b>
public static final	<a href="#">TAG_TKEY</a> Value: <b>TKEY</b>
public static final	<a href="#">TAG_TLAN</a> Value: <b>TLAN</b>
public static final	<a href="#">TAG_TLEN</a> Value: <b>TLEN</b>
public static final	<a href="#">TAG_TMCL</a> Value: <b>TMCL</b>
public static final	<a href="#">TAG_TMED</a> Value: <b>TMED</b>
public static final	<a href="#">TAG_TMOO</a> Value: <b>TMOO</b>
public static final	<a href="#">TAG_TOAL</a> Value: <b>TOAL</b>
public static final	<a href="#">TAG_TOFN</a> Value: <b>TOFN</b>
public static final	<a href="#">TAG_TOLY</a> Value: <b>TOLY</b>
public static final	<a href="#">TAG_TOPE</a> Value: <b>TOPE</b>
public static final	<a href="#">TAG_TOWN</a> Value: <b>TOWN</b>
public static final	<a href="#">TAG_TPE1</a> Value: <b>TPE1</b>
public static final	<a href="#">TAG_TPE2</a> Value: <b>TPE2</b>
public static final	<a href="#">TAG_TPE3</a> Value: <b>TPE3</b>
public static final	<a href="#">TAG_TPE4</a> Value: <b>TPE4</b>

public static final	<a href="#">TAG_TPOS</a> Value: <b>TPOS</b>
public static final	<a href="#">TAG_TPRO</a> Value: <b>TPRO</b>
public static final	<a href="#">TAG_TPUB</a> Value: <b>TPUB</b>
public static final	<a href="#">TAG_TRCK</a> Value: <b>TRCK</b>
public static final	<a href="#">TAG_TRSN</a> Value: <b>TRSN</b>
public static final	<a href="#">TAG_TRSO</a> Value: <b>TRSO</b>
public static final	<a href="#">TAG_TSOA</a> Value: <b>TSOA</b>
public static final	<a href="#">TAG_TSOP</a> Value: <b>TSOP</b>
public static final	<a href="#">TAG_TSOT</a> Value: <b>TSOT</b>
public static final	<a href="#">TAG_TSRC</a> Value: <b>TSRC</b>
public static final	<a href="#">TAG_TSSE</a> Value: <b>TSSE</b>
public static final	<a href="#">TAG_TSST</a> Value: <b>TSST</b>
public static final	<a href="#">TAG_TXXX</a> Value: <b>TXXX</b>
public static final	<a href="#">TAG_UNKN</a> Value: <b>UNKN</b>
public static final	<a href="#">TAG_WCOM</a> Value: <b>WCOM</b>
public static final	<a href="#">TAG_WCOP</a> Value: <b>WCOP</b>

public static final	<a href="#">TAG_WOAF</a> Value: <b>WOAF</b>
public static final	<a href="#">TAG_WOAR</a> Value: <b>WOAR</b>
public static final	<a href="#">TAG_WOAS</a> Value: <b>WOAS</b>
public static final	<a href="#">TAG_WORS</a> Value: <b>WORS</b>
public static final	<a href="#">TAG_WPAY</a> Value: <b>WPAY</b>
public static final	<a href="#">TAG_WPUB</a> Value: <b>WPUB</b>
public static final	<a href="#">TAG_WXXX</a> Value: <b>WXXX</b>
public static final	<a href="#">TAGS_TEXTINFORMATION</a>
public static final	<a href="#">TEXTENCODING_ISO_8859_1</a> Value: <b>0</b>
public static final	<a href="#">TEXTENCODING_UTF16</a> Value: <b>1</b>
public static final	<a href="#">TEXTENCODING_UTF16BE</a> Value: <b>2</b>
public static final	<a href="#">TEXTENCODING_UTF8</a> Value: <b>3</b>

## Constructor Summary

public	<a href="#">ID3V2FrameBase</a> (String idStr, int flags)
--------	--

## Method Summary

static int	<a href="#">byteStringLen</a> (String value)
static <a href="#">ID3V2FrameBase</a>	<a href="#">deserializeFrame</a> (byte[] buffer, int offset, int len)
static String	<a href="#">deserializeString</a> (byte[] buffer, int offset, int len)
int	<a href="#">getFlags</a> ()

String	<a href="#">getIdStr()</a>
String	<a href="#">getMapIdStr()</a>
int	<a href="#">getSize()</a>
int	<a href="#">serialize</a> (byte[] buffer, int offset)
static int	<a href="#">serializeString</a> (String value, byte[] buffer, int offset)
static int	<a href="#">serializeStringLen</a> (String value)
void	<a href="#">setFlags</a> (int flags)
void	<a href="#">setIdStr</a> (String idStr)
static String	<a href="#">trimTrailingZero</a> (String value)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.ID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Fields

### HEADERSIZE

```
public static final int HEADERSIZE
```

Constant value: **10**

### TEXTENCODING\_ISO\_8859\_1

```
public static final int TEXTENCODING_ISO_8859_1
```

Constant value: **0**

### TEXTENCODING\_UTF16

```
public static final int TEXTENCODING_UTF16
```

Constant value: **1**



(continued from last page)

---

## TEXTENCODING\_UTF16BE

```
public static final int TEXTENCODING_UTF16BE
```

Constant value: **2**

---

## TEXTENCODING\_UTF8

```
public static final int TEXTENCODING_UTF8
```

Constant value: **3**

---

## TAG\_UNKN

```
public static final java.lang.String TAG_UNKN
```

Constant value: **UNKN**

---

## TAG\_PRIV

```
public static final java.lang.String TAG_PRIV
```

Constant value: **PRIV**

---

## TAG\_APIC

```
public static final java.lang.String TAG_APIC
```

Constant value: **APIC**

---

## TAG\_LINK

```
public static final java.lang.String TAG_LINK
```

Constant value: **LINK**

---

## TAG\_SYLT

```
public static final java.lang.String TAG_SYLT
```

Constant value: **SYLT**

---

## TAG\_RBUF

```
public static final java.lang.String TAG_RBUF
```

Constant value: **RBUF**

---

## TAG\_TALB

```
public static final java.lang.String TAG_TALB
```

---

(continued from last page)

---

Constant value: **TALB**

---

## TAG\_TBPM

```
public static final java.lang.String TAG_TBPM
```

Constant value: **TBPM**

---

## TAG\_TCOM

```
public static final java.lang.String TAG_TCOM
```

Constant value: **TCOM**

---

## TAG\_TCON

```
public static final java.lang.String TAG_TCON
```

Constant value: **TCON**

---

## TAG\_TCOP

```
public static final java.lang.String TAG_TCOP
```

Constant value: **TCOP**

---

## TAG\_TDEN

```
public static final java.lang.String TAG_TDEN
```

Constant value: **TDEN**

---

## TAG\_TDLY

```
public static final java.lang.String TAG_TDLY
```

Constant value: **TDLY**

---

## TAG\_TDOR

```
public static final java.lang.String TAG_TDOR
```

Constant value: **TDOR**

---

## TAG\_TDRC

```
public static final java.lang.String TAG_TDRC
```

Constant value: **TDRC**

---

## TAG\_TDRL

```
public static final java.lang.String TAG_TDRL
```

Constant value: **TDRL**

---

## TAG\_TDTG

```
public static final java.lang.String TAG_TDTG
```

Constant value: **TDTG**

---

## TAG\_TENC

```
public static final java.lang.String TAG_TENC
```

Constant value: **TENC**

---

## TAG\_TEXT

```
public static final java.lang.String TAG_TEXT
```

Constant value: **TEXT**

---

## TAG\_TFLT

```
public static final java.lang.String TAG_TFLT
```

Constant value: **TFLT**

---

## TAG\_TIPL

```
public static final java.lang.String TAG_TIPL
```

Constant value: **TIPL**

---

## TAG\_TIT1

```
public static final java.lang.String TAG_TIT1
```

Constant value: **TIT1**

---

## TAG\_TIT2

```
public static final java.lang.String TAG_TIT2
```

Constant value: **TIT2**

---

(continued from last page)

---

## TAG\_TIT3

```
public static final java.lang.String TAG_TIT3
```

Constant value: **TIT3**

---

## TAG\_TKEY

```
public static final java.lang.String TAG_TKEY
```

Constant value: **TKEY**

---

## TAG\_TLAN

```
public static final java.lang.String TAG_TLAN
```

Constant value: **TLAN**

---

## TAG\_TLEN

```
public static final java.lang.String TAG_TLEN
```

Constant value: **TLEN**

---

## TAG\_TMCL

```
public static final java.lang.String TAG_TMCL
```

Constant value: **TMCL**

---

## TAG\_TMED

```
public static final java.lang.String TAG_TMED
```

Constant value: **TMED**

---

## TAG\_TMOO

```
public static final java.lang.String TAG_TMOO
```

Constant value: **TMOO**

---

## TAG\_TOAL

```
public static final java.lang.String TAG_TOAL
```

Constant value: **TOAL**

---

## TAG\_TOFN

```
public static final java.lang.String TAG_TOFN
```

---

(continued from last page)

---

Constant value: **TOFN**

---

## TAG\_TOLY

```
public static final java.lang.String TAG_TOLY
```

Constant value: **TOLY**

---

## TAG\_TOPE

```
public static final java.lang.String TAG_TOPE
```

Constant value: **TOPE**

---

## TAG\_TOWN

```
public static final java.lang.String TAG_TOWN
```

Constant value: **TOWN**

---

## TAG\_TPE1

```
public static final java.lang.String TAG_TPE1
```

Constant value: **TPE1**

---

## TAG\_TPE2

```
public static final java.lang.String TAG_TPE2
```

Constant value: **TPE2**

---

## TAG\_TPE3

```
public static final java.lang.String TAG_TPE3
```

Constant value: **TPE3**

---

## TAG\_TPE4

```
public static final java.lang.String TAG_TPE4
```

Constant value: **TPE4**

---

## TAG\_TPOS

```
public static final java.lang.String TAG_TPOS
```

Constant value: **TPOS**

---

## TAG\_TPRO

```
public static final java.lang.String TAG_TPRO
```

Constant value: **TPRO**

---

## TAG\_TPUB

```
public static final java.lang.String TAG_TPUB
```

Constant value: **TPUB**

---

## TAG\_TRCK

```
public static final java.lang.String TAG_TRCK
```

Constant value: **TRCK**

---

## TAG\_TRSN

```
public static final java.lang.String TAG_TRSN
```

Constant value: **TRSN**

---

## TAG\_TRSO

```
public static final java.lang.String TAG_TRSO
```

Constant value: **TRSO**

---

## TAG\_TSOA

```
public static final java.lang.String TAG_TSOA
```

Constant value: **TSOA**

---

## TAG\_TSOP

```
public static final java.lang.String TAG_TSOP
```

Constant value: **TSOP**

---

## TAG\_TSOT

```
public static final java.lang.String TAG_TSOT
```

Constant value: **TSOT**

---

(continued from last page)

---

## TAG\_TSRC

```
public static final java.lang.String TAG_TSRC
```

Constant value: **TSRC**

---

## TAG\_TSSE

```
public static final java.lang.String TAG_TSSE
```

Constant value: **TSSE**

---

## TAG\_TSST

```
public static final java.lang.String TAG_TSST
```

Constant value: **TSST**

---

## TAGS\_TEXTINFORMATION

```
public static final java.lang.String TAGS_TEXTINFORMATION
```

---

## TAG\_WCOM

```
public static final java.lang.String TAG_WCOM
```

Constant value: **WCOM**

---

## TAG\_WCOP

```
public static final java.lang.String TAG_WCOP
```

Constant value: **WCOP**

---

## TAG\_WOAF

```
public static final java.lang.String TAG_WOAF
```

Constant value: **WOAF**

---

## TAG\_WOAR

```
public static final java.lang.String TAG_WOAR
```

Constant value: **WOAR**

---

## TAG\_WOAS

```
public static final java.lang.String TAG_WOAS
```

(continued from last page)

Constant value: **WOAS**

---

## TAG\_WORS

```
public static final java.lang.String TAG_WORS
```

Constant value: **WORS**

---

## TAG\_WPAY

```
public static final java.lang.String TAG_WPAY
```

Constant value: **WPAY**

---

## TAG\_WPUB

```
public static final java.lang.String TAG_WPUB
```

Constant value: **WPUB**

---

## TAG\_TXXX

```
public static final java.lang.String TAG_TXXX
```

Constant value: **TXXX**

---

## TAG\_COMM

```
public static final java.lang.String TAG_COMM
```

Constant value: **COMM**

---

## TAG\_WXXX

```
public static final java.lang.String TAG_WXXX
```

Constant value: **WXXX**

---

## FLAGS\_DEFAULT

```
public static final int FLAGS_DEFAULT
```

Constant value: **0**

---

## Constructors

### ID3V2FrameBase

```
public ID3V2FrameBase(String idStr,  
                      int flags)
```



## Methods

### byteStringLen

```
public static int byteStringLen(String value)
```

### serializeStringLen

```
public static int serializeStringLen(String value)
```

### trimTrailingZero

```
public static String trimTrailingZero(String value)
```

### serializeString

```
public static int serializeString(String value,  
    byte[] buffer,  
    int offset)
```

### deserializeString

```
public static String deserializeString(byte[] buffer,  
    int offset,  
    int len)
```

### deserializeFrame

```
public static ID3V2FrameBase deserializeFrame(byte[] buffer,  
    int offset,  
    int len)
```

### serialize

```
public int serialize(byte[] buffer,  
    int offset)
```

### getIdStr

```
public String getIdStr()
```

(continued from last page)

**setIdStr**

```
public void setIdStr(String idStr)
```

---

**getFlags**

```
public int getFlags()
```

---

**setFlags**

```
public void setFlags(int flags)
```

---

**getSize**

```
public int getSize()
```

---


**getMapIdStr**

```
public String getMapIdStr()
```

---

## com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameComment

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

```

public class ID3V2FrameComment
extends ID3V2FrameBase
  
```

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOPI](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

### Constructor Summary

public	<a href="#">ID3V2FrameComment</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameComment</a> (String idStr)
public	<a href="#">ID3V2FrameComment</a> ()

### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
String	<a href="#">getDescription</a> ()
int	<a href="#">getTextEncoding</a> ()
String	<a href="#">getValue</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)

void	<a href="#"><u>setDescription</u></a> (String description)
void	<a href="#"><u>setTextEncoding</u></a> (int textEncoding)
void	<a href="#"><u>setValue</u></a> (String value)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Constructors

### ID3V2FrameComment

```
public ID3V2FrameComment(String idStr,
                          int flags)
```

### ID3V2FrameComment

```
public ID3V2FrameComment(String idStr)
```

### ID3V2FrameComment

```
public ID3V2FrameComment()
```

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,
                          int offset)
```

(continued from last page)

## deserializeBody

```
public void deserializeBody(byte[] buffer,  
    int offset,  
    int len)
```

---

## getBodySize

```
public int getBodySize()
```

---

## getValue

```
public String getValue()
```

---

## setValue

```
public void setValue(String value)
```

---

## getTextEncoding

```
public int getTextEncoding()
```

---

## setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

---

## getDescription

```
public String getDescription()
```

---

## setDescription


```
public void setDescription(String description)
```

---

## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FrameLinkedInformation

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameLinkedInformation**

extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOP](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

### Constructor Summary

public	<a href="#">ID3V2FrameLinkedInformation</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameLinkedInformation</a> ()

### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
byte[]	<a href="#">getData</a> ()
String	<a href="#">getDescription</a> ()
long	<a href="#">getFrameIdentifier</a> ()
String	<a href="#">getURL</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)

void	<a href="#"><u>setData</u></a> (byte[] data)
void	<a href="#"><u>setDescription</u></a> (String description)
void	<a href="#"><u>setFrameIdentifier</u></a> (long frameIdentifier)
void	<a href="#"><u>setURL</u></a> (String url)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Constructors

### ID3V2FrameLinkedInformation

```
public ID3V2FrameLinkedInformation(String idStr,
                                   int flags)
```

### ID3V2FrameLinkedInformation

```
public ID3V2FrameLinkedInformation()
```

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,
                          int offset)
```

### deserializeBody

```
public void deserializeBody(byte[] buffer,
                              int offset,
                              int len)
```

(continued from last page)

---

### getBodySize

```
public int getBodySize()
```

---

### getDescription

```
public String getDescription()
```

---

### setDescription

```
public void setDescription(String description)
```

---

### getFrameIdentifier

```
public long getFrameIdentifier()
```

---

### setFrameIdentifier

```
public void setFrameIdentifier(long frameIdentifier)
```

---

### getURL

```
public String getURL()
```

---

### setURL

```
public void setURL(String url)
```

---

### getData

```
public byte[] getData()
```

---

### setData


```
public void setData(byte[] data)
```



## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FramePrivate

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FramePrivate**  
 extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#),  
[TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOP](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#),  
[TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#),  
[TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#),  
[TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#),  
[TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#),  
[TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#),  
[TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#),  
[TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

### Constructor Summary

public	<a href="#">ID3V2FramePrivate</a> (String idStr, int flags)
public	<a href="#">ID3V2FramePrivate</a> ()

### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
byte[]	<a href="#">getData</a> ()
String	<a href="#">getOwnerIdentifier</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)
void	<a href="#">setData</a> (byte[] data)
void	<a href="#">setOwnerIdentifier</a> (String ownerIdentifier)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Constructors

### ID3V2FramePrivate

```
public ID3V2FramePrivate(String idStr,  
                           int flags)
```

### ID3V2FramePrivate

```
public ID3V2FramePrivate()
```

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,  
                           int offset)
```

### deserializeBody

```
public void deserializeBody(byte[] buffer,  
                              int offset,  
                              int len)
```

### getBodySize

```
public int getBodySize()
```

### getOwnerIdentifier

```
public String getOwnerIdentifier()
```

(continued from last page)

---

**setOwnerIdentifier**

```
public void setOwnerIdentifier(String ownerIdentifier)
```

---

**getData**

```
public byte[] getData()
```

---


**setData**

```
public void setData(byte[] data)
```

## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FrameRawBytes

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameRawBytes**

extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOPI](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

### Constructor Summary

public	<a href="#">ID3V2FrameRawBytes</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameRawBytes</a> (String idStr)

### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

---

## Constructors

### ID3V2FrameRawBytes

```
public ID3V2FrameRawBytes(String idStr,  
                           int flags)
```

---

### ID3V2FrameRawBytes

```
public ID3V2FrameRawBytes(String idStr)
```

---

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,  
                        int offset)
```

---

### deserializeBody

```
public void deserializeBody(byte[] buffer,  
                          int offset,  
                          int len)
```

---


### getBodySize

```
public int getBodySize()
```

---

## com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameRecommendedBufferSize

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameRecommendedBufferSize**  
extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOPI](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

### Constructor Summary

public	<a href="#">ID3V2FrameRecommendedBufferSize</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameRecommendedBufferSize</a> ()

### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
int	<a href="#">getBufferSize</a> ()
byte	<a href="#">getEmbeddedFlag</a> ()
long	<a href="#">getOffsetToNextTag</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)
void	<a href="#">setBufferSize</a> (int bufferSize)

void	<a href="#"><u>setEmbeddedFlag</u></a> (byte embeddedFlag)
void	<a href="#"><u>setOffsetToNextTag</u></a> (long offsetToNextTag)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Constructors

### ID3V2FrameRecommendedBufferSize

```
public ID3V2FrameRecommendedBufferSize(String idStr,
                                       int flags)
```

### ID3V2FrameRecommendedBufferSize

```
public ID3V2FrameRecommendedBufferSize()
```

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,
                        int offset)
```

### deserializeBody

```
public void deserializeBody(byte[] buffer,
                          int offset,
                          int len)
```

### getBodySize

```
public int getBodySize()
```

(continued from last page)

---

## getBufferSize

```
public int getBufferSize()
```

---

## setBufferSize

```
public void setBufferSize(int bufferSize)
```

---

## getEmbeddedFlag

```
public byte getEmbeddedFlag()
```

---

## setEmbeddedFlag

```
public void setEmbeddedFlag(byte embeddedFlag)
```

---

## getOffsetToNextTag

```
public long getOffsetToNextTag()
```

---

## setOffsetToNextTag

```
public void setOffsetToNextTag(long offsetToNextTag)
```



## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FrameSynchronizedText

java.lang.Object

```

  |
  +-- com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase
       |
       +-- com.wowza.wms.media.mp3.model.idtags.ID3V2FrameSynchronizedText
  
```

All Implemented Interfaces:

[IID3V2Frame](#)

```

public class ID3V2FrameSynchronizedText
extends ID3V2FrameBase
  
```

#### Field Summary

public static final	<a href="#">CONTENTTYPE_CHORD</a> Value: <b>5</b>
public static final	<a href="#">CONTENTTYPE_EVENTS</a> Value: <b>4</b>
public static final	<a href="#">CONTENTTYPE_LYRICS</a> Value: <b>1</b>
public static final	<a href="#">CONTENTTYPE_MOVEMENT</a> Value: <b>3</b>
public static final	<a href="#">CONTENTTYPE_OTHER</a> Value: <b>0</b>
public static final	<a href="#">CONTENTTYPE_TRANSCRIPTION</a> Value: <b>2</b>
public static final	<a href="#">CONTENTTYPE_TRIVIA</a> Value: <b>6</b>
public static final	<a href="#">CONTENTTYPE_URLIMAGES</a> Value: <b>8</b>
public static final	<a href="#">CONTENTTYPE_URLWEBPAGES</a> Value: <b>7</b>
public static final	<a href="#">TIMESTAMPFORMAT_MILLISECONDS</a> Value: <b>2</b>

public static final	<a href="#"><u>TIMESTAMPFORMAT_MPEG</u></a> Value: <b>1</b>
---------------------	--

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOPI](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

## Constructor Summary

public	<a href="#"><u>ID3V2FrameSynchronizedText</u></a> (String idStr, int flags)
public	<a href="#"><u>ID3V2FrameSynchronizedText</u></a> ()

## Method Summary

void	<a href="#"><u>addContentDescriptor</u></a> ( <a href="#"><u>ID3V2FrameSynchronizedTextDescriptor</u></a> contentDescriptor)
void	<a href="#"><u>addContentDescriptor</u></a> (long timecode, String value)
void	<a href="#"><u>deserializeBody</u></a> (byte[] buffer, int offset, int len)
int	<a href="#"><u>getBodySize</u></a> ()
java.util.List	<a href="#"><u>getContentDescriptors</u></a> ()
byte	<a href="#"><u>getContentType</u></a> ()
String	<a href="#"><u>getLanguage</u></a> ()
int	<a href="#"><u>getTextEncoding</u></a> ()
byte	<a href="#"><u>getTimeStampFormat</u></a> ()
int	<a href="#"><u>serializeBody</u></a> (byte[] buffer, int offset)
void	<a href="#"><u>setContentTypes</u></a> (byte contentType)
void	<a href="#"><u>setLanguage</u></a> (String language)
void	<a href="#"><u>setTextEncoding</u></a> (int textEncoding)

void	<a href="#"><u>setTimeStampFormat</u></a> (byte timeStampFormat)
------	--

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Fields

### CONTENTTYPE\_OTHER

```
public static final int CONTENTTYPE_OTHER
```

Constant value: **0**

### CONTENTTYPE\_LYRICS

```
public static final int CONTENTTYPE_LYRICS
```

Constant value: **1**

### CONTENTTYPE\_TRANSCRIPTION

```
public static final int CONTENTTYPE_TRANSCRIPTION
```

Constant value: **2**

### CONTENTTYPE\_MOVEMENT

```
public static final int CONTENTTYPE_MOVEMENT
```

Constant value: **3**

### CONTENTTYPE\_EVENTS

```
public static final int CONTENTTYPE_EVENTS
```

Constant value: **4**

(continued from last page)

---

## CONTENTTYPE\_CHORD

```
public static final int CONTENTTYPE_CHORD
```

Constant value: **5**

---

## CONTENTTYPE\_TRIVIA

```
public static final int CONTENTTYPE_TRIVIA
```

Constant value: **6**

---

## CONTENTTYPE\_URLWEBPAGES

```
public static final int CONTENTTYPE_URLWEBPAGES
```

Constant value: **7**

---

## CONTENTTYPE\_URLIMAGES

```
public static final int CONTENTTYPE_URLIMAGES
```

Constant value: **8**

---

## TIMESTAMPFORMAT\_MPEG

```
public static final int TIMESTAMPFORMAT_MPEG
```

Constant value: **1**

---

## TIMESTAMPFORMAT\_MILLISECONDS

```
public static final int TIMESTAMPFORMAT_MILLISECONDS
```

Constant value: **2**

---

## Constructors

### ID3V2FrameSynchronizedText

```
public ID3V2FrameSynchronizedText(String idStr,  
                                   int flags)
```

---

### ID3V2FrameSynchronizedText

```
public ID3V2FrameSynchronizedText()
```

---

## Methods

(continued from last page)

## serializeBody

```
public int serializeBody(byte[] buffer,  
    int offset)
```

---

## deserializeBody

```
public void deserializeBody(byte[] buffer,  
    int offset,  
    int len)
```

---

## getBodySize

```
public int getBodySize()
```

---

## getTextEncoding

```
public int getTextEncoding()
```

---

## setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

---

## getLanguage

```
public String getLanguage()
```

---

## setLanguage

```
public void setLanguage(String language)
```

---

## getTimeStampFormat

```
public byte getTimeStampFormat()
```

---

## setTimeStampFormat

```
public void setTimeStampFormat(byte timeStampFormat)
```

---

(continued from last page)

## getContentType

```
public byte getContentType()
```

---

## setContentType

```
public void setContentType(byte contentType)
```

---

## getContentDescriptors

```
public java.util.List getContentDescriptors()
```

---

## addContentDescriptor

```
public void addContentDescriptor(ID3V2FrameSynchronizedTextDescriptor  
contentDescriptor)
```

---

## addContentDescriptor

```
public void addContentDescriptor(long timecode,  
    String value)
```

---

## com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameSynchronizedTextDescriptor

java.lang.Object

└─com.wowza.wms.media.mp3.model.idtags.ID3V2FrameSynchronizedTextDescriptor

public class ID3V2FrameSynchronizedTextDescriptor  
extends Object

### Constructor Summary

public	<a href="#">ID3V2FrameSynchronizedTextDescriptor()</a>
public	<a href="#">ID3V2FrameSynchronizedTextDescriptor(long timecode, String value)</a>

### Method Summary

long	<a href="#">getTimecode()</a>
String	<a href="#">getValue()</a>
void	<a href="#">setTimecode(long timecode)</a>
void	<a href="#">setValue(String value)</a>

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### ID3V2FrameSynchronizedTextDescriptor

public ID3V2FrameSynchronizedTextDescriptor()

#### ID3V2FrameSynchronizedTextDescriptor

public ID3V2FrameSynchronizedTextDescriptor(long timecode,  
String value)

### Methods

(continued from last page)

## **getTimecode**

```
public long getTimecode()
```

---

## **setTimecode**

```
public void setTimecode(long timecode)
```

---

## **getValue**

```
public String getValue()
```

---

## **setValue**


```
public void setValue(String value)
```



## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FrameTextInformation

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameTextInformation**  
 extends [ID3V2FrameBase](#)

#### Field Summary

protected	<a href="#">addTrailingZero</a>
-----------	---------------------------------

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_T COP](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

#### Constructor Summary

public	<a href="#">ID3V2FrameTextInformation</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameTextInformation</a> (String idStr)

#### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
int	<a href="#">getTextEncoding</a> ()
String	<a href="#">getValue</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)

void	<a href="#">setTextEncoding</a> (int textEncoding)
void	<a href="#">setValue</a> (String value)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Fields

### **addTrailingZero**

protected boolean **addTrailingZero**

## Constructors

### **ID3V2FrameTextInformation**

```
public ID3V2FrameTextInformation(String idStr,  
                                int flags)
```

### **ID3V2FrameTextInformation**

```
public ID3V2FrameTextInformation(String idStr)
```

## Methods

### **serializeBody**

```
public int serializeBody(byte[] buffer,  
                        int offset)
```

(continued from last page)

## **deserializeBody**

```
public void deserializeBody(byte[] buffer,  
    int offset,  
    int len)
```

---

## **getBodySize**

```
public int getBodySize()
```

---

## **getValue**

```
public String getValue()
```

---

## **setValue**

```
public void setValue(String value)
```

---

## **getTextEncoding**

```
public int getTextEncoding()
```

---

## **setTextEncoding**


```
public void setTextEncoding(int textEncoding)
```

---

## com.wowza.wms.media.mp3.model.idtags

### Class ID3V2FrameURLLink

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameURLLink**

extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS\\_DEFAULT](#), [HEADERSIZE](#), [TAG\\_APIC](#), [TAG\\_COMM](#), [TAG\\_LINK](#), [TAG\\_PRIV](#), [TAG\\_RBUF](#), [TAG\\_SYLT](#), [TAG\\_TALB](#), [TAG\\_TBPM](#), [TAG\\_TCOM](#), [TAG\\_TCON](#), [TAG\\_TCOPI](#), [TAG\\_TDEN](#), [TAG\\_TDLY](#), [TAG\\_TDOR](#), [TAG\\_TDRC](#), [TAG\\_TDRL](#), [TAG\\_TDTG](#), [TAG\\_TENC](#), [TAG\\_TEXT](#), [TAG\\_TFLT](#), [TAG\\_TIPL](#), [TAG\\_TIT1](#), [TAG\\_TIT2](#), [TAG\\_TIT3](#), [TAG\\_TKEY](#), [TAG\\_TLAN](#), [TAG\\_TLEN](#), [TAG\\_TMCL](#), [TAG\\_TMED](#), [TAG\\_TMOO](#), [TAG\\_TOAL](#), [TAG\\_TOFN](#), [TAG\\_TOLY](#), [TAG\\_TOPE](#), [TAG\\_TOWN](#), [TAG\\_TPE1](#), [TAG\\_TPE2](#), [TAG\\_TPE3](#), [TAG\\_TPE4](#), [TAG\\_TPOS](#), [TAG\\_TPRO](#), [TAG\\_TPUB](#), [TAG\\_TRCK](#), [TAG\\_TRSN](#), [TAG\\_TRSO](#), [TAG\\_TSOA](#), [TAG\\_TSOP](#), [TAG\\_TSOT](#), [TAG\\_TSRC](#), [TAG\\_TSSE](#), [TAG\\_TSST](#), [TAG\\_TXXX](#), [TAG\\_UNKN](#), [TAG\\_WCOM](#), [TAG\\_WCOP](#), [TAG\\_WOAF](#), [TAG\\_WOAR](#), [TAG\\_WOAS](#), [TAG\\_WORS](#), [TAG\\_WPAY](#), [TAG\\_WPUB](#), [TAG\\_WXXX](#), [TAGS\\_TEXTINFORMATION](#), [TEXTENCODING\\_ISO\\_8859\\_1](#), [TEXTENCODING\\_UTF16](#), [TEXTENCODING\\_UTF16BE](#), [TEXTENCODING\\_UTF8](#)

## Constructor Summary

public	<a href="#">ID3V2FrameURLLink</a> (String idStr, int flags)
public	<a href="#">ID3V2FrameURLLink</a> (String idStr)

## Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
int	<a href="#">getTextEncoding</a> ()
String	<a href="#">getURL</a> ()
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)
void	<a href="#">setTextEncoding</a> (int textEncoding)
void	<a href="#">setURL</a> (String value)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

## Constructors

### ID3V2FrameURLLink

```
public ID3V2FrameURLLink(String idStr,
                          int flags)
```

### ID3V2FrameURLLink

```
public ID3V2FrameURLLink(String idStr)
```

## Methods

### serializeBody

```
public int serializeBody(byte[] buffer,
                          int offset)
```

### deserializeBody

```
public void deserializeBody(byte[] buffer,
                             int offset,
                             int len)
```

### getBodySize

```
public int getBodySize()
```

### getURL

```
public String getURL()
```

(continued from last page)

---

## **setURL**

```
public void setURL(String value)
```

---

## **getTextEncoding**

```
public int getTextEncoding()
```

---

## **setTextEncoding**

```
public void setTextEncoding(int textEncoding)
```

## com.wowza.wms.media.mp3.model.idtags Class ID3V2Utils

java.lang.Object

└─com.wowza.wms.media.mp3.model.idtags.ID3V2Utils

public class **ID3V2Utils**  
extends Object

### Constructor Summary

public	<a href="#">ID3V2Utils()</a>
--------	------------------------------

### Method Summary

static int	<a href="#">byteArrayToIntSafeSync</a> (byte[] b, int offset, int count)
static long	<a href="#">byteArrayToLongSafeSync</a> (byte[] b, int offset, int count)
static void	<a href="#">intToByteArraySafeSync</a> (int value, byte[] buffer, int offset, int size)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### ID3V2Utils

public **ID3V2Utils**()

### Methods

#### byteArrayToLongSafeSync

public static long **byteArrayToLongSafeSync**(byte[] b,  
int offset,  
int count)

(continued from last page)

## **byteArrayToIntSafeSync**

```
public static int byteArrayToIntSafeSync(byte[] b,  
    int offset,  
    int count)
```

---

## **intToByteArraySafeSync**

```
public static void intToByteArraySafeSync(int value,  
    byte[] buffer,  
    int offset,  
    int size)
```



## com.wowza.wms.media.mp3.model.idtags Interface IID3V2Frame

All Known Implementing Classes:  
[IID3V2FrameBase](#)

public interface **IID3V2Frame**  
extends

### Method Summary

void	<a href="#">deserializeBody</a> (byte[] buffer, int offset, int len)
int	<a href="#">getBodySize</a> ()
int	<a href="#">getFlags</a> ()
String	<a href="#">getIdStr</a> ()
String	<a href="#">getMapIdStr</a> ()
int	<a href="#">getSize</a> ()
int	<a href="#">serialize</a> (byte[] buffer, int offset)
int	<a href="#">serializeBody</a> (byte[] buffer, int offset)
void	<a href="#">setFlags</a> (int flags)
void	<a href="#">setIdStr</a> (String idStr)

### Methods

#### getIdStr

public String **getIdStr**()

#### setIdStr

public void **setIdStr**(String idStr)

(continued from last page)

---

## getMapIdStr

```
public String getMapIdStr()
```

---

## getFlags

```
public int getFlags()
```

---

## setFlags

```
public void setFlags(int flags)
```

---

## getSize

```
public int getSize()
```

---

## getBodySize

```
public int getBodySize()
```

---

## deserializeBody

```
public void deserializeBody(byte[] buffer,  
                             int offset,  
                             int len)
```

---

## serializeBody

```
public int serializeBody(byte[] buffer,  
                          int offset)
```

---

## serialize

```
public int serialize(byte[] buffer,  
                    int offset)
```

---

---

Package

**com.wowza.wms.mediacaster**

## com.wowza.wms.mediacaster Interface IMediaCaster

public interface **IMediaCaster**  
extends

### Field Summary

public static final	<a href="#"><u>MEDIACASTERTYPE_LIVEREPEATER</u></a> Value: <b>1</b>
public static final	<a href="#"><u>MEDIACASTERTYPE_RTPLIVE</u></a> Value: <b>3</b>
public static final	<a href="#"><u>MEDIACASTERTYPE_SHOUTCAST</u></a> Value: <b>2</b>
public static final	<a href="#"><u>MEDIACASTERTYPE_UNKNOWN</u></a> Value: <b>0</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_GOOD</u></a> Value: <b>100</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_MISSING</u></a> Value: <b>101</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_NORTSPSESSION</u></a> Value: <b>6</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_NOSESSION</u></a> Value: <b>2</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_NOSTREAM</u></a> Value: <b>4</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_NOTIMEOUT</u></a> Value: <b>1</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_NOURL</u></a> Value: <b>3</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_RECONNECTRUNNING</u></a> Value: <b>5</b>
public static final	<a href="#"><u>STREAMTIMEOUTREASON_UNKNOWN</u></a> Value: <b>0</b>

## Method Summary

boolean	<a href="#"><u>doWatchdog</u></a> ( ) Idle processor
void	<a href="#"><u>forceReset</u></a> ( ) Force a reset/reconnect of this media caster
<a href="#"><u>IApplicationInstance</u></a>	<a href="#"><u>getAppInstance</u></a> ( ) Get the application instance this media caster is associated with
long	<a href="#"><u>getConnectLastAttempt</u></a> ( ) Get system time in milliseconds of last connection attempt
long	<a href="#"><u>getConnectLastForceReset</u></a> ( ) Get system time in milliseconds of last time forceReset was called
long	<a href="#"><u>getConnectLastSuccess</u></a> ( ) Get system time in milliseconds of last connection success
int	<a href="#"><u>getIdleTimeout</u></a> ( ) Get the idle timeout for this media caster (milliseconds)
Object	<a href="#"><u>getLock</u></a> ( ) Get the MediaCaster lock for an individual MediaCaster item.
<a href="#"><u>MediaCasterItem</u></a>	<a href="#"><u>getMediaCasterDef</u></a> ( ) Get the media caster definition
String	<a href="#"><u>getMediaCasterId</u></a> ( ) Get the media caster id
<a href="#"><u>MediaCasterStreamItem</u></a>	<a href="#"><u>getMediaCasterStreamItem</u></a> ( ) Get the media caster item associated with this media caster
int	<a href="#"><u>getMediaCasterType</u></a> ( ) Get the media caster type.
int	<a href="#"><u>getReconnectWaitTime</u></a> ( ) Get the minimum time between reconnect attempts (milliseconds)
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream</u></a> ( ) Get the underlying stream being used by this media caster
long	<a href="#"><u>getStreamLastSeq</u></a> ( ) Get the AMFPacket sequence number of last watchdog processed packet
long	<a href="#"><u>getStreamMissingTime</u></a> ( ) Get the time in milliseconds the stream has been missing
int	<a href="#"><u>getStreamTimeout</u></a> ( ) Get the watchdog stream timeout (milliseconds)
long	<a href="#"><u>getStreamTimeoutLastReset</u></a> ( ) Get system time in milliseconds of last time stream was reset due to stream timeout (debug)
long	<a href="#"><u>getStreamTimeoutLastTime</u></a> ( ) Get system time in milliseconds of last time stream was considered in missing state (debug)

int	<a href="#"><u>getStreamTimeoutReason()</u></a> Get the reason the stream is in timeout condition (debug)
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost()</u></a> Get the virtual host associated with this media caster
void	<a href="#"><u>init(MediaCasterStreamItem mediaCasterStreamItem, MediaCasterItem mediaCasterDef, IApplicationInstance appInstance, String mediaCasterId, String streamExt)</u></a> Initialize the media caster
boolean	<a href="#"><u>isSession()</u></a> Is there current a session attached to this MediaCaster
boolean	<a href="#"><u>isStream()</u></a> Is there a stream associated with this MediaCaster
boolean	<a href="#"><u>isStreamIsRunning()</u></a> Return true if stream is currently running
void	<a href="#"><u>registerPlayer(IMediaStreamPlay player)</u></a> Register a player with this media caster
void	<a href="#"><u>sessionClosed(org.apache.mina.common.IoSession session)</u></a> sessionClosed callback
void	<a href="#"><u>sessionOpened(org.apache.mina.common.IoSession session)</u></a> sessionOpened callback
void	<a href="#"><u>setAppInstance(IApplicationInstance appInstance)</u></a> Set the application instance this media caster is assoicated with
void	<a href="#"><u>setMediaCasterDef(MediaCasterItem mediaCasterDef)</u></a> Set the media caster definition
void	<a href="#"><u>setMediaCasterId(String mediaCasterId)</u></a> Get the media caster id
void	<a href="#"><u>setMediaCasterType(int mediaCasterType)</u></a> Set the media caster type.
void	<a href="#"><u>setReconnectWaitTime(int reconnectWaitTime)</u></a> Set the minimum time between reconnect attempts (milliseconds)
void	<a href="#"><u>setStream(IMediaStream stream)</u></a> Set the underlying stream being used by this media caster
void	<a href="#"><u>setStreamRunning(boolean streamRunning)</u></a> Called internally to track when streams are running or are stopped.
void	<a href="#"><u>setStreamTimeout(int streamTimeout)</u></a> Set the watchdog stream timeout (milliseconds)
void	<a href="#"><u>shutdown(boolean isAppInstanceShutdown)</u></a> Shutdown media caster
void	<a href="#"><u>unregisterPlayer(IMediaStreamPlay player)</u></a> Unregister a player with this media caster

## Fields

### STREAMTIMEOUTREASON\_UNKNOWN

```
public static final int STREAMTIMEOUTREASON_UNKNOWN
```

Constant value: **0**

### STREAMTIMEOUTREASON\_NOTIMEOUT

```
public static final int STREAMTIMEOUTREASON_NOTIMEOUT
```

Constant value: **1**

### STREAMTIMEOUTREASON\_NOSESSION

```
public static final int STREAMTIMEOUTREASON_NOSESSION
```

Constant value: **2**

### STREAMTIMEOUTREASON\_NOURL

```
public static final int STREAMTIMEOUTREASON_NOURL
```

Constant value: **3**

### STREAMTIMEOUTREASON\_NOSTREAM

```
public static final int STREAMTIMEOUTREASON_NOSTREAM
```

Constant value: **4**

### STREAMTIMEOUTREASON\_RECONNECTRUNNING

```
public static final int STREAMTIMEOUTREASON_RECONNECTRUNNING
```

Constant value: **5**

### STREAMTIMEOUTREASON\_NORTSPSESSION

```
public static final int STREAMTIMEOUTREASON_NORTSPSESSION
```

Constant value: **6**

### STREAMTIMEOUTREASON\_GOOD

```
public static final int STREAMTIMEOUTREASON_GOOD
```

Constant value: **100**

---

## STREAMTIMEOUTREASON\_MISSING

```
public static final int STREAMTIMEOUTREASON_MISSING
```

Constant value: **101**

---

## MEDIACASTERTYPE\_UNKNOWN

```
public static final int MEDIACASTERTYPE_UNKNOWN
```

Constant value: **0**

---

## MEDIACASTERTYPE\_LIVEREPEATER

```
public static final int MEDIACASTERTYPE_LIVEREPEATER
```

Constant value: **1**

---

## MEDIACASTERTYPE\_SHOUTCAST

```
public static final int MEDIACASTERTYPE_SHOUTCAST
```

Constant value: **2**

---

## MEDIACASTERTYPE\_RTPLIVE

```
public static final int MEDIACASTERTYPE_RTPLIVE
```

Constant value: **3**

---

## Methods

### init

```
public void init(MediaCasterStreamItem mediaCasterStreamItem,  
    MediaCasterItem mediaCasterDef,  
    IApplicationInstance appInstance,  
    String mediaCasterId,  
    String streamExt)
```

Initialize the media caster

#### Parameters:

[mediaCasterStreamItem](#) - media caster item  
[mediaCasterDef](#) - media caster definition  
[appInstance](#) - application instance  
[mediaCasterId](#) - media caster id  
[streamExt](#) - stream ext or prefix

---

### getVHost

```
public IVHost getVHost()
```

Get the virtual host associated with this media caster

---



(continued from last page)

**Returns:**

virtual host associated with this media caster

---

**getMediaCasterId**

```
public String getMediaCasterId()
```

Get the media caster id

**Returns:**

media caster id

---

**setMediaCasterId**

```
public void setMediaCasterId(String mediaCasterId)
```

Get the media caster id

**Parameters:**

mediaCasterId - media caster id

---

**getStream**

```
public IMediaStream getStream()
```

Get the underlying stream being used by this media caster

**Returns:**

underlying stream being used by this media caster

---

**setStream**

```
public void setStream(IMediaStream stream)
```

Set the underlying stream being used by this media caster

**Parameters:**

stream - underlying stream being used by this media caster

---

**getAppInstance**

```
public IApplicationInstance getAppInstance()
```

Get the application instance this media caster is associated with

**Returns:**

application instance this media caster is associated with

---

**setAppInstance**

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set the application instance this media caster is associated with

**Parameters:**

appInstance - application instance this media caster is associated with

## getMediaCasterDef

```
public MediaCasterItem getMediaCasterDef()
```

Get the media caster definition

**Returns:**

media caster definition

---

## setMediaCasterDef

```
public void setMediaCasterDef(MediaCasterItem mediaCasterDef)
```

Set the media caster definition

**Parameters:**

mediaCasterDef - media caster definition

---

## shutdown

```
public void shutdown(boolean isAppInstanceShutdown)
```

Shutdown media caster

**Parameters:**

isAppInstanceShutdown - is server shutdown

---

## registerPlayer

```
public void registerPlayer(IMediaStreamPlay player)
```

Register a player with this media caster

**Parameters:**

player - player to register

---

## unregisterPlayer

```
public void unregisterPlayer(IMediaStreamPlay player)
```

Unregister a player with this media caster

**Parameters:**

player - player to unregister

---

## getIdleTimeout

```
public int getIdleTimeout()
```

Get the idle timeout for this media caster (milliseconds)

**Returns:**

idle timeout for this media caster (milliseconds)

---

## sessionOpened

```
public void sessionOpened(org.apache.mina.common.Session session)
```

---

(continued from last page)

sessionOpened callback

**Parameters:**

session - IO Session

---

## sessionClosed

```
public void sessionClosed(org.apache.mina.common.Session session)
```

sessionClosed callback

**Parameters:**

session - IO Session

---

## getMediaCasterStreamItem

```
public MediaCasterStreamItem getMediaCasterStreamItem()
```

Get the media caster item associated with this media caster

**Returns:**

media caster item associated with this media caster

---

## forceReset

```
public void forceReset()
```

Force a reset/reconnect of this media caster

---

## doWatchdog

```
public boolean doWatchdog()
```

Idle processor

**Returns:**

return true if media caster unloaded due to idle event

---

## getStreamTimeout

```
public int getStreamTimeout()
```

Get the watchdog stream timeout (milliseconds)

**Returns:**

stream timeout

---

## setStreamTimeout

```
public void setStreamTimeout(int streamTimeout)
```

Set the watchdog stream timeout (milliseconds)

**Parameters:**

streamTimeout - stream timeout

(continued from last page)

## getStreamMissingTime

```
public long getStreamMissingTime()
```

Get the time in milliseconds the stream has been missing

**Returns:**

time in milliseconds the stream has been missing

---

## getStreamLastSeq

```
public long getStreamLastSeq()
```

Get the AMFPacket sequence number of last watchdog processed packet

**Returns:**

AMFPacket sequence number

---

## getStreamTimeoutReason

```
public int getStreamTimeoutReason()
```

Get the reason the stream is in timeout condition (debug)

**Returns:**

reason the stream is in timeout condition (debug)

---

## getStreamTimeoutLastTime

```
public long getStreamTimeoutLastTime()
```

Get system time in milliseconds of last time stream was considered in missing state (debug)

**Returns:**

time in milliseconds of last time stream was considered in missing

---

## getStreamTimeoutLastReset

```
public long getStreamTimeoutLastReset()
```

Get system time in milliseconds of last time stream was reset due to stream timeout (debug)

**Returns:**

time in milliseconds of last time stream was reset

---

## isSession

```
public boolean isSession()
```

Is there current a session attached to this MediaCaster

**Returns:**

true is MediaCaster has session

---

## isStream

```
public boolean isStream()
```

---

(continued from last page)

Is there a stream associated with this MediaCaster

**Returns:**

true if stream associated with this MediaCaster

---

## getConnectLastAttempt

```
public long getConnectLastAttempt()
```

Get system time in milliseconds of last connection attempt

**Returns:**

system time in milliseconds of last connection attempt

---

## getConnectLastSuccess

```
public long getConnectLastSuccess()
```

Get system time in milliseconds of last connection success

**Returns:**

system time in milliseconds of last connection success

---

## getConnectLastForceReset

```
public long getConnectLastForceReset()
```

Get system time in milliseconds of last time forceReset was called

**Returns:**

system time in milliseconds of last time forceReset was called

---

## isStreamIsRunning

```
public boolean isStreamIsRunning()
```

Return true if stream is currently running

**Returns:**

true if stream is currently running

---

## getReconnectWaitTime

```
public int getReconnectWaitTime()
```

Get the minimum time between reconnect attempts (milliseconds)

**Returns:**

minimum time between reconnect attempts (milliseconds)

---

## setReconnectWaitTime

```
public void setReconnectWaitTime(int reconnectWaitTime)
```

Set the minimum time between reconnect attempts (milliseconds)

**Parameters:**

reconnectWaitTime - minimum time between reconnect attempts (milliseconds)

## getMediaCasterType

```
public int getMediaCasterType()
```

Get the media caster type. See IMediaCaster.MEDIACASTERTYPE\_\*

**Returns:**

media caster type

---

## setMediaCasterType

```
public void setMediaCasterType(int mediaCasterType)
```

Set the media caster type. See IMediaCaster.MEDIACASTERTYPE\_\*

**Parameters:**

mediaCasterType - media caster type

---

## getLock

```
public Object getLock()
```

Get the MediaCaster lock for an individual MediaCaster item.

---

## setStreamRunning

```
public void setStreamRunning(boolean streamRunning)
```

Called internally to track when streams are running or are stopped.

**Parameters:**

streamRunning - set to true if stream is running

---

---

## com.wowza.wms.mediacaster Interface IMediaCasterDataReceiver

---

public interface **IMediaCasterDataReceiver**  
extends

IMediaCasterDataReceiver: For internal use only.

---

### Method Summary

void	<a href="#">onData</a> (org.apache.mina.common.ByteBuffer data) Data callback
------	--

---

### Methods

#### **onData**

public void **onData**(org.apache.mina.common.ByteBuffer data)

Data callback

**Parameters:**

data - data

---

## com.wowza.wms.mediacaster Interface IMediaCasterNetConnection

---

public interface **IMediaCasterNetConnection**  
extends

IMediaCasterNetConnection: Internal use only

---

### Method Summary

com.wowza.wms.netconnection.NetConnection	<a href="#">getNetConnection()</a> Receives the INetConnection interface for a live repeater connection
---	--

---

### Methods

#### getNetConnection

public com.wowza.wms.netconnection.NetConnection **getNetConnection()**

Receives the INetConnection interface for a live repeater connection

**Returns:**

INetConnection interface



## com.wowza.wms.mediacaster Interface IMediaCasterNotify

All Subinterfaces:

[IMediaCasterNotify2](#)

public interface **IMediaCasterNotify**  
extends

IMediaCasterNotify: listener interface to MediaCaster system. See IApplicationInstance.addMediaCasterListener().

### Method Summary

void	<a href="#">onMediaCasterCreate</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when mediaCaster created
void	<a href="#">onMediaCasterDestroy</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when MediaCaster destroyed
void	<a href="#">onRegisterPlayer</a> ( <a href="#">IMediaCaster</a> mediaCaster, <a href="#">IMediaStreamPlay</a> player) Invoked when a player is added to this mediaCaster
void	<a href="#">onSetSourceStream</a> ( <a href="#">IMediaCaster</a> mediaCaster, <a href="#">IMediaStream</a> stream) Invoked when soure stream is set (can be called with stream of null)
void	<a href="#">onUnRegisterPlayer</a> ( <a href="#">IMediaCaster</a> mediaCaster, <a href="#">IMediaStreamPlay</a> player) Invoked when a player is removed from this mediaCaster

### Methods

#### onMediaCasterCreate

public void **onMediaCasterCreate**([IMediaCaster](#) mediaCaster)

Invoked when mediaCaster created

**Parameters:**

mediaCaster

#### onMediaCasterDestroy

public void **onMediaCasterDestroy**([IMediaCaster](#) mediaCaster)

Invoked when MediaCaster destroyed

**Parameters:**

mediaCaster

#### onRegisterPlayer

public void **onRegisterPlayer**([IMediaCaster](#) mediaCaster,  
[IMediaStreamPlay](#) player)

(continued from last page)

Invoked when a player is added to this mediaCaster

**Parameters:**

mediaCaster  
player

---

## onUnRegisterPlayer

```
public void onUnRegisterPlayer(IMediaCaster mediaCaster,  
    IMediaStreamPlay player)
```

Invoked when a player is removed from this mediaCaster

**Parameters:**

mediaCaster  
player

---

## onSetSourceStream

```
public void onSetSourceStream(IMediaCaster mediaCaster,  
    IMediaStream stream)
```

Invoked when source stream is set (can be called with stream of null)

**Parameters:**

mediaCaster  
stream

## com.wowza.wms.mediacaster Interface IMediaCasterNotify2

All Superinterfaces:

[IMediaCasterNotify](#)

public interface **IMediaCasterNotify2**

extends [IMediaCasterNotify](#)

### Method Summary

void	<a href="#">onConnectFailure</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when a connection or reconnection attempt fails
void	<a href="#">onConnectStart</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when a connection or reconnection attempt is invoked
void	<a href="#">onConnectSuccess</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when a connection or reconnection attempt is successful
void	<a href="#">onStreamStart</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when the stream starts receiving media data from the media source.
void	<a href="#">onStreamStop</a> ( <a href="#">IMediaCaster</a> mediaCaster) Invoked when the stream stops receiving media data from the media source after the streamTimeout value has passed.

Methods inherited from interface [com.wowza.wms.mediacaster.IMediaCasterNotify](#)

[onMediaCasterCreate](#), [onMediaCasterDestroy](#), [onRegisterPlayer](#), [onSetSourceStream](#), [onUnRegisterPlayer](#)

### Methods

#### onConnectStart

public void **onConnectStart**([IMediaCaster](#) mediaCaster)

Invoked when a connection or reconnection attempt is invoked

**Parameters:**

mediaCaster

#### onConnectSuccess

public void **onConnectSuccess**([IMediaCaster](#) mediaCaster)

Invoked when a connection or reconnection attempt is successful

**Parameters:**

mediaCaster

## onConnectFailure

```
public void onConnectFailure(IMediaCaster mediaCaster)
```

Invoked when a connection or reconnection attempt fails

**Parameters:**

mediaCaster

---

## onStreamStart

```
public void onStreamStart(IMediaCaster mediaCaster)
```

Invoked when the stream starts receiving media data from the media source. This event will only be thrown if the MediaCaster property streamTimeout is set to a non-zero value. NOTE: This is not implemented yet (coming soon)

**Parameters:**

mediaCaster

---

## onStreamStop

```
public void onStreamStop(IMediaCaster mediaCaster)
```

Invoked when the stream stops receiving media data from the media source after the streamTimeout value has passed. This event will only be thrown if the MediaCaster property streamTimeout is set to a non-zero value. NOTE: This is not implemented yet (coming soon)

**Parameters:**

mediaCaster

---

## com.wowza.wms.mediacaster Interface IMediaCasterValidateMediaCaster

All Known Implementing Classes:

[ModuleMediaCasterStreamMonitorAdvanced](#)

public interface **IMediaCasterValidateMediaCaster**  
extends

IMediaCasterValidateMediaCaster: interface for implementing stream validators. See  
`IApplicationInstance.setMediaCasterValidator(IMediaCasterValidateMediaCaster mediaCasterValidator)`

### Method Summary

boolean	<a href="#">onResetMediaCaster</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaCaster</a> mediaCaster) Called when media caster is reset
boolean	<a href="#">onValidateMediaCaster</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaCaster</a> mediaCaster) Called for each media caster to validate the media caster.
void	<a href="#">onValidateMediaCastersStart</a> ( <a href="#">IApplicationInstance</a> appInstance) Called when validation for all streams of an application instance is starting
void	<a href="#">onValidateMediaCastersStop</a> ( <a href="#">IApplicationInstance</a> appInstance) Called when validation for all streams of an application instance is done

### Methods

#### onValidateMediaCastersStart

public void **onValidateMediaCastersStart**([IApplicationInstance](#) appInstance)

Called when validation for all streams of an application instance is starting

**Parameters:**

appInstance - application instance

#### onValidateMediaCastersStop

public void **onValidateMediaCastersStop**([IApplicationInstance](#) appInstance)

Called when validation for all streams of an application instance is done

**Parameters:**

appInstance

#### onValidateMediaCaster

public boolean **onValidateMediaCaster**([IApplicationInstance](#) appInstance, [IMediaCaster](#) mediaCaster)

(continued from last page)

Called for each media caster to validate the media caster. Return true if valid.

**Parameters:**

appInstance - application instance  
mediaCaster - media caster

**Returns:**

true, if valid

---

## onResetMediaCaster

```
public boolean onResetMediaCaster(IApplicationInstance appInstance,  
    IMediaCaster mediaCaster)
```

Called when media caster is reset

**Parameters:**

appInstance - application instance  
mediaCaster - media caster

**Returns:**

return true

## com.wowza.wms.mediacaster

### Class MediaCasterItem

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterItem

public class **MediaCasterItem**  
extends Object

#### Constructor Summary

public	<a href="#">MediaCasterItem</a> (String name, String streamType, String baseClass) Media caster item constructor
--------	---

#### Method Summary

void	<a href="#">clearProperty</a> (String name) Clear property
String	<a href="#">getBaseClass</a> () Get base class
int	<a href="#">getConnectionTimeout</a> () Get connection timeout (milliseconds)
String	<a href="#">getDescription</a> () Get description
static String	<a href="#">getIdString</a> (String name, String liveStreamPacketizer, String liveStreamRepeater) Get id string for this media caster item (not used - returns name unchanged)
int	<a href="#">getKeepAliveTime</a> () Get keep alive time (milliseconds)
String	<a href="#">getName</a> () Get name
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> () Get properties collection
String	<a href="#">getProperty</a> (String name) Get property value
String	<a href="#">getStreamType</a> () Get the stream type
String	<a href="#">idStringToName</a> (String idString) Convert name to id string (not used - returns id string unchanged)
static MediaCasterStreamId	<a href="#">parseIdString</a> (String idString)

void	<a href="#"><code>setBaseClass</code></a> (String baseClass) Set base class
void	<a href="#"><code>setConnectionTimeout</code></a> (int connectionTimeout) Set connection timeout (milliseconds)
void	<a href="#"><code>setDescription</code></a> (String description) Set description
void	<a href="#"><code>setKeepAliveTime</code></a> (int keepAliveTime) Set keep alive time (milliseconds)
void	<a href="#"><code>setName</code></a> (String name) Set name
void	<a href="#"><code>setProperty</code></a> (String name, String value) Set a property
void	<a href="#"><code>setStreamType</code></a> (String streamType) Set stream type
String	<a href="#"><code>toString</code></a> () toString

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### MediaCasterItem

```
public MediaCasterItem(String name,
                      String streamType,
                      String baseClass)
```

Media caster item constructor

#### Parameters:

name - media caster name  
streamType - stream type  
baseClass - base class

## Methods

### getStreamType

```
public String getStreamType()
```

Get the stream type

#### Returns:

stream type



(continued from last page)

## setStreamType

```
public void setStreamType(String streamType)
```

Set stream type

**Parameters:**

streamType - stream type

---

## getName

```
public String getName()
```

Get name

**Returns:**

name

---

## setName

```
public void setName(String name)
```

Set name

**Parameters:**

name - name

---

## setProperty

```
public void setProperty(String name,  
                        String value)
```

Set a property

**Parameters:**

name - name

value - value

---

## clearProperty

```
public void clearProperty(String name)
```

Clear property

**Parameters:**

name - name

---

## getProperty

```
public String getProperty(String name)
```

Get property value

**Parameters:**

name - name

**Returns:**

property value

---

## getProperties

```
public WMSProperties getProperties()
```

Get properties collection

**Returns:**  
properties collection

---

## getDescription

```
public String getDescription()
```

Get description

**Returns:**  
description

---

## setDescription

```
public void setDescription(String description)
```

Set description

**Parameters:**  
description - description

---

## getBaseClass

```
public String getBaseClass()
```

Get base class

**Returns:**  
base class

---

## setBaseClass

```
public void setBaseClass(String baseClass)
```

Set base class

**Parameters:**  
baseClass - base class

---

## getConnectionTimeout

```
public int getConnectionTimeout()
```

Get connection timeout (milliseconds)

**Returns:**  
connection timeout (milliseconds)

---

## setConnectionTimeout

```
public void setConnectionTimeout(int connectionTimeout)
```

---

(continued from last page)

Set connection timeout (milliseconds)

**Parameters:**

connectionTimeout - connection timeout (milliseconds)

---

## getKeepAliveTime

```
public int getKeepAliveTime()
```

Get keep alive time (milliseconds)

**Returns:**

keep alive time (milliseconds)

---

## setKeepAliveTime

```
public void setKeepAliveTime(int keepAliveTime)
```

Set keep alive time (milliseconds)

**Parameters:**

keepAliveTime - keep alive time (milliseconds)

---

## getIdString

```
public static String getIdString(String name,  
    String liveStreamPacketizer,  
    String liveStreamRepeater)
```

Get id string for this media caster item (not used - returns name unchanged)

**Parameters:**

name - name

**Returns:**

id string for this media caster item

---

## parseIdString

```
public static MediaCasterStreamId parseIdString(String idString)
```

---

## idStringToName

```
public String idStringToName(String idString)
```

Convert name to id string (not used - returns id string unchanged)

**Parameters:**

idString - id string

**Returns:**

name

---

## toString

```
public String toString()
```

(continued from last page)

toString

## com.wowza.wms.mediacaster Class MediaCasterList

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterList

public class **MediaCasterList**  
extends Object

### Constructor Summary

public	<a href="#"><u>MediaCasterList()</u></a> Constructor
--------	---

### Method Summary

<a href="#"><u>MediaCasterItem</u></a>	<a href="#"><u>getMediaCasterDef()</u></a> (String name) Get media caster definition by name
java.util.Map	<a href="#"><u>getMediaCasterDefs()</u></a> Get map of media caster items
java.util.List	<a href="#"><u>getMediaCasterNames()</u></a> Get list of media caster names

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### MediaCasterList

public **MediaCasterList()**

Constructor

### Methods

#### getMediaCasterDefs

public java.util.Map **getMediaCasterDefs()**

Get map of media caster items

##### Returns:

map of media caster items

(continued from last page)

## getMediaCasterNames

```
public java.util.List getMediaCasterNames()
```

Get list of media caster names

**Returns:**

list of media caster names

---

## getMediaCasterDef

```
public MediaCasterItem getMediaCasterDef(String name)
```

Get media caster definition by name

**Parameters:**

name - name

**Returns:**

media caster definition

---

com.wowza.wms.mediacaster

# Class MediaCasterSettings



public class **MediaCasterSettings**  
extends Object

## Constructor Summary

public	<a href="#">MediaCasterSettings()</a>
--------	---------------------------------------

## Method Summary

HostPortConfig	<a href="#">getMediaCasterHostPortConfig()</a> Get media caster host port config
int	<a href="#">getMediaCasterProcessorCount()</a> Get the thread count use for this host port
void	<a href="#">setMediaCasterHostPortConfig</a> (HostPortConfig mediaCasterHostPortConfig) Set media caster host port config
void	<a href="#">setMediaCasterProcessorCount</a> (int mediaCasterProcessorCount) Set the thread count for this processor

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

**MediaCasterSettings**  
public **MediaCasterSettings()**

## Methods

**getMediaCasterHostPortConfig**  
public HostPortConfig **getMediaCasterHostPortConfig()**  
  
Get media caster host port config  
  
**Returns:**  
host port config

---

## setMediaCasterHostPortConfig

```
public void setMediaCasterHostPortConfig(HostPortConfig mediaCasterHostPortConfig)
```

Set media caster host port config

**Parameters:**

mediaCasterHostPortConfig

---

## getMediaCasterProcessorCount

```
public int getMediaCasterProcessorCount()
```

Get the thread count use for this host port

**Returns:**

thread count use for this host port

---

## setMediaCasterProcessorCount

```
public void setMediaCasterProcessorCount(int mediaCasterProcessorCount)
```

Set the thread count for this processor

**Parameters:**

mediaCasterProcessorCount - thread count use for this host port

---



## com.wowza.wms.mediacaster Class MediaCasterStreamItem

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterStreamItem

public class **MediaCasterStreamItem**  
extends Object

### Constructor Summary

public	<a href="#">MediaCasterStreamItem</a> (long uniqueId) Media caster item constructor
--------	--

### Method Summary

void	<a href="#">acquire</a> () Increment acquire lock count for this media caster item
void	<a href="#">acquireAndRelease</a> () Increment then decrement acquire lock count for this media caster item
boolean	<a href="#">doWatchdog</a> () Do idle processing
String	<a href="#">getLiveStreamPacketizer</a> () Get the live stream packetizer for this media caster stream item
String	<a href="#">getLiveStreamRepeater</a> () Get the live stream repeater for this media caster stream item
Object	<a href="#">getLock</a> ()
int	<a href="#">getLockCount</a> () Get the current number of acquire locks on this media caster item
<a href="#">IMediaCaster</a>	<a href="#">getMediaCaster</a> () Get the underlying IMediaCaster interface for this MediaCaster
String	<a href="#">getMediaCasterId</a> () Get this media caster item id
int	<a href="#">getPlayerCount</a> () Get the current number of players associated with this media caster item
String	<a href="#">getStreamExt</a> ()
long	<a href="#">getUniqueId</a> ()

void	<a href="#"><code>init</code></a> (String mediaCasterId, String streamExt, <a href="#"><code>MediaCasterItem</code></a> mediaCasterDef, <a href="#"><code>MediaCasterStreamMap</code></a> parent, String liveStreamPacketizer, String liveStreamRepeater) Initialize the media caster item (internal use)
boolean	<a href="#"><code>isShutdownOnRelease</code></a> ( ) On last release shutdown the stream even if clients are connected
boolean	<a href="#"><code>isValid</code></a> ( )
void	<a href="#"><code>registerPlayer</code></a> ( <a href="#"><code>IMediaStreamPlay</code></a> player) Register a player with a media caster item (internal use)
void	<a href="#"><code>release</code></a> ( ) Decrement acquire lock count for this media caster item
void	<a href="#"><code>reset</code></a> ( ) Force a reconnect or reset for this media caster item
void	<a href="#"><code>setLiveStreamPacketizer</code></a> (String liveStreamPacketizer) Set the live stream packetizer for this media caster stream item
void	<a href="#"><code>setLiveStreamRepeater</code></a> (String liveStreamRepeater) Set the live stream repeater for this media caster stream item
void	<a href="#"><code>setShutdownOnRelease</code></a> (boolean shutdownOnRelease) On last release shutdown the stream even if clients are connected
void	<a href="#"><code>setStreamExt</code></a> (String streamExt)
void	<a href="#"><code>setValid</code></a> (boolean isValid)
void	<a href="#"><code>shutdown</code></a> (boolean isAppInstanceShutdown) Shutdown this media caster item
void	<a href="#"><code>unregisterPlayer</code></a> ( <a href="#"><code>IMediaStreamPlay</code></a> player) Unregister a player with a media caster item (internal use)

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### MediaCasterStreamItem

```
public MediaCasterStreamItem(long uniqueId)
```

Media caster item constructor

## Methods

(continued from last page)

---

## getLock

```
public Object getLock()
```

---

## getUniqueId

```
public long getUniqueId()
```

---

## isValid

```
public boolean isValid()
```

---

## setValid

```
public void setValid(boolean isValid)
```

---

## init

```
public void init(String mediaCasterId,  
                String streamExt,  
                MediaCasterItem mediaCasterDef,  
                MediaCasterStreamMap parent,  
                String liveStreamPacketizer,  
                String liveStreamRepeater)
```

Initialize the media caster item (internal use)

### Parameters:

mediaCasterId - media caster id  
streamExt - stream extension or prefix  
mediaCasterDef - media caster definition  
parent - parent map

---

## getMediaCasterId

```
public String getMediaCasterId()
```

Get this media caster item id

### Returns:

media caster item id

---

## getMediaCaster

```
public IMediaCaster getMediaCaster()
```

Get the underlying IMediaCaster interface for this MediaCaster

### Returns:

underlying IMediaCaster interface

## registerPlayer

```
public void registerPlayer(IMediaStreamPlay player)
```

Register a player with a media caster item (internal use)

**Parameters:**

player - player to register

---

## unregisterPlayer

```
public void unregisterPlayer(IMediaStreamPlay player)
```

Unregister a player with a media caster item (internal use)

**Parameters:**

player - player to unregister

---

## doWatchdog

```
public boolean doWatchdog()
```

Do idle processing

**Returns:**

return true if caused shutdown of item

---

## reset

```
public void reset()
```

Force a reconnect or reset for this media caster item

---

## shutdown

```
public void shutdown(boolean isAppInstanceShutdown)
```

Shutdown this media caster item

**Parameters:**

isAppInstanceShutdown - is this due to application shutdown

---

## getPlayerCount

```
public int getPlayerCount()
```

Get the current number of players associated with this media caster item

**Returns:**

current number of players associated with this media caster item

---

## getLockCount

```
public int getLockCount()
```

Get the current number of acquire locks on this media caster item

---

---

(continued from last page)

**Returns:**

current number of acquire locks on this media caster item

---

**acquireAndRelease**

```
public void acquireAndRelease()
```

Increment then decrement acquire lock count for this media caster item

---

**acquire**

```
public void acquire()
```

Increment acquire lock count for this media caster item

---

**release**

```
public void release()
```

Decrement acquire lock count for this media caster item

---

**getStreamExt**

```
public String getStreamExt()
```

---

**setStreamExt**

```
public void setStreamExt(String streamExt)
```

---

**isShutdownOnRelease**

```
public boolean isShutdownOnRelease()
```

On last release shutdown the stream even if clients are connected

**Returns:**

true if shutting down on release

---

**setShutdownOnRelease**

```
public void setShutdownOnRelease(boolean shutdownOnRelease)
```

On last release shutdown the stream even if clients are connected

**Parameters:**

shutdownOnRelease - true if shutting down on release

---

**getLiveStreamPacketizer**

```
public String getLiveStreamPacketizer()
```

Get the live stream packetizer for this media caster stream item

**Returns:**

(continued from last page)

live stream packetizer

---

## setLiveStreamPacketizer

```
public void setLiveStreamPacketizer(String liveStreamPacketizer)
```

Set the live stream packetizer for this media caster stream item

**Parameters:**

liveStreamPacketizer - live stream packetizer

---

## getLiveStreamRepeater

```
public String getLiveStreamRepeater()
```

Get the live stream repeater for this media caster stream item

**Returns:**

live stream repeater

---

## setLiveStreamRepeater

```
public void setLiveStreamRepeater(String liveStreamRepeater)
```

Set the live stream repeater for this media caster stream item

**Parameters:**

liveStreamRepeater - live stream repeater

## com.wowza.wms.mediacaster Class MediaCasterStreamManager

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterStreamManager

public class **MediaCasterStreamManager**  
extends Object

### Constructor Summary

public	<a href="#">MediaCasterStreamManager</a> ( <a href="#">MediaCasterStreamMap</a> mediaCasterStreamMap)
--------	---

### Method Summary

String[]	<a href="#">getStreamArray</a> () Get a list of active streams
java.util.List	<a href="#">getStreamList</a> () Get a list of active streams
boolean	<a href="#">startStream</a> (String streamName, String mediaCasterType) Start a stream by name
boolean	<a href="#">stopStream</a> (String streamName) Stop a stream by name
boolean	<a href="#">streamExists</a> (String streamName) Returns true if stream exists

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### MediaCasterStreamManager

public **MediaCasterStreamManager**([MediaCasterStreamMap](#) mediaCasterStreamMap)

### Methods

#### getStreamArray

public String[] **getStreamArray**()

Get a list of active streams

---

(continued from last page)

**Returns:**

list of active streams

---

## getStreamList

```
public java.util.List getStreamList()
```

Get a list of active streams

**Returns:**

list of active streams

---

## streamExists

```
public boolean streamExists(String streamName)
```

Returns true if stream exists

**Parameters:**

streamName - stream name

**Returns:**

true if stream exists

---

## stopStream

```
public boolean stopStream(String streamName)
```

Stop a stream by name

**Parameters:**

streamName - stream name

**Returns:**

true is successful

---

## startStream

```
public boolean startStream(String streamName,  
    String mediaCasterType)
```

Start a stream by name

**Parameters:**

streamName - stream name

mediaCasterType - MediaCaster type as defined in the name field of conf/MediaCasters.xml

**Returns:**

true is successful

---



## com.wowza.wms.mediacaster

### Class MediaCasterStreamMap

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterStreamMap

public class **MediaCasterStreamMap**  
extends Object

#### Constructor Summary

public	<a href="#">MediaCasterStreamMap</a> ( <a href="#">IApplicationInstance</a> appInstance) Create a new mediacaster map
--------	--

#### Method Summary

<a href="#">MediaCasterStreamItem</a>	<a href="#">acquire</a> (String streamName) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
<a href="#">MediaCasterStreamItem</a>	<a href="#">acquire</a> (String inStreamName, <a href="#">MediaCasterItem</a> mediaCasterDef) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
<a href="#">MediaCasterStreamItem</a>	<a href="#">acquire</a> (String inStreamName, String streamType) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
<a href="#">MediaCasterStreamItem</a>	<a href="#">acquire</a> (String streamName, String liveStreamPacketizer, String liveStreamRepeater) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
<a href="#">MediaCasterStreamItem</a>	<a href="#">acquire</a> (String inStreamName, String liveStreamPacketizer, String liveStreamRepeater, <a href="#">MediaCasterItem</a> mediaCasterDef) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
<a href="#">MediaCasterStreamItem</a>	<a href="#">acquire</a> (String inStreamName, String liveStreamPacketizer, String liveStreamRepeater, String streamType) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
<a href="#">MediaCasterStreamItem</a>	<a href="#">acquireAndRelease</a> (String inStreamName, String liveStreamPacketizer, String liveStreamRepeater, <a href="#">MediaCasterItem</a> mediaCasterDef) Increment and then decrement the lock count for a media caster item (so that it is loaded and will stay loaded for at least the KeepAliveTime).
void	<a href="#">addStreamSrcToMediaCaster</a> (long streamSrc, String mediaCasterId)
void	<a href="#">clearStreamSrcToMediaCaster</a> (long streamSrc)
void	<a href="#">doWatchdog</a> () Do periodic idle time processing

<a href="#">IApplicationInstance</a>	<a href="#">getApplicationInstance()</a> Get the parent application instance for this map
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<a href="#">getLock()</a> Get the read/write lock for this interface
<a href="#">MediaCasterStreamItem</a>	<a href="#">getMediaCaster(String streamName)</a> Get media caster item based on given stream name
<a href="#">MediaCasterStreamItem</a>	<a href="#">getMediaCaster(String streamName, String liveStreamPacketizer, String liveStreamRepeater)</a> Get media caster item based on given stream name
int	<a href="#">getMediaCasterCount()</a> Get the number of mediacasters current running
java.util.List	<a href="#">getMediaCasterNames()</a> Get a list of all the currently running media caster names
<a href="#">MediaCasterStreamManager</a>	<a href="#">getStreamManager()</a> Get the stream manager interface for managing the starting and stopping of streams
void	<a href="#">registerPlayer(IMediaStreamPlay player, MediaCasterItem mediaCasterDef)</a> Register a player to a media caster item (internal use)
void	<a href="#">release(MediaCasterStreamItem mediaCasterStreamItem)</a> Decrement lock count on media caster item
void	<a href="#">release(MediaCasterStreamItem mediaCasterStreamItem, boolean removeIfZero)</a>
void	<a href="#">remove(MediaCasterStreamItem mediaCasterStreamItem)</a>
void	<a href="#">shutdown(boolean isAppInstanceShutdown)</a> Shutdown this media caster and close all running media casters
String	<a href="#">streamSrcToMediaCaster(long streamSrc)</a>
void	<a href="#">unregisterPlayer(IMediaStreamPlay player, MediaCasterItem mediaCasterDef)</a> Unregister a player to a media caster item (internal use)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### MediaCasterStreamMap

public **MediaCasterStreamMap**([IApplicationInstance](#) appInstance)

Create a new mediacaster map

(continued from last page)

**Parameters:**

appInstance - application instance

## Methods

### getLock

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock getLock()
```

Get the read/write lock for this interface

**Returns:**

read/write lock

### getStreamManager

```
public MediaCasterStreamManager getStreamManager()
```

Get the stream manager interface for managing the starting and stopping of streams

**Returns:**

stream manager interface

### getApplicationInstance

```
public IApplicationInstance getApplicationInstance()
```

Get the parent application instance for this map

**Returns:**

parent application instance for this map

### getMediaCasterCount

```
public int getMediaCasterCount()
```

Get the number of mediacasters current running

**Returns:**

number of mediacasters current running

### doWatchdog

```
public void doWatchdog()
```

Do periodic idle time processing

### shutdown

```
public void shutdown(boolean isAppInstanceShutdown)
```

Shutdown this media caster and close all running media casters

**Parameters:**

isAppInstanceShutdown - is this due to application shutdown

(continued from last page)

## getMediaCasterNames

```
public java.util.List getMediaCasterNames()
```

Get a list of all the currently running media caster names

**Returns:**

list of all the currently running media caster names

---

## getMediaCaster

```
public MediaCasterStreamItem getMediaCaster(String streamName)
```

Get media caster item based on given stream name

**Parameters:**

streamName - stream name

**Returns:**

media caster item

---

## getMediaCaster

```
public MediaCasterStreamItem getMediaCaster(String streamName,  
String liveStreamPacketizer,  
String liveStreamRepeater)
```

Get media caster item based on given stream name

**Parameters:**

streamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

**Returns:**

media caster item

---

## acquire

```
public MediaCasterStreamItem acquire(String streamName,  
String liveStreamPacketizer,  
String liveStreamRepeater)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. Uses default application instance stream type.

**Parameters:**

streamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

**Returns:**

media caster item

---

## acquire

```
public MediaCasterStreamItem acquire(String streamName)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. Uses default application instance stream type.

(continued from last page)

**Parameters:**

streamName - stream name

**Returns:**

media caster item

---

**acquire**

```
public MediaCasterStreamItem acquire(String inStreamName,  
    MediaCasterItem mediaCasterDef)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. This API allow loading of a MediaCaster into a non-MediaCaster stream type such as the "live" or "liverepeater-origin" stream type.

**Parameters:**

inStreamName - stream name

mediaCasterDef - MediaCaster definition

**Returns:**

media caster item

---

**acquire**

```
public MediaCasterStreamItem acquire(String inStreamName,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    MediaCasterItem mediaCasterDef)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. This API allow loading of a MediaCaster into a non-MediaCaster stream type such as the "live" or "liverepeater-origin" stream type.

**Parameters:**

inStreamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

mediaCasterDef - MediaCaster definition

**Returns:**

media caster item

---

**acquireAndRelease**

```
public MediaCasterStreamItem acquireAndRelease(String inStreamName,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    MediaCasterItem mediaCasterDef)
```

Increment and then decrement the lock count for a media caster item (so that it is loaded and will stay loaded for at least the KeepAliveTime). Will load the media caster if not already loaded. This API allow loading of a MediaCaster into a non-MediaCaster stream type such as the "live" or "liverepeater-origin" stream type.

**Parameters:**

inStreamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

mediaCasterDef - MediaCaster definition

**Returns:**

(continued from last page)

media caster item

---

## acquire

```
public MediaCasterStreamItem acquire(String inStreamName,  
    String streamType)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded.

**Parameters:**

inStreamName - stream name

streamType - stream type to use (null will use default application streamType)

**Returns:**

media caster item

---

## acquire

```
public MediaCasterStreamItem acquire(String inStreamName,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    String streamType)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded.

**Parameters:**

inStreamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

streamType - stream type to use (null will use default application streamType)

**Returns:**

media caster item

---

## release

```
public void release(MediaCasterStreamItem mediaCasterStreamItem)
```

Decrement lock count on media caster item

**Parameters:**

mediaCasterStreamItem - media caster item to decrement

---

## release

```
public void release(MediaCasterStreamItem mediaCasterStreamItem,  
    boolean removeIfZero)
```

---

## remove

```
public void remove(MediaCasterStreamItem mediaCasterStreamItem)
```

---

(continued from last page)

---

## streamSrcToMediaCaster

```
public String streamSrcToMediaCaster(long streamSrc)
```

---

## addStreamSrcToMediaCaster

```
public void addStreamSrcToMediaCaster(long streamSrc,  
    String mediaCasterId)
```

---

## clearStreamSrcToMediaCaster

```
public void clearStreamSrcToMediaCaster(long streamSrc)
```

---

## registerPlayer

```
public void registerPlayer(IMediaStreamPlay player,  
    MediaCasterItem mediaCasterDef)
```

Register a player to a media caster item (internal use)

**Parameters:**

player - player to register

mediaCasterDef - media caster definition

---

## unregisterPlayer

```
public void unregisterPlayer(IMediaStreamPlay player,  
    MediaCasterItem mediaCasterDef)
```

Unregister a player to a media caster item (internal use)

**Parameters:**


player - player to unregister

mediaCasterDef - media caster definition

---

## com.wowza.wms.mediacaster Class ModuleMediaCaster

java.lang.Object



All Implemented Interfaces:

[IModuleOnApp](#)

public class **ModuleMediaCaster**  
 extends [ModuleBase](#)  
 implements [IModuleOnApp](#)

ModuleMediaCaster: Module for manipulating media casters through a Flash UI.

### Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK\\_PARAM1](#), [CALLBACK\\_PARAM10](#), [CALLBACK\\_PARAM2](#), [CALLBACK\\_PARAM3](#), [CALLBACK\\_PARAM4](#),  
[CALLBACK\\_PARAM5](#), [CALLBACK\\_PARAM6](#), [CALLBACK\\_PARAM7](#), [CALLBACK\\_PARAM8](#), [CALLBACK\\_PARAM9](#), [PARAM1](#),  
[PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#),  
[PLAYTRANSITION\\_APPEND](#), [PLAYTRANSITION\\_APPEND\\_IMMEDIATE](#), [PLAYTRANSITION\\_RESET](#),  
[PLAYTRANSITION\\_RESET\\_IMMEDIATE](#), [PLAYTRANSITION\\_STOP](#), [PLAYTRANSITION\\_SWAP](#),  
[PLAYTRANSITION\\_SWITCH](#), [PLAYTRANSITION\\_UNKNOWN](#), [PLAYTRANSITIONSTR\\_APPEND](#),  
[PLAYTRANSITIONSTR\\_RESET](#), [PLAYTRANSITIONSTR\\_STOP](#), [PLAYTRANSITIONSTR\\_SWAP](#),  
[PLAYTRANSITIONSTR\\_SWITCH](#), [PLAYTRANSITIONSTR\\_UNKNOWN](#)

### Constructor Summary

public	<a href="#">ModuleMediaCaster</a> ()
--------	--------------------------------------

### Method Summary

void	<a href="#">acquireMediaCaster</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Increment the lock count of a media caster stream.
void	<a href="#">getLockCount</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the current lock count for a stream
void	<a href="#">getPlayerCount</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the numbers of players associated with a particular media caster
void	<a href="#">getStreamNames</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get an array of stream names that are media casters associate with this application instance (returned as AMFDataArray)
void	<a href="#">onAppStart</a> ( <a href="#">IApplicationInstance</a> appInstance) onAppStart



void	<a href="#">onAppStop</a> ( <a href="#">IApplicationInstance</a> appInstance) onAppStop
void	<a href="#">releaseMediaCaster</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Decrement the lock count of a media caster stream
void	<a href="#">resetStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Reset a media caster stream
void	<a href="#">shutdownStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Force shutdown a media caster stream

#### Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface [com.wowza.wms.module.IModuleOnApp](#)

[onAppStart](#), [onAppStop](#)

## Constructors

### ModuleMediaCaster

```
public ModuleMediaCaster()
```

## Methods

### onAppStart

```
public void onAppStart(IApplicationInstance appInstance)
```

onAppStart

### onAppStop

```
public void onAppStop(IApplicationInstance appInstance)
```

onAppStop

## getLockCount

```
public void getLockCount(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the current lock count for a stream

**Parameters:**

client - client  
function - function  
params - {streamName}

---

## getPlayerCount

```
public void getPlayerCount(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the numbers of players associated with a particular media caster

**Parameters:**

client - client  
function - function  
params - {streamName}

---

## getStreamNames

```
public void getStreamNames(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get an array of stream names that are media casters associate with this application instance (returned as AMFDataArray)

**Parameters:**

client - client  
function - function  
params - (no params)

---

## resetStream

```
public void resetStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Reset a media caster stream

**Parameters:**

client - client  
function - function  
params - {streamName}

---

## shutdownStream

```
public void shutdownStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Force shutdown a media caster stream

---

(continued from last page)

**Parameters:**

client - client  
function - function  
params - {streamName}

---

**acquireMediaCaster**

```
public void acquireMediaCaster(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Increment the lock count of a media caster stream. If the media caster does not exists create it and connect.

**Parameters:**

client - client  
function - function  
params - {streamName, streamType [optional]}

---

**releaseMediaCaster**

```
public void releaseMediaCaster(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Decrement the lock count of a media caster stream

**Parameters:**

client - client  
function - function  
params - {streamName}

---

Package

**com.wowza.wms.mediacaster.rtp**

## com.wowza.wms.mediacaster.rtp Interface IRTPSessionDescriptionDataProvider

public interface **IRTPSessionDescriptionDataProvider**  
extends

IRTPSessionDescriptionDataProvider: Internal use.

### Method Summary

boolean	<a href="#"><code>doIdle</code></a> (MediaCaster mediaCaster)
RTPSessionDescription Data	<a href="#"><code>getSessionDescriptionData</code></a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName, int retryCount, <a href="#">IRTPSessionDescriptionSessionHandler</a> handler, <a href="#">IMediaCaster</a> mediaCaster)
void	<a href="#"><code>init</code></a> (MediaCaster mediaCaster)
void	<a href="#"><code>sessionStart</code></a> ( <a href="#">RTPSession</a> rtpSession)
void	<a href="#"><code>sessionStop</code></a> ( <a href="#">RTPSession</a> rtpSession)

### Methods

#### **init**

public void **init**(MediaCaster mediaCaster)

#### **getSessionDescriptionData**

public RTPSessionDescriptionData **getSessionDescriptionData**([IApplicationInstance](#) appInstance,  
String streamName,  
int retryCount,  
[IRTPSessionDescriptionSessionHandler](#) handler,  
[IMediaCaster](#) mediaCaster)

#### **sessionStart**

public void **sessionStart**([RTPSession](#) rtpSession)

#### **sessionStop**

public void **sessionStop**([RTPSession](#) rtpSession)

(continued from last page)

---

## **doIdle**

```
public boolean doIdle(MediaCaster mediaCaster)
```

---

## com.wowza.wms.mediacaster.rtp Interface IRTPSessionDescriptionSessionHandler

---

public interface **IRTPSessionDescriptionSessionHandler**  
extends

IRTPSessionDescriptionSessionHandler: Internal use.

---

### Method Summary

void	<a href="#">onDisconnect()</a>
------	--------------------------------

---

### Methods

#### **onDisconnect**

public void **onDisconnect()**

---

Package

**com.wowza.wms.mediacaster.shoutcast**



## com.wowza.wms.mediacaster.shoutcast

### Interface IShoutCastFrameReceiver

public interface **IShoutCastFrameReceiver**  
 extends

IShoutCastFrameReceiver: Internal use.

#### Method Summary

void	<a href="#"><code>onCodecConfigAAC</code></a> (com.wowza.wms.media.aac.AACFrame frame, byte[] buffer, long offset)
void	<a href="#"><code>onFrameAAC</code></a> (com.wowza.wms.media.aac.AACFrame frame, byte[] buffer, long offset)
void	<a href="#"><code>onFrameMP3</code></a> (int frequency, int samplesPerFrame, int channels, byte[] syncHeader, byte[] packetHeader, byte[] frameData)
void	<a href="#"><code>onHeaderData</code></a> (java.util.Map headerMap)
void	<a href="#"><code>onMetaData</code></a> (java.util.Map metaMap)
void	<a href="#"><code>onTrim</code></a> ()

#### Methods

##### onFrameMP3

```
public void onFrameMP3(int frequency,
    int samplesPerFrame,
    int channels,
    byte[] syncHeader,
    byte[] packetHeader,
    byte[] frameData)
```

##### onCodecConfigAAC

```
public void onCodecConfigAAC(com.wowza.wms.media.aac.AACFrame frame,
    byte[] buffer,
    long offset)
```

##### onFrameAAC

```
public void onFrameAAC(com.wowza.wms.media.aac.AACFrame frame,
    byte[] buffer,
    long offset)
```

(continued from last page)

---

## **onTrim**

```
public void onTrim()
```

---

## **onHeaderData**

```
public void onHeaderData(java.util.Map headerMap)
```

---

## **onMetaData**

```
public void onMetaData(java.util.Map metaMap)
```

---

## com.wowza.wms.mediacaster.shoutcast Interface IShoutCastMetaDataListener

---

public interface **IShoutCastMetaDataListener**  
extends

IShoutCastMetaDataListener: Internal use.

---

### Method Summary

void	<a href="#">addMetaDataListener</a> ( <a href="#">IShoutCastMetaDataNotify</a> listener)
boolean	<a href="#">removeMetaDataListener</a> ( <a href="#">IShoutCastMetaDataNotify</a> listener)

---

### Methods

#### **addMetaDataListener**

public void **addMetaDataListener**([IShoutCastMetaDataNotify](#) listener)

---

#### **removeMetaDataListener**

public boolean **removeMetaDataListener**([IShoutCastMetaDataNotify](#) listener)

## com.wowza.wms.mediacaster.shoutcast

# Interface IShoutCastMetaDataNotify

public interface **IShoutCastMetaDataNotify**  
extends

IShoutCastMetaDataNotify: Internal use.

## Method Summary

void	<a href="#">onAACEncodeInfo</a> ( <a href="#">IMediaCaster</a> mediaCaster, int frequency, int channels, int samplesPerFrame)
void	<a href="#">onHeaderData</a> ( <a href="#">IMediaCaster</a> mediaCaster, java.util.Map headerMap)
void	<a href="#">onMetaData</a> ( <a href="#">IMediaCaster</a> mediaCaster, java.util.Map metaMap)
void	<a href="#">onMP3EncodeInfo</a> ( <a href="#">IMediaCaster</a> mediaCaster, int frequency, int channels, int samplesPerFrame)

## Methods

### onHeaderData

```
public void onHeaderData(IMediaCaster mediaCaster,  
    java.util.Map headerMap)
```

### onMetaData

```
public void onMetaData(IMediaCaster mediaCaster,  
    java.util.Map metaMap)
```

### onAACEncodeInfo

```
public void onAACEncodeInfo(IMediaCaster mediaCaster,  
    int frequency,  
    int channels,  
    int samplesPerFrame)
```

### onMP3EncodeInfo

```
public void onMP3EncodeInfo(IMediaCaster mediaCaster,  
    int frequency,  
    int channels,  
    int samplesPerFrame)
```

(continued from last page)

---

Package

**com.wowza.wms.medialist**

## com.wowza.wms.medialist

### Class MediaList

java.lang.Object

└─com.wowza.wms.medialist.MediaList

public class **MediaList**  
extends Object

#### Field Summary

protected	<a href="#">lock</a>
protected	<a href="#">name</a>
protected	<a href="#">properties</a>
protected	<a href="#">segments</a>

#### Constructor Summary

public	<a href="#">MediaList()</a>
--------	-----------------------------

#### Method Summary

void	<a href="#">addSegment</a> (int index, <a href="#">MediaListSegment</a> mediaListSegment)
void	<a href="#">addSegment</a> ( <a href="#">MediaListSegment</a> mediaListSegment)
void	<a href="#">clearSegments</a> ()
<a href="#">MediaListSegment</a>	<a href="#">getFirstSegment</a> ()
Object	<a href="#">getLock</a> ()
String	<a href="#">getName</a> ()
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> ()
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> (boolean write)
java.util.List	<a href="#">getSegment</a> ()
<a href="#">MediaListSegment</a>	<a href="#">getSegment</a> (int index)

<a href="#">MediaListSegment</a>	<a href="#">removeSegment</a> (int index)
void	<a href="#">removeSegment</a> ( <a href="#">MediaListSegment</a> mediaListSegment)
void	<a href="#">reset</a> ()
void	<a href="#">setName</a> (String name)
String	<a href="#">toSMILString</a> ()
String	<a href="#">toString</a> ()

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

**name**

protected java.lang.String **name**

**segments**

protected java.util.List **segments**

**properties**

protected com.wowza.wms.application.WMSProperties **properties**

**lock**

protected java.lang.Object **lock**

## Constructors

**MediaList**

public **MediaList**()

## Methods



(continued from last page)

---

**toString**

```
public String toString()
```

---

**toSMILString**

```
public String toSMILString()
```

---

**reset**

```
public void reset()
```

---

**getSegment**

```
public java.util.List getSegment()
```

---

**addSegment**

```
public void addSegment(MediaListSegment mediaListSegment)
```

---

**addSegment**

```
public void addSegment(int index,  
    MediaListSegment mediaListSegment)
```

---

**removeSegment**

```
public void removeSegment(MediaListSegment mediaListSegment)
```

---

**removeSegment**

```
public MediaListSegment removeSegment(int index)
```

---

**clearSegments**

```
public void clearSegments()
```

---

(continued from last page)

---

## getFirstSegment

```
public MediaListSegment getFirstSegment()
```

---

## getSegment

```
public MediaListSegment getSegment(int index)
```

---

## getLock

```
public Object getLock()
```

---

## getProperties

```
public WMSPProperties getProperties()
```

---

## getProperties

```
public WMSPProperties getProperties(boolean write)
```

---

## getName

```
public String getName()
```


---

## setName

```
public void setName(String name)
```

---

com.wowza.wms.medialist  
Class MediaListRendition



```
public class MediaListRendition
extends Object
```

Field Summary	
protected	<a href="#">audioCodecId</a>
protected	<a href="#">bitrateAudio</a>
protected	<a href="#">bitrateTotal</a>
protected	<a href="#">bitrateVideo</a>
protected	<a href="#">height</a>
protected	<a href="#">lock</a>
protected	<a href="#">mediaListSegment</a>
protected	<a href="#">name</a>
protected	<a href="#">playDuration</a>
protected	<a href="#">playStart</a>
protected	<a href="#">properties</a>
protected	<a href="#">type</a>
protected	<a href="#">videoCodecId</a>
protected	<a href="#">vodTranscodeNGRP</a>
protected	<a href="#">width</a>
protected	<a href="#">wowzaAudioOnly</a>

Constructor Summary	
---------------------	--

public	<a href="#">MediaListRendition()</a>
--------	--------------------------------------

## Method Summary

String	<a href="#">getAudioCodecId()</a>
int	<a href="#">getBitrateAudio()</a>
int	<a href="#">getBitrateTotal()</a>
int	<a href="#">getBitrateVideo()</a>
String	<a href="#">getCodecId()</a>
int	<a href="#">getHeight()</a>
String	<a href="#">getLanguage()</a>
Object	<a href="#">getLock()</a>
<a href="#">MediaListSegment</a>	<a href="#">getMediaListSegment()</a>
String	<a href="#">getName()</a>
long	<a href="#">getPlayDuration()</a>
long	<a href="#">getPlayStart()</a>
<a href="#">WMSProperties</a>	<a href="#">getProperties()</a>
<a href="#">WMSProperties</a>	<a href="#">getProperties(boolean write)</a>
int[]	<a href="#">getSize()</a>
int	<a href="#">getType()</a>
String	<a href="#">getTypeAsString()</a>
String	<a href="#">getVideoCodecId()</a>
String	<a href="#">getVODTranscodeNGRP()</a>
int	<a href="#">getWidth()</a>
boolean	<a href="#">isWowzaAudioOnly()</a>
static java.util.ArrayList	<a href="#">parseCommaSeparatedLanguages(String langStr)</a>

void	<a href="#"><u>setAudioCodecId</u></a> (String audioCodecId)
void	<a href="#"><u>setBitrateAudio</u></a> (int bitrateAudio)
void	<a href="#"><u>setBitrateTotal</u></a> (int bitrateTotal)
void	<a href="#"><u>setBitrateVideo</u></a> (int bitrateVideo)
void	<a href="#"><u>setHeight</u></a> (int height)
void	<a href="#"><u>setLanguage</u></a> (String language)
void	<a href="#"><u>setLock</u></a> (Object lock)
void	<a href="#"><u>setMediaListSegment</u></a> ( <a href="#"><u>MediaListSegment</u></a> mediaListSegment)
void	<a href="#"><u>setName</u></a> (String name)
void	<a href="#"><u>setPlayDuration</u></a> (long playDuration)
void	<a href="#"><u>setPlayStart</u></a> (long playStart)
void	<a href="#"><u>setSize</u></a> (int width, int height)
void	<a href="#"><u>setType</u></a> (int type)
void	<a href="#"><u>setVideoCodecId</u></a> (String videoCodecId)
void	<a href="#"><u>setVODTranscodeNGRP</u></a> (String vodTranscodeNGRP)
void	<a href="#"><u>setWidth</u></a> (int width)
void	<a href="#"><u>setWowzaAudioOnly</u></a> (boolean wowzaAudioOnly)
String	<a href="#"><u>toSMILString</u></a> ()
String	<a href="#"><u>toString</u></a> ()

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

(continued from last page)

## lock

protected java.lang.Object **lock**

---

## mediaListSegment

protected com.wowza.wms.medialist.MediaListSegment **mediaListSegment**

---

## properties

protected com.wowza.wms.application.WMSProperties **properties**

---

## name

protected java.lang.String **name**

---

## type

protected int **type**

---

## bitrateTotal

protected int **bitrateTotal**

---

## bitrateAudio

protected int **bitrateAudio**

---

## bitrateVideo

protected int **bitrateVideo**

---

## videoCodecId

protected java.lang.String **videoCodecId**

---

## audioCodecId

protected java.lang.String **audioCodecId**

---

(continued from last page)

---

### wowzaAudioOnly

protected boolean **wowzaAudioOnly**

---

### width

protected int **width**

---

### height

protected int **height**

---

### playStart

protected long **playStart**

---

### playDuration

protected long **playDuration**

---

### vodTranscodeNGRP

protected java.lang.String **vodTranscodeNGRP**

---

## Constructors

### MediaListRendition

public **MediaListRendition()**

## Methods

### toString

public String **toString()**

---

### toSMILString

public String **toSMILString()**

---

(continued from last page)

---

## getTypeAsString

```
public String getTypeAsString()
```

---

## getLock

```
public Object getLock()
```

---

## setLock

```
public void setLock(Object lock)
```

---

## getMediaListSegment

```
public MediaListSegment getMediaListSegment()
```

---

## setMediaListSegment

```
public void setMediaListSegment(MediaListSegment mediaListSegment)
```

---

## getProperties

```
public WMSProperties getProperties()
```

---

## getProperties

```
public WMSProperties getProperties(boolean write)
```

---

## getBitrateTotal

```
public int getBitrateTotal()
```

---

## setBitrateTotal

```
public void setBitrateTotal(int bitrateTotal)
```

---



(continued from last page)

## getBitrateAudio

```
public int getBitrateAudio()
```

---

## setBitrateAudio

```
public void setBitrateAudio(int bitrateAudio)
```

---

## getBitrateVideo

```
public int getBitrateVideo()
```

---

## setBitrateVideo

```
public void setBitrateVideo(int bitrateVideo)
```

---

## getVideoCodecId

```
public String getVideoCodecId()
```

---

## setVideoCodecId

```
public void setVideoCodecId(String videoCodecId)
```

---

## getCodecId

```
public String getCodecId()
```

---

## getAudioCodecId

```
public String getAudioCodecId()
```

---

## setAudioCodecId

```
public void setAudioCodecId(String audioCodecId)
```

---

## isWowzaAudioOnly

```
public boolean isWowzaAudioOnly()
```

---

(continued from last page)

---

**setWowzaAudioOnly**

```
public void setWowzaAudioOnly(boolean wowzaAudioOnly)
```

---

**getName**

```
public String getName()
```

---

**setName**

```
public void setName(String name)
```

---

**getType**

```
public int getType()
```

---

**setType**

```
public void setType(int type)
```

---

**getWidth**

```
public int getWidth()
```

---

**setWidth**

```
public void setWidth(int width)
```

---

**getHeight**

```
public int getHeight()
```

---

**setHeight**

```
public void setHeight(int height)
```

---

(continued from last page)

**setSize**

```
public void setSize(int width,  
                    int height)
```

---

**getSize**

```
public int[] getSize()
```

---

**getPlayStart**

```
public long getPlayStart()
```

---

**setPlayStart**

```
public void setPlayStart(long playStart)
```

---

**getPlayDuration**

```
public long getPlayDuration()
```

---

**setPlayDuration**

```
public void setPlayDuration(long playDuration)
```

---

**getVODTranscodeNGRP**

```
public String getVODTranscodeNGRP()
```

---

**setVODTranscodeNGRP**

```
public void setVODTranscodeNGRP(String vodTranscodeNGRP)
```

---

**setLanguage**

```
public void setLanguage(String language)
```

---

**getLanguage**

```
public String getLanguage()
```

---

(continued from last page)

---

## **parseCommaSeparatedLanguages**

```
public static java.util.ArrayList parseCommaSeparatedLanguages(String langStr)
```

## com.wowza.wms.medialist

### Class MediaListSegment

java.lang.Object

└─com.wowza.wms.medialist.MediaListSegment

public class **MediaListSegment**  
extends Object

#### Field Summary

protected	<a href="#">lock</a>
protected	<a href="#">mediaList</a>
protected	<a href="#">properties</a>
protected	<a href="#">renditions</a>

#### Constructor Summary

public	<a href="#">MediaListSegment()</a>
--------	------------------------------------

#### Method Summary

void	<a href="#">addRendition</a> (int index, <a href="#">MediaListRendition</a> mediaListRendition)
void	<a href="#">addRendition</a> ( <a href="#">MediaListRendition</a> mediaListRendition)
void	<a href="#">clearSegments</a> ()
<a href="#">MediaListRendition</a>	<a href="#">getFirstRendition</a> ()
Object	<a href="#">getLock</a> ()
<a href="#">MediaList</a>	<a href="#">getMediaList</a> ()
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> ()
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> (boolean write)
<a href="#">MediaListRendition</a>	<a href="#">getRendition</a> (int index)
java.util.List	<a href="#">getRenditions</a> ()

<a href="#">MediaListRendition</a>	<a href="#">removeRendition</a> (int index)
void	<a href="#">removeRendition</a> ( <a href="#">MediaListRendition</a> mediaListRendition)
void	<a href="#">setLock</a> (Object lock)
void	<a href="#">setMediaList</a> ( <a href="#">MediaList</a> mediaList)
String	<a href="#">toSMILString</a> ()
String	<a href="#">toString</a> ()

**Methods inherited from class java.lang.Object**

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### lock

protected java.lang.Object **lock**

### mediaList

protected com.wowza.wms.medialist.MediaList **mediaList**

### renditions

protected java.util.List **renditions**

### properties

protected com.wowza.wms.application.WMSProperties **properties**

## Constructors

### MediaListSegment

public **MediaListSegment**()

## Methods

(continued from last page)

---

## toString

```
public String toString()
```

---

## toSMILString

```
public String toSMILString()
```

---

## getRenditions

```
public java.util.List getRenditions()
```

---

## addRendition

```
public void addRendition(MediaListRendition mediaListRendition)
```

---

## addRendition

```
public void addRendition(int index,  
    MediaListRendition mediaListRendition)
```

---

## removeRendition

```
public void removeRendition(MediaListRendition mediaListRendition)
```

---

## removeRendition

```
public MediaListRendition removeRendition(int index)
```

---

## clearSegments

```
public void clearSegments()
```

---

## getFirstRendition

```
public MediaListRendition getFirstRendition()
```

---

(continued from last page)

## getRendition

```
public MediaListRendition getRendition(int index)
```

---

## getLock

```
public Object getLock()
```

---

## setLock

```
public void setLock(Object lock)
```

---

## getMediaList

```
public MediaList getMediaList()
```

---

## setMediaList

```
public void setMediaList(MediaList mediaList)
```

---

## getProperties

```
public WMSProperties getProperties()
```

---

## getProperties

```
public WMSProperties getProperties(boolean write)
```

---



---

Package

**com.wowza.wms.module**

## com.wowza.wms.module Interface IModuleCallResult

public interface **IModuleCallResult**  
extends

IModuleCallResult: callback interface used by IClient call.

### Method Summary

void	<code>onResult(<a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params)</code> Triggered on client side result from call to IClient.call
------	--

### Methods

#### onResult

```
public void onResult(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Triggered on client side result from call to IClient.call

#### Parameters:

client - client  
function - function object  
params - result parameters

## com.wowza.wms.module Interface IModuleNotify

public interface **IModuleNotify**  
extends

IModuleNotify: listener interface for listening to module loading and unloading. See  
IApplicationInstance.addModuleListener(IModuleNotify moduleListener)

### Method Summary

void	<a href="#"><u>onModuleLoad</u></a> (ModuleItem item) Called when module loaded
void	<a href="#"><u>onModuleUnload</u></a> (ModuleItem item) Called when module unloaded

### Methods

#### onModuleLoad

public void **onModuleLoad**(ModuleItem item)

Called when module loaded

**Parameters:**

item - module

#### onModuleUnload

public void **onModuleUnload**(ModuleItem item)

Called when module unloaded

**Parameters:**

item - module

## com.wowza.wms.module Interface IModuleOnApp

All Known Implementing Classes:  
[ModuleMediaCaster](#)

public interface **IModuleOnApp**  
extends

IModuleCallResult: method interface examples for application level methods in a module.

Since module method must be implemented as static method a module cannot directly implements this interface. This interface only serves as an example of the method names and call signature needed to implement these application methods.

### Method Summary

void	<a href="#">onAppStart</a> ( <a href="#">IApplicationInstance</a> appInstance) Invoked when an application instance is started.
void	<a href="#">onAppStop</a> ( <a href="#">IApplicationInstance</a> appInstance) Invoked when an application instance is stopped (destroyed).

### Methods

#### onAppStart

public void **onAppStart**([IApplicationInstance](#) appInstance)

Invoked when an application instance is started.

**Parameters:**

appInstance - application instance

#### onAppStop

public void **onAppStop**([IApplicationInstance](#) appInstance)

Invoked when an application instance is stopped (destroyed).

**Parameters:**

appInstance - application instance

## com.wowza.wms.module Interface IModuleOnCall

public interface **IModuleOnCall**  
extends

IModuleOnCall: method interface example for the catch-all method handler onCall.

Since module method must be implemented as static method a module cannot directly implements this interface. This interface only serves as an example of the method name and call signature needed to implement this method. The onCall method, when defined in a module, is invoked for all handlers that are undefined in a given module. The onCall handler can also be used to catch calls to server side component calls.

### Method Summary

void

[onCall](#)(String handlerName, [IClient](#) client,  
com.wowza.wms.request.RequestFunction function, [AMFDataList](#) params)  
Catch-all method handler.

### Methods

#### onCall

```
public void onCall(String handlerName,  
    IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Catch-all method handler. The onCall method, when defined in a module, is invoked for all handlers that are undefined in a given module.

##### Parameters:

handlerName - handler name  
client - client  
function - function object  
params - function parameters

## com.wowza.wms.module Interface IModuleOnConnect

public interface **IModuleOnConnect**  
extends

IModuleOnConnect: method interface examples for client level methods in a module.

Since module method must be implemented as static method a module cannot directly implements this interface. This interface only serves as an example of the method names and call signature needed to implement these client methods.

### Method Summary

void	<a href="#">onConnect</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Invoked when a client connection is initiated.
void	<a href="#">onConnectAccept</a> ( <a href="#">IClient</a> client) Invoked when a client connection is accepted.
void	<a href="#">onConnectReject</a> ( <a href="#">IClient</a> client) Invoked when a client connection is rejected.
void	<a href="#">onDisconnect</a> ( <a href="#">IClient</a> client) Invoked when a client disconnects.

### Methods

#### onConnect

```
public void onConnect(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Invoked when a client connection is initiated. It is within this method that module can call to client.acceptConnection or client.rejectConnection.

**Parameters:**

client - client  
function - function object  
params - function parameters

#### onDisconnect

```
public void onDisconnect(IClient client)
```

Invoked when a client disconnects.

**Parameters:**

client - client

(continued from last page)

## onConnectAccept

```
public void onConnectAccept(IClient client)
```

Invoked when a client connection is accepted.

**Parameters:**

client - client

---

## onConnectReject

```
public void onConnectReject(IClient client)
```

Invoked when a client connection is rejected.

**Parameters:**

client - client

## com.wowza.wms.module Interface IModuleOnHTTPCupertinoEncryption

public interface **IModuleOnHTTPCupertinoEncryption**  
extends

IModuleOnHTTPCupertinoEncryption: listener interface for listening to AES-128 encryption events.

### Field Summary

public static final	<a href="#"><u>KEYDATA_MODE_ENCRYPT</u></a> Value: <b>3</b>
public static final	<a href="#"><u>KEYDATA_MODE_INIT</u></a> Value: <b>1</b>
public static final	<a href="#"><u>KEYDATA_MODE_PLAYLIST</u></a> Value: <b>2</b>

### Method Summary

void	<a href="#"><u>onHTTPCupertinoEncryptionKeyCreateLive</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance, String streamName, byte[] encKey) Called when live stream key is requested (per-published stream)
void	<a href="#"><u>onHTTPCupertinoEncryptionKeyCreateVOD</u></a> ( <a href="#"><u>HTTPStreamerSessionCupertino</u></a> httpSession, byte[] encKey) Called when video on demand key is requested (per-session)
void	<a href="#"><u>onHTTPCupertinoEncryptionKeyData</u></a> ( <a href="#"><u>HTTPStreamerSessionCupertino</u></a> httpSession, <a href="#"><u>IHTTPRequest</u></a> req, <a href="#"><u>IHTTPResponse</u></a> resp, byte[] encKeyData) Called when a key data is requested.
void	<a href="#"><u>onHTTPCupertinoEncryptionKeyLiveChunk</u></a> ( <a href="#"><u>ILiveStreamPacketizer</u></a> liveStreamPacketizer, String streamName, <a href="#"><u>CupertinoEncInfo</u></a> encInfo, long chunkId, int mode) Called when live stream key is requested (per-published stream, per-chunk - for rotating keys)
void	<a href="#"><u>onHTTPCupertinoEncryptionKeyRequest</u></a> ( <a href="#"><u>HTTPStreamerSessionCupertino</u></a> httpSession, <a href="#"><u>IHTTPRequest</u></a> req, <a href="#"><u>IHTTPResponse</u></a> resp) Called when a key is requested.
void	<a href="#"><u>onHTTPCupertinoEncryptionKeyVODChunk</u></a> ( <a href="#"><u>HTTPStreamerSessionCupertino</u></a> httpSession, <a href="#"><u>IHTTPStreamerCupertinoIndex</u></a> index, <a href="#"><u>CupertinoEncInfo</u></a> encInfo, long chunkId, int mode) Called when video on demand key is requested (per-session).

### Fields



(continued from last page)

## KEYDATA\_MODE\_INIT

```
public static final int KEYDATA_MODE_INIT
```

Constant value: **1**

## KEYDATA\_MODE\_PLAYLIST

```
public static final int KEYDATA_MODE_PLAYLIST
```

Constant value: **2**

## KEYDATA\_MODE\_ENCRYPT

```
public static final int KEYDATA_MODE_ENCRYPT
```

Constant value: **3**

## Methods

### onHTTPCupertinoEncryptionKeyRequest

```
public void onHTTPCupertinoEncryptionKeyRequest(HTTPStreamerSessionCupertino
httpSession,
IHTTPRequest req,
IHTTPResponse resp)
```

Called when a key is requested. Call `httpSession.rejectSession` to reject the streaming session and stop delivery of the encryption key.

**Parameters:**

`httpSession` - HTTP session  
`req` - HTTP request  
`resp` - HTTP response

### onHTTPCupertinoEncryptionKeyData

```
public void onHTTPCupertinoEncryptionKeyData(HTTPStreamerSessionCupertino httpSession,
IHTTPRequest req,
IHTTPResponse resp,
byte[] encKeyData)
```

Called when a key data is requested. Set `encKeyData` to the key data to be sent to the client.

**Parameters:**

`httpSession` - HTTP session  
`req` - request  
`resp` - response  
`encKeyData` - key data

### onHTTPCupertinoEncryptionKeyCreateVOD

```
public void onHTTPCupertinoEncryptionKeyCreateVOD(HTTPStreamerSessionCupertino
httpSession,
byte[] encKey)
```

(continued from last page)

Called when video on demand key is requested (per-session)

**Parameters:**

httpSession - HTTP session  
encKey - encryption key

---

## onHTTPCupertinoEncryptionKeyVODChunk

```
public void onHTTPCupertinoEncryptionKeyVODChunk(HTTPStreamerSessionCupertino
httpSession,
    IHTTPStreamerCupertinoIndex index,
    CupertinoEncInfo encInfo,
    long chunkId,
    int mode)
```

Called when video on demand key is requested (per-session). Allows setting of encryption key and URL.

**Parameters:**

httpSession - HTTP session  
index - file index  
encInfo - encryption key  
mode - KEYDATA\_MODE\_\*

---

## onHTTPCupertinoEncryptionKeyCreateLive

```
public void onHTTPCupertinoEncryptionKeyCreateLive(IApplicationInstance appInstance,
    String streamName,
    byte[] encKey)
```

Called when live stream key is requested (per-published stream)

**Parameters:**

appInstance - application instance  
streamName - stream name  
encKey - encryption key

---

## onHTTPCupertinoEncryptionKeyLiveChunk

```
public void onHTTPCupertinoEncryptionKeyLiveChunk(ILiveStreamPacketizer
liveStreamPacketizer,
    String streamName,
    CupertinoEncInfo encInfo,
    long chunkId,
    int mode)
```

Called when live stream key is requested (per-published stream, per-chunk - for rotating keys)

**Parameters:**

liveStreamPacketizer - live stream packetizer  
streamName - stream name  
encInfo - encryption info  
chunkId - chunk ID, -1 for stream creation  
mode - KEYDATA\_MODE\_\*

## com.wowza.wms.module Interface IModuleOnHTTPCupertinoStreamingSession

public interface **IModuleOnHTTPCupertinoStreamingSession**  
extends

IModuleOnHTTPSession: method interface for HTTP Cupertino Streaming session create/destroy.

### Method Summary

void	<a href="#">onHTTPCupertinoStreamingSessionCreate</a> ( <a href="#">HTTPStreamerSessionCupertino</a> <a href="#">httpCupertinoStreamingSession</a> ) Invoked when an HTTP Cupertino Streaming session is created.
void	<a href="#">onHTTPCupertinoStreamingSessionDestroy</a> ( <a href="#">HTTPStreamerSessionCupertino</a> <a href="#">httpCupertinoStreamingSession</a> ) Invoked when an HTTP Cupertino Streaming session is destroyed.

### Methods

#### onHTTPCupertinoStreamingSessionCreate

public void **onHTTPCupertinoStreamingSessionCreate**([HTTPStreamerSessionCupertino](#) [httpCupertinoStreamingSession](#))

Invoked when an HTTP Cupertino Streaming session is created.

**Parameters:**

[httpCupertinoStreamingSession](#) - [httpCupertinoStreamingSession](#)

#### onHTTPCupertinoStreamingSessionDestroy

public void **onHTTPCupertinoStreamingSessionDestroy**([HTTPStreamerSessionCupertino](#) [httpCupertinoStreamingSession](#))

Invoked when an HTTP Cupertino Streaming session is destroyed.

**Parameters:**

[httpCupertinoStreamingSession](#) - [httpCupertinoStreamingSession](#)

com.wowza.wms.module

# Interface IModuleOnHTTPSanJoseStreamingSession

public interface IModuleOnHTTPSanJoseStreamingSession  
extends

IModuleOnHTTPSanJoseStreamingSession: method interface for HTTP SanJose Streaming session create/destroy.

Method Summary	
void	<a href="#">onHTTPSanJoseStreamingSessionCreate(HTTPStreamerSessionSanJose httpSanJoseStreamingSession)</a> Invoked when an HTTP SanJose Streaming session is created.
void	<a href="#">onHTTPSanJoseStreamingSessionDestroy(HTTPStreamerSessionSanJose httpSanJoseStreamingSession)</a> Invoked when an HTTP SanJose Streaming session is destroyed.

## Methods

### onHTTPSanJoseStreamingSessionCreate

public void **onHTTPSanJoseStreamingSessionCreate**([HTTPStreamerSessionSanJose httpSanJoseStreamingSession](#))

Invoked when an HTTP SanJose Streaming session is created.

**Parameters:**

`httpSanJoseStreamingSession` - httpSanJoseStreamingSession

### onHTTPSanJoseStreamingSessionDestroy

public void **onHTTPSanJoseStreamingSessionDestroy**([HTTPStreamerSessionSanJose httpSanJoseStreamingSession](#))

Invoked when an HTTP SanJose Streaming session is destroyed.

**Parameters:**

`httpSanJoseStreamingSession` - httpSanJoseStreamingSession

## com.wowza.wms.module Interface IModuleOnHTTPSession

public interface **IModuleOnHTTPSession**  
extends

IModuleOnHTTPSession: method interface for HTTP Streaming session create/destroy.

### Method Summary

void	<a href="#">onHTTPSessionCreate</a> ( <a href="#">IHTTPStreamerSession</a> httpSession) Invoked when an HTTP Session is created (both Smooth and Cupertino sessions).
void	<a href="#">onHTTPSessionDestroy</a> ( <a href="#">IHTTPStreamerSession</a> httpSession) Invoked when an HTTP Session is destroyed (both Smooth and Cupertino sessions).

### Methods

#### onHTTPSessionCreate

public void **onHTTPSessionCreate**([IHTTPStreamerSession](#) httpSession)

Invoked when an HTTP Session is created (both Smooth and Cupertino sessions).

**Parameters:**

httpSession - httpSession

#### onHTTPSessionDestroy

public void **onHTTPSessionDestroy**([IHTTPStreamerSession](#) httpSession)

Invoked when an HTTP Session is destroyed (both Smooth and Cupertino sessions).

**Parameters:**

httpSession - httpSession

## com.wowza.wms.module Interface IModuleOnHTTPSmoothStreamingPlayReady

public interface **IModuleOnHTTPSmoothStreamingPlayReady**  
extends

IModuleOnHTTPSmoothStreamingPlayReady: Still working on this...

### Method Summary

void	<a href="#">onHTTPSmoothStreamingPlayReadyCreateLive</a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName, com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)
void	<a href="#">onHTTPSmoothStreamingPlayReadyCreateVOD</a> ( <a href="#">HTTPStreamerSessionSmoothStreamer</a> httpSession, com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)

### Methods

#### onHTTPSmoothStreamingPlayReadyCreateVOD

```
public void onHTTPSmoothStreamingPlayReadyCreateVOD(HTTPStreamerSessionSmoothStreamer
httpSession,
    com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)
```

#### onHTTPSmoothStreamingPlayReadyCreateLive

```
public void onHTTPSmoothStreamingPlayReadyCreateLive(IApplicationInstance appInstance,
    String streamName,
    com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)
```

com.wowza.wms.module

# Interface IModuleOnHTTPSmoothStreamingSession

public interface IModuleOnHTTPSmoothStreamingSession  
extends

IModuleOnHTTPSession: method interface for HTTP Smooth Streaming session create/destroy.

Method Summary	
void	<a href="#">onHTTPSmoothStreamingSessionCreate(HTTPStreamerSessionSmoothStreamer httpSmoothStreamingSession)</a> Invoked when an HTTP Smooth Streaming session is created.
void	<a href="#">onHTTPSmoothStreamingSessionDestroy(HTTPStreamerSessionSmoothStreamer httpSmoothStreamingSession)</a> Invoked when an HTTP Smooth Streaming session is destroyed.

## Methods

### onHTTPSmoothStreamingSessionCreate

public void **onHTTPSmoothStreamingSessionCreate**([HTTPStreamerSessionSmoothStreamer httpSmoothStreamingSession](#))

Invoked when an HTTP Smooth Streaming session is created.

**Parameters:**

httpSmoothStreamingSession - httpSmoothStreamingSession

### onHTTPSmoothStreamingSessionDestroy

public void **onHTTPSmoothStreamingSessionDestroy**([HTTPStreamerSessionSmoothStreamer httpSmoothStreamingSession](#))

Invoked when an HTTP Smooth Streaming session is destroyed.

**Parameters:**

httpSmoothStreamingSession - httpSmoothStreamingSession

---

## com.wowza.wms.module Interface IModuleOnRTPSession

---

public interface **IModuleOnRTPSession**  
extends

IModuleOnRTPSession: method interface for RTP session create/destroy.

---

### Method Summary

void	<a href="#">onRTPSessionCreate(RTPSession rtpSession)</a> Invoked when an RTP Session is created.
void	<a href="#">onRTPSessionDestroy(RTPSession rtpSession)</a> Invoked when an RTP Session is destroyed.

---

### Methods

#### onRTPSessionCreate

public void **onRTPSessionCreate**([RTPSession](#) rtpSession)

Invoked when an RTP Session is created.

**Parameters:**

rtpSession - rtpSession

---

#### onRTPSessionDestroy

public void **onRTPSessionDestroy**([RTPSession](#) rtpSession)

Invoked when an RTP Session is destroyed.

**Parameters:**

rtpSession - rtpSession

---



## com.wowza.wms.module Interface IModuleOnStream

public interface **IModuleOnStream**  
extends

IModuleOnStream: method interface examples for stream level methods in a module.

### Method Summary

void	<a href="#">onStreamCreate</a> ( <a href="#">IMediaStream</a> stream) Invoked when a stream is created.
void	<a href="#">onStreamDestroy</a> ( <a href="#">IMediaStream</a> stream) Invoked when a stream is destroyed.

### Methods

#### onStreamCreate

public void **onStreamCreate**([IMediaStream](#) stream)

Invoked when a stream is created.

**Parameters:**

stream - stream object

#### onStreamDestroy

public void **onStreamDestroy**([IMediaStream](#) stream)

Invoked when a stream is destroyed.

**Parameters:**

stream - stream object

com.wowza.wms.module

# Interface IModulePingResult

public interface **IModulePingResult**  
extends

IModulePingResult: callback interface used by IClient ping.

Method Summary	
void	<a href="#">onResult</a> ( <a href="#">IClient</a> client, long pingTime, int pingId, boolean result) Triggered on client side result from call to IClient.ping.

## Methods

### onResult

```
public void onResult(IClient client,  
                    long pingTime,  
                    int pingId,  
                    boolean result)
```

Triggered on client side result from call to IClient.ping. This method will be called on a success or failure (ping timeout) of a ping.

**Parameters:**

- client - client
- pingTime - time in server time (milliseconds) when the ping was initiated
- pingId - internal server id for the ping request
- result - true is ping was successful false if failure (timeout)

## com.wowza.wms.module Class ModuleBase

java.lang.Object

└-com.wowza.wms.module.ModuleBase

Direct Known Subclasses:

[ModuleProperties](#), [ModuleMediaCasterStreamMonitorAdvanced](#), [ModuleFastPlay](#), [ModuleCore](#), [ModuleClientLogging](#), [ModuleMediaCaster](#)

public abstract class **ModuleBase**  
extends Object

ModuleBase: Base class that all server side modules should extend. Provides basic utility functionality for handling function parameters and return data. Also provides a simplified API for logging.

### Field Summary

public static final	<a href="#">CALLBACK_PARAM1</a> Callback param: param1 Value: <b>1</b>
public static final	<a href="#">CALLBACK_PARAM10</a> Callback param: param10 Value: <b>10</b>
public static final	<a href="#">CALLBACK_PARAM2</a> Callback param: param2 Value: <b>2</b>
public static final	<a href="#">CALLBACK_PARAM3</a> Callback param: param3 Value: <b>3</b>
public static final	<a href="#">CALLBACK_PARAM4</a> Callback param: param4 Value: <b>4</b>
public static final	<a href="#">CALLBACK_PARAM5</a> Callback param: param5 Value: <b>5</b>
public static final	<a href="#">CALLBACK_PARAM6</a> Callback param: param6 Value: <b>6</b>
public static final	<a href="#">CALLBACK_PARAM7</a> Callback param: param7 Value: <b>7</b>

public static final	<a href="#">CALLBACK_PARAM8</a> Callback param: param8 Value: <b>8</b>
public static final	<a href="#">CALLBACK_PARAM9</a> Callback param: param9 Value: <b>9</b>
public static final	<a href="#">PARAM1</a> Method param: param1 Value: <b>3</b>
public static final	<a href="#">PARAM10</a> Method param: param10 Value: <b>12</b>
public static final	<a href="#">PARAM2</a> Method param: param2 Value: <b>4</b>
public static final	<a href="#">PARAM3</a> Method param: param3 Value: <b>5</b>
public static final	<a href="#">PARAM4</a> Method param: param4 Value: <b>6</b>
public static final	<a href="#">PARAM5</a> Method param: param5 Value: <b>7</b>
public static final	<a href="#">PARAM6</a> Method param: param6 Value: <b>8</b>
public static final	<a href="#">PARAM7</a> Method param: param7 Value: <b>9</b>
public static final	<a href="#">PARAM8</a> Method param: param8 Value: <b>10</b>
public static final	<a href="#">PARAM9</a> Method param: param9 Value: <b>11</b>
public static final	<a href="#">PARAMMETHODNAME</a> Method: method name Value: <b>0</b>
public static final	<a href="#">PLAYTRANSITION_APPEND</a> Value: <b>0</b>

public static final	<a href="#"><u>PLAYTRANSITION_APPEND_IMMEDIATE</u></a> Value: <b>2</b>
public static final	<a href="#"><u>PLAYTRANSITION_RESET</u></a> Value: <b>1</b>
public static final	<a href="#"><u>PLAYTRANSITION_RESET_IMMEDIATE</u></a> Value: <b>3</b>
public static final	<a href="#"><u>PLAYTRANSITION_STOP</u></a> Value: <b>10</b>
public static final	<a href="#"><u>PLAYTRANSITION_SWAP</u></a> Value: <b>12</b>
public static final	<a href="#"><u>PLAYTRANSITION_SWITCH</u></a> Value: <b>13</b>
public static final	<a href="#"><u>PLAYTRANSITION_UNKNOWN</u></a> Value: <b>14</b>
public static final	<a href="#"><u>PLAYTRANSITIONSTR_APPEND</u></a> Play2 transition: APPEND Value: <b>append</b>
public static final	<a href="#"><u>PLAYTRANSITIONSTR_RESET</u></a> Play2 transition: RESET Value: <b>reset</b>
public static final	<a href="#"><u>PLAYTRANSITIONSTR_STOP</u></a> Play2 transition: STOP Value: <b>stop</b>
public static final	<a href="#"><u>PLAYTRANSITIONSTR_SWAP</u></a> Play2 transition: SWAP Value: <b>swap</b>
public static final	<a href="#"><u>PLAYTRANSITIONSTR_SWITCH</u></a> Play2 transition: SWITCH Value: <b>switch</b>
public static final	<a href="#"><u>PLAYTRANSITIONSTR_UNKNOWN</u></a> Play2 transition: UNKNOWN Value: <b>unknown</b>

## Constructor Summary

public	<a href="#"><u>ModuleBase()</u></a>
--------	-------------------------------------

## Method Summary

static <a href="#">IApplicationInstance</a>	<a href="#">getAppInstance</a> ( <a href="#">IClient</a> client) Get applicationInstace of a client.
static <a href="#">IApplication</a>	<a href="#">getApplication</a> ( <a href="#">IClient</a> client) Get application of a client.
static int	<a href="#">getCallbackParamCount</a> ( <a href="#">AMFDataList</a> params) Get the total number of parameters passed to callback.
static <a href="#">WMSLogger</a>	<a href="#">getLogger</a> () Get the logging interface.
static <a href="#">AMFData</a>	<a href="#">getParam</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index.
static boolean	<a href="#">getParamBoolean</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as boolean.
static boolean	<a href="#">getParamBoolean</a> ( <a href="#">AMFDataList</a> params, int index, boolean defaultVal) Get parameter by index, Return as boolean.
static int	<a href="#">getParamCount</a> ( <a href="#">AMFDataList</a> params) Get the total number of parameters passed to method.
static java.util.Date	<a href="#">getParamDate</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as Date.
static double	<a href="#">getParamDouble</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as double.
static double	<a href="#">getParamDouble</a> ( <a href="#">AMFDataList</a> params, int index, double defaultVal) Get parameter by index, Return as double.
static int	<a href="#">getParamInt</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as int.
static int	<a href="#">getParamInt</a> ( <a href="#">AMFDataList</a> params, int index, int defaultVal) Get parameter by index, Return as int.
static long	<a href="#">getParamLong</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as long.
static long	<a href="#">getParamLong</a> ( <a href="#">AMFDataList</a> params, int index, long defaultVal) Get parameter by index, Return as long.
static <a href="#">AMFDataMixedArray</a>	<a href="#">getParamMixedArray</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as AMFDataMixedArray.
static <a href="#">AMFDataObj</a>	<a href="#">getParamObj</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as Object.
static String	<a href="#">getParamString</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter by index, Return as String.
static String	<a href="#">getParamString</a> ( <a href="#">AMFDataList</a> params, int index, String defaultVal) Get parameter by index, Return as String.
static int	<a href="#">getParamType</a> ( <a href="#">AMFDataList</a> params, int index) Get parameter type.

static <a href="#">IMediaStream</a>	<a href="#">getStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function) For methods called from the client side object NetStream (publish, play, deleteStream) get the IMediaStream object associated with the call.
static <a href="#">IVHost</a>	<a href="#">getVHost</a> ( <a href="#">IClient</a> client) Get vHost of a client.
void	<a href="#">invokePrevious</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Wowza Pro will determine command priority based on the order of the modules in the module list.
static void	<a href="#">invokePrevious</a> (Object instance, <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Wowza Pro will determine command priority based on the order of the modules in the module list.
static boolean	<a href="#">isSendResult</a> ( <a href="#">AMFDataList</a> params) Is this method call expecting sendResult to be called.
static void	<a href="#">sendClientOnStatusError</a> ( <a href="#">IClient</a> client, String code, String description) Send an error message to the client-side client.onStatus handler
static boolean	<a href="#">sendResult</a> ( <a href="#">IClient</a> client, <a href="#">AMFDataList</a> params, <a href="#">AMFData</a> data) Send a result to client method call as a AMFData object.
static boolean	<a href="#">sendResult</a> ( <a href="#">IClient</a> client, <a href="#">AMFDataList</a> params, boolean value) Send a result to client method call as a single boolean value.
static boolean	<a href="#">sendResult</a> ( <a href="#">IClient</a> client, <a href="#">AMFDataList</a> params, double value) Send a result to client method call as a single double value.
static boolean	<a href="#">sendResult</a> ( <a href="#">IClient</a> client, <a href="#">AMFDataList</a> params, int value) Send a result to client method call as a single int value.
static boolean	<a href="#">sendResult</a> ( <a href="#">IClient</a> client, <a href="#">AMFDataList</a> params, String value) Send a result to client method call as a single String value.
static void	<a href="#">sendStreamOnStatusError</a> ( <a href="#">IMediaStream</a> stream, String code, String description) Send an error to the client-side NetStream.onStatus handler

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### PARAMMETHODNAME

public static final int **PARAMMETHODNAME**

Method: method name  
Constant value: 0

(continued from last page)

## PARAM1

```
public static final int PARAM1
```

Method param: param1  
Constant value: **3**

---

## PARAM2

```
public static final int PARAM2
```

Method param: param2  
Constant value: **4**

---

## PARAM3

```
public static final int PARAM3
```

Method param: param3  
Constant value: **5**

---

## PARAM4

```
public static final int PARAM4
```

Method param: param4  
Constant value: **6**

---

## PARAM5

```
public static final int PARAM5
```

Method param: param5  
Constant value: **7**

---

## PARAM6

```
public static final int PARAM6
```

Method param: param6  
Constant value: **8**

---

## PARAM7

```
public static final int PARAM7
```

Method param: param7  
Constant value: **9**

---

## PARAM8

```
public static final int PARAM8
```

Method param: param8  
Constant value: **10**

---

## PARAM9

```
public static final int PARAM9
```



(continued from last page)

Method param: param9  
Constant value: **11**

---

## PARAM10

public static final int **PARAM10**

Method param: param10  
Constant value: **12**

---

## CALLBACK\_PARAM1

public static final int **CALLBACK\_PARAM1**

Callback param: param1  
Constant value: **1**

---

## CALLBACK\_PARAM2

public static final int **CALLBACK\_PARAM2**

Callback param: param2  
Constant value: **2**

---

## CALLBACK\_PARAM3

public static final int **CALLBACK\_PARAM3**

Callback param: param3  
Constant value: **3**

---

## CALLBACK\_PARAM4

public static final int **CALLBACK\_PARAM4**

Callback param: param4  
Constant value: **4**

---

## CALLBACK\_PARAM5

public static final int **CALLBACK\_PARAM5**

Callback param: param5  
Constant value: **5**

---

## CALLBACK\_PARAM6

public static final int **CALLBACK\_PARAM6**

Callback param: param6  
Constant value: **6**

---

## CALLBACK\_PARAM7

public static final int **CALLBACK\_PARAM7**

Callback param: param7  
Constant value: **7**

---

## CALLBACK\_PARAM8

```
public static final int CALLBACK_PARAM8
```

Callback param: param8  
Constant value: **8**

---

## CALLBACK\_PARAM9

```
public static final int CALLBACK_PARAM9
```

Callback param: param9  
Constant value: **9**

---

## CALLBACK\_PARAM10

```
public static final int CALLBACK_PARAM10
```

Callback param: param10  
Constant value: **10**

---

## PLAYTRANSITIONSTR\_APPEND

```
public static final java.lang.String PLAYTRANSITIONSTR_APPEND
```

Play2 transition: APPEND  
Constant value: **append**

---

## PLAYTRANSITIONSTR\_RESET

```
public static final java.lang.String PLAYTRANSITIONSTR_RESET
```

Play2 transition: RESET  
Constant value: **reset**

---

## PLAYTRANSITIONSTR\_STOP

```
public static final java.lang.String PLAYTRANSITIONSTR_STOP
```

Play2 transition: STOP  
Constant value: **stop**

---

## PLAYTRANSITIONSTR\_SWAP

```
public static final java.lang.String PLAYTRANSITIONSTR_SWAP
```

Play2 transition: SWAP  
Constant value: **swap**

---

## PLAYTRANSITIONSTR\_SWITCH

```
public static final java.lang.String PLAYTRANSITIONSTR_SWITCH
```

Play2 transition: SWITCH  
Constant value: **switch**

---

(continued from last page)

---

## PLAYTRANSITIONSTR\_UNKNOWN

```
public static final java.lang.String PLAYTRANSITIONSTR_UNKNOWN
```

Play2 transition: UNKNOWN  
Constant value: **unknown**

---

## PLAYTRANSITION\_APPEND

```
public static final int PLAYTRANSITION_APPEND
```

Constant value: **0**

---

## PLAYTRANSITION\_RESET

```
public static final int PLAYTRANSITION_RESET
```

Constant value: **1**

---

## PLAYTRANSITION\_APPEND\_IMMEDIATE

```
public static final int PLAYTRANSITION_APPEND_IMMEDIATE
```

Constant value: **2**

---

## PLAYTRANSITION\_RESET\_IMMEDIATE

```
public static final int PLAYTRANSITION_RESET_IMMEDIATE
```

Constant value: **3**

---

## PLAYTRANSITION\_STOP

```
public static final int PLAYTRANSITION_STOP
```

Constant value: **10**

---

## PLAYTRANSITION\_SWAP

```
public static final int PLAYTRANSITION_SWAP
```

Constant value: **12**

---

## PLAYTRANSITION\_SWITCH

```
public static final int PLAYTRANSITION_SWITCH
```

Constant value: **13**

---

## PLAYTRANSITION\_UNKNOWN

```
public static final int PLAYTRANSITION_UNKNOWN
```

---

(continued from last page)

Constant value: **14**

## Constructors

### ModuleBase

```
public ModuleBase( )
```

## Methods

### getParamCount

```
protected static int getParamCount(AMFDataList params)
```

Get the total number of parameters passed to method.

**Parameters:**

params - parameters

**Returns:**

total number of parameters

### getCallbackParamCount

```
protected static int getCallbackParamCount(AMFDataList params)
```

Get the total number of parameters passed to callback.

**Parameters:**

params - parameters

**Returns:**

total number of parameters

### getParamType

```
protected static int getParamType(AMFDataList params,  
int index)
```

Get parameter type.

**Parameters:**

params - parameters

index - parameter index

**Returns:**

parameter type (AMFData.DATA\_TYPE\_\*)

### getParam

```
protected static AMFData getParam(AMFDataList params,  
int index)
```

Get parameter by index. Return as AMFData object.

(continued from last page)

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as AMFData object, null if out of bounds

---

## getParamMixedArray

```
protected static AMFDataMixedArray getParamMixedArray(AMFDataList params,  
int index)
```

Get parameter by index, Return as AMFDataMixedArray.

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as AMFDataMixedArray object, null if out of bounds

---

## getParamObj

```
protected static AMFDataObj getParamObj(AMFDataList params,  
int index)
```

Get parameter by index, Return as Object.

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as Object object, null if out of bounds

---

## getParamString

```
protected static String getParamString(AMFDataList params,  
int index)
```

Get parameter by index, Return as String.

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as String object, null if out of bounds

---

## getParamString

```
protected static String getParamString(AMFDataList params,  
int index,  
String defaultVal)
```

Get parameter by index, Return as String.

**Parameters:**

params - parameters

---

(continued from last page)

index - parameter index  
defaultVal - default value

**Returns:**

parameter value as String object, defaultVal if out of bounds

---

## getParamDate

```
protected static java.util.Date getParamDate(AMFDataList params,  
int index)
```

Get parameter by index, Return as Date.

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as Date object, null if out of bounds

---

## getParamInt

```
protected static int getParamInt(AMFDataList params,  
int index)
```

Get parameter by index, Return as int.

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as int, 0 if out of bounds

---

## getParamInt

```
protected static int getParamInt(AMFDataList params,  
int index,  
int defaultVal)
```

Get parameter by index, Return as int.

**Parameters:**

params - parameters  
index - parameter index  
defaultVal - default value

**Returns:**

parameter value as int, defaultVal if out of bounds

---

## getParamDouble

```
protected static double getParamDouble(AMFDataList params,  
int index)
```

Get parameter by index, Return as double.

**Parameters:**

params - parameters

---

(continued from last page)

index - parameter index

**Returns:**

parameter value as double, 0 if out of bounds

---

## getParamDouble

```
protected static double getParamDouble(AMFDataList params,  
    int index,  
    double defaultVal)
```

Get parameter by index, Return as double.

**Parameters:**

params - parameters  
index - parameter index  
defaultVal - default value

**Returns:**

parameter value as double, 0 if out of bounds

---

## getParamLong

```
protected static long getParamLong(AMFDataList params,  
    int index)
```

Get parameter by index, Return as long.

**Parameters:**

params - parameters  
index - parameter index

**Returns:**

parameter value as long, 0 if out of bounds

---

## getParamLong

```
protected static long getParamLong(AMFDataList params,  
    int index,  
    long defaultVal)
```

Get parameter by index, Return as long.

**Parameters:**

params - parameters  
index - parameter index  
defaultVal - default value

**Returns:**

parameter value as long, defaultVal if out of bounds

---

## getParamBoolean

```
protected static boolean getParamBoolean(AMFDataList params,  
    int index)
```

Get parameter by index, Return as boolean.

**Parameters:**

params - parameters

---

(continued from last page)

index - parameter index

**Returns:**

parameter value as boolean, false if out of bounds

---

## getParamBoolean

```
protected static boolean getParamBoolean(AMFDataList params,  
int index,  
boolean defaultVal)
```

Get parameter by index, Return as boolean.

**Parameters:**

params - parameters  
index - parameter index  
defaultVal - default value

**Returns:**

parameter value as boolean, defaultVal if out of bounds

---

## getAppInstance

```
protected static IApplicationInstance getAppInstance(IClient client)
```

Get applicationInstance of a client.

**Parameters:**

client - client

**Returns:**

applicationInstance

---

## getApplication

```
protected static IApplication getApplication(IClient client)
```

Get application of a client.

**Parameters:**

client - client

**Returns:**

application

---

## isSendResult

```
protected static boolean isSendResult(AMFDataList params)
```

Is this method call expecting sendResult to be called. If on the client side the call to `NetConnection.call("handlerName", resultObj, param1...)` had a value for resultObj (non-null), then the method is expecting some type of result or return data. Calling a variant of sendResult will provide this callback.

**Parameters:**

params - parameters

**Returns:**

true if client side call is expecting call to sendResult

---



## getVHost

protected static [IVHost](#) **getVHost**([IClient](#) client)

Get vHost of a client.

**Parameters:**

client - client

**Returns:**

vHost

---

## sendResult

protected static boolean **sendResult**([IClient](#) client,  
[AMFDataList](#) params,  
String value)

Send a result to client method call as a single String value.

**Parameters:**

client - client

params - parameters

value - return value

**Returns:**

true if client side call is expecting call to sendResult

---

## sendResult

protected static boolean **sendResult**([IClient](#) client,  
[AMFDataList](#) params,  
boolean value)

Send a result to client method call as a single boolean value.

**Parameters:**

client - client

params - parameters

value - return value

**Returns:**

true if client side call is expecting call to sendResult

---

## sendResult

protected static boolean **sendResult**([IClient](#) client,  
[AMFDataList](#) params,  
int value)

Send a result to client method call as a single int value.

**Parameters:**

client - client

params - parameters

value - return value

**Returns:**

true if client side call is expecting call to sendResult

---

## sendResult

```
protected static boolean sendResult(IClient client,  
    AMFDataList params,  
    double value)
```

Send a result to client method call as a single double value.

**Parameters:**

client - client  
params - parameters  
value - return value

**Returns:**

true if client side call is expecting call to sendResult

---

## sendResult

```
protected static boolean sendResult(IClient client,  
    AMFDataList params,  
    AMFData data)
```

Send a result to client method call as a AMFData object. This can be a single AMFData value like new AMFDataItem((double)1.234) or a complex type like AMFDataMixedArray, AMFDataArray or AMFDataObj.

**Parameters:**

client - client  
params - parameters  
data - return value

**Returns:**

true if client side call is expecting call to sendResult

---

## getLogger

```
protected static WMSLogger getLogger()
```

Get the logging interface.

**See Also:**

[WMSLogger](#)

---

## getStream

```
protected static IMediaStream getStream(IClient client,  
    com.wowza.wms.request.RequestFunction function)
```

For methods called from the client side object NetStream (publish, play, deleteStream) get the IMediaStream object associated with the call.

**Parameters:**

client - client  
function - functions

**Returns:**

media stream

---

(continued from last page)

## invokePrevious

```
protected static void invokePrevious(Object instance,
    IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Wowza Pro will determine command priority based on the order of the modules in the module list. Wowza Pro by default will only invoke the last module that defines a given command. This method enables you to call the method by the same name in the previous module that defines that command. For example if you have three modules defined in the module list; ModuleCore, ModuleSecureURLParams and ModuleMyModule and all three modules implement the "play" command. When "play" is invoked it will invoke the "play" command in ModuleMyModule. If in ModuleMyModule you would like to call the "play" command in ModuleSecureURLParams, you can call: invokePrevious(this, client, function, params); and it will invoke the "play" command defined in ModuleSecureURLParams.

### Parameters:

instance - instance of the current module  
 client - client object passed into command  
 function - function passed into command  
 params - parameters passed into command

## invokePrevious

```
protected void invokePrevious(IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Wowza Pro will determine command priority based on the order of the modules in the module list. Wowza Pro by default will only invoke the last module that defines a given command. This method enables you to call the method by the same name in the previous module that defines that command. For example if you have three modules defined in the module list; ModuleCore, ModuleSecureURLParams and ModuleMyModule and all three modules implement the "play" command. When "play" is invoked it will invoke the "play" command in ModuleMyModule. If in ModuleMyModule you would like to call the "play" command in ModuleSecureURLParams, you can call: this.invokePrevious(client, function, params); and it will invoke the "play" command defined in ModuleSecureURLParams.

### Parameters:

client - client object passed into command  
 function - function passed into command  
 params - parameters passed into command

## sendClientOnStatusError

```
protected static void sendClientOnStatusError(IClient client,
    String code,
    String description)
```

Send an error message to the client-side client.onStatus handler

### Parameters:

client - destination client  
 code - code  
 description - description

## sendStreamOnStatusError

```
protected static void sendStreamOnStatusError(IMediaStream stream,
    String code,
    String description)
```

Send an error to the client-side NetStream.onStatus handler


### Parameters:

(continued from last page)

stream - destination stream  
code - code  
description - description

## com.wowza.wms.module Class ModuleClientLogging

java.lang.Object



public class **ModuleClientLogging**  
extends [ModuleBase](#)

### Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK\\_PARAM1](#), [CALLBACK\\_PARAM10](#), [CALLBACK\\_PARAM2](#), [CALLBACK\\_PARAM3](#), [CALLBACK\\_PARAM4](#), [CALLBACK\\_PARAM5](#), [CALLBACK\\_PARAM6](#), [CALLBACK\\_PARAM7](#), [CALLBACK\\_PARAM8](#), [CALLBACK\\_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION\\_APPEND](#), [PLAYTRANSITION\\_APPEND\\_IMMEDIATE](#), [PLAYTRANSITION\\_RESET](#), [PLAYTRANSITION\\_RESET\\_IMMEDIATE](#), [PLAYTRANSITION\\_STOP](#), [PLAYTRANSITION\\_SWAP](#), [PLAYTRANSITION\\_SWITCH](#), [PLAYTRANSITION\\_UNKNOWN](#), [PLAYTRANSITIONSTR\\_APPEND](#), [PLAYTRANSITIONSTR\\_RESET](#), [PLAYTRANSITIONSTR\\_STOP](#), [PLAYTRANSITIONSTR\\_SWAP](#), [PLAYTRANSITIONSTR\\_SWITCH](#), [PLAYTRANSITIONSTR\\_UNKNOWN](#)

### Constructor Summary

public	<a href="#">ModuleClientLogging()</a>
--------	---------------------------------------

### Method Summary

static void	<a href="#">logDebug</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Send a debug message to the logging system NetConnection.call("logDebug", null, message);
static void	<a href="#">logError</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Send a error message to the logging system NetConnection.call("logError", null, message);
static void	<a href="#">logInfo</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Send a info message to the logging system NetConnection.call("logInfo", null, message);
static void	<a href="#">logWarn</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Send a warning message to the logging system NetConnection.call("logWarn", null, message);

### Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

**Methods inherited from class `java.lang.Object`**

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### ModuleClientLogging

```
public ModuleClientLogging()
```

## Methods

### logDebug

```
public static void logDebug(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a debug message to the logging system `NetConnection.call("logDebug", null, message);`

**Parameters:**

`client` - client  
`function` - function  
`params` - params (message)

### logInfo

```
public static void logInfo(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a info message to the logging system `NetConnection.call("logInfo", null, message);`

**Parameters:**

`client` - client  
`function` - function  
`params` - params (message)

### logWarn

```
public static void logWarn(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a warning message to the logging system `NetConnection.call("logWarn", null, message);`

**Parameters:**

`client` - client  
`function` - function  
`params` - params (message)

(continued from last page)

## logError

```
public static void logError(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a error message to the logging system `NetConnection.call("logError", null, message);`

### Parameters:

client - client

function - function

params - params (message)

## com.wowza.wms.module Class ModuleCore

```
java.lang.Object
|
+-com.wowza.wms.module.ModuleBase
|
+-com.wowza.wms.module.ModuleCore
```

```
public class ModuleCore
extends ModuleBase
```

ModuleCore includes all the basic commands support by the NetStream and NetConnection client side objects. Any of these methods can be overwritten in a custom module. Below is an example of custom module that overrides the play method to modify the name of the file to be played:

```
package com.wowza.wms.plugin.overrideexample;

import com.wowza.wms.amf.*;
import com.wowza.wms.client.*;
import com.wowza.wms.module.*;
import com.wowza.wms.request.*;

public class ModuleOverrideExample extends ModuleBase
{
    public void play(IClient client, RequestFunction function, AMFDataList params)
    {
        if (params.get(PARAM1).getType() == AMFData.DATA_TYPE_STRING)
        {
            String playName = params.getString(PARAM1);
            params.set(PARAM1, new AMFDataItem(playName+"_newname"));
        }
        this.invokePrevious(client, function, params);
    }
}
```

### Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK\\_PARAM1](#), [CALLBACK\\_PARAM10](#), [CALLBACK\\_PARAM2](#), [CALLBACK\\_PARAM3](#), [CALLBACK\\_PARAM4](#), [CALLBACK\\_PARAM5](#), [CALLBACK\\_PARAM6](#), [CALLBACK\\_PARAM7](#), [CALLBACK\\_PARAM8](#), [CALLBACK\\_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION\\_APPEND](#), [PLAYTRANSITION\\_APPEND\\_IMMEDIATE](#), [PLAYTRANSITION\\_RESET](#), [PLAYTRANSITION\\_RESET\\_IMMEDIATE](#), [PLAYTRANSITION\\_STOP](#), [PLAYTRANSITION\\_SWAP](#), [PLAYTRANSITION\\_SWITCH](#), [PLAYTRANSITION\\_UNKNOWN](#), [PLAYTRANSITIONSTR\\_APPEND](#), [PLAYTRANSITIONSTR\\_RESET](#), [PLAYTRANSITIONSTR\\_STOP](#), [PLAYTRANSITIONSTR\\_SWAP](#), [PLAYTRANSITIONSTR\\_SWITCH](#), [PLAYTRANSITIONSTR\\_UNKNOWN](#)

## Constructor Summary



public	<a href="#">ModuleCore()</a>
--------	------------------------------

## Method Summary

static void	<a href="#">closeStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.close();
static void	<a href="#">createStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Create new server side NetStream object (internal to Flash workings).
static void	<a href="#">deleteStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Delete server side stream object (internal to Flash workings).
static void	<a href="#">FCPublish</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) FCPublish method called by FME 2.5
static void	<a href="#">FCSubscribe</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) FCSubscribe subscribes to a live stream (if origin edge will start the stream from the origin to the edge)
static void	<a href="#">FCUnpublish</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) FCUnpublish method called by FME 2.5
static void	<a href="#">FCUnpublish</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) FCUnpublish method called by FME 2.5
static void	<a href="#">FCUnsubscribe</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) FCUnSubscribe to a live stream
static void	<a href="#">FCUnsubscribe</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params)
static void	<a href="#">getClientID</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the clientId for a client connection NetConnection.call("getClientID", resultObj);
static void	<a href="#">getLastStreamId</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the id for the last created stream NetConnection.call("getLastStreamId", resultObj);
static void	<a href="#">getLiveStreamPacketizer</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the live stream packetizer list for a client connection NetConnection.call("getLiveStreamPacketizer", resultObj);
static void	<a href="#">getPageUrl</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) getPageUrl returns the pageUrl from the onConnect metadata
static void	<a href="#">getReferrer</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) getReferrer returns the referrer from the onConnect metadata

static void	<a href="#">getRepeaterOriginUrl</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the Repeater Origin URL for this client
void	<a href="#">getStreamBitrate</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get stream bitrate in bits-per-second for a video on demand stream (will not work for live).
static void	<a href="#">getStreamLength</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get stream length in seconds NetConnection.call("getStreamLength", resultObj, streamName); If you pass in an array of streamNames it will return an array of durations.
static void	<a href="#">getStreamType</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the default stream type for a client connection NetConnection.call("getStreamType", resultObj);
static void	<a href="#">getVersion</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get the Wowza Pro server version and build number NetConnection.call("getVersion", resultObj);
static void	<a href="#">initLiveStreamRepeating</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Initialize a stream for live stream repeating
static void	<a href="#">initStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Create new server side NetStream object (internal to Flash workings).
static void	<a href="#">pause</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.pause([ flag : Boolean]);
static void	<a href="#">pauseRaw</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) pauseRaw method introduced in Flash player 10
static void	<a href="#">play</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.play(name : Object [,start : Number[, len : Number[, reset : Object]]]);
static void	<a href="#">play2</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.play(playOptions : NetStreamPlayOptions);
static void	<a href="#">publish</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.publish(name : String [, howToPublish : String]);
static void	<a href="#">receiveAudio</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.receiveAudio(receive : Boolean);
static void	<a href="#">receiveVideo</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.receiveVideo(receive : Boolean   FPS : Number); FPS does not work the same as FMS.
static void	<a href="#">releaseStream</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params)

static void	<a href="#">seek</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.seek(offset : Number);
static void	<a href="#">setBandwidthLimit</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params)
static void	<a href="#">setBufferTime</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Server side implementation of NetStream.setBufferTime(bufferTime : Number);
static void	<a href="#">setLiveStreamPacketizer</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set the live stream packetizer for a stream
static void	<a href="#">setRepeaterOriginUrl</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set the Repeater Origin URL for this client
static void	<a href="#">setStreamType</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set the default stream type for a client connection NetConnection.call("setStreamType", null, streamType);

#### Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

#### Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

## Constructors

### ModuleCore

```
public ModuleCore()
```

## Methods

### createStream

```
public static void createStream(IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Create new server side NetStream object (internal to Flash workings).

#### Parameters:

(continued from last page)

client - client  
function - function  
params - parameters (no params)

---

## initStream

```
public static void initStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Create new server side NetStream object (internal to Flash workings).

### Parameters:

client - client  
function - function  
params - parameters (streamIndex, boolean)

---

## releaseStream

```
public static void releaseStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

---

## getLastStreamId

```
public static void getLastStreamId(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the id for the last created stream NetConnection.call("getLastStreamId", resultObj);

### Parameters:

client - client  
function - client  
params - params (no params)

---

## deleteStream

```
public static void deleteStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Delete server side stream object (internal to Flash workings).

### Parameters:

client - client  
function - function  
params - params

---

## publish

```
public static void publish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.publish(name : String [, howToPublish : String]);

### Parameters:

(continued from last page)

client - client  
function - function  
params - params (name [if name = "false" or "null" stop publishing], howToPublish ["record", "live", "append"])

---

## setBandwidthLimit

```
public static void setBandwidthLimit(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

---

## play2

```
public static void play2(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.play(playOptions : NetStreamPlayOptions);

### Parameters:

client  
function  
params

---

## play

```
public static void play(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.play(name : Object [,start : Number[, len : Number[, reset : Object]]]);

### Parameters:

client - client  
function - function  
params - params (name, start, len, reset)

---

## closeStream

```
public static void closeStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.close();

### Parameters:

client - client  
function - function  
params - params (no params)

---

## seek

```
public static void seek(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.seek(offset : Number);

### Parameters:

(continued from last page)

client - client  
function - function  
params - params (offset)

---

## pause

```
public static void pause(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.pause([ flag : Boolean]);

### Parameters:

client - client  
function - function  
params - params (flag)

---

## setBufferTime

```
public static void setBufferTime(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.setBufferTime(bufferTime : Number);

### Parameters:

client - client  
function - function  
params - params (bufferTime)

---

## getClientID

```
public static void getClientID(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the clientId for a client connection NetConnection.call("getClientID", resultObj);

### Parameters:

client - client  
function - function  
params - params (no params)

---

## getVersion

```
public static void getVersion(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the Wowza Pro server version and build number NetConnection.call("getVersion", resultObj);

### Parameters:

client - client  
function - function  
params - params (no params)

---

(continued from last page)

---

## setLiveStreamPacketizer

```
public static void setLiveStreamPacketizer(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set the live stream packetizer for a stream

### Parameters:

client - client  
function - function  
params - params (liveStreamPacketizer)

---

## initLiveStreamRepeating

```
public static void initLiveStreamRepeating(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Initialize a stream for live stream repeating

### Parameters:

client - client  
function - function  
params - params (liveStreamPacketizer, liveStreamRepeater)

---

## getLiveStreamPacketizer

```
public static void getLiveStreamPacketizer(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the live stream packetizer list for a client connection `NetConnection.call("getLiveStreamPacketizer", resultObj);`

### Parameters:

client - client  
function - function  
params - params (no params)

---

## setStreamType

```
public static void setStreamType(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set the default stream type for a client connection `NetConnection.call("setStreamType", null, streamType);`

### Parameters:

client - client  
function - function  
params - params (streamType)

---

## getStreamType

```
public static void getStreamType(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the default stream type for a client connection `NetConnection.call("getStreamType", resultObj);`

(continued from last page)

**Parameters:**

client - client  
function - function  
params - params (no params)

---

## receiveAudio

```
public static void receiveAudio(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.receiveAudio(receive : Boolean);

**Parameters:**

client - client  
function - function  
params - params (receive)

---

## receiveVideo

```
public static void receiveVideo(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.receiveVideo(receive : Boolean | FPS : Number); FPS does not work the same as FMS. Wowza Pro accepts the following values:

- true: Send all video frames
- false: Send no video
- -1: Send all video frames
- -2: Send half the frames (remove B frames) (Note: only works with Sorenson Spark video with B-frames)
- -3: Send only key frames

**Parameters:**

client - client  
function - function  
params - params (receive | FPS)

---

## getStreamBitrate

```
public void getStreamBitrate(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get stream bitrate in bits-per-second for a video on demand stream (will not work for live). To call, NetConnection.call("getStreamBitrate", resultObj, streamName);

**Parameters:**

client - client  
function - function  
params - params (streamName:String)

---

## getStreamLength

```
public static void getStreamLength(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```



(continued from last page)

Get stream length in seconds `NetConnection.call("getStreamLength", resultObj, streamName)`; If you pass in an array of streamNames it will return an array of durations.

**Parameters:**

client - client  
function - function  
params - params (streamName:String or streamNames:Array)

---

## getRepeaterOriginUrl

```
public static void getRepeaterOriginUrl(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the Repeater Origin URL for this client

**Parameters:**

client - client  
function - function  
params - params

---

## setRepeaterOriginUrl

```
public static void setRepeaterOriginUrl(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set the Repeater Origin URL for this client

**Parameters:**

client - client  
function - function  
params - params (repeaterOriginUrl)

---

## FCPublish

```
public static void FCPublish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCPublish method called by FME 2.5

**Parameters:**

client - client  
function - function  
params - params

---

## FCUnPublish

```
public static void FCUnPublish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCUnpublish method called by FME 2.5

**Parameters:**

client - client  
function - function  
params - params

## FCUnpublish

```
public static void FCUnpublish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

---

## pauseRaw

```
public static void pauseRaw(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

pauseRaw method introduced in Flash player 10

### Parameters:

client - client  
function - function  
params - params

---

## getReferrer

```
public static void getReferrer(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

getReferrer returns the referrer from the onConnect metadata

### Parameters:

client - client  
function - function  
params - params

---

## getPageUrl

```
public static void getPageUrl(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

getPageUrl returns the pageUrl from the onConnect metadata

### Parameters:

client - client  
function - function  
params - params

---

## FCSubscribe

```
public static void FCSubscribe(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCSubscribe subscribes to a live stream (if origin edge will start the stream from the origin to the edge)

### Parameters:

client - client  
function - function  
params - params (streamName:String, [mediaCasterType:String])

---

## FCUnsubscribe

```
public static void FCUnsubscribe(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCUnSubscribe to a live stream

### Parameters:

client - client

function - function

params - params (streamName:String)


---

## FCUnSubscribe

```
public static void FCUnSubscribe(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

## com.wowza.wms.module Class ModuleFastPlay

java.lang.Object



public class **ModuleFastPlay**  
extends [ModuleBase](#)

### Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK\\_PARAM1](#), [CALLBACK\\_PARAM10](#), [CALLBACK\\_PARAM2](#), [CALLBACK\\_PARAM3](#), [CALLBACK\\_PARAM4](#),  
[CALLBACK\\_PARAM5](#), [CALLBACK\\_PARAM6](#), [CALLBACK\\_PARAM7](#), [CALLBACK\\_PARAM8](#), [CALLBACK\\_PARAM9](#), [PARAM1](#),  
[PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#),  
[PLAYTRANSITION\\_APPEND](#), [PLAYTRANSITION\\_APPEND\\_IMMEDIATE](#), [PLAYTRANSITION\\_RESET](#),  
[PLAYTRANSITION\\_RESET\\_IMMEDIATE](#), [PLAYTRANSITION\\_STOP](#), [PLAYTRANSITION\\_SWAP](#),  
[PLAYTRANSITION\\_SWITCH](#), [PLAYTRANSITION\\_UNKNOWN](#), [PLAYTRANSITIONSTR\\_APPEND](#),  
[PLAYTRANSITIONSTR\\_RESET](#), [PLAYTRANSITIONSTR\\_STOP](#), [PLAYTRANSITIONSTR\\_SWAP](#),  
[PLAYTRANSITIONSTR\\_SWITCH](#), [PLAYTRANSITIONSTR\\_UNKNOWN](#)

### Constructor Summary

public	<a href="#">ModuleFastPlay()</a>
--------	----------------------------------

### Method Summary

static void	<a href="#">setFastPlay</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Turn on fast play NetStream.call("setFastPlay", null, multiplier, frames-per-second, direction);
-------------	--

### Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#),  
[getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#),  
[getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#),  
[getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#),  
[getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#),  
[sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#),  
[sendStreamOnStatusError](#)

### Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#),  
[wait](#)

### Constructors

(continued from last page)

## ModuleFastPlay

```
public ModuleFastPlay()
```

## Methods

### setFastPlay

```
public static void setFastPlay(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Turn on fast play NetStream.call("setFastPlay", null, multiplier, frames-per-second, direction);

#### Parameters:

client - client

function - function

params - params (multiplier, frames-per-second, direction)

## com.wowza.wms.module Class ModuleMediaCasterStreamMonitorAdvanced

```
java.lang.Object
|
+-com.wowza.wms.module.ModuleBase
|
+-com.wowza.wms.module.ModuleMediaCasterStreamMonitorAdvanced
```

All Implemented Interfaces:

[IMediaCasterValidateMediaCaster](#)

```
public class ModuleMediaCasterStreamMonitorAdvanced
extends ModuleBase
implements IMediaCasterValidateMediaCaster
```

ModuleMediaCasterStreamMonitorAdvanced: Advanced stream monitoring module.

Add this <Module> definition to the end of the <Modules> list in [install-dir]/conf/[application]/Application.xml:

```
<Module>
  <Name>ModuleMediaCasterStreamMonitorAdvanced</Name>
  <Description>ModuleMediaCasterStreamMonitorAdvanced</Description>
  <Class>com.wowza.wms.module.ModuleMediaCasterStreamMonitorAdvanced</Class>
</Module>
```

Add these properties to the application level <Properties> container at the bottom of [install-dir]/conf/[application]/Application.xml (be sure to get the correct <Properties> container - there are several in the Application.xml file). Carefully read the instructions above each set of properties and set accordingly:

```

<!--
Monitor incoming packets (stream, audio, video) to be sure packets continue to flow from
encoder to stream. The
streamMonitor[type]StartTimeout controls the timeout (milliseconds) for the first packet. The
streamMonitor[type]Timeout
controls the timeout (milliseconds) for packets after the first packet. The stream type
refers to a catch all of any packet of
any type (audio, video, data). If any of these values are set to zero, the test is turned
off.
-->
<Property>
    <Name>streamMonitorStreamStartTimeout</Name>
    <Value>20000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorStreamTimeout</Name>
    <Value>12000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorVideoStartTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorVideoTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioStartTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>

<!--
Monitor the incoming packet timecodes (audio, video or data) to be sure packets do not arrive
out of order or late. The
streamMonitor[type]TCPosTolerance and streamMonitor[type]TCNegTolerance (milliseconds) values
define a sliding window
based on the timecode of the previous packet. For example if these values are set to -500 and
3000 respectively then the
timecode difference between the current arriving packet and the previous packet of that type
must fall within
-500 and 3000 milliseconds. If not and streamMonitor[type]TCToleranceEnable is set to true

```

then stream will be considered  
unhealthy and will be reset.

-->

```
<Property>
    <Name>streamMonitorVideoTCToleranceEnable</Name>
    <Value>>false</Value>
    <Type>Boolean</Type>
</Property>
<Property>
    <Name>streamMonitorVideoTCPosTolerance</Name>
    <Value>3000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorVideoTCNegTolerance</Name>
    <Value>-500</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTCToleranceEnable</Name>
    <Value>>false</Value>
    <Type>Boolean</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTCPosTolerance</Name>
    <Value>3000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTCNegTolerance</Name>
    <Value>-500</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorDataTCToleranceEnable</Name>
    <Value>>false</Value>
    <Type>Boolean</Type>
</Property>
<Property>
    <Name>streamMonitorDataTCPosTolerance</Name>
    <Value>3000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorDataTCNegTolerance</Name>
    <Value>-500</Value>
    <Type>Integer</Type>
</Property>

<!--
```



Monitors the time difference between the audio and video channel of a stream. If the difference between the currently arriving video packet and the previous audio packet (or vice-versa) is greater than streamMonitorAVSyncTolerance and streamMonitorAVSyncToleranceEnable is set to true, then the stream will be considered unhealthy and will be reset.

```
-->
```

```
<Property>
```

```
    <Name>streamMonitorAVSyncToleranceEnable</Name>
```

```
    <Value>>false</Value>
```

```
    <Type>Boolean</Type>
```

```
</Property>
```

```
<Property>
```

```
    <Name>streamMonitorAVSyncTolerance</Name>
```

```
    <Value>1500</Value>
```

```
    <Type>Integer</Type>
```

```
</Property>
```

```
<!--
```

If set to true, then when a stream is reset and it belong to a MediaStreamNameGroup all streams in the group will be reset. If false only the unhealthy stream will be reset.

```
-->
```

```
<Property>
```

```
    <Name>streamMonitorResetNameGroups</Name>
```

```
    <Value>>true</Value>
```

```
    <Type>Boolean</Type>
```

```
</Property>
```

```
<!--
```

Turns on debug logging of the monitoring.

```
-->
```

```
<Property>
```

```
    <Name>streamMonitorDebug</Name>
```

```
    <Value>>false</Value>
```

```
    <Type>Boolean</Type>
```

```
</Property>
```

## Field Summary

protected	<a href="#">appInstance</a>
protected	<a href="#">badStreams</a>
protected	<a href="#">monitors</a>
protected	<a href="#">streamMonitorAudioStartTimeout</a>

protected	<a href="#">streamMonitorAudioTCNegTolerance</a>
protected	<a href="#">streamMonitorAudioTCPosTolerance</a>
protected	<a href="#">streamMonitorAudioTCToleranceEnable</a>
protected	<a href="#">streamMonitorAudioTimeout</a>
protected	<a href="#">streamMonitorAVSyncTolerance</a>
protected	<a href="#">streamMonitorAVSyncToleranceEnable</a>
protected	<a href="#">streamMonitorDataTCNegTolerance</a>
protected	<a href="#">streamMonitorDataTCPosTolerance</a>
protected	<a href="#">streamMonitorDataTCToleranceEnable</a>
protected	<a href="#">streamMonitorDebug</a>
protected	<a href="#">streamMonitorResetNameGroups</a>
protected	<a href="#">streamMonitorStreamStartTimeout</a>
protected	<a href="#">streamMonitorStreamTimeout</a>
protected	<a href="#">streamMonitorVideoStartTimeout</a>
protected	<a href="#">streamMonitorVideoTCNegTolerance</a>
protected	<a href="#">streamMonitorVideoTCPosTolerance</a>
protected	<a href="#">streamMonitorVideoTCToleranceEnable</a>
protected	<a href="#">streamMonitorVideoTimeout</a>

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK\\_PARAM1](#), [CALLBACK\\_PARAM10](#), [CALLBACK\\_PARAM2](#), [CALLBACK\\_PARAM3](#), [CALLBACK\\_PARAM4](#), [CALLBACK\\_PARAM5](#), [CALLBACK\\_PARAM6](#), [CALLBACK\\_PARAM7](#), [CALLBACK\\_PARAM8](#), [CALLBACK\\_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION\\_APPEND](#), [PLAYTRANSITION\\_APPEND\\_IMMEDIATE](#), [PLAYTRANSITION\\_RESET](#), [PLAYTRANSITION\\_RESET\\_IMMEDIATE](#), [PLAYTRANSITION\\_STOP](#), [PLAYTRANSITION\\_SWAP](#), [PLAYTRANSITION\\_SWITCH](#), [PLAYTRANSITION\\_UNKNOWN](#), [PLAYTRANSITIONSTR\\_APPEND](#), [PLAYTRANSITIONSTR\\_RESET](#), [PLAYTRANSITIONSTR\\_STOP](#), [PLAYTRANSITIONSTR\\_SWAP](#), [PLAYTRANSITIONSTR\\_SWITCH](#), [PLAYTRANSITIONSTR\\_UNKNOWN](#)

## Constructor Summary

public	<a href="#">ModuleMediaCasterStreamMonitorAdvanced()</a>
--------	--

## Method Summary

void	<a href="#">onAppStart</a> ( <a href="#">IApplicationInstance</a> appInstance)
void	<a href="#">onAppStop</a> ( <a href="#">IApplicationInstance</a> appInstance)
boolean	<a href="#">onResetMediaCaster</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaCaster</a> mediaCaster)
void	<a href="#">onStreamCreate</a> ( <a href="#">IMediaStream</a> stream)
void	<a href="#">onStreamDestroy</a> ( <a href="#">IMediaStream</a> stream)
boolean	<a href="#">onValidateMediaCaster</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaCaster</a> mediaCaster)
void	<a href="#">onValidateMediaCastersStart</a> ( <a href="#">IApplicationInstance</a> appInstance)
void	<a href="#">onValidateMediaCastersStop</a> ( <a href="#">IApplicationInstance</a> appInstance)

### Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

### Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

### Methods inherited from interface [com.wowza.wms.mediacaster.IMediaCasterValidateMediaCaster](#)

[onResetMediaCaster](#), [onValidateMediaCaster](#), [onValidateMediaCastersStart](#), [onValidateMediaCastersStop](#)

## Fields

### streamMonitorStreamStartTimeout

protected int **streamMonitorStreamStartTimeout**

(continued from last page)

---

**streamMonitorStreamTimeout**

protected int **streamMonitorStreamTimeout**

---

---

**streamMonitorVideoTCToleranceEnable**

protected boolean **streamMonitorVideoTCToleranceEnable**

---

---

**streamMonitorVideoTCPosTolerance**

protected int **streamMonitorVideoTCPosTolerance**

---

---

**streamMonitorVideoTCNegTolerance**

protected int **streamMonitorVideoTCNegTolerance**

---

---

**streamMonitorAudioTCToleranceEnable**

protected boolean **streamMonitorAudioTCToleranceEnable**

---

---

**streamMonitorAudioTCPosTolerance**

protected int **streamMonitorAudioTCPosTolerance**

---

---

**streamMonitorAudioTCNegTolerance**

protected int **streamMonitorAudioTCNegTolerance**

---

---

**streamMonitorDataTCToleranceEnable**

protected boolean **streamMonitorDataTCToleranceEnable**

---

---

**streamMonitorDataTCPosTolerance**

protected int **streamMonitorDataTCPosTolerance**

---

---

**streamMonitorDataTCNegTolerance**

protected int **streamMonitorDataTCNegTolerance**

---

(continued from last page)

---

**streamMonitorAVSyncToleranceEnable**protected boolean **streamMonitorAVSyncToleranceEnable**

---

---

**streamMonitorAVSyncTolerance**protected int **streamMonitorAVSyncTolerance**

---

---

**streamMonitorVideoStartTimeout**protected int **streamMonitorVideoStartTimeout**

---

---

**streamMonitorVideoTimeout**protected int **streamMonitorVideoTimeout**

---

---

**streamMonitorAudioStartTimeout**protected int **streamMonitorAudioStartTimeout**

---

---

**streamMonitorAudioTimeout**protected int **streamMonitorAudioTimeout**

---

---

**streamMonitorResetNameGroups**protected boolean **streamMonitorResetNameGroups**

---

---

**streamMonitorDebug**protected boolean **streamMonitorDebug**

---

---

**appInstance**protected com.wowza.wms.application.IApplicationInstance **appInstance**

---

(continued from last page)

## monitors

```
protected java.util.Map monitors
```

## badStreams

```
protected java.util.Set badStreams
```

## Constructors

### ModuleMediaCasterStreamMonitorAdvanced

```
public ModuleMediaCasterStreamMonitorAdvanced()
```

## Methods

### onAppStart

```
public void onAppStart(IApplicationInstance appInstance)
```

### onAppStop

```
public void onAppStop(IApplicationInstance appInstance)
```

### onStreamCreate

```
public void onStreamCreate(IMediaStream stream)
```

### onStreamDestroy

```
public void onStreamDestroy(IMediaStream stream)
```

### onValidateMediaCastersStart

```
public void onValidateMediaCastersStart(IApplicationInstance appInstance)
```

### onValidateMediaCaster

```
public boolean onValidateMediaCaster(IApplicationInstance appInstance,  
    IMediaCaster mediaCaster)
```

---

## onValidateMediaCastersStop

```
public void onValidateMediaCastersStop(IApplicationInstance appInstance)
```


---

## onResetMediaCaster

```
public boolean onResetMediaCaster(IApplicationInstance appInstance,  
    IMediaCaster mediaCaster)
```

## com.wowza.wms.module Class ModuleProperties

java.lang.Object



public class **ModuleProperties**  
extends [ModuleBase](#)

### Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK\\_PARAM1](#), [CALLBACK\\_PARAM10](#), [CALLBACK\\_PARAM2](#), [CALLBACK\\_PARAM3](#), [CALLBACK\\_PARAM4](#), [CALLBACK\\_PARAM5](#), [CALLBACK\\_PARAM6](#), [CALLBACK\\_PARAM7](#), [CALLBACK\\_PARAM8](#), [CALLBACK\\_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION\\_APPEND](#), [PLAYTRANSITION\\_APPEND\\_IMMEDIATE](#), [PLAYTRANSITION\\_RESET](#), [PLAYTRANSITION\\_RESET\\_IMMEDIATE](#), [PLAYTRANSITION\\_STOP](#), [PLAYTRANSITION\\_SWAP](#), [PLAYTRANSITION\\_SWITCH](#), [PLAYTRANSITION\\_UNKNOWN](#), [PLAYTRANSITIONSTR\\_APPEND](#), [PLAYTRANSITIONSTR\\_RESET](#), [PLAYTRANSITIONSTR\\_STOP](#), [PLAYTRANSITIONSTR\\_SWAP](#), [PLAYTRANSITIONSTR\\_SWITCH](#), [PLAYTRANSITIONSTR\\_UNKNOWN](#)

### Constructor Summary

public	<a href="#">ModuleProperties</a> ( )
--------	--------------------------------------

### Method Summary

static void	<a href="#">getAppInstanceProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get application instance level property value NetConnection.call("getAppInstanceProperty", resultObj, name);
static void	<a href="#">getApplicationProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get application level property value NetConnection.call("getApplicationProperty", resultObj, name);
static void	<a href="#">getClientProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get client level property value NetConnection.call("getClientProperty", resultObj, name);
static void	<a href="#">getStreamProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Get stream level property value NetConnection.call("getStreamProperty", resultObj, streamId, name);
static void	<a href="#">setAppInstanceProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set application instance level property NetConnection.call("setAppInstanceProperty", null, name, value);
static void	<a href="#">setApplicationProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set application level property NetConnection.call("setApplicationProperty", null, name, value);



static void	<a href="#">setClientProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set client level property NetConnection.call("setClientProperty", null, name, value);
static void	<a href="#">setStreamProperty</a> ( <a href="#">IClient</a> client, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Set stream level property NetConnection.call("setStreamProperty", null, streamId, name, value);

#### Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#),  
[getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#),  
[getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#),  
[getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#),  
[getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#),  
[sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#),  
[sendStreamOnStatusError](#)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,  
wait

## Constructors

### ModuleProperties

```
public ModuleProperties()
```

## Methods

### setApplicationProperty

```
public static void setApplicationProperty(IClient client,  
com.wowza.wms.request.RequestFunction function,  
AMFDataList params)
```

Set application level property NetConnection.call("setApplicationProperty", null, name, value);

#### Parameters:

client - client  
function - function  
params - params (name, value)

### getApplicationProperty

```
public static void getApplicationProperty(IClient client,  
com.wowza.wms.request.RequestFunction function,  
AMFDataList params)
```

Get application level property value NetConnection.call("getApplicationProperty", resultObj, name);

#### Parameters:

client - client  
function - function

(continued from last page)

params - params (name)

---

## setAppInstanceProperty

```
public static void setAppInstanceProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set application instance level property NetConnection.call("setAppInstanceProperty", null, name, value);

### Parameters:

client - client  
function - function  
params - params (name, value)

---

## getAppInstanceProperty

```
public static void getAppInstanceProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get application instance level property value NetConnection.call("getAppInstanceProperty", resultObj, name);

### Parameters:

client - client  
function - function  
params - params (name)

---

## setClientProperty

```
public static void setClientProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set client level property NetConnection.call("setClientProperty", null, name, value);

### Parameters:

client - client  
function - function  
params - params (name, value)

---

## getClientProperty

```
public static void getClientProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get client level property value NetConnection.call("getClientProperty", resultObj, name);

### Parameters:

client - client  
function - function  
params - params (name)

---

## setStreamProperty

```
public static void setStreamProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

(continued from last page)

Set stream level property NetConnection.call("setStreamProperty", null, streamId, name, value);

**Parameters:**

client - client

function - function

params - params (streamId, name, value)

---

## getStreamProperty

```
public static void getStreamProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get stream level property value NetConnection.call("getStreamProperty", resultObj, streamId, name);

**Parameters:**

client - client

function - function

params - params (streamId, name)

---

Package

**com.wowza.wms.response**

## com.wowza.wms.response Class ResponseFunction

java.lang.Object

└-com.wowza.wms.response.ResponseFunction

public class **ResponseFunction**  
extends Object

ResponseFunction: class for sending status messages to the client.

### Field Summary

public	<a href="#">doBreak</a>
--------	-------------------------

### Constructor Summary

public	<a href="#">ResponseFunction</a> ( <a href="#">IClient</a> client) Create an empty ResponseFunction
public	<a href="#">ResponseFunction</a> (com.wowza.wms.netconnection.INetConnection netConnection) Create an empty ResponseFunction
public	<a href="#">ResponseFunction</a> (com.wowza.wms.netconnection.INetConnection netConnection, <a href="#">AMFObj</a> amfObj) Create an empty ResponseFunction
public	<a href="#">ResponseFunction</a> ( <a href="#">IClient</a> client, <a href="#">AMFObj</a> amfObj) Create an empty ResponseFunction
public	<a href="#">ResponseFunction</a> ( <a href="#">IMediaStream</a> stream, <a href="#">AMFObj</a> amfObj) Create an empty ResponseFunction

### Method Summary

void	<a href="#">addBody</a> ( <a href="#">AMFData</a> body) Add AMFData to the body of the message.
void	<a href="#">addBytes</a> (byte[] inbytes) Add raw AMFData bytes[] to message body
void	<a href="#">createBroadcastMessage</a> (java.nio.ByteBuffer messageBytes) Create broadcast message.
void	<a href="#">createConnectMessage</a> (String inName, double inResultNum) Create net connection connect message.
void	<a href="#">createDefaultMessage</a> (String inName, double inResultNum) Create a default message (onStatus type messages).
void	<a href="#">createEnhancedSeekMessage</a> (byte[] messageBuffer, int src, int tc)

void	<a href="#"><code>createPlayStatusMessage</code></a> (String inName) Create onPlayStatus message.
void	<a href="#"><code>createSeekMessage</code></a> (String inName) Create a seek result message.
void	<a href="#"><code>createSOMessage</code></a> (byte[] messageBuffer, int objectEncoding) Create shared object message.
long	<a href="#"><code>getTimecode</code></a> () Get function timecode (milliseconds).
int	<a href="#"><code>getType</code></a> () Get message type.
boolean	<a href="#"><code>isForceAMF0</code></a> ()
void	<a href="#"><code>setBody</code></a> (int index, <a href="#"><code>AMFData</code></a> body) Add AMFData to the body of the message.
void	<a href="#"><code>setForceAMF0</code></a> (boolean forceAMF0)
void	<a href="#"><code>setMessageBytes</code></a> (byte[] messageBytes)
void	<a href="#"><code>setRetAMFNumber</code></a> (int innum) Set the return channel id
void	<a href="#"><code>setSrc</code></a> (int src) Set the src (stream id) for the message.
void	<a href="#"><code>setTimecode</code></a> (long timecode) Set function timecode (milliseconds).
void	<a href="#"><code>setType</code></a> (int type) Set message type.
int	<a href="#"><code>write</code></a> (java.io.OutputStream out, boolean isAbsTimecode, int chunkSize) Write message directly to OutputStream
int	<a href="#"><code>write</code></a> (java.io.OutputStream out, int chunkSize) Write message directly to OutputStream.

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### doBreak

public boolean **doBreak**

(continued from last page)

## Constructors

### ResponseFunction

```
public ResponseFunction(IClient client)
```

Create an empty ResponseFunction

**Parameters:**

client - client

### ResponseFunction

```
public ResponseFunction(com.wowza.wms.netconnection.INetConnection netConnection)
```

Create an empty ResponseFunction

**Parameters:**

netConnection - net connection

### ResponseFunction

```
public ResponseFunction(com.wowza.wms.netconnection.INetConnection netConnection,  
AMFObj amfObj)
```

Create an empty ResponseFunction

**Parameters:**

netConnection - net connection

amfObj - amf object

### ResponseFunction

```
public ResponseFunction(IClient client,  
AMFObj amfObj)
```

Create an empty ResponseFunction

**Parameters:**

client - client object

amfObj - amf object

### ResponseFunction

```
public ResponseFunction(IMediaStream stream,  
AMFObj amfObj)
```

Create an empty ResponseFunction

**Parameters:**

stream - media stream object

amfObj - amf object

## Methods

### setSrc

```
public void setSrc(int src)
```

(continued from last page)

Set the src (stream id) for the message.

**Parameters:**

src - src (stream id)

---

## createDefaultMessage

```
public void createDefaultMessage(String inName,  
    double inResultNum)
```

Create a default message (onStatus type messages).

**Parameters:**

inName - handler name (example: onStatus)

inResultNum - result number of 0 if not result

---

## createConnectMessage

```
public void createConnectMessage(String inName,  
    double inResultNum)
```

Create net connection connect message.

**Parameters:**

inName - handler name (example: connection)

inResultNum - result number if 0 not a result

---

## createSeekMessage

```
public void createSeekMessage(String inName)
```

Create a seek result message.

**Parameters:**

inName - handler name (example: onStatus)

---

## createPlayStatusMessage

```
public void createPlayStatusMessage(String inName)
```

Create onPlayStatus message.

**Parameters:**

inName - handler name (example: onPlayStatus)

---

## setMessageBytes

```
public void setMessageBytes(byte[] messageBytes)
```

---

## createBroadcastMessage

```
public void createBroadcastMessage(java.nio.ByteBuffer messageBytes)
```

Create broadcast message. Used for ByteBuffer handler calls.

**Parameters:**



(continued from last page)

messageBytes - ByteBuffer with raw AMFData bytes to be sent to client

---

## createSOMessage

```
public void createSOMessage(byte[] messageBuffer,  
    int objectEncoding)
```

Create shared object message. Used for ByteBuffer handler calls.

### Parameters:

messageBuffer

---

## createEnhancedSeekMessage

```
public void createEnhancedSeekMessage(byte[] messageBuffer,  
    int src,  
    int tc)
```

---

## addBody

```
public void addBody(AMFData body)
```

Add AMFData to the body of the message.

### Parameters:

body - AMFData message

---

## setBody

```
public void setBody(int index,  
    AMFData body)
```

Add AMFData to the body of the message.

### Parameters:

index - index in body list

body - AMFData message

---

## addBytes

```
public void addBytes(byte[] inbytes)
```

Add raw AMFData bytes[] to message body

### Parameters:

inbytes - raw AMFData bytes[]

---

## setRetAMFNumber

```
public void setRetAMFNumber(int innum)
```

Set the return channel id

### Parameters:

innum - return channel id

(continued from last page)

## getTimecode

```
public long getTimecode()
```

Get function timecode (milliseconds).

**Returns:**

function timecode (milliseconds)

---

## setTimecode

```
public void setTimecode(long timecode)
```

Set function timecode (milliseconds).

**Parameters:**

timecode - function timecode (milliseconds)

---

## setType

```
public void setType(int type)
```

Set message type. See IVHost.CONTENTTYPE\_\*

**Parameters:**

type - message type

---

## getType

```
public int getType()
```

Get message type. See IVHost.CONTENTTYPE\_\*

**Returns:**

message type

---

## write

```
public int write(java.io.OutputStream out,  
int chunkSize)
```

Write message directly to OutputStream.

**Parameters:**

out - OutputStream

**Returns:**

number of bytes written

---

## isForceAMF0

```
public boolean isForceAMF0()
```

---

## setForceAMF0

```
public void setForceAMF0(boolean forceAMF0)
```

(continued from last page)

---

**write**

```
public int write(java.io.OutputStream out,  
                boolean isAbsTimecode,  
                int chunkSize)
```

Write message directly to OutputStream

**Parameters:**

out - OutputStream  
isAbsTimecode - is timecode absolute

**Returns:**

number of bytes written

## com.wowza.wms.response Class ResponseFunctions

java.lang.Object

└─com.wowza.wms.response.ResponseFunctions

public class **ResponseFunctions**  
extends Object

ResponseFunctions: collection of ResponseFunction objects. This interface is used to asynchronously collect up a set of client responses that will be sent to the client at the next opportunity.

### Constructor Summary

public	<a href="#">ResponseFunctions()</a>
--------	-------------------------------------

### Method Summary

void	<a href="#">add(ResponseFunction wmsResponseFunction)</a> Add a function.
void	<a href="#">clear()</a>
boolean	<a href="#">isPending()</a> Are there any pending items in the list.
int	<a href="#">output(java.io.OutputStream out, int sendChunkSize)</a> Write all functions (in order added to list) to OutputStream.

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### ResponseFunctions

public **ResponseFunctions()**

### Methods

#### add

public void **add**([ResponseFunction wmsResponseFunction](#))

Add a function.

(continued from last page)

**Parameters:**wmsResponseFunction - function

---

**clear**

```
public void clear()
```

**isPending**

```
public boolean isPending()
```

Are there any pending items in the list.

**Returns:**

true if items in list

---

**output**

```
public int output(java.io.OutputStream out,  
int sendChunkSize)
```

Write all functions (in order added to list) to OutputStream.

**Parameters:**

out - OutputStream

**Returns:**

total number of bytes written

---

---

Package

**com.wowza.wms.rtp.model**

---

## com.wowza.wms.rtp.model Interface IRTPMessageHandler

---

public interface **IRTPMessageHandler**  
extends

IRTPMessageHandler: Internal use.

---

### Method Summary

void	<a href="#">handleMessage</a> (java.net.SocketAddress socketAddr, byte[] buffer, int offset, int len)
------	---

---

### Methods

#### handleMessage

```
public void handleMessage(java.net.SocketAddress socketAddr,  
    byte[] buffer,  
    int offset,  
    int len)
```

com.wowza.wms.rtp.model

# Interface IRTPMetadataProvider

public interface **IRTPMetadataProvider**  
extends

IRTPMetadataProvider: Internal use.

Method Summary	
byte[]	<a href="#">getMetadataPacket</a> ( <a href="#">RTPStream</a> stream)

## Methods

**getMetadataPacket**  
public byte[] **getMetadataPacket**([RTPStream](#) stream)



com.wowza.wms.rtp.model

Interface IRTPSessionNotify

public interface IRTPSessionNotify

extends

IRTPSessionNotify: listener interface for RTP sessions. See RTPSessions.addSessionListener(IRTPSessionNotify listener)

Method Summary	
void	<a href="#">onRTPSessionCreate</a> ( <a href="#">RTPSession</a> rtpSession) Invoked when RTP session is created
void	<a href="#">onRTPSessionDestroy</a> ( <a href="#">RTPSession</a> rtpSession) Invoked when RTP session is destroyed

Methods

onRTPSessionCreate

public void **onRTPSessionCreate**([RTPSession](#) rtpSession)

    Invoked when RTP session is created

Parameters:

    rtpSession - RTP session

onRTPSessionDestroy

public void **onRTPSessionDestroy**([RTPSession](#) rtpSession)

    Invoked when RTP session is destroyed

Parameters:

    rtpSession - RTP session

## com.wowza.wms.rtp.model Interface IRTSPActionNotify

public interface **IRTSPActionNotify**  
extends

IRTSPActionNotify: listener interface for RTSP actions. See RTPSession.addActionListener(IRTSPActionNotify actionListener)

### Method Summary

void	<a href="#">onAnnounce(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by ANNOUNCE command
void	<a href="#">onDescribe(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by DESCRIBE command
void	<a href="#">onGetParameter(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by GET_PARAMETER command
void	<a href="#">onOptions(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by OPTIONS command
void	<a href="#">onPause(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by PAUSE command
void	<a href="#">onPlay(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by PLAY command
void	<a href="#">onRecord(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by RECORD command
void	<a href="#">onRedirect(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by REDIRECT command
void	<a href="#">onSetParameter(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by SET_PARAMETER command
void	<a href="#">onSetup(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by SETUP command
void	<a href="#">onTeardown(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</a> Invoked by TEARDOWN command

## Methods

### onDescribe

```
public void onDescribe(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by DESCRIBE command

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

### onAnnounce

```
public void onAnnounce(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by ANNOUNCE command

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

### onSetParameter

```
public void onSetParameter(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by SET\_PARAMETER command

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

### onGetParameter

```
public void onGetParameter(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by GET\_PARAMETER command

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

(continued from last page)

## onOptions

```
public void onOptions(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by OPTIONS command

### Parameters:

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

## onPause

```
public void onPause(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by PAUSE command

### Parameters:

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

## onPlay

```
public void onPlay(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by PLAY command

### Parameters:

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

## onRecord

```
public void onRecord(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by RECORD command

### Parameters:

rtspSession  
req  
resp

---

## onRedirect

```
public void onRedirect(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by REDIRECT command

(continued from last page)

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

**onSetup**

```
public void onSetup(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by SETUP command

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

---

**onTeardown**

```
public void onTeardown(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by TEARDOWN command

**Parameters:**

rtspSession - RTP session  
req - RTP request  
resp - RTP response

## com.wowza.wms.rtp.model

### Class RTPContext

java.lang.Object

└─com.wowza.wms.rtp.model.RTPContext

public class **RTPContext**  
extends Object

RTPContext: RTP context

#### Constructor Summary

public	<a href="#">RTPContext</a> ( <a href="#">IVHost</a> vhost) Constructor
--------	---

#### Method Summary

boolean	<a href="#">acquireSocketAddress</a> (java.net.SocketAddress socketAddress) Acquire UDP socket address
int	<a href="#">acquireUDPPortPair</a> () Acquire next available UDP port pair
int	<a href="#">acquireUDPPortPair</a> (int port) Acquire UDP port pair
void	<a href="#">cacheRTPStream</a> ( <a href="#">RTPStream</a> stream) Cache an RTP stream, Internal use.
void	<a href="#">doWatchdog</a> () Idle events for cleanup
boolean	<a href="#">existsRTSPTunnelingSession</a> (String sessionId) Return true if session id is valid RTSP/RTP tunneling session id
int[]	<a href="#">expandToPortPair</a> (int port) Expand a single port to a pair.
RTPPacketizerItem	<a href="#">getAudioPacketizerItem</a> ( <a href="#">IApplicationInstance</a> appInstance, int codecId) Get audio packetizer for a given codec id.
com.wowza.wms.rtp.dep acketizer.RTPDePacket izerList	<a href="#">getDePacketizerList</a> () Get a list of the available depacketizers
String	<a href="#">getDePacketizerName</a> (RTPTrack rtpTrack) Get a depacketizer by name
Object	<a href="#">getLock</a> () Get the UDP port manager lock
Object	<a href="#">getRTSPTunnelingLock</a> () Get the RTSP/RTP tunneling lock

com.wowza.wms.rtsp.RTSP TunnelingSession	<a href="#"><u>getRTSPTunnelingSession</u></a> (String sessionId) Get RTSP/RTP tunneling session by session id
<a href="#"><u>RTPSessions</u></a>	<a href="#"><u>getSessions</u></a> () Get RTP sessions
RTPPacketizerItem	<a href="#"><u>getStreamPacketizerItem</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance, int codecId) Get stream packetizer for a given codec id.
com.wowza.wms.rtp.transport.UDPTransportManager	<a href="#"><u>getUDPTransportManager</u></a> () Get the UDP transport manager
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost</u></a> () Get vhost
RTPPacketizerItem	<a href="#"><u>getVideoPacketizerItem</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance, int codecId) Get video packetizer for a given codec id.
void	<a href="#"><u>init</u></a> () Initialize
void	<a href="#"><u>putAudioPacketizerItem</u></a> (int codecId, RTPPacketizerItem rtpPacketizerInfo) Set the audio packetizer for a given codec id
void	<a href="#"><u>putRTSPTunnelingSession</u></a> (String sessionId, com.wowza.wms.rtsp.RTSP TunnelingSession rtspTunnelingSession) Remove RTSP/RTP tunneling session by session id
void	<a href="#"><u>putStreamPacketizerItem</u></a> (int codecId, RTPPacketizerItem rtpPacketizerInfo) Set the stream packetizer for a given codec id
void	<a href="#"><u>putVideoPacketizerItem</u></a> (int codecId, RTPPacketizerItem rtpPacketizerInfo) Set the video packetizer for a given codec id
boolean	<a href="#"><u>releaseSocketAddress</u></a> (java.net.SocketAddress socketAddress) Release UDP socket address
void	<a href="#"><u>releaseUDPPortPair</u></a> (int port) Release port pair
com.wowza.wms.rtsp.RTSP TunnelingSession	<a href="#"><u>removeRTSPTunnelingSession</u></a> (String sessionId) Remove RTSP/RTP tunneling session by session id
void	<a href="#"><u>shutdown</u></a> () Shutdown
void	<a href="#"><u>shutdownRTPSession</u></a> ( <a href="#"><u>RTPSession</u></a> rtpSession) Gracefully and forcefully shutdown and RTP session
<a href="#"><u>RTPStream</u></a>	<a href="#"><u>uncacheRTPStream</u></a> (String streamId) UnCache an RTP stream, Internal use.

**Methods inherited from class java.lang.Object**

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### RTPContext

```
public RTPContext(IVHost vhost)
```

Constructor

**Parameters:**

vhost - vhost

## Methods

### doWatchdog

```
public void doWatchdog()
```

Idle events for cleanup

### init

```
public void init()
```

Initialize

### shutdown

```
public void shutdown()
```

Shutdown

### getAudioPacketizerItem

```
public RTPPacketizerItem getAudioPacketizerItem(IApplicationInstance appInstance,  
int codecId)
```

Get audio packetizer for a given codec id.

**Parameters:**

appInstance - application instance

codecId - codec id, see IVHost.CODEC\_AUDIO\_\*

**Returns:**

packetizer info

### putAudioPacketizerItem

```
public void putAudioPacketizerItem(int codecId,  
RTPPacketizerItem rtpPacketizerInfo)
```

Set the audio packetizer for a given codec id

**Parameters:**

codecId - codec id, see IVHost.CODEC\_AUDIO\_\*

rtpPacketizerInfo - packetizer info



## getVideoPacketizerItem

```
public RTPPacketizerItem getVideoPacketizerItem(IApplicationInstance appInstance,  
int codecId)
```

Get video packetizer for a given codec id.

**Parameters:**

appInstance - application instance  
codecId - codec id, see IVHost.CODEC\_VIDEO\_\*

**Returns:**

packetizer info

---

## putVideoPacketizerItem

```
public void putVideoPacketizerItem(int codecId,  
RTPPacketizerItem rtpPacketizerInfo)
```

Set the video packetizer for a given codec id

**Parameters:**

codecId - codec id, see IVHost.CODEC\_VIDEO\_\*rtpPacketizerInfo - packetizer info

---

## getStreamPacketizerItem

```
public RTPPacketizerItem getStreamPacketizerItem(IApplicationInstance appInstance,  
int codecId)
```

Get stream packetizer for a given codec id.

**Parameters:**

appInstance - application instance  
codecId - codec id, see IVHost.CODEC\_STREAM\_\*

**Returns:**

packetizer info

---

## putStreamPacketizerItem

```
public void putStreamPacketizerItem(int codecId,  
RTPPacketizerItem rtpPacketizerInfo)
```

Set the stream packetizer for a given codec id

**Parameters:**

codecId - codec id, see IVHost.CODEC\_STREAM\_\*rtpPacketizerInfo - packetizer info

---

## getSessions

```
public RTPSessions getSessions()
```

Get RTP sessions

**Returns:**

RTP sessions

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

**Returns:**  
vhost

---

## getUDPTransportManager

```
public com.wowza.wms.rtp.transport.UDPTransportManager getUDPTransportManager()
```

Get the UDP transport manager

**Returns:**  
UDP transport manager

---

## getLock

```
public Object getLock()
```

Get the UDP port manager lock

**Returns:**  
UDP port manager lock

---

## acquireSocketAddress

```
public boolean acquireSocketAddress(java.net.SocketAddress socketAddress)
```

Acquire UDP socket address

**Parameters:**  
socketAddress - UDP socket address

**Returns:**  
true if available

---

## releaseSocketAddress

```
public boolean releaseSocketAddress(java.net.SocketAddress socketAddress)
```

Release UDP socket address

**Parameters:**  
socketAddress - UDP socket address

**Returns:**  
true if available

---

## acquireUDPPortPair

```
public int acquireUDPPortPair(int port)
```

Acquire UDP port pair

---

(continued from last page)

**Parameters:**

port - starting port

**Returns:**

port

---

## expandToPortPair

```
public int[] expandToPortPair(int port)
```

Expand a single port to a pair. Ports are allocated in pairs always starting with even port number.

**Parameters:**

port - port

**Returns:**

port

---

## acquireUDPPortPair

```
public int acquireUDPPortPair()
```

Acquire next available UDP port pair

**Returns:**

port

---

## releaseUDPPortPair

```
public void releaseUDPPortPair(int port)
```

Release port pair

**Parameters:**

port - first port of pair

---

## cacheRTPStream

```
public void cacheRTPStream(RTPStream stream)
```

Cache an RTP stream, Internal use.

**Parameters:**

stream - RTP stream

---

## uncacheRTPStream

```
public RTPStream uncacheRTPStream(String streamId)
```

UnCache an RTP stream, Internal use.

**Parameters:**

streamId - stream id

**Returns:**

RTP Stream

(continued from last page)

## getDePacketizerList

```
public com.wowza.wms.rtp.depaketizer.RTPDePacketizerList getDePacketizerList()
```

Get a list of the available depacketizers

**Returns:**

list of the available depacketizers

---

## getDePacketizerName

```
public String getDePacketizerName(RTPTrack rtpTrack)
```

Get a depacketizer by name

**Parameters:**

rtpTrack - track

**Returns:**

depacketizer

---

## getRTSPTunnelingLock

```
public Object getRTSPTunnelingLock()
```

Get the RTSP/RTP tunneling lock

**Returns:**

RTSP/RTP tunneling lock

---

## getRTSPTunnelingSession

```
public com.wowza.wms.rtsp.RTSPTunnelingSession getRTSPTunnelingSession(String  
sessionId)
```

Get RTSP/RTP tunneling session by session id

**Parameters:**

sessionId - session id

**Returns:**

RTSP/RTP tunneling session

---

## removeRTSPTunnelingSession

```
public com.wowza.wms.rtsp.RTSPTunnelingSession removeRTSPTunnelingSession(String  
sessionId)
```

Remove RTSP/RTP tunneling session by session id

**Parameters:**

sessionId - session id

**Returns:**

RTSP/RTP tunneling session if removed

(continued from last page)

## existsRTSPTunnelingSession

```
public boolean existsRTSPTunnelingSession(String sessionId)
```

Return true if session id is valid RTSP/RTP tunneling session id

**Parameters:**

sessionId - session id

**Returns:**

true if session id is valid RTSP/RTP tunneling session id

---

## putRTSPTunnelingSession

```
public void putRTSPTunnelingSession(String sessionId,  
    com.wowza.wms.rtsp.RTSPTunnelingSession rtspTunnelingSession)
```

Remove RTSP/RTP tunneling session by session id

**Parameters:**

sessionId - session id

rtspTunnelingSession - RTSP/RTP tunneling session

---

## shutdownRTPSession

```
public void shutdownRTPSession(RTPSession rtpSession)
```

Gracefully and forcefully shutdown and RTP session

**Parameters:**

rtpSession - RTP session

## com.wowza.wms.rtp.model

### Class RTPDestination

java.lang.Object

└─com.wowza.wms.rtp.model.RTPDestination

public class **RTPDestination**  
extends Object

RTPDestination: Fully describes an RTP destination.

#### Constructor Summary

public	<a href="#">RTPDestination()</a>
--------	----------------------------------

#### Method Summary

String	<a href="#">getAudioHost()</a> Get audio host
int	<a href="#">getAudioPort()</a> Get audio port
String	<a href="#">getHost()</a> Get the host
String	<a href="#">getHostType()</a> Get host type (default IP4)
String	<a href="#">getName()</a> Get name
int	<a href="#">getStreamPort()</a> Get stream port
int	<a href="#">getTTL()</a> Get time to live
String	<a href="#">getVideoHost()</a> Get video host
int	<a href="#">getVideoPort()</a> Get video port
boolean	<a href="#">isMulticast()</a> Return true if multicast destination
boolean	<a href="#">isRTPWrapped()</a> Is stream wrapped in RTP (MPEG-TS in RTP)
boolean	<a href="#">isStream()</a> Return true if stream destination (and not native RTP destination)

void	<a href="#"><code>setAudioHost</code></a> (String audioHost) Set audio host
void	<a href="#"><code>setAudioPort</code></a> (int audioPort) Set audio port
void	<a href="#"><code>setHost</code></a> (String host) Set host
void	<a href="#"><code>setHostType</code></a> (String hostType) Set host type (default IP4)
void	<a href="#"><code>setName</code></a> (String name) Set name
void	<a href="#"><code>setRTPWrapped</code></a> (boolean isRTPWrapped) Is stream wrapped in RTP (MPEG-TS in RTP)
void	<a href="#"><code>setStreamPort</code></a> (int streamPort) Set stream port
void	<a href="#"><code>setTTL</code></a> (int ttl) Set time to live
void	<a href="#"><code>setVideoHost</code></a> (String videoHost) Set video host
void	<a href="#"><code>setVideoPort</code></a> (int videoPort) Set video port
String	<a href="#"><code>toString</code></a> ()

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### RTPDestination

```
public RTPDestination()
```

## Methods

### toString

```
public String toString()
```

(continued from last page)

## isMulticast

```
public boolean isMulticast()
```

Return true if multicast destination

**Returns:**

true if multicast destination

---

## isStream

```
public boolean isStream()
```

Return true if stream destination (and not native RTP destination)

**Returns:**

true if stream destination

---

## getHost

```
public String getHost()
```

Get the host

**Returns:**

host

---

## setHost

```
public void setHost(String host)
```

Set host

**Parameters:**

host - host

---

## getVideoPort

```
public int getVideoPort()
```

Get video port

**Returns:**

video port

---

## setVideoPort

```
public void setVideoPort(int videoPort)
```

Set video port

**Parameters:**

videoPort - video port

---

## getAudioPort

```
public int getAudioPort()
```



(continued from last page)

Get audio port

**Returns:**

audio port

---

## setAudioPort

```
public void setAudioPort(int audioPort)
```

Set audio port

**Parameters:**

audioPort - audio port

---

## getStreamPort

```
public int getStreamPort()
```

Get stream port

**Returns:**

stream port

---

## setStreamPort

```
public void setStreamPort(int streamPort)
```

Set stream port

**Parameters:**

streamPort - stream port

---

## getVideoHost

```
public String getVideoHost()
```

Get video host

**Returns:**

video host

---

## setVideoHost

```
public void setVideoHost(String videoHost)
```

Set video host

**Parameters:**

videoHost - video host

---

## getAudioHost

```
public String getAudioHost()
```

Get audio host

**Returns:**

audio host

## setAudioHost

```
public void setAudioHost(String audioHost)
```

Set audio host

**Parameters:**

audioHost - audio host

---

## getHostType

```
public String getHostType()
```

Get host type (default IP4)

**Returns:**

host type

---

## setHostType

```
public void setHostType(String hostType)
```

Set host type (default IP4)

**Parameters:**

hostType - host type

---

## getTTL

```
public int getTTL()
```

Get time to live

**Returns:**

time to live

---

## setTTL

```
public void setTTL(int ttl)
```

Set time to live

**Parameters:**

ttl - time to live

---

## isRTPWrapped

```
public boolean isRTPWrapped()
```

Is stream wrapped in RTP (MPEG-TS in RTP)

**Returns:**

true if stream wrapped in RTP

---

## setRTPWrapped

```
public void setRTPWrapped(boolean isRTPWrapped)
```

---

(continued from last page)

Is stream wrapped in RTP (MPEG-TS in RTP)

**Parameters:**

isRTPWrapped - true if stream wrapped in RTP

---

## getName

```
public String getName()
```

Get name

**Returns:**

name

---

## setName

```
public void setName(String name)
```

Set name

**Parameters:**

name - name

## com.wowza.wms.rtp.model

### Class RTPPort

java.lang.Object

└─com.wowza.wms.rtp.model.RTPPort

All Implemented Interfaces:

com.wowza.wms.rtp.transport.IUDPMessageHandler

public class **RTPPort**  
 extends Object  
 implements com.wowza.wms.rtp.transport.IUDPMessageHandler

### Constructor Summary

public	<a href="#">RTPPort</a> (String inIpAddress, int inPort, String outIpAddress, int outPort, boolean isMulticast) Constructor
--------	--

### Method Summary

void	<a href="#">bind</a> (int direction) Bind to port
int	<a href="#">getAddressCount</a> () Get address count
<a href="#">I RTPMessageHandler</a>	<a href="#">getHandler</a> () Get the message handler
String	<a href="#">getInIpAddress</a> () Get in IP address
int	<a href="#">getInPort</a> () Get in port
String	<a href="#">getOutIpAddress</a> () Get out IP address
int	<a href="#">getOutPort</a> () Get out port
RTPTrack	<a href="#">getTrack</a> () Get RTP track
int	<a href="#">getTTL</a> () Get time to live (milliseconds)
com.wowza.wms.rtp.transport.IUDPTransport	<a href="#">getUDPTransport</a> () Get the UDP transport
void	<a href="#">handleMessage</a> (java.net.SocketAddress socketAddr, Object message)

boolean	<a href="#"><u>isBlockUDPOut</u></a> ( )
boolean	<a href="#"><u>isInMulticast</u></a> ( ) Is in stream multicast
boolean	<a href="#"><u>isMulticast</u></a> ( ) Is multicast
boolean	<a href="#"><u>isOutMulticast</u></a> ( ) Is out stream multicast
void	<a href="#"><u>sendMessage</u></a> (byte[] message, int offset, int len) Send a message out
void	<a href="#"><u>sendResponse</u></a> (byte[] message) Send a response
void	<a href="#"><u>sendResponse</u></a> (byte[] message, int offset, int len) Send response
void	<a href="#"><u>sendResponse</u></a> (byte[] message, int offset, int len, java.net.SocketAddress destination) Send response to destination
void	<a href="#"><u>sessionClosed</u></a> (com.wowza.wms.rtp.transport.IUDPTransportSession session)
void	<a href="#"><u>sessionOpened</u></a> (com.wowza.wms.rtp.transport.IUDPTransportSession session)
void	<a href="#"><u>setAddressCount</u></a> (int addressCount) Set address count
void	<a href="#"><u>setBlockUDPOut</u></a> (boolean blockUDPOut)
void	<a href="#"><u>setHandler</u></a> ( <a href="#"><u>IRTPMessageHandler</u></a> handler) Set the message handler
void	<a href="#"><u>setTrack</u></a> (RTPTrack track) Set RTP track
void	<a href="#"><u>setTTL</u></a> (int ttl) Set time to live (milliseconds)
void	<a href="#"><u>shutdown</u></a> ( ) Shutdown port
void	<a href="#"><u>unbind</u></a> ( ) Unbind

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface** com.wowza.wms.rtp.transport.IUDPMessageHandler

handleMessage, sessionClosed, sessionOpened

## Constructors

### RTPPort

```
public RTPPort(String inIpAddress,  
               int inPort,  
               String outIpAddress,  
               int outPort,  
               boolean isMulticast)
```

Constructor

**Parameters:**

inIpAddress - in ip address  
inPort - in port  
outIpAddress - out ip address  
outPort - out port  
isMulticast - true if multicast

## Methods

### getTrack

```
public RTPTrack getTrack()
```

Get RTP track

**Returns:**

RTP track

---

### setTrack

```
public void setTrack(RTPTrack track)
```

Set RTP track

**Parameters:**

track - RTP track

---

### getUDPTransport

```
public com.wowza.wms.rtp.transport.IUDPTransport getUDPTransport()
```

Get the UDP transport

**Returns:**

UDP transport

---

### getInIpAddress

```
public String getInIpAddress()
```

Get in IP address

**Returns:**

in IP address

## getOutIpAddress

```
public String getOutIpAddress()
```

Get out IP address

**Returns:**

out IP address

---

## getInPort

```
public int getInPort()
```

Get in port

**Returns:**

in port

---

## getOutPort

```
public int getOutPort()
```

Get out port

**Returns:**

out port

---

## bind

```
public void bind(int direction)
```

Bind to port

**Parameters:**

direction - in or out, see IUDPTTransport.DIRECTION\_\*

---

## unbind

```
public void unbind()
```

Unbind

---

## shutdown

```
public void shutdown()
```

Shutdown port

---

## getHandler

```
public IRTPMessageHandler getHandler()
```

Get the message handler

**Returns:**

message handler

---

## setHandler

```
public void setHandler(IRTPMessageHandler handler)
```

Set the message handler

### Parameters:

handler - message handler

---

## sendMessage

```
public void sendMessage(byte[] message,  
    int offset,  
    int len)
```

Send a message out

### Parameters:

message - message

offset - offset

len - len

---

## sendResponse

```
public void sendResponse(byte[] message)
```

Send a response

### Parameters:

message - message

---

## sendResponse

```
public void sendResponse(byte[] message,  
    int offset,  
    int len)
```

Send response

### Parameters:

message - message

offset - offset

len - len

---

## sendResponse

```
public void sendResponse(byte[] message,  
    int offset,  
    int len,  
    java.net.SocketAddress destination)
```

Send response to destination

### Parameters:

message - message

offset - offset

len - len

destination - destination address

---



---

## sessionOpened

```
public void sessionOpened(com.wowza.wms.rtp.transport.IUDPTransportSession session)
```

---

## sessionClosed

```
public void sessionClosed(com.wowza.wms.rtp.transport.IUDPTransportSession session)
```

---

## handleMessage

```
public void handleMessage(java.net.SocketAddress socketAddr,  
    Object message)
```

---

## isInMulticast

```
public boolean isInMulticast()
```

Is in stream multicast

**Returns:**

true if multicast

---

## isOutMulticast

```
public boolean isOutMulticast()
```

Is out stream multicast

**Returns:**

true if multicast

---

## isMulticast

```
public boolean isMulticast()
```

Is multicast

**Returns:**

true if multicast

---

## getTTL

```
public int getTTL()
```

Get time to live (milliseconds)

**Returns:**

time to live (milliseconds)

---

(continued from last page)

---

## setTTL

```
public void setTTL(int ttl)
```

Set time to live (milliseconds)

### Parameters:

ttl - time to live (milliseconds)

---

## getAddressCount

```
public int getAddressCount()
```

Get address count

### Returns:

address count

---

## setAddressCount

```
public void setAddressCount(int addressCount)
```

Set address count

### Parameters:

addressCount - address count

---

## isBlockUDPOut

```
public boolean isBlockUDPOut()
```

---

## setBlockUDPOut

```
public void setBlockUDPOut(boolean blockUDPOut)
```

## com.wowza.wms.rtp.model Class RTPPushPublishSession

java.lang.Object

└─com.wowza.wms.rtp.model.RTPPushPublishSession

public class **RTPPushPublishSession**  
extends Object

RTPPushPublishSession: RTP push publishing session

### Constructor Summary

public	<a href="#">RTPPushPublishSession()</a>
--------	---

### Method Summary

<a href="#">RTPSession</a>	<a href="#">getRTPSession()</a> Get RTP session
String	<a href="#">getSDPData()</a> Get SDP data
void	<a href="#">setRTPSession(<a href="#">RTPSession</a> rtpSession)</a> Set RTP session
void	<a href="#">setSDPData(String sdpData)</a> Set SDP data

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### RTPPushPublishSession

public **RTPPushPublishSession()**

### Methods

#### getSDPData

public String **getSDPData()**

Get SDP data

---

(continued from last page)

**Returns:**

SDP data

---

**setSDPData**

```
public void setSDPData(String sdpData)
```

Set SDP data

**Parameters:**

sdpData - SDP data

---

**getRTPSession**

```
public RTPSession getRTPSession()
```

Get RTP session

**Returns:**

RTP session

---

**setRTPSession**

```
public void setRTPSession(RTPSession rtpSession)
```

Set RTP session

**Parameters:**

rtpSession - RTP session

---

## com.wowza.wms.rtp.model

### Class RTPSession

java.lang.Object

└-com.wowza.wms.rtp.model.RTPSession

public class **RTPSession**  
extends Object

RTPSession: RTP session

#### Field Summary

protected	<a href="#">actionListeners</a>
protected	<a href="#">appInstance</a>
protected	<a href="#">appInstanceShutdown</a>
protected	<a href="#">audioPacketizers</a>
protected	<a href="#">authenticatePlayHandler</a>
protected	<a href="#">authenticatePublishHandler</a>
public static final	<a href="#">AUTHMETHOD_PLAY</a> Value: <b>1</b>
public static final	<a href="#">AUTHMETHOD_PUBLISH</a> Value: <b>2</b>
public static final	<a href="#">AUTHMETHOD_UNKNOWN</a> Value: <b>0</b>
protected	<a href="#">connectionHolder</a>
protected	<a href="#">cookieStr</a>
protected	<a href="#">debugRTSPSession</a>
protected	<a href="#">elapsedTime</a>
protected	<a href="#">idleFrequency</a>
protected	<a href="#">idleHandler</a>

protected	<a href="#"><u>ioPerformanceCounter</u></a>
protected	<a href="#"><u>ioSession</u></a>
protected	<a href="#"><u>ip</u></a>
protected	<a href="#"><u>isAnnounce</u></a>
protected	<a href="#"><u>isConnected</u></a>
protected	<a href="#"><u>isDescribe</u></a>
protected	<a href="#"><u>isSessionValid</u></a>
protected	<a href="#"><u>lastAuthenticateMethod</u></a>
protected	<a href="#"><u>lock</u></a>
protected	<a href="#"><u>loggedConnect</u></a>
protected	<a href="#"><u>properties</u></a>
protected	<a href="#"><u>queryStr</u></a>
protected	<a href="#"><u>redirectSession</u></a>
protected	<a href="#"><u>redirectSessionCode</u></a>
protected	<a href="#"><u>redirectSessionMessage</u></a>
protected	<a href="#"><u>redirectSessionURL</u></a>
protected	<a href="#"><u>referrer</u></a>
protected	<a href="#"><u>rtpWriteListener</u></a>
protected	<a href="#"><u>rtspPlayRangeStart</u></a>
protected	<a href="#"><u>rtspPlayRangeStop</u></a>
protected	<a href="#"><u>rtspTunnelingSessionId</u></a>
protected	<a href="#"><u>serverIp</u></a>
protected	<a href="#"><u>serverPort</u></a>
protected	<a href="#"><u>sessionId</u></a>

protected	<a href="#">shutdownClient</a>
protected	<a href="#">streamPacketizers</a>
protected	<a href="#">streams</a>
protected	<a href="#">streamsOrder</a>
protected	<a href="#">timeCreated</a>
protected	<a href="#">totalIOPerformance2Last</a>
protected	<a href="#">totalIOPerformanceLast</a>
protected	<a href="#">uri</a>
protected	<a href="#">userAgent</a>
protected	<a href="#">vhost</a>
protected	<a href="#">videoPacketizers</a>

## Constructor Summary

public	<a href="#">RTPSession</a> (String sessionId) Constructor
--------	--

## Method Summary

void	<a href="#">acceptSession</a> () Accept this session
void	<a href="#">addActionListener</a> ( <a href="#">IRTSPActionNotify</a> actionListener) Add action listener
void	<a href="#">addIOPerformance</a> ( <a href="#">IOPerformanceCounter</a> totalIOPerformanceResult) Internal use
void	<a href="#">addIOPerformance2</a> ( <a href="#">IOPerformanceCounter</a> totalIOPerformanceResult) Internal use
void	<a href="#">addRTSPStream</a> ( <a href="#">RTPStream</a> stream) Add RTP stream
void	<a href="#">clearLoggingValues</a> () Clear logging values, Internal use.
void	<a href="#">doIdle</a> ()
<a href="#">IApplicationInstance</a>	<a href="#">getAppInstance</a> () Get application instance

RTPPacketizerItem	<a href="#">getAudioPacketizerItem(RTPContext rtpContext, IApplicationInstance appInstance, int codecId)</a> Get audio packetizer for a given codec id.
<a href="#">IAuthenticateRTSP</a>	<a href="#">getAuthenticatePlayHandler()</a> Get the authentication play handler
<a href="#">IAuthenticateRTSP</a>	<a href="#">getAuthenticatePublishHandler()</a> Get the RTP authentication handler
ConnectionHolder	<a href="#">getConnectionHolder()</a> Get connection holder, Internal use.
String	<a href="#">getCookieStr()</a> Get cookie string
<a href="#">ElapsedTimer</a>	<a href="#">getElapsedTime()</a> Get the elapsed timer for this RTP session
int	<a href="#">getIdleFrequency()</a> Get idle frequency (milliseconds)
RTPIdleHandler	<a href="#">getIdleHandler()</a> Get idle handler
<a href="#">IOPerformanceCounter</a>	<a href="#">getIOPerformanceCounter()</a> Get IO performance counter
org.apache.mina.common.support.BaseIoSession	<a href="#">getIoSession()</a>
String	<a href="#">getIp()</a> Get remote IP address
int	<a href="#">getLastAuthenticateMethod()</a> Get the last method received
<a href="#">WMSProperties</a>	<a href="#">getProperties()</a> Get properties
String	<a href="#">getQueryStr()</a> Get query string
int	<a href="#">getRedirectSessionCode()</a>
String	<a href="#">getRedirectSessionMessage()</a>
String	<a href="#">getRedirectSessionURL()</a>
String	<a href="#">getReferrer()</a> Get referrer
RTPWriteListener	<a href="#">getRTPWriteListener()</a> Get the RTP write listener for this session
double	<a href="#">getRTSPPlayRangeStart()</a> Get play start range, Internal use.



double	<a href="#"><u>getRTSPPlayRangeStop()</u></a> Get play stop range, Internal use.
<a href="#"><u>RTPStream</u></a>	<a href="#"><u>getRTSPStream()</u></a> Get the default RTP Stream (all RTP sessions have a single RTP Stream)
<a href="#"><u>RTPStream</u></a>	<a href="#"><u>getRTSPStream(String streamId)</u></a> Get RTP Stream
String	<a href="#"><u>getRTSPTunnelingSessionId()</u></a> Get the RTSP/RTP tunneling session id
String	<a href="#"><u>getServerIp()</u></a> Get the server IP address
int	<a href="#"><u>getServerPort()</u></a> Get server port
String	<a href="#"><u>getSessionId()</u></a> Get session id
RTPPacketizerItem	<a href="#"><u>getStreamPacketizerItem(RTPContext rtpContext, IApplicationInstance appInstance, int codecId)</u></a> Get stream packetizer for a given codec id.
String	<a href="#"><u>getTimeRunning()</u></a> Get the time running for this RTP session
double	<a href="#"><u>getTimeRunningSeconds()</u></a> Get the number of second this RTP session has been running
String	<a href="#"><u>getUri()</u></a> Get URI
String	<a href="#"><u>getUserAgent()</u></a> Get user agent
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost()</u></a> Get vhost
RTPPacketizerItem	<a href="#"><u>getVideoPacketizerItem(RTPContext rtpContext, IApplicationInstance appInstance, int codecId)</u></a> Get video packetizer for a given codec id.
boolean	<a href="#"><u>isAnnounce()</u></a> Has ANNOUNCE command been called on this session
boolean	<a href="#"><u>isAnnounceOrDescribe()</u></a> Has announce or described been called
boolean	<a href="#"><u>isConnected()</u></a> Is session connection
boolean	<a href="#"><u>isDebugRTSPSession()</u></a> True if debugging RTSP session
boolean	<a href="#"><u>isDescribe()</u></a> Has DESCRIBE command been called on this session

boolean	<a href="#"><u>isLoggedConnect</u></a> ( ) Is connect logged
boolean	<a href="#"><u>isRedirectSession</u></a> ( )
boolean	<a href="#"><u>isSessionValid</u></a> ( ) Is this session valid
boolean	<a href="#"><u>isShutdownClient</u></a> ( ) Is RTP session shutdown
void	<a href="#"><u>onAnnounce</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on ANNOUNCE command
void	<a href="#"><u>onDescribe</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on DESCRIBE command
void	<a href="#"><u>onGetParameter</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on GET_PARAMETER command
void	<a href="#"><u>onOptions</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on OPTIONS command
void	<a href="#"><u>onPause</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on PAUSE command
void	<a href="#"><u>onPlay</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on PLAY command
void	<a href="#"><u>onRecord</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on RECORD command
void	<a href="#"><u>onRedirect</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on REDIRECT command
void	<a href="#"><u>onSetParameter</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on SET_PARAMETER command
void	<a href="#"><u>onSetup</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on SETUP command
void	<a href="#"><u>onTeardown</u></a> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on TEARDOWN command
void	<a href="#"><u>putAudioPacketizerItem</u></a> (int codecId, String classPath) Set the audio packetizer for a given codec id
void	<a href="#"><u>putStreamPacketizerItem</u></a> (int codecId, String classPath) Set the stream packetizer for a given codec id

void	<a href="#"><u>putVideoPacketizerItem</u></a> (int codecId, String classPath) Set the video packetizer for a given codec id
void	<a href="#"><u>redirectSession</u></a> (String redirectSessionURL)
void	<a href="#"><u>redirectSession</u></a> (String redirectSessionURL, int redirectSessionCode)
void	<a href="#"><u>rejectSession</u></a> () Reject this session
void	<a href="#"><u>removeActionListener</u></a> ( <a href="#"><u>IRTSPActionNotify</u></a> actionListener) Remove action listener
<a href="#"><u>RTPStream</u></a>	<a href="#"><u>removeRTSPStream</u></a> (String streamId) Remove RTP stream
void	<a href="#"><u>setAnnounce</u></a> (boolean isAnnounce) Set ANNOUNCE command been called on this session
void	<a href="#"><u>setAppInstance</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance) Set application instance
void	<a href="#"><u>setAuthenticatePlayHandler</u></a> ( <a href="#"><u>IAuthenticateRTSP</u></a> authenticatePlayHandler) Set the authentication play handler
void	<a href="#"><u>setAuthenticatePublishHandler</u></a> ( <a href="#"><u>IAuthenticateRTSP</u></a> authenticatePublishHandler) Set the RTP authentication handler
void	<a href="#"><u>setConnected</u></a> (boolean isConnected) Set session is connected
void	<a href="#"><u>setCookieStr</u></a> (String cookieStr) Set cooking string
void	<a href="#"><u>setDebugRTSPSession</u></a> (boolean debugRTSPSession) Set debugging RTSP session
void	<a href="#"><u>setDescribe</u></a> (boolean isDescribe) Set DESCRIBE command been called on this session
void	<a href="#"><u>setIdleFrequency</u></a> (int idleFrequency) Set idle frequency (milliseconds)
void	<a href="#"><u>setIdleHandler</u></a> ( <a href="#"><u>RTPIdleHandler</u></a> idleHandler) Set idle handler
void	<a href="#"><u>setIOPerformanceCounter</u></a> ( <a href="#"><u>IOPerformanceCounter</u></a> ioPerformanceCounter) Set IO performance counter
void	<a href="#"><u>setIoSession</u></a> (org.apache.mina.common.support.BaseIoSession ioSession)
void	<a href="#"><u>setIp</u></a> (String ip) Set remote IP address
void	<a href="#"><u>setLastAuthenticateMethod</u></a> (int lastAuthenticateMethod) Set last method received

void	<a href="#"><u>setLoggedConnect</u></a> (boolean loggedConnect) Set connect logged
void	<a href="#"><u>setQueryStr</u></a> (String queryStr) Set query string
void	<a href="#"><u>setRedirectSession</u></a> (boolean redirectSession)
void	<a href="#"><u>setRedirectSessionCode</u></a> (int redirectSessionCode)
void	<a href="#"><u>setRedirectSessionMessage</u></a> (String redirectSessionMessage)
void	<a href="#"><u>setRedirectSessionURL</u></a> (String redirectSessionURL)
void	<a href="#"><u>setReferrer</u></a> (String referrer) Set referrer
void	<a href="#"><u>setRTSPPlayRangeStart</u></a> (double rtspPlayRangeStart) Set play start range, Internal use.
void	<a href="#"><u>setRTSPPlayRangeStop</u></a> (double rtspPlayRangeStop) Set play stop range, Internal use.
void	<a href="#"><u>setRTSPTunnelingSessionId</u></a> (String rtspTunnelingSessionId) Set the RTSP/RTP tunneling session id
void	<a href="#"><u>setServerIp</u></a> (String serverIp) Set the server IP address
void	<a href="#"><u>setServerPort</u></a> (int serverPort) Set server port
void	<a href="#"><u>setSessionId</u></a> (String sessionId) Set session id
void	<a href="#"><u>setSessionValid</u></a> (boolean isSessionValid) Set session valid
void	<a href="#"><u>setShutdownClient</u></a> (boolean shutdownClient) Set RTP session shutdown
void	<a href="#"><u>setUri</u></a> (String uri) Set URI
void	<a href="#"><u>setUserAgent</u></a> (String userAgent) Set user agent
void	<a href="#"><u>setVHost</u></a> ( <a href="#"><u>IVHost</u></a> vhost) Set vhost
void	<a href="#"><u>shutdown</u></a> ( ) shutdown RTP session, Internal use.
void	<a href="#"><u>shutdown</u></a> (RTPRequestStatus status) shutdown RTP session, Internal use.
void	<a href="#"><u>touch</u></a> ( ) Touch the stream so it doesn't timeout

void

[updateLoggingValues\(\)](#)

Update logging values, Internal use.

**Methods inherited from class** `java.lang.Object``clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

## Fields

### **AUTHMETHOD\_UNKNOWN**

```
public static final int AUTHMETHOD_UNKNOWN
```

Constant value: **0**

### **AUTHMETHOD\_PLAY**

```
public static final int AUTHMETHOD_PLAY
```

Constant value: **1**

### **AUTHMETHOD\_PUBLISH**

```
public static final int AUTHMETHOD_PUBLISH
```

Constant value: **2**

### **sessionId**

```
protected java.lang.String sessionId
```

### **rtspTunnelingSessionId**

```
protected java.lang.String rtspTunnelingSessionId
```

### **streams**

```
protected java.util.Map streams
```

### **streamsOrder**

```
protected java.util.List streamsOrder
```

(continued from last page)

## vhost

protected com.wowza.wms.vhost.IVHost **vhost**

---

## userAgent

protected java.lang.String **userAgent**

---

## cookieStr

protected java.lang.String **cookieStr**

---

## ip

protected java.lang.String **ip**

---

## isSessionValid

protected boolean **isSessionValid**

---

## authenticatePlayHandler

protected com.wowza.wms.authentication.IAuthenticateRTSP **authenticatePlayHandler**

---

## authenticatePublishHandler

protected com.wowza.wms.authentication.IAuthenticateRTSP **authenticatePublishHandler**

---

## lastAuthenticateMethod

protected int **lastAuthenticateMethod**

---

## appInstance

protected com.wowza.wms.application.IApplicationInstance **appInstance**

---

## appInstanceShutdown

protected com.wowza.wms.application.IApplicationInstance **appInstanceShutdown**

---

(continued from last page)

---

## loggedConnect

protected boolean **loggedConnect**

---

## properties

protected com.wowza.wms.application.WMSProperties **properties**

---

## isDescribe

protected boolean **isDescribe**

---

## isAnnounce

protected boolean **isAnnounce**

---

## rtpWriteListener

protected com.wowza.wms.rtp.model.RTPWriteListener **rtpWriteListener**

---

## timeCreated

protected long **timeCreated**

---

## ioPerformanceCounter

protected com.wowza.util.IOPerformanceCounter **ioPerformanceCounter**

---

## totalIOPerformanceLast

protected com.wowza.util.IOPerformanceCounter **totalIOPerformanceLast**

---

## totalIOPerformance2Last

protected com.wowza.util.IOPerformanceCounter **totalIOPerformance2Last**

---

(continued from last page)

## connectionHolder

protected com.wowza.wms.client.ConnectionHolder **connectionHolder**

---

## isConnected

protected boolean **isConnected**

---

## idleHandler

protected com.wowza.wms.rtp.model.RTPIdleHandler **idleHandler**

---

## serverIp

protected java.lang.String **serverIp**

---

## serverPort

protected int **serverPort**

---

## uri

protected java.lang.String **uri**

---

## referrer

protected java.lang.String **referrer**

---

## queryStr

protected java.lang.String **queryStr**

---

## actionListeners

protected java.util.List **actionListeners**

---

## elapsedTime

protected com.wowza.util.ElapsedTimer **elapsedTime**

---



(continued from last page)

---

## idleFrequency

protected int **idleFrequency**

---

---

## debugRTSPSession

protected boolean **debugRTSPSession**

---

---

## rtspPlayRangeStart

protected double **rtspPlayRangeStart**

---

---

## rtspPlayRangeStop

protected double **rtspPlayRangeStop**

---

---

## shutdownClient

protected boolean **shutdownClient**

---

---

## audioPacketizers

protected java.util.Map **audioPacketizers**

---

---

## videoPacketizers

protected java.util.Map **videoPacketizers**

---

---

## streamPacketizers

protected java.util.Map **streamPacketizers**

---

---

## redirectSession

protected boolean **redirectSession**

---

(continued from last page)

---

## redirectSessionCode

protected int **redirectSessionCode**

---

## redirectSessionMessage

protected java.lang.String **redirectSessionMessage**

---

## redirectSessionURL

protected java.lang.String **redirectSessionURL**

---

## lock

protected java.lang.Object **lock**

---

## ioSession

protected org.apache.mina.common.support.BaseIoSession **ioSession**

---

## Constructors

### RTPSession

public **RTPSession**(String sessionId)

Constructor

#### Parameters:

sessionId - session id

## Methods

### acceptSession

public void **acceptSession**()

Accept this session

---

### rejectSession

public void **rejectSession**()

Reject this session

---

(continued from last page)

## getSessionId

```
public String getSessionId()
```

Get session id

**Returns:**

session id

---

## setSessionId

```
public void setSessionId(String sessionId)
```

Set session id

**Parameters:**

sessionId - session id

---

## addRTSPStream

```
public void addRTSPStream(RTSPStream stream)
```

Add RTP stream

**Parameters:**

stream - RTP stream

---

## removeRTSPStream

```
public RTSPStream removeRTSPStream(String streamId)
```

Remove RTP stream

**Parameters:**

streamId - stream id

**Returns:**

RTP stream

---

## getRTSPStream

```
public RTSPStream getRTSPStream(String streamId)
```

Get RTP Stream

**Parameters:**

streamId - stream id

**Returns:**

RTP Stream

---

## getRTSPStream

```
public RTSPStream getRTSPStream()
```

Get the default RTP Stream (all RTP sessions have a single RTP Stream)

**Returns:**

(continued from last page)

RTP stream

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

**Returns:**

vhost

---

## setVHost

```
public void setVHost(IVHost vhost)
```

Set vhost

**Parameters:**

vhost - vhost

---

## getUserAgent

```
public String getUserAgent()
```

Get user agent

**Returns:**

user agent

---

## setUserAgent

```
public void setUserAgent(String userAgent)
```

Set user agent

**Parameters:**

userAgent - user agent

---

## touch

```
public void touch()
```

Touch the stream so it doesn't timeout

---

## shutdown

```
public void shutdown()
```

shutdown RTP session, Internal use.

---

## shutdown

```
public void shutdown(RTPRequestStatus status)
```

shutdown RTP session, Internal use.

**Parameters:**

status

---

## isSessionValid

```
public boolean isSessionValid()
```

Is this session valid

**Returns:**

true if valid

---

## setSessionValid

```
public void setSessionValid(boolean isSessionValid)
```

Set session valid

**Parameters:**

isSessionValid - true if valid

---

## getAuthenticatePublishHandler

```
public IAuthenticateRTSP getAuthenticatePublishHandler()
```

Get the RTP authentication handler

**Returns:**

RTP authentication handler

---

## setAuthenticatePublishHandler

```
public void setAuthenticatePublishHandler(IAuthenticateRTSP  
authenticatePublishHandler)
```

Set the RTP authentication handler

**Parameters:**

authenticatePublishHandler - RTP authentication handler

---

## getAuthenticatePlayHandler

```
public IAuthenticateRTSP getAuthenticatePlayHandler()
```

Get the authentication play handler

**Returns:**

authentication play handler

---

## setAuthenticatePlayHandler

```
public void setAuthenticatePlayHandler(IAuthenticateRTSP authenticatePlayHandler)
```

Set the authentication play handler

**Parameters:**

authenticatePlayHandler - authentication play handler

---

(continued from last page)

## getLastAuthenticateMethod

```
public int getLastAuthenticateMethod()
```

Get the last method received

**Returns:**

last method received

---

## setLastAuthenticateMethod

```
public void setLastAuthenticateMethod(int lastAuthenticateMethod)
```

Set last method received

**Parameters:**

lastAuthenticateMethod - last method received

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get application instance

**Returns:**

application instance

---

## setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set application instance

**Parameters:**

appInstance - application instance

---

## isLoggedConnect

```
public boolean isLoggedConnect()
```

Is connect logged

**Returns:**

true if logged

---

## setLoggedConnect

```
public void setLoggedConnect(boolean loggedConnect)
```

Set connect logged

**Parameters:**

loggedConnect - true if logged

---

## getIp

```
public String getIp()
```

(continued from last page)

Get remote IP address

**Returns:**

remote IP address

---

## setIp

```
public void setIp(String ip)
```

Set remote IP address

**Parameters:**

ip - remote IP address

---

## getProperties

```
public WMSProperties getProperties()
```

Get properties

**Returns:**

properties

---

## isDescribe

```
public boolean isDescribe()
```

Has DESCRIBE command been called on this session

**Returns:**

true if called

---

## setDescribe

```
public void setDescribe(boolean isDescribe)
```

Set DESCRIBE command been called on this session

**Parameters:**

isDescribe - true if called

---

## isAnnounce

```
public boolean isAnnounce()
```

Has ANNOUNCE command been called on this session

**Returns:**

true if called

---

## setAnnounce

```
public void setAnnounce(boolean isAnnounce)
```

Set ANNOUNCE command been called on this session

**Parameters:**

isAnnounce - true if called

---

## isAnnounceOrDescribe

```
public boolean isAnnounceOrDescribe()
```

Has announce or described been called

**Returns:**

true if either called

---

## getRTPWriteListener

```
public RTPWriteListener getRTPWriteListener()
```

Get the RTP write listener for this session

**Returns:**

RTP write listener

---

## addIOPerformance

```
public void addIOPerformance(IOPerformanceCounter totalIOPerformanceResult)
```

Internal use

**Parameters:**

totalIOPerformanceResult - IO performance counter

---

## addIOPerformance2

```
public void addIOPerformance2(IOPerformanceCounter totalIOPerformanceResult)
```

Internal use

**Parameters:**

totalIOPerformanceResult - IO performance counter

---

## getConnectionHolder

```
public ConnectionHolder getConnectionHolder()
```

Get connection holder, Internal use.

**Returns:**

connection holder

---

## isConnected

```
public boolean isConnected()
```

Is session connection

**Returns:**

true if connected

---

## setConnected

```
public void setConnected(boolean isConnected)
```

---



(continued from last page)

Set session is connected

**Parameters:**

isConnected - true if connected

---

## getIdleHandler

```
public RTPIdleHandler getIdleHandler()
```

Get idle handler

**Returns:**

idle handler

---

## setIdleHandler

```
public void setIdleHandler(RTPIdleHandler idleHandler)
```

Set idle handler

**Parameters:**

idleHandler - idle handler

---

## getServerIp

```
public String getServerIp()
```

Get the server IP address

**Returns:**

IP address

---

## setServerIp

```
public void setServerIp(String serverIp)
```

Set the server IP address

**Parameters:**

serverIp - IP address

---

## getServerPort

```
public int getServerPort()
```

Get server port

**Returns:**

server port

---

## setServerPort

```
public void setServerPort(int serverPort)
```

Set server port

**Parameters:**

serverPort - server port

---

## getUri

```
public String getUri()
```

Get URI

**Returns:**  
URI

---

## setUri

```
public void setUri(String uri)
```

Set URI

**Parameters:**  
uri - URI

---

## getReferrer

```
public String getReferrer()
```

Get referrer

**Returns:**  
referrer

---

## setReferrer

```
public void setReferrer(String referrer)
```

Set referrer

**Parameters:**  
referrer - referrer

---

## getQueryStr

```
public String getQueryStr()
```

Get query string

**Returns:**  
query string

---

## setQueryStr

```
public void setQueryStr(String queryStr)
```

Set query string

**Parameters:**  
queryStr - query string

---

## updateLoggingValues

```
public void updateLoggingValues()
```

---

(continued from last page)

Update logging values, Internal use.

---

## clearLoggingValues

```
public void clearLoggingValues()
```

Clear logging values, Internal use.

---

## addActionListener

```
public void addActionListener(IRTSPActionNotify actionListener)
```

Add action listener

**Parameters:**

actionListener - action listener

---

## removeActionListener

```
public void removeActionListener(IRTSPActionNotify actionListener)
```

Remove action listener

**Parameters:**

actionListener - action listener

---

## onDescribe

```
public void onDescribe(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on DESCRIBE command

**Parameters:**

req - RTP request

resp - RTP response

---

## onAnnounce

```
public void onAnnounce(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on ANNOUNCE command

**Parameters:**

req - RTP request

resp - RTP response

---

## onGetParameter

```
public void onGetParameter(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on GET\_PARAMETER command

**Parameters:**

req - RTP request

resp - RTP response

## onSetParameter

```
public void onSetParameter(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on SET\_PARAMETER command

### Parameters:

req - RTP request  
resp - RTP response

---

## onOptions

```
public void onOptions(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on OPTIONS command

### Parameters:

req - RTP request  
resp - RTP response

---

## onPause

```
public void onPause(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on PAUSE command

### Parameters:

req - RTP request  
resp - RTP response

---

## onPlay

```
public void onPlay(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on PLAY command

### Parameters:

req - RTP request  
resp - RTP response

---

## onRecord

```
public void onRecord(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on RECORD command

### Parameters:

req - RTP request  
resp - RTP response

---

(continued from last page)

## onRedirect

```
public void onRedirect(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on REDIRECT command

**Parameters:**

req - RTP request  
resp - RTP response

---

## onSetup

```
public void onSetup(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on SETUP command

**Parameters:**

req - RTP request  
resp - RTP response

---

## onTeardown

```
public void onTeardown(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on TEARDOWN command

**Parameters:**

req - RTP request  
resp - RTP response

---

## getIdleFrequency

```
public int getIdleFrequency()
```

Get idle frequency (milliseconds)

**Returns:**

idle frequency (milliseconds)

---

## setIdleFrequency

```
public void setIdleFrequency(int idleFrequency)
```

Set idle frequency (milliseconds)

**Parameters:**

idleFrequency - idle frequency (milliseconds)

---

## isDebugRTSPSession

```
public boolean isDebugRTSPSession()
```

True if debugging RTSP session

**Returns:**

true if debugging RTSP session

---

## setDebugRTSPSession

```
public void setDebugRTSPSession(boolean debugRTSPSession)
```

Set debugging RTSP session

**Parameters:**

debugRTSPSession - true if debugging RTSP session

---

## getRTSPTunnelingSessionId

```
public String getRTSPTunnelingSessionId()
```

Get the RTSP/RTP tunneling session id

**Returns:**

RTSP/RTP tunneling session id

---

## setRTSPTunnelingSessionId

```
public void setRTSPTunnelingSessionId(String rtspTunnelingSessionId)
```

Set the RTSP/RTP tunneling session id

**Parameters:**

rtspTunnelingSessionId - RTSP/RTP tunneling session id

---

## getRTSPPlayRangeStart

```
public double getRTSPPlayRangeStart()
```

Get play start range, Internal use.

**Returns:**

start range

---

## setRTSPPlayRangeStart

```
public void setRTSPPlayRangeStart(double rtspPlayRangeStart)
```

Set play start range, Internal use.

**Parameters:**

rtspPlayRangeStart - start range

---

## getRTSPPlayRangeStop

```
public double getRTSPPlayRangeStop()
```

Get play stop range, Internal use.

**Returns:**

stop range

---

## setRTSPPlayRangeStop

```
public void setRTSPPlayRangeStop(double rtspPlayRangeStop)
```

---

(continued from last page)

Set play stop range, Internal use.

**Parameters:**

rtspPlayRangeStop - stop range

---

## getCookieStr

```
public String getCookieStr()
```

Get cookie string

**Returns:**

cookie string

---

## setCookieStr

```
public void setCookieStr(String cookieStr)
```

Set cooking string

**Parameters:**

cookieStr - cooking string

---

## getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter()
```

Get IO performance counter

**Returns:**

IO performance counter

---

## setIOPerformanceCounter

```
public void setIOPerformanceCounter(IOPerformanceCounter ioPerformanceCounter)
```

Set IO performance counter

**Parameters:**

ioPerformanceCounter - IO performance counter

---

## isShutdownClient

```
public boolean isShutdownClient()
```

Is RTP session shutdown

**Returns:**

true if shutdown

---

## setShutdownClient

```
public void setShutdownClient(boolean shutdownClient)
```

Set RTP session shutdown

**Parameters:**

shutdownClient - true if shutdown

## getAudioPacketizerItem

```
public RTPPacketizerItem getAudioPacketizerItem(RTPContext rtpContext,  
        IApplicationInstance appInstance,  
        int codecId)
```

Get audio packetizer for a given codec id.

**Parameters:**

rtpContext - RTP context  
appInstance - application instance  
codecId - codec id

**Returns:**

packetizer info

---

## getVideoPacketizerItem

```
public RTPPacketizerItem getVideoPacketizerItem(RTPContext rtpContext,  
        IApplicationInstance appInstance,  
        int codecId)
```

Get video packetizer for a given codec id.

**Parameters:**

rtpContext - RTP context  
appInstance - application instance  
codecId - codec id

**Returns:**

packetizer info

---

## getStreamPacketizerItem

```
public RTPPacketizerItem getStreamPacketizerItem(RTPContext rtpContext,  
        IApplicationInstance appInstance,  
        int codecId)
```

Get stream packetizer for a given codec id.

**Parameters:**

rtpContext - RTP context  
appInstance - application instance  
codecId - codec id

**Returns:**

packetizer info

---

## putAudioPacketizerItem

```
public void putAudioPacketizerItem(int codecId,  
        String classPath)
```

Set the audio packetizer for a given codec id

**Parameters:**

codecId - codec id  
classPath - class path

---



## putVideoPacketizerItem

```
public void putVideoPacketizerItem(int codecId,  
    String classPath)
```

Set the video packetizer for a given codec id

**Parameters:**

codecId - codec id  
classPath - class path

---

## putStreamPacketizerItem

```
public void putStreamPacketizerItem(int codecId,  
    String classPath)
```

Set the stream packetizer for a given codec id

**Parameters:**

codecId - codec id  
classPath - class path

---

## getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get the elapsed timer for this RTP session

**Returns:**

elapsed timer

---

## getTimeRunning

```
public String getTimeRunning()
```

Get the time running for this RTP session

**Returns:**

time running as a string

---

## getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get the number of second this RTP session has been running

**Returns:**

number of second this RTP session has been running

---

## isRedirectSession

```
public boolean isRedirectSession()
```

---

(continued from last page)

---

**setRedirectSession**

```
public void setRedirectSession(boolean redirectSession)
```

---

**getRedirectSessionCode**

```
public int getRedirectSessionCode()
```

---

**setRedirectSessionCode**

```
public void setRedirectSessionCode(int redirectSessionCode)
```

---

**getRedirectSessionURL**

```
public String getRedirectSessionURL()
```

---

**setRedirectSessionURL**

```
public void setRedirectSessionURL(String redirectSessionURL)
```

---

**redirectSession**

```
public void redirectSession(String redirectSessionURL)
```

---

**redirectSession**

```
public void redirectSession(String redirectSessionURL,  
    int redirectSessionCode)
```

---

**getRedirectSessionMessage**

```
public String getRedirectSessionMessage()
```

---

**setRedirectSessionMessage**

```
public void setRedirectSessionMessage(String redirectSessionMessage)
```

---

**getIoSession**

```
public org.apache.mina.common.support.BaseIoSession getIoSession()
```

---

(continued from last page)

---

## setIoSession

```
public void setIoSession(org.apache.mina.common.support.BaseIoSession ioSession)
```

---

## doIdle

```
public void doIdle()
```

## com.wowza.wms.rtp.model

### Class RTPSessions

java.lang.Object

└─com.wowza.wms.rtp.model.RTPSessions

public class **RTPSessions**  
extends Object

RTPSessions: collection of RTP sessions

#### Constructor Summary

public	<a href="#">RTPSessions</a> ( <a href="#">IVHost</a> vhost) Constructor
--------	--

#### Method Summary

<a href="#">RTPSession</a>	<a href="#">addSession</a> ( <a href="#">RTPSession</a> session) Add RTP session
void	<a href="#">addSessionListener</a> ( <a href="#">IRTPSessionNotify</a> listener) Add a RTP session listener
String	<a href="#">getNextSessionId</a> () Get next RTP session id for new session
<a href="#">RTPSession</a>	<a href="#">getSession</a> (String sessionId) Get RTP session by session id
java.util.List	<a href="#">getSessionIds</a> () Get list of current RTP session ids
<a href="#">IVHost</a>	<a href="#">getVHost</a> () Get vhost
void	<a href="#">notifySessionCreate</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">RTPSession</a> rtpSession) Notify session create
void	<a href="#">notifySessionCreate</a> ( <a href="#">RTPSession</a> rtpSession) Notify session create
void	<a href="#">notifySessionDestroy</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">RTPSession</a> rtpSession) Notify session destroy
void	<a href="#">notifySessionDestroy</a> ( <a href="#">RTPSession</a> rtpSession) Notify session destroy
void	<a href="#">releaseSessionId</a> (String sessionIdStr) Release an RTP session id

<a href="#">RTPSession</a>	<a href="#">removeSession</a> ( <a href="#">RTPSession</a> session) Remove RTP session by object
<a href="#">RTPSession</a>	<a href="#">removeSession</a> (String sessionId) Remove RTP session by session id
void	<a href="#">removeSessionListener</a> ( <a href="#">IRTPSessionNotify</a> listener) Remove an RTP session listener

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### RTPSessions

```
public RTPSessions(IVHost vhost)
```

Constructor

**Parameters:**

vhost - vhost

## Methods

### getNextSessionId

```
public String getNextSessionId()
```

Get next RTP session id for new session

**Returns:**

RTP session id

### getSessionIds

```
public java.util.List getSessionIds()
```

Get list of current RTP session ids

**Returns:**

list of current RTP session ids

### releaseSessionId

```
public void releaseSessionId(String sessionIdStr)
```

Release an RTP session id

**Parameters:**

sessionIdStr - RTP session id

(continued from last page)

## getSession

```
public RTPSession getSession(String sessionId)
```

Get RTP session by session id

**Parameters:**

sessionId - session id

**Returns:**

RTP session

---

## removeSession

```
public RTPSession removeSession(String sessionId)
```

Remove RTP session by session id

**Parameters:**

sessionId - session id

**Returns:**

RTP session if removed

---

## removeSession

```
public RTPSession removeSession(RTPSession session)
```

Remove RTP session by object

**Parameters:**

session - RTP session

**Returns:**

RTP session if removed

---

## addSession

```
public RTPSession addSession(RTPSession session)
```

Add RTP session

**Parameters:**

session - RTP session

**Returns:**

RTP session added

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

**Returns:**

vhost

---

(continued from last page)

## addSessionListener

```
public void addSessionListener(IRTPSessionNotify listener)
```

Add a RTP session listener

**Parameters:**

listener - RTP session listener

---

## removeSessionListener

```
public void removeSessionListener(IRTPSessionNotify listener)
```

Remove an RTP session listener

**Parameters:**

listener - RTP session listener

---

## notifySessionCreate

```
public void notifySessionCreate(IApplicationInstance appInstance,  
    RTPSession rtpSession)
```

Notify session create

**Parameters:**

appInstance - application instance

rtpSession - RTP session

---

## notifySessionDestroy

```
public void notifySessionDestroy(IApplicationInstance appInstance,  
    RTPSession rtpSession)
```

Notify session destroy

**Parameters:**

appInstance - application instance

rtpSession - RTP session

---

## notifySessionCreate

```
public void notifySessionCreate(RTPSession rtpSession)
```

Notify session create

**Parameters:**

rtpSession - RTP session

---

## notifySessionDestroy

```
public void notifySessionDestroy(RTPSession rtpSession)
```

Notify session destroy

**Parameters:**

rtpSession - RTP session

---

## com.wowza.wms.rtp.model Class RTPStream

java.lang.Object

└--com.wowza.wms.rtp.model.RTPStream

public class **RTPStream**  
extends Object

RTPStream: RTP Stream class which encapsulates an IMediaStream class for RTP streaming.

### Field Summary

public static final	<a href="#">AVSYNCMETHODS_RTPTIMECODE</a> Value: <b>3</b>
public static final	<a href="#">AVSYNCMETHODS_SENDERREPORT</a> Value: <b>1</b>
public static final	<a href="#">AVSYNCMETHODS_SYSTEMCLOCK</a> Value: <b>2</b>
public static final	<a href="#">AVSYNCMETHODS_UNKNOWN</a> Value: <b>0</b>
public static final	<a href="#">MODE_PLAY</a> Value: <b>1</b>
public static final	<a href="#">MODE_PUBLISH</a> Value: <b>2</b>
public static final	<a href="#">MODE_UNKNOWN</a> Value: <b>0</b>
public static final	<a href="#">SDPLOCATION_AUDIO</a> Value: <b>1</b>
public static final	<a href="#">SDPLOCATION_STREAM</a> Value: <b>0</b>
public static final	<a href="#">SDPLOCATION_VIDEO</a> Value: <b>2</b>
public static final	<a href="#">STREAMINFO_SESSIONATTRIBUTES</a> Value: <b>attributes</b>



public static final	<a href="#">STREAMINFO_SESSIONBANDWIDTH</a> Value: <b>bandwidth</b>
public static final	<a href="#">STREAMINFO_SESSIONCONNECTIONDATA</a> Value: <b>connectiondata</b>
public static final	<a href="#">STREAMINFO_SESSIONEMAILADDRESS</a> Value: <b>emailaddress</b>
public static final	<a href="#">STREAMINFO_SESSIONINFORMATION</a> Value: <b>information</b>
public static final	<a href="#">STREAMINFO_SESSIONNAME</a> Value: <b>name</b>
public static final	<a href="#">STREAMINFO_SESSIONPHONENUMBER</a> Value: <b>phonenum</b>
public static final	<a href="#">STREAMINFO_SESSIONPORIGIN</a> Value: <b>origin</b>
public static final	<a href="#">STREAMINFO_SESSIONPROTOCOLVERSION</a> Value: <b>protocolversion</b>
public static final	<a href="#">STREAMINFO_SESSIONREPEATTIMES</a> Value: <b>repeattimes</b>
public static final	<a href="#">STREAMINFO_SESSIONTIMEZONES</a> Value: <b>timezones</b>
public static final	<a href="#">STREAMINFO_SESSIONTIMING</a> Value: <b>timing</b>
public static final	<a href="#">STREAMINFO_SESSIONURI</a> Value: <b>uri</b>

## Constructor Summary

public	<a href="#">RTPStream(RTPContext context, String streamId)</a> Constructor
--------	---

## Method Summary

void	<a href="#">addStreamAttribute(String key, String value)</a> Add a name value pair to the stream attribute collection
void	<a href="#">addStreamInfo(String key, String value)</a> Add a name value pair to the stream info collection

void	<a href="#"><u>addTrack</u></a> (RTPTrack track) Add a track
void	<a href="#"><u>addTrackId</u></a> (String seq, String trackId) Add track
void	<a href="#"><u>addTrackInternal</u></a> (RTPTrack track) Add RTP track
void	<a href="#"><u>announce</u></a> (RTPRequestStatus status) Execute announce command
void	<a href="#"><u>attachToWMSSession</u></a> (RtmpSessionInfo wmsSessionInfo) Attach to WMS session, Internal use
static int	<a href="#"><u>avSyncNameToId</u></a> (String avSyncName) Get audio/video sync id from name
void	<a href="#"><u>checkSendMetadata</u></a> (long adjTimecode, RTPTrack rtpTrack) Check to see if we have sent onMetadata event, if not send
void	<a href="#"><u>clearRTSPSessionExtraLines</u></a> () Clear SDP extra lines
void	<a href="#"><u>clearTracks</u></a> () Clear all tracks
boolean	<a href="#"><u>createStream</u></a> (RTPRequestStatus status) Create IMediaStream, Internal use.
String	<a href="#"><u>describe</u></a> (RTPSession rtspSession, int isStreamPacketizer, RTPRequestStatus status) Execute describe command
String	<a href="#"><u>describe</u></a> (RTPSession rtspSession, RTPRequestStatus status) Execute describe command
void	<a href="#"><u>detachFromWMSSession</u></a> (RtmpSessionInfo wmsSessionInfo) Detach from WMS session, Internal use.
void	<a href="#"><u>extractCodecConfigFromTrackInfo</u></a> () Extract codec config information from SDP data
String	<a href="#"><u>formatRTPInfo</u></a> (long timecode, int videoSeq, int audioSeq) Format RTP info
<a href="#"><u>IApplicationInstance</u></a>	<a href="#"><u>getAppInstance</u></a> () Get application instance
String	<a href="#"><u>getAppInstanceName</u></a> () Get the application instance name
String	<a href="#"><u>getAppName</u></a> () Get the application name
RTPTrack	<a href="#"><u>getAudioTrack</u></a> () Get the most likely audio track
int	<a href="#"><u>getAutoAllocateInterleavePorts</u></a> ()

int	<a href="#"><u>getAVSyncMethod()</u></a> Get the audio/video sync method.
double	<a href="#"><u>getDuration()</u></a> Get the duration of the stream if video on demand
String	<a href="#"><u>getHost()</u></a> Get host
<a href="#"><u>AMFPacket[]</u></a>	<a href="#"><u>getLastPacketsByType()</u></a> ( <a href="#"><u>IMediaReader</u></a> localReader, double startTime) Analyzes stream to get information, Internal use.
<a href="#"><u>AMFPacket[]</u></a>	<a href="#"><u>getLastPacketsByType()</u></a> ( <a href="#"><u>IMediaStream</u></a> localStream) Analyzes stream to get information, Internal use.
int	<a href="#"><u>getMaxRTCPWaitTime()</u></a> Get max time to wait for RTCP sender reports (milliseconds)
String	<a href="#"><u>getMediaCasterType()</u></a> Get the media caster stream type for this stream
<a href="#"><u>IMediaReader</u></a>	<a href="#"><u>getMediaReader()</u></a> Get media reader if video on demand stream
byte[]	<a href="#"><u>getMetadataPacket()</u></a> Get the onMetadata packet for this RTP stream
int	<a href="#"><u>getMode()</u></a> Get the current play/publish mode
int	<a href="#"><u>getMPEGTSAudioBitrate()</u></a>
String	<a href="#"><u>getMPEGTSAudioLanguage()</u></a>
int	<a href="#"><u>getMPEGTSAudioPID()</u></a> Get the audio PID id if MPEG-TS stream
int	<a href="#"><u>getMPEGTSProgramID()</u></a>
int	<a href="#"><u>getMPEGTSVideoBitrate()</u></a>
int	<a href="#"><u>getMPEGTSVideoPID()</u></a> Get the video PID id if MPEG-TS stream
long	<a href="#"><u>getNormalizedNTPTimecode()</u></a> (long timecode) Turn a millisecond timcode into an NTP timecode
String	<a href="#"><u>getOutHost()</u></a> Get the out host
<a href="#"><u>RTPContext</u></a>	<a href="#"><u>getRTPContext()</u></a> Get the RTP context
<a href="#"><u>RTPDestination</u></a>	<a href="#"><u>getRTPDestination()</u></a> Get RTP destination
RTPStream.RTPInfo	<a href="#"><u>getRTPInfo()</u></a> (double startTime, int videoSeq, int audioSeq) Get the RTP info

RTPStreamContext	<a href="#"><u>getRTPStreamContext()</u></a>
String	<a href="#"><u>getRTSPBindIpAddress()</u></a> Get the bind RTSP bind IP address
String	<a href="#"><u>getRTSPConnectionAddressType()</u></a> Get the connection address type
String	<a href="#"><u>getRTSPConnectionIpAddress()</u></a> Get the connection IP address
int	<a href="#"><u>getRTSPMaximumPendingWriteBytes()</u></a> Get the maximum number of waiting bytes allow for this RTSP session
String	<a href="#"><u>getRTSPOriginAddressType()</u></a> Get the origin address type
String	<a href="#"><u>getRTSPOriginIpAddress()</u></a> Get the origin IP address
String	<a href="#"><u>getRTSPSessionDescription()</u></a> Get session description
java.util.List	<a href="#"><u>getRTSPSessionExtraLines()</u></a> Get extra SDP lines
String	<a href="#"><u>getRTSPSessionName()</u></a> Get session name
int	<a href="#"><u>getRTSPSessionTimeout()</u></a> Get RTP session timeout (milliseconds)
String	<a href="#"><u>getSDPLang()</u></a> Get the SDP language
<a href="#"><u>RTPSession</u></a>	<a href="#"><u>getSession()</u></a> Get the RTP session
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream()</u></a> Get the IMediaStream
java.util.Map	<a href="#"><u>getStreamAttributes()</u></a> Get all name/value pairs in the stream attributes collection
String	<a href="#"><u>getStreamExt()</u></a> Get the stream extension
String	<a href="#"><u>getStreamId()</u></a> Get the stream id
java.util.Map	<a href="#"><u>getStreamInfo()</u></a> Get all name/value pairs in the stream info collection
String	<a href="#"><u>getStreamInfo(String key)</u></a> Get stream info by name
Object	<a href="#"><u>getStreamLock()</u></a> Get the synchronization lock for this stream

String	<a href="#"><u>getStreamName()</u></a> Get stream name
String	<a href="#"><u>getStreamNameLogging()</u></a> Get the stream name used for logging
String	<a href="#"><u>getStreamQueryStr()</u></a> Get the stream query string
long	<a href="#"><u>getStreamSessionId()</u></a> Get the stream session id
String	<a href="#"><u>getStreamSessionIp()</u></a> Get the stream session ip
long	<a href="#"><u>getStreamSessionVersion()</u></a> Get the stream session version
RTPTrack	<a href="#"><u>getStreamTrack()</u></a> Get the most likely stream track
String	<a href="#"><u>getStreamType()</u></a> Get the stream type
RTPTrack	<a href="#"><u>getTrack(String trackId)</u></a> Get track by id
String	<a href="#"><u>getTrackId(String seq)</u></a> Get track by sequence number
java.util.List	<a href="#"><u>getTrackNames()</u></a> Get a list of track ids
String	<a href="#"><u>getTransportMode()</u></a> Get the transport mode
int	<a href="#"><u>getUDPManagedDeliveryCount()</u></a>
int	<a href="#"><u>getUDPManagedDeliveryDelay()</u></a>
com.wowza.wms.rtp.transport.IUDPTransport	<a href="#"><u>getUDPTransport(boolean isMulticast)</u></a> Get the UDP transport for this stream
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost()</u></a> Get vhost
RTPTrack	<a href="#"><u>getVideoTrack()</u></a> Get the most likely video track
long	<a href="#"><u>getVODLastTimeTC()</u></a> Get the last timecode (milliseconds) sent for video on demand
long	<a href="#"><u>getVODPlayLen()</u></a> Get the video on demand play duration (milliseconds)
long	<a href="#"><u>getVODStartTimeTC()</u></a> Get the video on demand start time (milliseconds)

void	<a href="#"><u>idle</u></a> (org.apache.mina.common.IoSession session, RtmpResponseMessage resp) Process idle event
void	<a href="#"><u>incrementMediaInBytes</u></a> (long bytes) Increment the media bytes in, Internal use.
void	<a href="#"><u>initProperties</u></a> ( <a href="#"><u>IApplicationInstance</u></a> appInstance)
boolean	<a href="#"><u>isAVSyncNonSR</u></a> () Is sync method based on RTCP packets (sender report)
boolean	<a href="#"><u>isBlockUDPOut</u></a> ()
boolean	<a href="#"><u>isCheckIpAddr</u></a> () Are we checking the ip address of each incoming RTP packet
boolean	<a href="#"><u>isCheckSSRC</u></a> () Are we checking the ssrc values of each incoming RTP packet
boolean	<a href="#"><u>isForceMPEGTSOut</u></a> ()
boolean	<a href="#"><u>isForceRTSPInterleaved</u></a> () True if forcing RTSP interleaved
boolean	<a href="#"><u>isLive</u></a> () Is live stream
boolean	<a href="#"><u>isModePlay</u></a> () Is this a play stream
boolean	<a href="#"><u>isModePublish</u></a> () Is this a publish stream
boolean	<a href="#"><u>isModeUnknown</u></a> () Is the stream mode unknown (publish vs play)
boolean	<a href="#"><u>isMPEGTSOut</u></a> () Is MPEG-TS out
boolean	<a href="#"><u>isPaused</u></a> () Is stream paused
boolean	<a href="#"><u>isPublishStreamReady</u></a> () See if a publishing stream has enough data to start playback
boolean	<a href="#"><u>isResetPlayStream</u></a> () Is reset stream trigger, Internal use.
boolean	<a href="#"><u>isResyncAudioVideoOnSR</u></a> () Reset audio/video sync on new RTCP packets (not just first packet)
boolean	<a href="#"><u>isRTPIgnoreProfileLevelId</u></a> ()
boolean	<a href="#"><u>isRTPIgnoreSPropParameterSets</u></a> ()

boolean	<a href="#"><u>isRTSP()</u></a> Is this RTP Stream managed by RTSP session
boolean	<a href="#"><u>isRTSPAlwaysUseSDPPorts()</u></a> Force RTSP to use ports in SDP data
boolean	<a href="#"><u>isRTSPPull()</u></a> Is this RTP Stream managed by RTSP session
boolean	<a href="#"><u>isSendSDESEvents()</u></a> Send RTCP SDES events
boolean	<a href="#"><u>isStreamStarted()</u></a> Is stream started
boolean	<a href="#"><u>isTimeout()</u></a> (long currTime, int timeout) Is the stream timeout out
void	<a href="#"><u>lockRepeaterStreams()</u></a> (java.util.List streamNames) Lock a list of live repeater stream names, Internal use.
void	<a href="#"><u>pause()</u></a> (RTPRequestStatus status) Execute pause
RTPStreamPlayResult	<a href="#"><u>play()</u></a> (RTPRequestStatus status) Execute play
RTPStreamPlayResult	<a href="#"><u>play()</u></a> (RTPRequestStatus status, double startTime, double stopTime) Execute play
void	<a href="#"><u>putRTSPSessionExtraLine()</u></a> (int location, String line) Add an extra line to the SDP data
RTPStreamPlayResult	<a href="#"><u>record()</u></a> (RTPRequestStatus status) Execute record
RTPStreamPlayResult	<a href="#"><u>record()</u></a> (RTPRequestStatus status, double startTime, double stopTime) Execute record
RTPTrack	<a href="#"><u>removeTrack()</u></a> (String trackId) Remove a track by id
RTPTrack	<a href="#"><u>removeTrackInternal()</u></a> (String trackId) Remove track by track id
void	<a href="#"><u>resetSentMetadataFlag()</u></a> Reset sendMetadata flag
void	<a href="#"><u>setAppInstanceName()</u></a> (String appInstanceName) Set the application instance name
void	<a href="#"><u>setAppName()</u></a> (String appName) Get the application name
void	<a href="#"><u>setAVSyncMethod()</u></a> (int avSyncMethod) Set the audio/video sync method.
void	<a href="#"><u>setBlockUDPOut()</u></a> (boolean blockUDPOut)

void	<a href="#"><u>setCheckIpAddr</u></a> (boolean checkIpAddr) Are we checking the ip address of each incoming RTP packet
void	<a href="#"><u>setCheckSSRC</u></a> (boolean checkSSRC) Are we checking the ssrc values of each incoming RTP packet
void	<a href="#"><u>setForceMPEGTSOut</u></a> (boolean isForceMPEGTSOut)
void	<a href="#"><u>setForceRTSPInterleaved</u></a> (boolean isForceRTSPInterleaved) True if forcing RTSP interleaved
void	<a href="#"><u>setHost</u></a> (String host) Set host
void	<a href="#"><u>setLive</u></a> (boolean isLive) Is live stream
void	<a href="#"><u>setMaxRTCPWaitTime</u></a> (int maxRTCPWaitTime) Set max time to wait for RTCP sender reports (milliseconds)
void	<a href="#"><u>setMode</u></a> (int mode) Set the play/publish mode
void	<a href="#"><u>setMPEGTSAudioBitrate</u></a> (int mpegtsAudioBitrate)
void	<a href="#"><u>setMPEGTSAudioLanguage</u></a> (String mpegtsAudioLanguage)
void	<a href="#"><u>setMPEGTSAudioPID</u></a> (int mpegtsAudioPID) Set the audio PID id if MPEG-TS stream
void	<a href="#"><u>setMPEGTSOut</u></a> (boolean isMPEGTSOut) Is MPEG-TS out
void	<a href="#"><u>setMPEGTSProgramID</u></a> (int mpegtsProgramId)
void	<a href="#"><u>setMPEGTSVideoBitrate</u></a> (int mpegtsVideoBitrate)
void	<a href="#"><u>setMPEGTSVideoPID</u></a> (int mpegtsVideoPID) Set the video PID id if MPEG-TS stream
void	<a href="#"><u>setOutHost</u></a> (String outHost) Set out host
void	<a href="#"><u>setResetPlayStream</u></a> (boolean doResetPlayStream) Set reset stream trigger
void	<a href="#"><u>setResyncAudioVideoOnSR</u></a> (boolean resyncAudioVideoOnSR) Reset audio/video sync on new RTCP packets (not just first packet)
void	<a href="#"><u>setRTPDestination</u></a> ( <a href="#"><u>RTPDestination</u></a> rtpDestination) Set RTP destination
void	<a href="#"><u>setRTPIgnoreProfileLevelId</u></a> (boolean rtpIgnoreProfileLevelId)
void	<a href="#"><u>setRTPIgnoreSPropParameterSets</u></a> (boolean rtpIgnoreSPropParameterSets)



void	<a href="#"><u>setRTPStreamContext</u></a> (RTPStreamContext rtpStreamContext) Is this RTP Stream managed by RTSP session
void	<a href="#"><u>setRTSP</u></a> (boolean isRTSP) Is this RTP Stream managed by RTSP session
void	<a href="#"><u>setRTSPAlwaysUseSDPPorts</u></a> (boolean rtspAlwaysUseSDPPorts) Force RTSP to use ports in SDP data
void	<a href="#"><u>setRTSPBindIpAddress</u></a> (String rtspBindIpAddress) Set the bind RTSP bind IP address
void	<a href="#"><u>setRTSPConnectionAddressType</u></a> (String rtspConnectionAddressType) Set the connection address type
void	<a href="#"><u>setRTSPConnectionIpAddress</u></a> (String rtspConnectionIpAddress) Set the connection IP address
void	<a href="#"><u>setRTSPMaximumPendingWriteBytes</u></a> (int rtspMaximumPendingWriteBytes) Set the maximum number of waiting bytes allow for this RTSP session
void	<a href="#"><u>setRTSPOriginAddressType</u></a> (String rtspOriginAddressType) Set the origin address type
void	<a href="#"><u>setRTSPOriginIpAddress</u></a> (String rtspOriginIpAddress) Set the origin IP address
void	<a href="#"><u>setRTSPPull</u></a> (boolean isRTSPPull) Is this RTP Stream managed by RTSP session
void	<a href="#"><u>setRTSPSessionDescription</u></a> (String rtspSessionDescription) Get session description
void	<a href="#"><u>setRTSPSessionName</u></a> (String rtspSessionName) Set session name
void	<a href="#"><u>setRTSPSessionTimeout</u></a> (int rtspSessionTimeout) Set RTP session timeout (milliseconds)
void	<a href="#"><u>setSDPLang</u></a> (String sdpLang) Set the SDP language
void	<a href="#"><u>setSendSDESEvents</u></a> (boolean sendSDESEvents) Send RTCP SDES events
void	<a href="#"><u>setSession</u></a> ( <a href="#"><u>RTPSession</u></a> session) Set the RTP session
void	<a href="#"><u>setStreamExt</u></a> (String streamExt) Set the stream extension
void	<a href="#"><u>setStreamName</u></a> (String streamName) Set stream name
void	<a href="#"><u>setStreamNameLogging</u></a> (String streamNameLogging) Set the stream name used for logging
void	<a href="#"><u>setStreamQueryStr</u></a> (String streamQueryStr) Set the stream query string

void	<a href="#"><u>setStreamSessionId</u></a> (long streamSessionId) Set the stream session id
void	<a href="#"><u>setStreamSessionIp</u></a> (String streamSessionIp) Set the stream session ip
void	<a href="#"><u>setStreamSessionVersion</u></a> (long streamSessionVersion) Set the stream session version
void	<a href="#"><u>setStreamType</u></a> (String streamType) Set the stream type
void	<a href="#"><u>setTransportMode</u></a> (String transportMode) Set the transport mode
void	<a href="#"><u>setUDPMangedDeliveryCount</u></a> (int udpManagedDeliveryCount)
void	<a href="#"><u>setUDPMangedDeliveryDelay</u></a> (int udpManagedDeliveryDelay)
void	<a href="#"><u>setVODLastTimeTC</u></a> (long vodLastTimeTC) Set the last timecode (milliseconds) sent for video on demand
void	<a href="#"><u>setVODPlayLen</u></a> (long vodPlayLen) Set the video on demand play duration (milliseconds)
void	<a href="#"><u>setVODStartTimeTC</u></a> (long vodStartTimeTC) Set the video on demand start time (milliseconds)
void	<a href="#"><u>shutdown</u></a> (RTPRequestStatus status) shutdown RTP stream, Internal use.
RTPTrack	<a href="#"><u>sloppyGetTrack</u></a> (String trackId) Sloppy method for finding track by name, Internal use.
boolean	<a href="#"><u>streamExists</u></a> ( ) Return true if RTP stream contains a IMediaStream
void	<a href="#"><u>switchSetupToMPEGTS</u></a> ( ) Switch a stream to MPEG-TS, Internal use.
void	<a href="#"><u>touch</u></a> ( ) Touch the stream so that it does not timeout
String	<a href="#"><u>transportFindBestMatch</u></a> (String transport) Based on a trasport string from SETUP command find best match
void	<a href="#"><u>unlockRepeaterStreams</u></a> ( ) Unlock live repeater streams

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Fields**

(continued from last page)

---

## SDPLOCATION\_STREAM

```
public static final int SDPLOCATION_STREAM
```

Constant value: **0**

---

## SDPLOCATION\_AUDIO

```
public static final int SDPLOCATION_AUDIO
```

Constant value: **1**

---

## SDPLOCATION\_VIDEO

```
public static final int SDPLOCATION_VIDEO
```

Constant value: **2**

---

## MODE\_UNKNOWN

```
public static final int MODE_UNKNOWN
```

Constant value: **0**

---

## MODE\_PLAY

```
public static final int MODE_PLAY
```

Constant value: **1**

---

## MODE\_PUBLISH

```
public static final int MODE_PUBLISH
```

Constant value: **2**

---

## AVSYNCMETHODS\_UNKNOWN

```
public static final int AVSYNCMETHODS_UNKNOWN
```

Constant value: **0**

---

## AVSYNCMETHODS\_SENDERREPORT

```
public static final int AVSYNCMETHODS_SENDERREPORT
```

Constant value: **1**

---

(continued from last page)

---

## AVSYNCMETHODS\_SYSTEMCLOCK

```
public static final int AVSYNCMETHODS_SYSTEMCLOCK
```

Constant value: **2**

---

## AVSYNCMETHODS\_RTPTIMECODE

```
public static final int AVSYNCMETHODS_RTPTIMECODE
```

Constant value: **3**

---

## STREAMINFO\_SESSIONPROTOCOLVERSION

```
public static final java.lang.String STREAMINFO_SESSIONPROTOCOLVERSION
```

Constant value: **protocolversion**

---

## STREAMINFO\_SESSIONPORIGIN

```
public static final java.lang.String STREAMINFO_SESSIONPORIGIN
```

Constant value: **origin**

---

## STREAMINFO\_SESSIONNAME

```
public static final java.lang.String STREAMINFO_SESSIONNAME
```

Constant value: **name**

---

## STREAMINFO\_SESSIONINFORMATION

```
public static final java.lang.String STREAMINFO_SESSIONINFORMATION
```

Constant value: **information**

---

## STREAMINFO\_SESSIONURI

```
public static final java.lang.String STREAMINFO_SESSIONURI
```

Constant value: **uri**

---

## STREAMINFO\_SESSIONEMAILADDRESS

```
public static final java.lang.String STREAMINFO_SESSIONEMAILADDRESS
```

Constant value: **emailaddress**

---

## STREAMINFO\_SESSIONPHONENUMBER

```
public static final java.lang.String STREAMINFO_SESSIONPHONENUMBER
```

(continued from last page)

Constant value: **phonenumber**

---

## STREAMINFO\_SESSIONCONNECTIONDATA

```
public static final java.lang.String STREAMINFO_SESSIONCONNECTIONDATA
```

Constant value: **connectiondata**

---

## STREAMINFO\_SESSIONBANDWIDTH

```
public static final java.lang.String STREAMINFO_SESSIONBANDWIDTH
```

Constant value: **bandwidth**

---

## STREAMINFO\_SESSIONTIMING

```
public static final java.lang.String STREAMINFO_SESSIONTIMING
```

Constant value: **timing**

---

## STREAMINFO\_SESSIONREPEATTIMES

```
public static final java.lang.String STREAMINFO_SESSIONREPEATTIMES
```

Constant value: **repeattimes**

---

## STREAMINFO\_SESSIONTIMEZONES

```
public static final java.lang.String STREAMINFO_SESSIONTIMEZONES
```

Constant value: **timezones**

---

## STREAMINFO\_SESSIONATTRIBUTES

```
public static final java.lang.String STREAMINFO_SESSIONATTRIBUTES
```

Constant value: **attributes**

---

## Constructors

### RTPStream

```
public RTPStream(RTPContext context,  
                 String streamId)
```

Constructor

**Parameters:**

context - RTP context

streamId - stream id

---

## Methods

(continued from last page)

---

## getRTPContext

```
public RTPContext getRTPContext()
```

Get the RTP context

**Returns:**

RTP context

---

## getStreamLock

```
public Object getStreamLock()
```

Get the synchronization lock for this stream

**Returns:**

synchronization lock for this stream

---

## addTrack

```
public void addTrack(RTPTrack track)
```

Add a track

**Parameters:**

track - RTP track

---

## removeTrack

```
public RTPTrack removeTrack(String trackId)
```

Remove a track by id

**Parameters:**

trackId - track id

**Returns:**

RTP track

---

## addTrackInternal

```
public void addTrackInternal(RTPTrack track)
```

Add RTP track

**Parameters:**

track - RTP track

---

## removeTrackInternal

```
public RTPTrack removeTrackInternal(String trackId)
```

Remove track by track id

**Parameters:**

trackId - track id

**Returns:**

(continued from last page)

RTP track that was removed

---

## clearTracks

```
public void clearTracks()
```

Clear all tracks

---

## incrementMediaInBytes

```
public void incrementMediaInBytes(long bytes)
```

Increment the media bytes in, Internal use.

**Parameters:**

bytes

---

## sloppyGetTrack

```
public RTPTrack sloppyGetTrack(String trackId)
```

Sloppy method for finding track by name, Internal use.

**Parameters:**

trackId - track name

**Returns:**

RTP track

---

## getTrack

```
public RTPTrack getTrack(String trackId)
```

Get track by id

**Parameters:**

trackId - track id

**Returns:**

RTP track

---

## addTrackId

```
public void addTrackId(String seq,  
    String trackId)
```

Add track

**Parameters:**

seq - sequence number

trackId - track id

---

## getTrackId

```
public String getTrackId(String seq)
```

Get track by sequence number

**Parameters:**

(continued from last page)

seq - sequence number

**Returns:**

RTP track

---

## getTrackNames

```
public java.util.List getTrackNames()
```

Get a list of track ids

**Returns:**

list of track ids

---

## getSession

```
public RTPSession getSession()
```

Get the RTP session

**Returns:**

RTP session

---

## setSession

```
public void setSession(RTPSession session)
```

Set the RTP session

**Parameters:**

session - RTP session

---

## getStreamId

```
public String getStreamId()
```

Get the stream id

**Returns:**

stream id

---

## getStream

```
public IMediaStream getStream()
```

Get the IMediaStream

**Returns:**

stream (IMediaStream) interface

---

## getAudioTrack

```
public RTPTrack getAudioTrack()
```

Get the most likely audio track

**Returns:**

RTP track



## getVideoTrack

```
public RTPTrack getVideoTrack()
```

Get the most likely video track

**Returns:**

RTP track

---

## getStreamTrack

```
public RTPTrack getStreamTrack()
```

Get the most likely stream track

**Returns:**

RTP track

---

## addStreamInfo

```
public void addStreamInfo(String key,  
                           String value)
```

Add a name value pair to the stream info collection

**Parameters:**

key - name

value - value

---

## getStreamInfo

```
public String getStreamInfo(String key)
```

Get stream info by name

**Parameters:**

key - name

**Returns:**

value

---

## addStreamAttribute

```
public void addStreamAttribute(String key,  
                               String value)
```

Add a name value pair to the stream attribute collection

**Parameters:**

key - name

value - value

---

## getVHost

```
public IVHost getVHost()
```

Get vhost

---

(continued from last page)

**Returns:**  
vhost

---

## getHost

```
public String getHost()
```

Get host

**Returns:**  
host

---

## setHost

```
public void setHost(String host)
```

Set host

**Parameters:**  
host - host

---

## streamExists

```
public boolean streamExists()
```

Return true if RTP stream contains a IMediaStream

**Returns:**  
true if RTP stream contains a IMediaStream

---

## isPublishStreamReady

```
public boolean isPublishStreamReady()
```

See if a publishing stream has enough data to start playback

**Returns:**  
true, if the stream is ready for playback

---

## lockRepeaterStreams

```
public void lockRepeaterStreams(java.util.List streamNames)
```

Lock a list of live repeater stream names, Internal use.

**Parameters:**  
streamNames - stream names

---

## unlockRepeaterStreams

```
public void unlockRepeaterStreams()
```

Unlock live repeater streams

---

## getMediaCasterType

```
public String getMediaCasterType()
```

(continued from last page)

Get the media caster stream type for this stream

**Returns:**

media caster stream type

---

## createStream

```
public boolean createStream(RTPRequestStatus status)
```

Create IMediaStream, Internal use.

**Parameters:**

status - status

**Returns:**

true if successful

---

## shutdown

```
public void shutdown(RTPRequestStatus status)
```

shutdown RTP stream, Internal use.

**Parameters:**

status - status

---

## initProperties

```
public void initProperties(IApplicationInstance appInstance)
```

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get application instance

**Returns:**

application instance

---

## isPaused

```
public boolean isPaused()
```

Is stream paused

**Returns:**

true if stream is paused

---

## getDuration

```
public double getDuration()
```

Get the duration of the stream if video on demand

**Returns:**

duration in seconds

## isResetPlayStream

```
public boolean isResetPlayStream()
```

Is reset stream trigger, Internal use.

**Returns:**

true if reset trigger

---

## setResetPlayStream

```
public void setResetPlayStream(boolean doResetPlayStream)
```

Set reset stream trigger

**Parameters:**

doResetPlayStream - true if reset trigger

---

## record

```
public RTPStreamPlayResult record(RTPRequestStatus status)
```

Execute record

**Parameters:**

status - RTP status

**Returns:**

status

---

## record

```
public RTPStreamPlayResult record(RTPRequestStatus status,  
    double startTime,  
    double stopTime)
```

Execute record

**Parameters:**

status - RTP status

startTime - playback start time

stopTime - playback stop time

**Returns:**

status

---

## play

```
public RTPStreamPlayResult play(RTPRequestStatus status)
```

Execute play

**Parameters:**

status - RTP status

**Returns:**

status

---

## play

```
public RTPStreamPlayResult play(RTPRequestStatus status,  
    double startTime,  
    double stopTime)
```

Execute play

### Parameters:

status - RTP status  
startTime - playback start time  
stopTime - playback stop time

### Returns:

status

---

## attachToWMSSession

```
public void attachToWMSSession(RtmpSessionInfo wmsSessionInfo)
```

Attach to WMS session, Internal use

### Parameters:

wmsSessionInfo - session info

---

## detachFromWMSSession

```
public void detachFromWMSSession(RtmpSessionInfo wmsSessionInfo)
```

Detach from WMS session, Internal use.

### Parameters:

wmsSessionInfo - session info

---

## pause

```
public void pause(RTPRequestStatus status)
```

Execute pause

### Parameters:

status - RTP status

---

## announce

```
public void announce(RTPRequestStatus status)
```

Execute announce command

### Parameters:

status - RTP status

---

## isResyncAudioVideoOnSR

```
public boolean isResyncAudioVideoOnSR()
```

Reset audio/video sync on new RTCP packets (not just first packet)

---

(continued from last page)

**Returns:**

true if resetting audio/video on new RTCP packets

---

**setResyncAudioVideoOnSR**

```
public void setResyncAudioVideoOnSR(boolean resyncAudioVideoOnSR)
```

Reset audio/video sync on new RTCP packets (not just first packet)

**Parameters:**

resyncAudioVideoOnSR - true if resetting audio/video on new RTCP packets

---

**getMetadataPacket**

```
public byte[] getMetadataPacket()
```

Get the onMetadata packet for this RTP stream

**Returns:**

onMetadata packet

---

**resetSentMetadataFlag**

```
public void resetSentMetadataFlag()
```

Reset sendMetadata flag

---

**checkSendMetadata**

```
public void checkSendMetadata(long adjTimecode,  
    RTPTrack rtpTrack)
```

Check to see if we have sent onMetadata event, if not send

**Parameters:**

adjTimecode - timecode (milliseconds)

---

**extractCodecConfigFromTrackInfo**

```
public void extractCodecConfigFromTrackInfo()
```

Extract codec config information from SDP data

---

**getStreamType**

```
public String getStreamType()
```

Get the stream type

**Returns:**

stream type

---

**setStreamType**

```
public void setStreamType(String streamType)
```

Set the stream type

(continued from last page)

**Parameters:**

streamType - stream type

---

**getAppName**

```
public String getAppName()
```

Get the application name

**Returns:**

application name

---

**setAppName**

```
public void setAppName(String appName)
```

Get the application name

**Parameters:**

appName - application name

---

**getAppInstanceName**

```
public String getAppInstanceName()
```

Get the application instance name

**Returns:**

application instance name

---

**setAppInstanceName**

```
public void setAppInstanceName(String appInstanceName)
```

Set the application instance name

**Parameters:**

appInstanceName - application instance name

---

**getStreamExt**

```
public String getStreamExt()
```

Get the stream extension

**Returns:**

stream extension

---

**setStreamExt**

```
public void setStreamExt(String streamExt)
```

Set the stream extension

**Parameters:**

streamExt - stream extension

(continued from last page)

## getStreamName

```
public String getStreamName()
```

Get stream name

**Returns:**

stream name

---

## setStreamName

```
public void setStreamName(String streamName)
```

Set stream name

**Parameters:**

streamName - stream name

---

## getStreamNameLogging

```
public String getStreamNameLogging()
```

Get the stream name used for logging

**Returns:**

stream name used for logging

---

## setStreamNameLogging

```
public void setStreamNameLogging(String streamNameLogging)
```

Set the stream name used for logging

**Parameters:**

streamNameLogging - stream name used for logging

---

## getStreamSessionId

```
public long getStreamSessionId()
```

Get the stream session id

**Returns:**

stream session id

---

## setStreamSessionId

```
public void setStreamSessionId(long streamSessionId)
```

Set the stream session id

**Parameters:**

streamSessionId - stream session id

---

## getStreamSessionVersion

```
public long getStreamSessionVersion()
```



(continued from last page)

Get the stream session version

**Returns:**

stream session version

---

## setStreamSessionVersion

```
public void setStreamSessionVersion(long streamSessionVersion)
```

Set the stream session version

**Parameters:**

streamSessionVersion - stream session version

---

## getStreamSessionIp

```
public String getStreamSessionIp()
```

Get the stream session ip

**Returns:**

stream session ip

---

## setStreamSessionIp

```
public void setStreamSessionIp(String streamSessionIp)
```

Set the stream session ip

**Parameters:**

streamSessionIp - stream session ip

---

## isCheckSSRC

```
public boolean isCheckSSRC()
```

Are we checking the ssrc values of each incoming RTP packet

**Returns:**

true if checking

---

## setCheckSSRC

```
public void setCheckSSRC(boolean checkSSRC)
```

Are we checking the ssrc values of each incoming RTP packet

**Parameters:**

checkSSRC - true if checking

---

## isCheckIpAddr

```
public boolean isCheckIpAddr()
```

Are we checking the ip address of each incoming RTP packet

**Returns:**

true if checking ip address of each incoming RTP packet

## setCheckIpAddr

```
public void setCheckIpAddr(boolean checkIpAddr)
```

Are we checking the ip address of each incoming RTP packet

**Parameters:**

checkIpAddr - true if checking ip address of each incoming RTP packet

---

## getUDPTransport

```
public com.wowza.wms.rtp.transport.IUDPTransport getUDPTransport(boolean isMulticast)
```

Get the UDP transport for this stream

**Parameters:**

isMulticast - true if multicast

**Returns:**

UDP transport

---

## getAVSyncMethod

```
public int getAVSyncMethod()
```

Get the audio/video sync method. See AVSYNCMETHODS\_\*

**Returns:**

audio/video sync method. See AVSYNCMETHODS\_\*

---

## setAVSyncMethod

```
public void setAVSyncMethod(int avSyncMethod)
```

Set the audio/video sync method. See AVSYNCMETHODS\_\*

**Parameters:**

avSyncMethod - audio/video sync method. See AVSYNCMETHODS\_\*

---

## isAVSyncNonSR

```
public boolean isAVSyncNonSR()
```

Is sync method based on RTCP packets (sender report)

**Returns:**

true if based in RTCP sender reports

---

## getMaxRTCPWaitTime

```
public int getMaxRTCPWaitTime()
```

Get max time to wait for RTCP sender reports (milliseconds)

**Returns:**

max time to wait for RTCP sender reports (milliseconds)

---

## setMaxRTCPWaitTime

```
public void setMaxRTCPWaitTime(int maxRTCPWaitTime)
```

Set max time to wait for RTCP sender reports (milliseconds)

**Parameters:**

maxRTCPWaitTime - max time to wait for RTCP sender reports (milliseconds)

---

## getStreamInfo

```
public java.util.Map getStreamInfo()
```

Get all name/value pairs in the stream info collection

**Returns:**

map of name/value pairs

---

## getStreamAttributes

```
public java.util.Map getStreamAttributes()
```

Get all name/value pairs in the stream attributes collection

**Returns:**

map of name/value pairs

---

## avSyncNameToId

```
public static int avSyncNameToId(String avSyncName)
```

Get audio/video sync id from name

**Parameters:**

avSyncName - audio/video sync name

**Returns:**

audio/video sync id, see AVSYNCMETHODS\_\*

---

## getMPEGTSAudioLanguage

```
public String getMPEGTSAudioLanguage()
```

---

## setMPEGTSAudioLanguage

```
public void setMPEGTSAudioLanguage(String mpegtsAudioLanguage)
```

---

## getMPEGTSProgramID

```
public int getMPEGTSProgramID()
```

---

---

## setMPEGTSProgramID

```
public void setMPEGTSProgramID(int mpegTsProgramId)
```

---

## getMPEGTSVideoPID

```
public int getMPEGTSVideoPID()
```

Get the video PID id if MPEG-TS stream

**Returns:**

video PID id if MPEG-TS stream

---

## setMPEGTSVideoPID

```
public void setMPEGTSVideoPID(int mpegTsVideoPID)
```

Set the video PID id if MPEG-TS stream

**Parameters:**

mpegTsVideoPID - video PID id if MPEG-TS stream

---

## getMPEGTSAudioPID

```
public int getMPEGTSAudioPID()
```

Get the audio PID id if MPEG-TS stream

**Returns:**

audio PID id if MPEG-TS stream

---

## setMPEGTSAudioPID

```
public void setMPEGTSAudioPID(int mpegTsAudioPID)
```

Set the audio PID id if MPEG-TS stream

**Parameters:**

mpegTsAudioPID - audio PID id if MPEG-TS stream

---

## isRTSP

```
public boolean isRTSP()
```

Is this RTP Stream managed by RTSP session

**Returns:**

true if managed by RTSP session

---

## setRTSP

```
public void setRTSP(boolean isRTSP)
```

Is this RTP Stream managed by RTSP session

(continued from last page)

**Parameters:**`isRTSP` - true if managed by RTSP session

---

**isRTSPPull**

```
public boolean isRTSPPull()
```

Is this RTP Stream managed by RTSP session

**Returns:**

true if managed by RTSP session

---

**setRTSPPull**

```
public void setRTSPPull(boolean isRTSPPull)
```

Is this RTP Stream managed by RTSP session

**Parameters:**`isRTSPPull` - true if managed by RTSP session

---

**getStreamQueryStr**

```
public String getStreamQueryStr()
```

Get the stream query string

**Returns:**

stream query string

---

**setStreamQueryStr**

```
public void setStreamQueryStr(String streamQueryStr)
```

Set the stream query string

**Parameters:**`streamQueryStr` - stream query string

---

**isModePublish**

```
public boolean isModePublish()
```

Is this a publish stream

**Returns:**

true if publish stream

---

**isModePlay**

```
public boolean isModePlay()
```

Is this a play stream

**Returns:**

true if play stream

(continued from last page)

## isModeUnknown

```
public boolean isModeUnknown()
```

Is the stream mode unknown (publish vs play)

**Returns:**

true if stream mode is unknown

---

## getOutHost

```
public String getOutHost()
```

Get the out host

**Returns:**

out host

---

## setOutHost

```
public void setOutHost(String outHost)
```

Set out host

**Parameters:**

outHost - out host

---

## idle

```
public void idle(org.apache.mina.common.Session session,  
    RtmpResponseMessage resp)
```

Process idle event

**Parameters:**

session - io session

resp - idle request

---

## getLastPacketsByType

```
public AMFPacket\[\] getLastPacketsByType(IMediaStream localStream)
```

Analyzes stream to get information, Internal use.

**Parameters:**

localStream - local stream

**Returns:**

important packets

---

## getLastPacketsByType

```
public AMFPacket\[\] getLastPacketsByType(IMediaReader localReader,  
    double startTime)
```

Analyzes stream to get information, Internal use.

**Parameters:**

localReader - media reader

(continued from last page)

startTime - start time

**Returns:**

important packets

---

## describe

```
public String describe(RTPSession rtspSession,  
    RTPRequestStatus status)
```

Execute describe command

**Parameters:**

rtspSession - RTP session  
status - RTP status

**Returns:**

describe response

---

## switchSetupToMPEGTS

```
public void switchSetupToMPEGTS()
```

Switch a stream to MPEG-TS, Internal use.

---

## describe

```
public String describe(RTPSession rtspSession,  
    int isStreamPacketizer,  
    RTPRequestStatus status)
```

Execute describe command

**Parameters:**

rtspSession - RTP session  
isStreamPacketizer - true is stream  
status - RTP status

**Returns:**

describe string

---

## getMode

```
public int getMode()
```

Get the current play/publish mode

**Returns:**

play/publish mode

---

## setMode

```
public void setMode(int mode)
```

Set the play/publish mode

**Parameters:**

mode - play/publish mode

## getTransportMode

```
public String getTransportMode()
```

Get the transport mode

**Returns:**

transport mode

---

## setTransportMode

```
public void setTransportMode(String transportMode)
```

Set the transport mode

**Parameters:**

transportMode - transport mode

---

## getNormalizedNTPTimecode

```
public long getNormalizedNTPTimecode(long timecode)
```

Turn a millisecond timecode into an NTP timecode

**Parameters:**

timecode - timecode (milliseconds)

**Returns:**

NTP timecode

---

## isForceRTSPInterleaved

```
public boolean isForceRTSPInterleaved()
```

True if forcing RTSP interleaved

**Returns:**

true if forcing RTSP interleaved

---

## setForceRTSPInterleaved

```
public void setForceRTSPInterleaved(boolean isForceRTSPInterleaved)
```

True if forcing RTSP interleaved

**Parameters:**

isForceRTSPInterleaved - true if forcing RTSP interleaved

---

## getRTPInfo

```
public RTPStream.RTPInfo getRTPInfo(double startTime,  
    int videoSeq,  
    int audioSeq)
```

Get the RTP info

**Parameters:**

startTime - start time

---



(continued from last page)

videoSeq - video sequence number

audioSeq - audio sequence number

**Returns:**

RTP info string

---

**formatRTPInfo**

```
public String formatRTPInfo(long timecode,  
    int videoSeq,  
    int audioSeq)
```

Format RTP info

**Parameters:**

timecode - timecode

videoSeq - video sequence number

audioSeq - audio sequence number

**Returns:**

RTP Info string

---

**getRTSPSessionName**

```
public String getRTSPSessionName()
```

Get session name

**Returns:**

session name

---

**setRTSPSessionName**

```
public void setRTSPSessionName(String rtspSessionName)
```

Set session name

**Parameters:**

rtspSessionName - session name

---

**getRTSPSessionDescription**

```
public String getRTSPSessionDescription()
```

Get session description

**Returns:**

session description

---

**setRTSPSessionDescription**

```
public void setRTSPSessionDescription(String rtspSessionDescription)
```

Get session description

**Parameters:**

rtspSessionDescription - session description

(continued from last page)

## isSendSDESEvents

```
public boolean isSendSDESEvents()
```

Send RTCP SDES events

**Returns:**

true if sending RTCP SDES events

---

## setSendSDESEvents

```
public void setSendSDESEvents(boolean sendSDESEvents)
```

Send RTCP SDES events

**Parameters:**

sendSDESEvents - true if sending RTCP SDES events

---

## isMPEGTSOut

```
public boolean isMPEGTSOut()
```

Is MPEG-TS out

**Returns:**

true if MPEG-TS out

---

## setMPEGTSOut

```
public void setMPEGTSOut(boolean isMPEGTSOut)
```

Is MPEG-TS out

**Parameters:**

isMPEGTSOut - true if MPEG-TS out

---

## transportFindBestMatch

```
public String transportFindBestMatch(String transport)
```

Based on a transport string from SETUP command find best match

**Parameters:**

transport - transport string

**Returns:**

best match

---

## getAutoAllocateInterleavePorts

```
public int getAutoAllocateInterleavePorts()
```

---

## isLive

```
public boolean isLive()
```

(continued from last page)

Is live stream

**Returns:**

true if live

---

## setLive

```
public void setLive(boolean isLive)
```

Is live stream

**Parameters:**

isLive - true if live

---

## getMediaReader

```
public IMediaReader getMediaReader()
```

Get media reader if video on demand stream

**Returns:**

media reader

---

## getRTSPSessionTimeout

```
public int getRTSPSessionTimeout()
```

Get RTP session timeout (milliseconds)

**Returns:**

RTP session timeout (milliseconds)

---

## setRTSPSessionTimeout

```
public void setRTSPSessionTimeout(int rtspSessionTimeout)
```

Set RTP session timeout (milliseconds)

**Parameters:**

rtspSessionTimeout - RTP session timeout (milliseconds)

---

## getRTSPMaximumPendingWriteBytes

```
public int getRTSPMaximumPendingWriteBytes()
```

Get the maximum number of waiting bytes allow for this RTSP session

**Returns:**

maximum number of waiting bytes allow for this RTSP session

---

## setRTSPMaximumPendingWriteBytes

```
public void setRTSPMaximumPendingWriteBytes(int rtspMaximumPendingWriteBytes)
```

Set the maximum number of waiting bytes allow for this RTSP session

**Parameters:**

rtspMaximumPendingWriteBytes - maximum number of waiting bytes allow for this RTSP session

---

## isTimeout

```
public boolean isTimeout(long currTime,  
    int timeout)
```

Is the stream timeout out

### Parameters:

currTime - current time  
timeout - timeout value

### Returns:

true if timed out

---

## touch

```
public void touch()
```

Touch the stream so that it does not timeout

---

## getRTSPBindIpAddress

```
public String getRTSPBindIpAddress()
```

Get the bind RTSP bind IP address

### Returns:

bind RTSP bind IP address

---

## setRTSPBindIpAddress

```
public void setRTSPBindIpAddress(String rtspBindIpAddress)
```

Set the bind RTSP bind IP address

### Parameters:

rtspBindIpAddress - bind RTSP bind IP address

---

## getRTSPConnectionIpAddress

```
public String getRTSPConnectionIpAddress()
```

Get the connection IP address

### Returns:

connection IP address

---

## setRTSPConnectionIpAddress

```
public void setRTSPConnectionIpAddress(String rtspConnectionIpAddress)
```

Set the connection IP address

### Parameters:

rtspConnectionIpAddress - connection IP address

---

(continued from last page)

---

## getRTSPConnectionAddressType

```
public String getRTSPConnectionAddressType()
```

Get the connection address type

**Returns:**

connection address type

---

## setRTSPConnectionAddressType

```
public void setRTSPConnectionAddressType(String rtspConnectionAddressType)
```

Set the connection address type

**Parameters:**

rtspConnectionAddressType - connection address type

---

## getRTSPOriginIpAddress

```
public String getRTSPOriginIpAddress()
```

Get the origin IP address

**Returns:**

origin IP address

---

## setRTSPOriginIpAddress

```
public void setRTSPOriginIpAddress(String rtspOriginIpAddress)
```

Set the origin IP address

**Parameters:**

rtspOriginIpAddress - origin IP address

---

## getRTSPOriginAddressType

```
public String getRTSPOriginAddressType()
```

Get the origin address type

**Returns:**

origin address type

---

## setRTSPOriginAddressType

```
public void setRTSPOriginAddressType(String rtspOriginAddressType)
```

Set the origin address type

**Parameters:**

rtspOriginAddressType - origin address type

---

## getVODStartTimeTC

```
public long getVODStartTimeTC()
```

(continued from last page)

Get the video on demand start time (milliseconds)

**Returns:**

video on demand start time (milliseconds)

---

## setVODStartTimeTC

```
public void setVODStartTimeTC(long vodStartTimeTC)
```

Set the video on demand start time (milliseconds)

**Parameters:**

vodStartTimeTC - video on demand start time (milliseconds)

---

## getVODLastTimeTC

```
public long getVODLastTimeTC( )
```

Get the last timecode (milliseconds) sent for video on demand

**Returns:**

last timecode (milliseconds) sent for video on demand

---

## setVODLastTimeTC

```
public void setVODLastTimeTC(long vodLastTimeTC)
```

Set the last timecode (milliseconds) sent for video on demand

**Parameters:**

vodLastTimeTC - last timecode (milliseconds) sent for video on demand

---

## getVODPlayLen

```
public long getVODPlayLen( )
```

Get the video on demand play duration (milliseconds)

**Returns:**

video on demand play duration (milliseconds)

---

## setVODPlayLen

```
public void setVODPlayLen(long vodPlayLen)
```

Set the video on demand play duration (milliseconds)

**Parameters:**

vodPlayLen - video on demand play duration (milliseconds)

---

## isStreamStarted

```
public boolean isStreamStarted( )
```

Is stream started

**Returns:**

true if stream has started playback

---

## isRTSPAlwaysUseSDPPorts

```
public boolean isRTSPAlwaysUseSDPPorts()
```

Force RTSP to use ports in SDP data

**Returns:**

true if using ports in SDP data

---

## setRTSPAlwaysUseSDPPorts

```
public void setRTSPAlwaysUseSDPPorts(boolean rtspAlwaysUseSDPPorts)
```

Force RTSP to use ports in SDP data

**Parameters:**

rtspAlwaysUseSDPPorts - true if using ports in SDP data

---

## putRTSPSessionExtraLine

```
public void putRTSPSessionExtraLine(int location,  
String line)
```

Add an extra line to the SDP data

**Parameters:**

location - location of line, see SDPLOCATION\_  
line - line to add

---

## clearRTSPSessionExtraLines

```
public void clearRTSPSessionExtraLines()
```

Clear SDP extra lines

---

## getRTSPSessionExtraLines

```
public java.util.List getRTSPSessionExtraLines()
```

Get extra SDP lines

**Returns:**

extra SDP lines

---

## getRTPDestination

```
public RTPDestination getRTPDestination()
```

Get RTP destination

**Returns:**

RTP destination

---

## setRTPDestination

```
public void setRTPDestination(RTPDestination rtpDestination)
```

---

(continued from last page)

Set RTP destination

**Parameters:**

rtpDestination - RTP destination

---

**getSDPLang**

```
public String getSDPLang()
```

Get the SDP language

**Returns:**

SDP language

---

**setSDPLang**

```
public void setSDPLang(String sdpLang)
```

Set the SDP language

**Parameters:**

sdpLang - SDP language

---

**isRTPIgnoreProfileLevelId**

```
public boolean isRTPIgnoreProfileLevelId()
```

---

**setRTPIgnoreProfileLevelId**

```
public void setRTPIgnoreProfileLevelId(boolean rtpIgnoreProfileLevelId)
```

---

**getUDPManagedDeliveryDelay**

```
public int getUDPManagedDeliveryDelay()
```

---

**setUDPManagedDeliveryDelay**

```
public void setUDPManagedDeliveryDelay(int udpManagedDeliveryDelay)
```

---

**getUDPManagedDeliveryCount**

```
public int getUDPManagedDeliveryCount()
```

---

**setUDPManagedDeliveryCount**

```
public void setUDPManagedDeliveryCount(int udpManagedDeliveryCount)
```



---

### **isForceMPEGTSOut**

```
public boolean isForceMPEGTSOut()
```

---

### **setForceMPEGTSOut**

```
public void setForceMPEGTSOut(boolean isForceMPEGTSOut)
```

---

### **isBlockUDPOut**

```
public boolean isBlockUDPOut()
```

---

### **setBlockUDPOut**

```
public void setBlockUDPOut(boolean blockUDPOut)
```

---

### **getMPEGTSAudioBitrate**

```
public int getMPEGTSAudioBitrate()
```

---

### **setMPEGTSAudioBitrate**

```
public void setMPEGTSAudioBitrate(int mpegtsAudioBitrate)
```

---

### **getMPEGTSVideoBitrate**

```
public int getMPEGTSVideoBitrate()
```

---

### **setMPEGTSVideoBitrate**

```
public void setMPEGTSVideoBitrate(int mpegtsVideoBitrate)
```

---

### **isRTPIgnoreSPropParameterSets**

```
public boolean isRTPIgnoreSPropParameterSets()
```

---

### **setRTPIgnoreSPropParameterSets**

```
public void setRTPIgnoreSPropParameterSets(boolean rtpIgnoreSPropParameterSets)
```

---

(continued from last page)

---

## **getRTPStreamContext**

```
public RTPStreamContext getRTPStreamContext()
```

---

## **setRTPStreamContext**

```
public void setRTPStreamContext(RTPStreamContext rtpStreamContext)
```

---

Package

**com.wowza.wms.server**

com.wowza.wms.server

# Interface ICommandInterfaceCommand

public interface **ICommandInterfaceCommand**  
extends

Method Summary	
boolean	<a href="#">canHandle</a> (CommandInterfaceRequestMessage req)
void	<a href="#">invoke</a> (CommandInterfaceRequestMessage req, CommandInterfaceResponseMessage resp)

## Methods

**invoke**

```
public void invoke(CommandInterfaceRequestMessage req,  
                  CommandInterfaceResponseMessage resp)
```

**canHandle**

```
public boolean canHandle(CommandInterfaceRequestMessage req)
```

## com.wowza.wms.server Interface ICompilerDirectives

public interface **ICompilerDirectives**  
extends

### Field Summary

public static final

[RTMPENABLED](#)

Value: **true**

### Fields

#### RTMPENABLED

public static final boolean **RTMPENABLED**

Constant value: **true**

---

## com.wowza.wms.server Interface IResponseListener

---

public interface **IResponseListener**  
extends

IResponseListener: Internal use.

---

### Method Summary

void	<a href="#"><u>onResponseWriteStart</u></a> (RtmpResponseMessage response)
void	<a href="#"><u>onResponseWriteStop</u></a> (RtmpResponseMessage response)

---

### Methods

#### **onResponseWriteStart**

public void **onResponseWriteStart**(RtmpResponseMessage response)

---

#### **onResponseWriteStop**

public void **onResponseWriteStop**(RtmpResponseMessage response)

## com.wowza.wms.server Interface IServer

All Known Implementing Classes:  
[Server](#)

public interface **IServer**  
extends

IServer: public interface to Server object.

### Method Summary

void	<a href="#">addServerListener</a> ( <a href="#">IServerNotify</a> serverListener) Add server listener
java.util.List	<a href="#">getAdminInterfaceObjectList</a> () Get the list of objects exposed through JMX interface
RandomIdGenerator	<a href="#">getClientIdGenerator</a> () Get the client id generator for the server
CommandInterfaceCommandHandler	<a href="#">getCommandInterfaceCommandHandler</a> () Get the command interface command handler
<a href="#">HostPort</a>	<a href="#">getCommandInterfaceHostPort</a> () Get the definition of the command interface
<a href="#">ConnectionCounter</a>	<a href="#">getConnectionCounter</a> () Get the server connection counter.
ConnectionCounterSimple	<a href="#">getConnectionCounter</a> (int counterIndex) Get the server connection counter for a specific technology (see IVHost.COUNTER_*)
int	<a href="#">getCoreHandlerPoolSize</a> () Get the handler core thread pool size.
int	<a href="#">getCoreTransportPoolSize</a> () Get the transport core thread pool size.
String	<a href="#">getDateStarted</a> () Get the date and time the server was started.
java.util.Properties	<a href="#">getDynamicLogProperties</a> () Get the dynamic log properties defined at the server level in conf/log4j.properties
<a href="#">ThreadPool</a>	<a href="#">getHandlerThreadPool</a> () Get the server handler thread pool.
<a href="#">IOPerformanceCounter</a>	<a href="#">getIoPerformanceCounter</a> () Get the server performance counter.
<a href="#">IOPerformanceCounter</a>	<a href="#">getIoPerformanceCounter</a> (int counterIndex) Get the server performance counter for a specific technology (see IVHost.COUNTER_*)

<a href="#">WMSProperties</a>	<a href="#">getProperties()</a> Get server level properties collection
<a href="#">ThreadPool</a>	<a href="#">getThreadPool()</a> Get the server handler thread pool.
String	<a href="#">getTimeRunning()</a> Get a formatted String of how long the server has been running.
double	<a href="#">getTimeRunningSeconds()</a> Get time running in seconds
<a href="#">ThreadPool</a>	<a href="#">getTransportThreadPool()</a> Get the server transport thread pool.
com.wowza.wms.transpo rt.udp.UDPPortManager	<a href="#">getUDPPortManager()</a> Get the UDP port manager which manages the allocation of incoming UDP port binding to be sure there are not port conflicts
com.wowza.wms.transpo rt.udp.UDPPortSharing Manager	<a href="#">getUDPPortSharingManager()</a> Get the UDP port sharing manager.
String[]	<a href="#">getUserAgents()</a> Get a pipe " " delimited list of user agents that the server recognizes as RTMPT client.
String	<a href="#">getVersion()</a> Get server version number.
<a href="#">VHostList</a>	<a href="#">getVHostList()</a> Returns the interface to the VHostList for the server
boolean	<a href="#">isAcceptWOWZConnections()</a> If true, WOWZ connections will use the WOWZ protocol.
boolean	<a href="#">isDynamicLogContextLoaded(String logContext)</a> Returns true of the given dynamic log context is already loaded.
boolean	<a href="#">isInitiateWOWZConnections()</a> If true, NetConnection attempts will use the WOWZ protocol when possible.
boolean	<a href="#">isSuspended()</a> Is the server current suspended
String	<a href="#">readConfig(String sName)</a> Method to read xml config file..
void	<a href="#">reloadVHostConfig()</a> Reload the VHosts.xml file.
void	<a href="#">removeServerListener(IServerNotify serverListener)</a> Remove server listener
void	<a href="#">setAcceptWOWZConnections(boolean acceptWOWZConnections)</a> If true, WOWZ connections will use the WOWZ protocol.
void	<a href="#">setCommandInterfaceHostPort(HostPort commandInterfaceHostPort)</a> Set the definition for the command interface.



void	<a href="#"><u>setCoreHandlerPoolSize</u></a> (int corePoolSize) Set the handler core thread pool size.
void	<a href="#"><u>setCoreTransportPoolSize</u></a> (int corePoolSize) Set the transport core thread pool size.
void	<a href="#"><u>setDynamicLogProperties</u></a> ( java.util.Properties dynamicLogProperties) Set the dynamic log properties set at the server level
void	<a href="#"><u>setInitiateWOWZConnections</u></a> (boolean initiateWOWZConnections) If true, NetConnection attempts will use the WOWZ protocol when possible.
void	<a href="#"><u>setUserAgents</u></a> (String[ ] userAgents) Set a pipe " " delimited list of user agents that the server recognizes as RTMPT client.
void	<a href="#"><u>startCommandInterface</u></a> ( ) Start the command interface as defined in Server.xml.
void	<a href="#"><u>startVHost</u></a> (String vhostName) Start a vHost by name.
void	<a href="#"><u>startVHosts</u></a> ( ) Start all vHosts
void	<a href="#"><u>stopAdminAgent</u></a> ( ) Stop the JMX interface
void	<a href="#"><u>stopCommandInterface</u></a> ( ) Stop the command interface as defined in Server.xml.
void	<a href="#"><u>stopVHost</u></a> (String vhostName) Stop a vHost by name.
void	<a href="#"><u>stopVHosts</u></a> ( ) Stop all vHosts
void	<a href="#"><u>suspendAllVHosts</u></a> ( ) Suspend all virtual hosts (Calls IVHost.suspendAllHostPorts for each vhost)
void	<a href="#"><u>suspendServer</u></a> ( ) Suspend all virtual hosts and the command interface
void	<a href="#"><u>unbindAllVHosts</u></a> ( ) Unbind all virtual hosts (Calls IVHost.unbindAllHostPorts for each vhost)
boolean	<a href="#"><u>writeConfig</u></a> (String sName, String data) Method to write xml config file..

## Methods

### startCommandInterface

```
public void startCommandInterface( )
```

Start the command interface as defined in Server.xml. The command interface is used by shutdown.sh script to stop the server. It is also used by ant task to stop and start the server on build events.

---

## stopCommandInterface

```
public void stopCommandInterface()
```

Stop the command interface as defined in Server.xml. The command interface is used by shutdown.sh script to stop the server. It is also used by ant task to stop and start the server on build events.

---

## getVersion

```
public String getVersion()
```

Get server version number.

**Returns:**

server version number

---

## reloadVHostConfig

```
public void reloadVHostConfig()
```

Reload the VHosts.xml file. This method can be invoked through the JMX interface to manage vHosts while the server is running.

---

## stopVHost

```
public void stopVHost(String vhostName)
```

Stop a vHost by name.

**Parameters:**

vhostName - vHost name

---

## stopVHosts

```
public void stopVHosts()
```

Stop all vHosts

---

## startVHost

```
public void startVHost(String vhostName)
```

Start a vHost by name.

**Parameters:**

vhostName - vHost name

---

## startVHosts

```
public void startVHosts()
```

Start all vHosts

---

## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter()
```

Get the server performance counter.

---

(continued from last page)

**Returns:**io performance counter

---

**getIoPerformanceCounter**

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

Get the server performance counter for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index (see IVHost.COUNTER\_\*)

**Returns:**io performance counter

---

**getConnectionCounter**

```
public ConnectionCounter getConnectionCounter( )
```

Get the server connection counter.

**Returns:**connection counter

---

**getConnectionCounter**

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get the server connection counter for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index (see IVHost.COUNTER\_\*)

**Returns:**connection counter

---

**getDateStarted**

```
public String getDateStarted( )
```

Get the date and time the server was started.

**Returns:**date and time the server was started

---

**getTimeRunning**

```
public String getTimeRunning( )
```

Get a formatted String of how long the server has been running.

**Returns:**formatted String of how long the server has been running

---

**getTimeRunningSeconds**

```
public double getTimeRunningSeconds( )
```

---

(continued from last page)

Get time running in seconds

**Returns:**

time running in seconds

---

## getCommandInterfaceHostPort

```
public HostPort getCommandInterfaceHostPort()
```

Get the definition of the command interface

**Returns:**

host port definition of command interface

---

## setCommandInterfaceHostPort

```
public void setCommandInterfaceHostPort(HostPort commandInterfaceHostPort)
```

Set the definition for the command interface.

**Parameters:**

commandInterfaceHostPort - host port definition of command interface

---

## getUserAgents

```
public String[] getUserAgents()
```

Get a pipe "|" delimited list of user agents that the server recognizes as RTMPT client.

**Returns:**

pipe "|" delimited list of user agents that the server recognizes as RTMPT client

---

## setUserAgents

```
public void setUserAgents(String[] userAgents)
```

Set a pipe "|" delimited list of user agents that the server recognizes as RTMPT client.

**Parameters:**

userAgents - pipe "|" delimited list of user agents that the server recognizes as RTMPT client

---

## addServerListener

```
public void addServerListener(IServerNotify serverListener)
```

Add server listener

**Parameters:**

serverListener - server listener

---

## removeServerListener

```
public void removeServerListener(IServerNotify serverListener)
```

Remove server listener

**Parameters:**

serverListener - server listener

## getAdminInterfaceObjectList

```
public java.util.List getAdminInterfaceObjectList()
```

Get the list of objects exposed through JMX interface

**Returns:**

list of objects exposed through JMX interface

---

## getCoreTransportPoolSize

```
public int getCoreTransportPoolSize()
```

Get the transport core thread pool size.

**Returns:**

default core thread pool size

---

## setCoreTransportPoolSize

```
public void setCoreTransportPoolSize(int corePoolSize)
```

Set the transport core thread pool size.

**Parameters:**

corePoolSize - core thread pool size

---

## getCoreHandlerPoolSize

```
public int getCoreHandlerPoolSize()
```

Get the handler core thread pool size.

**Returns:**

default core thread pool size

---

## setCoreHandlerPoolSize

```
public void setCoreHandlerPoolSize(int corePoolSize)
```

Set the handler core thread pool size.

**Parameters:**

corePoolSize - core thread pool size

---

## getThreadPool

```
public ThreadPool getThreadPool()
```

Get the server handler thread pool. Same as getHandlerThreadPool.

**Returns:**

server handler thread pool

---

## getTransportThreadPool

```
public ThreadPool getTransportThreadPool()
```

---

(continued from last page)

Get the server transport thread pool. This thread pool is used to read/write data from the transports sockets.

**Returns:**

server transport thread pool

---

## getHandlerThreadPool

```
public ThreadPool getHandlerThreadPool()
```

Get the server handler thread pool. This thread pool is used to process the incoming events.

**Returns:**

server handler thread pool

---

## getProperties

```
public WMSProperties getProperties()
```

Get server level properties collection

**Returns:**

server level properties collection

---

## getClientIdGenerator

```
public RandomIdGenerator getClientIdGenerator()
```

Get the client id generator for the server

**Returns:**

client id generator for the server

---

## getDynamicLogProperties

```
public java.util.Properties getDynamicLogProperties()
```

Get the dynamic log properties defined at the server level in conf/log4j.properties

**Returns:**

dynamic log properties defined at the server level

---

## setDynamicLogProperties

```
public void setDynamicLogProperties(java.util.Properties dynamicLogProperties)
```

Set the dynamic log properties set at the server level

**Parameters:**

dynamicLogProperties - dynamic log properties defined at the server level

---

## isDynamicLogContextLoaded

```
public boolean isDynamicLogContextLoaded(String logContext)
```

Returns true if the given dynamic log context is already loaded. If not loaded it will return false and add it to the a Set of loaded log context. Log context is [VHost].[Application].[AppInstance]

(continued from last page)

## getVHostList

```
public VHostList getVHostList()
```

Returns the interface to the VHostList for the server

**Returns:**

vhostList

---

## suspendAllVHosts

```
public void suspendAllVHosts()
```

Suspend all virtual hosts (Calls IVHost.suspendAllHostPorts for each vhost)

---

## unbindAllVHosts

```
public void unbindAllVHosts()
```

Unbind all virtual hosts (Calls IVHost.unbindAllHostPorts for each vhost)

---

## suspendServer

```
public void suspendServer()
```

Suspend all virtual hosts and the command interface

---

## isSuspended

```
public boolean isSuspended()
```

Is the server current suspended

---

## stopAdminAgent

```
public void stopAdminAgent()
```

Stop the JMX interface

---

## getUDPPortManager

```
public com.wowza.wms.transport.udp.UDPPortManager getUDPPortManager()
```

Get the UDP port manager which manages the allocation of incoming UDP port binding to be sure there are not port conflicts

**Returns:**

UDP port manager

---

## getUDPPortSharingManager

```
public com.wowza.wms.transport.udp.UDPPortSharingManager getUDPPortSharingManager()
```

Get the UDP port sharing manager.

**Returns:**

UDP port sharing manager

(continued from last page)

---

## readConfig

```
public String readConfig(String sName)
```

Method to read xml config file..

---

## writeConfig

```
public boolean writeConfig(String sName,  
    String data)
```

Method to write xml config file..

---

## getCommandInterfaceCommandHandler

```
public CommandInterfaceCommandHandler getCommandInterfaceCommandHandler()
```

Get the command interface command handler

**Returns:**

command interface command handler

---

## isAcceptWOWZConnections

```
public boolean isAcceptWOWZConnections()
```

If true, WOWZ connections will use the WOWZ protocol. If false, WOWZ connection attempts will fall back to RTMP.

**Returns:**

true, WOWZ connections will use the WOWZ protocol

---

## setAcceptWOWZConnections

```
public void setAcceptWOWZConnections(boolean acceptWOWZConnections)
```

If true, WOWZ connections will use the WOWZ protocol. If false, WOWZ connection attempts will fall back to RTMP.

**Parameters:**

acceptWOWZConnections - true, WOWZ connections will use the WOWZ protocol

---

## isInitiateWOWZConnections

```
public boolean isInitiateWOWZConnections()
```

If true, NetConnection attempts will use the WOWZ protocol when possible.

**Returns:**

true, NetConnection attempts will use the WOWZ protocol when possible.

---

## setInitiateWOWZConnections

```
public void setInitiateWOWZConnections(boolean initiateWOWZConnections)
```

If true, NetConnection attempts will use the WOWZ protocol when possible.

**Parameters:**

initiateWOWZConnections - true, NetConnection attempts will use the WOWZ protocol when possible.

---



## com.wowza.wms.server Interface IServerNotify

All Subinterfaces:

[IServerNotify2](#)

public interface **IServerNotify**  
extends

IServerNotify: listener interface. Configured by adding class entries definitions to Server.xml.Startup order is: [constructor]; onServerConfigLoaded, onServerCreate, onServerInit Shutdown order is: onServerShutdownStart, onServerShutdownComplete, [exit]

### Method Summary

void	<a href="#">onServerCreate</a> ( <a href="#">IServer</a> server) Triggered when server object is first created.
void	<a href="#">onServerInit</a> ( <a href="#">IServer</a> server) Triggered when server initialization is complete and all VHosts have been started
void	<a href="#">onServerShutdownComplete</a> ( <a href="#">IServer</a> server) Triggered at the end of server shutdown
void	<a href="#">onServerShutdownStart</a> ( <a href="#">IServer</a> server) Triggered at the beginning of server shutdown

### Methods

#### onServerCreate

public void **onServerCreate**([IServer](#) server)

Triggered when server object is first created.

**Parameters:**

server - server object

#### onServerInit

public void **onServerInit**([IServer](#) server)

Triggered when server initialization is complete and all VHosts have been started

**Parameters:**

server - server object

#### onServerShutdownStart

public void **onServerShutdownStart**([IServer](#) server)

Triggered at the beginning of server shutdown

(continued from last page)

**Parameters:**

server - server object

---

## onServerShutdownComplete

```
public void onServerShutdownComplete(IServer server)
```

Triggered at the end of server shutdown

**Parameters:**

server - server object

## com.wowza.wms.server Interface IServerNotify2

All Superinterfaces:  
[IServerNotify](#)

public interface **IServerNotify2**  
extends [IServerNotify](#)

IServerNotify2: listener interface. Configured by adding class entries definitions to Server.xml.Startup order is: [constructor]; onServerConfigLoaded, onServerCreate, onServerInit Shutdown order is: onServerShutdownStart, onServerShutdownComplete, [exit]

### Method Summary

void	<a href="#">onServerConfigLoaded</a> ( <a href="#">IServer</a> server) Triggered when server configuration is loaded
------	---

Methods inherited from interface [com.wowza.wms.server.IServerNotify](#)

[onServerCreate](#), [onServerInit](#), [onServerShutdownComplete](#), [onServerShutdownStart](#)

### Methods

#### onServerConfigLoaded

public void **onServerConfigLoaded**([IServer](#) server)

Triggered when server configuration is loaded

**Parameters:**

server - server object

## com.wowza.wms.server Class Server

java.lang.Object

└-com.wowza.wms.server.Server

All Implemented Interfaces:

[IServer](#)

public class **Server**  
extends Object  
implements [IServer](#)

### Nested Class Summary

class	<a href="#">Server.TranscoderPollingTracker</a> Server.TranscoderPollingTracker
-------	--

### Field Summary

public	<a href="#">debugWOWZProtocol</a>
public static	<a href="#">logNotifier</a>

### Constructor Summary

public	<a href="#">Server()</a>
--------	--------------------------

### Method Summary

void	<a href="#">addServerListener</a> ( <a href="#">IServerNotify</a> serverListener)
static void	<a href="#">decodeS</a> (String[] ins) <b>Deprecated.</b>
static boolean	<a href="#">decodeSS</a> (String in) <b>Deprecated.</b>
String	<a href="#">decodeStorageDir</a> ( <a href="#">IVHost</a> vhost, String storageDir)
void	<a href="#">doWatchdog</a> ()
static String	<a href="#">fs</a> (byte[] kiIn, String p) <b>Deprecated.</b>
com.wowza.wms.admin.AdminAgent	<a href="#">getAdminAgent</a> ()
String	<a href="#">getAdminGUID</a> ()

java.util.List	<a href="#">getAdminInterfaceObjectList()</a>
RandomIdGenerator	<a href="#">getClientIdGenerator()</a>
int	<a href="#">getClientIdGeneratorRecycleDelaySize()</a>
int	<a href="#">getClientIdGeneratorRecycleSize()</a>
long	<a href="#">getClientIdGeneratorTimeout()</a>
Object	<a href="#">getCommandInterface()</a>
CommandInterfaceCommandHandler	<a href="#">getCommandInterfaceCommandHandler()</a>
<a href="#">HostPort</a>	<a href="#">getCommandInterfaceHostPort()</a>
long	<a href="#">getCommittedVirtualMemory()</a>
<a href="#">ConnectionCounter</a>	<a href="#">getConnectionCounter()</a>
ConnectionCounterSimple	<a href="#">getConnectionCounter(int counterIndex)</a>
IConnectionValidator	<a href="#">getConnectionValidator()</a>
int	<a href="#">getCoreHandlerPoolSize()</a>
int	<a href="#">getCoreTransportPoolSize()</a>
int	<a href="#">getCryptoPoolActiveCount()</a>
int	<a href="#">getCryptoPoolMaxSize()</a>
long	<a href="#">getCurrentHeapSize()</a>
String	<a href="#">getDateStarted()</a>
java.util.Properties	<a href="#">getDynamicLogProperties()</a>
String	<a href="#">getGUID()</a>
<a href="#">ThreadPool</a>	<a href="#">getHandlerThreadPool()</a>
static <a href="#">Server</a>	<a href="#">getInstance()</a>
<a href="#">IOPerformanceCounter</a>	<a href="#">getIoPerformanceCounter()</a>
<a href="#">IOPerformanceCounter</a>	<a href="#">getIoPerformanceCounter(int counterIndex)</a>

JMXRemoteConfig	<a href="#">getJmxRemoteConfig()</a>
LicenseCounter	<a href="#">getLicenseCounter(int index)</a>
Server.LicenseSessionTracker	<a href="#">getLicenseTracker(int index)</a>
ILicenseValidator	<a href="#">getLicenseValidator()</a>
long	<a href="#">getLiveThreads()</a>
long	<a href="#">getMaxHeapSize()</a>
long	<a href="#">getPeakThreads()</a>
<a href="#">WMSProperties</a>	<a href="#">getProperties()</a>
boolean[]	<a href="#">getProtocolUsage()</a>
Server.ProtocolUsageSessionTracker	<a href="#">getProtocolUsageTracker()</a>
String	<a href="#">getServerGUID()</a>
String	<a href="#">getSessionGUID()</a>
<a href="#">ThreadPool</a>	<a href="#">getThreadPool()</a>
String	<a href="#">getTimeRunning()</a>
double	<a href="#">getTimeRunningSeconds()</a>
<a href="#">ThreadPool</a>	<a href="#">getTransportThreadPool()</a>
com.wowza.wms.transport.udp.UDPPortManager	<a href="#">getUDPPortManager()</a>
com.wowza.wms.transport.udp.UDPPortSharingManager	<a href="#">getUDPPortSharingManager()</a>
String[]	<a href="#">getUserAgents()</a>
String	<a href="#">getVersion()</a>
<a href="#">VHostList</a>	<a href="#">getVHostList()</a>
boolean	<a href="#">isAcceptWOWZConnections()</a>
boolean	<a href="#">isDynamicLogContextLoaded(String logContext)</a>

boolean	<a href="#"><u>isInitiateWOWZConnections()</u></a>
boolean	<a href="#"><u>isSuspended()</u></a>
boolean	<a href="#"><u>isVHostRunning</u></a> (String name)
static void	<a href="#"><u>main</u></a> (String[] args)
void	<a href="#"><u>onNewVHost</u></a> ( <a href="#"><u>IVHost</u></a> vhost)
String	<a href="#"><u>readConfig</u></a> (String sName)
static String	<a href="#"><u>readXMLConfig</u></a> (String sPath)
void	<a href="#"><u>registerLiveStreamTranscoder</u></a> ( <a href="#"><u>ILiveStreamTranscoder</u></a> liveStreamTranscoder, byte[] license)
void	<a href="#"><u>reloadVHostConfig</u></a> ()
void	<a href="#"><u>removeServerListener</u></a> ( <a href="#"><u>IServerNotify</u></a> serverListener)
void	<a href="#"><u>setAcceptWOWZConnections</u></a> (boolean acceptWOWZConnections)
void	<a href="#"><u>setCommandInterface</u></a> (Object commandInterface)
void	<a href="#"><u>setCommandInterfaceHostPort</u></a> ( <a href="#"><u>HostPort</u></a> commandInterfaceHostPort)
void	<a href="#"><u>setCoreHandlerPoolSize</u></a> (int corePoolSize)
void	<a href="#"><u>setCoreTransportPoolSize</u></a> (int corePoolSize)
void	<a href="#"><u>setDynamicLogProperties</u></a> (java.util.Properties dynamicLogProperties)
void	<a href="#"><u>setInitiateWOWZConnections</u></a> (boolean initiateWOWZConnections)
void	<a href="#"><u>setIoPerformanceCounter</u></a> ( <a href="#"><u>IOPerformanceCounter</u></a> ioPerformanceCounter)
void	<a href="#"><u>setUserAgents</u></a> (String[] userAgents)
static void	<a href="#"><u>start</u></a> ()
void	<a href="#"><u>startCommandInterface</u></a> ()
void	<a href="#"><u>startServer</u></a> ()
void	<a href="#"><u>startVHost</u></a> (String vhostName)
void	<a href="#"><u>startVHosts</u></a> ()

void	<a href="#"><u>stopAdminAgent()</u></a>
void	<a href="#"><u>stopCommandInterface()</u></a>
void	<a href="#"><u>stopServer()</u></a>
void	<a href="#"><u>stopVHost</u></a> (String vhostName)
void	<a href="#"><u>stopVHosts</u></a> ()
void	<a href="#"><u>suspendAllVHosts</u></a> ()
void	<a href="#"><u>suspendCommandInterface</u></a> ()
void	<a href="#"><u>suspendServer</u></a> ()
void	<a href="#"><u>unbindAllVHosts</u></a> ()
void	<a href="#"><u>unregisterLiveStreamTranscoder</u></a> ( <a href="#"><u>ILiveStreamTranscoder</u></a> liveStreamTranscoder, byte[] license)
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>updateIOPerformance</u></a> ()
void	<a href="#"><u>updateLoggingDuration</u></a> ()
boolean	<a href="#"><u>writeConfig</u></a> (String sName, String data)
static boolean	<a href="#"><u>writeXMLConfig</u></a> (String sPath, String data)

**Methods inherited from class java.lang.Object**

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface [com.wowza.wms.server.IServer](#)**

[addServerListener](#), [getAdminInterfaceObjectList](#), [getClientIdGenerator](#), [getCommandInterfaceCommandHandler](#), [getCommandInterfaceHostPort](#), [getConnectionCounter](#), [getConnectionCounter](#), [getCoreHandlerPoolSize](#), [getCoreTransportPoolSize](#), [getDateStarted](#), [getDynamicLogProperties](#), [getHandlerThreadPool](#), [getIoPerformanceCounter](#), [getIoPerformanceCounter](#), [getProperties](#), [getThreadPool](#), [getTimeRunning](#), [getTimeRunningSeconds](#), [getTransportThreadPool](#), [getUDPPortManager](#), [getUDPPortSharingManager](#), [getUserAgents](#), [getVersion](#), [getVHostList](#), [isAcceptWOWZConnections](#), [isDynamicLogContextLoaded](#), [isInitiateWOWZConnections](#), [isSuspended](#), [readConfig](#), [reloadVHostConfig](#), [removeServerListener](#), [setAcceptWOWZConnections](#), [setCommandInterfaceHostPort](#), [setCoreHandlerPoolSize](#), [setCoreTransportPoolSize](#), [setDynamicLogProperties](#), [setInitiateWOWZConnections](#), [setUserAgents](#), [startCommandInterface](#), [startVHost](#), [startVHosts](#), [stopAdminAgent](#), [stopCommandInterface](#), [stopVHost](#), [stopVHosts](#), [suspendAllVHosts](#), [suspendServer](#), [unbindAllVHosts](#), [writeConfig](#)



## Fields

### logNotifier

```
public static com.wowza.wms.logging.ILogNotify logNotifier
```

---

### debugWOWZProtocol

```
public boolean debugWOWZProtocol
```

---

## Constructors

### Server

```
public Server()
```

---

## Methods

### getInstance

```
public static Server getInstance()
```

---

### getAdminAgent

```
public com.wowza.wms.admin.AdminAgent getAdminAgent()
```

---

### main

```
public static void main(String[] args)
```

---

### start

```
public static void start()
```

---

### stopServer

```
public void stopServer()
```

---

(continued from last page)

---

## stopAdminAgent

```
public void stopAdminAgent()
```

---

## isVHostRunning

```
public boolean isVHostRunning(String name)
```

---

## suspendCommandInterface

```
public void suspendCommandInterface()
```

---

## startCommandInterface

```
public void startCommandInterface()
```

---

## stopCommandInterface

```
public void stopCommandInterface()
```

---

## startServer

```
public void startServer()
```

---

## getVersion

```
public String getVersion()
```

---

## reloadVHostConfig

```
public void reloadVHostConfig()
```

---

## stopVHost

```
public void stopVHost(String vhostName)
```

---

## stopVHosts

```
public void stopVHosts()
```

---

(continued from last page)

---

## decodeStorageDir

```
public String decodeStorageDir(IVHost vhost,  
    String storageDir)
```

---

## startVHost

```
public void startVHost(String vhostName)
```

---

## isSuspended

```
public boolean isSuspended()
```

---

## suspendServer

```
public void suspendServer()
```

---

## suspendAllVHosts

```
public void suspendAllVHosts()
```

---

## unbindAllVHosts

```
public void unbindAllVHosts()
```

---

## startVHosts

```
public void startVHosts()
```

---

## doWatchdog

```
public void doWatchdog()
```

---

## updateIOPerformance

```
public IOPerformanceCounter updateIOPerformance()
```

---

(continued from last page)

---

## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter()
```

---

## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

---

## setIoPerformanceCounter

```
public void setIoPerformanceCounter(IoPerformanceCounter ioPerformanceCounter)
```

---

## getConnectionCounter

```
public ConnectionCounter getConnectionCounter()
```

---

## getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

---

## getConnectionValidator

```
public IConnectionValidator getConnectionValidator()
```

---

## getLicenseValidator

```
public ILicenseValidator getLicenseValidator()
```

---

## onNewVHost

```
public void onNewVHost(IVHost vhost)
```

---

## getDateStarted

```
public String getDateStarted()
```

---

## getTimeRunning

```
public String getTimeRunning()
```

---

(continued from last page)

---

### getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

---

### getCommandInterfaceHostPort

```
public HostPort getCommandInterfaceHostPort()
```

---

### setCommandInterfaceHostPort

```
public void setCommandInterfaceHostPort(HostPort commandInterfaceHostPort)
```

---

### getCommandInterface

```
public Object getCommandInterface()
```

---

### setCommandInterface

```
public void setCommandInterface(Object commandInterface)
```

---

### getUserAgents

```
public String[] getUserAgents()
```

---

### setUserAgents

```
public void setUserAgents(String[] userAgents)
```

---

### updateLoggingDuration

```
public void updateLoggingDuration()
```

---

### addServerListener

```
public void addServerListener(IServerNotify serverListener)
```

---

(continued from last page)

---

## removeServerListener

```
public void removeServerListener(IServerNotify serverListener)
```

---

---

## getJmxRemoteConfig

```
public JMXRemoteConfig getJmxRemoteConfig()
```

---

---

## getAdminInterfaceObjectList

```
public java.util.List getAdminInterfaceObjectList()
```

---

---

## getCoreTransportPoolSize

```
public int getCoreTransportPoolSize()
```

---

---

## setCoreTransportPoolSize

```
public void setCoreTransportPoolSize(int corePoolSize)
```

---

---

## getCoreHandlerPoolSize

```
public int getCoreHandlerPoolSize()
```

---

---

## setCoreHandlerPoolSize

```
public void setCoreHandlerPoolSize(int corePoolSize)
```

---

---

## getThreadPool

```
public ThreadPool getThreadPool()
```

---

---

## getTransportThreadPool

```
public ThreadPool getTransportThreadPool()
```

---

---

## getHandlerThreadPool

```
public ThreadPool getHandlerThreadPool()
```

---

(continued from last page)

---

## getProperties

```
public WMSProperties getProperties()
```

---

## getClientIdGenerator

```
public RandomIdGenerator getClientIdGenerator()
```

---

## getDynamicLogProperties

```
public java.util.Properties getDynamicLogProperties()
```

---

## setDynamicLogProperties

```
public void setDynamicLogProperties(java.util.Properties dynamicLogProperties)
```

---

## isDynamicLogContextLoaded

```
public boolean isDynamicLogContextLoaded(String logContext)
```

---

## getVHostList

```
public VHostList getVHostList()
```

---

## getSessionGUID

```
public String getSessionGUID()
```

---

## getServerGUID

```
public String getServerGUID()
```

---

## getGUID

```
public String getGUID()
```

---

(continued from last page)

---

## getAdminGUID

```
public String getAdminGUID()
```

---

---

## getUDPPortSharingManager

```
public com.wowza.wms.transport.udp.UDPPortSharingManager getUDPPortSharingManager()
```

---

---

## getUDPPortManager

```
public com.wowza.wms.transport.udp.UDPPortManager getUDPPortManager()
```

---

---

## getCryptoPoolMaxSize

```
public int getCryptoPoolMaxSize()
```

---

---

## getCryptoPoolActiveCount

```
public int getCryptoPoolActiveCount()
```

---

---

## getLiveThreads

```
public long getLiveThreads()
```

---

---

## getPeakThreads

```
public long getPeakThreads()
```

---

---

## getCurrentHeapSize

```
public long getCurrentHeapSize()
```

---

---

## getMaxHeapSize

```
public long getMaxHeapSize()
```

---

---

## getCommittedVirtualMemory

```
public long getCommittedVirtualMemory()
```

---



(continued from last page)

---

**readConfig**

```
public String readConfig(String sName)
```

---

**writeConfig**

```
public boolean writeConfig(String sName,  
    String data)
```

---

**readXMLConfig**

```
public static String readXMLConfig(String sPath)
```

---

**writeXMLConfig**

```
public static boolean writeXMLConfig(String sPath,  
    String data)
```

---

**getClientIdGeneratorTimeout**

```
public long getClientIdGeneratorTimeout()
```

---

**getClientIdGeneratorRecycleSize**

```
public int getClientIdGeneratorRecycleSize()
```

---

**getClientIdGeneratorRecycleDelaySize**

```
public int getClientIdGeneratorRecycleDelaySize()
```

---

**getCommandInterfaceCommandHandler**

```
public CommandInterfaceCommandHandler getCommandInterfaceCommandHandler()
```

---

**getLicenseCounter**

```
public LicenseCounter getLicenseCounter(int index)
```

## getLicenseTracker

```
public Server.LicenseSessionTracker getLicenseTracker(int index)
```

---

## decodeS

```
public static void decodeS(String[] ins)
```

Deprecated.

---

## decodeSS

```
public static boolean decodeSS(String in)
```

Deprecated.

---

## fS

```
public static String fS(byte[] kiIn,  
                        String p)
```

Deprecated.

---

## registerLiveStreamTranscoder

```
public void registerLiveStreamTranscoder(ILiveStreamTranscoder liveStreamTranscoder,  
                                          byte[] license)
```

---

## unregisterLiveStreamTranscoder

```
public void unregisterLiveStreamTranscoder(ILiveStreamTranscoder liveStreamTranscoder,  
                                             byte[] license)
```

---

## getProtocolUsage

```
public boolean[] getProtocolUsage()
```

---

## getProtocolUsageTracker

```
public Server.ProtocolUsageSessionTracker getProtocolUsageTracker()
```

---

(continued from last page)

**isAcceptWOWZConnections**

```
public boolean isAcceptWOWZConnections()
```

---

**setAcceptWOWZConnections**

```
public void setAcceptWOWZConnections(boolean acceptWOWZConnections)
```

---

**isInitiateWOWZConnections**

```
public boolean isInitiateWOWZConnections()
```

---

**setInitiateWOWZConnections**

```
public void setInitiateWOWZConnections(boolean initiateWOWZConnections)
```

---

com.wowza.wms.server

## Class Server.TranscoderPollingTracker

java.lang.Object

└-com.wowza.wms.server.Server.TranscoderPollingTracker

---

public class **Server.TranscoderPollingTracker**

extends Object

---

Methods inherited from class java.lang.Object
---

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
--

---

---

Package

**com.wowza.wms.sharedobject**

## com.wowza.wms.sharedobject Interface ISharedObject

All Known Implementing Classes:

[SharedObject](#)

public interface **ISharedObject**  
extends

ISharedObject: public interface to SharedObject class.

### Field Summary

public static final	<a href="#">FILEEXTENSION</a> Value: <b>rso</b>
public static final	<a href="#">SHARED_OBJECT_CMD_CONNECT</a> shared object command: connect Value: <b>1</b>
public static final	<a href="#">SHARED_OBJECT_CMD_CONNECTSUCCESS</a> shared object command: clear Value: <b>11</b>
public static final	<a href="#">SHARED_OBJECT_CMD_DELETE</a> shared object command: delete Value: <b>10</b>
public static final	<a href="#">SHARED_OBJECT_CMD_DISCONNECT</a> shared object command: disconnect Value: <b>2</b>
public static final	<a href="#">SHARED_OBJECT_CMD_ERROR</a> shared object command: error Value: <b>7</b>
public static final	<a href="#">SHARED_OBJECT_CMD_SEND</a> shared object command: send Value: <b>6</b>
public static final	<a href="#">SHARED_OBJECT_CMD_SETVALUE</a> shared object command: setvalue Value: <b>3</b>
public static final	<a href="#">SHARED_OBJECT_STATUS_CHANGE</a> shared object status: change Value: <b>4</b>
public static final	<a href="#">SHARED_OBJECT_STATUS_CLEAR</a> shared object status: clear Value: <b>8</b>

public static final	<a href="#"><u>SHARED_OBJECT_STATUS_DELETE</u></a> shared object status: delete Value: <b>9</b>
public static final	<a href="#"><u>SHARED_OBJECT_STATUS_SUCCESS</u></a> shared object status: success Value: <b>5</b>

## Method Summary

void	<a href="#"><u>acquire()</u></a> Increment the reference count to this shared object.
void	<a href="#"><u>addClient(IClient client)</u></a> Add a client to this shared object.
void	<a href="#"><u>addSlotListener(ISharedObjectSlotNotify slotListener)</u></a> Add a slot listener.
void	<a href="#"><u>clear()</u></a> Clear all properties from a shared object
void	<a href="#"><u>close()</u></a> Force close this shared object (not implemented)
boolean	<a href="#"><u>containsProperty(String slotName)</u></a> Returns true is slot/property name exists
boolean	<a href="#"><u>containsSlot(String slotName)</u></a> Returns true is slot/property name exists
void	<a href="#"><u>deleteSlot(IClient client, String slotName)</u></a> Remove a slot (property)
void	<a href="#"><u>deleteSlot(String slotName)</u></a> Remove slot (property)
void	<a href="#"><u>disconnect(IClient client)</u></a> Disconnect client from shared object.
void	<a href="#"><u>flush()</u></a> Flush (write to disk) shared object
java.util.List	<a href="#"><u>getClients()</u></a> Get a list of client that are connected to this shared object.
String	<a href="#"><u>getName()</u></a> Get shared object name
<a href="#"><u>ISharedObjects</u></a>	<a href="#"><u>getParent()</u></a> Get the shared object container to which this shared object belongs.
<a href="#"><u>AMFData</u></a>	<a href="#"><u>getProperty(String slotName)</u></a> Get slot (property) value.
int	<a href="#"><u>getRefCount()</u></a> Get the current reference (clients) connected to this shared object.

<a href="#"><u>ISharedObjectSlot</u></a>	<a href="#"><u>getSlot</u></a> (String name) Get ISharedObjectSlot interface to a slot (property) by name
java.util.List	<a href="#"><u>getSlotNames</u></a> ( ) Get a list of slot (property) names
java.util.List	<a href="#"><u>getSlots</u></a> ( ) Get a list of active slots
String	<a href="#"><u>getStorageDir</u></a> ( ) Get path used to store shared object.
int	<a href="#"><u>getVersion</u></a> ( ) Get the interval version number.
boolean	<a href="#"><u>isClient</u></a> ( <a href="#"><u>IClient</u></a> client) Is this client connected to shared object
boolean	<a href="#"><u>isPersistent</u></a> ( ) Is this shared object being persisted.
void	<a href="#"><u>lock</u></a> ( ) Lock a shared object for write access
int	<a href="#"><u>purge</u></a> (int version) Purge all deleted properties older than the version number
void	<a href="#"><u>putSlot</u></a> (String name, <a href="#"><u>ISharedObjectSlot</u></a> slot) Add a new slot (property) to a shared object.
void	<a href="#"><u>release</u></a> ( ) Decrement the reference count to this shared object.
void	<a href="#"><u>removeClient</u></a> ( <a href="#"><u>IClient</u></a> client) Remove a client from this shared object.
void	<a href="#"><u>removeSlotListener</u></a> ( <a href="#"><u>ISharedObjectSlotNotify</u></a> slotListener) Remove slot listener
void	<a href="#"><u>send</u></a> (String handlerName) Call client side handler attached to shared object (no parameters).
void	<a href="#"><u>send</u></a> (String handlerName, Object[] params) Call client side handler attached to shared object.
void	<a href="#"><u>setName</u></a> (String name) Set shared object name
void	<a href="#"><u>setPersistent</u></a> (boolean isPersistent) Set is shared object persisted.
void	<a href="#"><u>setProperty</u></a> (String slotName, <a href="#"><u>AMFData</u></a> data) Set slot (property) value as AMFData object.
void	<a href="#"><u>setProperty</u></a> (String slotName, boolean value) Set slot (property) value as a boolean value (will be wrapped in an AMFDataItem object)
void	<a href="#"><u>setProperty</u></a> (String slotName, java.util.Date value) Set slot (property) value as a date value (will be wrapped in an AMFDataItem object)



void	<a href="#"><code>setProperty</code></a> (String slotName, double value) Set slot (property) value as a double value (will be wrapped in an AMFDataItem object)
void	<a href="#"><code>setProperty</code></a> (String slotName, int value) Set slot (property) value as a int value (will be wrapped in an AMFDataItem object)
void	<a href="#"><code>setProperty</code></a> (String slotName, long value) Set slot (property) value as a long value (will be wrapped in an AMFDataItem object)
void	<a href="#"><code>setProperty</code></a> (String slotName, String value) Set slot (property) value as a string value (will be wrapped in an AMFDataItem object)
void	<a href="#"><code>setStorageDir</code></a> (String storageDir) Set path used to store shared object.
void	<a href="#"><code>setVersion</code></a> (int version) Set the internal version number.
int	<a href="#"><code>size</code></a> () Get the number of active slot (properties).
void	<a href="#"><code>unlock</code></a> () Unlock a shared object for write access
void	<a href="#"><code>writeDeleteError</code></a> (IClient client, String soName, boolean isPersistent, String slotName, String errorMsg) Write an delete error message back to the client
void	<a href="#"><code>writeSetValueError</code></a> (IClient client, String soName, boolean isPersistent, String slotName, String errorMsg) Write an set value error message back to the client

## Fields

### FILEEXTENSION

```
public static final java.lang.String FILEEXTENSION
```

Constant value: **rs0**

### SHARED\_OBJECT\_CMD\_CONNECT

```
public static final byte SHARED_OBJECT_CMD_CONNECT
```

shared object command: connect

Constant value: **1**

### SHARED\_OBJECT\_CMD\_DISCONNECT

```
public static final byte SHARED_OBJECT_CMD_DISCONNECT
```

shared object command: disconnect

Constant value: **2**

(continued from last page)

---

## SHARED\_OBJECT\_CMD\_SETVALUE

```
public static final byte SHARED_OBJECT_CMD_SETVALUE
```

shared object command: setvalue  
Constant value: **3**

---

## SHARED\_OBJECT\_CMD\_SEND

```
public static final byte SHARED_OBJECT_CMD_SEND
```

shared object command: send  
Constant value: **6**

---

## SHARED\_OBJECT\_CMD\_ERROR

```
public static final byte SHARED_OBJECT_CMD_ERROR
```

shared object command: error  
Constant value: **7**

---

## SHARED\_OBJECT\_CMD\_DELETE

```
public static final byte SHARED_OBJECT_CMD_DELETE
```

shared object command: delete  
Constant value: **10**

---

## SHARED\_OBJECT\_CMD\_CONNECTSUCCESS

```
public static final byte SHARED_OBJECT_CMD_CONNECTSUCCESS
```

shared object command: clear  
Constant value: **11**

---

## SHARED\_OBJECT\_STATUS\_CHANGE

```
public static final byte SHARED_OBJECT_STATUS_CHANGE
```

shared object status: change  
Constant value: **4**

---

## SHARED\_OBJECT\_STATUS\_SUCCESS

```
public static final byte SHARED_OBJECT_STATUS_SUCCESS
```

shared object status: success  
Constant value: **5**

---

## SHARED\_OBJECT\_STATUS\_CLEAR

```
public static final byte SHARED_OBJECT_STATUS_CLEAR
```

shared object status: clear  
Constant value: **8**

---

## SHARED\_OBJECT\_STATUS\_DELETE

```
public static final byte SHARED_OBJECT_STATUS_DELETE
```

---

(continued from last page)

shared object status: delete  
Constant value: **9**

## Methods

### getSlotNames

```
public java.util.List getSlotNames()
```

Get a list of slot (property) names

**Returns:**

list of slot (property) names

### getSlot

```
public ISharedObjectSlot getSlot(String name)
```

Get ISharedObjectSlot interface to a slot (property) by name

**Parameters:**

name - slot (property) name

**Returns:**

ISharedObjectSlot interface

### putSlot

```
public void putSlot(String name,  
    ISharedObjectSlot slot)
```

Add a new slot (property) to a shared object.

**Parameters:**

name - slot (property) name

slot - new slot

### getClients

```
public java.util.List getClients()
```

Get a list of client that are connected to this shared object.

**Returns:**

list of client that are connected to this shared object

### isClient

```
public boolean isClient(IClient client)
```

Is this client connected to shared object

**Parameters:**

client - client

**Returns:**

true if client is conencted to shared object

---

## addClient

```
public void addClient(IClient client)
```

Add a client to this shared object.

**Parameters:**

client - client

---

## removeClient

```
public void removeClient(IClient client)
```

Remove a client from this shared object.

**Parameters:**

client - client

---

## size

```
public int size()
```

Get the number of active slot (properties). Deleted slots are not counted.

**Returns:**

number of active slot (properties). Deleted slots are not counted

---

## acquire

```
public void acquire()
```

Increment the reference count to this shared object.

---

## release

```
public void release()
```

Descrement the reference count to this shared object.

---

## close

```
public void close()
```

Force close this shared object (not implemented)

---

## getRefCount

```
public int getRefCount()
```

Get the current reference (clients) connected to this shared object. Includes unbalanced count of calls to acquire.

**Returns:**

the current reference (clients) connected to this shared object

---

## isPersistent

```
public boolean isPersistent()
```

---

(continued from last page)

Is this shared object being persisted.

**Returns:**

true if shared object is being persisted

---

**setPersistent**

```
public void setPersistent(boolean isPersistent)
```

Set is shared object persisted.

**Parameters:**

isPersistent - true if shared object is being persisted

---

**getVersion**

```
public int getVersion()
```

Get the interval version number.

**Returns:**

interval version number

---

**setVersion**

```
public void setVersion(int version)
```

Set the internal version number.

**Parameters:**

version - internal version number

---

**flush**

```
public void flush()
```

Flush (write to disk) shared object

---

**deleteSlot**

```
public void deleteSlot(IClient client,  
String slotName)
```

Remove a slot (property)

**Parameters:**

client - client removing slot or null if server side code  
slotName - slot (property) name

---

**deleteSlot**

```
public void deleteSlot(String slotName)
```

Remove slot (property)

**Parameters:**

slotName - slot (property) name

## getProperty

```
public AMFData getProperty(String slotName)
```

Get slot (property) value.

**Parameters:**

slotName - slot (property) name

**Returns:**

slot (property) value as AMFData object

---

## setProperty

```
public void setProperty(String slotName,  
    String value)
```

Set slot (property) value as a string value (will be wrapped in an AMFDataItem object)

**Parameters:**

slotName - slot (property) name

value - string value

---

## setProperty

```
public void setProperty(String slotName,  
    double value)
```

Set slot (property) value as a double value (will be wrapped in an AMFDataItem object)

**Parameters:**

slotName - slot (property) name

value - double value

---

## setProperty

```
public void setProperty(String slotName,  
    int value)
```

Set slot (property) value as a int value (will be wrapped in an AMFDataItem object)

**Parameters:**

slotName - slot (property) name

value - int value

---

## setProperty

```
public void setProperty(String slotName,  
    long value)
```

Set slot (property) value as a long value (will be wrapped in an AMFDataItem object)

**Parameters:**

slotName - slot (property) name

value - long value

---

(continued from last page)

## setProperty

```
public void setProperty(String slotName,  
                        java.util.Date value)
```

Set slot (property) value as a date value (will be wrapped in an AMFDataItem object)

### Parameters:

slotName - slot (property) name  
value - date value

---

## setProperty

```
public void setProperty(String slotName,  
                        boolean value)
```

Set slot (property) value as a boolean value (will be wrapped in an AMFDataItem object)

### Parameters:

slotName - slot (property) name  
value - boolean value

---

## setProperty

```
public void setProperty(String slotName,  
                        AMFData data)
```

Set slot (property) value as AMFData object.

### Parameters:

slotName - slot (property) name  
data - slot value as AMFData object. Example: new AMFDataItem((double)1.234) or new AMFDataItem()

---

## disconnect

```
public void disconnect(IClient client)
```

Disconnect client from shared object.

### Parameters:

client - client to disconnect

---

## getName

```
public String getName()
```

Get shared object name

### Returns:

shared object name

---

## setName

```
public void setName(String name)
```

Set shared object name

### Parameters:

name - shared object name

## send

```
public void send(String handlerName,  
                Object[] params)
```

Call client side handler attached to shared object.

**Parameters:**

handlerName - handler name

params - variable argument list of parameters

---

## send

```
public void send(String handlerName)
```

Call client side handler attached to shared object (no parameters).

**Parameters:**

handlerName - handler name

---

## addSlotListener

```
public void addSlotListener(ISharedObjectSlotNotify slotListener)
```

Add a slot listener. Will receive the following events: onSlotSetValue and onSlotDelete

**Parameters:**

slotListener - slot listener

---

## removeSlotListener

```
public void removeSlotListener(ISharedObjectSlotNotify slotListener)
```

Remove slot listener

**Parameters:**

slotListener - slot listener

---

## getStorageDir

```
public String getStorageDir()
```

Get path used to store shared object.

**Returns:**

path used to store shared object

---

## setStorageDir

```
public void setStorageDir(String storageDir)
```

Set path used to store shared object.

**Parameters:**

storageDir - path used to store shared object

---



(continued from last page)

---

## writeSetValueError

```
public void writeSetValueError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

Write an set value error message back to the client

### Parameters:

client - client removing slot or null if server side code  
soName - sharedObject name  
isPersistent - is persistent  
slotName - slot name  
errorMsg - error message

---

## writeDeleteError

```
public void writeDeleteError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

Write an delete error message back to the client

### Parameters:

client - client removing slot or null if server side code  
soName - sharedObject name  
isPersistent - is persistent  
slotName - slot name  
errorMsg - error message

---

## clear

```
public void clear()
```

Clear all properties from a shared object

---

## purge

```
public int purge(int version)
```

Purge all deleted properties older than the version number

### Returns:

number of slots purged

---

## getSlots

```
public java.util.List getSlots()
```

Get a list of active slots

### Returns:

list of active slots

---

(continued from last page)

## containsProperty

```
public boolean containsProperty(String slotName)
```

Returns true is slot/property name exists

**Parameters:**

slotName - slot/property name

**Returns:**

true is slot/property name exists

---

## containsSlot

```
public boolean containsSlot(String slotName)
```

Returns true is slot/property name exists

**Parameters:**

slotName - slot/property name

**Returns:**

true is slot/property name exists

---

## lock

```
public void lock()
```

Lock a shared object for write access

---

## unlock

```
public void unlock()
```

Unlock a shared object for write access

---

## getParent

```
public ISharedObjects getParent()
```

Get the shared object container to which this shared object belongs.

**Returns:**

shared object container

---

## com.wowza.wms.sharedobject Interface ISharedObjectNotify

public interface **ISharedObjectNotify**  
extends

ISharedObjectNotify: listener interface used by IApplicationInstance addSharedObjectListener

### Method Summary

void	<a href="#">onSharedObjectConnect</a> ( <a href="#">ISharedObject</a> sharedObject, <a href="#">IClient</a> client) Triggered when client connects to sharedObject
void	<a href="#">onSharedObjectCreate</a> ( <a href="#">ISharedObject</a> sharedObject) Triggered when sharedObject created
void	<a href="#">onSharedObjectDestroy</a> ( <a href="#">ISharedObject</a> sharedObject) Triggered when sharedObject destroyed
void	<a href="#">onSharedObjectDisconnect</a> ( <a href="#">ISharedObject</a> sharedObject, <a href="#">IClient</a> client) Triggered when client disconnects from sharedObject

### Methods

#### onSharedObjectCreate

public void **onSharedObjectCreate**([ISharedObject](#) sharedObject)

Triggered when sharedObject created

**Parameters:**

sharedObject - sharedObject

#### onSharedObjectDestroy

public void **onSharedObjectDestroy**([ISharedObject](#) sharedObject)

Triggered when sharedObject destroyed

**Parameters:**

sharedObject - sharedObject

#### onSharedObjectConnect

public void **onSharedObjectConnect**([ISharedObject](#) sharedObject, [IClient](#) client)

Triggered when client connects to sharedObject

**Parameters:**

sharedObject - sharedObject

client - client

## onSharedObjectDisconnect

```
public void onSharedObjectDisconnect(ISharedObject sharedObject,  
    IClient client)
```

Triggered when client disconnects from sharedObject

**Parameters:**

sharedObject - sharedObject

client - client

## com.wowza.wms.sharedobject Interface ISharedObjects

public interface **ISharedObjects**  
extends

ISharedObjects: public interface to SharedObjects. Represent the list of shared objects managed by IApplicationInstance.

### Method Summary

void	<a href="#"><u>addSharedObjectListener</u></a> ( <a href="#"><u>ISharedObjectNotify</u></a> sharedObjectListener)
	Add a shared object listener.
void	<a href="#"><u>disconnect</u></a> ( <a href="#"><u>IClient</u></a> client)
	Disconnect client from all shared objects in list.
boolean	<a href="#"><u>exists</u></a> ( <a href="#"><u>ISharedObject</u></a> sharedObject)
	Is sharedObject in this list (by shared object reference).
boolean	<a href="#"><u>exists</u></a> (String objectName)
	Is sharedObject in this list (by name).
void	<a href="#"><u>flush</u></a> ()
	Flush all persistent shared objects to disk.
<a href="#"><u>ISharedObject</u></a>	<a href="#"><u>get</u></a> (String name)
	Get shared object by name.
java.util.List	<a href="#"><u>getObjectNames</u></a> ()
	Get a list of shared object names.
<a href="#"><u>ISharedObject</u></a>	<a href="#"><u>getOrCreate</u></a> (String name)
	Get shared object by name if it does not exist create a new shared object with the given name.
String	<a href="#"><u>getStorageDir</u></a> ()
	Get the storage directory for all shared objects in list.
boolean	<a href="#"><u>isPersistent</u></a> ()
	Are shared objects in list persistent.
void	<a href="#"><u>load</u></a> ()
	Load persistent shared objects from file system.
void	<a href="#"><u>put</u></a> (String objectName, <a href="#"><u>ISharedObject</u></a> sharedObject)
	Add or replace a shared object.
void	<a href="#"><u>remove</u></a> (String objectName)
	Remove a shared object.
void	<a href="#"><u>removeClient</u></a> ( <a href="#"><u>IClient</u></a> client)
	Remove a client from any shared object that it is connected to in this list.
void	<a href="#"><u>removeSharedObjectListener</u></a> ( <a href="#"><u>ISharedObjectNotify</u></a> sharedObjectListener)
	Remove a shared object listener.

void	<a href="#"><code>setPersistent</code></a> (boolean isPersistent) Set is shared object in list persistent
void	<a href="#"><code>setStorageDir</code></a> (String storageDir) Set the storage directory for all shared objects in list.
int	<a href="#"><code>size</code></a> () Get number of shared objects.

## Methods

### size

```
public int size()
```

Get number of shared objects.

**Returns:**

number of shared objects

### get

```
public ISharedObject get(String name)
```

Get shared object by name. If the shared object does not exists null will be returned. (see `ISharedObjects.getOrCreate`)

**Parameters:**

name - shared object name

**Returns:**

shared object

### getOrCreate

```
public ISharedObject getOrCreate(String name)
```

Get shared object by name if it does not exist create a new shared object with the given name.

**Parameters:**

name - shared object name

**Returns:**

shared object

### getObjectNames

```
public java.util.List getObjectNames()
```

Get a list of shared object names.

**Returns:**

list of shared object names

(continued from last page)

## put

```
public void put(String objectName,  
    ISharedObject sharedObject)
```

Add or replace a shared object.

### Parameters:

objectName - shared object name  
sharedObject - shared object

---

## remove

```
public void remove(String objectName)
```

Remove a shared object.

### Parameters:

objectName - shared object name

---

## exists

```
public boolean exists(String objectName)
```

Is sharedObject in this list (by name).

### Parameters:

objectName - shared object name

### Returns:

true if shared object in list

---

## exists

```
public boolean exists(ISharedObject sharedObject)
```

Is sharedObject in this list (by shared object reference).

### Parameters:

sharedObject - shared object

### Returns:

true if shared object in list

---

## isPersistent

```
public boolean isPersistent()
```

Are shared objects in list persistent.

### Returns:

true if shared objects in list are persistent

---

## setPersistent

```
public void setPersistent(boolean isPersistent)
```

Set if shared object in list persistent

(continued from last page)

**Parameters:**

isPersistent - true is shared objects in list are persistent

---

**removeClient**

```
public void removeClient(IClient client)
```

Remove a client from any shared object that it is connected to in this list.

**Parameters:**

client - client

---

**flush**

```
public void flush()
```

Flush all persistent shared objects to disk.

---

**disconnect**

```
public void disconnect(IClient client)
```

Disconnect client from all shared objects in list.

**Parameters:**

client - client

---

**addSharedObjectListener**

```
public void addSharedObjectListener(ISharedObjectNotify sharedObjectListener)
```

Add a shared object listener. The listener will receive the following events: onSharedObjectCreate, onSharedObjectDestroy, onSharedObjectConnect, onSharedObjectDisconnect.

**Parameters:**

sharedObjectListener

---

**removeSharedObjectListener**

```
public void removeSharedObjectListener(ISharedObjectNotify sharedObjectListener)
```

Remove a shared object listener.

**Parameters:**

sharedObjectListener

---

**getStorageDir**

```
public String getStorageDir()
```

Get the storage directory for all shared objects in list.

**Returns:**

storage dir

---

**setStorageDir**

```
public void setStorageDir(String storageDir)
```

---



(continued from last page)

Set the storage directory for all shared objects in list.

**Parameters:**

storageDir

---

## **load**

```
public void load()
```

Load persistent shared objects from file system.

## com.wowza.wms.sharedobject Interface ISharedObjectSlot

public interface **ISharedObjectSlot**  
extends

ISharedObjectSlot: public interface to SharedObjectSlot class.

### Method Summary

<a href="#">AMFData</a>	<a href="#">getData()</a> Get slot data as AMFData object.
int	<a href="#">getLastClientId()</a> Get client id of client that performed last operation on slot.
int	<a href="#">getLastOperation()</a> Get last slot (property) operation.
String	<a href="#">getName()</a> Get slot (property) name.
int	<a href="#">getSlotVersion()</a> Get slot version
int	<a href="#">getSoVersion()</a> Get parent shared object version
void	<a href="#">incSlotVersion()</a> Increment slot version by 1.
void	<a href="#">init</a> (String name, <a href="#">AMFData</a> data, int slotVersion) Initialize shared object slot
void	<a href="#">setData</a> ( <a href="#">AMFData</a> data) Set slot data as AMFData object.
void	<a href="#">setData</a> (byte[] data) Set slot data as byte[].
void	<a href="#">setData</a> (byte[] data, <a href="#">AMFDataContextDeserialize</a> context) Set slot data as byte[].
void	<a href="#">setLastClientId</a> (int lastClientId) Set client id of client that performed last operation on slot.
void	<a href="#">setLastOperation</a> (int lastOperation) Set last slot (property) operation.
void	<a href="#">setName</a> (String name) Set slot (property) name
void	<a href="#">setSlotVersion</a> (int slotVersion) Set slot version

void	<a href="#">setSoVersion</a> (int soVersion) Set parent shared object version
------	--

## Methods

### init

```
public void init(String name,  
    AMFData data,  
    int slotVersion)
```

Initialize shared object slot

**Parameters:**

name - slot (property) name  
data - data  
slotVersion - version

### getData

```
public AMFData getData()
```

Get slot data as AMFData object.

**Returns:**

slot data as AMFData object

### setData

```
public void setData(byte[] data,  
    AMFDataContextDeserialize context)
```

Set slot data as byte[]. Data will be deserialized as AMFData object.

**Parameters:**

data - data as byte[]  
context - deserialization context

### setData

```
public void setData(byte[] data)
```

Set slot data as byte[]. Data will be deserialized as AMFData object.

**Parameters:**

data - data as byte[]

### setData

```
public void setData(AMFData data)
```

Set slot data as AMFData object.

**Parameters:**

data - data as AMFData object

## getName

```
public String getName()
```

Get slot (property) name.

**Returns:**

slot (property) name

---

## setName

```
public void setName(String name)
```

Set slot (property) name

**Parameters:**

name - slot (property) name

---

## getSlotVersion

```
public int getSlotVersion()
```

Get slot version

**Returns:**

slot version

---

## setSlotVersion

```
public void setSlotVersion(int slotVersion)
```

Set slot version

**Parameters:**

slotVersion - slot version

---

## incSlotVersion

```
public void incSlotVersion()
```

Increment slot version by 1.

---

## getSoVersion

```
public int getSoVersion()
```

Get parent shared object version

**Returns:**

parent shared object version

---

## setSoVersion

```
public void setSoVersion(int soVersion)
```

Set parent shared object version

---

(continued from last page)

**Parameters:**

soVersion - parent shared object version

---

**getLastOperation**

```
public int getLastOperation()
```

Get last slot (property) operation. See ISharedObject.SHAREDOBJECT\_CMD\_\*.

**Returns:**

last slot (property) operation (ISharedObject.SHAREDOBJECT\_CMD\_\*)

---

**setLastOperation**

```
public void setLastOperation(int lastOperation)
```

Set last slot (property) operation. See ISharedObject.SHAREDOBJECT\_CMD\_\*.

**Parameters:**

lastOperation - last slot (property) operation (ISharedObject.SHAREDOBJECT\_CMD\_\*)

---

**getLastClientId**

```
public int getLastClientId()
```

Get client id of client that performed last operation on slot.

**Returns:**

client id of client that performed last operation on slot

---

**setLastClientId**

```
public void setLastClientId(int lastClientId)
```

Set client id of client that performed last operation on slot.

**Parameters:**

lastClientId - client id of client that performed last operation on slot

## com.wowza.wms.sharedobject Interface ISharedObjectSlotNotify

public interface **ISharedObjectSlotNotify**  
extends

ISharedObjectNotify: listener interface used by ISharedObject addSlotListener

### Method Summary

void	<a href="#">onSlotDelete</a> ( <a href="#">ISharedObject</a> sharedObject, <a href="#">ISharedObjectSlot</a> slot) Triggered when sharedObject slot value deleted
void	<a href="#">onSlotSetValue</a> ( <a href="#">ISharedObject</a> sharedObject, <a href="#">ISharedObjectSlot</a> slot) Triggered when sharedObject slot value set

### Methods

#### onSlotSetValue

public void **onSlotSetValue**([ISharedObject](#) sharedObject,  
[ISharedObjectSlot](#) slot)

Triggered when sharedObject slot value set

**Parameters:**

sharedObject  
slot

#### onSlotDelete

public void **onSlotDelete**([ISharedObject](#) sharedObject,  
[ISharedObjectSlot](#) slot)

Triggered when sharedObject slot value deleted

**Parameters:**

sharedObject  
slot

## com.wowza.wms.sharedobject Class SharedObject

java.lang.Object

└─com.wowza.wms.sharedobject.SharedObject

All Implemented Interfaces:

[ISharedObject](#)

public class **SharedObject**  
extends Object  
implements [ISharedObject](#)

### Field Summary

public static final	<a href="#">READACCESS</a> Value: <b>0</b>
public static final	<a href="#">WRITEACCESS</a> Value: <b>1</b>

Fields inherited from interface [com.wowza.wms.sharedobject.ISharedObject](#)

[FILEEXTENSION](#), [SHARED\\_OBJECT\\_CMD\\_CONNECT](#), [SHARED\\_OBJECT\\_CMD\\_CONNECTSUCCESS](#),  
[SHARED\\_OBJECT\\_CMD\\_DELETE](#), [SHARED\\_OBJECT\\_CMD\\_DISCONNECT](#), [SHARED\\_OBJECT\\_CMD\\_ERROR](#),  
[SHARED\\_OBJECT\\_CMD\\_SEND](#), [SHARED\\_OBJECT\\_CMD\\_SETVALUE](#), [SHARED\\_OBJECT\\_STATUS\\_CHANGE](#),  
[SHARED\\_OBJECT\\_STATUS\\_CLEAR](#), [SHARED\\_OBJECT\\_STATUS\\_DELETE](#), [SHARED\\_OBJECT\\_STATUS\\_SUCCESS](#)

### Constructor Summary

public	<a href="#">SharedObject</a> (String name) Create new shared object
public	<a href="#">SharedObject</a> (String name, boolean isPersistent, String storageDir) Create new shared object

### Method Summary

void	<a href="#">acquire</a> ()
void	<a href="#">addClient</a> ( <a href="#">IClient</a> client)
void	<a href="#">addSlotListener</a> ( <a href="#">ISharedObjectSlotNotify</a> slotListener)
void	<a href="#">clear</a> ()
void	<a href="#">close</a> ()

boolean	<a href="#"><u>containsProperty</u></a> (String slotName)
boolean	<a href="#"><u>containsSlot</u></a> (String slotName)
void	<a href="#"><u>deleteSlot</u></a> ( <a href="#"><u>IClient</u></a> client, String slotName)
void	<a href="#"><u>deleteSlot</u></a> (String slotName)
void	<a href="#"><u>disconnect</u></a> ( <a href="#"><u>IClient</u></a> client)
void	<a href="#"><u>flush</u></a> ()
static boolean[]	<a href="#"><u>getAccess</u></a> ( <a href="#"><u>IClient</u></a> client, String soName)
java.util.List	<a href="#"><u>getClients</u></a> ()
void	<a href="#"><u>getClientUpdates</u></a> ( <a href="#"><u>IClient</u></a> client)
String	<a href="#"><u>getName</u></a> ()
<a href="#"><u>ISharedObjects</u></a>	<a href="#"><u>getParent</u></a> ()
<a href="#"><u>AMFData</u></a>	<a href="#"><u>getProperty</u></a> (String slotName)
int	<a href="#"><u>getRefCount</u></a> ()
<a href="#"><u>ISharedObjectSlot</u></a>	<a href="#"><u>getSlot</u></a> (String name)
java.util.List	<a href="#"><u>getSlotNames</u></a> ()
java.util.List	<a href="#"><u>getSlots</u></a> ()
String	<a href="#"><u>getStorageDir</u></a> ()
int	<a href="#"><u>getVersion</u></a> ()
boolean	<a href="#"><u>isClient</u></a> ( <a href="#"><u>IClient</u></a> client)
boolean	<a href="#"><u>isPersistent</u></a> ()
void	<a href="#"><u>load</u></a> ()
void	<a href="#"><u>lock</u></a> ()
void	<a href="#"><u>notifySlotDelete</u></a> ( <a href="#"><u>ISharedObjectSlot</u></a> slot)
void	<a href="#"><u>notifySlotSetValue</u></a> ( <a href="#"><u>ISharedObjectSlot</u></a> slot)



int	<a href="#">purge</a> (int version)
void	<a href="#">putSlot</a> (String name, <a href="#">ISharedObjectSlot</a> slot)
void	<a href="#">release</a> ()
void	<a href="#">removeClient</a> ( <a href="#">IClient</a> client)
void	<a href="#">removeSlotListener</a> ( <a href="#">ISharedObjectSlotNotify</a> slotListener)
void	<a href="#">send</a> (String handlerName)
void	<a href="#">send</a> (String handlerName, Object[] params)
void	<a href="#">sendInternal</a> ( <a href="#">IClient</a> client, String handlerName, byte[] msgBytes)
void	<a href="#">sendInternal</a> ( <a href="#">IClient</a> client, String handlerName, byte[] msgBytes, <a href="#">AMFDataContextDeserialize</a> context)
void	<a href="#">sendInternal</a> (String handlerName, <a href="#">AMFData[]</a> params)
void	<a href="#">setName</a> (String name)
void	<a href="#">setParent</a> ( <a href="#">ISharedObjects</a> parent)
void	<a href="#">setPersistent</a> (boolean isPersistent)
void	<a href="#">setProperty</a> (String slotName, <a href="#">AMFData</a> data)
void	<a href="#">setProperty</a> (String slotName, boolean value)
void	<a href="#">setProperty</a> (String slotName, java.util.Date value)
void	<a href="#">setProperty</a> (String slotName, double value)
void	<a href="#">setProperty</a> (String slotName, int value)
void	<a href="#">setProperty</a> (String slotName, long value)
void	<a href="#">setProperty</a> (String slotName, String value)
void	<a href="#">setSlotValue</a> ( <a href="#">IClient</a> client, String slotName, <a href="#">AMFData</a> amfData)
void	<a href="#">setSlotValue</a> ( <a href="#">IClient</a> client, String slotName, byte[] byteData)
void	<a href="#">setSlotValue</a> ( <a href="#">IClient</a> client, String slotName, byte[] byteData, <a href="#">AMFData</a> amfData)

void	<a href="#">setSlotValue(IClient client, String slotName, byte[] byteData, <a href="#">AMFData</a> amfData, <a href="#">AMFDataContextDeserialize</a> context)</a>
void	<a href="#">setSlotValue(IClient client, String slotName, byte[] byteData, <a href="#">AMFDataContextDeserialize</a> context)</a>
void	<a href="#">setStorageDir</a> (String storageDir)
void	<a href="#">setVersion</a> (int version)
int	<a href="#">size</a> ()
void	<a href="#">unlock</a> ()
void	<a href="#">writeDeleteError(IClient client, String soName, boolean isPersistent, String slotName, String errorMsg)</a>
static void	<a href="#">writeError(IClient client, String soName, boolean isPersistent, String errorMsg, boolean isConnect)</a>
void	<a href="#">writeSetValueError(IClient client, String soName, boolean isPersistent, String slotName, String errorMsg)</a>

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

#### Methods inherited from interface [com.wowza.wms.sharedobject.ISharedObject](#)

[acquire](#), [addClient](#), [addSlotListener](#), [clear](#), [close](#), [containsProperty](#), [containsSlot](#), [deleteSlot](#), [deleteSlot](#), [disconnect](#), [flush](#), [getClients](#), [getName](#), [getParent](#), [getProperty](#), [getRefCount](#), [getSlot](#), [getSlotNames](#), [getSlots](#), [getStorageDir](#), [getVersion](#), [isClient](#), [isPersistent](#), [lock](#), [purge](#), [putSlot](#), [release](#), [removeClient](#), [removeSlotListener](#), [send](#), [send](#), [setName](#), [setPersistent](#), [setProperty](#), [setProperty](#), [setProperty](#), [setProperty](#), [setProperty](#), [setProperty](#), [setStorageDir](#), [setVersion](#), [size](#), [unlock](#), [writeDeleteError](#), [writeSetValueError](#)

## Fields

### READACCESS

```
public static final int READACCESS
```

Constant value: **0**

### WRITEACCESS

```
public static final int WRITEACCESS
```

Constant value: **1**

(continued from last page)

## Constructors

### SharedObject

```
public SharedObject(String name)
```

Create new shared object

**Parameters:**

name - shared object name

### SharedObject

```
public SharedObject(String name,  
                    boolean isPersistent,  
                    String storageDir)
```

Create new shared object

**Parameters:**

name - shared object name

isPersistent - is persistent

storageDir - storage directory for persistent shared object

## Methods

### size

```
public int size()
```

### purge

```
public int purge(int version)
```

### clear

```
public void clear()
```

### getSlots

```
public java.util.List getSlots()
```

### getSlotNames

```
public java.util.List getSlotNames()
```

(continued from last page)

---

## getSlot

```
public ISharedObjectSlot getSlot(String name)
```

---

## putSlot

```
public void putSlot(String name,  
    ISharedObjectSlot slot)
```

---

## getClients

```
public java.util.List getClients()
```

---

## isClient

```
public boolean isClient(IClient client)
```

---

## addClient

```
public void addClient(IClient client)
```

---

## removeClient

```
public void removeClient(IClient client)
```

---

## acquire

```
public void acquire()
```

---

## release

```
public void release()
```

---

## getRefCount

```
public int getRefCount()
```

---

## isPersistent

```
public boolean isPersistent()
```

---

(continued from last page)

---

## setPersistent

```
public void setPersistent(boolean isPersistent)
```

---

## getVersion

```
public int getVersion()
```

---

## setVersion

```
public void setVersion(int version)
```

---

## deleteSlot

```
public void deleteSlot(String slotName)
```

---

## containsProperty

```
public boolean containsProperty(String slotName)
```

---

## containsSlot

```
public boolean containsSlot(String slotName)
```

---

## deleteSlot

```
public void deleteSlot(IClient client,  
                        String slotName)
```

---

## getProperty

```
public AMFData getProperty(String slotName)
```

---

## setProperty

```
public void setProperty(String slotName,  
                        boolean value)
```

---

**setProperty**

```
public void setProperty(String slotName,  
    java.util.Date value)
```

---

**setProperty**

```
public void setProperty(String slotName,  
    double value)
```

---

**setProperty**

```
public void setProperty(String slotName,  
    long value)
```

---

**setProperty**

```
public void setProperty(String slotName,  
    int value)
```

---

**setProperty**

```
public void setProperty(String slotName,  
    String value)
```

---

**setProperty**

```
public void setProperty(String slotName,  
    AMFData data)
```

---

**setSlotValue**

```
public void setSlotValue(IClient client,  
    String slotName,  
    AMFData amfData)
```

---

**setSlotValue**

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData)
```

---

(continued from last page)

---

## setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData,  
    AMFDataContextDeserialize context)
```

---

## setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData,  
    AMFData amfData)
```

---

## setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData,  
    AMFData amfData,  
    AMFDataContextDeserialize context)
```

---

## writeError

```
public static void writeError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String errorMsg,  
    boolean isConnect)
```

---

## writeSetValueError

```
public void writeSetValueError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

---

## writeDeleteError

```
public void writeDeleteError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

---

## getClientUpdates

```
public void getClientUpdates(IClient client)
```

---

(continued from last page)

---

## disconnect

```
public void disconnect(IClient client)
```

---

---

## getName

```
public String getName()
```

---

---

## setName

```
public void setName(String name)
```

---

---

## send

```
public void send(String handlerName,  
                 Object[] params)
```

---

---

## send

```
public void send(String handlerName)
```

---

---

## sendInternal

```
public void sendInternal(String handlerName,  
                        AMFData\[\] params)
```

---

---

## sendInternal

```
public void sendInternal(IClient client,  
                        String handlerName,  
                        byte[] msgBytes)
```

---

---

## sendInternal

```
public void sendInternal(IClient client,  
                        String handlerName,  
                        byte[] msgBytes,  
                        AMFDataContextDeserialize context)
```

---



(continued from last page)

---

## addSlotListener

```
public void addSlotListener(ISharedObjectSlotNotify slotListener)
```

---

## removeSlotListener

```
public void removeSlotListener(ISharedObjectSlotNotify slotListener)
```

---

## notifySlotSetValue

```
public void notifySlotSetValue(ISharedObjectSlot slot)
```

---

## notifySlotDelete

```
public void notifySlotDelete(ISharedObjectSlot slot)
```

---

## getStorageDir

```
public String getStorageDir()
```

---

## setStorageDir

```
public void setStorageDir(String storageDir)
```

---

## flush

```
public void flush()
```

---

## load

```
public void load()
```

---

## close

```
public void close()
```

---

## lock

```
public void lock()
```

---

(continued from last page)

---

## unlock

```
public void unlock()
```

---

## setParent

```
public void setParent(ISharedObjects parent)
```

---

## getParent

```
public ISharedObjects getParent()
```

---

## getAccess

```
public static boolean[] getAccess(IClient client,  
    String soName)
```

---

Package

**com.wowza.wms.stream**

## com.wowza.wms.stream

### Class FastPlaySettings

java.lang.Object

└─com.wowza.wms.stream.FastPlaySettings

public class **FastPlaySettings**  
extends Object

FastPlaySettings: data container for fast play settings

#### Constructor Summary

public	<a href="#">FastPlaySettings()</a> Create empty object
public	<a href="#">FastPlaySettings(double multiplier, int fps, int direction)</a> Create object

#### Method Summary

int	<a href="#">getDirection()</a> Get direction (1 forward, -1 reverse)
int	<a href="#">getFps()</a> Get frames per second
double	<a href="#">getMultiplier()</a> Get speed of fast play
long	<a href="#">getStartTC()</a> Get the timecode (milliseconds) where this fast play started
long	<a href="#">getStartTCOffset()</a> Get the timecode (milliseconds) where this fast play started (not sure why we have both values)
void	<a href="#">setDirection(int direction)</a> Set direction (1 forward, -1 reverse)
void	<a href="#">setFps(int fps)</a> Set frames per second
void	<a href="#">setMultiplier(double multiplier)</a> Set speed of fast play
void	<a href="#">setStartTC(long startTC)</a> Set the timecode (milliseconds) where this fast play started
void	<a href="#">setStartTCOffset(long startTCOffset)</a> Set the timecode (milliseconds) where this fast play started (not sure why we have both values)

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

---

## Constructors

### FastPlaySettings

```
public FastPlaySettings()
```

Create empty object

---

### FastPlaySettings

```
public FastPlaySettings(double multiplier,  
                        int fps,  
                        int direction)
```

Create object

**Parameters:**

multiplier - speed

fps - frames per second

direction - direction (1 forward, -1 reverse)

## Methods

### getFps

```
public int getFps()
```

Get frames per second

**Returns:**

frames per second

---

### setFps

```
public void setFps(int fps)
```

Set frames per second

**Parameters:**

fps - frames per second

---

### getMultiplier

```
public double getMultiplier()
```

Get speed of fast play

**Returns:**

speed of fast play

---

(continued from last page)

## setMultiplier

```
public void setMultiplier(double multiplier)
```

Set speed of fast play

### Parameters:

multiplier - speed of fast play

---

## getDirection

```
public int getDirection()
```

Get direction (1 forward, -1 reverse)

### Returns:

direction (1 forward, -1 reverse)

---

## setDirection

```
public void setDirection(int direction)
```

Set direction (1 forward, -1 reverse)

### Parameters:

direction - direction (1 forward, -1 reverse)

---

## getStartTC

```
public long getStartTC()
```

Get the timecode (milliseconds) where this fast play started

### Returns:

timecode of start of fast play (milliseconds)

---

## setStartTC

```
public void setStartTC(long startTC)
```

Set the timecode (milliseconds) where this fast play started

### Parameters:

startTC - timecode of start of fast play (milliseconds)

---

## getStartTCOffset

```
public long getStartTCOffset()
```

Get the timecode (milliseconds) where this fast play started (not sure why we have both values)

### Returns:

timecode of start of fast play (milliseconds)

---

## setStartTCOffset

```
public void setStartTCOffset(long startTCOffset)
```

---

(continued from last page)

Set the timecode (milliseconds) where this fast play started (not sure why we have both values)

**Parameters:**

`startTCOffset` - timecode of start of fast play (milliseconds)

## com.wowza.wms.stream Interface IMediaIndexItem

public interface **IMediaIndexItem**  
extends

IMediaIndexItem: generic interface to mediaIndex

### Field Summary

public static final	<a href="#">MISSING</a> media file is missing Value: <b>**missing**</b>
---------------------	---

### Method Summary

<a href="#">IMediaIndexItem</a>	<a href="#">clone()</a> Make a clone copy of media index
String	<a href="#">getChecksum()</a> Get checksum for media index
int	<a href="#">getExtent()</a> Get the duration (milliseconds) of media index
long	<a href="#">getLastAccessed()</a> Get last time media index was accessed (milliseconds)
boolean	<a href="#">isHitEnd()</a> Is media index complete
void	<a href="#">setChecksum(IRandomAccessReader file)</a> Set media index checksum.
void	<a href="#">setChecksum(String checksum)</a> Set media index checksum
void	<a href="#">setLastAccessed(long time)</a> Set last time media index accessed (milliseconds)
void	<a href="#">touch()</a> Set last time accessed to current time

### Fields

#### MISSING

public static final java.lang.String **MISSING**

media file is missing  
Constant value: **\*\*missing\*\***



(continued from last page)

## Methods

### getExtent

```
public int getExtent()
```

Get the duration (milliseconds) of media index

**Returns:**

duration (milliseconds)

### getChecksum

```
public String getChecksum()
```

Get checksum for media index

**Returns:**

checksum

### setChecksum

```
public void setChecksum(String checksum)
```

Set media index checksum

**Parameters:**

checksum

### setChecksum

```
public void setChecksum(IRandomAccessReader file)
```

Set media index checksum. Extract data from File spec

**Parameters:**

file

### clone

```
public IMediaIndexItem clone()
```

Make a clone copy of media index

**Returns:**

shallow copy of media index

### getLastAccessed

```
public long getLastAccessed()
```

Get last time media index was accessed (milliseconds)

**Returns:**

time media index was accessed (milliseconds)

(continued from last page)

## setLastAccessed

```
public void setLastAccessed(long time)
```

Set last time media index accessed (milliseconds)

**Parameters:**

time - media index was accessed (milliseconds)

---

## isHitEnd

```
public boolean isHitEnd()
```

Is media index complete

**Returns:**

true if media index is complete

---

## touch

```
public void touch()
```

Set last time accessed to current time

## com.wowza.wms.stream Interface IMediaListProvider

public interface **IMediaListProvider**  
extends

### Method Summary

<a href="#">MediaList</a>	<a href="#">resolveMediaList</a> ( <a href="#">IMediaListReader</a> mediaListReader, <a href="#">IMediaStream</a> stream, String streamName) Called to resolve a amlst:streamname to a media list
---------------------------	--

### Methods

#### **resolveMediaList**

```
public MediaList resolveMediaList(IMediaListReader mediaListReader,  
    IMediaStream stream,  
    String streamName)
```

Called to resolve a amlst:streamname to a media list

#### **Parameters:**

mediaListReader - mediaListReader  
stream - media stream  
streamName - stream name

#### **Returns:**

media list

## com.wowza.wms.stream Interface IMediaListReader

public interface **IMediaListReader**  
extends

### Method Summary

void	<a href="#"><code>close()</code></a> close file
<a href="#"><code>IHTTPStreamerSession</code></a>	<a href="#"><code>getHTTPStreamerSession()</code></a> Get the HTTPStreamerSession associated with this media list reader
String	<a href="#"><code>getMediaExtension()</code></a> Get media extension
<a href="#"><code>MediaList</code></a>	<a href="#"><code>getMediaList()</code></a> Get the MediaList object
String	<a href="#"><code>getPath()</code></a> Get abstract path to the media item
void	<a href="#"><code>init(IApplicationInstance appInstance, IMediaStream stream, String mediaReadType, String basePath, String mediaName, IHTTPStreamerSession httpStreamerSession)</code></a> Initialize mediaReader
boolean	<a href="#"><code>isOpen()</code></a> is file open
void	<a href="#"><code>open(String basePath, String name)</code></a> Open the file for reading
void	<a href="#"><code>setHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)</code></a> Set the HTTPStreamerSession associated with this media list reader
void	<a href="#"><code>setMediaReaderItem(MediaReaderItem mediaReaderItem)</code></a> Set the mediaReader item definition
void	<a href="#"><code>setProperties(WMSProperties properties)</code></a> Set the properties for this media reader

### Methods

#### init

```
public void init(IApplicationInstance appInstance,
IMediaStream stream,
String mediaReadType,
String basePath,
String mediaName,
IHTTPStreamerSession httpStreamerSession)
```

(continued from last page)

Initialize mediaReader

**Parameters:**

stream - parent stream  
mediaReadType - media reader type id. Example: flv  
basePath - Base path for application instance  
mediaName - name of the media item

---

## setMediaReaderItem

```
public void setMediaReaderItem(MediaReaderItem mediaReaderItem)
```

Set the mediaReader item definition

**Parameters:**

mediaReaderItem

---

## open

```
public void open(String basePath,  
String name)
```

Open the file for reading

**Parameters:**

basePath - base path to file  
name - file name without extension

---

## close

```
public void close()
```

close file

---

## isOpen

```
public boolean isOpen()
```

is file open

**Returns:**

is file open

---

## setProperties

```
public void setProperties(WMSPProperties properties)
```

Set the properties for this media reader

**Parameters:**

properties - properties

---

## getPath

```
public String getPath()
```

Get abstract path to the media item

**Returns:**

(continued from last page)

abstract path to the media item

---

## getMediaExtension

```
public String getMediaExtension()
```

Get media extension

**Returns:**

media extension

---

## getMediaList

```
public MediaList getMediaList()
```

Get the MediaList object

**Returns:**

MediaList object

---

## getHTTPStreamerSession

```
public IHTTPStreamerSession getHTTPStreamerSession()
```

Get the HTTPStreamerSession associated with this media list reader

**Returns:**

HTTPStreamerSession

---

## setHTTPStreamerSession

```
public void setHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Set the HTTPStreamerSession associated with this media list reader

**Parameters:**

httpStreamerSession - HTTPStreamerSession

## com.wowza.wms.stream Interface IMediaReader

public interface **IMediaReader**  
extends

IMediaReader: generic media reader interface. All media types implement this interface to interact with PlaylistPlayer.

### Field Summary

public static final	<a href="#"><u>CONTENTTYPE_MEDIA</u></a> Value: <b>1</b>
public static final	<a href="#"><u>CONTENTTYPE_MEDIALIST</u></a> Value: <b>2</b>
public static final	<a href="#"><u>DEFAULT_RANDOMACCESSREADER</u></a> Value: <b>com.wowza.io.DirectRandomAccessReader</b>
public static final	<a href="#"><u>DEFAULT_RANDOMACCESSREADEROPTIMIZER</u></a> Value: <b>com.wowza.io.RandomAccessReadOptimizer</b>
public static final	<a href="#"><u>PLAYEVENT_AFTERBUFFERFILL</u></a> Value: <b>5</b>
public static final	<a href="#"><u>PLAYEVENT_AFTERMETADATA</u></a> Value: <b>3</b>
public static final	<a href="#"><u>PLAYEVENT_BEFOREBUFFERFILL</u></a> Value: <b>4</b>
public static final	<a href="#"><u>PLAYEVENT_BEFOREMETADATA</u></a> Value: <b>2</b>
public static final	<a href="#"><u>PLAYEVENT_STARTPLAYBACK</u></a> Value: <b>1</b>
public static final	<a href="#"><u>SEEK_EXACT</u></a> Seek direction: closest frame (audio, video) (key, no-key) Value: <b>4</b>
public static final	<a href="#"><u>SEEK_KEYCLOSE</u></a> Seek direction: closest key frame Value: <b>3</b>
public static final	<a href="#"><u>SEEK_KEYDOWN</u></a> Seek direction: down to closets key frame Value: <b>2</b>

public static final	<a href="#">SEEK_KEYUP</a> Seek direction: up to closets key frame Value: <b>1</b>
public static final	<a href="#">SEEKTARGET_AUDIO</a> Value: <b>3</b>
public static final	<a href="#">SEEKTARGET_ENHANCED</a> Value: <b>4</b>
public static final	<a href="#">SEEKTARGET_VIDEOKEYFRAME</a> Value: <b>1</b>

## Method Summary

void	<a href="#">close()</a> close file
long	<a href="#">getDuration()</a> Get duration or time (milliseconds) of the media file
long	<a href="#">getLength()</a> Get the stream length in bytes
String	<a href="#">getMediaExtension()</a> Get media extension
java.util.List	<a href="#">getMetadata()</a> Get a collection of metadata packets in ByteBuffers for this file.
String	<a href="#">getPath()</a> Get abstract path to the media item
<a href="#">IMediaReaderStreamPosition</a>	<a href="#">getStreamPosition()</a> Get a reference to the current stream position
void	<a href="#">init()</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">IMediaStream</a> stream, String mediaReadType, String basePath, String mediaName) Initialize mediaReader
boolean	<a href="#">isOpen()</a> is file open
void	<a href="#">open()</a> (String basePath, String name) Open the file for reading
void	<a href="#">rewind()</a> rewind file to start
PlaylistSeekResult	<a href="#">seek()</a> (long timecode, int seektype) seek to timecode in file
int	<a href="#">sendZeroLengthPacket()</a> (int type, int timecode, boolean isAbsolute, <a href="#">IMediaStream</a> stream, java.io.OutputStream out, <a href="#">AMFObj</a> wmsObj, PlaylistCursor flvCursor, PlaylistWriteControl control, PlaylistReaderWriteResults results, long[] sizes, boolean isForceTCZero)



void	<a href="#"><code>setMediaReaderItem</code></a> ( <a href="#"><code>MediaReaderItem</code></a> mediaReaderItem) Set the mediaReader item definition
void	<a href="#"><code>setProperties</code></a> ( <a href="#"><code>WMSProperties</code></a> properties) Set the properties for this media reader
void	<a href="#"><code>setStreamPosition</code></a> ( <a href="#"><code>IMediaReaderStreamPosition</code></a> pos) Set the file position within the media file
void	<a href="#"><code>startPlayback</code></a> () Called each time the player being playback (before the buffer it filled)
int	<a href="#"><code>writeGeneratedKeyFrame</code></a> ( <a href="#"><code>IMediaStream</code></a> stream, java.io.OutputStream out, <a href="#"><code>AMFObj</code></a> wmsObjAudio, <a href="#"><code>AMFObj</code></a> wmsObjVideo, <a href="#"><code>AMFObj</code></a> wmsObjData, <a href="#"><code>PlaylistCursor</code></a> flvCursor, <a href="#"><code>PlaylistWriteControl</code></a> control, <a href="#"><code>PlaylistReaderWriteResults</code></a> results, long[] sizes, <a href="#"><code>FastPlaySettings</code></a> fastPlaySettings, boolean isForceTCZero) From current location in file generate a key frame (enhanced seek) and write it to out
int	<a href="#"><code>writePackets</code></a> ( <a href="#"><code>IMediaStream</code></a> stream, java.io.OutputStream out, <a href="#"><code>AMFObj</code></a> wmsObjAudio, <a href="#"><code>AMFObj</code></a> wmsObjVideo, <a href="#"><code>AMFObj</code></a> wmsObjData, <a href="#"><code>PlaylistCursor</code></a> flvCursor, <a href="#"><code>PlaylistWriteControl</code></a> control, <a href="#"><code>PlaylistReaderWriteResults</code></a> results, long[] sizes, <a href="#"><code>FastPlaySettings</code></a> fastPlaySettings, boolean isForceTCZero) From current location in file write packets to output
int	<a href="#"><code>writePackets</code></a> (java.util.List packetList, <a href="#"><code>PlaylistCursor</code></a> flvCursor, <a href="#"><code>PlaylistWriteControl</code></a> control, <a href="#"><code>PlaylistReaderWriteResults</code></a> results, long[] sizes, <a href="#"><code>FastPlaySettings</code></a> fastPlaySettings) Write packets to the packetList as AMFPackets

## Fields

### CONTENTTYPE\_MEDIA

```
public static final int CONTENTTYPE_MEDIA
```

Constant value: **1**

### CONTENTTYPE\_MEDIALIST

```
public static final int CONTENTTYPE_MEDIALIST
```

Constant value: **2**

### DEFAULT\_RANDOMACCESSREADER

```
public static final java.lang.String DEFAULT_RANDOMACCESSREADER
```

Constant value: **com.wowza.io.DirectRandomAccessReader**

### DEFAULT\_RANDOMACCESSREADEROPTIMIZER

```
public static final java.lang.String DEFAULT_RANDOMACCESSREADEROPTIMIZER
```

Constant value: **com.wowza.io.RandomAccessReadOptimizer**

---

## SEEKTARGET\_VIDEOKEYFRAME

```
public static final int SEEKTARGET_VIDEOKEYFRAME
```

Constant value: **1**

---

## SEEKTARGET\_AUDIO

```
public static final int SEEKTARGET_AUDIO
```

Constant value: **3**

---

## SEEKTARGET\_ENHANCED

```
public static final int SEEKTARGET_ENHANCED
```

Constant value: **4**

---

## PLAYEVENT\_STARTPLAYBACK

```
public static final int PLAYEVENT_STARTPLAYBACK
```

Constant value: **1**

---

## PLAYEVENT\_BEFOREMETADATA

```
public static final int PLAYEVENT_BEFOREMETADATA
```

Constant value: **2**

---

## PLAYEVENT\_AFTERMETADATA

```
public static final int PLAYEVENT_AFTERMETADATA
```

Constant value: **3**

---

## PLAYEVENT\_BEFOREBUFFERFILL

```
public static final int PLAYEVENT_BEFOREBUFFERFILL
```

Constant value: **4**

---

## PLAYEVENT\_AFTERBUFFERFILL

```
public static final int PLAYEVENT_AFTERBUFFERFILL
```

Constant value: **5**

---

(continued from last page)

---

## SEEK\_KEYUP

```
public static final int SEEK_KEYUP
```

Seek direction: up to closets key frame  
Constant value: **1**

---

## SEEK\_KEYDOWN

```
public static final int SEEK_KEYDOWN
```

Seek direction: down to closets key frame  
Constant value: **2**

---

## SEEK\_KEYCLOSE

```
public static final int SEEK_KEYCLOSE
```

Seek direction: closest key frame  
Constant value: **3**

---

## SEEK\_EXACT

```
public static final int SEEK_EXACT
```

Seek direction: closest frame (audio, video) (key, no-key)  
Constant value: **4**

---

## Methods

### init

```
public void init(IApplicationInstance appInstance,  
                IMediaStream stream,  
                String mediaReadType,  
                String basePath,  
                String mediaName)
```

Initialize mediaReader

**Parameters:**

stream - parent stream  
mediaReadType - media reader type id. Example: flv  
basePath - Base path for application instance  
mediaName - name of the media item

---

### setMediaReaderItem

```
public void setMediaReaderItem(MediaReaderItem mediaReaderItem)
```

Set the mediaReader item definition

**Parameters:**

mediaReaderItem

---

### open

```
public void open(String basePath,  
                String name)
```

---

(continued from last page)

Open the file for reading

**Parameters:**

basePath - base path to file  
name - file name without extension

---

## getMetadata

```
public java.util.List getMetadata()
```

Get a collection of metadata packets in ByteBuffers for this file. You can use 'new AMFDataList(data)' to convert to AMF objects.

**Returns:**

collection of metadata packets in ByteBuffers

---

## rewind

```
public void rewind()
```

rewind file to start

---

## close

```
public void close()
```

close file

---

## isOpen

```
public boolean isOpen()
```

is file open

**Returns:**

is file open

---

## seek

```
public PlaylistSeekResult seek(long timecode,  
int seektype)
```

seek to timecode in file

**Parameters:**

timecode - timecode (milliseconds) to seek to  
seektype - seek type IMediaReader.SEEK\_\*

**Returns:**

detailed results object of seek or null if failure

---

(continued from last page)

## writePackets

```
public int writePackets(IMediaStream stream,
    java.io.OutputStream out,
    AMFObj wmsObjAudio,
    AMFObj wmsObjVideo,
    AMFObj wmsObjData,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    FastPlaySettings fastPlaySettings,
    boolean isForceTCZero)
```

From current location in file write packets to output

### Parameters:

stream - parent mediaStream  
 out - output stream  
 wmsObjAudio - audio channel amfObj  
 wmsObjVideo - video channel amfObj  
 wmsObjData - data channel amfObj  
 flvCursor - current cursor that keeps track of timecodes and flags indicating position in media file  
 control - write control flags. Mainly used to control when it should stop writing  
 results - write results returned from this routine  
 sizes - array of values that keep track of number of bytes written and number of packets for each data type (audio, video, data). See [IMediaStreamPlay.PLAYSIZES\\_\\*](#)  
 fastPlaySettings - current fastPlay settings for the stream  
 isForceTCZero - are we forcing all timecodes to zero

### Returns:

number of bytes written

## writePackets

```
public int writePackets(java.util.List packetList,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    FastPlaySettings fastPlaySettings)
```

Write packets to the packetList as AMFPackets

### Parameters:

packetList - list to which to write packets  
 flvCursor - current cursor that keeps track of timecodes and flags indicating position in media file  
 control - write control flags. Mainly used to control when it should stop writing  
 results - write results returned from this routine  
 sizes - array of values that keep track of number of bytes written and number of packets for each data type (audio, video, data). See [IMediaStreamPlay.PLAYSIZES\\_\\*](#)  
 fastPlaySettings - current fastPlay settings for the stream

### Returns:

number of bytes written

(continued from last page)

## writeGeneratedKeyFrame

```
public int writeGeneratedKeyFrame(IMediaStream stream,
    java.io.OutputStream out,
    AMFObj wmsObjAudio,
    AMFObj wmsObjVideo,
    AMFObj wmsObjData,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    FastPlaySettings fastPlaySettings,
    boolean isForceTCZero)
```

From current location in file generate a key frame (enhanced seek) and write it to out

### Parameters:

stream - parent mediaStream  
 out - output stream  
 wmsObjAudio - audio channel amfObj  
 wmsObjVideo - video channel amfObj  
 wmsObjData - data channel amfObj  
 flvCursor - current cursor that keeps track of timecodes and flags indicating position in media file  
 control - write control flags. Mainly used to control when it should stop writing  
 results - write results returned from this routine  
 sizes - array of values that keep track of number of bytes written and number of packets for each data type (audio, video, data). See [IMediaStreamPlay.PLAYSIZES\\_\\*](#)  
 fastPlaySettings - current fastPlay settings for the stream  
 isForceTCZero - are we forcing all timecodes to zero

### Returns:

number of bytes written

## sendZeroLengthPacket

```
public int sendZeroLengthPacket(int type,
    int timecode,
    boolean isAbsolute,
    IMediaStream stream,
    java.io.OutputStream out,
    AMFObj wmsObj,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    boolean isForceTCZero)
```

## startPlayback

```
public void startPlayback()
```

Called each time the player being playback (before the buffer it filled)

## getDuration

```
public long getDuration()
```

Get duration or time (milliseconds) of the media file

### Returns:

(continued from last page)

duration or time (milliseconds) of the media file

---

## getLength

```
public long getLength()
```

Get the stream length in bytes

**Returns:**

stream length in bytes

---

## getPath

```
public String getPath()
```

Get abstract path to the media item

**Returns:**

abstract path to the media item

---

## getMediaExtension

```
public String getMediaExtension()
```

Get media extension

**Returns:**

media extension

---

## getStreamPosition

```
public IMediaReaderStreamPosition getStreamPosition()
```

Get a reference to the current stream position

**Returns:**

stream position

---

## setStreamPosition

```
public void setStreamPosition(IMediaReaderStreamPosition pos)
```

Set the file position within the media file

**Parameters:**

pos - stream position

---

## setProperties

```
public void setProperties(WMSProperties properties)
```

Set the properties for this media reader

**Parameters:**

properties - properties

## com.wowza.wms.stream Interface IMediaReaderActionNotify

public interface **IMediaReaderActionNotify**  
extends

IMediaReaderActionNotify: listener interface for IMediaReader actions: See  
IApplicationInstance.addMediaReaderListener(IMediaReaderActionNotify mediaReaderListener)

### Method Summary

void	<a href="#">onMediaReaderClose</a> ( <a href="#">IMediaReader</a> mediaReader, <a href="#">IMediaStream</a> stream) Called when media reader is closed
void	<a href="#">onMediaReaderCreate</a> ( <a href="#">IMediaReader</a> mediaReader) Called when media reader is created
void	<a href="#">onMediaReaderExtractMetaData</a> ( <a href="#">IMediaReader</a> mediaReader, <a href="#">IMediaStream</a> stream) Called after media reader metadata is extraced from the file
void	<a href="#">onMediaReaderInit</a> ( <a href="#">IMediaReader</a> mediaReader, <a href="#">IMediaStream</a> stream) Called after media reader is initialized
void	<a href="#">onMediaReaderOpen</a> ( <a href="#">IMediaReader</a> mediaReader, <a href="#">IMediaStream</a> stream) Called after media reader is opened

### Methods

#### onMediaReaderCreate

public void **onMediaReaderCreate**([IMediaReader](#) mediaReader)

Called when media reader is created

**Parameters:**

mediaReader - media reader

#### onMediaReaderInit

public void **onMediaReaderInit**([IMediaReader](#) mediaReader, [IMediaStream](#) stream)

Called after media reader is initialized

**Parameters:**

mediaReader - media reader

stream - stream



(continued from last page)

## onMediaReaderOpen

```
public void onMediaReaderOpen(IMediaReader mediaReader,  
    IMediaStream stream)
```

Called after media reader is opened

**Parameters:**

mediaReader - media reader  
stream - stream

---

## onMediaReaderExtractMetaData

```
public void onMediaReaderExtractMetaData(IMediaReader mediaReader,  
    IMediaStream stream)
```

Called after media reader metadata is extracted from the file

**Parameters:**

mediaReader - media reader  
stream - stream

---

## onMediaReaderClose

```
public void onMediaReaderClose(IMediaReader mediaReader,  
    IMediaStream stream)
```

Called when media reader is closed

**Parameters:**

mediaReader - media reader  
stream - stream

---

com.wowza.wms.stream  
Interface IMediaReaderEncInfo

public interface IMediaReaderEncInfo  
extends

Method Summary	
<a href="#">MediaReaderEncInfo</a>	<a href="#">getEncInfo()</a>

Methods

**getEncInfo**  
public [MediaReaderEncInfo](#) **getEncInfo()**

---

## com.wowza.wms.stream Interface IMediaReaderStreamPosition

---

public interface **IMediaReaderStreamPosition**  
extends

IMediaReaderStreamPosition: Internal use

---

### Method Summary

boolean	<a href="#">isValid()</a>
---------	---------------------------

---

### Methods

#### isValid

public boolean **isValid()**

## com.wowza.wms.stream Interface IMediaStream

public interface **IMediaStream**  
extends

IMediaStream: public, generic interface to mediaStream object. Upon creation of a new mediaStream, the client connection's default streamType value will be used to dynamically create a mediaStream object based on the definitions available in the vHosts.mediaStreamMap. All mediaStream implementations implement this interface.

### Field Summary

public static final	<a href="#">AUDIOSAMPLEACCESS</a> Value: <b>2</b>
public static final	<a href="#">READACCESS</a> Value: <b>0</b>
public static final	<a href="#">VIDEOSAMPLEACCESS</a> Value: <b>3</b>
public static final	<a href="#">WRITEACCESS</a> Value: <b>1</b>

### Method Summary

void	<a href="#">addAudioCodecConfigPacket</a> (long timecode, <a href="#">AMFPacket</a> packet) Set audio codec configuration packet (needed for H.264/AAC playback)
void	<a href="#">addAudioData</a> (byte[] data, int offset, int size) Add data to current audio packet
void	<a href="#">addCallbackListener</a> ( <a href="#">IMediaStreamCallback</a> callbackListener) Add a callback listener to listen for all stream metadata
void	<a href="#">addClientListener</a> ( <a href="#">IMediaStreamActionNotify</a> actionListener) Add client listener.
void	<a href="#">addClientListener</a> ( <a href="#">IMediaStreamActionNotify2</a> actionListener) Add client listener.
void	<a href="#">addClientListener</a> ( <a href="#">IMediaStreamActionNotify3</a> actionListener) Add client listener.
void	<a href="#">addDataData</a> (byte[] data, int offset, int size) Add data to current data packet
void	<a href="#">addVideoCodecConfigPacket</a> (long timecode, <a href="#">AMFPacket</a> packet) Set video codec configuration packet (needed for H.264/AAC playback)

void	<a href="#"><code>addVideoData</code></a> (byte[] data, int offset, int size) Add data to current video packet
void	<a href="#"><code>addVideoH264SEIListener</code></a> ( <a href="#"><code>IMediaStreamH264SEINotify</code></a> h264SEIListener) Add an H.264 SEI listener.
void	<a href="#"><code>clear</code></a> () Delete media file pointed to by this mediaStream (be careful)
void	<a href="#"><code>clearFastPlaySettings</code></a> () Clear fastPlay settings
void	<a href="#"><code>clearLoggingValues</code></a> ()
void	<a href="#"><code>close</code></a> () Close mediaStream
void	<a href="#"><code>flush</code></a> () Force publishing packets to be flushed from the input buffers to the output buffers
boolean[]	<a href="#"><code>getAccess</code></a> ( <a href="#"><code>IClient</code></a> client, String name) Get the read/write access to this stream for this client
<a href="#"><code>AMFPacket</code></a>	<a href="#"><code>getAudioCodecConfigPacket</code></a> (long timecode) Get audio codec configuration packet (needed for H.264/AAC playback)
int	<a href="#"><code>getAudioMissing</code></a> () Get number of audio bytes missing from current audio packet
int	<a href="#"><code>getAudioSize</code></a> () Get the size of the current audio packet that is being streamed from the client to the server
long	<a href="#"><code>getAudioTC</code></a> () Get last absolute audio timecode (milliseconds) sent to mediaStream
int	<a href="#"><code>getBufferTime</code></a> () Get buffer time for mediaStream (milliseconds)
byte[]	<a href="#"><code>getBurstStartStop</code></a> (boolean isStart) Get the dynamic streaming burst start/stop AMF packet
String	<a href="#"><code>getCacheName</code></a> () not used
<a href="#"><code>IClient</code></a>	<a href="#"><code>getClient</code></a> () Get parent client connection
int	<a href="#"><code>getClientId</code></a> () Get parent client connection (id)
String	<a href="#"><code>getContextStr</code></a> () Returns the stream context string in the form [application]/[appInstance]/[streamName].
int	<a href="#"><code>getDataMissing</code></a> () Get number of data bytes missing from current audio packet
int	<a href="#"><code>getDataSize</code></a> () Get the size of the current data packet that is being streamed from the client to the server

long	<a href="#"><code>getDataTC()</code></a> Get last absolute data timecode (milliseconds) sent to mediaStream
int	<a href="#"><code>getDataType()</code></a> Get the data packet type: (IVHost.CONTENTTYPE_DATA0 or IVHost.CONTENTTYPE_DATA3)
String	<a href="#"><code>getDvrRecorder()</code></a> Get the DVR Recorder for this stream
<a href="#"><code>ILiveStreamDvrRecorder</code></a>	<a href="#"><code>getDvrRecorder(String name)</code></a> Get the DVR Recorder interface to a stream by name
String	<a href="#"><code>getDvrRecorderList()</code></a> Get the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)
String	<a href="#"><code>getDvrRepeater()</code></a> Get the DVR repeater name for this stream
<a href="#"><code>ElapsedTimer</code></a>	<a href="#"><code>getElapsedTime()</code></a> Get the interface to the elapse timer
String	<a href="#"><code>getExt()</code></a> Get media file extension
<a href="#"><code>FastPlaySettings</code></a>	<a href="#"><code>getFastPlaySettings()</code></a> Get current fastPlay settings
int	<a href="#"><code>getHeaderSize()</code></a> Get the last packet header size (debugging)
<a href="#"><code>IHTTPStreamerSession</code></a>	<a href="#"><code>getHTTPStreamerSession()</code></a> Get the HTTPStreamer session associated with this stream
<a href="#"><code>AMFPacket</code></a>	<a href="#"><code>getLastKeyFrame()</code></a> Get most recent video key frame
<a href="#"><code>AMFPacket</code></a>	<a href="#"><code>getLastPacket()</code></a> Get most recent live packet
String	<a href="#"><code>getLiveStreamPacketizer()</code></a> Get the live stream packetizer that this stream is using
<a href="#"><code>ILiveStreamPacketizer</code></a>	<a href="#"><code>getLiveStreamPacketizer(String name)</code></a> Get the LiveStreamPacketizer interface to a stream by name
String	<a href="#"><code>getLiveStreamPacketizerList()</code></a> Get the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)
String	<a href="#"><code>getLiveStreamRepeater()</code></a> Get the live stream repeater name for the stream
<a href="#"><code>ILiveStreamTranscoder</code></a>	<a href="#"><code>getLiveStreamTranscoder(String name)</code></a> Get a live stream transcoder for this stream by name
String	<a href="#"><code>getLiveStreamTranscoderList()</code></a> Get the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)

java.util.Map	<a href="#"><u>getLiveStreamTranscoders()</u></a> Get the list of transcoders for this stream.
long	<a href="#"><u>getMaxTimecode()</u></a> Get the timecode of the latest received packet
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getMediaIOPerformance()</u></a> Get IO performance counter
<a href="#"><u>IMediaStreamMetaDataProvider</u></a>	<a href="#"><u>getMetaDataProvider()</u></a> Get the metaData provider
String	<a href="#"><u>getName()</u></a> Get stream name
com.wowza.wms.netconnection.INetConnection	<a href="#"><u>getNetConnection()</u></a> Get parent netConnection (future server to server communication)
<a href="#"><u>IMediaStreamPlay</u></a>	<a href="#"><u>getPlayer()</u></a> Get underlying player (IMediaStreamPlay) object
java.util.List	<a href="#"><u>getPlayPackets()</u></a> Get all available live packets
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties()</u></a> Get mediaStream properties
int	<a href="#"><u>getPublishAudioCodecId()</u></a> Get the codec id of the most recently published audio packet
int	<a href="#"><u>getPublishVideoCodecId()</u></a> Get the codec id of the most recently published video packet
String	<a href="#"><u>getQueryStr()</u></a> Get play/publish name query string.
int	<a href="#"><u>getReceiveVideoFPS()</u></a> Set frame per seconds for video (not currently implemented)
<a href="#"><u>AMFObj</u></a>	<a href="#"><u>getRespAMFAudioObj()</u></a> Get audio response channel object
<a href="#"><u>AMFObj</u></a>	<a href="#"><u>getRespAMFDataObj()</u></a> Get data response channel object
<a href="#"><u>AMFObj</u></a>	<a href="#"><u>getRespAMFVideoObj()</u></a> Get video response channel object
<a href="#"><u>RTPStream</u></a>	<a href="#"><u>getRTPStream()</u></a> Get the RTP based stream this stream is associated with
int	<a href="#"><u>getSrc()</u></a> Get the stream id
java.io.File	<a href="#"><u>getStreamFileForRead()</u></a> Get the File object to read from a stream (get stream name, ext and query from stream object)
java.io.File	<a href="#"><u>getStreamFileForRead(String name, String ext, String query)</u></a> Get the File object to read from a stream (specify name, ext and query)

java.io.File	<a href="#"><u>getStreamFileForWrite()</u></a> Get the File object to write to a stream (get stream name, ext and query from stream object)
java.io.File	<a href="#"><u>getStreamFileForWrite(String name, String ext, String query)</u></a> Get the File object to write to a stream (specify name, ext and query)
<a href="#"><u>MediaStreamMap</u></a>	<a href="#"><u>getStreams()</u></a> Get parent mediaStreamMap (owned by applicationInstance)
String	<a href="#"><u>getStreamType()</u></a> Get mediaStream streamType
String	<a href="#"><u>getUniqueStreamIdStr()</u></a> Get a string that uniquely identifies this stream
<a href="#"><u>AMFPacket</u></a>	<a href="#"><u>getVideoCodecConfigPacket(long timecode)</u></a> Get video codec configuration packet (needed for H.264/AAC playback)
int	<a href="#"><u>getVideoMissing()</u></a> Get number of video bytes missing from current audio packet
int	<a href="#"><u>getVideoSize()</u></a> Get the size of the current video packet that is being streamed from the client to the server
long	<a href="#"><u>getVideoTC()</u></a> Get last absolute video timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>handleCallback(com.wowza.wms.request.RequestFunction function)</u></a> Routes request function to callback handler onStatus, onPlayStatus or [method/handler]
boolean	<a href="#"><u>idle()</u></a> Allow the mediaStream to perform idle work (not currently in use)
long	<a href="#"><u>incrementMediaInBytes(long increment)</u></a> Increment the number of mediaStream bytes received
long	<a href="#"><u>incrementMediaLossBytes(long bytes, long count)</u></a> Increment the number of mediaStream loss bytes sent and number of packets sent
long	<a href="#"><u>incrementMediaOutBytes(long bytes, long count)</u></a> Increment the number of mediaStream bytes sent and number of packets sent
void	<a href="#"><u>init(MediaStreamMap parent, int src, WMSProperties properties)</u></a> Initialize the mediaStream object after creation.
void	<a href="#"><u>initLiveStreamRepeating(String liveStreamPacketizer, String liveStreamRepeater)</u></a> Initialize this stream for live stream repeating
boolean	<a href="#"><u>isAppend()</u></a> Is append to media file (only valid if isRecord)
boolean	<a href="#"><u>isClustered()</u></a> not used
boolean	<a href="#"><u>isMediaCasterPlay()</u></a> Is MediaCaster play enabled (if true, will trigger MediaCaster startup)
boolean	<a href="#"><u>isMergeOnMetadata()</u></a> If true, merge incoming onMetadata events with the current onMetadata event data.



boolean	<a href="#"><u>isOpen()</u></a> Is mediaStream open
boolean	<a href="#"><u>isPlay()</u></a> Is the stream a play stream (vs a publish stream)
boolean	<a href="#"><u>isPlaying()</u></a> Is mediaStream playing (or paused - false)
boolean	<a href="#"><u>isPublishStreamReady()</u></a> (boolean checkAudio, boolean checkVideo) Returns true if the publishing stream contains enough video/audio data to start playback
boolean	<a href="#"><u>isReceiveAudio()</u></a> Is client currently receiving audio.
boolean	<a href="#"><u>isReceiveVideo()</u></a> Is client currently receiving video.
boolean	<a href="#"><u>isRecord()</u></a> Is this stream being recorded to a file
boolean	<a href="#"><u>isSendPlayStopLogEvent()</u></a> Get need to send a log event for stop
boolean	<a href="#"><u>isSendPublishStopLogEvent()</u></a> Get need to send a log event for publishing
boolean	<a href="#"><u>isSendRecordStopLogEvent()</u></a> Get need to send a log event for recording
boolean	<a href="#"><u>isTranscodeResult()</u></a> Is this stream the result of a transcode operation.
boolean	<a href="#"><u>isVideoH264SEIListenerEmpty()</u></a> Is H.264 SEI listener list empty.
double	<a href="#"><u>length()</u></a> Get length/duration (seconds) of media file pointed to by mediaStream
void	<a href="#"><u>notifyActionOnCodecInfoAudio()</u></a> (com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio) Notify client listeners of audio codec information change
void	<a href="#"><u>notifyActionOnCodecInfoVideo()</u></a> (com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Notify client listeners of video codec information change
void	<a href="#"><u>notifyActionOnMetaData()</u></a> ( <a href="#"><u>AMFPacket</u></a> metaDataPacket) Notify client listeners of onMetaData change
void	<a href="#"><u>notifyActionPause()</u></a> (boolean isPause, long location) Notify client listeners of pause action
void	<a href="#"><u>notifyActionPauseRaw()</u></a> (boolean isPause, long location) Notify client listeners of pauseRaw action
void	<a href="#"><u>notifyActionPlay()</u></a> (String streamName, double playStart, double playLen, int playReset) Notify client listeners of play action

void	<a href="#"><u>notifyActionPublish</u></a> (String streamName, boolean isRecord, boolean isAppend) Notify client listeners of publish action
void	<a href="#"><u>notifyActionSeek</u></a> (double location) Notify client listeners of seek action
void	<a href="#"><u>notifyActionStop</u></a> () Notify client listeners of stop action
void	<a href="#"><u>notifyActionUnPublish</u></a> (String streamName, boolean isRecord, boolean isAppend) Notify client listeners of unpublish action
void	<a href="#"><u>notifyVideoH264Packet</u></a> ( <a href="#"><u>AMFPacket</u></a> packet, com.wowza.wms.media.h264.H264SEIMessages seiMessages) Notify H.264 SEI listener.
void	<a href="#"><u>packetComplete</u></a> () Invoked by requestAdapter when at the end of a set of packets
void	<a href="#"><u>publish</u></a> () Publish mediaStream
void	<a href="#"><u>putDvrRecorder</u></a> (String name, <a href="#"><u>ILiveStreamDvrRecorder</u></a> dvr) Add a live stream dvr to this stream
void	<a href="#"><u>putLiveStreamTranscoder</u></a> (String name, <a href="#"><u>ILiveStreamTranscoder</u></a> liveStreamTranscoder) Add a live stream transcoder to this stream
void	<a href="#"><u>registerCallback</u></a> (String handlerName, <a href="#"><u>IMediaStreamCallback</u></a> callback) Register a callback handler
void	<a href="#"><u>registerOnPlayStatus</u></a> ( <a href="#"><u>IMediaStreamCallback</u></a> callback) Register onPlayStatus handler
void	<a href="#"><u>registerOnStatus</u></a> ( <a href="#"><u>IMediaStreamCallback</u></a> callback) Register onStatus handler
void	<a href="#"><u>removeCalbackListener</u></a> ( <a href="#"><u>IMediaStreamCallback</u></a> callbackListener) Remove a callback listener to listen for all stream metadata
void	<a href="#"><u>removeClientListener</u></a> ( <a href="#"><u>IMediaStreamActionNotify</u></a> actionListener) Remove client listener.
void	<a href="#"><u>removeClientListener</u></a> ( <a href="#"><u>IMediaStreamActionNotify2</u></a> actionListener) Remove client listener.
void	<a href="#"><u>removeClientListener</u></a> ( <a href="#"><u>IMediaStreamActionNotify3</u></a> actionListener) Remove client listener.
<a href="#"><u>ILiveStreamDvrRecorder</u></a>	<a href="#"><u>removeDvrRecorder</u></a> (String name) Remove a live stream dvr by name
<a href="#"><u>ILiveStreamTranscoder</u></a>	<a href="#"><u>removeLiveStreamTranscoder</u></a> (String name) Remove a live stream transcoder by name
void	<a href="#"><u>removeVideoH264SEIListener</u></a> ( <a href="#"><u>IMediaStreamH264SEINotify</u></a> h264SEIListener) Remove an H.264 SEI listener.

void	<a href="#"><u>send</u></a> (String handlerName) Call client side NetStream method/handler with no parameters
void	<a href="#"><u>send</u></a> (String handlerName, Object[] params) Call client side NetStream method/handler
void	<a href="#"><u>sendAMF3</u></a> (String handlerName) Call client side NetStream method/handler with no parameters.
void	<a href="#"><u>sendAMF3</u></a> (String handlerName, Object[] params) Call client side NetStream method/handler.
int	<a href="#"><u>sendControlBytes</u></a> (int controlType, java.io.OutputStream out) Send playback control bytes.
void	<a href="#"><u>sendDirect</u></a> (String handlerName) Call client side NetStream method/handler and send event to underlying stream (will record event)
void	<a href="#"><u>sendDirect</u></a> (String handlerName, Object[] params) Call client side NetStream method/handler and send event to underlying stream (will record event)
void	<a href="#"><u>sendDirectAMF3</u></a> (String handlerName) Call client side NetStream method/handler and send event to underlying stream (will record event).
void	<a href="#"><u>sendDirectAMF3</u></a> (String handlerName, Object[] params) Call client side NetStream method/handler and send event to underlying stream (will record event).
int	<a href="#"><u>sendLivePlaySeek</u></a> (java.io.OutputStream out, String name, long timecode) Send onStatus(NetStream.Seek.Notify) event
int	<a href="#"><u>sendLivePlayStart</u></a> (java.io.OutputStream out, String name, long timecode, long timecodeOffset) Send onStatus(NetStream.Play.Start) event
int	<a href="#"><u>sendLivePlaySwitch</u></a> (java.io.OutputStream out, String name, long timecode) Send onStatus(NetStream.Play.Transition) event
int	<a href="#"><u>sendPauseNotify</u></a> (long timecode, String name) Send onStatus(NetStream.Pause.Notify) event
int	<a href="#"><u>sendPauseNotify</u></a> (java.io.OutputStream out, long timecode, String name) Send onStatus(NetStream.Pause.Notify) event.
int	<a href="#"><u>sendPlayReset</u></a> (java.io.OutputStream out, String name) Send onStatus(NetStream.Play.Reset) event.
int	<a href="#"><u>sendPlayReset</u></a> (String name) Send onStatus(NetStream.Play.Reset) event
int	<a href="#"><u>sendPlaySeek</u></a> (long location, long seekLocation, String name) Send onStatus(NetStream.Seek.Notify) event.
int	<a href="#"><u>sendPlaySeek</u></a> (java.io.OutputStream out, long location, long seekLocation, String name) Send onStatus(NetStream.Seek.Notify) event.

int	<a href="#"><code>sendPlaySeek</code></a> (java.io.OutputStream out, long location, long seekLocation, String name, java.util.List seekTypes) Send onStatus(NetStream.Seek.Notify) event.
int	<a href="#"><code>sendPlayStart</code></a> (java.io.OutputStream out, String name, boolean isSwitch, boolean isLive, long timecode, java.util.List seekTypes) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<a href="#"><code>sendPlayStart</code></a> (java.io.OutputStream out, String name, boolean isSwitch, long timecode) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<a href="#"><code>sendPlayStart</code></a> (java.io.OutputStream out, String name, boolean isSwitch, long timecode, java.util.List seekTypes) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<a href="#"><code>sendPlayStart</code></a> (String name, long timecode) Send onStatus(NetStream.Play.Start) event
int	<a href="#"><code>sendPlayStatus</code></a> (long timecode, int statusType, double duration, double bytesSent) Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event
int	<a href="#"><code>sendPlayStatus</code></a> (java.io.OutputStream out, long timecode, int statusType, double duration, double bytesSent) Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event.
int	<a href="#"><code>sendPlayStop</code></a> (long location, String name) Send onStatus(NetStream.Play.Stop) event
int	<a href="#"><code>sendPlayStop</code></a> (java.io.OutputStream out, long location, String name) Send onStatus(NetStream.Play.Stop) event.
int	<a href="#"><code>sendPlaySwitch</code></a> (java.io.OutputStream out, String name, boolean isSwitch, long timecode) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<a href="#"><code>sendPlaySwitch</code></a> (String name, long timecode) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<a href="#"><code>sendStreamNotFound</code></a> (java.io.OutputStream out, String name) Send onStatus(NetStream.Play.StreamNotFound) event.
int	<a href="#"><code>sendStreamNotFound</code></a> (String name) Send onStatus(NetStream.Play.StreamNotFound) event
int	<a href="#"><code>sendUnpauseNotify</code></a> (long location, String name) Send onStatus(NetStream.Unpause.Notify) event
int	<a href="#"><code>sendUnpauseNotify</code></a> (java.io.OutputStream out, long location, String name) Send onStatus(NetStream.Unpause.Notify) event.
int	<a href="#"><code>sendUnpauseNotify</code></a> (java.io.OutputStream out, long location, String name, java.util.List seekTypes) Send onStatus(NetStream.Unpause.Notify) event

int	<a href="#"><u>sendVODPlaySwitch</u></a> (java.io.OutputStream out, String name, long timecode) Send onStatus(NetStream.Play.Transition) event
void	<a href="#"><u>setAppend</u></a> (boolean isAppend) Set is append to media file (only valid if isRecord)
void	<a href="#"><u>setAudioSize</u></a> (int audioSize) Set the size of the current audio packet that is being streamed from the client to the server
void	<a href="#"><u>setAudioTC</u></a> (long audioTC) Set last absolute audio timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>setAudioTC</u></a> (long audioTC, boolean isAbsolute) Set last absolute audio timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>setBufferTime</u></a> (int bufferTime) Set buffer time for mediaStream (milliseconds)
void	<a href="#"><u>setClient</u></a> (IClient client) Set parent client connection
void	<a href="#"><u>setClustered</u></a> (boolean isClustered) not used
void	<a href="#"><u>setDataSize</u></a> (int dataSize) Set the size of the current data packet that is being streamed from the client to the server
void	<a href="#"><u>setDataTC</u></a> (long dataTC) Set last absolute data timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>setDataTC</u></a> (long dataTC, boolean isAbsolute) Set last absolute data timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>setDataType</u></a> (int dataType) Set the data packet type: (IVHost.CONTENTTYPE_DATA0 or IVHost.CONTENTTYPE_DATA3)
void	<a href="#"><u>setDvrRecorder</u></a> (String recorderName) Set the DVR Recorder that this stream is using
void	<a href="#"><u>setDvrRecorderList</u></a> (String recorderList) Set the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)
void	<a href="#"><u>setExt</u></a> (String ext) Set media file extension
void	<a href="#"><u>setFastPlaySettings</u></a> (FastPlaySettings fastPlaySettings) Set fastPlay settings
void	<a href="#"><u>setHeaderSize</u></a> (int headerSize) Set the last packet header size (debugging)
void	<a href="#"><u>setHTTPStreamerSession</u></a> (IHTTPStreamerSession httpStreamerSession) Set the HTTPStreamer session associated with this stream
void	<a href="#"><u>setIsPlaying</u></a> (boolean isPlaying) Set is mediaStream playing

void	<a href="#"><u>setLiveStreamPacketizer</u></a> (String liveStreamPacketizer) Set the live stream packetizer that this stream is using
void	<a href="#"><u>setLiveStreamPacketizerList</u></a> (String liveStreamPacketizerList) Set the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)
void	<a href="#"><u>setLiveStreamRepeater</u></a> (String liveStreamRepeater) Set the live stream repeater name for the stream
void	<a href="#"><u>setLiveStreamTranscoderList</u></a> (String liveStreamTranscoderList) Set the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)
void	<a href="#"><u>setMediaCasterPlay</u></a> (boolean isMediaCasterPlay) Is MediaCaster play enabled (if true, will trigger MediaCaster startup)
void	<a href="#"><u>setMergeOnMetadata</u></a> (boolean mergeOnMetadata) If true, merge incoming onMetadata events with the current onMetadata event data.
void	<a href="#"><u>setMetaDataProvider</u></a> ( <a href="#"><u>IMediaStreamMetaDataProvider</u></a> metaDataProvider) Set the metaData provider
void	<a href="#"><u>setName</u></a> (String name) Set stream name
void	<a href="#"><u>setName</u></a> (String name, String ext) Set stream name and extension.
void	<a href="#"><u>setName</u></a> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Set stream name, extension, query string, play start, play len and play reset from play command.
void	<a href="#"><u>setNetConnection</u></a> (com.wowza.wms.netconnection.INetConnection netConnection) Set parent netConnection (future server to server communication)
void	<a href="#"><u>setOpen</u></a> (boolean isOpen) Set mediaStream open
void	<a href="#"><u>setPlay</u></a> (boolean isPlay) Set is the stream a play stream (vs a publish stream)
void	<a href="#"><u>setPlayer</u></a> ( <a href="#"><u>IMediaStreamPlay</u></a> player) Set underlying player (IMediaStreamPlay) object
void	<a href="#"><u>setPublishAudioCodecId</u></a> (int publishAudioCodecId) Set the codec id of the most recently published audio packet
void	<a href="#"><u>setPublishVideoCodecId</u></a> (int publishVideoCodecId) Set the codec id of the most recently published video packet
void	<a href="#"><u>setQueryStr</u></a> (String queryStr) Set play/publish name query string.
void	<a href="#"><u>setReceiveAudio</u></a> (boolean receiveAudio) Set receive audio
void	<a href="#"><u>setReceiveVideo</u></a> (boolean receiveVideo) Set receive video

void	<a href="#"><u>setReceiveVideoFPS</u></a> (int receiveVideoFPS) Set frame per second for video (not currently implemented)
void	<a href="#"><u>setRecord</u></a> (boolean isRecord) Set is the stream being recorded
void	<a href="#"><u>setRTPStream</u></a> (RTPStream rtpStream) Set the RTP based stream this stream is associated with
void	<a href="#"><u>setSendPlayStopLogEvent</u></a> (boolean sendPlayStopLogEvent) Set need to send a log event for stop
void	<a href="#"><u>setSendPublishStopLogEvent</u></a> (boolean sendPlayStopLogEvent) Set need to send a log event for publishing
void	<a href="#"><u>setSendRecordStopLogEvent</u></a> (boolean sendPlayStopLogEvent) Set need to send a log event for recording
void	<a href="#"><u>setSrc</u></a> (int src) Set stream id
void	<a href="#"><u>setStreamType</u></a> (String streamType) Set mediaStream streamType.
void	<a href="#"><u>setTranscodeResult</u></a> (boolean isTranscodeResult) Is this stream the result of a transcode operation.
void	<a href="#"><u>setVideoSize</u></a> (int videoSize) Set the size of the current video packet that is being streamed from the client to the server
void	<a href="#"><u>setVideoTC</u></a> (long videoTC) Set last absolute video timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>setVideoTC</u></a> (long videoTC, boolean isAbsolute) Set last absolute video timecode (milliseconds) sent to mediaStream
void	<a href="#"><u>shutdown</u></a> ( ) shutdown or close this mediaStream
long	<a href="#"><u>size</u></a> ( ) Get size (bytes) of media file pointed to by mediaStream
void	<a href="#"><u>startAudioPacket</u></a> ( ) Called when an audio packet is first being populated with data
void	<a href="#"><u>startDataPacket</u></a> ( ) Called when a data packet is first being populated with data
void	<a href="#"><u>startPublishing</u></a> ( ) Start publishing live stream
void	<a href="#"><u>startVideoPacket</u></a> ( ) Called when a video packet is first being populated with data
void	<a href="#"><u>stopName</u></a> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Stop stream name
void	<a href="#"><u>stopPublishing</u></a> ( ) Stop publishing live stream

void	<a href="#"><code>switchName</code></a> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Switch to stream name
void	<a href="#"><code>trim</code></a> () Trim mediaStream.
void	<a href="#"><code>unregisterCallback</code></a> (String handlerName) Unregister a callback handler
void	<a href="#"><code>unregisterOnPlayStatus</code></a> ( <a href="#"><code>IMediaStreamCallback</code></a> callback) Unregister onPlayStatus handler
void	<a href="#"><code>unregisterOnStatus</code></a> ( <a href="#"><code>IMediaStreamCallback</code></a> callback) Unregister onStatus handler
void	<a href="#"><code>updateLoggingDuration</code></a> ( ) Update logging.MDC with mediaStream logging information
void	<a href="#"><code>updateLoggingValues</code></a> ( ) Update logging.MDC with mediaStream logging information

## Fields

### READACCESS

public static final int **READACCESS**

Constant value: **0**

### WRITEACCESS

public static final int **WRITEACCESS**

Constant value: **1**

### AUDIOSAMPLEACCESS

public static final int **AUDIOSAMPLEACCESS**

Constant value: **2**

### VIDEOSAMPLEACCESS

public static final int **VIDEOSAMPLEACCESS**

Constant value: **3**

## Methods



(continued from last page)

## init

```
public void init(MediaStreamMap parent,  
                int src,  
                WMSProperties properties)
```

Initialize the mediaStream object after creation. Creation and initialization are separated due to the order of the creation events.

### Parameters:

parent - parent mediaStreamMap of the parent applicationInstance  
src - stream id for this stream  
properties - initial properties as defined in Streams.xml

---

## getBufferTime

```
public int getBufferTime()
```

Get buffer time for mediaStream (milliseconds)

### Returns:

buffer time (milliseconds)

---

## setBufferTime

```
public void setBufferTime(int bufferTime)
```

Set buffer time for mediaStream (milliseconds)

### Parameters:

bufferTime - buffer time (milliseconds)

---

## isPlaying

```
public boolean isPlaying()
```

Is mediaStream playing (or paused - false)

### Returns:

is playing

---

## setIsPlaying

```
public void setIsPlaying(boolean isPlaying)
```

Set is mediaStream playing

### Parameters:

isPlaying

---

## getAudioSize

```
public int getAudioSize()
```

Get the size of the current audio packet that is being streamed from the client to the server

### Returns:

size

## getVideoSize

```
public int getVideoSize()
```

Get the size of the current video packet that is being streamed from the client to the server

**Returns:**  
size

---

## getDataSize

```
public int getDataSize()
```

Get the size of the current data packet that is being streamed from the client to the server

**Returns:**  
size

---

## setAudioSize

```
public void setAudioSize(int audioSize)
```

Set the size of the current audio packet that is being streamed from the client to the server

**Parameters:**  
audioSize

---

## setVideoSize

```
public void setVideoSize(int videoSize)
```

Set the size of the current video packet that is being streamed from the client to the server

**Parameters:**  
videoSize

---

## setDataSize

```
public void setDataSize(int dataSize)
```

Set the size of the current data packet that is being streamed from the client to the server

**Parameters:**  
dataSize

---

## getSrc

```
public int getSrc()
```

Get the stream id

**Returns:**  
stream id

---

## setSrc

```
public void setSrc(int src)
```

---

(continued from last page)

Set stream id

**Parameters:**

src - stream id

---

## getName

```
public String getName()
```

Get stream name

**Returns:**

stream name

---

## setName

```
public void setName(String name)
```

Set stream name

**Parameters:**

name - stream name

---

## setName

```
public void setName(String name,  
                    String ext)
```

Set stream name and extension. Example: if play command sent flv:test name=test, ext=flv.

**Parameters:**

name - stream name

ext - stream extension

---

## setName

```
public void setName(String name,  
                    String oldName,  
                    String ext,  
                    String queryStr,  
                    double playStart,  
                    double playLen,  
                    int playTransition)
```

Set stream name, extension, query string, play start, play len and play reset from play command.

**Parameters:**

name - stream name

oldName - old stream name

ext - stream extension

queryStr - query string

playStart - play start

playLen - play len

playTransition - play transition (see MediaBase.PLAYTRANSITION\_\*)

(continued from last page)

## switchName

```
public void switchName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Switch to stream name

### Parameters:

name - stream name  
oldName - old stream name  
ext - stream extension  
queryStr - query string  
playStart - play start  
playLen - play len  
playTransition - play transition (see MediaBase.PLAYTRANSITION\_\*)

---

## stopName

```
public void stopName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Stop stream name

### Parameters:

name - stream name  
oldName - old stream name  
ext - stream extension  
queryStr - query string  
playStart - play start  
playLen - play len  
playTransition - play transition (see MediaBase.PLAYTRANSITION\_\*)

---

## shutdown

```
public void shutdown()
```

shutdown or close this mediaStream

---

## getAudioTC

```
public long getAudioTC()
```

Get last absolute audio timecode (milliseconds) sent to mediaStream

### Returns:

last absolute audio timecode (milliseconds)

(continued from last page)

## setAudioTC

```
public void setAudioTC(long audioTC,  
    boolean isAbsolute)
```

Set last absolute audio timecode (milliseconds) sent to mediaStream

**Parameters:**

audioTC - timecode (milliseconds)

isAbsolute - is the timecode value relative to last timecode or absolute

---

## setAudioTC

```
public void setAudioTC(long audioTC)
```

Set last absolute audio timecode (milliseconds) sent to mediaStream

**Parameters:**

audioTC - timecode (milliseconds)

---

## getVideoTC

```
public long getVideoTC( )
```

Get last absolute video timecode (milliseconds) sent to mediaStream

**Returns:**

last absolute video timecode (milliseconds)

---

## setVideoTC

```
public void setVideoTC(long videoTC,  
    boolean isAbsolute)
```

Set last absolute video timecode (milliseconds) sent to mediaStream

**Parameters:**

videoTC - timecode (milliseconds)

isAbsolute - is the timecode value relative to last timecode or absolute

---

## setVideoTC

```
public void setVideoTC(long videoTC)
```

Set last absolute video timecode (milliseconds) sent to mediaStream

**Parameters:**

videoTC - timecode (milliseconds)

---

## getDataTC

```
public long getDataTC( )
```

Get last absolute data timecode (milliseconds) sent to mediaStream

**Returns:**

last absolute data timecode (milliseconds)

(continued from last page)

---

## setDataTC

```
public void setDataTC(long dataTC,  
    boolean isAbsolute)
```

Set last absolute data timecode (milliseconds) sent to mediaStream

### Parameters:

dataTC - timecode (milliseconds)

isAbsolute - is the timecode value relative to last timecode or absolute

---

## getDataType

```
public int getDataType()
```

Get the data packet type: (IVHost.CONTENTTYPE\_DATA0 or IVHost.CONTENTTYPE\_DATA3)

### Returns:

data packet type

---

## setDataType

```
public void setDataType(int dataType)
```

Set the data packet type: (IVHost.CONTENTTYPE\_DATA0 or IVHost.CONTENTTYPE\_DATA3)

### Parameters:

dataType - data packet type

---

## setDataTC

```
public void setDataTC(long dataTC)
```

Set last absolute data timecode (milliseconds) sent to mediaStream

### Parameters:

dataTC - timecode (milliseconds)

---

## isRecord

```
public boolean isRecord()
```

Is this stream being recorded to a file

### Returns:

is stream being recorded

---

## setRecord

```
public void setRecord(boolean isRecord)
```

Set is the stream being recorded

### Parameters:

isRecord

---

(continued from last page)

## isPlay

```
public boolean isPlay()
```

Is the stream a play stream (vs a publish stream)

**Returns:**

is play stream (has nothing to do with if its playing just that its play vs publish)

---

## setPlay

```
public void setPlay(boolean isPlay)
```

Set is the stream a play stream (vs a publish stream)

**Parameters:**

isPlay - is play stream (has nothing to do with if its playing just that its play vs publish)

---

## idle

```
public boolean idle()
```

Allow the mediaStream to perform idle work (not currently in use)

**Returns:**

true if it did some work

---

## getClientId

```
public int getClientId()
```

Get parent client connection (id)

**Returns:**

parent client connection (id)

---

## getClient

```
public IClient getClient()
```

Get parent client connection

**Returns:**

parent client connection

---

## getNetConnection

```
public com.wowza.wms.netconnection.INetConnection getNetConnection()
```

Get parent netConnection (future server to server communication)

**Returns:**

parent netConnection connection

---

## setNetConnection

```
public void setNetConnection(com.wowza.wms.netconnection.INetConnection netConnection)
```

(continued from last page)

Set parent netConnection (future server to server communication)

**Parameters:**

netConnection - netConnection connection

---

## setClient

```
public void setClient(IClient client)
```

Set parent client connection

**Parameters:**

client - parent client connection

---

## getStreams

```
public MediaStreamMap getStreams()
```

Get parent mediaStreamMap (owned by applicationInstance)

**Returns:**

parent mediaStreamMap

---

## packetComplete

```
public void packetComplete()
```

Invoked by requestAdapter when at the end of a set of packets

---

## sendStreamNotFound

```
public int sendStreamNotFound(String name)
```

Send onStatus(NetStream.Play.StreamNotFound) event

**Parameters:**

name - stream name

**Returns:**

bytes sent to client

---

## sendStreamNotFound

```
public int sendStreamNotFound(java.io.OutputStream out,  
    String name)
```

Send onStatus(NetStream.Play.StreamNotFound) event. Send directly to OutputStream.

**Parameters:**

out - OutputStream

name - stream name

**Returns:**

bytes sent to client

---



(continued from last page)

## sendLivePlayStart

```
public int sendLivePlayStart( java.io.OutputStream out,  
    String name,  
    long timecode,  
    long timecodeOffset)
```

Send onStatus(NetStream.Play.Start) event

### Parameters:

out - OutputStream  
name - stream name  
timecode - timecode  
timecodeOffset - timecode offset

### Returns:

bytes sent to client

---

## sendVODPlaySwitch

```
public int sendVODPlaySwitch( java.io.OutputStream out,  
    String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Transition) event

### Parameters:

out - OutputStream  
name - stream name  
timecode - timecode

### Returns:

bytes sent to client

---

## sendLivePlaySwitch

```
public int sendLivePlaySwitch( java.io.OutputStream out,  
    String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Transition) event

### Parameters:

out - OutputStream  
name - stream name  
timecode - timecode

### Returns:

bytes sent to client

---

## sendLivePlaySeek

```
public int sendLivePlaySeek( java.io.OutputStream out,  
    String name,  
    long timecode)
```

Send onStatus(NetStream.Seek.Notify) event

### Parameters:

out - OutputStream

(continued from last page)

name - stream name  
timecode - timecode

**Returns:**

bytes sent to client

---

**sendPlayReset**

```
public int sendPlayReset(String name)
```

Send onStatus(NetStream.Play.Reset) event

**Parameters:**

name - stream name

**Returns:**

bytes sent to client

---

**sendPlayReset**

```
public int sendPlayReset(java.io.OutputStream out,  
    String name)
```

Send onStatus(NetStream.Play.Reset) event. Send directly to OutputStream.

**Parameters:**

out - OutputStream  
name - stream name

**Returns:**

bytes sent to client

---

**sendPlayStop**

```
public int sendPlayStop(long location,  
    String name)
```

Send onStatus(NetStream.Play.Stop) event

**Parameters:**

location - timecode where play stopped  
name - stream name

**Returns:**

bytes sent to client

---

**sendPlayStop**

```
public int sendPlayStop(java.io.OutputStream out,  
    long location,  
    String name)
```

Send onStatus(NetStream.Play.Stop) event. Send directly to OutputStream

**Parameters:**

out - OutputStream  
location - timecode where play stopped  
name - stream name

(continued from last page)

**Returns:**

bytes sent to client

---

**sendPlaySeek**

```
public int sendPlaySeek(java.io.OutputStream out,  
    long location,  
    long seekLocation,  
    String name,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Seek.Notify) event.

**Parameters:**

out - OutputStream  
location - request location of seek  
seekLocation - result location of seek  
name - stream name  
seekTypes - list of commands to respond to (seek, unpause, play)

**Returns:**

bytes sent to client

---

**sendPlaySeek**

```
public int sendPlaySeek(long location,  
    long seekLocation,  
    String name)
```

Send onStatus(NetStream.Seek.Notify) event.

**Parameters:**

location - request location of seek  
seekLocation - result location of seek  
name - stream name

**Returns:**

bytes sent to client

---

**sendPlaySeek**

```
public int sendPlaySeek(java.io.OutputStream out,  
    long location,  
    long seekLocation,  
    String name)
```

Send onStatus(NetStream.Seek.Notify) event. Send directly to OutputStream

**Parameters:**

out - OutputStream  
location - request location of seek  
seekLocation - result location of seek  
name - stream name

**Returns:**

bytes sent to client

(continued from last page)

## sendPlayStart

```
public int sendPlayStart(String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Start) event

**Parameters:**

name - stream name

**Returns:**

bytes sent to client

---

## sendPlaySwitch

```
public int sendPlaySwitch(String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).

**Parameters:**

name - stream name

timecode - timecode of event

**Returns:**

bytes sent to client

---

## sendPlaySwitch

```
public int sendPlaySwitch(java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    long timecode)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

**Parameters:**

out - OutputStream

name - stream name

isSwitch - is this a switch or a start

timecode - timecode of event

**Returns:**

bytes sent to client

---

## sendPlayStart

```
public int sendPlayStart(java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    boolean isLive,  
    long timecode,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

**Parameters:**

out - OutputStream

(continued from last page)

name - stream name  
isSwitch - is this a switch or a start  
isLive - is the stream live  
timecode - timecode of event  
seekTypes - commands to respond to (seek, unpause, play)

---

## sendPlayStart

```
public int sendPlayStart( java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    long timecode,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

### Parameters:

out - OutputStream  
name - stream name  
isSwitch - is this a switch or a start  
timecode - timecode of event  
seekTypes - commands to respond to (seek, unpause, play)

### Returns:

bytes sent to client

---

## sendPlayStart

```
public int sendPlayStart( java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    long timecode)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

### Parameters:

out - OutputStream  
name - stream name  
isSwitch - is this a switch or a start  
timecode - timecode of event

### Returns:

bytes sent to client

---

## sendPlayStatus

```
public int sendPlayStatus(long timecode,  
    int statusType,  
    double duration,  
    double bytesSent)
```

Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event

### Parameters:

timecode - timecode of event  
statusType - status type IMediaStreamPlay.PLAYSTATUSTYPE\_\*  
duration - (not used)  
bytesSent - (not used)

(continued from last page)

**Returns:**

bytes sent to client

---

**sendPlayStatus**

```
public int sendPlayStatus(java.io.OutputStream out,  
    long timecode,  
    int statusType,  
    double duration,  
    double bytesSent)
```

Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event. Send directly to OutputStream.

**Parameters:**

out - OutputStream  
timecode - timecode of event  
statusType - status type IMediaStreamPlay.PLAYSTATUSTYPE\_\*  
duration - (not used)  
bytesSent - (not used)

**Returns:**

bytes sent to client

---

**sendPauseNotify**

```
public int sendPauseNotify(long timecode,  
    String name)
```

Send onStatus(NetStream.Pause.Notify) event

**Parameters:**

timecode - timecode of event  
name - stream name

**Returns:**

bytes sent to client

---

**sendPauseNotify**

```
public int sendPauseNotify(java.io.OutputStream out,  
    long timecode,  
    String name)
```

Send onStatus(NetStream.Pause.Notify) event. Send directly to OutputStream.

**Parameters:**

out - OutputStream  
timecode - timecode of event  
name - stream name

**Returns:**

bytes sent to client

---

**sendUnpauseNotify**

```
public int sendUnpauseNotify(java.io.OutputStream out,  
    long location,  
    String name,  
    java.util.List seekTypes)
```

(continued from last page)

Send onStatus(NetStream.Unpause.Notify) event

**Parameters:**

out - OutputStream  
location - timecode of event  
name - stream name  
seekTypes - list of operations to respond to (seek, play, unpause)

**Returns:**

bytes sent to client

---

## sendUnpauseNotify

```
public int sendUnpauseNotify(long location,  
    String name)
```

Send onStatus(NetStream.Unpause.Notify) event

**Parameters:**

location - timecode of event  
name - stream name

**Returns:**

bytes sent to client

---

## sendUnpauseNotify

```
public int sendUnpauseNotify(java.io.OutputStream out,  
    long location,  
    String name)
```

Send onStatus(NetStream.Unpause.Notify) event. Send directly to OutputStream.

**Parameters:**

out - OutputStream  
location - timecode of event  
name - stream name

**Returns:**

bytes sent to client

---

## isAppend

```
public boolean isAppend()
```

Is append to media file (only valid if isRecord)

**Returns:**

is appending or rewriting media file

---

## setAppend

```
public void setAppend(boolean isAppend)
```

Set is append to media file (only valid if isRecord)

**Parameters:**

isAppend - is appending or rewriting media file

## setPlayer

```
public void setPlayer(IMediaStreamPlay player)
```

Set underlying player (IMediaStreamPlay) object

**Parameters:**

player - underlying player (IMediaStreamPlay) object

---

## getPlayer

```
public IMediaStreamPlay getPlayer()
```

Get underlying player (IMediaStreamPlay) object

**Returns:**

underlying player (IMediaStreamPlay) object

---

## getAudioMissing

```
public int getAudioMissing()
```

Get number of audio bytes missing from current audio packet

**Returns:**

number of bytes missing

---

## getVideoMissing

```
public int getVideoMissing()
```

Get number of video bytes missing from current audio packet

**Returns:**

number of bytes missing

---

## getDataMissing

```
public int getDataMissing()
```

Get number of data bytes missing from current audio packet

**Returns:**

number of bytes missing

---

## addVideoData

```
public void addVideoData(byte[] data,  
    int offset,  
    int size)
```

Add data to current video packet

**Parameters:**

data - byte array

offset - offset in byte array

size - size of data to add

---



## addAudioData

```
public void addAudioData(byte[] data,  
    int offset,  
    int size)
```

Add data to current audio packet

### Parameters:

data - byte array  
offset - offset in byte array  
size - size of data to add

---

## addDataData

```
public void addDataData(byte[] data,  
    int offset,  
    int size)
```

Add data to current data packet

### Parameters:

data - byte array  
offset - offset in byte array  
size - size of data to add

---

## getProperties

```
public WMSProperties getProperties()
```

Get mediaStream properties

### Returns:

properties

---

## getPlayPackets

```
public java.util.List getPlayPackets()
```

Get all available live packets

### Returns:

play packets

---

## getMaxTimecode

```
public long getMaxTimecode()
```

Get the timecode of the latest received packet

### Returns:

timecode of the latest received packet

---

## getLastKeyFrame

```
public AMFPacket getLastKeyFrame()
```

Get most recent video key frame

---

(continued from last page)

**Returns:**

play packets

---

**getLastPacket**

```
public AMFPacket getLastPacket()
```

Get most recent live packet

**Returns:**

most recent live packet or null or no live packets

---

**getStreamType**

```
public String getStreamType()
```

Get mediaStream streamType

**Returns:**

streamType

---

**setStreamType**

```
public void setStreamType(String streamType)
```

Set mediaStream streamType. This method will not change the type of the current stream.

**Parameters:**

streamType

---

**sendDirectAMF3**

```
public void sendDirectAMF3(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler and send event to underlying stream (will record event). Force AMF3 encoding.

**Parameters:**

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

---

**sendDirect**

```
public void sendDirect(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler and send event to underlying stream (will record event)

**Parameters:**

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

---

**sendDirectAMF3**

```
public void sendDirectAMF3(String handlerName)
```

Call client side NetStream method/handler and send event to underlying stream (will record event). Force AMF3 encoding.

(continued from last page)

**Parameters:**

handlerName - handler name

---

**sendDirect**

```
public void sendDirect(String handlerName)
```

Call client side NetStream method/handler and send event to underlying stream (will record event)

**Parameters:**

handlerName - handler name

---

**sendAMF3**

```
public void sendAMF3(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler. Force AMF3 encoding.

**Parameters:**

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

---

**send**

```
public void send(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler

**Parameters:**

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

---

**sendAMF3**

```
public void sendAMF3(String handlerName)
```

Call client side NetStream method/handler with no parameters. Force AMF3 encoding.

**Parameters:**

handlerName - handler name

---

**send**

```
public void send(String handlerName)
```

Call client side NetStream method/handler with no parameters

**Parameters:**

handlerName - handler name

---

**close**

```
public void close()
```

Close mediaStream

(continued from last page)

## isOpen

```
public boolean isOpen()
```

Is mediaStream open

**Returns:**

is mediaStream open

---

## setOpen

```
public void setOpen(boolean isOpen)
```

Set mediaStream open

**Parameters:**

isOpen - mediaStream open

---

## getFastPlaySettings

```
public FastPlaySettings getFastPlaySettings()
```

Get current fastPlay settings

**Returns:**

fastPlay settings

---

## setFastPlaySettings

```
public void setFastPlaySettings(FastPlaySettings fastPlaySettings)
```

Set fastPlay settings

**Parameters:**

fastPlaySettings - fastPlay settings

---

## clearFastPlaySettings

```
public void clearFastPlaySettings()
```

Clear fastPlay settings

---

## isReceiveAudio

```
public boolean isReceiveAudio()
```

Is client currently receiving audio. Controlled by client side call receiveAudio.

**Returns:**

receive audio

---

## setReceiveAudio

```
public void setReceiveAudio(boolean receiveAudio)
```

Set receive audio

**Parameters:**

(continued from last page)

---

`receiveAudio` - receive audio

---

## `isReceiveVideo`

```
public boolean isReceiveVideo()
```

Is client currently receiving video. Controlled by client side call `receiveVideo`

**Returns:**

receive video

---

## `setReceiveVideo`

```
public void setReceiveVideo(boolean receiveVideo)
```

Set receive video

**Parameters:**

`receiveVideo` - receive video

---

## `getReceiveVideoFPS`

```
public int getReceiveVideoFPS()
```

Set frame per seconds for video (not currently implemented)

**Returns:**

video frames per second

---

## `setReceiveVideoFPS`

```
public void setReceiveVideoFPS(int receiveVideoFPS)
```

Set frame per second for video (not currently implemented)

**Parameters:**

`receiveVideoFPS` - video frames per second

---

## `getMediaIOPerformance`

```
public IOPerformanceCounter getMediaIOPerformance()
```

Get IO performance counter

**Returns:**

IO performance counter

---

## `incrementMediaOutBytes`

```
public long incrementMediaOutBytes(long bytes,  
    long count)
```

Increment the number of mediaStream bytes sent and number of packets sent

**Parameters:**

`bytes` - number of bytes sent  
`count` - number of packets sent

**Returns:**

(continued from last page)

total number of bytes sent (after increment)

---

## incrementMediaLossBytes

```
public long incrementMediaLossBytes(long bytes,  
                                     long count)
```

Increment the number of mediaStream loss bytes sent and number of packets sent

### Parameters:

bytes - number of bytes sent  
count - number of packets sent

### Returns:

total number of bytes sent (after increment)

---

## incrementMediaInBytes

```
public long incrementMediaInBytes(long increment)
```

Increment the number of mediaStream bytes received

### Parameters:

increment - number of byte received

### Returns:

total number of bytes received (after increment)

---

## publish

```
public void publish()
```

Publish mediaStream

---

## trim

```
public void trim()
```

Trim mediaStream. This method will remove live packets that are older than the live buffer size.

---

## handleCallback

```
public void handleCallback(com.wowza.wms.request.RequestFunction function)
```

Routes request function to callback handler onStatus, onPlayStatus or [method/handler]

### Parameters:

function - request function

---

## unregisterCallback

```
public void unregisterCallback(String handlerName)
```

Unregister a callback handler

### Parameters:

handlerName - handler name

## registerCallback

```
public void registerCallback(String handlerName,  
    IMediaStreamCallback callback)
```

Register a callback handler

### Parameters:

handlerName - handler name  
callback - callback object

---

## unregisterOnStatus

```
public void unregisterOnStatus(IMediaStreamCallback callback)
```

Unregister onStatus handler

### Parameters:

callback

---

## registerOnStatus

```
public void registerOnStatus(IMediaStreamCallback callback)
```

Register onStatus handler

### Parameters:

callback - callback object

---

## unregisterOnPlayStatus

```
public void unregisterOnPlayStatus(IMediaStreamCallback callback)
```

Unregister onPlayStatus handler

### Parameters:

callback - callback object

---

## registerOnPlayStatus

```
public void registerOnPlayStatus(IMediaStreamCallback callback)
```

Register onPlayStatus handler

### Parameters:

callback - callback object

---

## addClientListener

```
public void addClientListener(IMediaStreamActionNotify actionListener)
```

Add client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

### Parameters:

actionListener - listener

---

(continued from last page)

---

## addClientListener

```
public void addClientListener(IMediaStreamActionNotify2 actionListener)
```

Add client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

**Parameters:**

actionListener - listener

---

## addClientListener

```
public void addClientListener(IMediaStreamActionNotify3 actionListener)
```

Add client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

**Parameters:**

actionListener - listener

---

## removeClientListener

```
public void removeClientListener(IMediaStreamActionNotify actionListener)
```

Remove client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

**Parameters:**

actionListener - listener

---

## removeClientListener

```
public void removeClientListener(IMediaStreamActionNotify2 actionListener)
```

Remove client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

**Parameters:**

actionListener - listener

---

## removeClientListener

```
public void removeClientListener(IMediaStreamActionNotify3 actionListener)
```

Remove client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

**Parameters:**

actionListener - listener

---

## notifyActionPlay

```
public void notifyActionPlay(String streamName,  
    double playStart,  
    double playLen,  
    int playReset)
```

Notify client listeners of play action

**Parameters:**

streamName - stream name

playStart - play start

playLen - play length

playReset - play reset

---



## notifyActionPauseRaw

```
public void notifyActionPauseRaw(boolean isPause,  
    long location)
```

Notify client listeners of pauseRaw action

### Parameters:

isPause - is pause or unpause  
location - timecode (milliseconds) of action

---

## notifyActionPause

```
public void notifyActionPause(boolean isPause,  
    long location)
```

Notify client listeners of pause action

### Parameters:

isPause - is pause or unpause  
location - timecode (milliseconds) of action

---

## notifyActionSeek

```
public void notifyActionSeek(double location)
```

Notify client listeners of seek action

### Parameters:

location - timecode (milliseconds) of seek request

---

## notifyActionPublish

```
public void notifyActionPublish(String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Notify client listeners of publish action

### Parameters:

streamName - stream name  
isRecord - is record or live  
isAppend - is append if isRecord is true

---

## notifyActionUnPublish

```
public void notifyActionUnPublish(String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Notify client listeners of unpublish action

### Parameters:

streamName - stream name  
isRecord - is record or live  
isAppend - is append if isRecord is true

---

(continued from last page)

## notifyActionOnMetaData

```
public void notifyActionOnMetaData(AMFPacket metaDataPacket)
```

Notify client listeners of onMetaData change

**Parameters:**

metaDataPacket - metaDataPacket

---

## notifyActionOnCodecInfoVideo

```
public void notifyActionOnCodecInfoVideo(com.wowza.wms.media.model.MediaCodecInfoVideo  
codecInfoVideo)
```

Notify client listeners of video codec information change

**Parameters:**

codecInfoVideo - video codec information

---

## notifyActionOnCodecInfoAudio

```
public void notifyActionOnCodecInfoAudio(com.wowza.wms.media.model.MediaCodecInfoAudio  
codecInfoAudio)
```

Notify client listeners of audio codec information change

**Parameters:**

codecInfoAudio - audio codec information

---

## notifyActionStop

```
public void notifyActionStop()
```

Notify client listeners of stop action

---

## isClustered

```
public boolean isClustered()
```

not used

**Returns:**

isClustered

---

## setClustered

```
public void setClustered(boolean isClustered)
```

not used

**Parameters:**

isClustered

---

## getCacheName

```
public String getCacheName()
```

not used

(continued from last page)

**Returns:**

cache name

---

**startPublishing**

```
public void startPublishing()
```

Start publishing live stream

---

**stopPublishing**

```
public void stopPublishing()
```

Stop publishing live stream

---

**getStreamFileForWrite**

```
public java.io.File getStreamFileForWrite()
```

Get the File object to write to a stream (get stream name, ext and query from stream object)

**Returns:**

resultant File object

---

**getStreamFileForWrite**

```
public java.io.File getStreamFileForWrite(String name,  
                                           String ext,  
                                           String query)
```

Get the File object to write to a stream (specify name, ext and query)

**Parameters:**

name - stream name

ext - stream prefix (Ex. mp4:)

query - query part of stream name (Ex. mystream?param1=value1)

**Returns:**

resultant File object

---

**getStreamFileForRead**

```
public java.io.File getStreamFileForRead()
```

Get the File object to read from a stream (get stream name, ext and query from stream object)

**Returns:**

resultant File object

---

**getStreamFileForRead**

```
public java.io.File getStreamFileForRead(String name,  
                                           String ext,  
                                           String query)
```

Get the File object to read from a stream (specify name, ext and query)

**Parameters:**

name - stream name

(continued from last page)

ext - stream prefix (Ex. mp4:)

query - query part of stream name (Ex. mystream?param1=value1)

**Returns:**

resultant File object

---

## sendControlBytes

```
public int sendControlBytes(int controlType,  
    java.io.OutputStream out)
```

Send playback control bytes. Valid values are (0, 1, 4)

**Parameters:**

controlType - control types (0, 1, 4)

out - OutputStream

**Returns:**

bytes sent to client

---

## getBurstStartStop

```
public byte[] getBurstStartStop(boolean isStart)
```

Get the dynamic streaming burst start/stop AMF packet

**Parameters:**

isStart - is start

**Returns:**

byte array with AMF packet

---

## getRespAMFAudioObj

```
public AMFObj getRespAMFAudioObj()
```

Get audio response channel object

**Returns:**

audio response channel object

---

## getRespAMFVideoObj

```
public AMFObj getRespAMFVideoObj()
```

Get video response channel object

**Returns:**

video response channel object

---

## getRespAMFDataObj

```
public AMFObj getRespAMFDataObj()
```

Get data response channel object

**Returns:**

data response channel object

## getQueryStr

```
public String getQueryStr()
```

Get play/publish name query string. Example: if play name is flv:test?param1=data1&param2=data2, query string is "param1=data1&param2=data2".

**Returns:**

query string

---

## setQueryStr

```
public void setQueryStr(String queryStr)
```

Set play/publish name query string. Example: if play name is flv:test?param1=data1&param2=data2, query string is "param1=data1&param2=data2".

**Parameters:**

queryStr

---

## updateLoggingDuration

```
public void updateLoggingDuration()
```

Update logging.MDC with mediaStream logging information

---

## updateLoggingValues

```
public void updateLoggingValues()
```

Update logging.MDC with mediaStream logging information

---

## clearLoggingValues

```
public void clearLoggingValues()
```

---

## length

```
public double length()
```

Get length/duration (seconds) of media file pointed to by mediaStream

**Returns:**

length (seconds)

---

## size

```
public long size()
```

Get size (bytes) of media file pointed to by mediaStream

**Returns:**

size (bytes)

---

(continued from last page)

## getExt

```
public String getExt()
```

Get media file extension

**Returns:**

media file extension

---

## setExt

```
public void setExt(String ext)
```

Set media file extension

**Parameters:**

ext

---

## clear

```
public void clear()
```

Delete media file pointed to by this mediaStream (be careful)

---

## isSendPlayStopLogEvent

```
public boolean isSendPlayStopLogEvent()
```

Get need to send a log event for stop

**Returns:**

need to send a log event for stop

---

## setSendPlayStopLogEvent

```
public void setSendPlayStopLogEvent(boolean sendPlayStopLogEvent)
```

Set need to send a log event for stop

**Parameters:**

sendPlayStopLogEvent - need to send a log event for stop

---

## isSendRecordStopLogEvent

```
public boolean isSendRecordStopLogEvent()
```

Get need to send a log event for recording

**Returns:**

need to send a log event for stop

---

## setSendRecordStopLogEvent

```
public void setSendRecordStopLogEvent(boolean sendPlayStopLogEvent)
```

Set need to send a log event for recording

**Parameters:**

(continued from last page)

sendPlayStopLogEvent - need to send a log event for stop

---

## isSendPublishStopLogEvent

```
public boolean isSendPublishStopLogEvent()
```

Get need to send a log event for publishing

**Returns:**

need to send a log event for stop

---

## setSendPublishStopLogEvent

```
public void setSendPublishStopLogEvent(boolean sendPlayStopLogEvent)
```

Set need to send a log event for publishing

**Parameters:**

sendPlayStopLogEvent - need to send a log event for stop

---

## getAccess

```
public boolean[] getAccess(IClient client,  
    String name)
```

Get the read/write access to this stream for this client

**Parameters:**

client - client

name - stream name

**Returns:**

array of booleans read[0], write[1]

---

## getMetaDataProvider

```
public IMediaStreamMetaDataProvider getMetaDataProvider()
```

Get the metaData provider

**Returns:**

metaData provider

---

## setMetaDataProvider

```
public void setMetaDataProvider(IMediaStreamMetaDataProvider metaDataProvider)
```

Set the metaData provider

**Parameters:**

metaDataProvider - metaData provider

---

## getHeaderSize

```
public int getHeaderSize()
```

Get the last packet header size (debugging)

**Returns:**

(continued from last page)

last packet header size

---

## setHeaderSize

```
public void setHeaderSize(int headerSize)
```

Set the last packet header size (debugging)

**Parameters:**

headerSize - last packet header size

---

## getAudioCodecConfigPacket

```
public AMFPacket getAudioCodecConfigPacket(long timecode)
```

Get audio codec configuration packet (needed for H.264/AAC playback)

**Parameters:**

timecode - timecode of the packet to which you want to get the codec config information

**Returns:**

audio codec configuration packet (needed for H.264/AAC playback)

---

## addAudioCodecConfigPacket

```
public void addAudioCodecConfigPacket(long timecode,  
    AMFPacket packet)
```

Set audio codec configuration packet (needed for H.264/AAC playback)

**Parameters:**

timecode - timecode in milliseconds of first packet that uses this timecode

packet - audio codec configuration packet (needed for H.264/AAC playback)

---

## getVideoCodecConfigPacket

```
public AMFPacket getVideoCodecConfigPacket(long timecode)
```

Get video codec configuration packet (needed for H.264/AAC playback)

**Parameters:**

timecode - timecode of the packet to which you want to get the codec config information

**Returns:**

video codec configuration packet (needed for H.264/AAC playback)

---

## addVideoCodecConfigPacket

```
public void addVideoCodecConfigPacket(long timecode,  
    AMFPacket packet)
```

Set video codec configuration packet (needed for H.264/AAC playback)

**Parameters:**

timecode - timecode in milliseconds of first packet that uses this timecode

packet - video codec configuration packet (needed for H.264/AAC playback)

---



(continued from last page)

---

## getRTPStream

```
public RTPStream getRTPStream( )
```

Get the RTP based stream this stream is associated with

**Returns:**

RTP based stream this stream is associated with

---

## setRTPStream

```
public void setRTPStream(RTPStream rtpStream)
```

Set the RTP based stream this stream is associated with

**Parameters:**

rtpStream - RTP based stream this stream is associated with

---

## flush

```
public void flush( )
```

Force publishing packets to be flushed from the input buffers to the output buffers

---

## startAudioPacket

```
public void startAudioPacket( )
```

Called when an audio packet is first being populated with data

---

## startVideoPacket

```
public void startVideoPacket( )
```

Called when a video packet is first being populated with data

---

## startDataPacket

```
public void startDataPacket( )
```

Called when a data packet is first being populated with data

---

## getLiveStreamPacketizerList

```
public String getLiveStreamPacketizerList( )
```

Get the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)

**Returns:**

comma separated list of LiveStreamPacketizers names

---

## setLiveStreamPacketizerList

```
public void setLiveStreamPacketizerList(String liveStreamPacketizerList)
```

Set the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)

**Parameters:**

(continued from last page)

liveStreamPacketizerList - comma separated list of LiveStreamPacketizers names

---

## getLiveStreamTranscoderList

```
public String getLiveStreamTranscoderList()
```

Get the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)

**Returns:**

comma separated list of LiveStreamTranscoders names

---

## setLiveStreamTranscoderList

```
public void setLiveStreamTranscoderList(String liveStreamTranscoderList)
```

Set the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)

**Parameters:**

liveStreamTranscoderList - comma separated list of LiveStreamTranscoders names

---

## getLiveStreamPacketizer

```
public ILiveStreamPacketizer getLiveStreamPacketizer(String name)
```

Get the LiveStreamPacketizer interface to a stream by name

**Parameters:**

name - LiveStreamPacketizer name

**Returns:**

LiveStreamPacketizer interface

---

## getDvrRecorderList

```
public String getDvrRecorderList()
```

Get the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)

**Returns:**

comma separated list of DVR Recorder names

---

## setDvrRecorderList

```
public void setDvrRecorderList(String recorderList)
```

Set the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)

**Parameters:**

recorderList - comma separated list of DVR Recorder names

---

## getDvrRecorder

```
public ILiveStreamDvrRecorder getDvrRecorder(String name)
```

Get the DVR Recorder interface to a stream by name

**Parameters:**

(continued from last page)

name - DVR Recorder name

**Returns:**

DVR Recorder interface

---

## getUniqueStreamIdStr

```
public String getUniqueStreamIdStr()
```

Get a string that uniquely identifies this stream

**Returns:**

unique stream identifier

---

## getHTTPStreamerSession

```
public IHTTPStreamerSession getHTTPStreamerSession()
```

Get the HTTPStreamer session associated with this stream

**Returns:**

HTTPStreamer session associated with this stream

---

## setHTTPStreamerSession

```
public void setHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Set the HTTPStreamer session associated with this stream

**Parameters:**

httpStreamerSession - HTTPStreamer session associated with this stream

---

## getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get the interface to the elapse timer

**Returns:**

interface to the elapse timer

---

## getLiveStreamPacketizer

```
public String getLiveStreamPacketizer()
```

Get the live stream packetizer that this stream is using

**Returns:**

live stream packetizer

---

## setLiveStreamPacketizer

```
public void setLiveStreamPacketizer(String liveStreamPacketizer)
```

Set the live stream packetizer that this stream is using

**Parameters:**

liveStreamPacketizer - live stream packetizer

## getLiveStreamRepeater

```
public String getLiveStreamRepeater()
```

Get the live stream repeater name for the stream

**Returns:**

live stream repeater name

---

## setLiveStreamRepeater

```
public void setLiveStreamRepeater(String liveStreamRepeater)
```

Set the live stream repeater name for the stream

**Parameters:**

liveStreamRepeater - live stream repeater name

---

## initLiveStreamRepeating

```
public void initLiveStreamRepeating(String liveStreamPacketizer,  
    String liveStreamRepeater)
```

Initialize this stream for live stream repeating

**Parameters:**

liveStreamPacketizer - live stream packetizer

liveStreamRepeater - live stream repeater name

---

## getPublishVideoCodecId

```
public int getPublishVideoCodecId()
```

Get the codec id of the most recently published video packet

**Returns:**

codec id of the most recently published video packet

---

## setPublishVideoCodecId

```
public void setPublishVideoCodecId(int publishVideoCodecId)
```

Set the codec id of the most recently published video packet

**Parameters:**

publishVideoCodecId - codec id of the most recently published video packet

---

## getPublishAudioCodecId

```
public int getPublishAudioCodecId()
```

Get the codec id of the most recently published audio packet

**Returns:**

codec id of the most recently published audio packet

---

(continued from last page)

## setPublishAudioCodecId

```
public void setPublishAudioCodecId(int publishAudioCodecId)
```

Set the codec id of the most recently published audio packet

**Parameters:**

publishAudioCodecId - codec id of the most recently published audio packet

---

## isPublishStreamReady

```
public boolean isPublishStreamReady(boolean checkAudio,  
    boolean checkVideo)
```

Returns true if the publishing stream contains enough video/audio data to start playback

**Parameters:**

checkAudio - check audio stream

checkVideo - check video stream

**Returns:**

true if the publishing stream contains enough video/audio data to start playback

---

## getContextStr

```
public String getContextStr()
```

Returns the stream context string in the form [application]/[appInstance]/[streamName].

**Returns:**

stream context string

---

## isMediaCasterPlay

```
public boolean isMediaCasterPlay()
```

Is MediaCaster play enabled (if true, will trigger MediaCaster startup)

**Returns:**

true if MediaCaster play enabled

---

## setMediaCasterPlay

```
public void setMediaCasterPlay(boolean isMediaCasterPlay)
```

Is MediaCaster play enabled (if true, will trigger MediaCaster startup)

**Parameters:**

isMediaCasterPlay - true if MediaCaster play enabled

---

## isMergeOnMetadata

```
public boolean isMergeOnMetadata()
```

If true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

**Returns:**

true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

---

## setMergeOnMetadata

```
public void setMergeOnMetadata(boolean mergeOnMetadata)
```

If true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

**Parameters:**

mergeOnMetadata - true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

---

## getDvrRecorder

```
public String getDvrRecorder()
```

Get the DVR Recorder for this stream

**Returns:**

DVR Recorder

---

## getDvrRepeater

```
public String getDvrRepeater()
```

Get the DVR repeater name for this stream

**Returns:**

repeater name

---

## setDvrRecorder

```
public void setDvrRecorder(String recorderName)
```

Set the DVR Recorder that this stream is using

**Parameters:**

recorderName - DVR Recorder

---

## removeDvrRecorder

```
public ILiveStreamDvrRecorder removeDvrRecorder(String name)
```

Remove a live stream dvr by name

**Parameters:**

name - dvr name

**Returns:**

live stream dvr

---

## putDvrRecorder

```
public void putDvrRecorder(String name,  
    ILiveStreamDvrRecorder dvr)
```

Add a live stream dvr to this stream

**Parameters:**

name - dvr name

dvr - live stream dvr

---

## getLiveStreamTranscoders

```
public java.util.Map getLiveStreamTranscoders()
```

Get the list of transcoders for this stream.

**Returns:**

list of transcoders for this stream

---

## getLiveStreamTranscoder

```
public ILiveStreamTranscoder getLiveStreamTranscoder(String name)
```

Get a live stream transcoder for this stream by name

**Parameters:**

name - transcoder name

**Returns:**

live stream transcoder

---

## removeLiveStreamTranscoder

```
public ILiveStreamTranscoder removeLiveStreamTranscoder(String name)
```

Remove a live stream transcoder by name

**Parameters:**

name - transcoder name

**Returns:**

live stream transcoder

---

## putLiveStreamTranscoder

```
public void putLiveStreamTranscoder(String name,  
    ILiveStreamTranscoder liveStreamTranscoder)
```

Add a live stream transcoder to this stream

**Parameters:**

name - transcoder name

liveStreamTranscoder - live stream transcoder

---

## isTranscodeResult

```
public boolean isTranscodeResult()
```

Is this stream the result of a transcode operation.

**Returns:**

true if stream the result of a transcode operation

---

## setTranscodeResult

```
public void setTranscodeResult(boolean isTranscodeResult)
```

Is this stream the result of a transcode operation.

---

(continued from last page)

**Parameters:**

isTranscodeResult - true if stream the result of a transcode operation

---

**addVideoH264SEIListener**

```
public void addVideoH264SEIListener(IMediaStreamH264SEINotify h264SEIListener)
```

Add an H.264 SEI listener. This listener will be notified of all incoming H.264 video packets and has the ability to read and/or modify SEI section of the video frame.

**Parameters:**

h264SEIListener - H.264 SEI listener

---

**removeVideoH264SEIListener**

```
public void removeVideoH264SEIListener(IMediaStreamH264SEINotify h264SEIListener)
```

Remove an H.264 SEI listener. This listener will be notified of all incoming H.264 video packets and has the ability to read and/or modify SEI section of the video frame.

**Parameters:**

h264SEIListener - H.264 SEI listener

---

**isVideoH264SEIListenerEmpty**

```
public boolean isVideoH264SEIListenerEmpty()
```

Is H.264 SEI listener list empty. This listener will be notified of all incoming H.264 video packets and has the ability to read and/or modify SEI section of the video frame.

**Returns:**

true if H.264 SEI listener list empty

---

**notifyVideoH264Packet**

```
public void notifyVideoH264Packet(AMFPacket packet,  
com.wowza.wms.media.h264.H264SEIMessages seiMessages)
```

Notify H.264 SEI listener.

**Parameters:**

packet - AMF Packet

seiMessages - seiMessages

---

**addCallbackListener**

```
public void addCallbackListener(IMediaStreamCallback callbackListener)
```

Add a callback listener to listen for all stream metadata

**Parameters:**

callbackListener

---

**removeCallbackListener**

```
public void removeCallbackListener(IMediaStreamCallback callbackListener)
```

Remove a callback listener to listen for all stream metadata



(continued from last page)

**Parameters:**

callbackListener

## com.wowza.wms.stream Interface IMediaStreamActionNotify

All Subinterfaces:

[IMediaStreamActionNotify2](#), [IMediaStreamActionNotify3](#)

All Known Implementing Classes:

[LiveStreamRecordActionNotifier](#)

public interface **IMediaStreamActionNotify**  
extends

IMediaStreamActionNotify: listener interface used by IMediaStream addClientListener

### Method Summary

void	<a href="#">onPause</a> ( <a href="#">IMediaStream</a> stream, boolean isPause, double location) Triggered on mediaStream pause
void	<a href="#">onPlay</a> ( <a href="#">IMediaStream</a> stream, String streamName, double playStart, double playLen, int playReset) Triggered on mediaStream play
void	<a href="#">onPublish</a> ( <a href="#">IMediaStream</a> stream, String streamName, boolean isRecord, boolean isAppend) Triggered on mediaStream publish
void	<a href="#">onSeek</a> ( <a href="#">IMediaStream</a> stream, double location) Triggered on mediaStream seek
void	<a href="#">onStop</a> ( <a href="#">IMediaStream</a> stream) Triggered on mediaStream stop
void	<a href="#">onUnPublish</a> ( <a href="#">IMediaStream</a> stream, String streamName, boolean isRecord, boolean isAppend) Triggered on mediaStream unpublish

### Methods

#### onPlay

```
public void onPlay(IMediaStream stream,  
    String streamName,  
    double playStart,  
    double playLen,  
    int playReset)
```

Triggered on mediaStream play

#### Parameters:

stream - mediaStream  
streamName - streamName  
playStart - playStart offset  
playLen - playLen

(continued from last page)

playReset - reset playlist

---

## onPublish

```
public void onPublish(IMediaStream stream,  
    String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Triggered on mediaStream publish

### Parameters:

stream - mediaStream  
streamName - streamName  
isRecord - recording stream  
isAppend - appending to file

---

## onUnPublish

```
public void onUnPublish(IMediaStream stream,  
    String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Triggered on mediaStream unpublish

### Parameters:

stream - mediaStream  
streamName - streamName  
isRecord - recording stream  
isAppend - appending to file

---

## onPause

```
public void onPause(IMediaStream stream,  
    boolean isPause,  
    double location)
```

Triggered on mediaStream pause

### Parameters:

stream - mediaStream  
isPause - pause or unpause  
location - location (milliseconds)

---

## onSeek

```
public void onSeek(IMediaStream stream,  
    double location)
```

Triggered on mediaStream seek

### Parameters:

stream - mediaStream  
location - location (milliseconds)

---

## onStop

```
public void onStop(IMediaStream stream)
```

(continued from last page)

Triggered on mediaStream stop

**Parameters:**

stream - mediaStream

## com.wowza.wms.stream Interface IMediaStreamActionNotify2

All Superinterfaces:

[IMediaStreamActionNotify](#)

All Subinterfaces:

[IMediaStreamActionNotify3](#)

public interface **IMediaStreamActionNotify2**  
extends [IMediaStreamActionNotify](#)

### Method Summary

void	<a href="#">onMetaData</a> ( <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> metaDataPacket) Triggered when a published streams metadata is set or changes
void	<a href="#">onPauseRaw</a> ( <a href="#">IMediaStream</a> stream, boolean isPause, double location) Triggered on mediaStream pauseRaw.

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify](#)

[onPause](#), [onPlay](#), [onPublish](#), [onSeek](#), [onStop](#), [onUnPublish](#)

### Methods

#### onMetaData

```
public void onMetaData(IMediaStream stream,  
    AMFPacket metaDataPacket)
```

Triggered when a published streams metadata is set or changes

#### onPauseRaw

```
public void onPauseRaw(IMediaStream stream,  
    boolean isPause,  
    double location)
```

Triggered on mediaStream pauseRaw. The pauseRaw method is called when a pause occurs in the player.

##### Parameters:

stream - mediaStream  
isPause - pause or unpause  
location - location (milliseconds)

## com.wowza.wms.stream Interface IMediaStreamActionNotify3

All Superinterfaces:

[IMediaStreamActionNotify2](#), [IMediaStreamActionNotify](#)

public interface **IMediaStreamActionNotify3**  
extends [IMediaStreamActionNotify2](#)

### Method Summary

void	<a href="#">onCodecInfoAudio</a> ( <a href="#">IMediaStream</a> stream, <a href="#">com.wowza.wms.media.model.MediaCodecInfoAudio</a> codecInfoAudio) Triggered when publishing stream receives codec information.
void	<a href="#">onCodecInfoVideo</a> ( <a href="#">IMediaStream</a> stream, <a href="#">com.wowza.wms.media.model.MediaCodecInfoVideo</a> codecInfoVideo) Triggered when publishing stream receives codec information.

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify2](#)

[onMetaData](#), [onPauseRaw](#)

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify](#)

[onPause](#), [onPlay](#), [onPublish](#), [onSeek](#), [onStop](#), [onUnPublish](#)

### Methods

#### onCodecInfoVideo

```
public void onCodecInfoVideo(IMediaStream stream,  
    com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
```

Triggered when publishing stream receives codec information.

**Parameters:**

stream - mediaStream  
codecInfoVideo - video codec information

#### onCodecInfoAudio

```
public void onCodecInfoAudio(IMediaStream stream,  
    com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
```

Triggered when publishing stream receives codec information.

**Parameters:**

stream - mediaStream  
codecInfoAudio - video codec information

com.wowza.wms.stream

# Interface IMediaStreamCallback

public interface **IMediaStreamCallback**  
extends

IMediaStreamCallback: callback interface used by IMediaStream registerCallback, registerOnStatus, registerOnPlayStatus

Method Summary	
void	<div><div>onCallback(<a href="#">IMediaStream</a> stream, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params)</div><div>Triggered on callback event</div></div>

## Methods

### onCallback

```
public void onCallback(IMediaStream stream,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Triggered on callback event

**Parameters:**

- stream - mediaStream
- function - function that triggered callback
- params - function parameters

## com.wowza.wms.stream Interface IMediaStreamFileMapper

public interface **IMediaStreamFileMapper**  
extends

Interface for mapping a IMediaStream to the underlying file system. Implement this interface and set your class using `IApplicationInstance.setStreamFileMapper(IMediaStreamFileMapper streamFileMapper)`. Your class will then be called each time a stream needs to be mapped to the underlying file system.

### Method Summary

java.io.File	<a href="#"><code>streamToFileForRead(IMediaStream stream)</code></a> Get the File object to read from a stream (get stream name, ext and query from stream object)
java.io.File	<a href="#"><code>streamToFileForRead(IMediaStream stream, String name, String ext, String query)</code></a> Get the File object to read from a stream (specify name, ext and query)
java.io.File	<a href="#"><code>streamToFileForWrite(IMediaStream stream)</code></a> Get the File object to write to a stream (get stream name, ext and query from stream object)
java.io.File	<a href="#"><code>streamToFileForWrite(IMediaStream stream, String name, String ext, String query)</code></a> Get the File object to write to a stream (specify name, ext and query)

### Methods

#### **streamToFileForRead**

```
public java.io.File streamToFileForRead(IMediaStream stream,  
    String name,  
    String ext,  
    String query)
```

Get the File object to read from a stream (specify name, ext and query)

**Parameters:**

stream - stream  
name - stream name  
ext - stream prefix (Ex. mp4:)  
query - query part of stream name (Ex. mystream?param1=value1)

**Returns:**

resultant File object

#### **streamToFileForRead**

```
public java.io.File streamToFileForRead(IMediaStream stream)
```

Get the File object to read from a stream (get stream name, ext and query from stream object)

**Parameters:**



---

(continued from last page)

stream - stream

**Returns:**

resultant File object

---

## streamToFileForWrite

```
public java.io.File streamToFileForWrite(IMediaStream stream,  
    String name,  
    String ext,  
    String query)
```

Get the File object to write to a stream (specify name, ext and query)

**Parameters:**

stream - stream

name - stream name

ext - stream prefix (Ex. mp4:)

query - query part of stream name (Ex. mystream?param1=value1)

**Returns:**

resultant File object

---

## streamToFileForWrite

```
public java.io.File streamToFileForWrite(IMediaStream stream)
```

Get the File object to write to a stream (get stream name, ext and query from stream object)

**Parameters:**

stream - stream

**Returns:**

resultant File object

com.wowza.wms.stream

Interface IMediaStreamH264SEINotify

public interface IMediaStreamH264SEINotify

extends

Method Summary	
void	<a href="#">onVideoH264Packet</a> ( <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> packet, <a href="#">com.wowza.wms.media.h264.H264SEIMessages</a> seiMessages)

Methods

onVideoH264Packet

public void **onVideoH264Packet**([IMediaStream](#) stream, [AMFPacket](#) packet, [com.wowza.wms.media.h264.H264SEIMessages](#) seiMessages)

## com.wowza.wms.stream Interface IMediaStreamMediaCaster

public interface **IMediaStreamMediaCaster**  
extends

IMediaStreamMediaCaster: Internal use

### Method Summary

<a href="#">IMediaCaster</a>	<a href="#">getMediaCaster()</a>
void	<a href="#">setMediaCasterItem(<a href="#">MediaCasterItem</a> mediaCasterItem)</a>

### Methods

#### setMediaCasterItem

public void **setMediaCasterItem**([MediaCasterItem](#) mediaCasterItem)

#### getMediaCaster

public [IMediaCaster](#) **getMediaCaster**()

---

**com.wowza.wms.stream****Interface IMediaStreamMetaDataProvider**

---

public interface **IMediaStreamMetaDataProvider**  
extends

IMediaStreamMetaDataProvider: Live streaming metadata provider.

---

## Method Summary

void	<a href="#"><code>onStreamStart</code></a> (java.util.List metaDataList, long timecode) Called to get the onMetadata data at a particular point in time in the stream
------	--

---

## Methods

### **onStreamStart**

```
public void onStreamStart(java.util.List metaDataList,  
    long timecode)
```

Called to get the onMetadata data at a particular point in time in the stream

**Parameters:**

metaDataList - list of onMetadata data (should always be one item in list)  
timecode - timecode in milliseconds

## com.wowza.wms.stream Interface IMediaStreamNameAliasProvider

All Subinterfaces:

[IMediaStreamNameAliasProvider2](#)

public interface **IMediaStreamNameAliasProvider**  
extends

IMediaStreamNameAliasProvider: alias provider interface. See [IAApplication.setStreamNameAliasProvider\(IMediaStreamNameAliasProvider streamNameAliasProvider\)](#). See updated interface [IMediaStreamNameAliasProvider2](#) which provides more complete context information.

### Method Summary

String	<a href="#">resolvePlayAlias</a> ( <a href="#">IAApplicationInstance</a> appInstance, String name) Called to resolve a play alias
String	<a href="#">resolveStreamAlias</a> ( <a href="#">IAApplicationInstance</a> appInstance, String name) Called to resolve a stream alias

### Methods

#### resolvePlayAlias

```
public String resolvePlayAlias(IAApplicationInstance appInstance,  
    String name)
```

Called to resolve a play alias

**Parameters:**

appInstance - applicationInstance  
name - stream name

**Returns:**

resultant name, null if want to block playback

#### resolveStreamAlias

```
public String resolveStreamAlias(IAApplicationInstance appInstance,  
    String name)
```

Called to resolve a stream alias

**Parameters:**

appInstance - applicationInstance  
name - stream name

**Returns:**

resultant name, null if want to block playback

## com.wowza.wms.stream Interface IMediaStreamNameAliasProvider2

All Superinterfaces:

[IMediaStreamNameAliasProvider](#)

public interface **IMediaStreamNameAliasProvider2**

extends [IMediaStreamNameAliasProvider](#)

IMediaStreamNameAliasProvider: alias provider interface. See

`IApplication.setStreamNameAliasProvider(IMediaStreamNameAliasProvider streamNameAliasProvider)`.

### Method Summary

String	<a href="#">resolvePlayAlias</a> ( <a href="#">IApplicationInstance</a> appInstance, String name, <a href="#">IClient</a> client) Resolve play alias for RTMP streaming
String	<a href="#">resolvePlayAlias</a> ( <a href="#">IApplicationInstance</a> appInstance, String name, <a href="#">IHTTPStreamerSession</a> httpSession) Resolve play alias for HTTP streaming.
String	<a href="#">resolvePlayAlias</a> ( <a href="#">IApplicationInstance</a> appInstance, String name, <a href="#">ILiveStreamPacketizer</a> liveStreamPacketizer) Resolve play alias for live stream packetizer
String	<a href="#">resolvePlayAlias</a> ( <a href="#">IApplicationInstance</a> appInstance, String name, <a href="#">RTPSession</a> rtpSession) Resolve play alias for RTSP/RTP streaming
String	<a href="#">resolveStreamAlias</a> ( <a href="#">IApplicationInstance</a> appInstance, String name, <a href="#">IMediaCaster</a> mediaCaster) Resolve stream alias for MediaCaster

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamNameAliasProvider](#)

[resolvePlayAlias](#), [resolveStreamAlias](#)

### Methods

#### resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    IClient client)
```

Resolve play alias for RTMP streaming

**Parameters:**

appInstance - application instance  
name - stream name  
client - client interface

**Returns:**

(continued from last page)

resultant name, null if want to block playback

---

## resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    IHTTPStreamerSession httpSession)
```

Resolve play alias for HTTP streaming. This callback may be called when there is not a valid HTTP session. In this case a phantom HTTP session will be created and will be populated with information from the underlying HTTP request (such as IP address and query string) but the session Id will be null.

### Parameters:

appInstance - application instance

name - name

httpSession - HTTP session

### Returns:

resultant name, null if want to block playback

---

## resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    RTPSession rtpSession)
```

Resolve play alias for RTSP/RTP streaming

### Parameters:

appInstance - application instance

name - name

rtpSession - RTP session

### Returns:

resultant name, null if want to block playback

---

## resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    ILiveStreamPacketizer liveStreamPacketizer)
```

Resolve play alias for live stream packetizer

### Parameters:

appInstance - application instance

name - name

liveStreamPacketizer - live stream packetizer

### Returns:

resultant name, null if want to block playback

---

## resolveStreamAlias

```
public String resolveStreamAlias(IApplicationInstance appInstance,  
    String name,  
    IMediaCaster mediaCaster)
```

Resolve stream alias for MediaCaster

(continued from last page)

**Parameters:**

appInstance - application instance  
name - name  
mediaCaster - media caster

**Returns:**

resultant name, null if want to block playback



## com.wowza.wms.stream Interface IMediaStreamNotify

public interface **IMediaStreamNotify**  
extends

IMediaStreamNotify: listener interface used by IApplicationInstance addMediaStreamListener

### Method Summary

void	<a href="#">onMediaStreamCreate</a> ( <a href="#">IMediaStream</a> stream) Triggered when mediaStream created
void	<a href="#">onMediaStreamDestroy</a> ( <a href="#">IMediaStream</a> stream) Triggered when mediaStream destroyed

### Methods

#### onMediaStreamCreate

public void **onMediaStreamCreate**([IMediaStream](#) stream)

Triggered when mediaStream created

**Parameters:**

stream - mediaStream

#### onMediaStreamDestroy

public void **onMediaStreamDestroy**([IMediaStream](#) stream)

Triggered when mediaStream destroyed

**Parameters:**

stream - mediaStream

## com.wowza.wms.stream Interface IMediaStreamPlay

public interface **IMediaStreamPlay**  
extends

IMediaStreamPlay: public interface of mediaPlayer object.

### Field Summary

public static final	<a href="#"><u>PAUSE_PAUSE</u></a> Pause type: pause Value: <b>1</b>
public static final	<a href="#"><u>PAUSE_PLAY</u></a> Pause type: play Value: <b>0</b>
public static final	<a href="#"><u>PAUSE_TOGGLE</u></a> Pause type: toggle Value: <b>-1</b>
public static final	<a href="#"><u>PLAYSIZES_AUDIO_BYTES</u></a> IMediaReader sizes array: audio byte count Value: <b>0</b>
public static final	<a href="#"><u>PLAYSIZES_AUDIO_COUNT</u></a> IMediaReader sizes array: audio packet count Value: <b>1</b>
public static final	<a href="#"><u>PLAYSIZES_DATA_BYTES</u></a> IMediaReader sizes array: data byte count Value: <b>4</b>
public static final	<a href="#"><u>PLAYSIZES_DATA_COUNT</u></a> IMediaReader sizes array: data packet count Value: <b>5</b>
public static final	<a href="#"><u>PLAYSIZES_LOSS_BYTES</u></a> IMediaReader sizes array: data byte count Value: <b>6</b>
public static final	<a href="#"><u>PLAYSIZES_LOSS_COUNT</u></a> IMediaReader sizes array: data packet count Value: <b>7</b>
public static final	<a href="#"><u>PLAYSIZES_SIZE</u></a> IMediaReader sizes array: size of sizes array long[PLAYSIZES_SIZE] Value: <b>8</b>
public static final	<a href="#"><u>PLAYSIZES_VIDEO_BYTES</u></a> IMediaReader sizes array: video byte count Value: <b>2</b>

public static final	<a href="#">PLAYSIZES_VIDEO_COUNT</a> IMediaReader sizes array: video packet count Value: <b>3</b>
public static final	<a href="#">PLAYSTATUSTYPE_COMPLETE</a> onPlayStatus type: complete Value: <b>2</b>
public static final	<a href="#">PLAYSTATUSTYPE_STOP</a> onPlayStatus type: stop Value: <b>3</b>
public static final	<a href="#">PLAYSTATUSTYPE_SWITCH</a> onPlayStatus type: switch Value: <b>1</b>

## Method Summary

void	<a href="#">close()</a> Close mediaStreamPlay
<a href="#">IMediaStream</a>	<a href="#">getParent()</a> Get the parent media stream object
void	<a href="#">init</a> ( <a href="#">IMediaStream</a> parent, <a href="#">MediaStreamMap</a> streams) Initialize mediaStreamPlayer
void	<a href="#">initLiveStreamRepeating</a> (String liveStreamPacketizer, String liveStreamRepeater) Initialize this stream for live stream repeating
void	<a href="#">interruptPlay()</a> Interrupt play to perform operation.
double	<a href="#">length()</a> Get stream length/seconds (seconds)
void	<a href="#">pause</a> (int pauseType, long timecode) pause mediaPlayStream
void	<a href="#">pauseRaw</a> (int pauseType, long timecode) pauseRaw mediaPlayStream
boolean	<a href="#">play()</a> Return true if there are packets to play
int	<a href="#">play</a> (java.io.OutputStream out, <a href="#">AMFObj</a> wmsObjAudio, <a href="#">AMFObj</a> wmsObjVideo, <a href="#">AMFObj</a> wmsObjData, long[] sizes) Write new packets or play packets
void	<a href="#">reset</a> (boolean isReset) Reset mediaStreamPlayer
void	<a href="#">resetNoLookup()</a> Reset but do not lookup current position in live stream
void	<a href="#">seek</a> (int location) seek mediaPlayStream

void	<a href="#"><code>setBufferTime</code></a> (int bufferTime) Set buffer time
void	<a href="#"><code>setName</code></a> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Set mediaPlayStream name, extension, query string, play start, play len, play reset
void	<a href="#"><code>shutdown</code></a> () Shutdown mediaStreamPlayer
long	<a href="#"><code>size</code></a> () Get stream media file size
void	<a href="#"><code>startPlay</code></a> () Start playing stream
void	<a href="#"><code>stopName</code></a> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Stop stream name
void	<a href="#"><code>switchName</code></a> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Switch to stream name
void	<a href="#"><code>switchPlay</code></a> ()
void	<a href="#"><code>updateLoggingValues</code></a> () Update internal logging values

## Fields

### PAUSE\_PAUSE

```
public static final int PAUSE_PAUSE
```

Pause type: pause  
Constant value: **1**

### PAUSE\_TOGGLE

```
public static final int PAUSE_TOGGLE
```

Pause type: toggle  
Constant value: **-1**

### PAUSE\_PLAY

```
public static final int PAUSE_PLAY
```

Pause type: play  
Constant value: **0**

### PLAYSTATUSTYPE\_SWITCH

```
public static final int PLAYSTATUSTYPE_SWITCH
```

onPlayStatus type: switch

(continued from last page)

Constant value: **1**

---

## PLAYSTATUSTYPE\_COMPLETE

```
public static final int PLAYSTATUSTYPE_COMPLETE
```

onPlayStatus type: complete  
Constant value: **2**

---

## PLAYSTATUSTYPE\_STOP

```
public static final int PLAYSTATUSTYPE_STOP
```

onPlayStatus type: stop  
Constant value: **3**

---

## PLAYSIZES\_AUDIO\_BYTES

```
public static final int PLAYSIZES_AUDIO_BYTES
```

IMediaReader sizes array: audio byte count  
Constant value: **0**

---

## PLAYSIZES\_AUDIO\_COUNT

```
public static final int PLAYSIZES_AUDIO_COUNT
```

IMediaReader sizes array: audio packet count  
Constant value: **1**

---

## PLAYSIZES\_VIDEO\_BYTES

```
public static final int PLAYSIZES_VIDEO_BYTES
```

IMediaReader sizes array: video byte count  
Constant value: **2**

---

## PLAYSIZES\_VIDEO\_COUNT

```
public static final int PLAYSIZES_VIDEO_COUNT
```

IMediaReader sizes array: video packet count  
Constant value: **3**

---

## PLAYSIZES\_DATA\_BYTES

```
public static final int PLAYSIZES_DATA_BYTES
```

IMediaReader sizes array: data byte count  
Constant value: **4**

---

## PLAYSIZES\_DATA\_COUNT

```
public static final int PLAYSIZES_DATA_COUNT
```

IMediaReader sizes array: data packet count  
Constant value: **5**

---

(continued from last page)

## PLAYSIZES\_LOSS\_BYTES

```
public static final int PLAYSIZES_LOSS_BYTES
```

IMediaReader sizes array: data byte count  
Constant value: **6**

## PLAYSIZES\_LOSS\_COUNT

```
public static final int PLAYSIZES_LOSS_COUNT
```

IMediaReader sizes array: data packet count  
Constant value: **7**

## PLAYSIZES\_SIZE

```
public static final int PLAYSIZES_SIZE
```

IMediaReader sizes array: size of sizes array long[PLAYSIZES\_SIZE]  
Constant value: **8**

## Methods

### init

```
public void init(IMediaStream parent,  
                 MediaStreamMap streams)
```

Initialize mediaStreamPlayer

#### Parameters:

parent - parent mediaStream object  
streams - parent mediaStreamMap

### shutdown

```
public void shutdown()
```

Shutdown mediaStreamPlayer

### reset

```
public void reset(boolean isReset)
```

Reset mediaStreamPlayer

#### Parameters:

isReset - is this a playlist reset or addition, true if reset

### resetNoLookup

```
public void resetNoLookup()
```

Reset but do not lookup current position in live stream

(continued from last page)

## play

```
public int play(java.io.OutputStream out,
    AMFObj wmsObjAudio,
    AMFObj wmsObjVideo,
    AMFObj wmsObjData,
    long[] sizes)
```

Write new packets or play packets

### Parameters:

out - OutputStream  
wmsObjAudio - audio response channel  
wmsObjVideo - video response channel  
wmsObjData - data response channel  
sizes - sizes array. See IMediaStreamPlay.PLAYSIZES\_\*

### Returns:

total byte output

## play

```
public boolean play()
```

Return true if there are packets to play

### Returns:

true if packets to play

## seek

```
public void seek(int location)
```

seek mediaPlayStream

### Parameters:

location - timecode (milliseconds)

## pause

```
public void pause(int pauseType,
    long timecode)
```

pause mediaPlayStream

### Parameters:

pauseType - pause type. See IMediaStreamPlay.PAUSE\_\*  
timecode - timecode (milliseconds)

## pauseRaw

```
public void pauseRaw(int pauseType,
    long timecode)
```

pauseRaw mediaPlayStream

### Parameters:

pauseType - pause type. See IMediaStreamPlay.PAUSE\_\*  
timecode - timecode (milliseconds)

## setBufferTime

```
public void setBufferTime(int bufferTime)
```

Set buffer time

**Parameters:**

bufferTime

---

## setName

```
public void setName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Set mediaPlayStream name, extension, query string, play start, play len, play reset

**Parameters:**

name - stream name  
oldName - old stream name  
ext - extension  
queryStr - query string  
playStart - play start  
playLen - play len  
playTransition - play reset

---

## switchName

```
public void switchName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Switch to stream name

**Parameters:**

name - stream name  
oldName - old stream name  
ext - stream extension  
queryStr - query string  
playStart - play start  
playLen - play len  
playTransition - play transition (see MediaBase.PLAYTRANSITION\_\*)

---

## stopName

```
public void stopName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```



(continued from last page)

Stop stream name

**Parameters:**

name - stream name  
oldName - old stream name  
ext - stream extension  
queryStr - query string  
playStart - play start  
playLen - play len  
playTransition - play transition (see MediaBase.PLAYTRANSITION\_\*)

---

**close**

```
public void close()
```

Close mediaStreamPlay

---

**interruptPlay**

```
public void interruptPlay()
```

Interrupt play to perform operation. Usually for seek or pause.

---

**startPlay**

```
public void startPlay()
```

Start playing stream

---

**switchPlay**

```
public void switchPlay()
```

---

**updateLoggingValues**

```
public void updateLoggingValues()
```

Update internal logging values

---

**length**

```
public double length()
```

Get stream length/seconds (seconds)

**Returns:**

length/duration (seconds)

---

**size**

```
public long size()
```

Get stream media file size

**Returns:**

media file size

---

## getParent

```
public IMediaStream getParent( )
```

Get the parent media stream object

**Returns:**

parent media stream object

---

## initLiveStreamRepeating

```
public void initLiveStreamRepeating(String liveStreamPacketizer,  
    String liveStreamRepeater)
```

Initialize this stream for live stream repeating

**Parameters:**

liveStreamPacketizer - live stream packetizer

liveStreamRepeater - live stream repeater name

---

**com.wowza.wms.stream****Interface IMediaStreamTimecodeControl**

---

public interface **IMediaStreamTimecodeControl**  
extends

IMediaStreamTimecodeControl: Internal use.

---

## Method Summary

void	<a href="#">resetTimecodes()</a>
------	----------------------------------

---

## Methods

**resetTimecodes**

public void **resetTimecodes**()

## **com.wowza.wms.stream**

### **Interface IMediaWriter**

---

public interface **IMediaWriter**  
extends

IMediaWriter: generic media writer interface. The flv recording system using this interface to persist .flv data captured from the Flash client. These classes are referenced in [\[install-dir\]/conf/MediaWriters.xml](#).

### Example IMediaWriter implementation: MediaWriterFLVBasic

This is a basic IMediaWriter implementation that can handle record and append.

```
import java.io.*;
import java.nio.ByteBuffer;
import java.util.*;

import com.wowza.util.*;
import com.wowza.wms.stream.*;
import com.wowza.wms.amf.AMFData;
import com.wowza.wms.logging.*;

public class MediaWriterFLV implements IMediaWriter
{
    private IMediaStream parent = null;
    private MediaWriterItem mediaWriterItem = null;
    private long[] currentTCs = new long[3];
    private long duration = 0;
    private Map extraMetadata = new HashMap();
    private boolean versionFile = false;

    public void setMediaWriterItem(MediaWriterItem mediaWriterItem)
    {
        this.mediaWriterItem = mediaWriterItem;
    }

    public void setParent(IMediaStream parent)
    {
        this.parent = parent;
    }

    public void writePackets(List audioPackets, List videoPackets,
                             List dataPackets, List audioTCs, List videoTCs, List dataTCs, List
dataTypes,
                             boolean isFirst, boolean isLast)
    {
        File newFile = this.parent.getStreamFile();

        boolean localAppend = this.parent.isAppend();

        if (isFirst)
        {
            long startTC = 0;
            if (newFile.exists())
            {
                if (localAppend)
                    startTC = FLVUtils.getLastTC(newFile);
                else
                {
                    if (versionFile)
                        FileUtils.versionFile(newFile);
                    else
                    {
                        try
```

```

        {
            newFile.delete();
        }
        catch (Exception e)
        {
        }
    }
}
else
    localAppend = false;

this.currentTCs[FLVUtils.FLV_TCINDEXAUDIO] = startTC;
this.currentTCs[FLVUtils.FLV_TCINDEXVIDEO] = startTC;
this.currentTCs[FLVUtils.FLV_TCINDEXDATA] = startTC;
}
else
    localAppend = true;

try
{
    if (newFile.getParentFile() == null)

WMSLoggerFactory.getLogger(MediaWriterFLV.class).warn("MediaWriterFLV: File path does not
exist: "+newFile.getPath());
        else if (!newFile.getParentFile().exists())

WMSLoggerFactory.getLogger(MediaWriterFLV.class).warn("MediaWriterFLV: Folder does not exist:
"+newFile.getParentFile().getPath());
        else if (newFile.exists() && !newFile.canWrite())

WMSLoggerFactory.getLogger(MediaWriterFLV.class).warn("MediaWriterFLV: Cannot write to file
(permission error): "+newFile.getPath());

        FileOutputStream ds = new FileOutputStream(newFile, localAppend);

        if (isFirst)
        {
            if (!localAppend)
            {
                FLVUtils.writeHeader(ds, 0.0, extraMetadata);

                boolean writeZeroPacket = true;
                while(true)
                {
                    if (audioPackets.size() == 0)
                        break;

                    ByteBuffer data =
(ByteBuffer)audioPackets.get(0);

                    long tcA = ((Long)audioTCs.get(0)).longValue();

```

```

        if (tcA == 0 && data.limit() == 0)
            writeZeroPacket = false;

        break;
    }

    if (writeZeroPacket)
    {
        FLVUtils.writeChunk(ds, null, 0,

this.currentTCs[FLVUtils.FLV_TCINDEXAUDIO],

                                                                    (byte) 0x08); //
write zero length audio block
    }
}

    FLVUtils.writePackets(ds, audioPackets, videoPackets, dataPackets,
        audioTCs, videoTCs, dataTCs, dataTypes, currentTCs);

    ds.flush();
    ds.close();
}
catch (Exception e)
{
    WMSLoggerFactory.getLogger(MediaWriterFLV.class).error(
        "MediaWriterFLV: Error writing to file:
"+newFile.getPath()+": "+e.toString());
    e.printStackTrace();
}

    if (isLast)
    {
        duration = Math.max(Math.max(currentTCs[FLVUtils.FLV_TCINDEXAUDIO],
            currentTCs[FLVUtils.FLV_TCINDEXVIDEO]),
            currentTCs[FLVUtils.FLV_TCINDEXDATA]);
        double durationSecs = ((double)duration) / 1000.0;

        FLVUtils.writeDuration(newFile, durationSecs);
    }
}

public Map getExtraMetadata()
{
    return extraMetadata;
}

public void setExtraMetadata(Map extraMetadata)
{
    this.extraMetadata = extraMetadata;
}

```

```
    }

    public boolean isVersionFile()
    {
        return versionFile;
    }

    public void setVersionFile(boolean versionFile)
    {
        this.versionFile = versionFile;
    }

    public void putMetaData(String name, AMFData value)
    {
        this.extraMetadata.put(name, value);
    }
}
```

To use this class, edit [install-dir]/conf/MediaWriter and replace the definition for the **flv** MediaWriter:

```
<MediaWriter>
  <Name>flv</Name>
  <Description>FLV Media Writer</Description>
  <FileExtension>flv</FileExtension>
  <ClassBase>com.wowza.wms.plugin.mediawriter.flv.MediaWriterFLVBasic</ClassBase>
</MediaWriter>
```

## Example IMediaWriter implementation: MediaWriterFLVMetadata

This example illustrates how to write custom metadata into the recorded flv file on the fly.



```
public class MediaWriterFLVMetadata implements IMediaWriter
{
    private IMediaStream parent = null;
    private MediaWriterItem mediaWriterItem = null;
    private long[] currentTCs = new long[3];
    private long duration = 0;
    private File tmpFile = null;
    private Map extraMetadata = new HashMap();
    private boolean versionFile = false;

    public void setMediaWriterItem(MediaWriterItem mediaWriterItem)
    {
        this.mediaWriterItem = mediaWriterItem;
    }

    public void setParent(IMediaStream parent)
    {
        this.parent = parent;
    }

    public void writePackets(List audioPackets, List videoPackets,
        List dataPackets, List audioTCs, List videoTCs, List dataTCs,
        boolean isFirst, boolean isLast)
    {
        File newFile = this.parent.getStreamFile();
        try
        {
            if (tmpFile == null)
                tmpFile = File.createTempFile("wowza", "flv");
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
                "MediaWriterFLVMetadata: Error createTempFile: "+
                tmpFile+" :"+e.toString());
        }

        boolean localAppend = this.parent.isAppend();
        if (isFirst)
        {
            AMFDataArray keyFrames = null;

            long startTC = 0;
            if (newFile.exists())
            {
                if (localAppend)
                {
                    startTC = FLVUtils.getLastTC(newFile);
                    keyFrames = getKeyFrames(newFile);
                    copyPacketsToTmpFile(newFile, tmpFile);
                }
            }
        }
    }
}
```

```

        if (versionFile)
            FileUtils.versionFile(newFile);
        else
        {
            try
            {
                newFile.delete();
            }
            catch (Exception e)
            {
            }
        }
    }
    else
        localAppend = false;

    if (keyFrames == null)
        keyFrames = new AMFDataArray();
    extraMetadata.put("keyFrames", keyFrames);

    this.currentTCs[FLVUtils.FLV_TCINDEXAUDIO] = startTC;
    this.currentTCs[FLVUtils.FLV_TCINDEXVIDEO] = startTC;
    this.currentTCs[FLVUtils.FLV_TCINDEXDATA] = startTC;
}
else
    localAppend = true;

    AMFDataArray keyFrames = (AMFDataArray)extraMetadata.get("keyFrames");
    long timecode = this.currentTCs[FLVUtils.FLV_TCINDEXVIDEO];
    int size = videoPackets.size();
    for(int i=0;i<size;i++)
    {
        ByteBuffer data = (ByteBuffer)videoPackets.get(i);
        int firstByte = data.get(0);
        timecode += ((Long)videoTCs.get(i)).longValue();
        if (FLVUtils.getFrameType(firstByte) == FLVUtils.FLV_KFRAME)
        {
            double durationSecs = ((double)timecode) / 1000.0;
            AMFDataObj dataObj = new AMFDataObj();
            dataObj.put("name", new AMFDataItem("keyframe
"+durationSecs));

            dataObj.put("time", new AMFDataItem(durationSecs));
            keyFrames.add(dataObj);
        }
    }

    try
    {
        FileOutputStream ds = new FileOutputStream(tmpFile, localAppend);
        FLVUtils.writePackets(ds, audioPackets, videoPackets, dataPackets,

```

```

        audioTCs, videoTCs, dataTCs, currentTCs);

        ds.flush();
        ds.close();
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
            "MediaWriterFLVMetadata: Error writing to tmp file:
"+
            newFile.getPath()+" :"+e.toString());
    }

    if (isLast)
    {
        duration = Math.max(Math.max(currentTCs[FLVUtils.FLV_TCINDEXAUDIO],
            currentTCs[FLVUtils.FLV_TCINDEXVIDEO]),
            currentTCs[FLVUtils.FLV_TCINDEXDATA]);
        double durationSecs = ((double)duration) / 1000.0;

        try
        {
            AMFPacket packet = null;
            FileOutputStream ds = new FileOutputStream(newFile);

            FileInputStream di = new FileInputStream(tmpFile);
            FLVUtils.writeHeader(ds, durationSecs, extraMetadata);
            while((packet = FLVUtils.readChunk(di)) != null)
            {
                FLVUtils.writeChunk(ds, packet.getDataBuffer(),
packet.getSize(),
                                packet.getTimecode(),
(byte)packet.getType());
            }
            di.close();

            ds.flush();
            ds.close();

            tmpFile.delete();
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
                "MediaWriterFLVMetadata: Error tmp writing to
file: "+
                newFile.getPath()+" :"+e.toString());
        }
    }
}

private void copyPacketsToTmpFile(File newFile, File tmpFile)

```

```

{
    AMFDataArray keyFrames = null;
    try
    {
        AMFPacket packet = null;
        FileOutputStream ds = new FileOutputStream(tmpFile);

        FileInputStream di = new FileInputStream(newFile);
        FLVUtils.readHeader(di);
        FLVUtils.readChunk(di); // skip metaData packet
        while((packet = FLVUtils.readChunk(di)) != null)
        {
            FLVUtils.writeChunk(ds, packet.getDataBuffer(),
packet.getSize(),
                                packet.getTimecode(),
(byte)packet.getType());
        }
        di.close();

        ds.flush();
        ds.close();
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
            "MediaWriterFLVMetadata: Error copyPacketsToTmpFile:
"+
            newFile.getPath()+" "+e.toString());
    }
}

private AMFDataArray getKeyFrames(File newFile)
{
    AMFDataArray keyFrames = null;
    try
    {
        BufferedInputStream inStream = new BufferedInputStream(new
FileInputStream(newFile));
        FLVUtils.readHeader(inStream);
        AMFPacket packet = FLVUtils.readChunk(inStream);
        if (packet.getType() == IVHost.CONTENTTYPE_DATA0 || packet.getType()
== IVHost.CONTENTTYPE_DATA3)
        {
            byte[] mbytes = packet.getData();
            int moffset = 0;
            if (packet.getType() == IVHost.CONTENTTYPE_DATA3 &&
mbytes.length > 0)
            {
                if (mbytes[0] == 0)
                    moffset = 1;
            }
        }
    }
}

```

```

        AMFDataList dataList = new AMFDataList(mbytes, moffset,
mbytes.length-moffset);
        if (dataList.size() > 1)
        {
            if (dataList.get(1).getType() ==
AMFData.DATA_TYPE_MIXED_ARRAY)
            {
                AMFDataMixedArray metaValues =
                (AMFDataMixedArray)dataList.get(1);
                if (metaValues.containsKey("keyFrames"))
                    keyFrames =
                (AMFDataArray)metaValues.get("keyFrames");
            }
        }
        inStream.close();
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
            "MediaWriterFLVMetadata: Error getKeyFrames: " +
            newFile.getPath()+" "+e.toString());
    }

    return keyFrames;
}

public boolean isVersionFile()
{
    return versionFile;
}

public void setVersionFile(boolean versionFile)
{
    this.versionFile = versionFile;
}

public void putMetadata(String name, AMFData value)
{
    this.extraMetadata.put(name, value);
}
}

```

To use this class, edit [install-dir]/conf/MediaWriter and replace the definition for the **flv** MediaWriter:

```

<MediaWriter>
  <Name>flv</Name>
  <Description>FLV Media Writer</Description>
  <FileExtension>flv</FileExtension>
  <ClassBase>com.wowza.wms.plugin.mediawriter.flv.MediaWriterFLVMetadata</ClassBase>
</MediaWriter>

```

## Method Summary

long	<a href="#"><code>getDuration()</code></a> Get the recorded duration of the file in seconds
boolean	<a href="#"><code>isVersionFile()</code></a> Return true if the old file is to be versioned
boolean	<a href="#"><code>isWaitForVideoKeyFrame()</code></a> get wait for key frame
void	<a href="#"><code>putMetaData(String name, AMFData value)</code></a> Add metadata to the metadata packet.
void	<a href="#"><code>setMediaWriterItem(MediaWriterItem mediaWriterItem)</code></a> Set the media write definition
void	<a href="#"><code>setParent(IMediaStream parent)</code></a> Set the parent stream for this media write object
void	<a href="#"><code>setVersionFile(boolean versionFile)</code></a> Set to true if the old file is to be versioned
void	<a href="#"><code>setWaitForVideoKeyFrame(boolean waitForVideoKeyFrame)</code></a> Set to true if you want the recorder to skip opening frames until it hits a key frame
void	<a href="#"><code>writePackets(java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, boolean isFirst, boolean isLast)</code></a> Invoked each time a set of packets are ready to be presisted.

## Methods

### writePackets

```

public void writePackets(java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    java.util.List dataTypes,
    boolean isFirst,
    boolean isLast)

```

Invoked each time a set of packets are ready to be presisted.

(continued from last page)

**Parameters:**

audioPackets - List of audio packets  
videoPackets - List of video packets  
dataPackets - List of data packets  
audioTCs - List of audio timecodes  
videoTCs - List of video timecodes  
dataTCs - List of data timecodes  
dataTypes - list of integer packets types (IVHost.CONTENTTYPE\_DATA0, IVHost.CONTENTTYPE\_DATA3) - if null assumed to be IVHost.CONTENTTYPE\_DATA0  
isFirst - true if first packet to be written  
isLast - false if last packet to be written

---

**setMediaWriterItem**

```
public void setMediaWriterItem(MediaWriterItem mediaWriterItem)
```

Set the media write definition

**Parameters:**

mediaWriterItem - media write definition

---

**setParent**

```
public void setParent(IMediaStream parent)
```

Set the parent stream for this media write object

**Parameters:**

parent

---

**isVersionFile**

```
public boolean isVersionFile()
```

Return true if the old file is to be versioned

**Returns:**

true if the old file is to be versioned

---

**setVersionFile**

```
public void setVersionFile(boolean versionFile)
```

Set to true if the old file is to be versioned

**Parameters:**

versionFile

---

**isWaitForVideoKeyFrame**

```
public boolean isWaitForVideoKeyFrame()
```

get wait for key frame

**Returns:**

wait for key frame

(continued from last page)

## setWaitForVideoKeyFrame

```
public void setWaitForVideoKeyFrame(boolean waitForVideoKeyFrame)
```

Set to true if you want the recorder to skip opening frames until it hits a key frame

### Parameters:

waitForVideoKeyFrame - wait for key frame

---

## putMetaData

```
public void putMetaData(String name,  
    AMFData value)
```

Add metadata to the metadata packet. Only metadata added before the first call to writePackets will be included in the file

### Parameters:

name - field name

value - metadata value

---

## getDuration

```
public long getDuration()
```

Get the recorded duration of the file in seconds

### Returns:

recorded duration of the file in seconds



## com.wowza.wms.stream Interface IMediaWriterActionNotify

public interface **IMediaWriterActionNotify**  
extends

IMediaWriterActionNotify: listener interface for file writing. See  
IApplicationInstance.addMediaWriterListener(IMediaWriterActionNotify listener)

### Method Summary

void	<a href="#">onFLVAddMetadata</a> ( <a href="#">IMediaStream</a> stream, java.util.Map extraMetadata) Called just before metadata is written to the file (FLV only)
void	<a href="#">onWriteComplete</a> ( <a href="#">IMediaStream</a> stream, java.io.File file) Called when writing is complete

### Methods

#### onWriteComplete

```
public void onWriteComplete(IMediaStream stream,  
    java.io.File file)
```

Called when writing is complete

**Parameters:**

stream - stream  
file - file handle

#### onFLVAddMetadata

```
public void onFLVAddMetadata(IMediaStream stream,  
    java.util.Map extraMetadata)
```

Called just before metadata is written to the file (FLV only)

**Parameters:**

stream - stream  
extraMetadata - additional metadata, add to this collection to add items to onMetadata event written to FLV file.

## com.wowza.wms.stream Class MediaReaderEncInfo

java.lang.Object

└─com.wowza.wms.stream.MediaReaderEncInfo

public class **MediaReaderEncInfo**  
extends Object

### Field Summary

public static final	<a href="#">METHOD_NONE</a> Value: <b>0</b>
public static final	<a href="#">METHOD_SAMPLE_PLAYREADY</a> Value: <b>1</b>

### Constructor Summary

public	<a href="#">MediaReaderEncInfo()</a>
--------	--------------------------------------

### Method Summary

void	<a href="#">addPlayReadyDecryptorKey</a> (com.wowza.wms.drm.playready.PlayReadyKeyInfo decryptorKey)
int	<a href="#">getEncMethod</a> ()
com.wowza.wms.drm.playready.PlayReadyKeyInfo	<a href="#">getPlayReadyDecryptorKey</a> ()
com.wowza.wms.drm.playready.PlayReadyKeyInfo	<a href="#">getPlayReadyDecryptorKey</a> (String keyId)
void	<a href="#">setEncMethod</a> (int encMethod)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Fields

#### METHOD\_NONE

public static final int **METHOD\_NONE**

(continued from last page)

Constant value: **0**

---

## METHOD\_SAMPLE\_PLAYREADY

```
public static final int METHOD_SAMPLE_PLAYREADY
```

Constant value: **1**

---

## Constructors

### MediaReaderEncInfo

```
public MediaReaderEncInfo()
```

---

## Methods

### addPlayReadyDecryptorKey

```
public void addPlayReadyDecryptorKey(com.wowza.wms.drm.playready.PlayReadyKeyInfo  
decryptorKey)
```

---

### getPlayReadyDecryptorKey

```
public com.wowza.wms.drm.playready.PlayReadyKeyInfo getPlayReadyDecryptorKey()
```

---

### getPlayReadyDecryptorKey

```
public com.wowza.wms.drm.playready.PlayReadyKeyInfo getPlayReadyDecryptorKey(String  
keyId)
```

---

### getEncMethod

```
public int getEncMethod()
```

---


### setEncMethod

```
public void setEncMethod(int encMethod)
```

## com.wowza.wms.stream

### Class MediaStreamBase

java.lang.Object



All Implemented Interfaces:

[IMediaStream](#)

public class **MediaStreamBase**  
extends [MediaStream](#)

#### Field Summary

public static	<a href="#">p</a> Deprecated.
public static	<a href="#">sinfo</a> Deprecated.

#### Fields inherited from class com.wowza.wms.stream.MediaStream

actionListeners, audioBytes, audioSize, audioTC, BASE\_STREAM\_EXT, bufferTime, callbackListeners, callbacks, client, dataBytes, dataSize, dataTC, dataType, dvrLock, dvrMap, dvrPlayer, dvrRecorder, dvrRecorderList, dvrRepeater, elapsedTime, ext, fastPlaySettings, h264SEIListeners, headerSize, httpStreamerSession, ID3\_STREAM\_EXT, isAppend, isClustered, isMediaCasterPlay, isOpen, isPlay, isPlaying, isRecord, isTranscodeResult, liveStreamPacketizer, liveStreamPacketizerList, liveStreamRepeater, liveStreamTranscoderList, lock, mediaIOPerformance, mergeOnMetadata, metaDataProvider, MP3\_STREAM\_EXT, MP4\_STREAM\_EXT, name, netConnection, parent, player, playLen, playStart, playTransition, properties, queryStr, receiveAudio, receiveVideo, receiveVideoFPS, rtpStream, SEND\_CONTROL0, SEND\_CONTROL1, SEND\_CONTROL3, SEND\_CONTROL4, sendDirectLock, sendDirectMessages, sendPlayStopLogEvent, sendPublishStopLogEvent, sendRecordStopLogEvent, SMIL\_STREAM\_EXT, src, STREAM\_DEFAULTNAME, streamType, transcoderLock, transcoderMap, tss, videoBytes, videoSize, videoTC

#### Fields inherited from interface [com.wowza.wms.stream.IMediaStream](#)

[AUDIOSAMPLEACCESS](#), [READACCESS](#), [VIDEOSAMPLEACCESS](#), [WRITEACCESS](#)

#### Constructor Summary

public	<a href="#">MediaStreamBase()</a>
--------	-----------------------------------

#### Method Summary

void	<a href="#">init</a> ( <a href="#">MediaStreamMap</a> parent, int src, <a href="#">WMSProperties</a> properties)
void	<a href="#">publish</a> ()

void	<a href="#">trim()</a>
------	------------------------

**Methods inherited from class** com.wowza.wms.stream.MediaStream

addAudioCodecConfigPacket, addAudioData, addCallbackListener, addClientListener, addClientListener, addClientListener, addDataData, addVideoCodecConfigPacket, addVideoData, addVideoH264SEIListener, clear, clearFastPlaySettings, clearLoggingValues, close, flush, getAccess, getAudioCodecConfigPacket, getAudioMissing, getAudioSize, getAudioTC, getBufferTime, getBurstStartStop, getCacheName, getClient, getClientId, getContextStr, getDataMissing, getDataSize, getDataTC, getDataType, getDvrRecorder, getDvrRecorder, getDvrRecorderList, getDvrRepeater, getElapsedTime, getExt, getFastPlaySettings, getHeaderSize, getHTTPStreamerSession, getLastKeyFrame, getLastPacket, getLiveStreamDvr, getLiveStreamDvrs, getLiveStreamPacketizer, getLiveStreamPacketizer, getLiveStreamPacketizerList, getLiveStreamRepeater, getLiveStreamTranscoder, getLiveStreamTranscoderList, getLiveStreamTranscoders, getMaxTimecode, getMediaIOPerformance, getMetaDataProvider, getName, getNetConnection, getPlayer, getPlayPackets, getProperties, getPublishAudioCodecId, getPublishVideoCodecId, getQueryStr, getReceiveVideoFPS, getRespAMFAudioObj, getRespAMFDataObj, getRespAMFVideoObj, getRTPStream, getSrc, getStreamFileForRead, getStreamFileForRead, getStreamFileForWrite, getStreamFileForWrite, getStreams, getStreamType, getTss, getUniqueStreamIdStr, getVideoCodecConfigPacket, getVideoMissing, getVideoSize, getVideoTC, handleCallback, idle, incrementMediaInBytes, incrementMediaLossBytes, incrementMediaOutBytes, init, initDvrRepeating, initLiveStreamRepeating, isAppend, isClustered, isMediaCasterPlay, isMergeOnMetadata, isOpen, isPlay, isPlaying, isPublishStreamReady, isReceiveAudio, isReceiveVideo, isRecord, isSendDirectMessages, isSendPlayStopLogEvent, isSendPublishStopLogEvent, isSendRecordStopLogEvent, isTranscodeResult, isVideoH264SEIListenerEmpty, length, notifyActionOnCodecInfoAudio, notifyActionOnCodecInfoVideo, notifyActionOnMetaData, notifyActionPause, notifyActionPauseRaw, notifyActionPlay, notifyActionPublish, notifyActionSeek, notifyActionStop, notifyActionUnPublish, notifyVideoH264Packet, packetComplete, processSendDirectMessages, publish, putDvrRecorder, putLiveStreamTranscoder, registerCallback, registerOnPlayStatus, registerOnStatus, removeCallbackListener, removeClientListener, removeClientListener, removeClientListener, removeDvrRecorder, removeLiveStreamTranscoder, removeVideoH264SEIListener, reset, send, send, sendAMF3, sendAMF3, sendControlBytes, sendDataToCallback, sendDirect, sendDirect, sendDirectAMF3, sendDirectAMF3, sendDirectInternal, sendDirectInternal, sendInternal, sendInternal, sendLivePlaySeek, sendLivePlayStart, sendLivePlaySwitch, sendPauseNotify, sendPauseNotify, sendPlayReset, sendPlayReset, sendPlaySeek, sendPlaySeek, sendPlaySeek, sendPlayStart, sendPlayStart, sendPlayStart, sendPlayStart, sendPlayStatus, sendPlayStatus, sendPlayStop, sendPlayStop, sendPlaySwitch, sendPlaySwitch, sendStreamNotFound, sendStreamNotFound, sendUnpauseNotify, sendUnpauseNotify, sendUnpauseNotify, sendVODPlaySwitch, setAppend, setAudioSize, setAudioTC, setAudioTC, setBufferTime, setClient, setClustered, setDataSize, setDataTC, setDataTC, setDataTC, setDataType, setDvrRecorder, setDvrRecorderList, setDvrRepeater, setExt, setFastPlaySettings, setHeaderSize, setHTTPStreamerSession, setIsPlaying, setJustName, setLiveStreamPacketizer, setLiveStreamPacketizerList, setLiveStreamRepeater, setLiveStreamTranscoderList, setMediaCasterPlay, setMergeOnMetadata, setMetaDataProvider, setName, setName, setName, setNetConnection, setOpen, setPlay, setPlayer, setPublishAudioCodecId, setPublishVideoCodecId, setQueryStr, setReceiveAudio, setReceiveVideo, setReceiveVideoFPS, setRecord, setRTPStream, setSendPlayStopLogEvent, setSendPublishStopLogEvent, setSendRecordStopLogEvent, setSrc, setStreamType, setTranscodeResult, setTss, setVideoSize, setVideoTC, setVideoTC, shutdown, size, startAudioPacket, startDataPacket, startPublishing, startVideoPacket, stopName, stopPublishing, switchName, trim, unregisterCallback, unregisterOnPlayStatus, unregisterOnStatus, updateLoggingDuration, updateLoggingValues

**Methods inherited from class `java.lang.Object`**

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

**Methods inherited from interface `com.wowza.wms.stream.IMediaStream`**

[`addAudioCodecConfigPacket`](#), [`addAudioData`](#), [`addCallbackListener`](#), [`addClientListener`](#), [`addClientListener`](#), [`addClientListener`](#), [`addDataData`](#), [`addVideoCodecConfigPacket`](#), [`addVideoData`](#), [`addVideoH264SEIListener`](#), [`clear`](#), [`clearFastPlaySettings`](#), [`clearLoggingValues`](#), [`close`](#), [`flush`](#), [`getAccess`](#), [`getAudioCodecConfigPacket`](#), [`getAudioMissing`](#), [`getAudioSize`](#), [`getAudioTC`](#), [`getBufferTime`](#), [`getBurstStartStop`](#), [`getCacheName`](#), [`getClient`](#), [`getClientId`](#), [`getContextStr`](#), [`getDataMissing`](#), [`getDataSize`](#), [`getDataTC`](#), [`getDataType`](#), [`getDvrRecorder`](#), [`getDvrRecorder`](#), [`getDvrRecorderList`](#), [`getDvrRepeater`](#), [`getElapsedTime`](#), [`getExt`](#), [`getFastPlaySettings`](#), [`getHeaderSize`](#), [`getHTTPStreamerSession`](#), [`getLastKeyFrame`](#), [`getLastPacket`](#), [`getLiveStreamPacketizer`](#), [`getLiveStreamPacketizer`](#), [`getLiveStreamPacketizerList`](#), [`getLiveStreamRepeater`](#), [`getLiveStreamTranscoder`](#), [`getLiveStreamTranscoderList`](#), [`getLiveStreamTranscoders`](#), [`getMaxTimecode`](#), [`getMediaIOPerformance`](#), [`getMetaDataProvider`](#), [`getName`](#), [`getNetConnection`](#), [`getPlayer`](#), [`getPlayPackets`](#), [`getProperties`](#), [`getPublishAudioCodecId`](#), [`getPublishVideoCodecId`](#), [`getQueryStr`](#), [`getReceiveVideoFPS`](#), [`getRespAMFAudioObj`](#), [`getRespAMFDataObj`](#), [`getRespAMFVideoObj`](#), [`getRTPStream`](#), [`getSrc`](#), [`getStreamFileForRead`](#), [`getStreamFileForRead`](#), [`getStreamFileForWrite`](#), [`getStreamFileForWrite`](#), [`getStreams`](#), [`getStreamType`](#), [`getUniqueStreamIdStr`](#), [`getVideoCodecConfigPacket`](#), [`getVideoMissing`](#), [`getVideoSize`](#), [`getVideoTC`](#), [`handleCallback`](#), [`idle`](#), [`incrementMediaInBytes`](#), [`incrementMediaLossBytes`](#), [`incrementMediaOutBytes`](#), [`init`](#), [`initLiveStreamRepeating`](#), [`isAppend`](#), [`isClustered`](#), [`isMediaCasterPlay`](#), [`isMergeOnMetadata`](#), [`isOpen`](#), [`isplay`](#), [`isplaying`](#), [`isPublishStreamReady`](#), [`isReceiveAudio`](#), [`isReceiveVideo`](#), [`isRecord`](#), [`isSendPlayStopLogEvent`](#), [`isSendPublishStopLogEvent`](#), [`isSendRecordStopLogEvent`](#), [`isTranscodeResult`](#), [`isVideoH264SEIListenerEmpty`](#), [`length`](#), [`notifyActionOnCodecInfoAudio`](#), [`notifyActionOnCodecInfoVideo`](#), [`notifyActionOnMetadata`](#), [`notifyActionPause`](#), [`notifyActionPauseRaw`](#), [`notifyActionPlay`](#), [`notifyActionPublish`](#), [`notifyActionSeek`](#), [`notifyActionStop`](#), [`notifyActionUnPublish`](#), [`notifyVideoH264Packet`](#), [`packetComplete`](#), [`publish`](#), [`putDvrRecorder`](#), [`putLiveStreamTranscoder`](#), [`registerCallback`](#), [`registerOnPlayStatus`](#), [`registerOnStatus`](#), [`removeCallbackListener`](#), [`removeClientListener`](#), [`removeClientListener`](#), [`removeClientListener`](#), [`removeDvrRecorder`](#), [`removeLiveStreamTranscoder`](#), [`removeVideoH264SEIListener`](#), [`send`](#), [`send`](#), [`sendAMF3`](#), [`sendAMF3`](#), [`sendControlBytes`](#), [`sendDirect`](#), [`sendDirect`](#), [`sendDirectAMF3`](#), [`sendDirectAMF3`](#), [`sendLivePlaySeek`](#), [`sendLivePlayStart`](#), [`sendLivePlaySwitch`](#), [`sendPauseNotify`](#), [`sendPauseNotify`](#), [`sendPlayReset`](#), [`sendPlayReset`](#), [`sendPlaySeek`](#), [`sendPlaySeek`](#), [`sendPlaySeek`](#), [`sendPlayStart`](#), [`sendPlayStart`](#), [`sendPlayStart`](#), [`sendPlayStart`](#), [`sendPlayStatus`](#), [`sendPlayStatus`](#), [`sendPlayStop`](#), [`sendPlayStop`](#), [`sendPlaySwitch`](#), [`sendPlaySwitch`](#), [`sendStreamNotFound`](#), [`sendStreamNotFound`](#), [`sendUnpauseNotify`](#), [`sendUnpauseNotify`](#), [`sendUnpauseNotify`](#), [`sendVODPlaySwitch`](#), [`setAppend`](#), [`setAudioSize`](#), [`setAudioTC`](#), [`setAudioTC`](#), [`setBufferTime`](#), [`setClient`](#), [`setClustered`](#), [`setDataSize`](#), [`setDataTC`](#), [`setDataTC`](#), [`setDataType`](#), [`setDvrRecorder`](#), [`setDvrRecorderList`](#), [`setExt`](#), [`setFastPlaySettings`](#), [`setHeaderSize`](#), [`setHTTPStreamerSession`](#), [`setIsPlaying`](#), [`setLiveStreamPacketizer`](#), [`setLiveStreamPacketizerList`](#), [`setLiveStreamRepeater`](#), [`setLiveStreamTranscoderList`](#), [`setMediaCasterPlay`](#), [`setMergeOnMetadata`](#), [`setMetaDataProvider`](#), [`setName`](#), [`setName`](#), [`setName`](#), [`setNetConnection`](#), [`setOpen`](#), [`setPlay`](#), [`setPlayer`](#), [`setPublishAudioCodecId`](#), [`setPublishVideoCodecId`](#), [`setQueryStr`](#), [`setReceiveAudio`](#), [`setReceiveVideo`](#), [`setReceiveVideoFPS`](#), [`setRecord`](#), [`setRTPStream`](#), [`setSendPlayStopLogEvent`](#), [`setSendPublishStopLogEvent`](#), [`setSendRecordStopLogEvent`](#), [`setSrc`](#), [`setStreamType`](#), [`setTranscodeResult`](#), [`setVideoSize`](#), [`setVideoTC`](#), [`setVideoTC`](#), [`shutdown`](#), [`size`](#), [`startAudioPacket`](#), [`startDataPacket`](#), [`startPublishing`](#), [`startVideoPacket`](#), [`stopName`](#), [`stopPublishing`](#), [`switchName`](#), [`trim`](#), [`unregisterCallback`](#), [`unregisterOnPlayStatus`](#), [`unregisterOnStatus`](#), [`updateLoggingDuration`](#), [`updateLoggingValues`](#)

---

## Fields

### **sinfo**

```
public static java.util.Map sinfo
```

Deprecated.

---

### **p**

```
public static java.lang.String p
```

Deprecated.

---

## Constructors

### **MediaStreamBase**

```
public MediaStreamBase()
```

---

## Methods

### **init**

```
public void init(MediaStreamMap parent,  
                int src,  
                WMSProperties properties)
```

---

### **publish**

```
public void publish()
```

---

### **trim**

```
public void trim()
```

## com.wowza.wms.stream Class MediaStreamMap

java.lang.Object

└--com.wowza.wms.stream.MediaStreamMap

public class **MediaStreamMap**  
extends Object

MediaStreamMap: collection of IMediaStream object. This collection is usually attached to an IApplicationInstance object.

### Field Summary

protected	<a href="#">appInstance</a>
protected	<a href="#">dvrRecorders</a>
protected	<a href="#">liveStreamPacketizers</a>
public static final	<a href="#">MAXSTREAMINDEX</a> Value: <b>65536</b>
protected	<a href="#">mediaStreamListeners</a>
protected	<a href="#">nameGroupId</a>
protected	<a href="#">nameGroups</a>
protected	<a href="#">nextStreamId</a>
protected	<a href="#">packetizerLicenses</a>
protected	<a href="#">streamLicenses</a>
protected	<a href="#">streamLock</a>
protected	<a href="#">streamNames</a>
protected	<a href="#">streamNamesLock</a>
protected	<a href="#">streamNameToGroup</a>
protected	<a href="#">streams</a>

### Constructor Summary



public	<a href="#">MediaStreamMap</a> ( <a href="#">IApplicationInstance</a> appInstance) Create empty MediaStreamMap collection
--------	--

## Method Summary

LicenseHolder	<a href="#">addLicense</a> ( <a href="#">ILiveStreamPacketizer</a> liveStreamPacketizer, int licenseType)
LicenseHolder	<a href="#">addLicense</a> ( <a href="#">IMediaStream</a> stream, int licenseType)
void	<a href="#">addMediaStreamListener</a> ( <a href="#">IMediaStreamNotify</a> mediaStreamListener) Add a media stream listener.
MediaStreamMapGroup	<a href="#">addNameGroup</a> (MediaStreamMapGroup newGroup)
void	<a href="#">broadcastPlayMessage</a> ( <a href="#">IMediaStream</a> stream, long timecode, <a href="#">java.nio.ByteBuffer</a> msg, int objectEncoding) Send a broadcast message to all play stream that are listening to this live published stream.
int	<a href="#">broadcastGetObjectEncoding</a> ( <a href="#">IMediaStream</a> stream) Get the minimum object encoding level for the clients playing this stream.
void	<a href="#">clearStreamName</a> (String name) Unregister a published live media stream name.
void	<a href="#">clearStreamName</a> (String name, <a href="#">IMediaStream</a> stream) Unregister a published live media stream name.
<a href="#">IApplicationInstance</a>	<a href="#">getAppInstance</a> () Get the parent applicationInstance.
String	<a href="#">getAppInstanceName</a> () Get the name of the parent applicationInstance.
String	<a href="#">getAppName</a> () Get the name of the parent application.
int	<a href="#">getCount</a> () Get the total number of streams stored in the mediaStreamMap
<a href="#">ILiveStreamDvrRecorder</a>	<a href="#">getDvrRecorder</a> (String streamName, String recorderName, boolean doCreate) Get a DVR recorder by name and recorder name
java.util.List	<a href="#">getDvrRecorders</a> () Returns a list of <a href="#">ILiveStreamDvrRecorder</a> objects
<a href="#">ILiveStreamPacketizer</a>	<a href="#">getLiveStreamPacketizer</a> (String streamName, String packetizerName, boolean doCreate) Get a live stream packetizer by name and packetizer id
Object	<a href="#">getLiveStreamPacketizerLock</a> () Get the lock to the live stream packetizer system
MediaStreamMapGroup	<a href="#">getNameGroupByGroupName</a> (String groupName)
java.util.Set	<a href="#">getNameGroups</a> ()

java.util.Set	<a href="#"><u>getNameGroups</u></a> (String streamName)
java.util.Set	<a href="#"><u>getNameGroupStreamNames</u></a> (String streamName)
long	<a href="#"><u>getNextNameGroupId</u></a> (MediaStreamMapGroup newGroup)
int	<a href="#"><u>getNextStreamIndex</u></a> ( ) Reserve a clientless stream id for a new media stream.
int	<a href="#"><u>getNextStreamIndex</u></a> ( <a href="#"><u>IClient</u></a> client) Reserve a stream for a client connection.
int	<a href="#"><u>getNextStreamIndex</u></a> (com.wowza.wms.netconnection.INetConnection netConnection) Reserve a stream for a netConnection connection.
java.util.List	<a href="#"><u>getPublishStreamNames</u></a> ( ) Returns a List of published stream names
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream</u></a> ( <a href="#"><u>IClient</u></a> client, int index) Get a media stream reference by stream id.
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream</u></a> ( <a href="#"><u>IClient</u></a> client, int index, boolean doCreate) Get a media stream reference by stream id.
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream</u></a> (com.wowza.wms.netconnection.INetConnection netConnection, int index) Get a media stream object that is owned by a server to server netConnection object (not yet implemented).
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream</u></a> (com.wowza.wms.netconnection.INetConnection netConnection, int index, boolean doCreate) Get a media stream reference by stream id.
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream</u></a> (String name) Get a media stream by stream name.
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStreamClientless</u></a> (int index, String streamTypeStr) Get a media stream reference by stream id.
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<a href="#"><u>getStreamListLock</u></a> ( ) Get the underlying read/write lock associated with the list of streams
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<a href="#"><u>getStreamNameLock</u></a> ( ) Get the underlying read/write lock associated with the stream names list
java.util.List	<a href="#"><u>getStreams</u></a> ( ) Returns a list of IMediaStream objects
<a href="#"><u>IVHost</u></a>	<a href="#"><u>getVHost</u></a> ( ) Get the parent vHost.
void	<a href="#"><u>notifyMediaStreamCreate</u></a> ( <a href="#"><u>IMediaStream</u></a> mediaStream) Notify all media stream listeners that a new media stream object has been created.

void	<a href="#"><u>notifyMediaStreamDestroy</u></a> ( <a href="#"><u>IMediaStream</u></a> mediaStream) Notify all media stream listeners that a media stream object is being destroyed.
void	<a href="#"><u>notifyPlayPublish</u></a> ( <a href="#"><u>IMediaStream</u></a> stream) Notify all play streams that are listening to this stream that the stream is going into a state of publish (NetStream.Play.PublishNotify).
void	<a href="#"><u>notifyPlayUnpublish</u></a> ( <a href="#"><u>IMediaStream</u></a> stream) Notify all play streams that are listening to this stream that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).
void	<a href="#"><u>notifyPlayUnpublish</u></a> (String streamName) Notify all play streams that are listening to this stream name that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).
void	<a href="#"><u>removeDvrRecorder</u></a> (String streamName)
<a href="#"><u>ILiveStreamDvrRecorder</u></a>	<a href="#"><u>removeDvrRecorder</u></a> (String streamName, String recorderName) Remove DVR Recorder
void	<a href="#"><u>removeLiveStreamPacketizer</u></a> (String streamName) Remove all live stream packetizers for this stream name
<a href="#"><u>ILiveStreamPacketizer</u></a>	<a href="#"><u>removeLiveStreamPacketizer</u></a> (String streamName, String packetizerName) Remove live stream packetizer
void	<a href="#"><u>removeMediaStreamListener</u></a> ( <a href="#"><u>IMediaStreamNotify</u></a> mediaStreamListener) Remove a media stream listener.
MediaStreamMapGroup	<a href="#"><u>removeNameGroup</u></a> (int groupId)
MediaStreamMapGroup	<a href="#"><u>removeNameGroup</u></a> (MediaStreamMapGroup nameGroup)
void	<a href="#"><u>removeStream</u></a> ( <a href="#"><u>IClient</u></a> client, int index) Remove a stream associated with a client connection
void	<a href="#"><u>removeStream</u></a> (com.wowza.wms.netconnection.INetConnection netConnection, int index) Remove a stream associated with a netConnection object
void	<a href="#"><u>removeStream</u></a> (int index) Remove a clientless media stream
void	<a href="#"><u>setStreamName</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, String name) Insert live media stream into the mediaStreamMap by name.
long	<a href="#"><u>streamToIndex</u></a> ( <a href="#"><u>IMediaStream</u></a> stream) Get the unique stream identifier for a given stream

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Fields**

(continued from last page)

## MAXSTREAMINDEX

```
public static final int MAXSTREAMINDEX
```

Constant value: **65536**

---

## streams

```
protected java.util.Map streams
```

---

## streamNames

```
protected java.util.Map streamNames
```

---

## streamLicenses

```
protected java.util.Map streamLicenses
```

---

## packetizerLicenses

```
protected java.util.Map packetizerLicenses
```

---

## streamNameToGroup

```
protected java.util.Map streamNameToGroup
```

---

## nameGroups

```
protected java.util.List nameGroups
```

---

## nameGroupId

```
protected long nameGroupId
```

---

## streamLock

```
protected edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
streamLock
```

---

(continued from last page)

---

## streamNamesLock

protected edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
**streamNamesLock**

---

## appInstance

protected com.wowza.wms.application.IApplicationInstance **appInstance**

---

## mediaStreamListeners

protected java.util.List **mediaStreamListeners**

---

## nextStreamId

protected java.util.concurrent.atomic.AtomicLong **nextStreamId**

---

## liveStreamPacketizers

protected java.util.Map **liveStreamPacketizers**

---

## dvrRecorders

protected java.util.Map **dvrRecorders**

---

## Constructors

### MediaStreamMap

public **MediaStreamMap**([IApplicationInstance](#) appInstance)

Create empty MediaStreamMap collection

**Parameters:**

appInstance - parent applicationInstance

## Methods

### getStreamListLock

public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
**getStreamListLock**( )

Get the underlying read/write lock associated with the list of streams

**Returns:**

(continued from last page)

underlying read/write lock associated with the list of streams

---

## getStreamNameLock

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
getStreamNameLock()
```

Get the underlying read/write lock associated with the stream names list

**Returns:**

underlying read/write lock associated with the stream names list

---

## getPublishStreamNames

```
public java.util.List getPublishStreamNames()
```

Returns a List of published stream names

**Returns:**

List of published stream names

---

## getStreams

```
public java.util.List getStreams()
```

Returns a list of IMediaStream objects

**Returns:**

list of IMediaStream objects

---

## getStream

```
public IMediaStream getStream(IClient client,  
int index)
```

Get a media stream reference by stream id.

**Parameters:**

client - client  
index - stream id

**Returns:**

media stream object or null if does not exist.

---

## getStreamClientless

```
public IMediaStream getStreamClientless(int index,  
String streamTypeStr)
```

Get a media stream reference by stream id. If it does not exist, create a new one with the given id. This is a clientless stream that is served by the backend of the server. If creating a new media stream object, its id must first be obtained by calling [getNextStreamIndex\(\)](#).

**Parameters:**

index - stream id  
streamTypeStr - stream type

**Returns:**

media stream object

## getStream

```
public IMediaStream getStream(IClient client,  
                               int index,  
                               boolean doCreate)
```

Get a media stream reference by stream id. If it does not exist, create a new one with the given id. If creating a new media stream object, its id must first be obtained by calling [getNextStreamIndex\(IClient\)](#).

**Parameters:**

client - client  
index - stream id  
doCreate - true to create if it does not exist

**Returns:**

media stream object

---

## getStream

```
public IMediaStream getStream(com.wowza.wms.netconnection.INetConnection  
netConnection,  
                               int index)
```

Get a media stream object that is owned by a server to server netConnection object (not yet implemented).

**Parameters:**

netConnection - netConnection to remote server  
index - stream id

**Returns:**

media stream object or null if does not exist

---

## getStream

```
public IMediaStream getStream(com.wowza.wms.netconnection.INetConnection  
netConnection,  
                               int index,  
                               boolean doCreate)
```

Get a media stream reference by stream id. If it does not exist, create a new one with the given id. If creating a new media stream object, its id must first be obtained by calling [getNextStreamIndex\(INetConnection\)](#).

**Parameters:**

netConnection - netConnection to remote server  
index - stream id  
doCreate - true to create if it does not exist

**Returns:**

media stream object

---

## getStream

```
public IMediaStream getStream(String name)
```

Get a media stream by stream name. Only published live streams are stored in the mediaStreamMap by name. This method is used to lookup a published live stream by name.

**Parameters:**

name - stream name

---

(continued from last page)

**Returns:**

media stream object or null if does not exist

---

**setStreamName**

```
public void setStreamName(IMediaStream stream,  
    String name)
```

Insert live media stream into the mediaStreamMap by name.

**Parameters:**stream - media stream object  
name - media stream name

---

**clearStreamName**

```
public void clearStreamName(String name)
```

Unregister a published live media stream name.

**Parameters:**

name - stream name

---

**streamToIndex**

```
public long streamToIndex(IMediaStream stream)
```

Get the unique stream identifier for a given stream

**Parameters:**

stream - stream

**Returns:**

unique stream identifier

---

**clearStreamName**

```
public void clearStreamName(String name,  
    IMediaStream stream)
```

Unregister a published live media stream name.

**Parameters:**name - stream name  
stream - stream

---

**getNextStreamIndex**

```
public int getNextStreamIndex(com.wowza.wms.netconnection.INetConnection  
    netConnection)
```

Reserve a stream for a netConnection connection. Use [getStream\(INetConnection, int, boolean\)](#) to create stream.**Parameters:**

netConnection

**Returns:**

next stream index



## getNextStreamIndex

```
public int getNextStreamIndex(IClient client)
```

Reserve a stream for a client connection. Use [getStream\(IClient, int, boolean\)](#) to create stream.

**Parameters:**

client - parent client

**Returns:**

stream index

---

## getNextStreamIndex

```
public int getNextStreamIndex()
```

Reserve a clientless stream id for a new media stream. Use this method to obtain a stream id for a new media stream object that is then created with a call to getClientlessStream().

**Returns:**

new reserved stream id

---

## getCount

```
public int getCount()
```

Get the total number of streams stored in the mediaStreamMap

**Returns:**

total number of streams stored in the mediaStreamMap

---

## removeStream

```
public void removeStream(com.wowza.wms.netconnection.INetConnection netConnection,  
int index)
```

Remove a stream associated with a netConnection object

**Parameters:**

netConnection - net connection

index - stream index

---

## removeStream

```
public void removeStream(IClient client,  
int index)
```

Remove a stream associated with a client connection

**Parameters:**

client - client

index - stream index

---

## removeStream

```
public void removeStream(int index)
```

Remove a clientless media stream

---

(continued from last page)

**Parameters:**

index - stream index

---

**getAppName**

```
public String getAppName()
```

Get the name of the parent application.

**Returns:**

parent application name.

---

**getAppInstanceName**

```
public String getAppInstanceName()
```

Get the name of the parent applicationInstance.

**Returns:**

parent applicationInstance name

---

**getVHost**

```
public IVHost getVHost()
```

Get the parent vHost.

**Returns:**

parent vHost

---

**getAppInstance**

```
public IApplicationInstance getAppInstance()
```

Get the parent applicationInstance.

**Returns:**

parent applicationInstance

---

**notifyPlayUnpublish**

```
public void notifyPlayUnpublish(IMediaStream stream)
```

Notify all play streams that are listening to this stream that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).

**Parameters:**

stream - live published stream that is being unpublished

---

**notifyPlayUnpublish**

```
public void notifyPlayUnpublish(String streamName)
```

Notify all play streams that are listening to this stream name that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).

**Parameters:**

streamName - live published stream that is being unpublished

## broadcastGetObjectEncoding

```
public int broadcastGetObjectEncoding(IMediaStream stream)
```

Get the minimum object encoding level for the clients playing this stream.

**Parameters:**

stream - publish stream

**Returns:**

object encoding level (AMF0 or AMF3)

---

## broadcastPlayMessage

```
public void broadcastPlayMessage(IMediaStream stream,  
    long timecode,  
    java.nio.ByteBuffer msg,  
    int objectEncoding)
```

Send a broadcast message to all play stream that are listening to this live published stream.

**Parameters:**

stream - media stream

timecode - timecode (milliseconds)

msg - byte[] of data that will be deserialized as an AMFData object.

objectEncoding - object encoding (AMF0 or AMF3)

---

## notifyPlayPublish

```
public void notifyPlayPublish(IMediaStream stream)
```

Notify all play streams that are listening to this stream that the stream is going into a state of publish (NetStream.Play.PublishNotify).

**Parameters:**

stream - live published stream that is being published

---

## addMediaStreamListener

```
public void addMediaStreamListener(IMediaStreamNotify mediaStreamListener)
```

Add a media stream listener. A media stream listener will receive the following events: onMediaStreamCreate, onMediaStreamDestroy.

**Parameters:**

mediaStreamListener - media stream listener

---

## removeMediaStreamListener

```
public void removeMediaStreamListener(IMediaStreamNotify mediaStreamListener)
```

Remove a media stream listener.

**Parameters:**

mediaStreamListener - media stream listener

---

(continued from last page)

## notifyMediaStreamCreate

```
public void notifyMediaStreamCreate(IMediaStream mediaStream)
```

Notify all media stream listeners that a new media stream object has been created.

**Parameters:**

mediaStream - new media stream object

---

## notifyMediaStreamDestroy

```
public void notifyMediaStreamDestroy(IMediaStream mediaStream)
```

Notify all media stream listeners that a media stream object is being destroyed.

**Parameters:**

mediaStream - media stream object being destroyed

---

## removeLiveStreamPacketizer

```
public void removeLiveStreamPacketizer(String streamName)
```

Remove all live stream packetizers for this stream name

**Parameters:**

streamName - streamName

---

## removeLiveStreamPacketizer

```
public ILiveStreamPacketizer removeLiveStreamPacketizer(String streamName,  
String packetizerName)
```

Remove live stream packetizer

**Parameters:**

streamName - stream name

packetizerName - packetizer id

**Returns:**

live stream packetizer

---

## getLiveStreamPacketizerLock

```
public Object getLiveStreamPacketizerLock()
```

Get the lock to the live stream packetizer system

**Returns:**

lock to the live stream packetizer system

---

## getLiveStreamPacketizer

```
public ILiveStreamPacketizer getLiveStreamPacketizer(String streamName,  
String packetizerName,  
boolean doCreate)
```

Get a live stream packetizer by name and packetizer id

**Parameters:**

(continued from last page)

streamName - stream name  
packetizerName - packetizer id  
doCreate - create if does not exist

**Returns:**

live stream packetizer

---

**getNextNameGroupId**

```
public long getNextNameGroupId(MediaStreamMapGroup newGroup)
```

---

**addNameGroup**

```
public MediaStreamMapGroup addNameGroup(MediaStreamMapGroup newGroup)
```

---

**removeNameGroup**

```
public MediaStreamMapGroup removeNameGroup(int groupId)
```

---

**removeNameGroup**

```
public MediaStreamMapGroup removeNameGroup(MediaStreamMapGroup nameGroup)
```

---

**getNameGroups**

```
public java.util.Set getNameGroups()
```

---

**getNameGroupByGroupName**

```
public MediaStreamMapGroup getNameGroupByGroupName(String groupName)
```

---

**getNameGroups**

```
public java.util.Set getNameGroups(String streamName)
```

---

**getNameGroupStreamNames**

```
public java.util.Set getNameGroupStreamNames(String streamName)
```

---

(continued from last page)

## getDvrRecorder

```
public ILiveStreamDvrRecorder getDvrRecorder(String streamName,  
String recorderName,  
boolean doCreate)
```

Get a DVR recorder by name and recorder name

### Parameters:

streamName - stream name  
recorderName - packetizer id  
doCreate - create if does not exist

### Returns:

dvr recorder

---

## removeDvrRecorder

```
public void removeDvrRecorder(String streamName)
```

---

## removeDvrRecorder

```
public ILiveStreamDvrRecorder removeDvrRecorder(String streamName,  
String recorderName)
```

Remove DVR Recorder

### Parameters:

streamName - stream name  
recorderName - recorder name

### Returns:

DVR Recorder

---

## getDvrRecorders

```
public java.util.List getDvrRecorders()
```

Returns a list of [ILiveStreamDvrRecorder](#) objects

### Returns:

list of [ILiveStreamDvrRecorder](#) objects

---

## addLicense

```
public LicenseHolder addLicense(IMediaStream stream,  
int licenseType)
```

---

## addLicense

```
public LicenseHolder addLicense(ILiveStreamPacketizer liveStreamPacketizer,  
int licenseType)
```

---

Package

**com.wowza.wms.stream.livedvr**

## com.wowza.wms.stream.livedvr Interface IDvrStreamManagerActionNotify

public interface **IDvrStreamManagerActionNotify**  
extends

IDvrActionNotify notify interface for dvr stores. See IApplicationInstance.addDvrStoreListener(IDvrStoreActionNotify storeListener)

### Method Summary

void	<a href="#">onDvrStreamManagerCreate</a> ( <a href="#">IDvrStreamManager</a> dvrMgr) Called when DVR stream manager created but before it is initialized.
void	<a href="#">onDvrStreamManagerDestroy</a> ( <a href="#">IDvrStreamManager</a> dvrMgr) Called when DVR stream manager destroyed.
void	<a href="#">onDvrStreamManagerInit</a> ( <a href="#">IDvrStreamManager</a> dvrMgr) Called when DVR stream manager initialized.

### Methods

#### onDvrStreamManagerCreate

public void **onDvrStreamManagerCreate**([IDvrStreamManager](#) dvrMgr)

Called when DVR stream manager created but before it is initialized.

**Parameters:**

dvrMgr - DVR stream manager

#### onDvrStreamManagerInit

public void **onDvrStreamManagerInit**([IDvrStreamManager](#) dvrMgr)

Called when DVR stream manager initialized.

**Parameters:**

dvrMgr - DVR stream manager

#### onDvrStreamManagerDestroy

public void **onDvrStreamManagerDestroy**([IDvrStreamManager](#) dvrMgr)

Called when DVR stream manager destroyed.

**Parameters:**

dvrMgr - DVR stream manager



## com.wowza.wms.stream.livedvr Interface **ILiveStreamDvrRecorder**

public interface **ILiveStreamDvrRecorder**  
extends

ILiveStreamDvrRecorder: DVR Recorder interface.

### Method Summary

boolean	<a href="#"><u>canRecordAudio()</u></a> True if audio is being recorded
boolean	<a href="#"><u>canRecordData()</u></a> True if data is being recorded
boolean	<a href="#"><u>canRecordVideo()</u></a> True if video is being recorded
<a href="#"><u>IApplicationInstance</u></a>	<a href="#"><u>getAppInstance()</u></a> Get associated applicationInstance.
<a href="#"><u>IDvrStreamManager</u></a>	<a href="#"><u>getDvrManager()</u></a> Get DVR recorder's associated DVR stream manager
int	<a href="#"><u>getDvrRecorderId()</u></a> Get the DVR recorder id
LicenseHolder	<a href="#"><u>getLicenseHolder()</u></a>
<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties()</u></a> Get properties
String	<a href="#"><u>getRecordingName()</u></a>
<a href="#"><u>IMediaStream</u></a>	<a href="#"><u>getStream()</u></a> Get the current stream that is being recorded
void	<a href="#"><u>handlePacket()</u></a> ( <a href="#"><u>IMediaStream</u></a> stream, <a href="#"><u>AMFPacket</u></a> packet) Called to handle an incoming packet
void	<a href="#"><u>init()</u></a> (String streamName, String recorderName, <a href="#"><u>IApplicationInstance</u></a> appInstance, DvrRecorderItem dvrRecorderItem) Initialize DVR recorder.
boolean	<a href="#"><u>isActive()</u></a> Is the DVR recorder active
boolean	<a href="#"><u>isRecording()</u></a> Is this stream currently recording.
boolean	<a href="#"><u>isRecordingPaused()</u></a> Is this stream currently paused from recording.

boolean	<a href="#"><u>pauseRecording()</u></a> Request that stream recording pause.
void	<a href="#"><u>resetStream()</u></a> ( <a href="#"><u>IMediaStream</u></a> stream) Called when something happens that forces the stream to reset
boolean	<a href="#"><u>resumeRecording()</u></a> Request that stream recording resume.
void	<a href="#"><u>setDvrRecorderId()</u></a> (int liveStreamId) Set the DVR recorder id
void	<a href="#"><u>setRecordAudio()</u></a> (boolean recordAudio) Set to true to record audio
void	<a href="#"><u>setRecordData()</u></a> (boolean recordVideo) Set to true to record data
void	<a href="#"><u>setRecordingName()</u></a> (String name)
void	<a href="#"><u>setRecordVideo()</u></a> (boolean recordVideo) Set to true to record video
void	<a href="#"><u>setStartRecordingOnStartup()</u></a> (boolean shouldStartRecordingOnStartup) Set recording behavior of DVR Manager on startup.
boolean	<a href="#"><u>shouldStartRecordingOnStartup()</u></a> Should DVR start recording when packets start flowing.
void	<a href="#"><u>shutdown()</u></a> Called to shutdown the DVR recorder
<a href="#"><u>IDvrStreamManager</u></a>	<a href="#"><u>startRecording()</u></a> Request that stream recording start.
void	<a href="#"><u>startStream()</u></a> ( <a href="#"><u>IMediaStream</u></a> stream) Called when the stream starts
boolean	<a href="#"><u>stopRecording()</u></a> Request that stream recording stop.
void	<a href="#"><u>touch()</u></a> (long timecode) Touch the stream to keep it active

## Methods

### init

```
public void init(String streamName,
    String recorderName,
    IApplicationInstance appInstance,
    DvrRecorderItem dvrRecorderItem)
```

Initialize DVR recorder.

#### Parameters:

streamName - stream name

(continued from last page)

recorderName - DVR recorder name  
appInstance - application instance  
dvrRecorderItem - DVR recorder

---

## shutdown

```
public void shutdown()
```

Called to shutdown the DVR recorder

---

## getStream

```
public IMediaStream getStream()
```

Get the current stream that is being recorded

**Returns:**  
stream

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get associated applicationInstance.

**Returns:**  
application Instance

---

## handlePacket

```
public void handlePacket(IMediaStream stream,  
    AMFPacket packet)
```

Called to handle an incoming packet

**Parameters:**  
stream - stream  
packet - packet

---

## startStream

```
public void startStream(IMediaStream stream)
```

Called when the stream starts

**Parameters:**  
stream - stream

---

## resetStream

```
public void resetStream(IMediaStream stream)
```

Called when something happens that forces the stream to reset

**Parameters:**  
stream - stream

(continued from last page)

## touch

```
public void touch(long timecode)
```

Touch the stream to keep it active

**Parameters:**

timecode - timecode of touch in milliseconds

---

## isActive

```
public boolean isActive()
```

Is the DVR recorder active

**Returns:**

true if active

---

## getProperties

```
public WMSProperties getProperties()
```

Get properties

**Returns:**

properties

---

## getDvrRecorderId

```
public int getDvrRecorderId()
```

Get the DVR recorder id

**Returns:**

DVR recorder id

---

## setDvrRecorderId

```
public void setDvrRecorderId(int liveStreamId)
```

Set the DVR recorder id

**Parameters:**

liveStreamId

---

## getDvrManager

```
public IDvrStreamManager getDvrManager()
```

Get DVR recorder's associated DVR stream manager

**Returns:**

DVR manager

---

## canRecordAudio

```
public boolean canRecordAudio()
```

---

(continued from last page)

True if audio is being recorded

**Returns:**

True if audio is being recorded

---

## setRecordAudio

```
public void setRecordAudio(boolean recordAudio)
```

Set to true to record audio

**Parameters:**

recordAudio - true to record audio

---

## canRecordVideo

```
public boolean canRecordVideo()
```

True if video is being recorded

**Returns:**

True if video is being recorded

---

## setRecordVideo

```
public void setRecordVideo(boolean recordVideo)
```

Set to true to record video

**Parameters:**

recordVideo - true to record video

---

## canRecordData

```
public boolean canRecordData()
```

True if data is being recorded

**Returns:**

True if data is being recorded

---

## setRecordData

```
public void setRecordData(boolean recordVideo)
```

Set to true to record data

**Parameters:**

recordVideo - true to record data

---

## startRecording

```
public IDvrStreamManager startRecording()
```

Request that stream recording start.

**Returns:**

stream manager if successful. null otherwise.

## isRecording

```
public boolean isRecording()
```

Is this stream currently recording. If this stream is not recordable, the method returns false.

**Returns:**

true if has a recording stream and it is recording.

---

## isRecordingPaused

```
public boolean isRecordingPaused()
```

Is this stream currently paused from recording. If this stream is not recording and not paused, the method returns false.

**Returns:**

true if has a recording is paused.

---

## stopRecording

```
public boolean stopRecording()
```

Request that stream recording stop. Note that this call places the DVR stream in the *not* recording state.

A successful stop will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingStopped\(IDvrStreamStore\)](#) method called.

Success only occurs if the stream is already in the recording state [IDvrStreamStore.isRecording\(\)](#).

**Returns:**

store if successful. null otherwise.

---

## pauseRecording

```
public boolean pauseRecording()
```

Request that stream recording pause. The stream does not have to be actively recording to be paused. For example, it could be paused before packets start flowing.

A successful pause will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingPaused\(IDvrStreamStore\)](#) method called.

**Returns:**

store if successful. null otherwise.

---

## resumeRecording

```
public boolean resumeRecording()
```

Request that stream recording resume. The stream does not have to be actively recording to be resumed. For example, it could have been paused before the stream started, and this call would move it out of the paused state.

A successful resume will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingResumed\(IDvrStreamStore\)](#) method called.

**Returns:**

store if successful. null otherwise.

---

(continued from last page)

---

## setRecordingName

```
public void setRecordingName(String name)
```

---

## getRecordingName

```
public String getRecordingName()
```

---

## shouldStartRecordingOnStartup

```
public boolean shouldStartRecordingOnStartup()
```

Should DVR start recording when packets start flowing.

**Returns:**

true if should start recording initially, false otherwise

---

## setStartRecordingOnStartup

```
public void setStartRecordingOnStartup(boolean shouldStartRecordingOnStartup)
```

Set recording behavior of DVR Manager on startup.

**Parameters:**

shouldStartRecordingOnStartup - should recording start when DVR manager starts.

---

## getLicenseHolder

```
public LicenseHolder getLicenseHolder()
```

## com.wowza.wms.stream.livedvr Interface **ILiveStreamDvrRecorderActionNotify**

public interface **ILiveStreamDvrRecorderActionNotify**  
extends

ILiveStreamDvrRecorderActionNotify: notify interface for dvr recorders.

See Also:

[IApplicationInstance.addDvrRecorderListener\(ILiveStreamDvrRecorderActionNotify\)](#),

### Method Summary

void	<a href="#">onLiveStreamDvrRecorderCreate</a> ( <a href="#">ILiveStreamDvrRecorder</a> recorder, String streamName) Called when recorder created
void	<a href="#">onLiveStreamDvrRecorderDestroy</a> ( <a href="#">ILiveStreamDvrRecorder</a> recorder) Called when recorder destroyed
void	<a href="#">onLiveStreamDvrRecorderInit</a> ( <a href="#">ILiveStreamDvrRecorder</a> recorder, String streamName) Called after recorder is initialized

### Methods

#### **onLiveStreamDvrRecorderCreate**

```
public void onLiveStreamDvrRecorderCreate(ILiveStreamDvrRecorder recorder,  
String streamName)
```

Called when recorder created

**Parameters:**

recorder - recorder  
streamName - stream name

#### **onLiveStreamDvrRecorderInit**

```
public void onLiveStreamDvrRecorderInit(ILiveStreamDvrRecorder recorder,  
String streamName)
```

Called after recorder is initialized

**Parameters:**

recorder - recorder  
streamName - stream name

#### **onLiveStreamDvrRecorderDestroy**

```
public void onLiveStreamDvrRecorderDestroy(ILiveStreamDvrRecorder recorder)
```

Called when recorder destroyed



(continued from last page)

**Parameters:**

recorder - recorder

# com.wowza.wms.stream.livedvr

## Interface ILiveStreamDvrRecorderControl

public interface **ILiveStreamDvrRecorderControl**  
extends

ILiveStreamDvrRecorderControl: interface to control which recorders are run for which streams.  
**See Also:**  
[IApplicationInstance.setLiveStreamDvrRecorderControl\(ILiveStreamDvrRecorderControl\)](#)

Method Summary	
boolean	<a href="#">shouldDvrRecord</a> (String recorderName, <a href="#">IMediaStream</a> stream) Returns true if given string should be recorded.;

## Methods

### shouldDvrRecord

public boolean **shouldDvrRecord**(String recorderName, [IMediaStream](#) stream)

Returns true if given string should be recorded.;

**Parameters:**

- recorderName - recorder name
- stream - stream

**Returns:**

true to record

---

Package

**com.wowza.wms.stream.livepacketizer**

## com.wowza.wms.stream.livepacketizer

### Interface ILiveStreamPacketizer

All Subinterfaces:

[IDvrStreamManager](#)

public interface **ILiveStreamPacketizer**

extends

ILiveStreamPacketizer: live stream packetizer interface.

#### Method Summary

<a href="#">IMediaStream</a>	<a href="#">getAndSetStartStream</a> ( <a href="#">IMediaStream</a> stream) Get the current stream that is being packetized
<a href="#">IApplicationInstance</a>	<a href="#">getApplicationInstance</a> () Get the application instance associated with this live stream packetizer.
int	<a href="#">getLiveStreamPacketizerId</a> () Get the live stream packetizer id
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> () Get properties
long	<a href="#">getRepeaterLastSequence</a> () Get the sequence number of the last added repeater item
void	<a href="#">handlePacket</a> ( <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> packet) Called to handle an incoming packet
void	<a href="#">init</a> (String streamName, String packetizerName, <a href="#">IApplicationInstance</a> appInstance, LiveStreamPacketizerItem liveStreamPacketizerItem) Initialize live stream packetizer
boolean	<a href="#">isActive</a> () Is the live stream packetizer active
boolean	<a href="#">isPacketizeAudio</a> () True if audio is being packetized
boolean	<a href="#">isPacketizeData</a> () True if data is being packetized
boolean	<a href="#">isPacketizeVideo</a> () True if video is being packetized
boolean	<a href="#">isRepeaterEdge</a> () Is this packetizer a live repeater edge
void	<a href="#">resetStream</a> ( <a href="#">IMediaStream</a> stream) Called when something happens that forces the stream to reset
void	<a href="#">setLiveStreamPacketizerId</a> (int id) Set the live stream packetizer id

void	<a href="#"><u>setPacketizeAudio</u></a> (boolean packetizeAudio) Set to true to packetize audio
void	<a href="#"><u>setPacketizeData</u></a> (boolean packetizeVideo) Set to true to packetize data
void	<a href="#"><u>setPacketizeVideo</u></a> (boolean packetizeVideo) Set to true to packetize video
void	<a href="#"><u>setRepeaterEdge</u></a> (boolean isRepeaterEdge) Set is live repeater edge
void	<a href="#"><u>shutdown</u></a> ( ) Called to shutdown the live stream packetizer
void	<a href="#"><u>startStream</u></a> ( <a href="#"><u>IMediaStream</u></a> stream) Called when the stream starts
void	<a href="#"><u>touch</u></a> (long timecode) Touch the stream to keep it active

## Methods

### init

```
public void init(String streamName,
String packetizerName,
IApplicationInstance appInstance,
LiveStreamPacketizerItem liveStreamPacketizerItem)
```

Initialize live stream packetizer

#### Parameters:

streamName - stream name  
packetizerName - packetizer name  
appInstance - application instance  
liveStreamPacketizerItem - live stream packetizer

### shutdown

```
public void shutdown( )
```

Called to shutdown the live stream packetizer

### isActive

```
public boolean isActive( )
```

Is the live stream packetizer active

#### Returns:

true if active

### getProperties

```
public WMSProperties getProperties( )
```

(continued from last page)

Get properties

**Returns:**  
properties

---

## getRepeaterLastSequence

```
public long getRepeaterLastSequence()
```

Get the sequence number of the last added repeater item

**Returns:**  
sequence number

---

## getLiveStreamPacketizerId

```
public int getLiveStreamPacketizerId()
```

Get the live stream packetizer id

**Returns:**  
live stream packetizer id

---

## setLiveStreamPacketizerId

```
public void setLiveStreamPacketizerId(int id)
```

Set the live stream packetizer id

**Parameters:**  
id

---

## handlePacket

```
public void handlePacket(IMediaStream stream,  
    AMFPacket packet)
```

Called to handle an incoming packet

**Parameters:**  
stream - stream  
packet - packet

---

## startStream

```
public void startStream(IMediaStream stream)
```

Called when the stream starts

**Parameters:**  
stream - stream

---

## resetStream

```
public void resetStream(IMediaStream stream)
```

Called when something happens that forces the stream to reset

**Parameters:**

(continued from last page)

stream - stream

---

## touch

```
public void touch(long timecode)
```

Touch the stream to keep it active

**Parameters:**

timecode - timecode of touch in milliseconds

---

## isRepeaterEdge

```
public boolean isRepeaterEdge()
```

Is this packetizer a live repeater edge

**Returns:**

true if live repeater edge

---

## setRepeaterEdge

```
public void setRepeaterEdge(boolean isRepeaterEdge)
```

Set is live repeater edge

**Parameters:**

isRepeaterEdge - is live repeater edge

---

## isPacketizeAudio

```
public boolean isPacketizeAudio()
```

True if audio is being packetized

**Returns:**

True if audio is being packetized

---

## setPacketizeAudio

```
public void setPacketizeAudio(boolean packetizeAudio)
```

Set to true to packetize audio

**Parameters:**

packetizeAudio - true to packetize audio

---

## isPacketizeVideo

```
public boolean isPacketizeVideo()
```

True if video is being packetized

**Returns:**

True if video is being packetized

---

(continued from last page)

## setPacketizeVideo

```
public void setPacketizeVideo(boolean packetizeVideo)
```

Set to true to packetize video

**Parameters:**

packetizeVideo - true to packetize video

---

## isPacketizeData

```
public boolean isPacketizeData()
```

True if data is being packetized

**Returns:**

True if data is being packetized

---

## setPacketizeData

```
public void setPacketizeData(boolean packetizeVideo)
```

Set to true to packetize data

**Parameters:**

packetizeVideo - true to packetize data

---

## getAndSetStartStream

```
public IMediaStream getAndSetStartStream(IMediaStream stream)
```

Get the current stream that is being packetized

**Returns:**

stream

---

## getApplicationInstance

```
public IApplicationInstance getApplicationInstance()
```

Get the application instance associated with this live stream packetizer.

**Returns:**

application instance

---



## com.wowza.wms.stream.livepacketizer Interface **ILiveStreamPacketizerActionNotify**

public interface **ILiveStreamPacketizerActionNotify**  
extends

ILiveStreamPacketizerActionNotify: notify interface for live stream packetizers. See  
IApplicationInstance.addLiveStreamPacketizerListener(ILiveStreamPacketizerActionNotify liveStreamPacketizerListener)

### Method Summary

void	<a href="#">onLiveStreamPacketizerCreate</a> ( <a href="#">ILiveStreamPacketizer</a> liveStreamPacketizer, String streamName) Called when packetizer created
void	<a href="#">onLiveStreamPacketizerDestroy</a> ( <a href="#">ILiveStreamPacketizer</a> liveStreamPacketizer) Called when packetizer destroyed
void	<a href="#">onLiveStreamPacketizerInit</a> ( <a href="#">ILiveStreamPacketizer</a> liveStreamPacketizer, String streamName) Called after packetizer is initialized

### Methods

#### **onLiveStreamPacketizerCreate**

```
public void onLiveStreamPacketizerCreate(ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Called when packetizer created

**Parameters:**

liveStreamPacketizer - packetizer  
streamName - stream name

#### **onLiveStreamPacketizerDestroy**

```
public void onLiveStreamPacketizerDestroy(ILiveStreamPacketizer liveStreamPacketizer)
```

Called when packetizer destroyed

**Parameters:**

liveStreamPacketizer - packetizer

#### **onLiveStreamPacketizerInit**

```
public void onLiveStreamPacketizerInit(ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Called after packetizer is initialized

**Parameters:**

(continued from last page)

liveStreamPacketizer - packetizer  
streamName - stream name

# com.wowza.wms.stream.livepacketizer

## Interface ILiveStreamPacketizerControl

public interface **ILiveStreamPacketizerControl**  
extends

ILiveStreamPacketizerControl: interface to control which packetizers are run for which streams. See:  
IApplicationInstance.setLiveStreamPacketizerControl(ILiveStreamPacketizerControl liveStreamPacketizerControl)

Method Summary	
boolean	<a href="#">isLiveStreamPacketize</a> (String packetizer, <a href="#">IMediaStream</a> stream) Return true to packetize stream

## Methods

### isLiveStreamPacketize

public boolean **isLiveStreamPacketize**(String packetizer, [IMediaStream](#) stream)

Return true to packetize stream

**Parameters:**

- packetizer - packetizer name
- stream - stream

**Returns:**

true to packetize

---

Package

**com.wowza.wms.stream.livetranscoder**

## com.wowza.wms.stream.livetranscoder

### Interface **ILiveStreamTranscoder**

public interface **ILiveStreamTranscoder**  
 extends

ILiveStreamTranscoder: Interface to live stream transcoder.

#### Field Summary

public static final	<a href="#">TRANSCODERTYPE_LIVE</a> Value: <b>1</b>
public static final	<a href="#">TRANSCODERTYPE_VOD</a> Value: <b>2</b>

#### Method Summary

void	<a href="#">close</a> ( <a href="#">IMediaStream</a> stream) Called when live stream transcoder is stream is closed
<a href="#">IApplicationInstance</a>	<a href="#">getAppInstance</a> () Get the application instance associated with this live stream transcoder.
String	<a href="#">getContextStr</a> () Get the streaming context for this live stream transcoder.
LicenseHolder	<a href="#">getLicenseHolder</a> () Get license holder.
LiveStreamTranscoderItem	<a href="#">getLiveStreamTranscoderItem</a> () Get the definition for live stream transcoder.
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> () Get the user properties
String	<a href="#">getStreamName</a> () Get the stream name of the source stream.
String	<a href="#">getTranscoderName</a> () Get the live stream transcoder name
int	<a href="#">getTranscoderType</a> () Get the live stream transcoder type.
void	<a href="#">handleOnMetadata</a> ( <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> packet, long timecode, boolean isSetDataFrame) Called for each new onMetaData packet
void	<a href="#">handlePacket</a> ( <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> packet) Called for each new source packet

void	<a href="#"><code>init</code></a> (String streamName, <a href="#">IMediaStream</a> stream, String transcoderName, <a href="#">IApplicationInstance</a> appInstance, <a href="#">LiveStreamTranscoderItem</a> liveStreamTranscoderItem) Called when live stream transcoder interface is initialized.
boolean	<a href="#"><code>isTemplateLoaded</code></a> ( ) Is the transcoder template loaded.
boolean	<a href="#"><code>isTranscoderActive</code></a> (long currTime) Returns true if the transcoder is actively receiving packets
void	<a href="#"><code>resetStream</code></a> ( <a href="#">IMediaStream</a> stream) Called when source stream changes.
void	<a href="#"><code>setAppInstance</code></a> ( <a href="#">IApplicationInstance</a> appInstance) Set the application instance associated with this live stream transcoder.
void	<a href="#"><code>setLiveStreamTranscoderItem</code></a> ( <a href="#">LiveStreamTranscoderItem</a> liveStreamTranscoderItem) Set the definition for live stream transcoder.
void	<a href="#"><code>setStreamName</code></a> (String streamName) Set source stream name.
void	<a href="#"><code>setTranscoderName</code></a> (String transcoderName) Get the live stream transcoder name
void	<a href="#"><code>setTranscoderType</code></a> (int transcoderType) Set the live stream transcoder type.
void	<a href="#"><code>shutdown</code></a> ( <a href="#">IMediaStream</a> stream) Called when live stream transcoder is shutdown

## Fields

### TRANSCODERTYPE\_LIVE

```
public static final int TRANSCODERTYPE_LIVE
```

Constant value: **1**

### TRANSCODERTYPE\_VOD

```
public static final int TRANSCODERTYPE_VOD
```

Constant value: **2**

## Methods

### **init**

```
public void init(String streamName,
    IMediaStream stream,
    String transcoderName,
    IApplicationInstance appInstance,
    LiveStreamTranscoderItem liveStreamTranscoderItem)
```

(continued from last page)

Called when live stream transcoder interface is initialized.

**Parameters:**

streamName - stream name  
transcoderName - transcoder name  
appInstance - application instance  
liveStreamTranscoderItem - live stream transcoder config item

---

## handlePacket

```
public void handlePacket(IMediaStream stream,  
    AMFPacket packet)
```

Called for each new source packet

**Parameters:**

stream - stream  
packet - packet

---

## handleOnMetadata

```
public void handleOnMetadata(IMediaStream stream,  
    AMFPacket packet,  
    long timecode,  
    boolean isSetDataFrame)
```

Called for each new onMetaData packet

**Parameters:**

stream - stream  
packet - packet  
timecode - timecode (milliseconds)  
isSetDataFrame - is SetDataFrame call

---

## resetStream

```
public void resetStream(IMediaStream stream)
```

Called when source stream changes.

**Parameters:**

stream - stream interface

---

## close

```
public void close(IMediaStream stream)
```

Called when live stream transcoder is stream is closed

**Parameters:**

stream - stream interface

---

## shutdown

```
public void shutdown(IMediaStream stream)
```

Called when live stream transcoder is shutdown

**Parameters:**

(continued from last page)

stream - stream interface

---

## getStreamName

```
public String getStreamName()
```

Get the stream name of the source stream.

**Returns:**

stream name of the source stream

---

## setStreamName

```
public void setStreamName(String streamName)
```

Set source stream name.

**Parameters:**

streamName - source stream name

---

## getTranscoderName

```
public String getTranscoderName()
```

Get the live stream transcoder name

**Returns:**

live stream transcoder name

---

## setTranscoderName

```
public void setTranscoderName(String transcoderName)
```

Get the live stream transcoder name

**Parameters:**

transcoderName - live stream transcoder name

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get the application instance associated with this live stream transcoder.

**Returns:**

application instance associated with this live stream transcoder

---

## setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set the application instance associated with this live stream transcoder.

**Parameters:**

appInstance - application instance associated with this live stream transcoder

---



(continued from last page)

## getLiveStreamTranscoderItem

```
public LiveStreamTranscoderItem getLiveStreamTranscoderItem()
```

Get the definition for live stream transcoder.

**Returns:**

definition for live stream transcoder

---

## setLiveStreamTranscoderItem

```
public void setLiveStreamTranscoderItem(LiveStreamTranscoderItem  
liveStreamTranscoderItem)
```

Set the definition for live stream transcoder.

**Parameters:**

liveStreamTranscoderItem - definition for live stream transcoder

---

## getProperties

```
public WMSProperties getProperties()
```

Get the user properties

**Returns:**

user properties

---

## getLicenseHolder

```
public LicenseHolder getLicenseHolder()
```

Get license holder.

**Returns:**

license holder

---

## isTranscoderActive

```
public boolean isTranscoderActive(long currTime)
```

Returns true if the transcoder is actively receiving packets

**Parameters:**

currTime - current timecode in milliseconds

**Returns:**

true if the transcoder is actively receiving packets

---

## isTemplateLoaded

```
public boolean isTemplateLoaded()
```

Is the transcoder template loaded.

**Returns:**

true if transcoder template is loaded.

## getContextStr

```
public String getContextStr()
```

Get the streaming context for this live stream transcoder.

**Returns:**

streaming context for this live stream transcoder

---

## getTranscoderType

```
public int getTranscoderType()
```

Get the live stream transcoder type. See ILiveStreamTranscoder.TRANSCODERTYPE\_\*

**Returns:**

live stream transcoder type

---

## setTranscoderType

```
public void setTranscoderType(int transcoderType)
```

Set the live stream transcoder type. See ILiveStreamTranscoder.TRANSCODERTYPE\_\*

**Parameters:**

transcoderType - live stream transcoder type

## com.wowza.wms.stream.livetranscoder Interface **ILiveStreamTranscoderControl**

public interface **ILiveStreamTranscoderControl**  
extends

Interface used to control if stream is transcoded. See  
`IApplicationInstance.setLiveStreamTranscoderControl(ILiveStreamTranscoderControl)`

### Method Summary

boolean	<a href="#"><code>isLiveStreamTranscode</code></a> (String transcoder, <a href="#"><code>IMediaStream</code></a> stream) Called each time a new publishing stream is started.
---------	--

### Methods

#### **isLiveStreamTranscode**

```
public boolean isLiveStreamTranscode(String transcoder,  
    IMediaStream stream)
```

Called each time a new publishing stream is started. Return true if you wish stream to be transcoded. See  
`IApplicationInstance.setLiveStreamTranscoderControl(ILiveStreamTranscoderControl)`

**Parameters:**

transcoder - name of transcoder  
stream - stream interface

**Returns:**

true if wish stream to be transcoded

## com.wowza.wms.stream.livetranscoder Interface `ILiveStreamTranscoderNotify`

public interface `ILiveStreamTranscoderNotify`  
extends

`ILiveStreamTranscoderNotify`: Listener interface for listening for new live stream transcoders. See `IApplicationInstance.addLiveStreamTranscoderListener(ILiveStreamTranscoderNotify)`

### Method Summary

void	<a href="#"><code>onLiveStreamTranscoderCreate</code></a> ( <a href="#"><code>ILiveStreamTranscoder</code></a> liveStreamTranscoder, <a href="#"><code>IMediaStream</code></a> stream) Triggered when live stream transcoder is created.
void	<a href="#"><code>onLiveStreamTranscoderDestroy</code></a> ( <a href="#"><code>ILiveStreamTranscoder</code></a> liveStreamTranscoder, <a href="#"><code>IMediaStream</code></a> stream) Triggered when live stream transcoder is destroyed.
void	<a href="#"><code>onLiveStreamTranscoderInit</code></a> ( <a href="#"><code>ILiveStreamTranscoder</code></a> liveStreamTranscoder, <a href="#"><code>IMediaStream</code></a> stream) Triggered after live stream transcoder is initialized.

### Methods

#### `onLiveStreamTranscoderCreate`

```
public void onLiveStreamTranscoderCreate(ILiveStreamTranscoder liveStreamTranscoder,  
    IMediaStream stream)
```

Triggered when live stream transcoder is created.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
stream - source stream

#### `onLiveStreamTranscoderDestroy`

```
public void onLiveStreamTranscoderDestroy(ILiveStreamTranscoder liveStreamTranscoder,  
    IMediaStream stream)
```

Triggered when live stream transcoder is destroyed.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
stream - source stream

#### `onLiveStreamTranscoderInit`

```
public void onLiveStreamTranscoderInit(ILiveStreamTranscoder liveStreamTranscoder,  
    IMediaStream stream)
```

Triggered after live stream transcoder is initialized.

(continued from last page)

**Parameters:**

liveStreamTranscoder - live stream transcoder

stream - source stream

---

Package

**com.wowza.wms.stream.publish**

## com.wowza.wms.stream.publish Interface IPublishingProvider

All Known Implementing Classes:

[PublishingProviderMediaReader](#), [PublishingProviderLive](#)

public interface **IPublishingProvider**  
extends

IPublishingProvider: publishing provider interface.

### Method Summary

void	<a href="#">close()</a> Invoked on stream close
boolean	<a href="#">isSendOnMetadata()</a> Get to send onMetadata event when stream starts
boolean	<a href="#">play(Publisher publisher)</a> Invoked on play
boolean	<a href="#">seek(long timecode)</a> Invoked on seek
boolean	<a href="#">seek(long timecode, int seekType)</a> Invoked on seek
void	<a href="#">setDuration(long duration)</a> Set target duration for playback (milliseconds)
void	<a href="#">setRealTimeStartTime(long realTimeStartTime)</a> Set real start time (milliseconds)
void	<a href="#">setSendOnMetadata(boolean sendOnMetadata)</a> Set to send onMetadata event when stream starts

### Methods

#### play

public boolean **play**([Publisher](#) publisher)

Invoked on play

#### Parameters:

publisher - publisher

#### Returns:

true if successful

(continued from last page)

## close

```
public void close()
```

Invoked on stream close

---

## seek

```
public boolean seek(long timecode,  
                    int seekType)
```

Invoked on seek

### Parameters:

timecode - target timecode

seekType - seek type, see IMediaReader.SEEKTARGET\_\*

### Returns:

true, if seek successful

---

## seek

```
public boolean seek(long timecode)
```

Invoked on seek

### Parameters:

timecode - target timecode

### Returns:

true, if seek successful

---

## setDuration

```
public void setDuration(long duration)
```

Set target duration for playback (milliseconds)

### Parameters:

duration - duration for playback (milliseconds)

---

## setRealTimeStartTime

```
public void setRealTimeStartTime(long realTimeStartTime)
```

Set real start time (milliseconds)

### Parameters:

realTimeStartTime - real start time (milliseconds)

---

## setSendOnMetadata

```
public void setSendOnMetadata(boolean sendOnMetadata)
```

Set to send onMetadata event when stream starts

### Parameters:

sendOnMetadata - true to send onMetadata event

---



---

## isSendOnMetadata

```
public boolean isSendOnMetadata()
```

Get to send onMetadata event when stream starts

**Returns:**

true to send onMetadata event

## com.wowza.wms.stream.publish Interface IStreamActionNotify

public interface **IStreamActionNotify**  
extends

IStreamActionNotify: listener interface to Stream class for playlist items. See Stream.addListener(IStreamActionNotify listener)

### Method Summary

void	<a href="#">onPlaylistItemStart</a> ( <a href="#">Stream</a> stream, <a href="#">PlaylistItem</a> playlistItem) Invoked when playlist item playback is started
void	<a href="#">onPlaylistItemStop</a> ( <a href="#">Stream</a> stream, <a href="#">PlaylistItem</a> playlistItem) Invoked when playlist item playback has ended

### Methods

#### onPlaylistItemStart

```
public void onPlaylistItemStart(Stream stream,  
    PlaylistItem playlistItem)
```

Invoked when playlist item playback is started

**Parameters:**

stream - stream

playlistItem - playlist item

#### onPlaylistItemStop

```
public void onPlaylistItemStop(Stream stream,  
    PlaylistItem playlistItem)
```

Invoked when playlist item playback has ended

**Parameters:**

stream - stream

playlistItem - playlist item

## com.wowza.wms.stream.publish Class Playlist

java.lang.Object

└─com.wowza.wms.stream.publish.Playlist

public class **Playlist**  
extends Object

### Constructor Summary

public	<a href="#">Playlist</a> (String sName) Class constructor - A simple structure that maintains a list of playlist items.
--------	--

### Method Summary

void	<a href="#">addItem</a> (String sName, int start, int length) Appends an item to this playlist
java.util.List	<a href="#">getItems</a> () Get the items in the playlist (returns a copy of the list)
String	<a href="#">getName</a> () Returns the name of this playlist as defined in the XML definition file
boolean	<a href="#">getRepeat</a> ()
boolean	<a href="#">open</a> ( <a href="#">Stream</a> s) Opens this playlist on the given stream...
void	<a href="#">removeItem</a> (int index) Remove an item from the list
void	<a href="#">setRepeat</a> (boolean repeat)

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### Playlist

public **Playlist**(String sName)

Class constructor - A simple structure that maintains a list of playlist items.

#### Parameters:

sName -- name of playlist - as defined in the XML definition file

## Methods

### getItems

```
public java.util.List getItems()
```

Get the items in the playlist (returns a copy of the list)

**Returns:**

items in the playlist (returns a copy of the list)

### getRepeat

```
public boolean getRepeat()
```

### setRepeat

```
public void setRepeat(boolean repeat)
```

### addItem

```
public void addItem(String sName,  
                    int start,  
                    int length)
```

Appends an item to this playlist

**Parameters:**

sName - - item name

start - - start seconds

length - - playlength seconds

### removeItem

```
public void removeItem(int index)
```

Remove an item from the list

**Parameters:**

index - index of item to remove

### open

```
public boolean open(Stream s)
```

Opens this playlist on the given stream... stopping anything currently playing on that stream and switching over.

**Parameters:**

s - - stream to play on

**Returns:**

- true if successful

## getName

```
public String getName()
```

Returns the name of this playlist as defined in the XML definition file

**Returns:**

name of this playlist

## com.wowza.wms.stream.publish Class PlaylistItem

java.lang.Object

└─com.wowza.wms.stream.publish.PlaylistItem

public class **PlaylistItem**  
extends Object

### Constructor Summary

public	<a href="#">PlaylistItem</a> (String name, int start, int length, int index) Class constructor - A simple structure to define parameters associated with a playlist item
--------	---

### Method Summary

int	<a href="#">getIndex()</a>
int	<a href="#">getLength()</a> Number of seconds of track to play
String	<a href="#">getName()</a> Name of playlist stream
int	<a href="#">getStart()</a> Number of seconds into track to start from
void	<a href="#">setIndex</a> (int index)
String	<a href="#">toString()</a>

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### PlaylistItem

```
public PlaylistItem(String name,  
                    int start,  
                    int length,  
                    int index)
```

Class constructor - A simple structure to define parameters associated with a playlist item

#### Parameters:

name - - name of the playlist stream

start - - number of seconds into the track to start from (-2 means live stream)

(continued from last page)

length -- number of seconds of track to play

index -- index in the playlist

## Methods

### getName

```
public String getName()
```

Name of playlist stream

**Returns:**- name of stream

---

### getStart

```
public int getStart()
```

Number of seconds into track to start from

**Returns:**- number of seconds

---

### getLength

```
public int getLength()
```

Number of seconds of track to play

**Returns:**- number of seconds

---

### getIndex

```
public int getIndex()
```

---

### setIndex

```
public void setIndex(int index)
```

---

### toString

```
public String toString()
```

## com.wowza.wms.stream.publish Class Publisher

java.lang.Object

└─com.wowza.wms.stream.publish.Publisher

---

```
public class Publisher  
extends Object
```

Publisher: clientless stream publisher. This class can be used to publish raw video, audio and metadata packets to the Wowza Pro server. Here is a quick snippet of code that illustrates how to use it.

This code below will publish data the stream named "myStream". It will be streamed to the default virtual host and available at the rtmp address rtmp://[server-ip-address]/streamtest.



```
IVHost vhost = VHostSingleton.getInstance(VHost.VHOST_DEFAULT);
Publisher publisher = Publisher.createInstance(vhost, "streamtest");

publisher.setFileExtension("flv");
publisher.setStreamType("live");

publisher.publish("myStream", "live");

// sit in a loop adding data
boolean done = false;
while(true)
{
    AMFPacket amfPacket;

    // read packet from audio, video, data source
    // amfPacket = readPacketFromSomewhere();

    switch (amfPacket.getType())
    {
        case IVHost.CONTENTTYPE_AUDIO:
            publisher.addAudioData(amfPacket.getData(), amfPacket.getSize(),
amfPacket.getTimecode());
            break;
        case IVHost.CONTENTTYPE_VIDEO:
            publisher.addVideoData(amfPacket.getData(), amfPacket.getSize(),
amfPacket.getTimecode());
            break;
        case IVHost.CONTENTTYPE_DATA:
            publisher.addDataData(amfPacket.getData(), amfPacket.getSize(),
amfPacket.getTimecode());
            break;
    }
    if (done)
        break;
}

publisher.unpublish();
publisher.close();
```

Basic packet format:

Audio:

AAC

[1-byte header]

[1-byte codec config indicator (1 - audio data, 0 - codec config packet)]

[n-bytes audio content or codec config data]

All others

[1-byte header]

[n-bytes audio content]

Below is the bit

layout of the header byte of data (table goes from least significant bit to most significant bit):

1 bit Number of channels:

- 0 mono
- 1 stereo

1 bit Sample size:

- 0 8 bits per sample
- 1 16 bits per sample

2 bits Sample rate:

- 0 special or 8KHz
- 1 11KHz
- 2 22KHz
- 3 44KHz

4 bits Audio type:

- 0 PCM (big endian)
- 1 PCM (swf - ADPCM)
- 2 MP3
- 3 PCM (little endian)
- 4 Nelly Moser ASAO 16KHz Mono
- 5 Nelly Moser ASAO 8KHz Mono
- 6 Nelly Moser ASAO
- 7 G.711 ALaw
- 8 G.711 MULaw
- 9 Reserved
- a AAC
- b Speex
- f MP3 8Khz

Note: For AAC the codec config data is generally a two byte packet that describes the stream. It must

be published first. Here is the basic code to fill in the codec config data.

```
AACFrame frame = new AACFrame();
```

```

int sampleRate = 22100;
int channels = 2;
frame.setSampleRate(sampleRate);
frame.setRateIndex(AACUtils.sampleRateToIndex(sampleRate));
frame.setChannels(channels);
frame.setChannelIndex(AACUtils.channelCountToIndex(sampleRate));
byte[] codecConfig = new byte[2];
AACUtils.encodeAACCodecConfig(frame, codecConfig, 0);

```

Note: For AAC the header byte is always 0xaf

Note: For Speex the audio data must be encoded as 16000Hz wide band

Video:

H.264

```

[1-byte header]
[1-byte codec config indicator (1 - video data, 0 - codec config packet)]
[3-byte time difference between dts and pts in milliseconds]
[n-bytes video content or codec config data]

```

All others

```

[1-byte header]
[n-bytes audio content]

```

Below is the bit layout of the header byte of data (table goes from least significant bit to most significant bit):

4 bits Video type:

- 2    Sorenson Spark (H.263)
- 3    Screen
- 4    On2 VP6
- 5    On2 VP6A
- 6    Screen2
- 7    H.264

2 bit Frame type:

- 1    K frame (key frame)
- 2    P frame
- 3    B frame

Note: H.264 codec config data is the same as the AVCc packet in a QuickTime container.

Note: All timecode data is in milliseconds

## Method Summary

void	<a href="#">addAudioData</a> (byte[] data, int offset, int len, long timecode) Add audio data
void	<a href="#">addAudioData</a> (byte[] data, int len, long timecode) Add audio data
void	<a href="#">addAudioData</a> (byte[] data, long timecode) Add audio data
void	<a href="#">addAudioDataInc</a> (byte[] data, int offset, int len)
void	<a href="#">addDataData</a> (byte[] data, int offset, int len, long timecode) Add metadata
void	<a href="#">addDataData</a> (byte[] data, int len, long timecode) Add metadata
void	<a href="#">addDataData</a> (byte[] data, long timecode) Add metadata
void	<a href="#">addDataDataInc</a> (byte[] data, int offset, int len)
void	<a href="#">addVideoData</a> (byte[] data, int offset, int len, long timecode) Add video data
void	<a href="#">addVideoData</a> (byte[] data, int len, long timecode) Add video data
void	<a href="#">addVideoData</a> (byte[] data, long timecode) Add video data
void	<a href="#">addVideoDataInc</a> (byte[] data, int offset, int len)
void	<a href="#">close</a> () Close the publisher
static <a href="#">Publisher</a>	<a href="#">createInstance</a> ( <a href="#">IApplicationInstance</a> appInstance)
static <a href="#">Publisher</a>	<a href="#">createInstance</a> ( <a href="#">IVHost</a> vhost, String applicationName)
static <a href="#">Publisher</a>	<a href="#">createInstance</a> ( <a href="#">IVHost</a> vhost, String applicationName, String appInstanceName)
void	<a href="#">createStream</a> () Create underlying IMediaStream object if not already created
void	<a href="#">flush</a> () Flush the packets from the input buffer to the output buffer
<a href="#">IApplicationInstance</a>	<a href="#">getAppInstance</a> ()
String	<a href="#">getFileExtension</a> () Get the file extension (default flv)
long	<a href="#">getLastAudioTimecode</a> () Get last audio timecode written through this publisher (milliseconds).

long	<a href="#"><code>getLastDataTimecode()</code></a> Get last data timecode written through this publisher (milliseconds).
long	<a href="#"><code>getLastVideoTimecode()</code></a> Get last video timecode written through this publisher (milliseconds).
long	<a href="#"><code>getMaxTimecode()</code></a> Highest timecode written through this publisher (milliseconds).
<a href="#"><code>IMediaStream</code></a>	<a href="#"><code>getStream()</code></a> Get the media stream object
String	<a href="#"><code>getStreamType()</code></a>
boolean	<a href="#"><code>isPublishDataEvents()</code></a>
void	<a href="#"><code>publish(String streamName)</code></a> Publish a stream (null to stop publishing)
void	<a href="#"><code>publish(String streamName, String howToPublish)</code></a> Start publishing a stream (streamName = null to stop).
void	<a href="#"><code>setFileExtension(String fileExtension)</code></a> Set the file extension
void	<a href="#"><code>setPublishDataEvents(boolean publishDataEvents)</code></a>
void	<a href="#"><code>setStreamType(String streamType)</code></a> Set the stream type (default live)
void	<a href="#"><code>startAudioData(int len, long timecode)</code></a>
void	<a href="#"><code>startDataData(int len, long timecode)</code></a>
void	<a href="#"><code>startVideoData(int len, long timecode)</code></a>
void	<a href="#"><code>unpublish()</code></a>

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Methods

### **createInstance**

```
public static Publisher createInstance(IVHost vhost,
    String applicationName)
```

(continued from last page)

---

## createInstance

```
public static Publisher createInstance(IVHost vhost,  
    String applicationName,  
    String appInstanceName)
```

---

## createInstance

```
public static Publisher createInstance(IApplicationInstance appInstance)
```

---

## getStream

```
public IMediaStream getStream()
```

Get the media stream object

**Returns:**

media stream object

---

## getStreamType

```
public String getStreamType()
```

---

## setStreamType

```
public void setStreamType(String streamType)
```

Set the stream type (default live)

**Parameters:**

streamType - stream type

---

## publish

```
public void publish(String streamName)
```

Publish a stream (null to stop publishing)

**Parameters:**

streamName - stream name

---

## getFileExtension

```
public String getFileExtension()
```

Get the file extension (default flv)

**Returns:**

file extension

---

(continued from last page)

---

## setFileExtension

```
public void setFileExtension(String fileExtension)
```

Set the file extension

### Parameters:

fileExtension - file extension

---

## getAppInstance

```
public IApplicationInstance getAppInstance()
```

---

## unpublish

```
public void unpublish()
```

---

## createStream

```
public void createStream()
```

Create underlying IMediaStream object if not already created

---

## publish

```
public void publish(String streamName,  
String howToPublish)
```

Start publishing a stream (streamName = null to stop). Valid howToPublish values are (live, record, append)

### Parameters:

streamName - stream name

howToPublish - publish method (live, record, append)

---

## addVideoData

```
public void addVideoData(byte[] data,  
long timecode)
```

Add video data

### Parameters:

data - data

timecode - absolute timecode (milliseconds)

---

## addVideoData

```
public void addVideoData(byte[] data,  
int len,  
long timecode)
```

Add video data

### Parameters:

data - data

---

(continued from last page)

len - data length  
timecode - absolute timecode (milliseconds)

---

## addVideoData

```
public void addVideoData(byte[] data,  
    int offset,  
    int len,  
    long timecode)
```

Add video data

### Parameters:

data - data  
offset - offset  
len - data length  
timecode - absolute timecode (milliseconds)

---

## startVideoData

```
public void startVideoData(int len,  
    long timecode)
```

---

## addVideoDataInc

```
public void addVideoDataInc(byte[] data,  
    int offset,  
    int len)
```

---

## startAudioData

```
public void startAudioData(int len,  
    long timecode)
```

---

## addAudioDataInc

```
public void addAudioDataInc(byte[] data,  
    int offset,  
    int len)
```

---

## addAudioData

```
public void addAudioData(byte[] data,  
    long timecode)
```

Add audio data

### Parameters:

data - data  
timecode - absolute timecode (milliseconds)

---



(continued from last page)

## addAudioData

```
public void addAudioData(byte[] data,  
    int len,  
    long timecode)
```

Add audio data

### Parameters:

data - data  
len - data length  
timecode - absolute timecode (milliseconds)

---

## addAudioData

```
public void addAudioData(byte[] data,  
    int offset,  
    int len,  
    long timecode)
```

Add audio data

### Parameters:

data - data  
len - data length  
offset - offset  
timecode - absolute timecode (milliseconds)

---

## addDataData

```
public void addDataData(byte[] data,  
    long timecode)
```

Add metadata

### Parameters:

data - data  
timecode - absolute timecode (milliseconds)

---

## addDataData

```
public void addDataData(byte[] data,  
    int len,  
    long timecode)
```

Add metadata

### Parameters:

data - data  
len - data length  
timecode - absolute timecode (milliseconds)

---

## addDataData

```
public void addDataData(byte[] data,  
    int offset,  
    int len,  
    long timecode)
```

Add metadata

(continued from last page)

**Parameters:**

data - data  
offset - offset  
len - data length  
timecode - absolute timecode (milliseconds)

---

**startDataData**

```
public void startDataData(int len,  
    long timecode)
```

---

**addDataDataInc**

```
public void addDataDataInc(byte[] data,  
    int offset,  
    int len)
```

---

**flush**

```
public void flush()
```

Flush the packets from the input buffer to the output buffer

---

**close**

```
public void close()
```

Close the publisher

---

**getMaxTimecode**

```
public long getMaxTimecode()
```

Highest timecode written through this publisher (milliseconds).

**Returns:**

highest timecode written through this publisher (milliseconds)

---

**getLastAudioTimecode**

```
public long getLastAudioTimecode()
```

Get last audio timecode written through this publisher (milliseconds).

**Returns:**

last audio timecode written through this publisher (milliseconds).

---

**getLastVideoTimecode**

```
public long getLastVideoTimecode()
```

Get last video timecode written through this publisher (milliseconds).

**Returns:**

(continued from last page)

last video timecode written through this publisher (milliseconds).

---

## **getLastDataTimecode**

```
public long getLastDataTimecode()
```

Get last data timecode written through this publisher (milliseconds).

### **Returns:**

last data timecode written through this publisher (milliseconds).

---

## **isPublishDataEvents**

```
public boolean isPublishDataEvents()
```

---

## **setPublishDataEvents**

```
public void setPublishDataEvents(boolean publishDataEvents)
```

## com.wowza.wms.stream.publish Class PublishingProviderBase

java.lang.Object

└--com.wowza.wms.stream.publish.PublishingProviderBase

Direct Known Subclasses:

[PublishingProviderMediaReader](#), [PublishingProviderLive](#)

```
public class PublishingProviderBase
extends Object
```

PublishingProviderBase: Base class for publishing providers.

### Field Summary

protected	<a href="#">sendOnMetadata</a>
-----------	--------------------------------

### Constructor Summary

public	<a href="#">PublishingProviderBase()</a>
--------	--

### Method Summary

boolean	<a href="#">isSendOnMetadata()</a> True to send onMetadata event on stream start
void	<a href="#">setSendOnMetadata</a> (boolean sendOnMetadata) True to send onMetadata event on stream start

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Fields

#### sendOnMetadata

protected boolean **sendOnMetadata**

### Constructors

#### PublishingProviderBase

```
public PublishingProviderBase()
```

(continued from last page)

## Methods

### isSendOnMetadata

```
public boolean isSendOnMetadata()
```

True to send onMetadata event on stream start

**Returns:**

True to send onMetadata event on stream start

---

### setSendOnMetadata

```
public void setSendOnMetadata(boolean sendOnMetadata)
```


True to send onMetadata event on stream start

**Parameters:**

sendOnMetadata - True to send onMetadata event on stream start

## com.wowza.wms.stream.publish Class PublishingProviderLive

java.lang.Object



All Implemented Interfaces:

[IPublishingProvider](#)

public class **PublishingProviderLive**

extends [PublishingProviderBase](#)

implements [IPublishingProvider](#)

Fields inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[sendOnMetadata](#)

### Constructor Summary

public	<a href="#">PublishingProviderLive</a> ( <a href="#">Publisher</a> publisher, long timeoffset, String streamName)
--------	---

### Method Summary

void	<a href="#">close</a> ()
long	<a href="#">getDuration</a> ()
long	<a href="#">getStartOnPreviousBufferTime</a> ()
boolean	<a href="#">isStartOnPreviousKeyFrame</a> ()
boolean	<a href="#">isStopIfStreamMissing</a> ()
boolean	<a href="#">play</a> ( <a href="#">Publisher</a> publisher)
boolean	<a href="#">seek</a> (long timecode)
boolean	<a href="#">seek</a> (long timecode, int seekType)
void	<a href="#">setDuration</a> (long duration)
void	<a href="#">setRealTimeStartTime</a> (long realTimeStartTime)
void	<a href="#">setStartOnPreviousBufferTime</a> (long startOnPreviousBufferTime)

void	<a href="#">setStartOnPreviousKeyFrame</a> (boolean startOnPreviousKeyFrame)
void	<a href="#">setStopIfStreamMissing</a> (boolean stopIfStreamMissing)

Methods inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[isSendOnMetadata](#), [setSendOnMetadata](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.stream.publish.IPublishingProvider](#)

[close](#), [isSendOnMetadata](#), [play](#), [seek](#), [seek](#), [setDuration](#), [setRealTimeStartTime](#), [setSendOnMetadata](#)

## Constructors

### PublishingProviderLive

```
public PublishingProviderLive(Publisher publisher,
                             long timeoffset,
                             String streamName)
```

## Methods

### close

```
public void close()
```

### play

```
public boolean play(Publisher publisher)
```

### seek

```
public boolean seek(long timecode)
```

### seek

```
public boolean seek(long timecode,
                    int seekType)
```

---

### **getDuration**

```
public long getDuration()
```

---

### **setDuration**

```
public void setDuration(long duration)
```

---

### **setRealTimeStartTime**

```
public void setRealTimeStartTime(long realTimeStartTime)
```

---

### **isStartOnPreviousKeyFrame**

```
public boolean isStartOnPreviousKeyFrame()
```

---

### **setStartOnPreviousKeyFrame**

```
public void setStartOnPreviousKeyFrame(boolean startOnPreviousKeyFrame)
```

---

### **getStartOnPreviousBufferTime**

```
public long getStartOnPreviousBufferTime()
```

---

### **setStartOnPreviousBufferTime**

```
public void setStartOnPreviousBufferTime(long startOnPreviousBufferTime)
```

---

### **isStopIfStreamMissing**

```
public boolean isStopIfStreamMissing()
```

---

### **setStopIfStreamMissing**


```
public void setStopIfStreamMissing(boolean stopIfStreamMissing)
```

---



## com.wowza.wms.stream.publish Class PublishingProviderMediaReader

java.lang.Object



All Implemented Interfaces:

[IPublishingProvider](#)

public class **PublishingProviderMediaReader**

extends [PublishingProviderBase](#)

implements [IPublishingProvider](#)

PublishingProviderMediaReader: Publishing provider for media reader based stream (vod).

Fields inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[sendOnMetadata](#)

### Constructor Summary

public	<a href="#">PublishingProviderMediaReader</a> ( <a href="#">Publisher</a> publisher, long timeoffset, String streamName) Constructor
--------	---

### Method Summary

void	<a href="#">close</a> ()
long	<a href="#">getDuration</a> () Get the target playback duration (milliseconds)
double	<a href="#">getSpeed</a> ()
boolean	<a href="#">play</a> ( <a href="#">Publisher</a> publisher)
boolean	<a href="#">seek</a> (long timecode)
boolean	<a href="#">seek</a> (long timecode, int seekType)
void	<a href="#">setDuration</a> (long duration)
void	<a href="#">setRealTimeStartTime</a> (long realTimeStartTime)
void	<a href="#">setSpeed</a> (double speed)

Methods inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[isSendOnMetadata](#), [setSendOnMetadata](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.stream.publish.IPublishingProvider](#)

[close](#), [isSendOnMetadata](#), [play](#), [seek](#), [seek](#), [setDuration](#), [setRealTimeStartTime](#), [setSendOnMetadata](#)

## Constructors

### PublishingProviderMediaReader

```
public PublishingProviderMediaReader(Publisher publisher,  
                                     long timeoffset,  
                                     String streamName)
```

Constructor

#### Parameters:

`publisher` - publisher  
`timeoffset` - timeoffset (milliseconds)  
`streamName` - stream name

## Methods

### seek

```
public boolean seek(long timecode)
```

### seek

```
public boolean seek(long timecode,  
                    int seekType)
```

### play

```
public boolean play(Publisher publisher)
```

### close

```
public void close()
```

(continued from last page)

## **getDuration**

```
public long getDuration()
```

Get the target playback duration (milliseconds)

### **Returns:**

playback duration (milliseconds)

---

## **setDuration**

```
public void setDuration(long duration)
```

---

## **setRealTimeStartTime**

```
public void setRealTimeStartTime(long realTimeStartTime)
```

---

## **getSpeed**

```
public double getSpeed()
```

---

## **setSpeed**

```
public void setSpeed(double speed)
```

---

## com.wowza.wms.stream.publish Class Stream

java.lang.Object

└─com.wowza.wms.stream.publish.Stream

All Implemented Interfaces:

Runnable

public class **Stream**  
extends Object  
implements Runnable

### Constructor Summary

public	<a href="#">Stream()</a>
--------	--------------------------

### Method Summary

void	<a href="#">addListener(IStreamActionNotify listener)</a> Add a listener
boolean	<a href="#">addToPlaylist(int index, String name, int start, int length)</a> Inserts a media source item to this playlist at a particular index, without interruption.
boolean	<a href="#">addToPlaylist(String existing, String name, int start, int length)</a> Insert item into playlist just after the first item in the playlist with a given name.
void	<a href="#">close()</a> Call this method when you have finished with the playlist object.
void	<a href="#">closeAndWait()</a> Call this method when you have finished with the playlist object.
static <a href="#">Stream</a>	<a href="#">createInstance(IApplicationInstance appInstance, String sName)</a> Use this to create a named Stream on an application instance.
static <a href="#">Stream</a>	<a href="#">createInstance(IVHost vhost, String applicationName, String sName)</a> Use this to create a named Stream on the default instance (_definst_) of an application on a particular VHost.
static <a href="#">Stream</a>	<a href="#">createInstance(IVHost vhost, String applicationName, String appInstanceName, String sName)</a> Use this to create a named Stream on the non-default instance of an application on a particular VHost.
<a href="#">PlaylistItem</a>	<a href="#">getCurrentItem()</a> Get the currently playing playlist item
Object	<a href="#">getLock()</a> Get the synchronization lock for this interface.

String	<a href="#"><u>getName()</u></a> Returns the name of the playlist stream - the client would play this stream by this name.
java.util.List	<a href="#"><u>getPlaylist()</u></a> Get the current playlist
int	<a href="#"><u>getPollingInterval()</u></a> Get the polling interval (milliseconds)
<a href="#"><u>Publisher</u></a>	<a href="#"><u>getPublisher()</u></a>
boolean	<a href="#"><u>getRepeat()</u></a> Use this to determine if the playlist is auto-repeating
long	<a href="#"><u>getStartLiveOnPreviousBufferTime()</u></a> Get time in milliseconds to go back in live stream buffer to get previous key frame
int	<a href="#"><u>getTimeOffsetBetweenItems()</u></a> Get time in milliseconds to add to stream time between playlist items (default is zero)
double	<a href="#"><u>getVODSpeed()</u></a>
boolean	<a href="#"><u>isMoveToNextIfLiveStreamMissing()</u></a> If true, will move to next playlist item if live stream is missing or is unpublished.
boolean	<a href="#"><u>isSendOnMetadata()</u></a> True if sending onMetadata events
boolean	<a href="#"><u>isStartLiveOnPreviousKeyFrame()</u></a> Set to true to start live streams on most recent key frame (smoother switching)
boolean	<a href="#"><u>isSwitchLog()</u></a> Log when a playlist switch occurs
boolean	<a href="#"><u>isTimesInMilliseconds()</u></a> If true start time and duration and are milliseconds.
boolean	<a href="#"><u>isUnpublishOnEnd()</u></a> If true, stop publishing if end of playlist and repeat is false
void	<a href="#"><u>next()</u></a>
void	<a href="#"><u>next(int n)</u></a>
void	<a href="#"><u>play(int n)</u></a>
boolean	<a href="#"><u>play(String sPlaylist)</u></a> Add a media item to the playlist as defined by an XML file ..
boolean	<a href="#"><u>play(String name, int start, int length, boolean reset)</u></a> Adds a media source item to this playlist -
void	<a href="#"><u>previous()</u></a>
void	<a href="#"><u>previous(int n)</u></a>

boolean	<a href="#"><code>removeFromPlaylist(int index)</code></a> Remove item from playlist based on index.
boolean	<a href="#"><code>removeFromPlaylist(String name)</code></a> Remove all items matching the given stream name from the playlist.
void	<a href="#"><code>removeListener(IStreamActionNotify listener)</code></a> Remove a listener
void	<a href="#"><code>run()</code></a> Overridden from class Runnable ....
void	<a href="#"><code>setMoveToNextIfLiveStreamMissing(boolean moveToNextIfLiveStreamMissing)</code></a> If true, will move to next playlist item if live stream is missing or is unpublished.
void	<a href="#"><code>setPollingInterval(int pollingInterval)</code></a> Set the polling interval (milliseconds)
void	<a href="#"><code>setRepeat(boolean repeat)</code></a> Use this to make the playlist repeat or not...
void	<a href="#"><code>setSendOnMetadata(boolean sendOnMetadata)</code></a> True if sending onMetadata events
void	<a href="#"><code>setStartLiveOnPreviousBufferTime(long startLiveOnPreviousBufferTime)</code></a> Set time in milliseconds to go back in live stream buffer to get previous key frame
void	<a href="#"><code>setStartLiveOnPreviousKeyFrame(boolean startLiveOnPreviousKeyFrame)</code></a> Set to true to start live streams on most recent key frame (smoother switching)
void	<a href="#"><code>setSwitchLog(boolean switchLog)</code></a> Log when a playlist switch occurs
void	<a href="#"><code>setTimeOffsetBetweenItems(int timeOffsetBetweenItems)</code></a> Set time in milliseconds to add to stream time between playlist items (default is zero)
void	<a href="#"><code>setTimesInMilliseconds(boolean timesInMilliseconds)</code></a> If true start time and duration and are milliseconds.
void	<a href="#"><code>setUnpublishOnEnd(boolean stopOnEnd)</code></a> If true, stop publishing if end of playlist and repeat is false
void	<a href="#"><code>setVODSpeed(double vodSpeed)</code></a>

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

#### Methods inherited from interface java.lang.Runnable

run

## Constructors

(continued from last page)

## Stream

```
public Stream()
```

## Methods

### createInstance

```
public static Stream createInstance(IVHost vhost,  
    String applicationName,  
    String sName)
```

Use this to create a named Stream on the default instance (\_definst\_) of an application on a particular VHost.

**Parameters:**

vhost -- Virtual Host  
applicationName -- Application name  
sName -- Name of Stream

**Returns:**

stream interface

---

### createInstance

```
public static Stream createInstance(IVHost vhost,  
    String applicationName,  
    String appInstanceName,  
    String sName)
```

Use this to create a named Stream on the non-default instance of an application on a particular VHost.

**Parameters:**

vhost -- Virtual Host  
applicationName -- Application name  
appInstanceName -- Instance name  
sName -- Name of Stream

**Returns:**

stream interface

---

### getLock

```
public Object getLock()
```

Get the synchronization lock for this interface.

**Returns:**

synchronization lock for this interface

---

### createInstance

```
public static Stream createInstance(IApplicationInstance appInstance,  
    String sName)
```

Use this to create a named Stream on an application instance.

**Parameters:**

(continued from last page)

appInstance - - Application instance  
sName - - Name of Stream

**Returns:**

stream interface

---

**run**

```
public void run()
```

Overridden from class Runnable .... do NOT call this directly. This method handles switching between media sources in the playlist.

---

**getPlaylist**

```
public java.util.List getPlaylist()
```

Get the current playlist

**Returns:**

current playlist

---

**getCurrentItem**

```
public PlaylistItem getCurrentItem()
```

Get the currently playing playlist item

**Returns:**

currently playing playlist item

---

**play**

```
public boolean play(String name,  
                    int start,  
                    int length,  
                    boolean reset)
```

Adds a media source item to this playlist -

**Parameters:**

name - - name of media item  
start - - where to start playing the item. (-2 implies play a live stream)  
length - - how much of the item to play (-1 implies play the entire file or live stream)  
reset - - if true, will begin a new playlist, otherwise items are appended

**Returns:**

- returns true if item was added successfully ...otherwise false.

---

**addToPlaylist**

```
public boolean addToPlaylist(int index,  
                             String name,  
                             int start,  
                             int length)
```

Inserts a media source item to this playlist at a particular index, without interruption.

**Parameters:**

index - - insertion index



---

(continued from last page)

name -- name of media item being inserted

start -- where to start playing the item. (-2 implies play a live stream)

length -- how much of the item to play (-1 implies play the entire file or live stream)

**Returns:**

- returns true if item was inserted successfully ...otherwise false. this should not interrupt anything that might be currently playing.... will do nothing if existing item does not exist.. if existing == "" insert at head of list

---

## addToPlaylist

```
public boolean addToPlaylist(String existing,  
    String name,  
    int start,  
    int length)
```

Insert item into playlist just after the first item in the playlist with a given name.

**Parameters:**

existing - name of playlist item in which to insert the item after

name - name of new item

start - where to start playing the item. (-2 implies play a live stream)

length - how much of the item to play (-1 implies play the entire file or live stream)

**Returns:**

true if item inserted

---

## removeFromPlaylist

```
public boolean removeFromPlaylist(int index)
```

Remove item from playlist based on index.

**Parameters:**

index - item index

**Returns:**

true if at least one item from removed

---

## removeFromPlaylist

```
public boolean removeFromPlaylist(String name)
```

Remove all items matching the given stream name from the playlist. If the item is currently being played, it is not removed.

**Parameters:**

name - stream name

**Returns:**

true if at least one item from removed

---

## play

```
public boolean play(String sPlaylist)
```

Add a media item to the playlist as defined by an XML file ..

**Parameters:**

sPlaylist -- the playlist XML definition file

---

---

(continued from last page)

**Returns:**

- returns true if item was added successfully ...otherwise false.

---

**close**

```
public void close()
```

Call this method when you have finished with the playlist object. It will terminate the playlist thread. The playlist object cannot be used after this call.

---

**closeAndWait**

```
public void closeAndWait()
```

Call this method when you have finished with the playlist object. It will terminate the playlist thread. The playlist object cannot be used after this call. This method will wait for the thread to exit.

---

**getName**

```
public String getName()
```

Returns the name of the playlist stream - the client would play this stream by this name.

**Returns:**

- the name of the playlist stream

---

**getRepeat**

```
public boolean getRepeat()
```

Use this to determine if the playlist is auto-repeating

**Returns:**

- true if repeating otherwise false.

---

**setRepeat**

```
public void setRepeat(boolean repeat)
```

Use this to make the playlist repeat or not...

**Parameters:**

repeat - - true to repeat otherwise false

---

**play**

```
public void play(int n)
```

---

**next**

```
public void next(int n)
```

---

(continued from last page)

---

## next

```
public void next()
```

---

## previous

```
public void previous()
```

---

## previous

```
public void previous(int n)
```

---

## getPollingInterval

```
public int getPollingInterval()
```

Get the polling interval (milliseconds)

**Returns:**

polling interval (milliseconds)

---

## setPollingInterval

```
public void setPollingInterval(int pollingInterval)
```

Set the polling interval (milliseconds)

**Parameters:**

pollingInterval - polling interval (milliseconds)

---

## getPublisher

```
public Publisher getPublisher()
```

---

## addListener

```
public void addListener(IStreamActionNotify listener)
```

Add a listener

**Parameters:**

listener - listener

---

## removeListener

```
public void removeListener(IStreamActionNotify listener)
```

Remove a listener

**Parameters:**

(continued from last page)

listener - listener

---

## isSwitchLog

```
public boolean isSwitchLog()
```

Log when a playlist switch occurs

**Returns:**

log when a playlist switch occurs

---

## setSwitchLog

```
public void setSwitchLog(boolean switchLog)
```

Log when a playlist switch occurs

**Parameters:**

switchLog - log when a playlist switch occurs

---

## isSendOnMetadata

```
public boolean isSendOnMetadata()
```

True if sending onMetadata events

**Returns:**

True if sending onMetadata events

---

## setSendOnMetadata

```
public void setSendOnMetadata(boolean sendOnMetadata)
```

True if sending onMetadata events

**Parameters:**

sendOnMetadata - True if sending onMetadata events

---

## isTimesInMilliseconds

```
public boolean isTimesInMilliseconds()
```

If true start time and duration and are milliseconds. If false startTime and duration are in seconds.

**Returns:**

true start time and duration and are milliseconds

---

## setTimesInMilliseconds

```
public void setTimesInMilliseconds(boolean timesInMilliseconds)
```

If true start time and duration and are milliseconds. If false startTime and duration are in seconds.

**Parameters:**

timesInMilliseconds - true start time and duration and are milliseconds

---

(continued from last page)

## isStartLiveOnPreviousKeyFrame

```
public boolean isStartLiveOnPreviousKeyFrame( )
```

Set to true to start live streams on most recent key frame (smoother switching)

**Returns:**

true to start live streams on most recent key frame

---

## setStartLiveOnPreviousKeyFrame

```
public void setStartLiveOnPreviousKeyFrame(boolean startLiveOnPreviousKeyFrame)
```

Set to true to start live streams on most recent key frame (smoother switching)

**Parameters:**

startLiveOnPreviousKeyFrame - true to start live streams on most recent key frame

---

## getStartLiveOnPreviousBufferTime

```
public long getStartLiveOnPreviousBufferTime( )
```

Get time in milliseconds to go back in live stream buffer to get previous key frame

**Returns:**

time in milliseconds to go back in live stream buffer to get previous key frame

---

## setStartLiveOnPreviousBufferTime

```
public void setStartLiveOnPreviousBufferTime(long startLiveOnPreviousBufferTime)
```

Set time in milliseconds to go back in live stream buffer to get previous key frame

**Parameters:**

startLiveOnPreviousBufferTime - time in milliseconds to go back in live stream buffer to get previous key frame

---

## getTimeOffsetBetweenItems

```
public int getTimeOffsetBetweenItems( )
```

Get time in milliseconds to add to stream time between playlist items (default is zero)

**Returns:**

time in milliseconds to add to stream time between playlist items

---

## setTimeOffsetBetweenItems

```
public void setTimeOffsetBetweenItems(int timeOffsetBetweenItems)
```

Set time in milliseconds to add to stream time between playlist items (default is zero)

**Parameters:**

timeOffsetBetweenItems - time in milliseconds to add to stream time between playlist items

---

## isMoveToNextIfLiveStreamMissing

```
public boolean isMoveToNextIfLiveStreamMissing( )
```

(continued from last page)

If true, will move to next playlist item if live stream is missing or is unpublished.

**Returns:**

move to next playlist item if live stream is missing or is unpublished

---

## setMoveToNextIfLiveStreamMissing

```
public void setMoveToNextIfLiveStreamMissing(boolean moveToNextIfLiveStreamMissing)
```

If true, will move to next playlist item if live stream is missing or is unpublished.

**Parameters:**

moveToNextIfLiveStreamMissing - move to next playlist item if live stream is missing or is unpublished

---

## isUnpublishOnEnd

```
public boolean isUnpublishOnEnd()
```

If true, stop publishing if end of playlist and repeat is false

**Returns:**

stop publishing if end of playlist and repeat is false

---

## setUnpublishOnEnd

```
public void setUnpublishOnEnd(boolean stopOnEnd)
```

If true, stop publishing if end of playlist and repeat is false

**Parameters:**

stopOnEnd - stop publishing if end of playlist and repeat is false

---

## getVODSpeed

```
public double getVODSpeed()
```

---

## setVODSpeed

```
public void setVODSpeed(double vodSpeed)
```

---

---

Package

**com.wowza.wms.timedtext.cea608**

## com.wowza.wms.timedtext.cea608 Class ClosedCaptionCEA608Utils

java.lang.Object

└-com.wowza.wms.timedtext.cea608.CEA608Constants

└-com.wowza.wms.timedtext.cea608.ClosedCaptionCEA608Utils

Direct Known Subclasses:

[ClosedCaptionCEA608Utils](#)

```
public class ClosedCaptionCEA608Utils
extends CEA608Constants
```

### Field Summary

public static final	<a href="#">CEA608_EXTENDED_FR_SP_MAP</a>
public static final	<a href="#">CEA608_EXTENDED_NA_MAP</a>
public static final	<a href="#">CEA608_EXTENDED_PORT_GERMAN_DANISH_MAP</a>
public static	<a href="#">CEA608_MUSICAL_NOTE</a>
public static	<a href="#">CEA608_SOLID_BLOCK</a>
public static final	<a href="#">CHANNEL1</a> Value: <b>0</b>
public static final	<a href="#">CHANNEL2</a> Value: <b>1</b>
public static final	<a href="#">COL_0</a> Value: <b>0</b>
public static final	<a href="#">COL_12</a> Value: <b>6</b>
public static final	<a href="#">COL_16</a> Value: <b>8</b>
public static final	<a href="#">COL_20</a> Value: <b>10</b>
public static final	<a href="#">COL_24</a> Value: <b>12</b>



public static final	<a href="#">COL_28</a> Value: <b>14</b>
public static final	<a href="#">COL_4</a> Value: <b>2</b>
public static final	<a href="#">COL_5</a> Value: <b>4</b>
public static final	<a href="#">COL0_BLUE</a> Value: <b>4</b>
public static final	<a href="#">COL0_CYAN</a> Value: <b>6</b>
public static final	<a href="#">COL0_GREEN</a> Value: <b>2</b>
public static final	<a href="#">COL0_HIBYTE</a> Move to set color (high-byte) [channel][row]
public static final	<a href="#">COL0_LOWBYTE</a> Move to set color (low-byte) [color][row]
public static final	<a href="#">COL0_MAGENTA</a> Value: <b>12</b>
public static final	<a href="#">COL0_RED</a> Value: <b>8</b>
public static final	<a href="#">COL0_WHITE</a> Value: <b>0</b>
public static final	<a href="#">COL0_YELLOW</a> Value: <b>10</b>
public static final	<a href="#">COLN_LOWBYTE</a>
public static final	<a href="#">CONTROLCODES_AOF</a> AOF Reserved (formerly Alarm Off) [channel]
public static final	<a href="#">CONTROLCODES_AON</a> AON Reserved (formerly Alarm On) [channel]
public static final	<a href="#">CONTROLCODES_BAO</a> BAO Background Black, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BAS</a> BAS Background Black, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BBO</a> BBO Background Blue, Opaque [channel]

public static final	<a href="#">CONTROLCODES_BBS</a> BBS Background Blue, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BCO</a> BCO Background Cyan, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BCS</a> BCS Background Cyan, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BGO</a> BGO Background Green, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BGS</a> BGS Background Green, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BMO</a> BMO Background Magenta, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BMS</a> BMS Background Magenta, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BRO</a> BRO Background Red, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BRS</a> BRS Background Red, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BS</a> BS Backspace [channel]
public static final	<a href="#">CONTROLCODES_BT</a> BT Background Transparent [channel]
public static final	<a href="#">CONTROLCODES_BWO</a> BWO Background White, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BWS</a> BWS Background White, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_BYO</a> BYO Background Yellow, Opaque [channel]
public static final	<a href="#">CONTROLCODES_BYS</a> BYS Background Yellow, Semi-transparent [channel]
public static final	<a href="#">CONTROLCODES_CR</a> CR Carriage Return [channel]
public static final	<a href="#">CONTROLCODES_DER</a> DER Delete to End of Row [channel]
public static final	<a href="#">CONTROLCODES_EDM</a> EDM Erase Displayed Memory [channel]
public static final	<a href="#">CONTROLCODES_ENM</a> ENM Erase Non-Displayed Memory [channel]
public static final	<a href="#">CONTROLCODES_EOC</a> EOC End of Caption (Flip Memories) [channel]

public static final	<a href="#"><u>CONTROLCODES_FA</u></a> FA Foreground Black [channel]
public static final	<a href="#"><u>CONTROLCODES_FAU</u></a> FAU Foreground Black Underline [channel]
public static final	<a href="#"><u>CONTROLCODES_FON</u></a> FON Flash On [channel]
public static final	<a href="#"><u>CONTROLCODES_RCL</u></a> RCL Resume caption loading [channel]
public static final	<a href="#"><u>CONTROLCODES_RDC</u></a> RDC Resume Direct Captioning [channel]
public static final	<a href="#"><u>CONTROLCODES_RTD</u></a> RTD Resume Text Display [channel]
public static final	<a href="#"><u>CONTROLCODES_RU2</u></a> RU2 Roll-Up Captions-2 Rows [channel]
public static final	<a href="#"><u>CONTROLCODES_RU3</u></a> RU3 Roll-Up Captions-3 Rows [channel]
public static final	<a href="#"><u>CONTROLCODES_RU4</u></a> RU4 Roll-Up Captions-4 Rows [channel]
public static final	<a href="#"><u>CONTROLCODES_TO1</u></a> TO1 Tab Offset 1 Column [channel]
public static final	<a href="#"><u>CONTROLCODES_TO2</u></a> TO2 Tab Offset 2 Columns [channel]
public static final	<a href="#"><u>CONTROLCODES_TO3</u></a> TO3 Tab Offset 3 Columns [channel]
public static final	<a href="#"><u>CONTROLCODES_TR</u></a> TR Text Restart [channel]
public static final	<a href="#"><u>COUNT_COLS</u></a> Total number of columns per frame Value: <b>31</b>
public static final	<a href="#"><u>COUNT_ROWS</u></a> Total number of rows of characters per frame Value: <b>15</b>
public static final	<a href="#"><u>DONOTHING_BYTE</u></a> Value: <b>-128</b>
public static final	<a href="#"><u>DONOTHING_SHORT</u></a> Value: <b>-32640</b>
public static final	<a href="#"><u>FORMAT_COLOR</u></a>
public static final	<a href="#"><u>FORMAT_FLASH</u></a> Value: <b>-27480</b>

public static final	<a href="#"><u>FORMAT_ITALICS</u></a> Value: <b>-28242</b>
public static final	<a href="#"><u>FORMAT_ITALICS_UNDERLINE</u></a> Value: <b>-28369</b>
public static final	<a href="#"><u>LANG_ASCII</u></a> Select the standard line 21 character set in normal size.
public static final	<a href="#"><u>LANG_ASCII_DBL</u></a> Select the standard line 21 character set in double size.
public static final	<a href="#"><u>LANG_GB231280</u></a> Select the People's Republic of China character set: GB 2312-80.
public static final	<a href="#"><u>LANG_KSC56011987</u></a> Select the Korean Standard character set: KSC 5601-1987.
public static final	<a href="#"><u>LANG_PRIV1</u></a> Select the first private character set.
public static final	<a href="#"><u>LANG_PRIV2</u></a> Select the second private character set.
public static final	<a href="#"><u>LANG_REG1</u></a> Select the first registered character set.
public static final	<a href="#"><u>MAX_CCCOUNT</u></a> Maximum number of closed caption codes per SEI packet Value: <b>31</b>
public static final	<a href="#"><u>ODDPARITY</u></a> Odd parity calculator
public static final	<a href="#"><u>SEI_PAYLOADTYPE</u></a> Value: <b>4</b>
public static final	<a href="#"><u>SEI_STARTCODE</u></a> SEI start code
public static final	<a href="#"><u>SEI_USERDATATYPECODE</u></a> Value: <b>3</b>
public static final	<a href="#"><u>UTF8_BRITISH_POUND</u></a> Value: <b>163</b>
public static final	<a href="#"><u>UTF8_BULLET</u></a> Value: <b>8226</b>
public static final	<a href="#"><u>UTF8_CENTS</u></a> Value: <b>162</b>
public static final	<a href="#"><u>UTF8_CLOSING_DOUBLE_QUOTE</u></a> Value: <b>8221</b>

public static final	<a href="#"><u>UTF8_CLOSING_GUILLEMETS</u></a> Value: <b>187</b>
public static final	<a href="#"><u>UTF8_CONNECTING_VERTICAL_BAR</u></a> Value: <b>9474</b>
public static final	<a href="#"><u>UTF8_COPYRIGHT</u></a> Value: <b>169</b>
public static final	<a href="#"><u>UTF8_CURRENCY</u></a> Value: <b>164</b>
public static final	<a href="#"><u>UTF8_DASH</u></a> Value: <b>45</b>
public static final	<a href="#"><u>UTF8_DEGREE</u></a> Value: <b>176</b>
public static final	<a href="#"><u>UTF8_DOUBLEQUOTE</u></a> Value: <b>34</b>
public static final	<a href="#"><u>UTF8_EM_DASH</u></a> Value: <b>8212</b>
public static final	<a href="#"><u>UTF8_EXCLAMATION</u></a> Value: <b>33</b>
public static final	<a href="#"><u>UTF8_GREATERTHAN</u></a> Value: <b>62</b>
public static final	<a href="#"><u>UTF8_INVERTED_EXCLAMATION</u></a> Value: <b>161</b>
public static final	<a href="#"><u>UTF8_LEFT_SINGLE_QUOTATION</u></a> Value: <b>8216</b>
public static final	<a href="#"><u>UTF8_LEFTPAREN</u></a> Value: <b>40</b>
public static final	<a href="#"><u>UTF8_LESSTHAN</u></a> Value: <b>60</b>
public static final	<a href="#"><u>UTF8_LOWER_A</u></a> Value: <b>97</b>
public static final	<a href="#"><u>UTF8_LOWER_A_WITH_CIRCUMFLEX</u></a> Value: <b>226</b>

public static final	<a href="#"><u>UTF8_LOWER_A_WITH_DIAERESIS</u></a> Value: <b>228</b>
public static final	<a href="#"><u>UTF8_LOWER_A_WITH_GRAVE</u></a> Value: <b>224</b>
public static final	<a href="#"><u>UTF8_LOWER_A_WITH_RING</u></a> Value: <b>229</b>
public static final	<a href="#"><u>UTF8_LOWER_A_WITH_TILDE</u></a> Value: <b>227</b>
public static final	<a href="#"><u>UTF8_LOWER_B</u></a> Value: <b>98</b>
public static final	<a href="#"><u>UTF8_LOWER_C</u></a> Value: <b>99</b>
public static final	<a href="#"><u>UTF8_LOWER_D</u></a> Value: <b>100</b>
public static final	<a href="#"><u>UTF8_LOWER_E</u></a> Value: <b>101</b>
public static final	<a href="#"><u>UTF8_LOWER_E_WITH_CIRCUMFLEX</u></a> Value: <b>234</b>
public static final	<a href="#"><u>UTF8_LOWER_E_WITH_DIAERESIS</u></a> Value: <b>235</b>
public static final	<a href="#"><u>UTF8_LOWER_E_WITH_GRAVE</u></a> Value: <b>232</b>
public static final	<a href="#"><u>UTF8_LOWER_F</u></a> Value: <b>102</b>
public static final	<a href="#"><u>UTF8_LOWER_G</u></a> Value: <b>103</b>
public static final	<a href="#"><u>UTF8_LOWER_H</u></a> Value: <b>104</b>
public static final	<a href="#"><u>UTF8_LOWER_I</u></a> Value: <b>105</b>
public static final	<a href="#"><u>UTF8_LOWER_I_WITH_CIRCUMFLEX</u></a> Value: <b>238</b>

public static final	<a href="#">UTF8_LOWER_I_WITH_DIAERESIS</a> Value: <b>239</b>
public static final	<a href="#">UTF8_LOWER_I_WITH_GRAVE</a> Value: <b>236</b>
public static final	<a href="#">UTF8_LOWER_J</a> Value: <b>106</b>
public static final	<a href="#">UTF8_LOWER_K</a> Value: <b>107</b>
public static final	<a href="#">UTF8_LOWER_L</a> Value: <b>108</b>
public static final	<a href="#">UTF8_LOWER_M</a> Value: <b>109</b>
public static final	<a href="#">UTF8_LOWER_N</a> Value: <b>110</b>
public static final	<a href="#">UTF8_LOWER_O</a> Value: <b>111</b>
public static final	<a href="#">UTF8_LOWER_O_WITH_CIRCUMFLEX</a> Value: <b>244</b>
public static final	<a href="#">UTF8_LOWER_O_WITH_DIAERESIS</a> Value: <b>246</b>
public static final	<a href="#">UTF8_LOWER_O_WITH_GRAVE</a> Value: <b>242</b>
public static final	<a href="#">UTF8_LOWER_O_WITH_STROKE</a> Value: <b>248</b>
public static final	<a href="#">UTF8_LOWER_O_WITH_TILDE</a> Value: <b>245</b>
public static final	<a href="#">UTF8_LOWER_P</a> Value: <b>112</b>
public static final	<a href="#">UTF8_LOWER_Q</a> Value: <b>113</b>
public static final	<a href="#">UTF8_LOWER_R</a> Value: <b>114</b>

public static final	<a href="#"><u>UTF8_LOWER_S</u></a> Value: <b>115</b>
public static final	<a href="#"><u>UTF8_LOWER_T</u></a> Value: <b>116</b>
public static final	<a href="#"><u>UTF8_LOWER_U</u></a> Value: <b>117</b>
public static final	<a href="#"><u>UTF8_LOWER_U_WITH_CIRCUMFLEX</u></a> Value: <b>251</b>
public static final	<a href="#"><u>UTF8_LOWER_U_WITH_DIAERESIS</u></a> Value: <b>252</b>
public static final	<a href="#"><u>UTF8_LOWER_U_WITH_GRAVE</u></a> Value: <b>249</b>
public static final	<a href="#"><u>UTF8_LOWER_V</u></a> Value: <b>118</b>
public static final	<a href="#"><u>UTF8_LOWER_W</u></a> Value: <b>119</b>
public static final	<a href="#"><u>UTF8_LOWER_X</u></a> Value: <b>120</b>
public static final	<a href="#"><u>UTF8_LOWER_Y</u></a> Value: <b>121</b>
public static final	<a href="#"><u>UTF8_LOWER_Z</u></a> Value: <b>122</b>
public static final	<a href="#"><u>UTF8_MINUSHYPHEN</u></a> Value: <b>45</b>
public static final	<a href="#"><u>UTF8_MUSICAL_NOTE</u></a> Value: <b>9834</b>
public static final	<a href="#"><u>UTF8_NBSP</u></a> Value: <b>160</b>
public static final	<a href="#"><u>UTF8_NOTMATCH</u></a>
public static final	<a href="#"><u>UTF8_ONE_HALF</u></a> Value: <b>189</b>



public static final	<a href="#"><u>UTF8_OPENING_DOUBLE_QUOTE</u></a> Value: <b>8220</b>
public static final	<a href="#"><u>UTF8_OPENING_GUILLEMETS</u></a> Value: <b>171</b>
public static final	<a href="#"><u>UTF8_PERIOD</u></a> Value: <b>46</b>
public static final	<a href="#"><u>UTF8_PIPE</u></a> Value: <b>124</b>
public static final	<a href="#"><u>UTF8_QUESTION</u></a> Value: <b>63</b>
public static final	<a href="#"><u>UTF8_REGISTERED_MARK</u></a> Value: <b>174</b>
public static final	<a href="#"><u>UTF8_REVERSE_QUERY</u></a> Value: <b>191</b>
public static final	<a href="#"><u>UTF8_RIGHTPAREN</u></a> Value: <b>41</b>
public static final	<a href="#"><u>UTF8_SERVICE_MARK</u></a> Value: <b>8480</b>
public static final	<a href="#"><u>UTF8_SINGLEQUOTE</u></a> Value: <b>39</b>
public static final	<a href="#"><u>UTF8_SPACE</u></a> Value: <b>32</b>
public static final	<a href="#"><u>UTF8_TRADEMARK</u></a> Value: <b>8482</b>
public static final	<a href="#"><u>UTF8_UNDERSCORE</u></a> Value: <b>84</b>
public static final	<a href="#"><u>UTF8_UPPER_A</u></a> Value: <b>65</b>
public static final	<a href="#"><u>UTF8_UPPER_A_WITH_ACUTE</u></a> Value: <b>193</b>
public static final	<a href="#"><u>UTF8_UPPER_A_WITH_CURCUMFLEX</u></a> Value: <b>194</b>

public static final	<a href="#"><u>UTF8_UPPER_A_WITH_DIAERESIS</u></a> Value: <b>196</b>
public static final	<a href="#"><u>UTF8_UPPER_A_WITH_GRAVE</u></a> Value: <b>192</b>
public static final	<a href="#"><u>UTF8_UPPER_A_WITH_RING</u></a> Value: <b>197</b>
public static final	<a href="#"><u>UTF8_UPPER_A_WITH_TILDE</u></a> Value: <b>195</b>
public static final	<a href="#"><u>UTF8_UPPER_B</u></a> Value: <b>66</b>
public static final	<a href="#"><u>UTF8_UPPER_C</u></a> Value: <b>67</b>
public static final	<a href="#"><u>UTF8_UPPER_C_WITH_CEDILLA</u></a> Value: <b>199</b>
public static final	<a href="#"><u>UTF8_UPPER_D</u></a> Value: <b>68</b>
public static final	<a href="#"><u>UTF8_UPPER_E</u></a> Value: <b>69</b>
public static final	<a href="#"><u>UTF8_UPPER_E_WITH_ACUTE</u></a> Value: <b>201</b>
public static final	<a href="#"><u>UTF8_UPPER_E_WITH_CIRCUMFLEX</u></a> Value: <b>202</b>
public static final	<a href="#"><u>UTF8_UPPER_E_WITH_DIAERESIS</u></a> Value: <b>203</b>
public static final	<a href="#"><u>UTF8_UPPER_E_WITH_GRAVE</u></a> Value: <b>200</b>
public static final	<a href="#"><u>UTF8_UPPER_F</u></a> Value: <b>70</b>
public static final	<a href="#"><u>UTF8_UPPER_G</u></a> Value: <b>71</b>
public static final	<a href="#"><u>UTF8_UPPER_H</u></a> Value: <b>72</b>

public static final	<a href="#"><u>UTF8_UPPER_I</u></a> Value: <b>73</b>
public static final	<a href="#"><u>UTF8_UPPER_I_WITH_CIRCUMFLEX</u></a> Value: <b>206</b>
public static final	<a href="#"><u>UTF8_UPPER_I_WITH_DIAERESIS</u></a> Value: <b>207</b>
public static final	<a href="#"><u>UTF8_UPPER_I_WITH_GRAVE</u></a> Value: <b>204</b>
public static final	<a href="#"><u>UTF8_UPPER_I_WITH_TILDE</u></a> Value: <b>205</b>
public static final	<a href="#"><u>UTF8_UPPER_J</u></a> Value: <b>74</b>
public static final	<a href="#"><u>UTF8_UPPER_K</u></a> Value: <b>75</b>
public static final	<a href="#"><u>UTF8_UPPER_L</u></a> Value: <b>76</b>
public static final	<a href="#"><u>UTF8_UPPER_M</u></a> Value: <b>77</b>
public static final	<a href="#"><u>UTF8_UPPER_N</u></a> Value: <b>78</b>
public static final	<a href="#"><u>UTF8_UPPER_O</u></a> Value: <b>79</b>
public static final	<a href="#"><u>UTF8_UPPER_O_WITH_ACUTE</u></a> Value: <b>211</b>
public static final	<a href="#"><u>UTF8_UPPER_O_WITH_CIRCUMFLEX</u></a> Value: <b>212</b>
public static final	<a href="#"><u>UTF8_UPPER_O_WITH_DIAERESIS</u></a> Value: <b>214</b>
public static final	<a href="#"><u>UTF8_UPPER_O_WITH_GRAVE</u></a> Value: <b>210</b>
public static final	<a href="#"><u>UTF8_UPPER_O_WITH_STROKE</u></a> Value: <b>216</b>

public static final	<a href="#"><u>UTF8_UPPER_O_WITH_TILDE</u></a> Value: <b>213</b>
public static final	<a href="#"><u>UTF8_UPPER_P</u></a> Value: <b>80</b>
public static final	<a href="#"><u>UTF8_UPPER_Q</u></a> Value: <b>81</b>
public static final	<a href="#"><u>UTF8_UPPER_R</u></a> Value: <b>82</b>
public static final	<a href="#"><u>UTF8_UPPER_S</u></a> Value: <b>83</b>
public static final	<a href="#"><u>UTF8_UPPER_T</u></a> Value: <b>84</b>
public static final	<a href="#"><u>UTF8_UPPER_U</u></a> Value: <b>85</b>
public static final	<a href="#"><u>UTF8_UPPER_U_WITH_ACUTE</u></a> Value: <b>218</b>
public static final	<a href="#"><u>UTF8_UPPER_U_WITH_CIRCUMFLEX</u></a> Value: <b>219</b>
public static final	<a href="#"><u>UTF8_UPPER_U_WITH_DIAERESIS</u></a> Value: <b>220</b>
public static final	<a href="#"><u>UTF8_UPPER_U_WITH_GRAVE</u></a> Value: <b>217</b>
public static final	<a href="#"><u>UTF8_UPPER_V</u></a> Value: <b>86</b>
public static final	<a href="#"><u>UTF8_UPPER_W</u></a> Value: <b>87</b>
public static final	<a href="#"><u>UTF8_UPPER_X</u></a> Value: <b>88</b>
public static final	<a href="#"><u>UTF8_UPPER_Y</u></a> Value: <b>89</b>
public static final	<a href="#"><u>UTF8_UPPER_Z</u></a> Value: <b>90</b>

public static final	<a href="#">UTF8_YEN</a> Value: <b>165</b>
public static final	<a href="#">UTF8MAP</a>
public static final	<a href="#">UTF8MAP_INDEX_OFFSET</a> Value: <b>32</b>

#### Fields inherited from class com.wowza.wms.timedtext.cea608.CEA608Constants

CC\_CHANNEL\_CC1, CC\_CHANNEL\_CC2, CC\_CHANNEL\_CC3, CC\_CHANNEL\_CC4, CC\_TYPE\_DTVCC\_PACKET\_DATA, CC\_TYPE\_DTVCC\_PACKET\_START, CC\_TYPE\_NTSC\_FIELD\_1, CC\_TYPE\_NTSC\_FIELD\_2

## Constructor Summary

public	<a href="#">ClosedCaptionCEA608Utils()</a>
--------	--

## Method Summary

static byte	<a href="#">calcParity</a> (byte inByte)
static short	<a href="#">calcParity</a> (short inShort)
static char	<a href="#">cea608CharToCharUTF8</a> (short b)
static Character	<a href="#">cea608ExtendedCharacterToUTF8</a> (short command)
static byte[]	<a href="#">charUTF8ToCAE608</a> (CEACaptionConversionContext ceaContext, String text, int pos, String characterSet, int channel)
static byte[]	<a href="#">charUTF8ToCAE608</a> (String text, int pos, String characterSet, int channel)
static boolean	<a href="#">checkParity</a> (byte inByte)
static boolean	<a href="#">checkParity</a> (short inShort)

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Fields

### SEI\_PAYLOADTYPE

public static final byte **SEI\_PAYLOADTYPE**

Constant value: **4**

---

## SEI\_USERDATATYPECODE

```
public static final byte SEI_USERDATATYPECODE
```

Constant value: **3**

---

## UTF8\_BULLET

```
public static final char UTF8_BULLET
```

Constant value: **8226**

---

## UTF8\_CLOSING\_DOUBLE\_QUOTE

```
public static final char UTF8_CLOSING_DOUBLE_QUOTE
```

Constant value: **8221**

---

## UTF8\_CLOSING\_GUILLEMETS

```
public static final char UTF8_CLOSING_GUILLEMETS
```

Constant value: **187**

---

## UTF8\_CONNECTING\_VERTICAL\_BAR

```
public static final char UTF8_CONNECTING_VERTICAL_BAR
```

Constant value: **9474**

---

## UTF8\_COPYRIGHT

```
public static final char UTF8_COPYRIGHT
```

Constant value: **169**

---

## UTF8\_CURRENCY

```
public static final char UTF8_CURRENCY
```

Constant value: **164**

---

## UTF8\_DEGREE

```
public static final char UTF8_DEGREE
```

Constant value: **176**

---

(continued from last page)

---

## UTF8\_EM\_DASH

```
public static final char UTF8_EM_DASH
```

Constant value: **8212**

---

## UTF8\_INVERTED\_EXCLAMATION

```
public static final char UTF8_INVERTED_EXCLAMATION
```

Constant value: **161**

---

## UTF8\_LEFT\_SINGLE\_QUOTATION

```
public static final char UTF8_LEFT_SINGLE_QUOTATION
```

Constant value: **8216**

---

## UTF8\_OPENING\_DOUBLE\_QUOTE

```
public static final char UTF8_OPENING_DOUBLE_QUOTE
```

Constant value: **8220**

---

## UTF8\_OPENING\_GUILLEMETS

```
public static final char UTF8_OPENING_GUILLEMETS
```

Constant value: **171**

---

## UTF8\_REGISTERED\_MARK

```
public static final char UTF8_REGISTERED_MARK
```

Constant value: **174**

---

## UTF8\_SERVICE\_MARK

```
public static final char UTF8_SERVICE_MARK
```

Constant value: **8480**

---

## UTF8\_YEN

```
public static final char UTF8_YEN
```

Constant value: **165**

---

## UTF8\_LOWER\_A\_WITH\_DIAERESIS

```
public static final char UTF8_LOWER_A_WITH_DIAERESIS
```

(continued from last page)

---

Constant value: **228**

---

**UTF8\_LOWER\_A\_WITH\_RING**

```
public static final char UTF8_LOWER_A_WITH_RING
```

Constant value: **229**

---

**UTF8\_LOWER\_A\_WITH\_TILDE**

```
public static final char UTF8_LOWER_A_WITH_TILDE
```

Constant value: **227**

---

**UTF8\_LOWER\_E\_WITH\_DIAERESIS**

```
public static final char UTF8_LOWER_E_WITH_DIAERESIS
```

Constant value: **235**

---

**UTF8\_LOWER\_I\_WITH\_DIAERESIS**

```
public static final char UTF8_LOWER_I_WITH_DIAERESIS
```

Constant value: **239**

---

**UTF8\_LOWER\_I\_WITH\_GRAVE**

```
public static final char UTF8_LOWER_I_WITH_GRAVE
```

Constant value: **236**

---

**UTF8\_LOWER\_O\_WITH\_DIAERESIS**

```
public static final char UTF8_LOWER_O_WITH_DIAERESIS
```

Constant value: **246**

---

**UTF8\_LOWER\_O\_WITH\_GRAVE**

```
public static final char UTF8_LOWER_O_WITH_GRAVE
```

Constant value: **242**

---

**UTF8\_LOWER\_O\_WITH\_STROKE**

```
public static final char UTF8_LOWER_O_WITH_STROKE
```

Constant value: **248**

---



---

## UTF8\_LOWER\_O\_WITH\_TILDE

```
public static final char UTF8_LOWER_O_WITH_TILDE
```

Constant value: **245**

---

## UTF8\_LOWER\_U\_WITH\_DIAERESIS

```
public static final char UTF8_LOWER_U_WITH_DIAERESIS
```

Constant value: **252**

---

## UTF8\_LOWER\_U\_WITH\_GRAVE

```
public static final char UTF8_LOWER_U_WITH_GRAVE
```

Constant value: **249**

---

## UTF8\_UPPER\_A\_WITH\_ACUTE

```
public static final char UTF8_UPPER_A_WITH_ACUTE
```

Constant value: **193**

---

## UTF8\_UPPER\_A\_WITH\_CURCUMFLEX

```
public static final char UTF8_UPPER_A_WITH_CURCUMFLEX
```

Constant value: **194**

---

## UTF8\_UPPER\_A\_WITH\_DIAERESIS

```
public static final char UTF8_UPPER_A_WITH_DIAERESIS
```

Constant value: **196**

---

## UTF8\_UPPER\_A\_WITH\_GRAVE

```
public static final char UTF8_UPPER_A_WITH_GRAVE
```

Constant value: **192**

---

## UTF8\_UPPER\_A\_WITH\_RING

```
public static final char UTF8_UPPER_A_WITH_RING
```

Constant value: **197**

---

(continued from last page)

---

## UTF8\_UPPER\_A\_WITH\_TILDE

```
public static final char UTF8_UPPER_A_WITH_TILDE
```

Constant value: **195**

---

## UTF8\_UPPER\_C\_WITH\_CEDILLA

```
public static final char UTF8_UPPER_C_WITH_CEDILLA
```

Constant value: **199**

---

## UTF8\_UPPER\_E\_WITH\_ACUTE

```
public static final char UTF8_UPPER_E_WITH_ACUTE
```

Constant value: **201**

---

## UTF8\_UPPER\_E\_WITH\_CIRCUMFLEX

```
public static final char UTF8_UPPER_E_WITH_CIRCUMFLEX
```

Constant value: **202**

---

## UTF8\_UPPER\_E\_WITH\_DIAERESIS

```
public static final char UTF8_UPPER_E_WITH_DIAERESIS
```

Constant value: **203**

---

## UTF8\_UPPER\_E\_WITH\_GRAVE

```
public static final char UTF8_UPPER_E_WITH_GRAVE
```

Constant value: **200**

---

## UTF8\_UPPER\_I\_WITH\_CIRCUMFLEX

```
public static final char UTF8_UPPER_I_WITH_CIRCUMFLEX
```

Constant value: **206**

---

## UTF8\_UPPER\_I\_WITH\_DIAERESIS

```
public static final char UTF8_UPPER_I_WITH_DIAERESIS
```

Constant value: **207**

---

## UTF8\_UPPER\_I\_WITH\_GRAVE

```
public static final char UTF8_UPPER_I_WITH_GRAVE
```

---

(continued from last page)

---

Constant value: **204**

---

**UTF8\_UPPER\_I\_WITH\_TILDE**

```
public static final char UTF8_UPPER_I_WITH_TILDE
```

Constant value: **205**

---

**UTF8\_UPPER\_O\_WITH\_ACUTE**

```
public static final char UTF8_UPPER_O_WITH_ACUTE
```

Constant value: **211**

---

**UTF8\_UPPER\_O\_WITH\_CIRCUMFLEX**

```
public static final char UTF8_UPPER_O_WITH_CIRCUMFLEX
```

Constant value: **212**

---

**UTF8\_UPPER\_O\_WITH\_DIAERESIS**

```
public static final char UTF8_UPPER_O_WITH_DIAERESIS
```

Constant value: **214**

---

**UTF8\_UPPER\_O\_WITH\_GRAVE**

```
public static final char UTF8_UPPER_O_WITH_GRAVE
```

Constant value: **210**

---

**UTF8\_UPPER\_O\_WITH\_STROKE**

```
public static final char UTF8_UPPER_O_WITH_STROKE
```

Constant value: **216**

---

**UTF8\_UPPER\_O\_WITH\_TILDE**

```
public static final char UTF8_UPPER_O_WITH_TILDE
```

Constant value: **213**

---

**UTF8\_UPPER\_U\_WITH\_ACUTE**

```
public static final char UTF8_UPPER_U_WITH_ACUTE
```

Constant value: **218**

---

## UTF8\_UPPER\_U\_WITH\_CIRCUMFLEX

```
public static final char UTF8_UPPER_U_WITH_CIRCUMFLEX
```

Constant value: **219**

---

## UTF8\_UPPER\_U\_WITH\_DIAERESIS

```
public static final char UTF8_UPPER_U_WITH_DIAERESIS
```

Constant value: **220**

---

## UTF8\_UPPER\_U\_WITH\_GRAVE

```
public static final char UTF8_UPPER_U_WITH_GRAVE
```

Constant value: **217**

---

## MAX\_CCCOUNT

```
public static final int MAX_CCCOUNT
```

Maximum number of closed caption codes per SEI packet

Constant value: **31**

---

## SEI\_STARTCODE

```
public static final byte SEI_STARTCODE
```

SEI start code

---

## ODDPARITY

```
public static final byte ODDPARITY
```

Odd parity calculator

---

## COL0\_WHITE

```
public static final int COL0_WHITE
```

Constant value: **0**

---

## COL0\_GREEN

```
public static final int COL0_GREEN
```

Constant value: **2**

---

## COL0\_BLUE

```
public static final int COL0_BLUE
```

---

(continued from last page)

Constant value: **4**

---

**COL0\_CYAN**

```
public static final int COL0_CYAN
```

Constant value: **6**

---

**COL0\_RED**

```
public static final int COL0_RED
```

Constant value: **8**

---

**COL0\_YELLOW**

```
public static final int COL0_YELLOW
```

Constant value: **10**

---

**COL0\_MAGENTA**

```
public static final int COL0_MAGENTA
```

Constant value: **12**

---

**CHANNEL1**

```
public static final int CHANNEL1
```

Constant value: **0**

---

**CHANNEL2**

```
public static final int CHANNEL2
```

Constant value: **1**

---

**DONOTHING\_SHORT**

```
public static final short DONOTHING_SHORT
```

Constant value: **-32640**

---

**DONOTHING\_BYTE**

```
public static final byte DONOTHING_BYTE
```

Constant value: **-128**

(continued from last page)

---

## CONTROLCODES\_RCL

```
public static final short CONTROLCODES_RCL
```

RCL Resume caption loading [channel]

---

## CONTROLCODES\_BS

```
public static final short CONTROLCODES_BS
```

BS Backspace [channel]

---

## CONTROLCODES\_AOF

```
public static final short CONTROLCODES_AOF
```

AOF Reserved (formerly Alarm Off) [channel]

---

## CONTROLCODES\_AON

```
public static final short CONTROLCODES_AON
```

AON Reserved (formerly Alarm On) [channel]

---

## CONTROLCODES\_DER

```
public static final short CONTROLCODES_DER
```

DER Delete to End of Row [channel]

---

## CONTROLCODES\_RU2

```
public static final short CONTROLCODES_RU2
```

RU2 Roll-Up Captions-2 Rows [channel]

---

## CONTROLCODES\_RU3

```
public static final short CONTROLCODES_RU3
```

RU3 Roll-Up Captions-3 Rows [channel]

---

## CONTROLCODES\_RU4

```
public static final short CONTROLCODES_RU4
```

RU4 Roll-Up Captions-4 Rows [channel]

---

## CONTROLCODES\_FON

```
public static final short CONTROLCODES_FON
```

FON Flash On [channel]

---

## CONTROLCODES\_RDC

```
public static final short CONTROLCODES_RDC
```

---

(continued from last page)

---

RDC Resume Direct Captioning [channel]

---

## CONTROLCODES\_TR

public static final short **CONTROLCODES\_TR**

TR Text Restart [channel]

---

## CONTROLCODES\_RTD

public static final short **CONTROLCODES\_RTD**

RTD Resume Text Display [channel]

---

## CONTROLCODES\_EDM

public static final short **CONTROLCODES\_EDM**

EDM Erase Displayed Memory [channel]

---

## CONTROLCODES\_CR

public static final short **CONTROLCODES\_CR**

CR Carriage Return [channel]

---

## CONTROLCODES\_ENM

public static final short **CONTROLCODES\_ENM**

ENM Erase Non-Displayed Memory [channel]

---

## CONTROLCODES\_EOC

public static final short **CONTROLCODES\_EOC**

EOC End of Caption (Flip Memories) [channel]

---

## CONTROLCODES\_TO1

public static final short **CONTROLCODES\_TO1**

TO1 Tab Offset 1 Column [channel]

---

## CONTROLCODES\_TO2

public static final short **CONTROLCODES\_TO2**

TO2 Tab Offset 2 Columns [channel]

---

## CONTROLCODES\_TO3

public static final short **CONTROLCODES\_TO3**

TO3 Tab Offset 3 Columns [channel]

---

(continued from last page)

---

## CONTROLCODES\_BWO

```
public static final short CONTROLCODES_BWO
```

BWO Background White, Opaque [channel]

---

## CONTROLCODES\_BWS

```
public static final short CONTROLCODES_BWS
```

BWS Background White, Semi-transparent [channel]

---

## CONTROLCODES\_BGO

```
public static final short CONTROLCODES_BGO
```

BGO Background Green, Opaque [channel]

---

## CONTROLCODES\_BGS

```
public static final short CONTROLCODES_BGS
```

BGS Background Green, Semi-transparent [channel]

---

## CONTROLCODES\_BBO

```
public static final short CONTROLCODES_BBO
```

BBO Background Blue, Opaque [channel]

---

## CONTROLCODES\_BBS

```
public static final short CONTROLCODES_BBS
```

BBS Background Blue, Semi-transparent [channel]

---

## CONTROLCODES\_BCO

```
public static final short CONTROLCODES_BCO
```

BCO Background Cyan, Opaque [channel]

---

## CONTROLCODES\_BCS

```
public static final short CONTROLCODES_BCS
```

BCS Background Cyan, Semi-transparent [channel]

---

## CONTROLCODES\_BRO

```
public static final short CONTROLCODES_BRO
```

BRO Background Red, Opaque [channel]

---

## CONTROLCODES\_BRS

```
public static final short CONTROLCODES_BRS
```

---



(continued from last page)

BRS Background Red, Semi-transparent [channel]

---

## CONTROLCODES\_BYO

public static final short **CONTROLCODES\_BYO**

BYO Background Yellow, Opaque [channel]

---

## CONTROLCODES\_BYS

public static final short **CONTROLCODES\_BYS**

BYS Background Yellow, Semi-transparent [channel]

---

## CONTROLCODES\_BMO

public static final short **CONTROLCODES\_BMO**

BMO Background Magenta, Opaque [channel]

---

## CONTROLCODES\_BMS

public static final short **CONTROLCODES\_BMS**

BMS Background Magenta, Semi-transparent [channel]

---

## CONTROLCODES\_BAO

public static final short **CONTROLCODES\_BAO**

BAO Background Black, Opaque [channel]

---

## CONTROLCODES\_BAS

public static final short **CONTROLCODES\_BAS**

BAS Background Black, Semi-transparent [channel]

---

## CONTROLCODES\_BT

public static final short **CONTROLCODES\_BT**

BT Background Transparent [channel]

---

## CONTROLCODES\_FA

public static final short **CONTROLCODES\_FA**

FA Foreground Black [channel]

---

## CONTROLCODES\_FAU

public static final short **CONTROLCODES\_FAU**

FAU Foreground Black Underline [channel]

(continued from last page)

---

## LANG\_ASCII

public static final short **LANG\_ASCII**

Select the standard line 21 character set in normal size. [channel]

---

## LANG\_ASCII\_DBL

public static final short **LANG\_ASCII\_DBL**

Select the standard line 21 character set in double size. [channel]

---

## LANG\_PRIV1

public static final short **LANG\_PRIV1**

Select the first private character set. [channel]

---

## LANG\_PRIV2

public static final short **LANG\_PRIV2**

Select the second private character set. [channel]

---

## LANG\_GB231280

public static final short **LANG\_GB231280**

Select the People's Republic of China character set: GB 2312-80. [channel]

---

## LANG\_KSC56011987

public static final short **LANG\_KSC56011987**

Select the Korean Standard character set: KSC 5601-1987. [channel]

---

## LANG\_REG1

public static final short **LANG\_REG1**

Select the first registered character set. [channel]

---

## COUNT\_ROWS

public static final int **COUNT\_ROWS**

Total number of rows of characters per frame  
Constant value: **15**

---

## COUNT\_COLS

public static final int **COUNT\_COLS**

Total number of columns per frame  
Constant value: **31**

---

(continued from last page)

---

## COL0\_HIBYTE

```
public static final short COL0_HIBYTE
```

Move to set color (high-byte) [channel][row]

---

## COL0\_LOWBYTE

```
public static final short COL0_LOWBYTE
```

Move to set color (low-byte) [color][row]

---

## COL\_0

```
public static final int COL_0
```

Constant value: **0**

---

## COL\_4

```
public static final int COL_4
```

Constant value: **2**

---

## COL\_5

```
public static final int COL_5
```

Constant value: **4**

---

## COL\_12

```
public static final int COL_12
```

Constant value: **6**

---

## COL\_16

```
public static final int COL_16
```

Constant value: **8**

---

## COL\_20

```
public static final int COL_20
```

Constant value: **10**

---

## COL\_24

```
public static final int COL_24
```

---

(continued from last page)

Constant value: **12**

---

**COL\_28**

```
public static final int COL_28
```

Constant value: **14**

---

**COLN\_LOWBYTE**

```
public static final short COLN_LOWBYTE
```

---

**FORMAT\_COLOR**

```
public static final short FORMAT_COLOR
```

---

**FORMAT\_ITALICS**

```
public static final short FORMAT_ITALICS
```

Constant value: **-28242**

---

**FORMAT\_ITALICS\_UNDERLINE**

```
public static final short FORMAT_ITALICS_UNDERLINE
```

Constant value: **-28369**

---

**FORMAT\_FLASH**

```
public static final short FORMAT_FLASH
```

Constant value: **-27480**

---

**UTF8\_NOTMATCH**

```
public static final byte UTF8_NOTMATCH
```

---

**UTF8\_PERIOD**

```
public static final byte UTF8_PERIOD
```

Constant value: **46**

---

**UTF8\_SINGLEQUOTE**

```
public static final byte UTF8_SINGLEQUOTE
```

(continued from last page)

Constant value: **39**

---

## UTF8\_DOUBLEQUOTE

```
public static final byte UTF8_DOUBLEQUOTE
```

Constant value: **34**

---

## UTF8\_DASH

```
public static final byte UTF8_DASH
```

Constant value: **45**

---

## UTF8\_UNDERSCORE

```
public static final byte UTF8_UNDERSCORE
```

Constant value: **84**

---

## UTF8\_LEFTPAREN

```
public static final byte UTF8_LEFTPAREN
```

Constant value: **40**

---

## UTF8\_RIGHTPAREN

```
public static final byte UTF8_RIGHTPAREN
```

Constant value: **41**

---

## UTF8\_SPACE

```
public static final byte UTF8_SPACE
```

Constant value: **32**

---

## UTF8\_EXCLAMATION

```
public static final byte UTF8_EXCLAMATION
```

Constant value: **33**

---

## UTF8\_QUESTION

```
public static final byte UTF8_QUESTION
```

Constant value: **63**

(continued from last page)

---

## UTF8\_LESSTHAN

public static final byte **UTF8\_LESSTHAN**

Constant value: **60**

---

## UTF8\_GREATERTHAN

public static final byte **UTF8\_GREATERTHAN**

Constant value: **62**

---

## UTF8\_MINUSHYPHEN

public static final byte **UTF8\_MINUSHYPHEN**

Constant value: **45**

---

## UTF8\_PIPE

public static final byte **UTF8\_PIPE**

Constant value: **124**

---

## UTF8\_LOWER\_A

public static final byte **UTF8\_LOWER\_A**

Constant value: **97**

---

## UTF8\_LOWER\_B

public static final byte **UTF8\_LOWER\_B**

Constant value: **98**

---

## UTF8\_LOWER\_C

public static final byte **UTF8\_LOWER\_C**

Constant value: **99**

---

## UTF8\_LOWER\_D

public static final byte **UTF8\_LOWER\_D**

Constant value: **100**

---

## UTF8\_LOWER\_E

public static final byte **UTF8\_LOWER\_E**

---

(continued from last page)

Constant value: **101**

---

**UTF8\_LOWER\_F**public static final byte **UTF8\_LOWER\_F**Constant value: **102**

---

**UTF8\_LOWER\_G**public static final byte **UTF8\_LOWER\_G**Constant value: **103**

---

**UTF8\_LOWER\_H**public static final byte **UTF8\_LOWER\_H**Constant value: **104**

---

**UTF8\_LOWER\_I**public static final byte **UTF8\_LOWER\_I**Constant value: **105**

---

**UTF8\_LOWER\_J**public static final byte **UTF8\_LOWER\_J**Constant value: **106**

---

**UTF8\_LOWER\_K**public static final byte **UTF8\_LOWER\_K**Constant value: **107**

---

**UTF8\_LOWER\_L**public static final byte **UTF8\_LOWER\_L**Constant value: **108**

---

**UTF8\_LOWER\_M**public static final byte **UTF8\_LOWER\_M**Constant value: **109**

---

## UTF8\_LOWER\_N

public static final byte UTF8\_LOWER\_N

Constant value: **110**

---

## UTF8\_LOWER\_O

public static final byte UTF8\_LOWER\_O

Constant value: **111**

---

## UTF8\_LOWER\_P

public static final byte UTF8\_LOWER\_P

Constant value: **112**

---

## UTF8\_LOWER\_Q

public static final byte UTF8\_LOWER\_Q

Constant value: **113**

---

## UTF8\_LOWER\_R

public static final byte UTF8\_LOWER\_R

Constant value: **114**

---

## UTF8\_LOWER\_S

public static final byte UTF8\_LOWER\_S

Constant value: **115**

---

## UTF8\_LOWER\_T

public static final byte UTF8\_LOWER\_T

Constant value: **116**

---

## UTF8\_LOWER\_U

public static final byte UTF8\_LOWER\_U

Constant value: **117**

---



(continued from last page)

---

## UTF8\_LOWER\_V

public static final byte **UTF8\_LOWER\_V**

Constant value: **118**

---

## UTF8\_LOWER\_W

public static final byte **UTF8\_LOWER\_W**

Constant value: **119**

---

## UTF8\_LOWER\_X

public static final byte **UTF8\_LOWER\_X**

Constant value: **120**

---

## UTF8\_LOWER\_Y

public static final byte **UTF8\_LOWER\_Y**

Constant value: **121**

---

## UTF8\_LOWER\_Z

public static final byte **UTF8\_LOWER\_Z**

Constant value: **122**

---

## UTF8\_UPPER\_A

public static final byte **UTF8\_UPPER\_A**

Constant value: **65**

---

## UTF8\_UPPER\_B

public static final byte **UTF8\_UPPER\_B**

Constant value: **66**

---

## UTF8\_UPPER\_C

public static final byte **UTF8\_UPPER\_C**

Constant value: **67**

---

## UTF8\_UPPER\_D

public static final byte **UTF8\_UPPER\_D**

---

(continued from last page)

Constant value: **68**

---

**UTF8\_UPPER\_E**public static final byte **UTF8\_UPPER\_E**Constant value: **69**

---

**UTF8\_UPPER\_F**public static final byte **UTF8\_UPPER\_F**Constant value: **70**

---

**UTF8\_UPPER\_G**public static final byte **UTF8\_UPPER\_G**Constant value: **71**

---

**UTF8\_UPPER\_H**public static final byte **UTF8\_UPPER\_H**Constant value: **72**

---

**UTF8\_UPPER\_I**public static final byte **UTF8\_UPPER\_I**Constant value: **73**

---

**UTF8\_UPPER\_J**public static final byte **UTF8\_UPPER\_J**Constant value: **74**

---

**UTF8\_UPPER\_K**public static final byte **UTF8\_UPPER\_K**Constant value: **75**

---

**UTF8\_UPPER\_L**public static final byte **UTF8\_UPPER\_L**Constant value: **76**

---

## UTF8\_UPPER\_M

public static final byte **UTF8\_UPPER\_M**

Constant value: **77**

---

## UTF8\_UPPER\_N

public static final byte **UTF8\_UPPER\_N**

Constant value: **78**

---

## UTF8\_UPPER\_O

public static final byte **UTF8\_UPPER\_O**

Constant value: **79**

---

## UTF8\_UPPER\_P

public static final byte **UTF8\_UPPER\_P**

Constant value: **80**

---

## UTF8\_UPPER\_Q

public static final byte **UTF8\_UPPER\_Q**

Constant value: **81**

---

## UTF8\_UPPER\_R

public static final byte **UTF8\_UPPER\_R**

Constant value: **82**

---

## UTF8\_UPPER\_S

public static final byte **UTF8\_UPPER\_S**

Constant value: **83**

---

## UTF8\_UPPER\_T

public static final byte **UTF8\_UPPER\_T**

Constant value: **84**

---

(continued from last page)

---

**UTF8\_UPPER\_U**

```
public static final byte UTF8_UPPER_U
```

Constant value: **85**

---

**UTF8\_UPPER\_V**

```
public static final byte UTF8_UPPER_V
```

Constant value: **86**

---

**UTF8\_UPPER\_W**

```
public static final byte UTF8_UPPER_W
```

Constant value: **87**

---

**UTF8\_UPPER\_X**

```
public static final byte UTF8_UPPER_X
```

Constant value: **88**

---

**UTF8\_UPPER\_Y**

```
public static final byte UTF8_UPPER_Y
```

Constant value: **89**

---

**UTF8\_UPPER\_Z**

```
public static final byte UTF8_UPPER_Z
```

Constant value: **90**

---

**UTF8\_LOWER\_A\_WITH\_CIRCUMFLEX**

```
public static final char UTF8_LOWER_A_WITH_CIRCUMFLEX
```

Constant value: **226**

---

**UTF8\_LOWER\_E\_WITH\_CIRCUMFLEX**

```
public static final char UTF8_LOWER_E_WITH_CIRCUMFLEX
```

Constant value: **234**

---

**UTF8\_LOWER\_I\_WITH\_CIRCUMFLEX**

```
public static final char UTF8_LOWER_I_WITH_CIRCUMFLEX
```

---

(continued from last page)

---

Constant value: **238**

---

**UTF8\_LOWER\_O\_WITH\_CIRCUMFLEX**

```
public static final char UTF8_LOWER_O_WITH_CIRCUMFLEX
```

Constant value: **244**

---

**UTF8\_LOWER\_U\_WITH\_CIRCUMFLEX**

```
public static final char UTF8_LOWER_U_WITH_CIRCUMFLEX
```

Constant value: **251**

---

**UTF8\_LOWER\_A\_WITH\_GRAVE**

```
public static final char UTF8_LOWER_A_WITH_GRAVE
```

Constant value: **224**

---

**UTF8\_LOWER\_E\_WITH\_GRAVE**

```
public static final char UTF8_LOWER_E_WITH_GRAVE
```

Constant value: **232**

---

**UTF8\_NBSP**

```
public static final char UTF8_NBSP
```

Constant value: **160**

---

**UTF8\_MUSICAL\_NOTE**

```
public static final char UTF8_MUSICAL_NOTE
```

Constant value: **9834**

---

**UTF8\_BRITISH\_POUND**

```
public static final char UTF8_BRITISH_POUND
```

Constant value: **163**

---

**UTF8\_CENTS**

```
public static final char UTF8_CENTS
```

Constant value: **162**

---

## UTF8\_TRADEMARK

public static final char **UTF8\_TRADEMARK**

Constant value: **8482**

---

## UTF8\_REVERSE\_QUERY

public static final char **UTF8\_REVERSE\_QUERY**

Constant value: **191**

---

## UTF8\_ONE\_HALF

public static final char **UTF8\_ONE\_HALF**

Constant value: **189**

---

## CEA608\_MUSICAL\_NOTE

public static byte **CEA608\_MUSICAL\_NOTE**

---

## CEA608\_SOLID\_BLOCK

public static byte **CEA608\_SOLID\_BLOCK**

---

## UTF8MAP\_INDEX\_OFFSET

public static final int **UTF8MAP\_INDEX\_OFFSET**

Constant value: **32**

---

## UTF8MAP

public static final byte **UTF8MAP**

---

## CEA608\_EXTENDED\_NA\_MAP

public static final char **CEA608\_EXTENDED\_NA\_MAP**

---

## CEA608\_EXTENDED\_FR\_SP\_MAP

public static final char **CEA608\_EXTENDED\_FR\_SP\_MAP**

---

---

## CEA608\_EXTENDED\_PORT\_GERMAN\_DANISH\_MAP

```
public static final char CEA608_EXTENDED_PORT_GERMAN_DANISH_MAP
```

## Constructors

### ClosedCaptionCEA608Utils

```
public ClosedCaptionCEA608Utils()
```

## Methods

### charUTF8ToCAE608

```
public static byte[] charUTF8ToCAE608(CEACaptionConversionContext ceaContext,  
    String text,  
    int pos,  
    String characterSet,  
    int channel)
```

---

### charUTF8ToCAE608

```
public static byte[] charUTF8ToCAE608(String text,  
    int pos,  
    String characterSet,  
    int channel)
```

---

### cea608CharToCharUTF8

```
public static char cea608CharToCharUTF8(short b)
```

---

### calcParity

```
public static byte calcParity(byte inByte)
```

---

### calcParity

```
public static short calcParity(short inShort)
```

---

### checkParity

```
public static boolean checkParity(byte inByte)
```

---

## **checkParity**

```
public static boolean checkParity(short inShort)
```

---

## **cea608ExtendedCharacterToUTF8**

```
public static Character cea608ExtendedCharacterToUTF8(short command)
```



---

Package

**com.wowza.wms.timedtext.model**

## com.wowza.wms.timedtext.model Interface ITimedTextConstants

public interface **ITimedTextConstants**  
extends **ITimedTextPrivateConstants**

### Field Summary

public static final	<a href="#"><u>AMF_TEXTTYPE_ON_TEXT_DATA</u></a> Value: <b>onTextData</b>
public static final	<a href="#"><u>DEFAULT_AMF_CONVERTER_TEXT_TYPE</u></a> Value: <b>onTextData</b>
public static final	<a href="#"><u>DEFAULT_AMF_CONVERTER_TRACK_INDEX</u></a> Value: <b>99</b>
public static final	<a href="#"><u>DEFAULT_CAPTION_CHARACTER_SET</u></a> Default value for Timed Text Property "captionCharacterSet". Value: <b>UTF-8</b>
public static final	<a href="#"><u>DEFAULT_MAXIMUM_CAPTION_DURATION</u></a> Default value for Timed Text Property "maximumCaptionDuration". Value: <b>5000</b>
public static final	<a href="#"><u>DEFAULT_PROPERTY_CAPTION_LANGUAGES</u></a> Default value for Timed Text Property "captionLanguages". Value: <b>*</b>
public static final	<a href="#"><u>DEFAULT_PROPERTY_CAPTION_FILE_NAMING_RULE</u></a> Default value for Timed Text Property "captionFileNamingRule". Value: <b>\${SourceStreamName}.\${FileExtension}</b>
public static final	<a href="#"><u>DEFAULT_PROPERTY_CAPTION_PATH_NAMING_RULE</u></a> Default value for Timed Text Property "captionFileNamingRule". Value: <b>\${SourceBasePath}</b>
public static final	<a href="#"><u>LANGUAGE_ID_ENGLISH</u></a> Value: <b>eng</b>
public static final	<a href="#"><u>LANGUAGE_LOCALE</u></a> Value: <b>locale</b>
public static final	<a href="#"><u>ON_TEXT_DATA</u></a> Value: <b>onTextData</b>
public static final	<a href="#"><u>OUTPUT_TYPE_AMF</u></a> Value: <b>AMF</b>

public static final	<a href="#"><u>OUTPUT_TYPE_CEA608</u></a> Value: <b>CEA608</b>
public static final	<a href="#"><u>OUTPUT_TYPE_TTML</u></a> Value: <b>TTML</b>
public static final	<a href="#"><u>PROP_3GPP_CAPTION_CHARACTER_SET</u></a> Timed Text Property "reader3GPPCaptionCharacterSet": used to determine character set when ingesting TTML captions Overrides general property "captionCharacterSet" Value: <b>reader3GPPCaptionCharacterSet</b>
public static final	<a href="#"><u>PROP_AMF_CONVERTER_INSERT_ERASES_IN_GAPS</u></a> Timed Text Property "amfCaptionConverterInsertErases": insert erase captions if gaps between captions are greater than PROP_MAXIMUM_CAPTION_DURATION Value: <b>amfCaptionConverterInsertErases</b>
public static final	<a href="#"><u>PROP_AMF_CONVERTER_TEXT_TYPE</u></a> Timed Text Property "amfCaptionConverterTextType": AMF text type used in conversion Value: <b>amfCaptionConverterTextType</b>
public static final	<a href="#"><u>PROP_AMF_CONVERTER_TRACK_INDEX</u></a> Timed Text Property "amfCaptionConverterTrackIndex": track index used for captions Value: <b>amfCaptionConverterTrackIndex</b>
public static final	<a href="#"><u>PROP_CAPTION_CHARACTER_SET</u></a> Timed Text Property "captionCharacterSet": used to determine character set when ingesting captions Value: <b>captionCharacterSet</b>
public static final	<a href="#"><u>PROP_CAPTION_FILE_NAMING_RULE</u></a> Timed Text Property "captionFileNamingRule": to change logic determining the caption companion file naming scheme Value: <b>captionFileNamingRule</b>
public static final	<a href="#"><u>PROP_CAPTION_FILENAME_QUERY_PARAMETER</u></a> HTTP Streamer Property "captionFilenameQueryParameter": used for changing query string param used for caption file selection. Value: <b>captionFilenameQueryParameter</b>
public static final	<a href="#"><u>PROP_CAPTION_LANGUAGE_QUERY_PARAMETER</u></a> HTTP Streamer Property "captionLanguageQueryParameter": used for changing query string param used for caption language selection. Value: <b>captionLanguageQueryParameter</b>
public static final	<a href="#"><u>PROP_CAPTION_LANGUAGES</u></a> Timed Text Property "captionLanguages": used to select presented caption Language. Value: <b>captionLanguages</b>
public static final	<a href="#"><u>PROP_CAPTION_PATH_NAMING_RULE</u></a> Timed Text Property "captionPathNamingRule": to change logic determining the caption companion path Value: <b>captionPathNamingRule</b>

public static final	<a href="#"><u>PROP_CEA608_CONVERTER_CHARACTER_SET</u></a> Timed Text Property "cea608CaptionConverterCharacterSet": character set in default CEA caption converter. Value: <b>cea608CaptionConverterCharacterSet</b>
public static final	<a href="#"><u>PROP_CEA608_CONVERTER_CHARS_PER_LINE</u></a> Timed Text Property "cea608CaptionConverterCharsPerLine": max number characters per line in default CEA caption converter. Value: <b>cea608CaptionConverterCharsPerLine</b>
public static final	<a href="#"><u>PROP_CEA608_CONVERTER_COLOR</u></a> Timed Text Property "cea608CaptionConverterColor": color of text in default CEA caption converter. Value: <b>cea608CaptionConverterColor</b>
public static final	<a href="#"><u>PROP_CUPERTINO_CAPTION_LANGUAGES</u></a> Timed Text Property "cupertinoCaptionLanguages": to enabled captionLanguage selection for Cupertino streaming. Value: <b>cupertinoCaptionLanguages</b>
public static final	<a href="#"><u>PROP_CUPERTINO_LIVE_USE_WEBVTT</u></a> Timed Text Property "cupertinoLiveCaptionsUseWebVTT" Value: <b>cupertinoLiveCaptionsUseWebVTT</b>
public static final	<a href="#"><u>PROP_CUPERTINO_VOD_CAPTIONS_ENABLED</u></a> Timed Text Property "cupertinoVODCaptionsEnabled": to enabled VOD captions for Cupertino streaming. Value: <b>cupertinoVODCaptionsEnabled</b>
public static final	<a href="#"><u>PROP_CUPERTINO_VOD_REMOVE_EXISTING_CEA608</u></a> Timed Text Property "cupertinoVODCaptionsRemoveExistingCEA608": if existing VOD has 608, remove them Value: <b>cupertinoVODCaptionsRemoveExistingCEA608</b>
public static final	<a href="#"><u>PROP_CUPERTINO_VOD_USE_WEBVTT</u></a> Timed Text Property "cupertinoVODCaptionsUseWebVTT" Value: <b>cupertinoVODCaptionsUseWebVTT</b>
public static final	<a href="#"><u>PROP_DEBUG_3GPP_CAPTION_PARSER</u></a> Timed Text Property "debug3GPPCaptionParser": adds info level logging regarding the 3GPP parser Value: <b>debug3GPPCaptionParser</b>
public static final	<a href="#"><u>PROP_DEBUG_3GPP_CAPTION_PARSER_TIME</u></a> Timed Text Property "debug3GPPCaptionParserTime": adds info level logging regarding how long it took parser to index Value: <b>debug3GPPCaptionParserTime</b>
public static final	<a href="#"><u>PROP_DEBUG_CUPERTINO_VOD_CAPTION_LANGUAGE_SELECTION</u></a> Timed Text Property "cupertinoDebugVODCaptionLanguageSelection": adds info level logging regarding language selection for Cupertino Streaming Value: <b>cupertinoDebugVODCaptionLanguageSelection</b>
public static final	<a href="#"><u>PROP_DEBUG_CUPERTINO_VOD_CAPTION_PROVIDER_DETERMINATION</u></a> Timed Text Property "cupertinoDebugVODCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset for Cupertino Streaming. Value: <b>cupertinoDebugVODCaptionProviderDetermination</b>

public static final	<a href="#"><u>PROP_DEBUG_LIVE_CAPTION_INGEST</u></a> Timed Text Property "debugCaptionLiveIngest" Value: <b>debugCaptionLiveIngest</b>
public static final	<a href="#"><u>PROP_DEBUG_LIVE_CAPTION_ONTEXTDATA_INGEST</u></a> Timed Text Property "debugCaptionLiveOnTextDataIngest" Value: <b>debugCaptionLiveOnTextDataIngest</b>
public static final	<a href="#"><u>PROP_DEBUG_RTMP_VOD_CAPTION_LANGUAGE_SELECTION</u></a> Timed Text Property "rtmpDebugVODCaptionLanguageSelection": adds info level logging regarding language selection for RTMP Streaming Value: <b>rtmpDebugVODCaptionLanguageSelection</b>
public static final	<a href="#"><u>PROP_DEBUG_RTMP_VOD_CAPTION_PROVIDER_DETERMINATION</u></a> Timed Text Property "rtmpDebugVODCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset for RTMP Streaming. Value: <b>rtmpDebugVODCaptionProviderDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_SANJOSE_VOD_CAPTION_LANGUAGE_SELECTION</u></a> Timed Text Property "sanJoseDebugVODCaptionLanguageSelection": adds info level logging regarding language selection for San Jose Streaming Value: <b>sanJoseDebugVODCaptionLanguageSelection</b>
public static final	<a href="#"><u>PROP_DEBUG_SANJOSE_VOD_CAPTION_PROVIDER_DETERMINATION</u></a> Timed Text Property "sanJoseVODDebugCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset for San Jose Streaming. Value: <b>sanJoseVODDebugCaptionProviderDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_SCC_CAPTION_PARSER</u></a> Timed Text Property "debugSCCCaptionParser": adds info level logging regarding the SCC caption parser Value: <b>debugSCCCaptionParser</b>
public static final	<a href="#"><u>PROP_DEBUG_SCC_CAPTION_PARSER_TIME</u></a> Timed Text Property "debugSCCCaptionParserTime": adds info level logging regarding how long it took parser to index Value: <b>debugSCCCaptionParserTime</b>
public static final	<a href="#"><u>PROP_DEBUG_SCC_VOD_CAPTION_COMPANION_FILES</u></a> Timed Text Property "debugSCCVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for SCC provider Value: <b>debugSCCVODCaptionFileDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_SRT_CAPTION_PARSER</u></a> Timed Text Property "debugSRTCaptionParser": adds info level logging regarding the SRT caption parser Value: <b>debugSRTCaptionParser</b>
public static final	<a href="#"><u>PROP_DEBUG_SRT_CAPTION_PARSER_TIME</u></a> Timed Text Property "debugSRTCaptionParserTime": adds info level logging regarding how long it took parser to index Value: <b>debugSRTCaptionParserTime</b>

public static final	<a href="#"><u>PROP_DEBUG_SRT_VOD_CAPTION_COMPANION_FILES</u></a> Timed Text Property "debugSRTVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for SRT provider Value: <b>debugSRTVODCaptionFileDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_TTML_CAPTION_PARSER</u></a> Timed Text Property "debugTTMLCaptionParser": adds info level logging regarding the TTML caption parser Value: <b>debugTTMLCaptionParser</b>
public static final	<a href="#"><u>PROP_DEBUG_TTML_CAPTION_PARSER_TIME</u></a> Timed Text Property "debugTTMLCaptionParserTime": adds info level logging regarding how long it took parser to index Value: <b>debugTTMLCaptionParserTime</b>
public static final	<a href="#"><u>PROP_DEBUG_TTML_VOD_CAPTION_COMPANION_FILES</u></a> Timed Text Property "debugTTMLVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for TTML Streaming. Value: <b>debugTTMLVODCaptionFileDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_VOD_CAPTION_COMPANION_FILES</u></a> Timed Text Property "debugVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset Value: <b>debugVODCaptionFileDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_VOD_CAPTION_LANGUAGE_SELECTION</u></a> Timed Text Property "debugVODCaptionLanguageSelection": adds info level logging regarding language selection Value: <b>debugVODCaptionLanguageSelection</b>
public static final	<a href="#"><u>PROP_DEBUG_VOD_CAPTION_PROVIDER_DETERMINATION</u></a> Timed Text Property "debugVODCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset Value: <b>debugVODCaptionProviderDetermination</b>
public static final	<a href="#"><u>PROP_DEBUG_WEBVTT_CAPTION_PARSER</u></a> Timed Text Property "debugWebVTTCaptionParser": adds info level logging regarding the WebVTT caption parser Value: <b>debugWebVTTCaptionParser</b>
public static final	<a href="#"><u>PROP_DEBUG_WEBVTT_CAPTION_PARSER_TIME</u></a> Timed Text Property "debugWebVTTCaptionParserTime": adds info level logging regarding how long it took parser to index Value: <b>debugWebVTTCaptionParserTime</b>
public static final	<a href="#"><u>PROP_DEBUG_WEBVTT_VOD_CAPTION_COMPANION_FILES</u></a> Timed Text Property "debugWebVTTVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for WebVTT provider Value: <b>debugWebVTTVODCaptionFileDetermination</b>
public static final	<a href="#"><u>PROP_LIVE_CAPTION_DEFAULT_LANGUAGES</u></a> Timed Text Property "captionLiveIngestLanguages": comma separated ISO-639 language codes determining what languages are expected in the live stream Value: <b>captionLiveIngestLanguages</b>

public static final	<a href="#"><u>PROP_LIVE_CAPTION_INGEST_AMF_ID_STRING</u></a> Timed Text Property "captionLiveIngestAMFIDString": to change AMF identifier from default "onTextData" to something else Value: <b>captionLiveIngestAMFIDString</b>
public static final	<a href="#"><u>PROP_LIVE_CAPTION_INGEST_TYPE</u></a> Timed Text Property "captionLiveIngestType": type of live caption ingestion. Value: <b>captionLiveIngestType</b>
public static final	<a href="#"><u>PROP_LIVE_CAPTION_USE_STREAM_NAME_GROUPS</u></a> Timed Text Property "captionLiveIngestUseStreamNameGroups": to enable use of smil files to determine available languages and ingest type Value: <b>captionLiveIngestUseStreamNameGroups</b>
public static final	<a href="#"><u>PROP_MAXIMUM_CAPTION_DURATION</u></a> Timed Text Property "maximumCaptionDuration": used to determine maximum caption duration Value: <b>maximumCaptionDuration</b>
public static final	<a href="#"><u>PROP_RTMP_CAPTION_LANGUAGES</u></a> Timed Text Property "rtmpCaptionLanguages": to enabled captionLanguage selection for RTMP Type String. Value: <b>rtmpCaptionLanguages</b>
public static final	<a href="#"><u>PROP_RTMP_VOD_CAPTIONS_ENABLED</u></a> Timed Text Property "rtmpVODCaptionsEnabled": to enabled VOD captions for RTMP streaming. Value: <b>rtmpVODCaptionsEnabled</b>
public static final	<a href="#"><u>PROP_SANJOSE_CAPTION_LANGUAGES</u></a> Timed Text Property "sanJoseCaptionLanguages": to enabled captionLanguage selection for San Jose streaming. Value: <b>sanJoseCaptionLanguages</b>
public static final	<a href="#"><u>PROP_SANJOSE_VOD_CAPTIONS_ENABLED</u></a> Timed Text Property "sanJoseVODCaptionsEnabled": to enabled VOD captions for San Jose streaming. Value: <b>sanJoseVODCaptionsEnabled</b>
public static final	<a href="#"><u>PROP_SRT_CAPTION_CHARACTER_SET</u></a> Timed Text Property "srtReaderCaptionCharacterSet": used to determine character set when ingesting SRT captions Overrides general property "captionCharacterSet" Value: <b>srtReaderCaptionCharacterSet</b>
public static final	<a href="#"><u>PROP_TTML_CAPTION_CHARACTER_SET</u></a> Timed Text Property "ttmlReaderCaptionCharacterSet": used to determine character set when ingesting TTML captions Overrides general property "captionCharacterSet" Value: <b>ttmlReaderCaptionCharacterSet</b>
public static final	<a href="#"><u>PROP_TTML_INLINE_TAGS_IN_TEXT</u></a> Timed Text Property "ttmlInlineTagsInText": TTML parser includes in-line styling and line-break tags in the sample text Value: <b>ttmlInlineTagsInText</b>
public static final	<a href="#"><u>PROP_UNDEFINED_LANG_CODE</u></a> Timed Text Property "captionUndefinedLanguageId": if incoming caption language is undefined, use this language ID. Value: <b>captionUndefinedLanguageId</b>

public static final	<a href="#"><u>PROP_VOD_CAPTIONS_ENABLED</u></a> Timed Text Property "vodCaptionsEnabled": to enabled VOD captions for all supported protocols Value: <b>vodCaptionsEnabled</b>
public static final	<a href="#"><u>PROP_WEBVTT_CONVERTER_INSERT_ERASES_IN_GAPS</u></a> Timed Text Property "webVTTCaptionConverterInsertErases": insert erase captions if gaps between captions are greater than PROP_MAXIMUM_CAPTION_DURATION Value: <b>webVTTCaptionConverterInsertErases</b>
public static final	<a href="#"><u>QUERYSTR_CAPTION_FILENAME</u></a> Query string used for choosing caption languages. Value: <b>wowzacaptionfile</b>
public static final	<a href="#"><u>QUERYSTR_CAPTIONLANGUAGES</u></a> Query string used for choosing caption languages. Value: <b>wowzacaptionlanguages</b>
public static final	<a href="#"><u>SMIL_PARAM_IS_WOWZA_CAPTION_STREAM</u></a> Value: <b>iswowzacaptionstream</b>
public static final	<a href="#"><u>SMIL_PARAM_WOWZA_CAPTION_INGEST_TYPE</u></a> Value: <b>wowzacaptioningesttype</b>
public static final	<a href="#"><u>SOURCE_TYPE_3GPP</u></a> Value: <b>3GPP</b>
public static final	<a href="#"><u>SOURCE_TYPE_AMF</u></a> Value: <b>AMF</b>
public static final	<a href="#"><u>SOURCE_TYPE_SCC</u></a> Value: <b>SCC</b>
public static final	<a href="#"><u>SOURCE_TYPE_SRT</u></a> Value: <b>SRT</b>
public static final	<a href="#"><u>SOURCE_TYPE_TTML</u></a> Value: <b>TTML</b>
public static final	<a href="#"><u>SOURCE_TYPE_WEBVTT</u></a> Value: <b>WebVTT</b>
public static final	<a href="#"><u>TIMED_TEXT_TYPE_CAPTION</u></a> Value: <b>Caption</b>

Fields inherited from interface `com.wowza.wms.timedtext.model.ITimedTextPrivateConstants`



```
DEFAULT_AMF_CONVERTER_CLASS, DEFAULT_CEA608_CONVERTER_CLASS,
DEFAULT_CEA608_IDENTITY_CONVERTER_CLASS,
DEFAULT_PROPERTY_CUPERTINO_VOD_CAPTIONS_DELEGATE_CLASS,
DEFAULT_PROPERTY_RTMP_VOD_CAPTIONS_DELEGATE_CLASS,
DEFAULT_PROPERTY_SANJOSE_VOD_CAPTIONS_DELEGATE_CLASS, DEFAULT_TIMED_TEXT_READER_SCC,
DEFAULT_TIMED_TEXT_READER_SRT, DEFAULT_TIMED_TEXT_READER_TTML,
DEFAULT_TIMED_TEXT_READER_WEBVTT, DEFAULT_WEBVTT_CONVERTER_CLASS,
PROP_AMF_CONVERTER_CLASS, PROP_CEA608_CONVERTER_CLASS,
PROP_CEA608_MAX_COMMANDS_PER_FRAME, PROP_CUPERTINO_VOD_CAPTIONS_DELEGATE_CLASS,
PROP_LIVE_ONTEXTDATA_TO_AMF_CONVERTER_CLASS,
PROP_LIVE_ONTEXTDATA_TO_WEBVTT_CONVERTER_CLASS, PROP_MP4_TO_AMF_CONVERTER_CLASS,
PROP_MP4_TO_CEA608_CONVERTER_CLASS, PROP_MP4_TO_WEBVTT_CONVERTER_CLASS,
PROP_RTMP_VOD_CAPTIONS_DELEGATE_CLASS, PROP_SANJOSE_VOD_CAPTIONS_DELEGATE_CLASS,
PROP_SCC_TO_AMF_CONVERTER_CLASS, PROP_SCC_TO_CEA608_CONVERTER_CLASS,
PROP_SCC_TO_WEBVTT_CONVERTER_CLASS, PROP_SRT_TO_AMF_CONVERTER_CLASS,
PROP_SRT_TO_CEA608_CONVERTER_CLASS, PROP_SRT_TO_WEBVTT_CONVERTER_CLASS,
PROP_TTML_TO_AMF_CONVERTER_CLASS, PROP_TTML_TO_CEA608_CONVERTER_CLASS,
PROP_TTML_TO_WEBVTT_CONVERTER_CLASS, PROP_WEBVTT_CONVERTER_CLASS,
PROP_WEBVTT_TO_AMF_CONVERTER_CLASS, PROP_WEBVTT_TO_CEA608_CONVERTER_CLASS,
PROP_WEBVTT_TO_WEBVTT_CONVERTER_CLASS, PROPERTY_SOURCE_DURATION,
PROPERTY_SOURCE_TIME_SCALE, PROPERTY_SOURCE_TRACK_INDEX, TIMED_TEXT_READER_EXTENSION_SCC,
TIMED_TEXT_READER_EXTENSION_SRT, TIMED_TEXT_READER_EXTENSION_TTML,
TIMED_TEXT_READER_EXTENSION_WEBVTT
```

## Fields

### TIMED\_TEXT\_TYPE\_CAPTION

```
public static final java.lang.String TIMED_TEXT_TYPE_CAPTION
```

Constant value: **Caption**

### SOURCE\_TYPE\_AMF

```
public static final java.lang.String SOURCE_TYPE_AMF
```

Constant value: **AMF**

### SOURCE\_TYPE\_TTML

```
public static final java.lang.String SOURCE_TYPE_TTML
```

Constant value: **TTML**

### SOURCE\_TYPE\_3GPP

```
public static final java.lang.String SOURCE_TYPE_3GPP
```

Constant value: **3GPP**

(continued from last page)

---

## SOURCE\_TYPE\_SRT

```
public static final java.lang.String SOURCE_TYPE_SRT
```

Constant value: **SRT**

---

## SOURCE\_TYPE\_SCC

```
public static final java.lang.String SOURCE_TYPE_SCC
```

Constant value: **SCC**

---

## SOURCE\_TYPE\_WEBVTT

```
public static final java.lang.String SOURCE_TYPE_WEBVTT
```

Constant value: **WebVTT**

---

## OUTPUT\_TYPE\_CEA608

```
public static final java.lang.String OUTPUT_TYPE_CEA608
```

Constant value: **CEA608**

---

## OUTPUT\_TYPE\_AMF

```
public static final java.lang.String OUTPUT_TYPE_AMF
```

Constant value: **AMF**

---

## OUTPUT\_TYPE\_TTML

```
public static final java.lang.String OUTPUT_TYPE_TTML
```

Constant value: **TTML**

---

## AMF\_TEXTTYPE\_ON\_TEXT\_DATA

```
public static final java.lang.String AMF_TEXTTYPE_ON_TEXT_DATA
```

Constant value: **onTextData**

---

## LANGUAGE\_LOCALE

```
public static final java.lang.String LANGUAGE_LOCALE
```

Constant value: **locale**

---

## LANGUAGE\_ID\_ENGLISH

```
public static final java.lang.String LANGUAGE_ID_ENGLISH
```

---

(continued from last page)

Constant value: **eng**

---

## PROP\_VOD\_CAPTIONS\_ENABLED

```
public static final java.lang.String PROP_VOD_CAPTIONS_ENABLED
```

Timed Text Property "vodCaptionsEnabled": to enabled VOD captions for all supported protocols

Type boolean. The default is true.

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled on a per protocol basis using [PROP\\_CUPERTINO\\_VOD\\_CAPTIONS\\_ENABLED](#), [PROP\\_RTMP\\_VOD\\_CAPTIONS\\_ENABLED](#), [PROP\\_SANJOSE\\_VOD\\_CAPTIONS\\_ENABLED](#).

Constant value: **vodCaptionsEnabled**

### See Also:

[PROP\\_CUPERTINO\\_VOD\\_CAPTIONS\\_ENABLED](#)

[PROP\\_RTMP\\_VOD\\_CAPTIONS\\_ENABLED](#)

[PROP\\_SANJOSE\\_VOD\\_CAPTIONS\\_ENABLED](#)

---

## PROP\_CUPERTINO\_VOD\_CAPTIONS\_ENABLED

```
public static final java.lang.String PROP_CUPERTINO_VOD_CAPTIONS_ENABLED
```

Timed Text Property "cupertinoVODCaptionsEnabled": to enabled VOD captions for Cupertino streaming.

Type boolean. The default is true.

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled for all protocols using [PROP\\_VOD\\_CAPTIONS\\_ENABLED](#).

Constant value: **cupertinoVODCaptionsEnabled**

### See Also:

[PROP\\_VOD\\_CAPTIONS\\_ENABLED](#)

---

## PROP\_RTMP\_VOD\_CAPTIONS\_ENABLED

```
public static final java.lang.String PROP_RTMP_VOD_CAPTIONS_ENABLED
```

Timed Text Property "rtmpVODCaptionsEnabled": to enabled VOD captions for RTMP streaming.

Type boolean. The default is true.

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled for all protocols using [PROP\\_VOD\\_CAPTIONS\\_ENABLED](#).

Constant value: **rtmpVODCaptionsEnabled**

### See Also:

[PROP\\_VOD\\_CAPTIONS\\_ENABLED](#)

---

## PROP\_SANJOSE\_VOD\_CAPTIONS\_ENABLED

```
public static final java.lang.String PROP_SANJOSE_VOD_CAPTIONS_ENABLED
```

(continued from last page)

Timed Text Property "sanJoseVODCaptionsEnabled": to enabled VOD captions for San Jose streaming.

Type boolean. The default is true.

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled for all protocols using [PROP\\_VOD\\_CAPTIONS\\_ENABLED](#).

Constant value: **sanJoseVODCaptionsEnabled**

See Also:

[PROP\\_VOD\\_CAPTIONS\\_ENABLED](#)

---

## PROP\_CAPTION\_LANGUAGES

```
public static final java.lang.String PROP_CAPTION_LANGUAGES
```

Timed Text Property "captionLanguages": used to select presented caption Language.

Type String. The default is [DEFAULT\\_PROPERTY\\_CAPION\\_LANGUAGES](#)

Add the property to Application/TimedText/Properties in Application.xml

VOD Caption languages can be specified on a per protocol basis using [PROP\\_CUPERTINO\\_CAPTION\\_LANGUAGES](#), [PROP\\_RTMP\\_CAPTION\\_LANGUAGES](#), [PROP\\_SANJOSE\\_CAPTION\\_LANGUAGES](#).

Constant value: **captionLanguages**

See Also:

[PROP\\_CUPERTINO\\_CAPTION\\_LANGUAGES](#)

[PROP\\_RTMP\\_CAPTION\\_LANGUAGES](#)

[PROP\\_SANJOSE\\_CAPTION\\_LANGUAGES](#)

---

## DEFAULT\_PROPERTY\_CAPION\_LANGUAGES

```
public static final java.lang.String DEFAULT_PROPERTY_CAPION_LANGUAGES
```

Default value for Timed Text Property "captionLanguages".

Default value is "\*", meaning present all found languages.

Constant value: **\***

See Also:

[PROP\\_CAPTION\\_LANGUAGES](#)

---

## PROP\_CUPERTINO\_CAPTION\_LANGUAGES

```
public static final java.lang.String PROP_CUPERTINO_CAPTION_LANGUAGES
```

Timed Text Property "cupertinoCaptionLanguages": to enabled captionLanguage selection for Cupertino streaming.

Type String. The default is [DEFAULT\\_PROPERTY\\_CAPION\\_LANGUAGES](#)

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled for all protocols using [PROP\\_CAPTION\\_LANGUAGES](#).

Constant value: **cupertinoCaptionLanguages**

See Also:

[PROP\\_CAPTION\\_LANGUAGES](#)

---

## PROP\_RTMP\_CAPTION\_LANGUAGES

```
public static final java.lang.String PROP_RTMP_CAPTION_LANGUAGES
```

---

(continued from last page)

Timed Text Property "rtmpCaptionLanguages": to enabled captionLanguage selection for RTMP Type String. The default is [DEFAULT\\_PROPERTY\\_CAPION\\_LANGUAGES](#)

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled for all protocols using [PROP\\_CAPTION\\_LANGUAGES](#).  
Constant value: **rtmpCaptionLanguages**

See Also:

[PROP\\_CAPTION\\_LANGUAGES](#)

---

## PROP\_SANJOSE\_CAPTION\_LANGUAGES

```
public static final java.lang.String PROP_SANJOSE_CAPTION_LANGUAGES
```

Timed Text Property "sanJoseCaptionLanguages": to enabled captionLanguage selection for San Jose streaming.

Type String. The default is [DEFAULT\\_PROPERTY\\_CAPION\\_LANGUAGES](#)

Add the property to Application/TimedText/Properties in Application.xml

VOD Captions can be enabled for all protocols using [PROP\\_CAPTION\\_LANGUAGES](#).  
Constant value: **sanJoseCaptionLanguages**

See Also:

[PROP\\_CAPTION\\_LANGUAGES](#)

---

## PROP\_DEBUG\_VOD\_CAPTION\_LANGUAGE\_SELECTION

```
public static final java.lang.String PROP_DEBUG_VOD_CAPTION_LANGUAGE_SELECTION
```

Timed Text Property "debugVODCaptionLanguageSelection": adds info level logging regarding language selection

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Can be enabled on a per protocol basis using [PROP\\_DEBUG\\_CUPERTINO\\_VOD\\_CAPTION\\_LANGUAGE\\_SELECTION](#),  
[PROP\\_DEBUG\\_RTMP\\_VOD\\_CAPTION\\_LANGUAGE\\_SELECTION](#),  
[PROP\\_DEBUG\\_SANJOSE\\_VOD\\_CAPTION\\_LANGUAGE\\_SELECTION](#).  
Constant value: **debugVODCaptionLanguageSelection**

---

## PROP\_DEBUG\_CUPERTINO\_VOD\_CAPTION\_LANGUAGE\_SELECTION

```
public static final java.lang.String  
PROP_DEBUG_CUPERTINO_VOD_CAPTION_LANGUAGE_SELECTION
```

Timed Text Property "cupertinoDebugVODCaptionLanguageSelection": adds info level logging regarding language selection for Cupertino Streaming

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **cupertinoDebugVODCaptionLanguageSelection**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_LANGUAGE\\_SELECTION](#)

---

## PROP\_DEBUG\_RTMP\_VOD\_CAPTION\_LANGUAGE\_SELECTION

```
public static final java.lang.String PROP_DEBUG_RTMP_VOD_CAPTION_LANGUAGE_SELECTION
```

---

(continued from last page)

Timed Text Property "rtmpDebugVODCaptionLanguageSelection": adds info level logging regarding language selection for RTMP Streaming

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **rtmpDebugVODCaptionLanguageSelection**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_LANGUAGE\\_SELECTION](#)

---

## PROP\_DEBUG\_SANJOSE\_VOD\_CAPTION\_LANGUAGE\_SELECTION

```
public static final java.lang.String PROP_DEBUG_SANJOSE_VOD_CAPTION_LANGUAGE_SELECTION
```

Timed Text Property "sanJoseDebugVODCaptionLanguageSelection": adds info level logging regarding language selection for San Jose Streaming

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **sanJoseDebugVODCaptionLanguageSelection**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_LANGUAGE\\_SELECTION](#)

---

## PROP\_DEBUG\_VOD\_CAPTION\_PROVIDER\_DETERMINATION

```
public static final java.lang.String PROP_DEBUG_VOD_CAPTION_PROVIDER_DETERMINATION
```

Timed Text Property "debugVODCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Can be enabled on a per protocol basis using [PROP\\_DEBUG\\_CUPERTINO\\_VOD\\_CAPTION\\_PROVIDER\\_DETERMINATION](#), [PROP\\_DEBUG\\_RTMP\\_VOD\\_CAPTION\\_PROVIDER\\_DETERMINATION](#), [PROP\\_DEBUG\\_SANJOSE\\_VOD\\_CAPTION\\_PROVIDER\\_DETERMINATION](#).

Constant value: **debugVODCaptionProviderDetermination**

---

## PROP\_DEBUG\_CUPERTINO\_VOD\_CAPTION\_PROVIDER\_DETERMINATION

```
public static final java.lang.String  
PROP_DEBUG_CUPERTINO_VOD_CAPTION_PROVIDER_DETERMINATION
```

Timed Text Property "cupertinoDebugVODCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset for Cupertino Streaming.

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **cupertinoDebugVODCaptionProviderDetermination**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_PROVIDER\\_DETERMINATION](#)

---

## PROP\_DEBUG\_RTMP\_VOD\_CAPTION\_PROVIDER\_DETERMINATION

```
public static final java.lang.String  
PROP_DEBUG_RTMP_VOD_CAPTION_PROVIDER_DETERMINATION
```

Timed Text Property "rtmpDebugVODCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset for RTMP Streaming.

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **rtmpDebugVODCaptionProviderDetermination**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_PROVIDER\\_DETERMINATION](#)

---

## PROP\_DEBUG\_SANJOSE\_VOD\_CAPTION\_PROVIDER\_DETERMINATION

```
public static final java.lang.String  
PROP_DEBUG_SANJOSE_VOD_CAPTION_PROVIDER_DETERMINATION
```

Timed Text Property "sanJoseVODDebugCaptionProviderDetermination": adds info level logging regarding caption provider determination for a given VOD asset for San Jose Streaming.

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **sanJoseVODDebugCaptionProviderDetermination**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_PROVIDER\\_DETERMINATION](#)

---

## PROP\_DEBUG\_VOD\_CAPTION\_COMPANION\_FILES

```
public static final java.lang.String PROP_DEBUG_VOD_CAPTION_COMPANION_FILES
```

Timed Text Property "debugVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Can be enabled on a per provider basis as well using [PROP\\_DEBUG\\_TTML\\_VOD\\_CAPTION\\_COMPANION\\_FILES](#)

Constant value: **debugVODCaptionFileDetermination**

---

## PROP\_UNDEFINED\_LANG\_CODE

```
public static final java.lang.String PROP_UNDEFINED_LANG_CODE
```

Timed Text Property "captionUndefinedLanguageId": if incoming caption language is undefined, use this language ID.

Type String. If not defined, the Locale's 3 character language code is used. See `Locale.getDefault().getISO3Language()`

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **captionUndefinedLanguageId**

---

(continued from last page)

## PROP\_CAPTION\_FILE\_NAMING\_RULE

```
public static final java.lang.String PROP_CAPTION_FILE_NAMING_RULE
```

Timed Text Property "captionFileNameRule": to change logic determining the caption companion file naming scheme

Type String. The default value is [DEFAULT\\_PROPERTY\\_CAPTION\\_FILE\\_NAMING\\_RULE](#).

This string is used to find the caption file for a given VOD asset. It is used in conjunction with [PROP\\_CAPTION\\_PATH\\_NAMING\\_RULE](#), which determines the file location.

It is comprised of variables preceded by a dollar sign and enclosed in squiggly brackets. For example: "\${var1}.{var2}"

Valid variables include these:

- \${SourceStreamName} : The baseName of the VOD file
- \${SourceBasePath} : The base path of the VOD asset
- \${FileExtension} : Registered file extensions with the Timed Text Provider

and these standard ones:

- \${com.wowza.wms.context.VHost}
- \${com.wowza.wms.context.VHostConfigHome", appInstance.getVHost().getHomePath()};
- \${com.wowza.wms.context.Application", appInstance.getApplication().getName()};
- \${com.wowza.wms.context.ApplicationInstance", appInstance.getName()};

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **captionFileNameRule**

See Also:

[DEFAULT\\_PROPERTY\\_CAPTION\\_FILE\\_NAMING\\_RULE](#)

---

## DEFAULT\_PROPERTY\_CAPTION\_FILE\_NAMING\_RULE

```
public static final java.lang.String DEFAULT_PROPERTY_CAPTION_FILE_NAMING_RULE
```

Default value for Timed Text Property "captionFileNameRule".

Default value is "\${SourceStreamName}.\${FileExtension}"

Constant value: **\${SourceStreamName}.\${FileExtension}**

See Also:

[PROP\\_CAPTION\\_FILE\\_NAMING\\_RULE](#)

---

## PROP\_CAPTION\_PATH\_NAMING\_RULE

```
public static final java.lang.String PROP_CAPTION_PATH_NAMING_RULE
```



(continued from last page)

Timed Text Property "captionPathNamingRule": to change logic determining the caption companion path

Type String. The default value is [DEFAULT\\_PROPERTY\\_CAPTION\\_PATH\\_NAMING\\_RULE](#).

This string is used to find the caption file location for a given VOD asset. It is used in conjunction with [PROP\\_CAPTION\\_FILE\\_NAMING\\_RULE](#), which determines the file name.

It is comprised of variables preceded by a dollar sign and enclosed in squiggly brackets. For example: "\${var1}.\${var2}"

Valid variables include these:

- `${SourceStreamName}` : The baseName of the VOD file
- `${SourceBasePath}` : The base path of the VOD asset
- `${FileExtension}` : Registered file extensions with the Timed Text Provider

and these standard ones:

- `${com.wowza.wms.context.VHost}`
- `${com.wowza.wms.context.VHostConfigHome, appInstance.getVHost().getHomePath()};`
- `${com.wowza.wms.context.Application, appInstance.getApplication().getName()};`
- `${com.wowza.wms.context.ApplicationInstance, appInstance.getName()};`

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **captionPathNamingRule**

See Also:

[DEFAULT\\_PROPERTY\\_CAPTION\\_PATH\\_NAMING\\_RULE](#)

## DEFAULT\_PROPERTY\_CAPTION\_PATH\_NAMING\_RULE

```
public static final java.lang.String DEFAULT_PROPERTY_CAPTION_PATH_NAMING_RULE
```

Default value for Timed Text Property "captionFileNamingRule". Default value is "\${SourceBasePath}"  
Constant value: **\${SourceBasePath}**

See Also:

[PROP\\_CAPTION\\_PATH\\_NAMING\\_RULE](#)

## PROP\_MAXIMUM\_CAPTION\_DURATION

```
public static final java.lang.String PROP_MAXIMUM_CAPTION_DURATION
```

Timed Text Property "maximumCaptionDuration": used to determine maximum caption duration

Type Integer. In ms. The default is [DEFAULT\\_MAXIMUM\\_CAPTION\\_DURATION](#)

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **maximumCaptionDuration**

## DEFAULT\_MAXIMUM\_CAPTION\_DURATION

```
public static final int DEFAULT_MAXIMUM_CAPTION_DURATION
```

Default value for Timed Text Property "maximumCaptionDuration".

Default value is 10000.  
Constant value: **5000**

See Also:

(continued from last page)

---

### [PROP\\_MAXIMUM\\_CAPTION\\_DURATION](#)

---

## PROP\_CAPTION\_CHARACTER\_SET

```
public static final java.lang.String PROP_CAPTION_CHARACTER_SET
```

Timed Text Property "captionCharacterSet": used to determine character set when ingesting captions

Type String. The default is [DEFAULT\\_CAPTION\\_CHARACTER\\_SET](#)

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **captionCharacterSet**

---

## DEFAULT\_CAPTION\_CHARACTER\_SET

```
public static final java.lang.String DEFAULT_CAPTION_CHARACTER_SET
```

Default value for Timed Text Property "captionCharacterSet".

Default value is "UTF-8"

Constant value: **UTF-8**

See Also:

[PROP\\_CAPTION\\_CHARACTER\\_SET](#)

---

## PROP\_SRT\_CAPTION\_CHARACTER\_SET

```
public static final java.lang.String PROP_SRT_CAPTION_CHARACTER_SET
```

Timed Text Property "srtReaderCaptionCharacterSet": used to determine character set when ingesting SRT captions  
Overrides general property "captionCharacterSet"

Type String. The default is [DEFAULT\\_CAPTION\\_CHARACTER\\_SET](#)

Constant value: **srtReaderCaptionCharacterSet**

See Also:

Add the property to Application/TimedText/Properties in Application.xml

---

## PROP\_TTML\_CAPTION\_CHARACTER\_SET

```
public static final java.lang.String PROP_TTML_CAPTION_CHARACTER_SET
```

Timed Text Property "ttmlReaderCaptionCharacterSet": used to determine character set when ingesting TTML captions  
Overrides general property "captionCharacterSet"

Type String. The default is [DEFAULT\\_CAPTION\\_CHARACTER\\_SET](#)

Constant value: **ttmlReaderCaptionCharacterSet**

See Also:

Add the property to Application/TimedText/Properties in Application.xml

---

(continued from last page)

## PROP\_3GPP\_CAPTION\_CHARACTER\_SET

```
public static final java.lang.String PROP_3GPP_CAPTION_CHARACTER_SET
```

Timed Text Property "reader3GPPCaptionCharacterSet": used to determine character set when ingesting TTML captions Overrides general property "captionCharacterSet"

Type String. The default is [DEFAULT\\_CAPTION\\_CHARACTER\\_SET](#)  
Constant value: **reader3GPPCaptionCharacterSet**

### See Also:

Add the property to Application/TimedText/Properties in Application.xml

---

## PROP\_CEA608\_CONVERTER\_COLOR

```
public static final java.lang.String PROP_CEA608_CONVERTER_COLOR
```

Timed Text Property "cea608CaptionConverterColor": color of text in default CEA caption converter.

Type Integer. Default is [ClosedCaptionCEA608Utils.COL0\\_WHITE](#)

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **cea608CaptionConverterColor**

### See Also:

[ClosedCaptionCEA608Utils.COL0\\_WHITE](#)  
[ClosedCaptionCEA608Utils.COL0\\_GREEN](#)  
[ClosedCaptionCEA608Utils.COL0\\_BLUE](#)  
[ClosedCaptionCEA608Utils.COL0\\_CYAN](#)  
[ClosedCaptionCEA608Utils.COL0\\_RED](#)  
[ClosedCaptionCEA608Utils.COL0\\_YELLOW](#)  
[ClosedCaptionCEA608Utils.COL0\\_MAGENTA](#)

---

## PROP\_CEA608\_CONVERTER\_CHARS\_PER\_LINE

```
public static final java.lang.String PROP_CEA608_CONVERTER_CHARS_PER_LINE
```

Timed Text Property "cea608CaptionConverterCharsPerLine": max number characters per line in default CEA caption converter.

Type Integer. Default is [ClosedCaptionCEA608Utils.COUNT\\_COLS](#)

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **cea608CaptionConverterCharsPerLine**

---

## PROP\_CEA608\_CONVERTER\_CHARACTER\_SET

```
public static final java.lang.String PROP_CEA608_CONVERTER_CHARACTER_SET
```

Timed Text Property "cea608CaptionConverterCharacterSet": character set in default CEA caption converter.

Type String. Default is "UTF-8"

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **cea608CaptionConverterCharacterSet**

(continued from last page)

---

## PROP\_CUPERTINO\_VOD\_REMOVE\_EXISTING\_CEA608

```
public static final java.lang.String PROP_CUPERTINO_VOD_REMOVE_EXISTING_CEA608
```

Timed Text Property "cupertinoVODCaptionsRemoveExistingCEA608": if existing VOD has 608, remove them

Type Boolean. Default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **cupertinoVODCaptionsRemoveExistingCEA608**

---

## PROP\_CUPERTINO\_VOD\_USE\_WEBVTT

```
public static final java.lang.String PROP_CUPERTINO_VOD_USE_WEBVTT
```

Timed Text Property "cupertinoVODCaptionsUseWebVTT"

Type Boolean. Default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **cupertinoVODCaptionsUseWebVTT**

---

## PROP\_CUPERTINO\_LIVE\_USE\_WEBVTT

```
public static final java.lang.String PROP_CUPERTINO_LIVE_USE_WEBVTT
```

Timed Text Property "cupertinoLiveCaptionsUseWebVTT"

Type Boolean. Default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **cupertinoLiveCaptionsUseWebVTT**

---

## PROP\_AMF\_CONVERTER\_TEXT\_TYPE

```
public static final java.lang.String PROP_AMF_CONVERTER_TEXT_TYPE
```

Timed Text Property "amfCaptionConverterTextType": AMF text type used in conversion

Type String. Default is [AMF\\_TEXTTYPE\\_ON\\_TEXT\\_DATA](#)

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **amfCaptionConverterTextType**

---

## DEFAULT\_AMF\_CONVERTER\_TEXT\_TYPE

```
public static final java.lang.String DEFAULT_AMF_CONVERTER_TEXT_TYPE
```

Constant value: **onTextData**

---

## PROP\_AMF\_CONVERTER\_TRACK\_INDEX

```
public static final java.lang.String PROP_AMF_CONVERTER_TRACK_INDEX
```

Timed Text Property "amfCaptionConverterTrackIndex": track index used for captions

Type Integer.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **amfCaptionConverterTrackIndex**

---

(continued from last page)

---

## DEFAULT\_AMF\_CONVERTER\_TRACK\_INDEX

```
public static final int DEFAULT_AMF_CONVERTER_TRACK_INDEX
```

Constant value: **99**

---

## PROP\_AMF\_CONVERTER\_INSERT\_ERASES\_IN\_GAPS

```
public static final java.lang.String PROP_AMF_CONVERTER_INSERT_ERASES_IN_GAPS
```

Timed Text Property "amfCaptionConverterInsertErases": insert erase captions if gaps between captions are greater than PROP\_MAXIMUM\_CAPTION\_DURATION

Type boolean. The default is true.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **amfCaptionConverterInsertErases**

---

## PROP\_WEBVTT\_CONVERTER\_INSERT\_ERASES\_IN\_GAPS

```
public static final java.lang.String PROP_WEBVTT_CONVERTER_INSERT_ERASES_IN_GAPS
```

Timed Text Property "webVTTCaptionConverterInsertErases": insert erase captions if gaps between captions are greater than PROP\_MAXIMUM\_CAPTION\_DURATION

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **webVTTCaptionConverterInsertErases**

---

## PROP\_DEBUG\_TTML\_VOD\_CAPTION\_COMPANION\_FILES

```
public static final java.lang.String PROP_DEBUG_TTML_VOD_CAPTION_COMPANION_FILES
```

Timed Text Property "debugTTMLVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for TTML Streaming.

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugTTMLVODCaptionFileDetermination**

---

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_COMPANION\\_FILES](#)

---

## PROP\_DEBUG\_TTML\_CAPTION\_PARSER

```
public static final java.lang.String PROP_DEBUG_TTML_CAPTION_PARSER
```

Timed Text Property "debugTTMLCaptionParser": adds info level logging regarding the TTML caption parser

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

---

(continued from last page)

Constant value: **debugTTMLCaptionParser**

---

## PROP\_DEBUG\_TTML\_CAPTION\_PARSER\_TIME

```
public static final java.lang.String PROP_DEBUG_TTML_CAPTION_PARSER_TIME
```

Timed Text Property "debugTTMLCaptionParserTime": adds info level logging regarding how long it took parser to index

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugTTMLCaptionParserTime**

---

## PROP\_TTML\_INLINE\_TAGS\_IN\_TEXT

```
public static final java.lang.String PROP_TTML_INLINE_TAGS_IN_TEXT
```

Timed Text Property "ttmlInlineTagsInText": TTML parser includes in-line styling and line-break tags in the sample text

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Example sample: "

I can linebreak

or change fontWeight to bold in the middle of a sample." If ttmlInlineTagsInText=true then the parser provides the sample text as: "I can linebreak

or change fontWeight to bold in the middle of a sample." If ttmlInlineTagsInText=false then the parser provides the sample text as: "I can linebreak or change fontWeight to bold in the middle of a sample."

Constant value: **ttmlInlineTagsInText**

---

## PROP\_DEBUG\_SRT\_VOD\_CAPTION\_COMPANION\_FILES

```
public static final java.lang.String PROP_DEBUG_SRT_VOD_CAPTION_COMPANION_FILES
```

Timed Text Property "debugSRTVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for SRT provider

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugSRTVODCaptionFileDetermination**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_COMPANION\\_FILES](#)

---

## PROP\_DEBUG\_SRT\_CAPTION\_PARSER

```
public static final java.lang.String PROP_DEBUG_SRT_CAPTION_PARSER
```

Timed Text Property "debugSRTCaptionParser": adds info level logging regarding the SRT caption parser

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

(continued from last page)

Constant value: **debugSRTCaptionParser**

---

## PROP\_DEBUG\_SRT\_CAPTION\_PARSER\_TIME

```
public static final java.lang.String PROP_DEBUG_SRT_CAPTION_PARSER_TIME
```

Timed Text Property "debugSRTCaptionParserTime": adds info level logging regarding how long it took parser to index

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugSRTCaptionParserTime**

---

## PROP\_DEBUG\_WEBVTT\_VOD\_CAPTION\_COMPANION\_FILES

```
public static final java.lang.String PROP_DEBUG_WEBVTT_VOD_CAPTION_COMPANION_FILES
```

Timed Text Property "debugWebVTTVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for WebVTT provider

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugWebVTTVODCaptionFileDetermination**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_COMPANION\\_FILES](#)

---

## PROP\_DEBUG\_WEBVTT\_CAPTION\_PARSER

```
public static final java.lang.String PROP_DEBUG_WEBVTT_CAPTION_PARSER
```

Timed Text Property "debugWebVTTCaptionParser": adds info level logging regarding the WebVTT caption parser

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugWebVTTCaptionParser**

---

## PROP\_DEBUG\_WEBVTT\_CAPTION\_PARSER\_TIME

```
public static final java.lang.String PROP_DEBUG_WEBVTT_CAPTION_PARSER_TIME
```

Timed Text Property "debugWebVTTCaptionParserTime": adds info level logging regarding how long it took parser to index

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugWebVTTCaptionParserTime**

---

## PROP\_DEBUG\_SCC\_VOD\_CAPTION\_COMPANION\_FILES

```
public static final java.lang.String PROP_DEBUG_SCC_VOD_CAPTION_COMPANION_FILES
```

---

(continued from last page)

Timed Text Property "debugSCCVODCaptionFileDetermination": adds info level logging regarding caption companion file determination for a given VOD asset for SCC provider

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugSCCVODCaptionFileDetermination**

See Also:

[PROP\\_DEBUG\\_VOD\\_CAPTION\\_COMPANION\\_FILES](#)

---

## PROP\_DEBUG\_SCC\_CAPTION\_PARSER

```
public static final java.lang.String PROP_DEBUG_SCC_CAPTION_PARSER
```

Timed Text Property "debugSCCCaptionParser": adds info level logging regarding the SCC caption parser

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugSCCCaptionParser**

---

## PROP\_DEBUG\_SCC\_CAPTION\_PARSER\_TIME

```
public static final java.lang.String PROP_DEBUG_SCC_CAPTION_PARSER_TIME
```

Timed Text Property "debugSCCCaptionParserTime": adds info level logging regarding how long it took parser to index

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debugSCCCaptionParserTime**

---

## PROP\_DEBUG\_3GPP\_CAPTION\_PARSER

```
public static final java.lang.String PROP_DEBUG_3GPP_CAPTION_PARSER
```

Timed Text Property "debug3GPPCaptionParser": adds info level logging regarding the 3GPP parser

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debug3GPPCaptionParser**

---

## PROP\_DEBUG\_3GPP\_CAPTION\_PARSER\_TIME

```
public static final java.lang.String PROP_DEBUG_3GPP_CAPTION_PARSER_TIME
```

Timed Text Property "debug3GPPCaptionParserTime": adds info level logging regarding how long it took parser to index

Type boolean. The default is false.

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **debug3GPPCaptionParserTime**



---

## QUERYSTR\_CAPTIONLANGUAGES

```
public static final java.lang.String QUERYSTR_CAPTIONLANGUAGES
```

Query string used for choosing caption languages. Language must be presented using ISO 3 letter language codes.  
Constant value: **wowzacaptionlanguages**

---

## PROP\_CAPTION\_LANGUAGE\_QUERY\_PARAMETER

```
public static final java.lang.String PROP_CAPTION_LANGUAGE_QUERY_PARAMETER
```

HTTP Streamer Property "captionLanguageQueryParameter": used for changing query string param used for caption language selection. Note: Must go into HTTPStreamers.xml under Properties for each streamer type

Type String. The default is "wowzacaptionlanguages"

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **captionLanguageQueryParameter**

---

## QUERYSTR\_CAPTION\_FILENAME

```
public static final java.lang.String QUERYSTR_CAPTION_FILENAME
```

Query string used for choosing caption languages. Language must be presented using ISO 3 letter language codes.  
Constant value: **wowzacaptionfile**

---

## PROP\_CAPTION\_FILENAME\_QUERY\_PARAMETER

```
public static final java.lang.String PROP_CAPTION_FILENAME_QUERY_PARAMETER
```

HTTP Streamer Property "captionFilenameQueryParameter": used for changing query string param used for caption file selection. Note: Must go into HTTPStreamers.xml under Properties for each streamer type

Type String. The default is "wowzacaptionfile"

Add the property to Application/TimedText/Properties in Application.xml

Constant value: **captionFilenameQueryParameter**

---

## PROP\_LIVE\_CAPTION\_INGEST\_AMF\_ID\_STRING

```
public static final java.lang.String PROP_LIVE_CAPTION_INGEST_AMF_ID_STRING
```

Timed Text Property "captionLiveIngestAMFIDString": to change AMF identifier from default "onTextData" to something else

Type String. The default value is "onTextData".

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **captionLiveIngestAMFIDString**

---

## PROP\_LIVE\_CAPTION\_USE\_STREAM\_NAME\_GROUPS

```
public static final java.lang.String PROP_LIVE_CAPTION_USE_STREAM_NAME_GROUPS
```

---

(continued from last page)

Timed Text Property "captionLiveIngestUseStreamNameGroups": to enable use of smil files to determine available languages and ingest type

Type Boolean. The default value is true. Only affects streams started with .smil files using StartupStreams or stream manager.

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **captionLiveIngestUseStreamNameGroups**

---

## PROP\_LIVE\_CAPTION\_DEFAULT\_LANGUAGES

```
public static final java.lang.String PROP_LIVE_CAPTION_DEFAULT_LANGUAGES
```

Timed Text Property "captionLiveIngestLanguages": comma separated ISO-639 language codes determining what languages are expected in the live stream

Type String. The default value is the language returned by `Locale.getDefault().getISO3Language()`.

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **captionLiveIngestLanguages**

---

## PROP\_LIVE\_CAPTION\_INGEST\_TYPE

```
public static final java.lang.String PROP_LIVE_CAPTION_INGEST_TYPE
```

Timed Text Property "captionLiveIngestType": type of live caption ingestion.

This corresponds to LiveIngestTypes in TimedTextProviders.

Type String. The default value is "onTextData", which is also currently only permitted value.

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **captionLiveIngestType**

---

## PROP\_DEBUG\_LIVE\_CAPTION\_INGEST

```
public static final java.lang.String PROP_DEBUG_LIVE_CAPTION_INGEST
```

Timed Text Property "debugCaptionLiveIngest "

Type Boolean. The default value is false.

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **debugCaptionLiveIngest**

---

## PROP\_DEBUG\_LIVE\_CAPTION\_ONTEXTDATA\_INGEST

```
public static final java.lang.String PROP_DEBUG_LIVE_CAPTION_ONTEXTDATA_INGEST
```

Timed Text Property "debugCaptionLiveOnTextDataIngest "

Type Boolean. The default value is false. Overrides [PROP\\_LIVE\\_CAPTION\\_DEFAULT\\_LANGUAGES](#)

Add the property to Application/TimedText/Properties in Application.xml  
Constant value: **debugCaptionLiveOnTextDataIngest**

---

## ON\_TEXT\_DATA

```
public static final java.lang.String ON_TEXT_DATA
```

Constant value: **onTextData**

---

(continued from last page)

## SMIL\_PARAM\_WOWZA\_CAPTION\_INGEST\_TYPE

```
public static final java.lang.String SMIL_PARAM_WOWZA_CAPTION_INGEST_TYPE
```

Constant value: **wowzacaptioningesttype**

---

## SMIL\_PARAM\_IS\_WOWZA\_CAPTION\_STREAM

```
public static final java.lang.String SMIL_PARAM_IS_WOWZA_CAPTION_STREAM
```

Constant value: **iswowzacaptionstream**

---

Package

**com.wowza.wms.transcoder.model**

## com.wowza.wms.transcoder.model Interface ILiveStreamTranscoderActionNotify

public interface **ILiveStreamTranscoderActionNotify**  
extends

ILiveStreamTranscoderActionNotify: listener interface for live stream transcoder events.

### Method Summary

void	<a href="#">onCalculateSourceAudioBitrate</a> (LiveStreamTranscoder liveStreamTranscoder, long bitrate) Called when the bitrate of the source audio stream is calculated
void	<a href="#">onCalculateSourceVideoBitrate</a> (LiveStreamTranscoder liveStreamTranscoder, long bitrate) Called when the bitrate of the source video stream is calculated
void	<a href="#">onInitAfterLoadTemplate</a> (LiveStreamTranscoder liveStreamTranscoder) Called just after transcoder template is loaded.
void	<a href="#">onInitBeforeLoadTemplate</a> (LiveStreamTranscoder liveStreamTranscoder) Called just before transcoder template is loaded
void	<a href="#">onInitStart</a> (LiveStreamTranscoder liveStreamTranscoder, String streamName, String transcoderName, <a href="#">IApplicationInstance</a> appInstance, LiveStreamTranscoderItem liveStreamTranscoderItem) Call when live stream transcoder is first created
void	<a href="#">onInitStop</a> (LiveStreamTranscoder liveStreamTranscoder) At the end of the initialization process
void	<a href="#">onRegisterStreamNameGroup</a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderStreamNameGroup streamNameGroup) Called after a stream name group is resolved and registered with MediaStreamMap
void	<a href="#">onResetStream</a> (LiveStreamTranscoder liveStreamTranscoder) Called when the stream feeding the live stream transcoder switches.
void	<a href="#">onSessionAudioDecodeCodecInfo</a> (LiveStreamTranscoder liveStreamTranscoder, com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio) Called when audio decoding information is available.
void	<a href="#">onSessionAudioEncodeCodecInfo</a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode, com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio) Called when audio encoding information is available.
void	<a href="#">onSessionAudioEncodeCreate</a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode) Called when audio encoder session is created.
void	<a href="#">onSessionAudioEncodeInit</a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode) Called after audio session is initialized.

void	<a href="#"><u>onSessionAudioEncodeSetup</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode) Called after native audio encoder is created and initialized.
void	<a href="#"><u>onSessionDataEncodeCreate</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionDataEncode sessionDataEncode) Called when data encoder session is created.
void	<a href="#"><u>onSessionDataEncodeInit</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionDataEncode sessionDataEncode) Called after data session is initialized.
void	<a href="#"><u>onSessionDestinationCreate</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionDestination sessionDestination) Called when transcoding destination is created
void	<a href="#"><u>onSessionVideoDecodeCodecInfo</u></a> (LiveStreamTranscoder liveStreamTranscoder, com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Called when video decoding information is available.
void	<a href="#"><u>onSessionVideoEncodeCodecInfo</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode, com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Called when video encoding information is available.
void	<a href="#"><u>onSessionVideoEncodeCreate</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode) Called when video encoder session is created.
void	<a href="#"><u>onSessionVideoEncodeInit</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode) Called after video session is initialized.
void	<a href="#"><u>onSessionVideoEncodeSetup</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode) Called after native video encoder is created and initialized.
void	<a href="#"><u>onShutdownStart</u></a> (LiveStreamTranscoder liveStreamTranscoder) Called when the live stream transcoder starts to shutdown.
void	<a href="#"><u>onShutdownStop</u></a> (LiveStreamTranscoder liveStreamTranscoder) Called when the live stream transcoder is shutdown.
void	<a href="#"><u>onUnregisterStreamNameGroup</u></a> (LiveStreamTranscoder liveStreamTranscoder, TranscoderStreamNameGroup streamNameGroup) Called after a stream name group is unregistered with MediaStreamMap

## Methods

### onInitStart

```
public void onInitStart(LiveStreamTranscoder liveStreamTranscoder,
    String streamName,
    String transcoderName,
    IApplicationInstance appInstance,
    LiveStreamTranscoderItem liveStreamTranscoderItem)
```

Call when live stream transcoder is first created

#### Parameters:

(continued from last page)

liveStreamTranscoder - live stream transcoder  
streamName - stream name  
transcoderName - transcoder name  
appInstance - application instance  
liveStreamTranscoderItem - live stream transcoder definition

---

## onInitBeforeLoadTemplate

```
public void onInitBeforeLoadTemplate(LiveStreamTranscoder liveStreamTranscoder)
```

Called just before transcoder template is loaded

**Parameters:**

liveStreamTranscoder - live stream transcoder

---

## onInitAfterLoadTemplate

```
public void onInitAfterLoadTemplate(LiveStreamTranscoder liveStreamTranscoder)
```

Called just after transcoder template is loaded. Good place to modify values loaded from template.

**Parameters:**

liveStreamTranscoder - live stream transcoder

---

## onInitStop

```
public void onInitStop(LiveStreamTranscoder liveStreamTranscoder)
```

At the end of the initialization process

**Parameters:**

liveStreamTranscoder - live stream transcoder

---

## onCalculateSourceVideoBitrate

```
public void onCalculateSourceVideoBitrate(LiveStreamTranscoder liveStreamTranscoder,  
long bitrate)
```

Called when the bitrate of the source video stream is calculated

**Parameters:**

liveStreamTranscoder - live stream transcoder  
bitrate - source bitrate (bytes per second)

---

## onCalculateSourceAudioBitrate

```
public void onCalculateSourceAudioBitrate(LiveStreamTranscoder liveStreamTranscoder,  
long bitrate)
```

Called when the bitrate of the source audio stream is calculated

**Parameters:**

liveStreamTranscoder - live stream transcoder  
bitrate - source bitrate (bytes per second)

---

(continued from last page)

## onSessionDestinationCreate

```
public void onSessionDestinationCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionDestination sessionDestination)
```

Called when transcoding destination is created

### Parameters:

liveStreamTranscoder - live stream transcoder  
sessionDestination - destination

---

## onSessionVideoEncodeCreate

```
public void onSessionVideoEncodeCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode)
```

Called when video encoder session is created.

### Parameters:

liveStreamTranscoder - live stream transcoder  
sessionVideoEncode - video session

---

## onSessionAudioEncodeCreate

```
public void onSessionAudioEncodeCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode)
```

Called when audio encoder session is created.

### Parameters:

liveStreamTranscoder - live stream transcoder  
sessionAudioEncode - audio session

---

## onSessionDataEncodeCreate

```
public void onSessionDataEncodeCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionDataEncode sessionDataEncode)
```

Called when data encoder session is created.

### Parameters:

liveStreamTranscoder - live stream transcoder  
sessionDataEncode - data session

---

## onSessionVideoEncodeInit

```
public void onSessionVideoEncodeInit(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode)
```

Called after video session is initialized.

### Parameters:

liveStreamTranscoder - live stream transcoder  
sessionVideoEncode - video session

---

## onSessionAudioEncodeInit

```
public void onSessionAudioEncodeInit(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode)
```



(continued from last page)

Called after audio session is initialized.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
sessionAudioEncode - audio session

---

## onSessionDataEncodeInit

```
public void onSessionDataEncodeInit(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionDataEncode sessionDataEncode)
```

Called after data session is initialized.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
sessionDataEncode - data session

---

## onSessionVideoEncodeSetup

```
public void onSessionVideoEncodeSetup(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode)
```

Called after native video encoder is created and initialized.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
sessionVideoEncode - video session

---

## onSessionAudioEncodeSetup

```
public void onSessionAudioEncodeSetup(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode)
```

Called after native audio encoder is created and initialized.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
sessionAudioEncode - audio session

---

## onSessionVideoEncodeCodecInfo

```
public void onSessionVideoEncodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode,  
    com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
```

Called when video encoding information is available.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
sessionVideoEncode - video session  
codecInfoVideo - encoding info

---

## onSessionAudioEncodeCodecInfo

```
public void onSessionAudioEncodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode,  
    com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
```

Called when audio encoding information is available.

(continued from last page)

**Parameters:**

liveStreamTranscoder - live stream transcoder  
sessionAudioEncode - audio session  
codecInfoAudio - encoding info

---

**onSessionVideoDecodeCodecInfo**

```
public void onSessionVideoDecodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
```

Called when video decoding information is available.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
codecInfoVideo - video info

---

**onSessionAudioDecodeCodecInfo**

```
public void onSessionAudioDecodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
```

Called when audio decoding information is available.

**Parameters:**

liveStreamTranscoder - live stream transcoder  
codecInfoAudio - audio info

---

**onRegisterStreamNameGroup**

```
public void onRegisterStreamNameGroup(LiveStreamTranscoder liveStreamTranscoder,  
TranscoderStreamNameGroup streamNameGroup)
```

Called after a stream name group is resolved and registered with MediaStreamMap

**Parameters:**

liveStreamTranscoder - live stream transcoder  
streamNameGroup - stream name group

---

**onUnregisterStreamNameGroup**

```
public void onUnregisterStreamNameGroup(LiveStreamTranscoder liveStreamTranscoder,  
TranscoderStreamNameGroup streamNameGroup)
```

Called after a stream name group is unregistered with MediaStreamMap

**Parameters:**

liveStreamTranscoder - live stream transcoder  
streamNameGroup - stream name group

---

**onShutdownStart**

```
public void onShutdownStart(LiveStreamTranscoder liveStreamTranscoder)
```

Called when the live stream transcoder starts to shutdown.

**Parameters:**

liveStreamTranscoder - live stream transcoder

---

---

## onShutdownStop

```
public void onShutdownStop(LiveStreamTranscoder liveStreamTranscoder)
```

Called when the live stream transcoder is shutdown.

**Parameters:**

liveStreamTranscoder - live stream transcoder

---

## onResetStream

```
public void onResetStream(LiveStreamTranscoder liveStreamTranscoder)
```

Called when the stream feeding the live stream transcoder switches.

**Parameters:**

liveStreamTranscoder - live stream transcoder

## com.wowza.wms.transcoder.model Interface ITranscoderFrameGrabProvider

public interface **ITranscoderFrameGrabProvider**  
extends

ITranscoderFrameGrabProvider: interface used to grab frames from the live stream transcoder.

### Method Summary

java.util.List	<a href="#">getAndClearPendingFrameGrabs()</a> Returns a list of all grab frame requests that are pending and clears the pending list.
void	<a href="#">grabFrame(ITranscoderFrameGrabResult grabResult)</a> Call to grab a frame.
void	<a href="#">grabFrame(ITranscoderFrameGrabResult grabResult, int width, int height)</a> Call to grab a frame.

### Methods

#### grabFrame

public void **grabFrame**([ITranscoderFrameGrabResult](#) grabResult)

Call to grab a frame. The size of the frame will be the full size of the video frame.

**Parameters:**

grabResult - the class that will be called back when frame is available

#### grabFrame

public void **grabFrame**([ITranscoderFrameGrabResult](#) grabResult,  
int width,  
int height)

Call to grab a frame. The size of the frame is controlled by width and height.

**Parameters:**

grabResult - the class that will be called back when frame is available

width - frame width

height - frame height

#### getAndClearPendingFrameGrabs

public java.util.List **getAndClearPendingFrameGrabs**()

Returns a list of all grab frame requests that are pending and clears the pending list.

**Returns:**

list of pending grab frames

# com.wowza.wms.transcoder.model

## Interface ITranscoderFrameGrabResult

public interface **ITranscoderFrameGrabResult**  
extends

ITranscoderFrameGrabResult: Implement this interface when using frame grabber interface to grab transcoder video frames.

Method Summary	
void	<a href="#">onGrabFrame</a> (TranscoderNativeVideoFrame nativeFrame) Trigger when frame is available.

## Methods

### onGrabFrame

public void **onGrabFrame**(TranscoderNativeVideoFrame nativeFrame)

Trigger when frame is available.

**Parameters:**

nativeFrame - native video frame.

com.wowza.wms.transcoder.model  
Interface ITranscoderOverlayImages

public interface ITranscoderOverlayImages  
extends

Method Summary	
void	<a href="#">addOverlayImage</a> (int index, TranscoderVideoOverlayFrame overlay)
java.util.Map	<a href="#">getOverlayImages</a> ()

Methods

addOverlayImage

```
public void addOverlayImage(int index,  
    TranscoderVideoOverlayFrame overlay)
```

getOverlayImages

```
public java.util.Map getOverlayImages()
```

## com.wowza.wms.transcoder.model Interface ITranscoderOverlayProvider

public interface **ITranscoderOverlayProvider**  
extends

ITranscoderOverlayProvider: interface to add and remove video overlays.

### Method Summary

void	<a href="#"><code>addOverlay</code></a> (int index, TranscoderVideoOverlayFrame overlay) Add an overlay to a video stream.
void	<a href="#"><code>clearOverlay</code></a> (int index) Clear video overlay
java.util.Map	<a href="#"><code>getAndClearPendingOverlays</code></a> ( ) Get a list of pending overlay requests and clear the pending overlay queue.
boolean	<a href="#"><code>isOverlayAvailable</code></a> ( ) Returns true if there is a pending overlay request.

### Methods

#### **addOverlay**

```
public void addOverlay(int index,  
    TranscoderVideoOverlayFrame overlay)
```

Add an overlay to a video stream.

**Parameters:**

index - over lay index (zero is bottom in z-order)  
overlay - overlay object

#### **clearOverlay**

```
public void clearOverlay(int index)
```

Clear video overlay

**Parameters:**

index - over lay index (zero is bottom in z-order)

#### **isOverlayAvailable**

```
public boolean isOverlayAvailable( )
```

Returns true if there is a pending overlay request.

**Returns:**

true if there is a pending overlay request

---

## **getAndClearPendingOverlays**

```
public java.util.Map getAndClearPendingOverlays()
```

Get a list of pending overlay requests and clear the pending overlay queue.

**Returns:**

list of pending overlay requests



## com.wowza.wms.transcoder.model Interface ITranscoderVideoDecoderNotify

public interface **ITranscoderVideoDecoderNotify**  
extends

### Method Summary

void	<a href="#"><code>onAfterDecodeFrame</code></a> (TranscoderSessionVideo sessionVideo, TranscoderStreamSourceVideo sourceVideo, long frameCount)
void	<a href="#"><code>onAfterScaleFrame</code></a> (TranscoderSessionVideo sessionVideo, TranscoderStreamSourceVideo sourceVideo, long frameCount)
void	<a href="#"><code>onBeforeDecodeFrame</code></a> (TranscoderSessionVideo sessionVideo, TranscoderStreamSourceVideo sourceVideo, long frameCount)
void	<a href="#"><code>onBeforeScaleFrame</code></a> (TranscoderSessionVideo sessionVideo, TranscoderStreamSourceVideo sourceVideo, long frameCount)

### Methods

#### **onBeforeDecodeFrame**

```
public void onBeforeDecodeFrame(TranscoderSessionVideo sessionVideo,  
    TranscoderStreamSourceVideo sourceVideo,  
    long frameCount)
```

#### **onAfterDecodeFrame**

```
public void onAfterDecodeFrame(TranscoderSessionVideo sessionVideo,  
    TranscoderStreamSourceVideo sourceVideo,  
    long frameCount)
```

#### **onBeforeScaleFrame**

```
public void onBeforeScaleFrame(TranscoderSessionVideo sessionVideo,  
    TranscoderStreamSourceVideo sourceVideo,  
    long frameCount)
```

#### **onAfterScaleFrame**

```
public void onAfterScaleFrame(TranscoderSessionVideo sessionVideo,  
    TranscoderStreamSourceVideo sourceVideo,  
    long frameCount)
```

(continued from last page)

---

## com.wowza.wms.transcoder.model Interface ITranscoderVideoEncoderNotify

---

public interface **ITranscoderVideoEncoderNotify**  
extends

---

### Method Summary

void	<a href="#"><code>onAfterEncodeFrame</code></a> (TranscoderSessionVideoEncode sessionVideoEncode, TranscoderStreamDestinationVideo destinationVideo, long frameCount)
void	<a href="#"><code>onBeforeEncodeFrame</code></a> (TranscoderSessionVideoEncode sessionVideoEncode, TranscoderStreamDestinationVideo destinationVideo, long frameCount)

---

### Methods

#### **onBeforeEncodeFrame**

```
public void onBeforeEncodeFrame(TranscoderSessionVideoEncode sessionVideoEncode,  
    TranscoderStreamDestinationVideo destinationVideo,  
    long frameCount)
```

---

#### **onAfterEncodeFrame**

```
public void onAfterEncodeFrame(TranscoderSessionVideoEncode sessionVideoEncode,  
    TranscoderStreamDestinationVideo destinationVideo,  
    long frameCount)
```

com.wowza.wms.transcoder.model

Interface ITranscoderWorker

public interface ITranscoderWorker

extends

For internal use.

Method Summary	
long	<a href="#">getFrameCount</a> ( )
boolean	<a href="#">isEncoderInUse</a> ( )
boolean	<a href="#">isRunning</a> ( ) Returns true if transcoder worker is running (internal use)
void	<a href="#">setFrameCount</a> (long frameCount )

Methods

isRunning

public boolean **isRunning** ( )

Returns true if transcoder worker is running (internal use)

**Returns:**  
true if transcoder worker is running (internal use)

getFrameCount

public long **getFrameCount** ( )

setFrameCount

public void **setFrameCount** (long frameCount )

isEncoderInUse

public boolean **isEncoderInUse** ( )

## com.wowza.wms.transcoder.model Interface ITranscoderWorkerSorterSender

public interface **ITranscoderWorkerSorterSender**  
extends

For internal use.

### Method Summary

void	<a href="#"><u>addSorterPacket</u></a> (TranscoderPacketSorterHolder sorterHolder) For internal use.
------	---

### Methods

#### **addSorterPacket**

public void **addSorterPacket**(TranscoderPacketSorterHolder sorterHolder)

For internal use.

**Parameters:**

sorterHolder - sorter holder

---

Package

**com.wowza.wms.util**

## com.wowza.wms.util

### Class RTPUtils

java.lang.Object

└─com.wowza.wms.util.RTPUtils

public class **RTPUtils**  
extends Object

#### Constructor Summary

public	<a href="#">RTPUtils()</a>
--------	----------------------------

#### Method Summary

static double[]	<a href="#">decodeRangeHeader</a> (String rangeStr) Decode RTP range header, Internal use.
static <a href="#">RTPStream</a>	<a href="#">decodeStreamInfo</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">RTPContext</a> context, String streamId, String streamInfo) Decode SDP info and create RTP stream
static <a href="#">RTPStream</a>	<a href="#">decodeStreamInfo</a> ( <a href="#">IApplicationInstance</a> appInstance, <a href="#">RTPStreamContext</a> rtpStreamContext, <a href="#">RTPContext</a> context, String streamId, String streamInfo) Decode SDP info and create RTP stream
static <a href="#">RTPStream</a>	<a href="#">decodeStreamInfo</a> ( <a href="#">RTPContext</a> context, String streamId, String streamInfo) Decode SDP info and create RTP stream
static byte[]	<a href="#">formatH264CodecConfig</a> (byte[] sps, java.util.List ppss, byte[] profileLevel) Format codec config info, Internal use.
static byte[]	<a href="#">formatH264CodecConfigPacket</a> (byte[] sps, java.util.List ppss, byte[] profileLevel) Format codec config info, Internal use.
static void	<a href="#">loadConfigFile</a> ( <a href="#">RTPContext</a> rtpContext, String fileURL) Load config file, Internal use.
static <a href="#">RTTPushPublishSession</a>	<a href="#">startRTTPull</a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName, boolean streamPacketizer, String ipAddress, int streamPort) Start pushing an RTP stream
static <a href="#">RTTPushPublishSession</a>	<a href="#">startRTTPull</a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName, boolean streamPacketizer, String ipAddress, int streamPort, boolean isRTPWrapped) Start pushing an RTP stream
static <a href="#">RTTPushPublishSession</a>	<a href="#">startRTTPull</a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName, boolean streamPacketizer, String ipAddress, int audioPort, int videoPort) Start pushing an RTP stream

<code>static <a href="#">RTPPushPublishSession</a></code>	<code><a href="#">startRTPPull</a>(<a href="#">IApplicationInstance</a> appInstance, String streamName, boolean streamPacketizer, String ipAddress, int audioPort, int videoPort, boolean isRTPWrapped)</code> Start pushing an RTP stream
<code>static <a href="#">RTPPushPublishSession</a></code>	<code><a href="#">startRTPPull</a>(<a href="#">IApplicationInstance</a> appInstance, String streamName, <a href="#">RTPDestination</a> rtpDestination)</code> Start pushing an RTP stream
<code>static void</code>	<code><a href="#">stopRTPPull</a>(<a href="#">RTPPushPublishSession</a> rtpPushPublishSession)</code> Stop pushing an RTP stream
<code>static String</code>	<code><a href="#">updateSDPDestination</a>(<a href="#">RTPDestination</a> rtpDestination, String sdpData)</code> Update SDP data information with RTP destination information
<code>static void</code>	<code><a href="#">writeCodecConfig</a>(RTPTrack rtpTrack, int codecId, long adjTimecode, byte[] codecConfig)</code>
<code>static void</code>	<code><a href="#">writeCodecConfig</a>(RTPTrack rtpTrack, long adjTimecode, byte[] codecConfig)</code> Write codec config information, Internal use.

**Methods inherited from class `java.lang.Object`**

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,  
wait`

## Constructors

### RTPUtils

`public RTPUtils()`

## Methods

### updateSDPDestination

`public static String updateSDPDestination(RTPDestination rtpDestination,  
String sdpData)`

Update SDP data information with RTP destination information

**Parameters:**

`rtpDestination` - RTP destination  
`sdpData` - SDP data

**Returns:**

modified SDP data

### decodeRangeHeader

`public static double[] decodeRangeHeader(String rangeStr)`

Decode RTP range header, Internal use.



(continued from last page)

**Parameters:**

rangeStr

**Returns:**

range values

---

## stopRTPPull

```
public static void stopRTPPull(RTPPushPublishSession rtpPushPublishSession)
```

Stop pushing an RTP stream

**Parameters:**

rtpPushPublishSession - RTP push session

---

## startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int streamPort,  
    boolean isRTPWrapped)
```

Start pushing an RTP stream

**Parameters:**

appInstance - application instance  
streamName - stream name  
streamPacketizer - stream packetizer  
ipAddress - IP address  
streamPort - stream port  
isRTPWrapped - is RTP wrapped

**Returns:**

RTP push session

---

## startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int streamPort)
```

Start pushing an RTP stream

**Parameters:**

appInstance - application instance  
streamName - stream name  
streamPacketizer - stream packetizer  
ipAddress - IP address  
streamPort - stream port

**Returns:**

RTP push session

(continued from last page)

## startRTPPull

```
public static RTTPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int audioPort,  
    int videoPort)
```

Start pushing an RTP stream

### Parameters:

appInstance - application instance  
streamName - stream name  
streamPacketizer - stream packetizer  
ipAddress - IP address  
audioPort - audio port  
videoPort - video port

### Returns:

RTP push session

---

## startRTPPull

```
public static RTTPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int audioPort,  
    int videoPort,  
    boolean isRTPWrapped)
```

Start pushing an RTP stream

### Parameters:

appInstance - application instance  
streamName - stream name  
streamPacketizer - stream packetizer  
ipAddress - IP address  
audioPort - audio port  
videoPort - video port  
isRTPWrapped - is RTP wrapped

### Returns:

RTP push session

---

## startRTPPull

```
public static RTTPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    RTPDestination rtpDestination)
```

Start pushing an RTP stream

### Parameters:

appInstance - application instance  
streamName - stream name  
rtpDestination - RTP destination

### Returns:

RTP push session

## writeCodecConfig

```
public static void writeCodecConfig(RTPTrack rtpTrack,
    int codecId,
    long adjTimecode,
    byte[] codecConfig)
```

---

## writeCodecConfig

```
public static void writeCodecConfig(RTPTrack rtpTrack,
    long adjTimecode,
    byte[] codecConfig)
```

Write codec config information, Internal use.

**Parameters:**

rtpTrack - RTP track  
adjTimecode - timecode (milliseconds)  
codecConfig - codec config

---

## loadConfigFile

```
public static void loadConfigFile(RTPContext rtpContext,
    String fileURL)
```

Load config file, Internal use.

**Parameters:**

rtpContext  
fileURL

---

## decodeStreamInfo

```
public static RTPStream decodeStreamInfo(RTPContext context,
    String streamId,
    String streamInfo)
```

Decode SDP info and create RTP stream

**Parameters:**

context - RTP context  
streamId - stream id  
streamInfo - SDP data

**Returns:**

RTP stream

---

## decodeStreamInfo

```
public static RTPStream decodeStreamInfo(IApplicationInstance appInstance,
    RTPContext context,
    String streamId,
    String streamInfo)
```

Decode SDP info and create RTP stream

**Parameters:**

(continued from last page)

appInstance - app instance  
context - rtp context  
streamId - stream id  
streamInfo - stream info (SDP data)

**Returns:**

rtp stream

---

## decodeStreamInfo

```
public static RTPStream decodeStreamInfo(IApplicationInstance appInstance,  
    RTPStreamContext rtpStreamContext,  
    RTPContext context,  
    String streamId,  
    String streamInfo)
```

Decode SDP info and create RTP stream

**Parameters:**

appInstance - app instance  
rtpStreamContext - rtp stream context  
context - rtp context  
streamId - stream id  
streamInfo - stream info (SDP data)

**Returns:**

rtp stream

---

## formatH264CodecConfigPacket

```
public static byte[] formatH264CodecConfigPacket(byte[] sps,  
    java.util.List ppss,  
    byte[] profileLevel)
```

Format codec config info, Internal use.

**Parameters:**

sps  
ppss  
profileLevel

**Returns:**

bytes

---

## formatH264CodecConfig

```
public static byte[] formatH264CodecConfig(byte[] sps,  
    java.util.List ppss,  
    byte[] profileLevel)
```

Format codec config info, Internal use.

**Parameters:**

sps  
ppss  
profileLevel

**Returns:**

bytes

## com.wowza.wms.util Class StreamUtils

java.lang.Object

└─com.wowza.wms.util.StreamUtils

public class **StreamUtils**  
extends Object

### Constructor Summary

public	<a href="#">StreamUtils()</a>
--------	-------------------------------

### Method Summary

static int	<a href="#">directOutput</a> (byte[] dataBuffer, int[] headerValues, boolean isAbsTimecode, int src, java.io.OutputStream out, <a href="#">AMFObj</a> wmsObj, byte[] workBuffer, int chunkSize) Direct output, Internal use.
static double	<a href="#">getStreamBitrate</a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName)
static double	<a href="#">getStreamBitrate</a> ( <a href="#">IMediaStream</a> stream) Get the approximate bitrate of a media file in bits/per-second.
static double	<a href="#">getStreamLength</a> ( <a href="#">IApplicationInstance</a> appInstance, String streamName) Get the duration of a media file in seconds.
static double	<a href="#">getStreamLength</a> ( <a href="#">IMediaStream</a> stream) Get the duration of a media file in seconds.
static void	<a href="#">loadConfigFile</a> ( <a href="#">StreamList</a> streamDefs, String fileURL) Load Streams.xml, Internal use.
static int	<a href="#">packetOutput</a> (java.io.OutputStream out, <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> packet, long timecode, <a href="#">AMFObj</a> wmsObj, byte[] workBuffer, int chunkSize) Packet output.
static int	<a href="#">packetOutput</a> (java.io.OutputStream out, <a href="#">IMediaStream</a> stream, <a href="#">AMFPacket</a> packet, long timecode, <a href="#">AMFObj</a> wmsObj, byte[] workBuffer, int chunkSize, boolean referenceWrite) Packet output.

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

(continued from last page)

## StreamUtils

```
public StreamUtils()
```

## Methods

### getStreamLength

```
public static double getStreamLength(IMediaStream stream)
```

Get the duration of a media file in seconds. This will work correctly with all RandomAccessReaders and caching technology

**Parameters:**

stream - stream

**Returns:**

duration in seconds

### getStreamBitrate

```
public static double getStreamBitrate(IMediaStream stream)
```

Get the approximate bitrate of a media file in bits/per-second. This will work correctly with all RandomAccessReaders and caching technology.

**Parameters:**

stream - stream

**Returns:**

bitrate in bits/per-second

### getStreamLength

```
public static double getStreamLength(IApplicationInstance appInstance,  
String streamName)
```

Get the duration of a media file in seconds. This will work correctly with all RandomAccessReaders and caching technology

**Parameters:**

appInstance - application instance

streamName - stream name

**Returns:**

duration in seconds

### getStreamBitrate

```
public static double getStreamBitrate(IApplicationInstance appInstance,  
String streamName)
```

(continued from last page)

## directOutput

```
public static int directOutput(byte[] dataBuffer,  
    int[] headerValues,  
    boolean isAbsTimecode,  
    int src,  
    java.io.OutputStream out,  
    AMFObj wmsObj,  
    byte[] workBuffer,  
    int chunkSize)
```

Direct output. Internal use.

### Parameters:

dataBuffer  
headerValues  
isAbsTimecode  
src  
out  
wmsObj  
workBuffer  
chunkSize

### Returns:

c

---

## packetOutput

```
public static int packetOutput(java.io.OutputStream out,  
    IMediaStream stream,  
    AMFPacket packet,  
    long timecode,  
    AMFObj wmsObj,  
    byte[] workBuffer,  
    int chunkSize)
```

Packet output. Internal use.

### Parameters:

out  
stream  
packet  
timecode  
wmsObj  
workBuffer  
chunkSize

### Returns:

bytes

---

## packetOutput

```
public static int packetOutput(java.io.OutputStream out,  
    IMediaStream stream,  
    AMFPacket packet,  
    long timecode,  
    AMFObj wmsObj,  
    byte[] workBuffer,  
    int chunkSize,  
    boolean referenceWrite)
```

Packet output. Internal use.

(continued from last page)

**Parameters:**

- out
- stream
- packet
- timecode
- wmsObj
- workBuffer
- chunkSize
- referenceWrite

**Returns:**

- bytes

---

## loadConfigFile

```
public static void loadConfigFile(StreamList streamDefs,  
    String fileURL)
```

Load Strreams.xml, Internal use.

**Parameters:**

- streamDefs
- fileURL



---

Package

**com.wowza.wms.util.crontab**

## com.wowza.wms.util.crontab Class CrontabEvent

java.lang.Object

└-com.wowza.wms.util.crontab.CrontabEvent

All Implemented Interfaces:

Comparable

public class **CrontabEvent**  
extends Object  
implements Comparable

Holds an event's schedule and is responsible for calculating event activation.

### Field Summary

public static final	<a href="#">DAY</a> Value: <b>2</b>
public static	<a href="#">DT_FORMAT</a>
public static final	<a href="#">HOUR</a> Value: <b>1</b>
public static final	<a href="#">MINUTE</a> Value: <b>0</b>
public static final	<a href="#">MONTH</a> Value: <b>3</b>
public static final	<a href="#">WEEKDAY</a> Value: <b>5</b>
public static final	<a href="#">YEAR</a> Value: <b>4</b>

### Constructor Summary

public	<a href="#">CrontabEvent</a> ( )
--------	----------------------------------

### Method Summary

int	<a href="#">compareTo</a> ( <a href="#">CrontabEvent</a> o) Allows CronEvents to be sorted via Java Sort Class.
void	<a href="#">dump</a> ( ) dumps this event's information to the console

<a href="#"><u>ICrontabEventHandler</u></a>	<a href="#"><u>getEventHandler()</u></a>
String	<a href="#"><u>getEventStr()</u></a>
CrontabField	<a href="#"><u>getField()</u></a> (int whichField)
org.joda.time.MutableDateTime	<a href="#"><u>getLastRun()</u></a>
org.joda.time.MutableDateTime	<a href="#"><u>getNextRun()</u></a>
String	<a href="#"><u>getTarget()</u></a>
boolean	<a href="#"><u>isDebugEnabled()</u></a>
boolean	<a href="#"><u>isExpired()</u></a> Indicates whether or not all execution dates for this event occur in the past
boolean	<a href="#"><u>isMatch()</u></a> (org.joda.time.MutableDateTime date) Determines if this event will fire on the date passed in
void	<a href="#"><u>setDebug()</u></a> (boolean debug) turns on/off debug logging
void	<a href="#"><u>setEventHandler()</u></a> ( <a href="#"><u>ICrontabEventHandler</u></a> handler)
void	<a href="#"><u>setEventStr()</u></a> (String entry)
void	<a href="#"><u>setField()</u></a> (int whichField, CrontabField field)
void	<a href="#"><u>setLastRun()</u></a> Sets the last run time to now
void	<a href="#"><u>setLastRun()</u></a> (org.joda.time.MutableDateTime date)
void	<a href="#"><u>setTarget()</u></a> (String target)
boolean	<a href="#"><u>start()</u></a> Starts this events timer
void	<a href="#"><u>stop()</u></a> stops this events timer

**Methods inherited from class** java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

**Methods inherited from interface** java.lang.Comparable

compareTo

(continued from last page)

## Fields

### DT\_FORMAT

```
public static org.joda.time.format.DateTimeFormatter DT_FORMAT
```

### MINUTE

```
public static final int MINUTE
```

Constant value: **0**

### HOUR

```
public static final int HOUR
```

Constant value: **1**

### DAY

```
public static final int DAY
```

Constant value: **2**

### MONTH

```
public static final int MONTH
```

Constant value: **3**

### YEAR

```
public static final int YEAR
```

Constant value: **4**

### WEEKDAY

```
public static final int WEEKDAY
```

Constant value: **5**

## Constructors

### CrontabEvent

```
public CrontabEvent()
```

(continued from last page)

## Methods

### start

```
public boolean start()
```

Starts this events timer

**Returns:**

true - if timer is started, else false

### stop

```
public void stop()
```

stops this events timer

### isMatch

```
public boolean isMatch(org.joda.time.MutableDateTime date)
```

Determines if this event will fire on the date passed in

**Parameters:**

date

**Returns:**

boolean

### setField

```
public void setField(int whichField,  
    CrontabField field)
```

### getField

```
public CrontabField getField(int whichField)
```

### setTarget

```
public void setTarget(String target)
```

### getTarget

```
public String getTarget()
```

### setEventStr

```
public void setEventStr(String entry)
```

(continued from last page)

---

## getEventStr

```
public String getEventStr()
```

---

## getNextRun

```
public org.joda.time.MutableDateTime getNextRun()
```

---

## getLastRun

```
public org.joda.time.MutableDateTime getLastRun()
```

---

## setLastRun

```
public void setLastRun(org.joda.time.MutableDateTime date)
```

---

## setLastRun

```
public void setLastRun()
```

Sets the last run time to now

---

## setDebug

```
public void setDebug(boolean debug)
```

turns on/off debug logging

### Parameters:

debug - - true/false

---

## isDebugEnabled

```
public boolean isDebugEnabled()
```

---

## setEventHandler

```
public void setEventHandler(ICrontabEventHandler handler)
```

---

## getEventHandler

```
public ICrontabEventHandler getEventHandler()
```

---

## isExpired

```
public boolean isExpired()
```

Indicates whether or not all execution dates for this event occur in the past

**Returns:**

true/false

---

## compareTo

```
public int compareTo(CrontabEvent o)
```

Allows CronEvents to be sorted via Java Sort Class. Compares nextRun dates of two CronEvents where earlier events are considered "less" than later events, (e.g. today < tomorrow) and nulls are "greater" than events with dates (e.g. tomorrow < null) This provides the logic to sort events by soonest to latest with nulls at the end

**Parameters:**

o - - CronEvent to compare this event to

**Returns:**

-1,0,1 - if equal, if this event is greater than

---

## dump

```
public void dump()
```

dumps this event's information to the console

## com.wowza.wms.util.crontab Interface ICrontabEventHandler

All Known Implementing Classes:  
[LiveStreamRecorderBase](#)

public interface **ICrontabEventHandler**  
extends

EventHandler functions are called from a Java timer task context and therefore should execute very quickly so as not to delay execution of subsequent timers. If there is heavy processing which needs to take place, the implementation for these functions should spawn a thread to do it.

### Method Summary

void	<a href="#">onCronEvent</a> ( <a href="#">CrontabEvent</a> event)
------	---

### Methods

#### onCronEvent

public void **onCronEvent**([CrontabEvent](#) event)



---

Package

**com.wowza.wms.vhost**

## com.wowza.wms.vhost Class HostPort

java.lang.Object

└─com.wowza.wms.vhost.HostPort

public class **HostPort**  
extends Object

HostPort: data object that describes a socket connection. The address can be defined by ipAddress or by domainName. It can also contain a reference to an SSLFactory class that can be used to create a secure connection to the server.

### Constructor Summary

public	<a href="#">HostPort()</a> Create an empty HostPort object
--------	---

### Method Summary

void	<a href="#">addHttpProvider(IHTTPProvider httpProvider)</a>
void	<a href="#">addHttpProvider(IHTTPProvider2 httpProvider)</a>
void	<a href="#">addHttpProvider(int index, IHTTPProvider2 httpProvider)</a>
void	<a href="#">addHTTPStreamerAdapterID(String ID)</a>
void	<a href="#">configureSocketAcceptor(org.apache.mina.transport.socket.nio.SocketAcceptorConfig socketConfig)</a> Configure a socketAcceptor
java.net.InetAddress	<a href="#">getAddress()</a> Get the ipAddress as an InetAddress object
String	<a href="#">getAddressRawStr()</a>
String	<a href="#">getAddressStr()</a> Get a String representation of the address
HostPortConfig	<a href="#">getConfiguration()</a> Get the socket configuration
String	<a href="#">getHTTPIdent2Response()</a>
String	<a href="#">getHTTPIdentResponse()</a>
java.util.List	<a href="#">getHttpProviders()</a>
java.util.List	<a href="#">getHTTPStreamerAdapterIDs()</a>

int	<a href="#"><u>getPort()</u></a> Get port
int	<a href="#"><u>getProcessorCount()</u></a> Get the number of threads to use to service this incoming port
HostPortSSLConfig	<a href="#"><u>getSSLConfig()</u></a>
String	<a href="#"><u>getSslFactoryClass()</u></a> Get full class name or SSLFactory class
boolean	<a href="#"><u>isSuspended()</u></a>
void	<a href="#"><u>setDomainName()</u></a> (String domainName) Set domainName.
void	<a href="#"><u>setHTTPIdent2Response()</u></a> (String httpIdent2Response)
void	<a href="#"><u>setHTTPIdentResponse()</u></a> (String httpIdentResponse)
void	<a href="#"><u>setIpAddress()</u></a> (String ipAddress) Set ipAddress for object.
void	<a href="#"><u>setPort()</u></a> (int port) Set port
void	<a href="#"><u>setProcessorCount()</u></a> (int processorCount) Set the number of threads to use to service this incoming port
void	<a href="#"><u>setSSLConfig()</u></a> (HostPortSSLConfig sslConfig)
void	<a href="#"><u>setSslFactoryClass()</u></a> (String sslFactoryClass) Set full class name of SSLFactory class
void	<a href="#"><u>setSuspended()</u></a> (boolean isSuspended)
int	<a href="#"><u>size()</u></a> (int index, <a href="#"><u>IHTTPProvider2</u></a> httpProvider)
String	<a href="#"><u>toString()</u></a> Return object as formatted string
String	<a href="#"><u>toString()</u></a> (boolean mBeanSafe) Return object as formatted string

#### Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

(continued from last page)

## HostPort

```
public HostPort()
```

Create an empty HostPort object

## Methods

### setDomainName

```
public void setDomainName(String domainName)
```

Set domainName. A domainName of \* defines a local connection.

**Parameters:**

domainName - domainName like www.mycompany.com or \* for local

### getAddress

```
public java.net.InetAddress getAddress()
```

Get the ipAddress as an InetAddress object

**Returns:**

ipAddress as an InetAddress object. At this point the domainName (if specified) will be resolved.

### getAddressStr

```
public String getAddressStr()
```

Get a String representation of the address

**Returns:**

String representation of the address/domainName. If \* it will return [any]

### getAddressRawStr

```
public String getAddressRawStr()
```

### setIpAddress

```
public void setIpAddress(String ipAddress)
```

Set ipAddress for object. A ipAddress of \* defines a local connection.

**Parameters:**

ipAddress - ipAddress like 127.0.0.1 or \* for local

### getPort

```
public int getPort()
```

Get port

**Returns:**

(continued from last page)

port

---

## setPort

```
public void setPort(int port)
```

Set port

### Parameters:

port - port

---

## getSslFactoryClass

```
public String getSslFactoryClass()
```

Get full class name or SSLFactory class

### Returns:

full class name or SSLFactory or "" if not specified

---

## setSslFactoryClass

```
public void setSslFactoryClass(String sslFactoryClass)
```

Set full class name of SSLFactory class

### Parameters:

sslFactoryClass - full class name or SSLFactory or "" if not specified

---

## getProcessorCount

```
public int getProcessorCount()
```

Get the number of threads to use to service this incoming port

### Returns:

number of processor threads

---

## setProcessorCount

```
public void setProcessorCount(int processorCount)
```

Set the number of threads to use to service this incoming port

### Parameters:

processorCount - number of processor threads

---

## toString

```
public String toString(boolean mBeanSafe)
```

Return object as formatted string

### Parameters:

mBeanSafe - make the name safe for JMX management interface

### Returns:

formatted string

## toString

```
public String toString()
```

Return object as formatted string

**Returns:**

formmatted string

---

## getConfiguration

```
public HostPortConfig getConfiguration()
```

Get the socket configuration

**Returns:**

socket configuration

---

## configureSocketAcceptor

```
public void  
configureSocketAcceptor(org.apache.mina.transport.socket.nio.SocketAcceptorConfig  
socketConfig)
```

Configure a socketAcceport

**Parameters:**

socketConfig - socket acceptor

---

## getHttpProviders

```
public java.util.List getHttpProviders()
```

---

## addHttpProvider

```
public void addHttpProvider(IHTTPProvider httpProvider)
```

---

## addHttpProvider

```
public void addHttpProvider(IHTTPProvider2 httpProvider)
```

---

## addHttpProvider

```
public void addHttpProvider(int index,  
    IHTTPProvider2 httpProvider)
```

---

(continued from last page)

## size

```
public int size(int index,  
    IHTTPProvider2 httpProvider)
```

---

## isSuspended

```
public boolean isSuspended()
```

---

## setSuspended

```
public void setSuspended(boolean isSuspended)
```

---

## getHTTPStreamerAdapterIDs

```
public java.util.List getHTTPStreamerAdapterIDs()
```

---

## addHTTPStreamerAdapterID

```
public void addHTTPStreamerAdapterID(String ID)
```

---

## getSSLConfig

```
public HostPortSSLConfig getSSLConfig()
```

---

## setSSLConfig

```
public void setSSLConfig(HostPortSSLConfig sslConfig)
```

---

## getHTTPIdentResponse

```
public String getHTTPIdentResponse()
```

---

## setHTTPIdentResponse

```
public void setHTTPIdentResponse(String httpIdentResponse)
```

---

## getHTTPIdent2Response

```
public String getHTTPIdent2Response()
```

---

(continued from last page)

---

## setHTTPIdent2Response

```
public void setHTTPIdent2Response(String httpIdent2Response)
```



## com.wowza.wms.vhost Class HostPortList

java.lang.Object

└--com.wowza.wms.vhost.HostPortList

```
public class HostPortList
extends Object
```

HostPortList: data object that contains a collection of HostPort objects.

### Constructor Summary

public	<a href="#">HostPortList()</a> Create empty HostPortList
--------	---

### Method Summary

void	<a href="#">add(<a href="#">HostPort</a> hostPort)</a> Add HostPort object
<a href="#">HostPort</a>	<a href="#">get(int index)</a> Get HostPort object at index, null if out of bounds
int	<a href="#">size()</a> Get number of HostPort objects

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### HostPortList

```
public HostPortList()
```

Create empty HostPortList

## Methods

### add

```
public void add(HostPort hostPort)
```

Add HostPort object

#### Parameters:

hostPort

---

## size

```
public int size()
```

Get number of HostPort objects

**Returns:**

number of HostPort objects

---

## get

```
public HostPort get(int index)
```

Get HostPort object at index, null if out of bounds

**Parameters:**

index - index

**Returns:**

HostPort object at index, null if out of bounds

## com.wowza.wms.vhost Interface IAcceptorNotify

---

public interface **IAcceptorNotify**  
extends

IAcceptorNotify: listener interface used by IVHost addAcceptorListener

---

### Method Summary

void	<a href="#"><code>onAcceptorCreate</code></a> ( <a href="#"><code>HostPort</code></a> hostPort, java.util.Map acceptorMap) Triggered when a new acceptor is created
void	<a href="#"><code>onAcceptorDestroy</code></a> ( <a href="#"><code>HostPort</code></a> hostPort, java.util.Map acceptorMap) Triggered when a new acceptor is deleted

---

### Methods

#### **onAcceptorCreate**

```
public void onAcceptorCreate(HostPort hostPort,  
                             java.util.Map acceptorMap)
```

Triggered when a new acceptor is created

**Parameters:**

hostPort - HostPort object

acceptorMap - Map of acceptors

---

#### **onAcceptorDestroy**

```
public void onAcceptorDestroy(HostPort hostPort,  
                               java.util.Map acceptorMap)
```

Triggered when a new acceptor is deleted

**Parameters:**

hostPort - HostPort object

acceptorMap - Map of acceptors

---

## com.wowza.wms.vhost Interface IVHost

public interface **IVHost**  
extends

IVHost: public interface to VHost object.

### Field Summary

public static final	<a href="#">ACCEPTORS_ACCEPTOR</a> Acceptor types: acceptor Value: <b>acceptor</b>
public static final	<a href="#">ACCEPTORS_HANDLERADAPTER</a> Acceptor types: handler Value: <b>handlerAdapter</b>
public static final	<a href="#">CODEC_AUDIO_AAC</a> Value: <b>10</b>
public static final	<a href="#">CODEC_AUDIO_AC3</a> Value: <b>1</b>
public static final	<a href="#">CODEC_AUDIO_G711_ALAW</a> Value: <b>7</b>
public static final	<a href="#">CODEC_AUDIO_G711_MULAW</a> Value: <b>8</b>
public static final	<a href="#">CODEC_AUDIO_MP3</a> Value: <b>2</b>
public static final	<a href="#">CODEC_AUDIO_MP3_8</a> Value: <b>15</b>
public static final	<a href="#">CODEC_AUDIO_NELLYMOSER</a> Value: <b>6</b>
public static final	<a href="#">CODEC_AUDIO_NELLYMOSER_16MONO</a> Value: <b>4</b>
public static final	<a href="#">CODEC_AUDIO_NELLYMOSER_8MONO</a> Value: <b>5</b>
public static final	<a href="#">CODEC_AUDIO_PCM_BE</a> Value: <b>0</b>

public static final	<a href="#">CODEC_AUDIO_PCM_LE</a> Value: <b>3</b>
public static final	<a href="#">CODEC_AUDIO_PCM_SWF</a> Value: <b>1</b>
public static final	<a href="#">CODEC_AUDIO_RESERVED</a> Value: <b>9</b>
public static final	<a href="#">CODEC_AUDIO_SPEEX</a> Value: <b>11</b>
public static final	<a href="#">CODEC_AUDIO_UNKNOWN</a> Value: <b>-1</b>
public static final	<a href="#">CODEC_AUDIO_VORBIS</a> Value: <b>9</b>
public static final	<a href="#">CODEC_STREAM_MP2T</a> Value: <b>0</b>
public static final	<a href="#">CODEC_STREAM_UNKNOWN</a> Value: <b>-1</b>
public static final	<a href="#">CODEC_VIDEO_H263</a> Value: <b>9</b>
public static final	<a href="#">CODEC_VIDEO_H264</a> Value: <b>7</b>
public static final	<a href="#">CODEC_VIDEO_MPEG2</a> Value: <b>11</b>
public static final	<a href="#">CODEC_VIDEO_MPEG4</a> Value: <b>10</b>
public static final	<a href="#">CODEC_VIDEO_SCREEN</a> Value: <b>3</b>
public static final	<a href="#">CODEC_VIDEO_SCREEN2</a> Value: <b>6</b>
public static final	<a href="#">CODEC_VIDEO_SPARK</a> Value: <b>2</b>
public static final	<a href="#">CODEC_VIDEO_UNKNOWN</a> Value: <b>-1</b>

public static final	<a href="#">CODEC_VIDEO_VP6</a> Value: <b>4</b>
public static final	<a href="#">CODEC_VIDEO_VP6A</a> Value: <b>5</b>
public static final	<a href="#">CODEC_VIDEO_VP8</a> Value: <b>8</b>
public static final	<a href="#">CONTENTTYPE_ACKBANDWIDTH</a> AMF Content type: set acknowledge bandwidth size Value: <b>5</b>
public static final	<a href="#">CONTENTTYPE_AUDIO</a> AMF Content type: audio packet Value: <b>8</b>
public static final	<a href="#">CONTENTTYPE_BUFFERSIZE</a> AMF Content type: set buffer size Value: <b>4</b>
public static final	<a href="#">CONTENTTYPE_DATA</a> AMF Content type: data packet Value: <b>18</b>
public static final	<a href="#">CONTENTTYPE_DATA0</a> AMF Content type: data packet (AMF0) Value: <b>18</b>
public static final	<a href="#">CONTENTTYPE_DATA3</a> AMF Content type: data packet (AMF3) Value: <b>15</b>
public static final	<a href="#">CONTENTTYPE_FUNCTION</a> AMF Content type: function data (AMF0) Value: <b>20</b>
public static final	<a href="#">CONTENTTYPE_FUNCTION0</a> AMF Content type: function data (AMF0) Value: <b>20</b>
public static final	<a href="#">CONTENTTYPE_FUNCTION3</a> AMF Content type: function data (AMF3) Value: <b>17</b>
public static final	<a href="#">CONTENTTYPE_MEDIACHUNK</a> AMF Content type: media chunk Value: <b>22</b>
public static final	<a href="#">CONTENTTYPE_PLAYCALLBACK</a> AMF Content type: play callback Value: <b>127</b>

public static final	<a href="#"><u>CONTENTTYPE_SETBANDWIDTH</u></a> AMF Content type: set bandwidth size Value: <b>6</b>
public static final	<a href="#"><u>CONTENTTYPE_SETCHUNKSIZE</u></a> AMF Content type: set packet chunk size Value: <b>1</b>
public static final	<a href="#"><u>CONTENTTYPE_SHAREDOBJECTS</u></a> AMF Content type: shared object packet (AMF0) Value: <b>19</b>
public static final	<a href="#"><u>CONTENTTYPE_SHAREDOBJECTS0</u></a> AMF Content type: shared object packet (AMF0) Value: <b>19</b>
public static final	<a href="#"><u>CONTENTTYPE_SHAREDOBJECTS3</u></a> AMF Content type: shared object packet (AMF3) Value: <b>16</b>
public static final	<a href="#"><u>CONTENTTYPE_UNKNOWN</u></a> AMF Content type: unknown Value: <b>0</b>
public static final	<a href="#"><u>CONTENTTYPE_VIDEO</u></a> AMF Content type: video packet Value: <b>9</b>
public static final	<a href="#"><u>CONTENTTYPE_WATCHDOG</u></a> AMF Content type: watch dog Value: <b>3</b>
public static final	<a href="#"><u>COUNTER_HTTPCUPERTINO</u></a> Value: <b>2</b>
public static final	<a href="#"><u>COUNTER_HTTPDVRCHUNKS</u></a> Value: <b>7</b>
public static final	<a href="#"><u>COUNTER_HTTPMPEGDASH</u></a> Value: <b>6</b>
public static final	<a href="#"><u>COUNTER_HTTPSANJOSE</u></a> Value: <b>4</b>
public static final	<a href="#"><u>COUNTER_HTTPSMOOTH</u></a> Value: <b>3</b>
public static final	<a href="#"><u>COUNTER_HTTPWEBM</u></a> Value: <b>5</b>
public static final	<a href="#"><u>COUNTER_RTMP</u></a> Value: <b>0</b>

public static final	<a href="#"><u>COUNTER_RTP</u></a> Value: <b>1</b>
public static final	<a href="#"><u>COUNTER_TOTAL</u></a> Value: <b>8</b>
public static final	<a href="#"><u>FILEFORMAT_FLV</u></a> Value: <b>1</b>
public static final	<a href="#"><u>FILEFORMAT_MP4</u></a> Value: <b>2</b>
public static final	<a href="#"><u>FILEFORMAT_UNKNOWN</u></a> Value: <b>-1</b>
public static final	<a href="#"><u>LICENSECOUNTER_DRM_BUYDRM_LIVE</u></a> Value: <b>9</b>
public static final	<a href="#"><u>LICENSECOUNTER_DRM_BUYDRM_VOD</u></a> Value: <b>10</b>
public static final	<a href="#"><u>LICENSECOUNTER_DRM_EZDRM_LIVE</u></a> Value: <b>4</b>
public static final	<a href="#"><u>LICENSECOUNTER_DRM_EZDRM_VOD</u></a> Value: <b>5</b>
public static final	<a href="#"><u>LICENSECOUNTER_DRM_VERIMATRIX_LIVE</u></a> Value: <b>6</b>
public static final	<a href="#"><u>LICENSECOUNTER_DRM_VERIMATRIX_VOD</u></a> Value: <b>7</b>
public static final	<a href="#"><u>LICENSECOUNTER_NDVR</u></a> Value: <b>3</b>
public static final	<a href="#"><u>LICENSECOUNTER_PUBLISHER</u></a> Value: <b>0</b>
public static final	<a href="#"><u>LICENSECOUNTER_PUBLISHERTRANSCODER</u></a> Value: <b>8</b>
public static final	<a href="#"><u>LICENSECOUNTER_TOTAL</u></a> Value: <b>20</b>
public static final	<a href="#"><u>LICENSECOUNTER_TRANSCODE_DECODE</u></a> Value: <b>1</b>



public static final	<a href="#">LICENSECOUNTER_TRANSCODE_DECODECOUNTAUDIO</a> Value: <b>14</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_DECODECOUNTAUDIOVIDEO</a> Value: <b>16</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_DECODECOUNTVIDEO</a> Value: <b>15</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_DECODEPOLLING</a> Value: <b>11</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_ENCODE</a> Value: <b>2</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_ENCODECOUNTAUDIO</a> Value: <b>17</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_ENCODECOUNTAUDIOVIDEO</a> Value: <b>19</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_ENCODECOUNTVIDEO</a> Value: <b>18</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_ENCODEPOLLING</a> Value: <b>12</b>
public static final	<a href="#">LICENSECOUNTER_TRANSCODE_STREAMNAMES</a> Value: <b>13</b>
public static final	<a href="#">VHOST_DEFAULT</a> Value: <b>_defaultVHost_</b>

## Method Summary

void	<a href="#">addAcceptorListener</a> ( <a href="#">IAcceptorNotify</a> acceptorListener) Add acceptor listener.
void	<a href="#">addApplicationListener</a> ( <a href="#">IApplicationNotify</a> applicationListener) Add application listener.
void	<a href="#">addIdleWorkerListener</a> ( <a href="#">IIdleWorkerNotify</a> idleWorkerListener) Add idleWorker listener.
void	<a href="#">addStartupStream</a> (StartupStream startupStream) Add a stream to the list of streams to start and virtual host startup
boolean	<a href="#">applicationExists</a> (String name) Return true if an application folder exists for this application name

void	<a href="#"><u>closeHostPort</u></a> ( <a href="#"><u>HostPort</u></a> hostPort, boolean isSuspend) Close an individual HostPort
boolean	<a href="#"><u>createApplication</u></a> (String sName, String sStreamType, String sContentLoc) Method to create a new application
<a href="#"><u>IApplication</u></a>	<a href="#"><u>getApplication</u></a> (String applicationName) Get application by name.
java.util.List	<a href="#"><u>getApplicationFolderNames</u></a> ( ) Get a list of application folder names
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<a href="#"><u>getApplicationLock</u></a> ( ) Get the object used in synchronized statements to lock and application.
java.util.List	<a href="#"><u>getApplicationNames</u></a> ( ) Get a list of application names
int	<a href="#"><u>getApplicationTimeout</u></a> ( ) Get application time out (milliseconds).
AuthenticationList	<a href="#"><u>getAuthenticationList</u></a> ( ) Get the list of available authentication methods
CEACaptionConversionContext	<a href="#"><u>getCEACaptionConversionContext</u></a> ( ) Get CEACaptionConversionContextMP3 tag map attached to vHost (CEACaptionConversion.xml).
<a href="#"><u>IClient</u></a>	<a href="#"><u>getClient</u></a> (int clientId) Get client by client id.
<a href="#"><u>IClient</u></a>	<a href="#"><u>getClient</u></a> (int clientId, boolean create) Get client by client id and create if does not exist.
int	<a href="#"><u>getClientCount</u></a> ( ) Get number of clients connected to this vHost.
int	<a href="#"><u>getClientIdleFrequency</u></a> ( ) Get default client idle frequency (milliseconds)
int	<a href="#"><u>getClientTimeout</u></a> ( ) Get client timeout.
<a href="#"><u>ConnectionCounter</u></a>	<a href="#"><u>getConnectionCounter</u></a> ( ) Get vHost connection counter.
ConnectionCounterSimple	<a href="#"><u>getConnectionCounter</u></a> (int counterIndex) Get vHost connection counter for a specific technology (see IVHost.COUNTER_*)
int	<a href="#"><u>getConnectionLimit</u></a> ( ) Get vHost connection limit.
int	<a href="#"><u>getCoreHandlerPoolSize</u></a> ( ) Get the handler core thread pool size.
int	<a href="#"><u>getCoreTransportPoolSize</u></a> ( ) Get the transport core thread pool size.

String	<a href="#"><u>getDateStarted()</u></a> Get date and time the server was started.
DvrRecorderList	<a href="#"><u>getDvrRecorderList()</u></a> Get the DvrRecorderList
DvrStoreList	<a href="#"><u>getDvrStoreList()</u></a> Get the list of DVR Stores
java.util.Properties	<a href="#"><u>getDynamicLogProperties()</u></a> Get the dynamic log properties defined at the vhost level in conf/log4j.properties
int	<a href="#"><u>getFileIOPoolSize()</u></a> Get the default file io pool size.
<a href="#"><u>ThreadPool</u></a>	<a href="#"><u>getHandlerThreadPool()</u></a> Get the VHost handler thread pool.
String	<a href="#"><u>getHomePath()</u></a> Get vHost configuration path.
<a href="#"><u>HostPortList</u></a>	<a href="#"><u>getHostPortsList()</u></a> Get list of host port definitions for vHost.
<a href="#"><u>IHTTPStreamerAdapter</u></a>	<a href="#"><u>getHTTPStreamerAdapter(String ID)</u></a> Get an HTTPStreamerAdapter by ID
java.util.List	<a href="#"><u>getHTTPStreamerAdapterIDs()</u></a> Get a list of HTTPStreamerAdapter IDs
HTTPStreamerContext	<a href="#"><u>getHTTPStreamerContext()</u></a> Get the HTTPStreamer (Cupertino Streaming and Silverlight Smooth Streaming) host context
HTTPStreamerList	<a href="#"><u>getHTTPStreamerList()</u></a> Get the list of HTTPStreamers
int	<a href="#"><u>getHTTPStreamerMaxPathLen()</u></a> Get the max HTTP streamer path length
<a href="#"><u>IVHostHTTPStreamerRequestValidator</u></a>	<a href="#"><u>getHTTPStreamerRequestValidator()</u></a> Get the HTTP streamer request validator
int	<a href="#"><u>getIdleCheckFrequency()</u></a> Get idle check frequency (milliseconds)
int	<a href="#"><u>getIdleMinimumWaitTime()</u></a> Get the minimum time (milliseconds) the idle worker thread will sleep before generating idle events
int	<a href="#"><u>getIdleWorkerCount()</u></a> Get number of threads used to generate idle events
IdleWorkersUtil	<a href="#"><u>getIdleWorkers()</u></a> Get the idle worker utility
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getIoPerformanceCounter()</u></a> Get vHost IO performance counter.
<a href="#"><u>IOPerformanceCounter</u></a>	<a href="#"><u>getIoPerformanceCounter(int counterIndex)</u></a> Get vHost IO performance counter for a specific technology (see IVHost.COUNTER_*)

IOScheduler	<a href="#">getIOScheduler()</a> Get IO scheduler for vHost.
int	<a href="#">getKeepAliveTimeout()</a> Get the RTMPT connection keep alive timeout
LiveStreamPacketizerList	<a href="#">getLiveStreamPacketizerList()</a> Get the LiveStreamPacketizerList
LiveStreamTranscoderList	<a href="#">getLiveStreamTranscoderList()</a> Get the LiveStreamTranscoderList
int	<a href="#">getMaximumPendingReadBytes()</a> Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
int	<a href="#">getMaximumPendingWriteBytes()</a> Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
int	<a href="#">getMaximumSetBufferTime()</a> Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
<a href="#">MediaCasterList</a>	<a href="#">getMediaCasterList()</a> Get the list of media caster definitions (MediaCaster.xml)
<a href="#">MediaCasterSettings</a>	<a href="#">getMediaCasterSettings()</a> Get the media caster settings
int	<a href="#">getMediaReaderContentType(String mediaType)</a> Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE_*)
MediaReaderList	<a href="#">getMediaReaders()</a> Get the media readers attached to vHost (MediaReaders.xml).
MediaWriterList	<a href="#">getMediaWriters()</a> Get the media writers attached to vHost (MediaWriters.xml).
java.util.Map	<a href="#">getMp3TagMap()</a> Get MP3 tag map attached to vHost (MP3Tags.xml).
String	<a href="#">getName()</a> Get vHost name
HostPortConfig	<a href="#">getNetConnectionHostPortConfig()</a> Get the socket configuration for server to server connections
int	<a href="#">getNetConnectionIdleFrequency()</a> Get server to server idle frequency (milliseconds)
int	<a href="#">getNetConnectionProcessorCount()</a> Get net connection processor count.
int	<a href="#">getNextNetConnectionId()</a> Get next connection id.
int	<a href="#">getPingTimeout()</a> Get ping timeout (milliseconds)

<a href="#"><u>WMSProperties</u></a>	<a href="#"><u>getProperties()</u></a> Get properties attached to this vHost.
String	<a href="#"><u>getProperty(String key)</u></a> Get virtual host property.
void	<a href="#"><u>getProtocolUsage(boolean[] protocolsInUse)</u></a> Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE_*)
<a href="#"><u>RTPContext</u></a>	<a href="#"><u>getRTPContext()</u></a> Get the RTP (real time protocol) virtual host context
com.wowza.wms.rtp.transport.RTPUDPDatagramConfig	<a href="#"><u>getRTPDatagramConfigIncoming()</u></a> Get the RTP Datagram Socket configuration
com.wowza.wms.rtp.transport.RTPUDPDatagramConfig	<a href="#"><u>getRTPDatagramConfigOutgoing()</u></a> Get the RTP Datagram Socket configuration
int	<a href="#"><u>getRTPIidleFrequency()</u></a> Get default RTP idle frequency (milliseconds)
int	<a href="#"><u>getRTSPMaxPathLen()</u></a> Get the max RTSP stream path length
<a href="#"><u>IVHostRTSPRequestValidator</u></a>	<a href="#"><u>getRTSPRequestValidator()</u></a> Get the RTSP request validator
java.util.List	<a href="#"><u>getStartupStreams()</u></a> Get the list of streams to start at virtual host startup
<a href="#"><u>StreamList</u></a>	<a href="#"><u>getStreamTypes()</u></a> Get default stream type.
<a href="#"><u>ThreadPool</u></a>	<a href="#"><u>getThreadPool()</u></a> Get the VHost handler thread pool.
TimedTextProviderConfiguration	<a href="#"><u>getTimedTextProviderConfig()</u></a> Get the config of TimedTextProviders
String	<a href="#"><u>getTimeRunning()</u></a> Get the time vHost has been running.
double	<a href="#"><u>getTimeRunningSeconds()</u></a> Get time running in seconds
com.wowza.wms.transcoder.vod.TranscoderVODContext	<a href="#"><u>getTranscoderVODContext()</u></a> Get the VOD transcoder context
<a href="#"><u>ThreadPool</u></a>	<a href="#"><u>getTransportThreadPool()</u></a> Get the VHost transport thread pool.
com.wowza.wms.rtp.transport.UDPTransportManager	<a href="#"><u>getUDPTransportManager()</u></a> Get the UDP transport manager.
int	<a href="#"><u>getValidationFrequency()</u></a> Get time between validation pings (milliseconds)

void	<a href="#"><u>init</u></a> (String basePath) Initialize vHost.
boolean	<a href="#"><u>isApplicationLoaded</u></a> (String applicationName) Return true is the application is loaded
boolean	<a href="#"><u>isShuttingDown</u></a> ( ) Is the VHost shutting down
boolean	<a href="#"><u>isStartStarupStreams</u></a> ( ) Returns true if the startup streams are to start and vhost startup
boolean	<a href="#"><u>isSuspended</u></a> ( ) Returns true is all HostPorts connected to this VHost are suspended
void	<a href="#"><u>killClient</u></a> (int clientId) Remove client from vHost and send disconnect message.
void	<a href="#"><u>killRTSPSession</u></a> (String rtspSessionId) Kill an RTSP connection by the RTSP session id
void	<a href="#"><u>putHTTPStreamerAdapter</u></a> (String ID, <a href="#"><u>IHTTPStreamerAdapter</u></a> adapter) Add an HTTPStreamerAdapter
String	<a href="#"><u>readVHostConfig</u></a> (String sName) Method to read xml config file..
void	<a href="#"><u>removeAcceptorListener</u></a> ( <a href="#"><u>IAcceptorNotify</u></a> acceptorListener) Remove acceptor listener.
boolean	<a href="#"><u>removeApplication</u></a> (String sName) Method to remove an application
void	<a href="#"><u>removeApplicationListener</u></a> ( <a href="#"><u>IApplicationNotify</u></a> applicationListener) Remove aplation listener.
void	<a href="#"><u>removeClient</u></a> (int clientId) Remove client from vHost.
void	<a href="#"><u>removeIdleWorkerListener</u></a> ( <a href="#"><u>IIIdleWorkerNotify</u></a> idleWorkerListener) Remove idleWorker listener
void	<a href="#"><u>reparentClient</u></a> ( <a href="#"><u>IClient</u></a> client) Move a client object to a new vhost.
void	<a href="#"><u>setAdminInterfaceHostPort</u></a> ( <a href="#"><u>HostPort</u></a> adminInterfaceHostPort) Set admin interface host port (not used)
void	<a href="#"><u>setApplicationTimeout</u></a> (int applicationTimeout) Set application time out (milliseconds).
void	<a href="#"><u>setClientIdleFrequency</u></a> (int clientIdleFrequency) Set default client idle frequency (milliseconds)
void	<a href="#"><u>setClientTimeout</u></a> (int clientTimeout) Set client timeout.
void	<a href="#"><u>setCoreHandlerPoolSize</u></a> (int corePoolSize) Set the handler core thread pool size.

void	<a href="#"><u>setCoreTransportPoolSize</u></a> (int corePoolSize) Set the transport core thread pool size.
void	<a href="#"><u>setDynamicLogProperties</u></a> ( java.util.Properties dynamicLogProperties) Set the dynamic log properties set at the vhost level
void	<a href="#"><u>setFileIOPoolSize</u></a> (int fileIOPoolSize) Set default file io thread pool size.
void	<a href="#"><u>setHTTPStreamerMaxPathLen</u></a> (int httpStreamerMaxPathLen) Set the max HTTP streamer path length
void	<a href="#"><u>setHTTPStreamerRequestValidator</u></a> ( <a href="#"><u>IVHostHTTPStreamerRequestValidator</u></a> httpRequestValidator) Set the HTTP streamer request validator
void	<a href="#"><u>setIdleCheckFrequency</u></a> (int idleCheckFrequency) Set idle check frequency (milliseconds)
void	<a href="#"><u>setIdleMinimumWaitTime</u></a> (int idleMinimumWaitTime) Set the minimum time (milliseconds) the idle worker thread will sleep before generating idle events
void	<a href="#"><u>setIdleWorkerCount</u></a> (int idleWorkerCount) Set number of threads used to generate idle events
void	<a href="#"><u>setKeepAliveTimeout</u></a> (int keepAliveTimeout) Set the RTMPT connection keep alive timeout
void	<a href="#"><u>setMaximumPendingReadBytes</u></a> (int maximumPendingReaderBytes) Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
void	<a href="#"><u>setMaximumPendingWriteBytes</u></a> (int maximumPendingWriteBytes) Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
void	<a href="#"><u>setMaximumSetBufferTime</u></a> (int maximumSetBufferTime) Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
void	<a href="#"><u>setNetConnectionIdleFrequency</u></a> (int netConnectionIdleFrequency) Set the server to server idle frequency (milliseconds)
void	<a href="#"><u>setNetConnectionProcessorCount</u></a> (int netConnectionProcessorCount) Set net connection processor count.
void	<a href="#"><u>setPingTimeout</u></a> (int pingTimeout) Set ping timeout (milliseconds)
void	<a href="#"><u>setRTPIdleFrequency</u></a> (int rtpIdleFrequency) Set default RTP idle frequency (milliseconds)
void	<a href="#"><u>setRTSPMaxPathLen</u></a> (int rtspStreamerMaxPathLen) Set the max RTSP stream path length
void	<a href="#"><u>setRTSPRequestValidator</u></a> ( <a href="#"><u>IVHostRTSPRequestValidator</u></a> rtspRequestValidator) Set the RTSP request validator

void	<a href="#"><u>setShuttingDown</u></a> (boolean shuttingDown) Set VHost shutting down flag
void	<a href="#"><u>setStartStartupStreams</u></a> (boolean startStarupStreams) Set to true to startup startup stream as vhost startup
void	<a href="#"><u>setValidationFrequency</u></a> (int validationFrequency) Set time between validation pings (milliseconds)
void	<a href="#"><u>shutdown</u></a> ( ) Shutdown.
void	<a href="#"><u>shutdownApplication</u></a> (String appName) Shutdown an application by name.
boolean	<a href="#"><u>startApplicationInstance</u></a> (String appName) Start an application instance.
boolean	<a href="#"><u>startApplicationInstance</u></a> (String appName, String appInstanceName) Start an application instance.
void	<a href="#"><u>startStartupStreams</u></a> ( ) Method to start startup streams
void	<a href="#"><u>stopStartupStreams</u></a> ( ) Method to stop startup streams
void	<a href="#"><u>suspendAllHostPorts</u></a> ( ) Suspend all HostPorts from accepting new connections.
boolean	<a href="#"><u>touchApplicationInstance</u></a> (String appName) Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds.
boolean	<a href="#"><u>touchApplicationInstance</u></a> (String appName, String appInstanceName) Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds.
void	<a href="#"><u>unbindAllHostPorts</u></a> ( ) Unbind all HostPorts and drop all connections
void	<a href="#"><u>updateLoggingDuration</u></a> ( ) Internal: update the internal logging values.
boolean	<a href="#"><u>writeVHostConfig</u></a> (String sName, String data) Method to write xml config file..

## Fields

### VHOST\_DEFAULT

```
public static final java.lang.String VHOST_DEFAULT
```

Constant value: **`_defaultVHost_`**



(continued from last page)

---

## LICENSECOUNTER\_PUBLISHER

```
public static final int LICENSECOUNTER_PUBLISHER
```

Constant value: **0**

---

## LICENSECOUNTER\_TRANSCODE\_DECODE

```
public static final int LICENSECOUNTER_TRANSCODE_DECODE
```

Constant value: **1**

---

## LICENSECOUNTER\_TRANSCODE\_ENCODE

```
public static final int LICENSECOUNTER_TRANSCODE_ENCODE
```

Constant value: **2**

---

## LICENSECOUNTER\_NDVR

```
public static final int LICENSECOUNTER_NDVR
```

Constant value: **3**

---

## LICENSECOUNTER\_DRM\_EZDRM\_LIVE

```
public static final int LICENSECOUNTER_DRM_EZDRM_LIVE
```

Constant value: **4**

---

## LICENSECOUNTER\_DRM\_EZDRM\_VOD

```
public static final int LICENSECOUNTER_DRM_EZDRM_VOD
```

Constant value: **5**

---

## LICENSECOUNTER\_DRM\_VERIMATRIX\_LIVE

```
public static final int LICENSECOUNTER_DRM_VERIMATRIX_LIVE
```

Constant value: **6**

---

## LICENSECOUNTER\_DRM\_VERIMATRIX\_VOD

```
public static final int LICENSECOUNTER_DRM_VERIMATRIX_VOD
```

Constant value: **7**

---

## LICENSECOUNTER\_PUBLISHERTRANSCODER

```
public static final int LICENSECOUNTER_PUBLISHERTRANSCODER
```

---

(continued from last page)

Constant value: **8**

---

## LICENSECOUNTER\_DRM\_BUYDRM\_LIVE

```
public static final int LICENSECOUNTER_DRM_BUYDRM_LIVE
```

Constant value: **9**

---

## LICENSECOUNTER\_DRM\_BUYDRM\_VOD

```
public static final int LICENSECOUNTER_DRM_BUYDRM_VOD
```

Constant value: **10**

---

## LICENSECOUNTER\_TRANSCODE\_DECODEPOLLING

```
public static final int LICENSECOUNTER_TRANSCODE_DECODEPOLLING
```

Constant value: **11**

---

## LICENSECOUNTER\_TRANSCODE\_ENCODEPOLLING

```
public static final int LICENSECOUNTER_TRANSCODE_ENCODEPOLLING
```

Constant value: **12**

---

## LICENSECOUNTER\_TRANSCODE\_STREAMNAMES

```
public static final int LICENSECOUNTER_TRANSCODE_STREAMNAMES
```

Constant value: **13**

---

## LICENSECOUNTER\_TRANSCODE\_DECODECOUNTAUDIO

```
public static final int LICENSECOUNTER_TRANSCODE_DECODECOUNTAUDIO
```

Constant value: **14**

---

## LICENSECOUNTER\_TRANSCODE\_DECODECOUNTVIDEO

```
public static final int LICENSECOUNTER_TRANSCODE_DECODECOUNTVIDEO
```

Constant value: **15**

---

## LICENSECOUNTER\_TRANSCODE\_DECODECOUNTAUDIOVIDEO

```
public static final int LICENSECOUNTER_TRANSCODE_DECODECOUNTAUDIOVIDEO
```

Constant value: **16**

---

## LICENSECOUNTER\_TRANSCODE\_ENCODECOUNTAUDIO

```
public static final int LICENSECOUNTER_TRANSCODE_ENCODECOUNTAUDIO
```

Constant value: **17**

---

## LICENSECOUNTER\_TRANSCODE\_ENCODECOUNTVIDEO

```
public static final int LICENSECOUNTER_TRANSCODE_ENCODECOUNTVIDEO
```

Constant value: **18**

---

## LICENSECOUNTER\_TRANSCODE\_ENCODECOUNTAUDIOVIDEO

```
public static final int LICENSECOUNTER_TRANSCODE_ENCODECOUNTAUDIOVIDEO
```

Constant value: **19**

---

## LICENSECOUNTER\_TOTAL

```
public static final int LICENSECOUNTER_TOTAL
```

Constant value: **20**

---

## COUNTER\_RTMP

```
public static final int COUNTER_RTMP
```

Constant value: **0**

---

## COUNTER\_RTP

```
public static final int COUNTER_RTP
```

Constant value: **1**

---

## COUNTER\_HTTPCUPERTINO

```
public static final int COUNTER_HTTPCUPERTINO
```

Constant value: **2**

---

## COUNTER\_HTTPSMOOTH

```
public static final int COUNTER_HTTPSMOOTH
```

Constant value: **3**

---

(continued from last page)

---

## COUNTER\_HTTPSANJOSE

```
public static final int COUNTER_HTTPSANJOSE
```

Constant value: **4**

---

## COUNTER\_HTTPWEBM

```
public static final int COUNTER_HTTPWEBM
```

Constant value: **5**

---

## COUNTER\_HTTPMPEGDASH

```
public static final int COUNTER_HTTPMPEGDASH
```

Constant value: **6**

---

## COUNTER\_HTTPDVRCHUNKS

```
public static final int COUNTER_HTTPDVRCHUNKS
```

Constant value: **7**

---

## COUNTER\_TOTAL

```
public static final int COUNTER_TOTAL
```

Constant value: **8**

---

## CODEC\_VIDEO\_UNKNOWN

```
public static final int CODEC_VIDEO_UNKNOWN
```

Constant value: **-1**

---

## CODEC\_VIDEO\_SPARK

```
public static final int CODEC_VIDEO_SPARK
```

Constant value: **2**

---

## CODEC\_VIDEO\_SCREEN

```
public static final int CODEC_VIDEO_SCREEN
```

Constant value: **3**

---

## CODEC\_VIDEO\_VP6

```
public static final int CODEC_VIDEO_VP6
```

---

(continued from last page)

Constant value: **4**

---

## CODEC\_VIDEO\_VP6A

```
public static final int CODEC_VIDEO_VP6A
```

Constant value: **5**

---

## CODEC\_VIDEO\_SCREEN2

```
public static final int CODEC_VIDEO_SCREEN2
```

Constant value: **6**

---

## CODEC\_VIDEO\_H264

```
public static final int CODEC_VIDEO_H264
```

Constant value: **7**

---

## CODEC\_VIDEO\_VP8

```
public static final int CODEC_VIDEO_VP8
```

Constant value: **8**

---

## CODEC\_VIDEO\_H263

```
public static final int CODEC_VIDEO_H263
```

Constant value: **9**

---

## CODEC\_VIDEO\_MPEG4

```
public static final int CODEC_VIDEO_MPEG4
```

Constant value: **10**

---

## CODEC\_VIDEO\_MPEG2

```
public static final int CODEC_VIDEO_MPEG2
```

Constant value: **11**

---

## CODEC\_AUDIO\_UNKNOWN

```
public static final int CODEC_AUDIO_UNKNOWN
```

Constant value: **-1**

---

## CODEC\_AUDIO\_PCM\_BE

```
public static final int CODEC_AUDIO_PCM_BE
```

Constant value: **0**

---

## CODEC\_AUDIO\_PCM\_SWF

```
public static final int CODEC_AUDIO_PCM_SWF
```

Constant value: **1**

---

## CODEC\_AUDIO\_AC3

```
public static final int CODEC_AUDIO_AC3
```

Constant value: **1**

---

## CODEC\_AUDIO\_MP3

```
public static final int CODEC_AUDIO_MP3
```

Constant value: **2**

---

## CODEC\_AUDIO\_PCM\_LE

```
public static final int CODEC_AUDIO_PCM_LE
```

Constant value: **3**

---

## CODEC\_AUDIO\_NELLYMOSER\_16MONO

```
public static final int CODEC_AUDIO_NELLYMOSER_16MONO
```

Constant value: **4**

---

## CODEC\_AUDIO\_NELLYMOSER\_8MONO

```
public static final int CODEC_AUDIO_NELLYMOSER_8MONO
```

Constant value: **5**

---

## CODEC\_AUDIO\_NELLYMOSER

```
public static final int CODEC_AUDIO_NELLYMOSER
```

Constant value: **6**

---

(continued from last page)

---

## CODEC\_AUDIO\_G711\_ALAW

```
public static final int CODEC_AUDIO_G711_ALAW
```

Constant value: **7**

---

## CODEC\_AUDIO\_G711\_MULAW

```
public static final int CODEC_AUDIO_G711_MULAW
```

Constant value: **8**

---

## CODEC\_AUDIO\_RESERVED

```
public static final int CODEC_AUDIO_RESERVED
```

Constant value: **9**

---

## CODEC\_AUDIO\_VORBIS

```
public static final int CODEC_AUDIO_VORBIS
```

Constant value: **9**

---

## CODEC\_AUDIO\_AAC

```
public static final int CODEC_AUDIO_AAC
```

Constant value: **10**

---

## CODEC\_AUDIO\_SPEEX

```
public static final int CODEC_AUDIO_SPEEX
```

Constant value: **11**

---

## CODEC\_AUDIO\_MP3\_8

```
public static final int CODEC_AUDIO_MP3_8
```

Constant value: **15**

---

## CODEC\_STREAM\_UNKNOWN

```
public static final int CODEC_STREAM_UNKNOWN
```

Constant value: **-1**

---

## CODEC\_STREAM\_MP2T

```
public static final int CODEC_STREAM_MP2T
```

---

(continued from last page)

Constant value: **0**

---

## FILEFORMAT\_UNKNOWN

```
public static final int FILEFORMAT_UNKNOWN
```

Constant value: **-1**

---

## FILEFORMAT\_FLV

```
public static final int FILEFORMAT_FLV
```

Constant value: **1**

---

## FILEFORMAT\_MP4

```
public static final int FILEFORMAT_MP4
```

Constant value: **2**

---

## CONTENTTYPE\_UNKNOWN

```
public static final byte CONTENTTYPE_UNKNOWN
```

AMF Content type: unknown  
Constant value: **0**

---

## CONTENTTYPE\_SETCHUNKSIZE

```
public static final byte CONTENTTYPE_SETCHUNKSIZE
```

AMF Content type: set packet chunk size  
Constant value: **1**

---

## CONTENTTYPE\_WATCHDOG

```
public static final byte CONTENTTYPE_WATCHDOG
```

AMF Content type: watch dog  
Constant value: **3**

---

## CONTENTTYPE\_BUFFERSIZE

```
public static final byte CONTENTTYPE_BUFFERSIZE
```

AMF Content type: set buffer size  
Constant value: **4**

---

## CONTENTTYPE\_ACKBANDWIDTH

```
public static final byte CONTENTTYPE_ACKBANDWIDTH
```

AMF Content type: set acknowledge bandwidth size  
Constant value: **5**



---

## CONTENTTYPE\_SETBANDWIDTH

public static final byte **CONTENTTYPE\_SETBANDWIDTH**

AMF Content type: set bandwidth size  
Constant value: **6**

---

## CONTENTTYPE\_AUDIO

public static final byte **CONTENTTYPE\_AUDIO**

AMF Content type: audio packet  
Constant value: **8**

---

## CONTENTTYPE\_VIDEO

public static final byte **CONTENTTYPE\_VIDEO**

AMF Content type: video packet  
Constant value: **9**

---

## CONTENTTYPE\_DATA

public static final byte **CONTENTTYPE\_DATA**

AMF Content type: data packet  
Constant value: **18**

---

## CONTENTTYPE\_DATA0

public static final byte **CONTENTTYPE\_DATA0**

AMF Content type: data packet (AMF0)  
Constant value: **18**

---

## CONTENTTYPE\_DATA3

public static final byte **CONTENTTYPE\_DATA3**

AMF Content type: data packet (AMF3)  
Constant value: **15**

---

## CONTENTTYPE\_SHAREDOBJECTS

public static final byte **CONTENTTYPE\_SHAREDOBJECTS**

AMF Content type: shared object packet (AMF0)  
Constant value: **19**

---

## CONTENTTYPE\_SHAREDOBJECTS0

public static final byte **CONTENTTYPE\_SHAREDOBJECTS0**

AMF Content type: shared object packet (AMF0)  
Constant value: **19**

---

(continued from last page)

## CONTENTTYPE\_SHARED OBJECTS3

```
public static final byte CONTENTTYPE_SHARED OBJECTS3
```

AMF Content type: shared object packet (AMF3)  
Constant value: **16**

## CONTENTTYPE\_FUNCTION

```
public static final byte CONTENTTYPE_FUNCTION
```

AMF Content type: function data (AMF0)  
Constant value: **20**

## CONTENTTYPE\_FUNCTION0

```
public static final byte CONTENTTYPE_FUNCTION0
```

AMF Content type: function data (AMF0)  
Constant value: **20**

## CONTENTTYPE\_MEDIACHUNK

```
public static final byte CONTENTTYPE_MEDIACHUNK
```

AMF Content type: media chunk  
Constant value: **22**

## CONTENTTYPE\_FUNCTION3

```
public static final byte CONTENTTYPE_FUNCTION3
```

AMF Content type: function data (AMF3)  
Constant value: **17**

## CONTENTTYPE\_PLAYCALLBACK

```
public static final byte CONTENTTYPE_PLAYCALLBACK
```

AMF Content type: play callback  
Constant value: **127**

## ACCEPTORS\_ACCEPTOR

```
public static final java.lang.String ACCEPTORS_ACCEPTOR
```

Acceptor types: acceptor  
Constant value: **acceptor**

## ACCEPTORS\_HANDLERADAPTER

```
public static final java.lang.String ACCEPTORS_HANDLERADAPTER
```

Acceptor types: handler  
Constant value: **handlerAdapter**

## Methods

(continued from last page)

## init

```
public void init(String basePath)
```

Initialize vHost.

**Parameters:**

basePath - base path to configuration files

---

## shutdown

```
public void shutdown()
```

Shutdown.

---

## getStreamTypes

```
public StreamList getStreamTypes()
```

Get default stream type.

**Returns:**

default stream type

---

## getProperty

```
public String getProperty(String key)
```

Get virtual host property.

**Parameters:**

key - key

**Returns:**

property value or null if does not exist

---

## getClientTimeout

```
public int getClientTimeout()
```

Get client timeout.

**Returns:**

client timeout

---

## getNextNetConnectionId

```
public int getNextNetConnectionId()
```

Get next connection id.

**Returns:**

next connection id

---

## getClient

```
public IClient getClient(int clientId)
```

---

(continued from last page)

Get client by client id.

**Parameters:**

clientId - client id

**Returns:**

client

---

## getClient

```
public IClient getClient(int clientId,  
                        boolean create)
```

Get client by client id and create if does not exist.

**Parameters:**

clientId - client id

create - create if does not exist

**Returns:**

client

---

## removeClient

```
public void removeClient(int clientId)
```

Remove client from vHost.

**Parameters:**

clientId - client id

---

## killClient

```
public void killClient(int clientId)
```

Remove client from vHost and send disconnect message.

**Parameters:**

clientId - client id

---

## killRTSPSession

```
public void killRTSPSession(String rtspSessionId)
```

Kill an RTSP connection by the RTSP session id

**Parameters:**

rtspSessionId - RTSP session id

---

## getApplication

```
public IApplication getApplication(String applicationName)
```

Get application by name.

**Parameters:**

applicationName - application name

---

(continued from last page)

**Returns:**  
application

---

## isApplicationLoaded

```
public boolean isApplicationLoaded(String applicationName)
```

Return true is the application is loaded

**Parameters:**  
applicationName - application name

**Returns:**  
true if application is loaded

---

## getHomePath

```
public String getHomePath()
```

Get vHost configuration path.

**Returns:**  
configuration path

---

## getProperties

```
public WMSProperties getProperties()
```

Get properties attached to this vHost.

**Returns:**  
properties attached to this vHost

---

## getCoreTransportPoolSize

```
public int getCoreTransportPoolSize()
```

Get the transport core thread pool size.

**Returns:**  
default core thread pool size

---

## setCoreTransportPoolSize

```
public void setCoreTransportPoolSize(int corePoolSize)
```

Set the transport core thread pool size.

**Parameters:**  
corePoolSize - core thread pool size

---

## getCoreHandlerPoolSize

```
public int getCoreHandlerPoolSize()
```

Get the handler core thread pool size.

**Returns:**

(continued from last page)

default core thread pool size

---

## setCoreHandlerPoolSize

```
public void setCoreHandlerPoolSize(int corePoolSize)
```

Set the handler core thread pool size.

**Parameters:**

corePoolSize - core thread pool size

---

## getFileIOPoolSize

```
public int getFileIOPoolSize()
```

Get the default file io pool size.

**Returns:**

default file io pool size

---

## setFileIOPoolSize

```
public void setFileIOPoolSize(int fileIOPoolSize)
```

Set default file io thread pool size.

**Parameters:**

fileIOPoolSize - default file io thread pool size

---

## setClientTimeout

```
public void setClientTimeout(int clientTimeout)
```

Set client timeout. An inactive client connected by RTMPT protocol will be deleted after this timeout.

**Parameters:**

clientTimeout - client timeout

---

## getHostPortsList

```
public HostPortList getHostPortsList()
```

Get list of host port definitions for vHost.

**Returns:**

list of host port definitions for vHost

---

## getThreadPool

```
public ThreadPool getThreadPool()
```

Get the VHost handler thread pool. Same as getHandlerThreadPool.

**Returns:**

VHost handler thread pool

---

(continued from last page)

---

## getTransportThreadPool

```
public ThreadPool getTransportThreadPool ( )
```

Get the VHost transport thread pool. This thread pool is used to read/write data from the transports sockets.

**Returns:**

VHost transport thread pool

---

## getHandlerThreadPool

```
public ThreadPool getHandlerThreadPool ( )
```

Get the VHost handler thread pool. This thread pool is used to process the incoming events.

**Returns:**

VHost handler thread pool

---

## getName

```
public String getName ( )
```

Get vHost name

**Returns:**

vHost name

---

## setAdminInterfaceHostPort

```
public void setAdminInterfaceHostPort (HostPort adminInterfaceHostPort )
```

Set admin interface host port (not used)

**Parameters:**

adminInterfaceHostPort - admin interface host port

---

## getClientCount

```
public int getClientCount ( )
```

Get number of clients connected to this vHost.

**Returns:**

number of clients connected to this vHost

---

## getNetConnectionProcessorCount

```
public int getNetConnectionProcessorCount ( )
```

Get net connection processor count. Number of threads used for server to server communication (not finished).

**Returns:**

net connection processor count

---

## setNetConnectionProcessorCount

```
public void setNetConnectionProcessorCount (int netConnectionProcessorCount )
```

---

(continued from last page)

Set net connection processor count. Number of threads used for server to server communication (not finished).

**Parameters:**

netConnectionProcessorCount - net connection processor count

---

## addApplicationListener

```
public void addApplicationListener(IApplicationNotify applicationListener)
```

Add application listener. An application listener will receive the following events: onApplicationCreate, onApplicationDestroy.

**Parameters:**

applicationListener - application listener

---

## removeApplicationListener

```
public void removeApplicationListener(IApplicationNotify applicationListener)
```

Remove application listener.

**Parameters:**

applicationListener - application listener

---

## addAcceptorListener

```
public void addAcceptorListener(IAcceptorNotify acceptorListener)
```

Add acceptor listener. Acceptor listeners will receive the following events: onAcceptorCreate, onAcceptorDestroy.

**Parameters:**

acceptorListener - acceptor listener

---

## removeAcceptorListener

```
public void removeAcceptorListener(IAcceptorNotify acceptorListener)
```

Remove acceptor listener.

**Parameters:**

acceptorListener - acceptor listener

---

## getIOScheduler

```
public IOScheduler getIOScheduler()
```

Get IO scheduler for vHost. IO scheduler is used to schedule reads from the disk to increase server throughput for static flv serving.

**Returns:**

IO scheduler for vHost

---

## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter()
```

Get vHost IO performance counter.

**Returns:**

io performance counter

---



## getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

Get vHost IO performance counter for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index (see IVHost.COUNTER\_\*)

**Returns:**

io performance counter

---

## getConnectionCounter

```
public ConnectionCounter getConnectionCounter()
```

Get vHost connection counter.

**Returns:**

connection counter

---

## getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get vHost connection counter for a specific technology (see IVHost.COUNTER\_\*)

**Parameters:**

counterIndex - counter index (see IVHost.COUNTER\_\*)

**Returns:**

connection counter

---

## getDateStarted

```
public String getDateStarted()
```

Get date and time the server was started.

**Returns:**

date and time the server was started

---

## getTimeRunning

```
public String getTimeRunning()
```

Get the time vHost has been running.

**Returns:**

formatted string with vHost uptime

---

## getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

---

(continued from last page)

**Returns:**

time running in seconds

---

## getConnectionLimit

```
public int getConnectionLimit()
```

Get vHost connection limit.

**Returns:**

vHost connection limit

---

## getMediaReaders

```
public MediaReaderList getMediaReaders()
```

Get the media readers attached to vHost (MediaReaders.xml).

**Returns:**

media readers attached to vHost

---

## getMediaWriters

```
public MediaWriterList getMediaWriters()
```

Get the media writers attached to vHost (MediaWriters.xml).

**Returns:**

media writers attached to vHost

---

## getMp3TagMap

```
public java.util.Map getMp3TagMap()
```

Get MP3 tag map attached to vHost (MP3Tags.xml).

**Returns:**

MP3 tag map attached to vHost

---

## getCEACaptionConversionContext

```
public CEACaptionConversionContext getCEACaptionConversionContext()
```

Get CEACaptionConversionContextMP3 tag map attached to vHost (CEACaptionConversion.xml).

**Returns:**

MP3 tag map attached to vHost

---

## updateLoggingDuration

```
public void updateLoggingDuration()
```

Internal: update the internal logging values.

---

## getApplicationTimeout

```
public int getApplicationTimeout()
```

(continued from last page)

Get application time out (milliseconds). Time from last client disconnect to application destruction.

**Returns:**

application time out (milliseconds)

---

## setApplicationTimeout

```
public void setApplicationTimeout(int applicationTimeout)
```

Set application time out (milliseconds).

**Parameters:**

applicationTimeout - application time out (milliseconds)

---

## getPingTimeout

```
public int getPingTimeout()
```

Get ping timeout (milliseconds)

**Returns:**

ping timeout (milliseconds)

---

## setPingTimeout

```
public void setPingTimeout(int pingTimeout)
```

Set ping timeout (milliseconds)

**Parameters:**

pingTimeout - ping timeout (milliseconds)

---

## getValidationFrequency

```
public int getValidationFrequency()
```

Get time between validation pings (milliseconds)

**Returns:**

time between validation pings (milliseconds)

---

## setValidationFrequency

```
public void setValidationFrequency(int validationFrequency)
```

Set time between validation pings (milliseconds)

**Parameters:**

validationFrequency - time between validation pings (milliseconds)

---

## getMaximumPendingWriteBytes

```
public int getMaximumPendingWriteBytes()
```

Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

**Returns:**

maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

---

## setMaximumPendingWriteBytes

```
public void setMaximumPendingWriteBytes(int maximumPendingWriteBytes)
```

Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

**Parameters:**

maximumPendingWriteBytes - maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

---

## getMaximumPendingReadBytes

```
public int getMaximumPendingReadBytes()
```

Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

**Returns:**

maximum number of bytes a client connection can have waiting to be written before the connection is terminated

---

## setMaximumPendingReadBytes

```
public void setMaximumPendingReadBytes(int maximumPendingReaderBytes)
```

Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

**Parameters:**

maximumPendingReaderBytes - maximum number of bytes a client connection can have waiting to be written before the connection is terminated

---

## getMaximumSetBufferTime

```
public int getMaximumSetBufferTime()
```

Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

**Returns:**

maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

---

## setMaximumSetBufferTime

```
public void setMaximumSetBufferTime(int maximumSetBufferTime)
```

Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

**Parameters:**

maximumSetBufferTime - maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

---

## getApplicationLock

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
getApplicationLock()
```

Get the object used in synchronized statements to lock and application.

---

---

(continued from last page)

**Returns:**

object used in synchronized statements to lock and application

---

**getClientIdleFrequency**

```
public int getClientIdleFrequency()
```

Get default client idle frequency (milliseconds)

**Returns:**

default client idle frequency (milliseconds)

---

**setClientIdleFrequency**

```
public void setClientIdleFrequency(int clientIdleFrequency)
```

Set default client idle frequency (milliseconds)

**Parameters:**

clientIdleFrequency - default client idle frequency (milliseconds)

---

**getRTPIdeFrequency**

```
public int getRTPIdeFrequency()
```

Get default RTP idle frequency (milliseconds)

**Returns:**

default RTP idle frequency (milliseconds)

---

**setRTPIdeFrequency**

```
public void setRTPIdeFrequency(int rtpIdleFrequency)
```

Set default RTP idle frequency (milliseconds)

**Parameters:**

rtpIdleFrequency - RTP default client idle frequency (milliseconds)

---

**getNetConnectionIdleFrequency**

```
public int getNetConnectionIdleFrequency()
```

Get server to server idle frequency (milliseconds)

**Returns:**

server to server idle frequency (milliseconds)

---

**setNetConnectionIdleFrequency**

```
public void setNetConnectionIdleFrequency(int netConnectionIdleFrequency)
```

Set the server to server idle frequency (milliseconds)

**Parameters:**

netConnectionIdleFrequency - server to server idle frequency (milliseconds)

---

(continued from last page)

## getIdleCheckFrequency

```
public int getIdleCheckFrequency()
```

Get idle check frequency (milliseconds)

**Returns:**

idle check frequency (milliseconds)

---

## setIdleCheckFrequency

```
public void setIdleCheckFrequency(int idleCheckFrequency)
```

Set idle check frequency (milliseconds)

**Parameters:**

idleCheckFrequency - idle check frequency (milliseconds)

---

## getIdleWorkerCount

```
public int getIdleWorkerCount()
```

Get number of threads used to generate idle events

**Returns:**

number of threads used to generate idle events

---

## setIdleWorkerCount

```
public void setIdleWorkerCount(int idleWorkerCount)
```

Set number of threads used to generate idle events

**Parameters:**

idleWorkerCount - number of threads used to generate idle events

---

## getKeepAliveTimeout

```
public int getKeepAliveTimeout()
```

Get the RTMPT connection keep alive timeout

**Returns:**

RTMPT connection keep alive timeout

---

## setKeepAliveTimeout

```
public void setKeepAliveTimeout(int keepAliveTimeout)
```

Set the RTMPT connection keep alive timeout

**Parameters:**

keepAliveTimeout - RTMPT connection keep alive timeout

---

## addIdleWorkerListener

```
public void addIdleWorkerListener(IIdleWorkerNotify idleWorkerListener)
```

(continued from last page)

Add idleWorker listener. An idleWorker listener will receive the following events: onIdleWorkerCreate, onIdleWorkerDestroy.

**Parameters:**

idleWorkerListener - idleWorker listener

---

## removeIdleWorkerListener

```
public void removeIdleWorkerListener(IIIdleWorkerNotify idleWorkerListener)
```

Remove idleWorker listener

**Parameters:**

idleWorkerListener - idleWorker listener

---

## getNetConnectionHostPortConfig

```
public HostPortConfig getNetConnectionHostPortConfig()
```

Get the socket configuration for server to server connections

**Returns:**

socket configuration for server to server connections

---

## getMediaCasterSettings

```
public MediaCasterSettings getMediaCasterSettings()
```

Get the media caster settings

**Returns:**

media caster settings

---

## getMediaCasterList

```
public MediaCasterList getMediaCasterList()
```

Get the list of media caster definitions (MediaCaster.xml)

**Returns:**

list of media caster definitions

---

## getApplicationNames

```
public java.util.List getApplicationNames()
```

Get a list of application names

**Returns:**

list of application names

---

## getApplicationFolderNames

```
public java.util.List getApplicationFolderNames()
```

Get a list of application folder names

**Returns:**

list of application folder names

## applicationExists

```
public boolean applicationExists(String name)
```

Return true if an application folder exists for this application name

**Parameters:**

name - application name

**Returns:**

true if an application folder exists for this application name

---

## getRTPContext

```
public RTPContext getRTPContext()
```

Get the RTP (real time protocol) virtual host context

**Returns:**

RTP (real time protocol) virtual host context

---

## getHTTPStreamerContext

```
public HTTPStreamerContext getHTTPStreamerContext()
```

Get the HTTPStreamer (Cupertino Streaming and Silverlight Smooth Streaming) host context

**Returns:**

HTTPStreamer (Cupertino Streaming and Silverlight Smooth Streaming) host context

---

## getRTPDatagramConfigIncoming

```
public com.wowza.wms.rtp.transport.RTPUDPDatagramConfig getRTPDatagramConfigIncoming()
```

Get the RTP Datagram Socket configuration

**Returns:**

RTP Datagram Socket configuration

---

## getRTPDatagramConfigOutgoing

```
public com.wowza.wms.rtp.transport.RTPUDPDatagramConfig getRTPDatagramConfigOutgoing()
```

Get the RTP Datagram Socket configuration

**Returns:**

RTP Datagram Socket configuration

---

## getAuthenticationList

```
public AuthenticationList getAuthenticationList()
```

Get the list of available authentication methods

**Returns:**

list of available authentication methods

---



## getIdleMinimumWaitTime

```
public int getIdleMinimumWaitTime()
```

Get the minimum time (milliseconds) the idle worker thread will sleep before generating idle events

**Returns:**

minimum time (milliseconds) the idle worker thread will sleep before generating idle events

---

## setIdleMinimumWaitTime

```
public void setIdleMinimumWaitTime(int idleMinimumWaitTime)
```

Set the minimum time (milliseconds) the idle worker thread will sleep before generating idle events

**Parameters:**

idleMinimumWaitTime - minimum time (milliseconds) the idle worker thread will sleep before generating idle events

---

## getIdleWorkers

```
public IdleWorkersUtil getIdleWorkers()
```

Get the idle worker utility

**Returns:**

idle worker utility

---

## isShuttingDown

```
public boolean isShuttingDown()
```

Is the VHost shutting down

**Returns:**

true if the vhost is shutting down

---

## setShuttingDown

```
public void setShuttingDown(boolean shuttingDown)
```

Set VHost shutting down flag

**Parameters:**

shuttingDown - true if the vhost is shutting down

---

## reparentClient

```
public void reparentClient(IClient client)
```

Move a client object to a new vhost. This can only be done right after the handshake process has completed. See `IVHostNotify.onVHostClientConnect`.

**Parameters:**

client - client object to move

---

(continued from last page)

---

## getDynamicLogProperties

```
public java.util.Properties getDynamicLogProperties()
```

Get the dynamic log properties defined at the vhost level in conf/log4j.properties

**Returns:**

dynamic log properties defined at the vhost level

---

## setDynamicLogProperties

```
public void setDynamicLogProperties(java.util.Properties dynamicLogProperties)
```

Set the dynamic log properties set at the vhost level

**Parameters:**

dynamicLogProperties - dynamic log properties defined at the vhost level

---

## shutdownApplication

```
public void shutdownApplication(String appName)
```

Shutdown an application by name. This will disconnect all clients connected to all child application instances.

**Parameters:**

appName - application name

---

## unbindAllHostPorts

```
public void unbindAllHostPorts()
```

Unbind all HostPorts and drop all connections

---

## suspendAllHostPorts

```
public void suspendAllHostPorts()
```

Suspend all HostPorts from accepting new connections. Current connections will continue to be serviced

---

## closeHostPort

```
public void closeHostPort(HostPort hostPort,  
    boolean isSuspend)
```

Close an individual HostPort

**Parameters:**

hostPort - host port to close

isSuspend - if true will just suspend the HostPort from accepting new connections, if false will unbind and drop all connections

---

## isSuspended

```
public boolean isSuspended()
```

Returns true is all HostPorts connected to this VHost are suspended

---

(continued from last page)

---

## touchApplicationInstance

```
public boolean touchApplicationInstance(String appName)
```

Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds.

**Parameters:**

appName - application name

**Returns:**

true is successful

---

## touchApplicationInstance

```
public boolean touchApplicationInstance(String appName,  
    String appInstanceName)
```

Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds. The default appInstanceName `_definst_` will be used.

**Parameters:**

appName - application name

appInstanceName - app instance name

**Returns:**

true is successful

---

## startApplicationInstance

```
public boolean startApplicationInstance(String appName)
```

Start an application instance. The default appInstanceName `_definst_` will be used.

**Parameters:**

appName - application name

**Returns:**

true is successful

---

## startApplicationInstance

```
public boolean startApplicationInstance(String appName,  
    String appInstanceName)
```

Start an application instance.

**Parameters:**

appName - application name

appInstanceName - app instance name

**Returns:**

true is successful

---

## getUDPTransportManager

```
public com.wowza.wms.rtp.transport.UDPTransportManager getUDPTransportManager()
```

Get the UDP transport manager.

---

(continued from last page)

**Returns:**

UDP transport manager

---

**getHTTPStreamerList**

```
public HTTPStreamerList getHTTPStreamerList()
```

Get the list of HTTPStreamers

**Returns:**

list of HTTPStreamers

---

**getHTTPStreamerAdapter**

```
public IHTTPStreamerAdapter getHTTPStreamerAdapter(String ID)
```

Get an HTTPStreamerAdapter by ID

**Parameters:**

ID - HTTPStreamerAdapter ID

**Returns:**

HTTPStreamerAdapter

---

**putHTTPStreamerAdapter**

```
public void putHTTPStreamerAdapter(String ID,  
    IHTTPStreamerAdapter adapter)
```

Add an HTTPStreamerAdapter

**Parameters:**

ID - HTTPStreamerAdapter ID

adapter - HTTPStreamerAdapter

---

**getHTTPStreamerAdapterIDs**

```
public java.util.List getHTTPStreamerAdapterIDs()
```

Get a list of HTTPStreamerAdapter IDs

**Returns:**

list of HTTPStreamerAdapter IDs

---

**getLiveStreamPacketizerList**

```
public LiveStreamPacketizerList getLiveStreamPacketizerList()
```

Get the LiveStreamPacketizerList

**Returns:**

LiveStreamPacketizerList

---

**getLiveStreamTranscoderList**

```
public LiveStreamTranscoderList getLiveStreamTranscoderList()
```

Get the LiveStreamTranscoderList

(continued from last page)

**Returns:**

LiveStreamTranscoderList

---

## getTimedTextProviderConfig

```
public TimedTextProviderConfiguration getTimedTextProviderConfig()
```

Get the config of TimedTextProviders

**Returns:**

TimedTextProviders config

---

## getStartupStreams

```
public java.util.List getStartupStreams()
```

Get the list of streams to start at virtual host startup

**Returns:**

list of streams to start at virtual host startup

---

## addStartupStream

```
public void addStartupStream(StartupStream startupStream)
```

Add a stream to the list of streams to start and virtual host startup

**Parameters:**

startupStream - startup stream

---

## isStartStarupStreams

```
public boolean isStartStarupStreams()
```

Returns true if the startup streams are to start and vhost startup

**Returns:**

true if the startup streams are to start and vhost startup

---

## setStartStarupStreams

```
public void setStartStarupStreams(boolean startStarupStreams)
```

Set to true to startup startup stream as vhost startup

**Parameters:**

startStarupStreams - true if the startup streams are to start and vhost startup

---

## startStartupStreams

```
public void startStartupStreams()
```

Method to start startup streams

---

## stopStartupStreams

```
public void stopStartupStreams()
```

(continued from last page)

Method to stop startup streams

---

## createApplication

```
public boolean createApplication(String sName,  
    String sStreamType,  
    String sContentLoc)
```

Method to create a new application

---

## removeApplication

```
public boolean removeApplication(String sName)
```

Method to remove an application

---

## readVHostConfig

```
public String readVHostConfig(String sName)
```

Method to read xml config file..

---

## writeVHostConfig

```
public boolean writeVHostConfig(String sName,  
    String data)
```

Method to write xml config file..

---

## getDvrRecorderList

```
public DvrRecorderList getDvrRecorderList()
```

Get the DvrRecorderList

**Returns:**

list of DVR Recorders

---

## getDvrStoreList

```
public DvrStoreList getDvrStoreList()
```

Get the list of DVR Stores

**Returns:**

list of DVR Stores

---

## getMediaReaderContentType

```
public int getMediaReaderContentType(String mediaType)
```

Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE\_\*)

**Parameters:**

mediaType - mediaType (such as flv or smil)

**Returns:**

content type (see IMediaReader.CONTENTTYPE\_\*)

## getProtocolUsage

```
public void getProtocolUsage(boolean[] protocolsInUse)
```

Get the protocols in use by this application instance (see IApplicationInstance.PROTOCOLUSAGE\_\*)

---

## getTranscoderVODContext

```
public com.wowza.wms.transcoder.vod.TranscoderVODContext getTranscoderVODContext()
```

Get the VOD transcoder context

**Returns:**

VOD transcoder context

---

## getHTTPStreamerRequestValidator

```
public IVHostHTTPStreamerRequestValidator getHTTPStreamerRequestValidator()
```

Get the HTTP streamer request validator

**Returns:**

HTTP streamer request validator

---

## setHTTPStreamerRequestValidator

```
public void setHTTPStreamerRequestValidator(IVHostHTTPStreamerRequestValidator httpRequestValidator)
```

Set the HTTP streamer request validator

**Parameters:**

httpRequestValidator - HTTP streamer request validator

---

## getHTTPStreamerMaxPathLen

```
public int getHTTPStreamerMaxPathLen()
```

Get the max HTTP streamer path length

**Returns:**

max HTTP streamer path length

---

## setHTTPStreamerMaxPathLen

```
public void setHTTPStreamerMaxPathLen(int httpStreamerMaxPathLen)
```

Set the max HTTP streamer path length

**Parameters:**

httpStreamerMaxPathLen - max HTTP streamer path length

---

## getRTSPRequestValidator

```
public IVHostRTSPRequestValidator getRTSPRequestValidator()
```

Get the RTSP request validator

---

(continued from last page)

**Returns:**RTSP request validator

---

**setRTSPRequestValidator**

```
public void setRTSPRequestValidator(IVHostRTSPRequestValidator rtspRequestValidator)
```

Set the RTSP request validator

**Parameters:**rtspRequestValidator - RTSP request validator

---

**getRTSPMaxPathLen**

```
public int getRTSPMaxPathLen()
```

Get the max RTSP stream path length

**Returns:**max RTSP stream path length

---

**setRTSPMaxPathLen**

```
public void setRTSPMaxPathLen(int rtspStreamerMaxPathLen)
```

Set the max RTSP stream path length

**Parameters:**rtspStreamerMaxPathLen - max RTSP stream path length

---



---

## com.wowza.wms.vhost Interface IVHostHTTPStreamerRequestValidator

---

public interface IVHostHTTPStreamerRequestValidator  
extends

---

### Method Summary

boolean	<a href="#">validateHTTPStreamerRequest</a> (RtmpRequestMessage request, <a href="#">HostPort</a> hostPort, String path)
---------	--

---

### Methods

#### validateHTTPStreamerRequest

```
public boolean validateHTTPStreamerRequest(RtmpRequestMessage request,  
    HostPort hostPort,  
    String path)
```

## com.wowza.wms.vhost Interface IVHostItemNotify

public interface **IVHostItemNotify**  
extends

IVHostItemNotify: listener interface used by VHostList addVHostItemListener

VHostList is the list vHost definitions in VHosts.xml not the vHosts themselves. With this listener interface you can monitor the vHost definition changes.

### Method Summary

void	<a href="#">onVHostItemCreate</a> ( <a href="#">VHostItem</a> vhostItem) Triggered when vHostItem created
void	<a href="#">onVHostItemDestroy</a> ( <a href="#">VHostItem</a> vhostItem) Triggered when vHostItem destroyed
void	<a href="#">onVHostItemUpdate</a> ( <a href="#">VHostItem</a> vhostItem) Triggered when vHostItem updated

### Methods

#### onVHostItemCreate

public void **onVHostItemCreate**([VHostItem](#) vhostItem)

Triggered when vHostItem created

**Parameters:**

vhostItem - vhostItem

#### onVHostItemUpdate

public void **onVHostItemUpdate**([VHostItem](#) vhostItem)

Triggered when vHostItem updated

**Parameters:**

vhostItem - vhostItem

#### onVHostItemDestroy

public void **onVHostItemDestroy**([VHostItem](#) vhostItem)

Triggered when vHostItem destroyed

**Parameters:**

vhostItem - vhostItem

## com.wowza.wms.vhost Interface IVHostNotify

public interface **IVHostNotify**  
extends

IVHostNotify: listener interface used by VHostSingleton addVHostListener

### Method Summary

void	<a href="#">onVHostClientConnect</a> ( <a href="#">IVHost</a> vhost, <a href="#">IClient</a> inClient, <a href="#">com.wowza.wms.request.RequestFunction</a> function, <a href="#">AMFDataList</a> params) Triggered before a client connects to this virtual host.
void	<a href="#">onVHostCreate</a> ( <a href="#">IVHost</a> vhost) Triggered when vHost created
void	<a href="#">onVHostInit</a> ( <a href="#">IVHost</a> vhost) Triggered when vHost initialized
void	<a href="#">onVHostShutdownComplete</a> ( <a href="#">IVHost</a> vhost) Triggered at the end of vhost shutdown
void	<a href="#">onVHostShutdownStart</a> ( <a href="#">IVHost</a> vhost) Triggered at the beginning of vhost shutdown

### Methods

#### onVHostCreate

public void **onVHostCreate**([IVHost](#) vhost)

Triggered when vHost created

**Parameters:**

vhost

#### onVHostInit

public void **onVHostInit**([IVHost](#) vhost)

Triggered when vHost initialized

**Parameters:**

vhost - vhost

#### onVHostShutdownStart

public void **onVHostShutdownStart**([IVHost](#) vhost)

Triggered at the beginning of vhost shutdown

(continued from last page)

**Parameters:**vhost - vhost

---

**onVHostShutdownComplete**

```
public void onVHostShutdownComplete(IVHost vhost)
```

Triggered at the end of vhost shutdown

**Parameters:**vhost - vhost

---

**onVHostClientConnect**

```
public void onVHostClientConnect(IVHost vhost,  
    IClient inClient,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Triggered before a client connects to this virtual host. Provides an opportunity to rewrite the information that is being used to connect.

**Parameters:**

vhost

inClient - client object of the connection

function - function

params - parameters

---

## com.wowza.wms.vhost Interface IVHostRTSPRequestValidator

---

public interface IVHostRTSPRequestValidator  
extends

---

### Method Summary

boolean	<a href="#">validateRTSPRequest</a> (com.wowza.wms.rtsp.RTSPRequestMessage req)
---------	---

---

### Methods

#### **validateRTSPRequest**

public boolean **validateRTSPRequest**(com.wowza.wms.rtsp.RTSPRequestMessage req)

---

## com.wowza.wms.vhost Interface IWorkerThreadClear

---

public interface **IWorkerThreadClear**  
extends

IWorkerThreadClear: Internal use.

---

### Method Summary

void	<a href="#">clear()</a>
void	<a href="#">reset()</a>

---

### Methods

#### **reset**

public void **reset**()

---

#### **clear**

public void **clear**()

## com.wowza.wms.vhost Class StreamItem

java.lang.Object

└─com.wowza.wms.vhost.StreamItem

public class **StreamItem**  
extends Object

StreamItem: data object that defines a streamType.

### Constructor Summary

public	<a href="#">StreamItem</a> (String name, String baseClass, String playClass) Create a new streamItem
--------	---

### Method Summary

void	<a href="#">clearProperty</a> (String name) Clear property.
String	<a href="#">getBaseClass</a> () Get base class path.
String	<a href="#">getDescription</a> () Get streamType description.
String	<a href="#">getName</a> () Get streamType name.
String	<a href="#">getPlayClass</a> () Get play class path.
<a href="#">WMSProperties</a>	<a href="#">getProperties</a> () Get properties.
String	<a href="#">getProperty</a> (String name) Get property by name.
void	<a href="#">setBaseClass</a> (String baseClass) Set base class path.
void	<a href="#">setDescription</a> (String description) Set streamType description.
void	<a href="#">setName</a> (String name) Set streamType name.
void	<a href="#">setPlayClass</a> (String playClass) Set play class path.
void	<a href="#">setProperty</a> (String name, String value) Set property value.

String	<a href="#">toString()</a>
--------	----------------------------

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

## Constructors

### StreamItem

```
public StreamItem(String name,  
                  String baseClass,  
                  String playClass)
```

Create a new streamItem

**Parameters:**

`name` - streamType name  
`baseClass` - base class path  
`playClass` - play class path

## Methods

### getBaseClass

```
public String getBaseClass()
```

Get base class path.

**Returns:**

base clas path

### setBaseClass

```
public void setBaseClass(String baseClass)
```

Set base class path.

**Parameters:**

`baseClass` - base class path

### getName

```
public String getName()
```

Get streamType name.

**Returns:**

streamType name

### setName

```
public void setName(String name)
```



(continued from last page)

Set streamType name.

**Parameters:**

name - streamType name

---

## getPlayClass

```
public String getPlayClass()
```

Get play class path.

**Returns:**

play class path

---

## setPlayClass

```
public void setPlayClass(String playClass)
```

Set play class path.

**Parameters:**

playClass - play class path

---

## setProperty

```
public void setProperty(String name,  
                        String value)
```

Set property value.

**Parameters:**

name - property name

value - property value

---

## clearProperty

```
public void clearProperty(String name)
```

Clear property.

**Parameters:**

name - property name

---

## getProperty

```
public String getProperty(String name)
```

Get property by name.

**Parameters:**

name - property name

**Returns:**

property value

---

## getProperties

```
public WMSProperties getProperties()
```

---

(continued from last page)

Get properties.

**Returns:**

properties

---

## getDescription

```
public String getDescription()
```

Get streamType description.

**Returns:**

streamType description

---

## setDescription

```
public void setDescription(String description)
```

Set streamType description.

**Parameters:**

description - streamType description

---

## toString

```
public String toString()
```

## com.wowza.wms.vhost Class StreamList

java.lang.Object

└─com.wowza.wms.vhost.StreamList

```
public class StreamList
extends Object
```

StreamList: collection of StreamItems

### Constructor Summary

public	<a href="#">StreamList()</a> Create empty StreamList
--------	---

### Method Summary

<a href="#">StreamItem</a>	<a href="#">getStreamDef(String name)</a> Get streamItem by streamType name.
java.util.Map	<a href="#">getStreamDefs()</a> Get Map of streamItems (by streamType names).
java.util.List	<a href="#">getStreamTypeNames()</a> Get list of streamType names.

#### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

### Constructors

#### StreamList

```
public StreamList()
```

Create empty StreamList

### Methods

#### getStreamDefs

```
public java.util.Map getStreamDefs()
```

Get Map of streamItems (by streamType names).

##### Returns:

Map of streamItems

## getStreamTypeNames

```
public java.util.List getStreamTypeNames()
```

Get list of streamType names. Returns shallow copy of list.

**Returns:**

list of streamType names

---

## getStreamDef

```
public StreamItem getStreamDef(String name)
```

Get streamItem by streamType name.

**Parameters:**

name - streamType name

**Returns:**

streamItem

---

## com.wowza.wms.vhost Class ThreadPool

java.lang.Object

└─com.wowza.wms.vhost.ThreadPool

public class **ThreadPool**  
extends Object

ThreadPool: class for managing a pool of threads.

### Constructor Summary

public	<a href="#">ThreadPool</a> ( <a href="#">IVHost</a> vhost, String name) Create a new thread pool attached to a vHost.
--------	--

### Method Summary

void	<a href="#">execute</a> (Runnable command) Execute a runnable object.
int	<a href="#">getActiveCount</a> () Get number of active threads.
java.util.concurrent. Executor	<a href="#">getExecutor</a> () Get the underlying Executor pool.
int	<a href="#">getQueueSize</a> () Get the number of command objects in the LinkedBlockingQueue.
void	<a href="#">init</a> (int corePoolSize) Initialize threadPool.
void	<a href="#">terminate</a> () Terminate all threads and cleanup threadPool.

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

## Constructors

### ThreadPool

public **ThreadPool**([IVHost](#) vhost,  
[String](#) name)

Create a new thread pool attached to a vHost.

**Parameters:**

(continued from last page)

vhost - vHost

## Methods

### init

```
public void init(int corePoolSize)
```

Initialize threadPool.

**Parameters:**

corePoolSize - core pool size

### terminate

```
public void terminate()
```

Terminate all threads and cleanup threadPool.

### execute

```
public void execute(Runnable command)
```

Execute a runnable object. If the threadPool is at the corePool size, the object will be added to a LinkedBlockingQueue in the order it was received.

**Parameters:**

command

### getExecutor

```
public java.util.concurrent.Executor getExecutor()
```

Get the underlying Executor pool.

**Returns:**

Executor pool

### getActiveCount

```
public int getActiveCount()
```

Get number of active threads.

**Returns:**

number of active threads

### getQueueSize

```
public int getQueueSize()
```

Get the number of command objects in the LinkedBlockingQueue.

**Returns:**

number of command objects in the LinkedBlockingQueue

## com.wowza.wms.vhost Class VHostItem

java.lang.Object

└─com.wowza.wms.vhost.VHostItem

public class **VHostItem**  
extends Object

VHostItem: data class that hold definition of a virtual host.

### Constructor Summary

public	<a href="#">VHostItem()</a> Create empty vHostItem
--------	---

### Method Summary

String	<a href="#">getConfigDir()</a> Get configuration path for vHost.
int	<a href="#">getConnectionLimit()</a> Get connection limit of this vHost item.
String	<a href="#">getName()</a> Get vHost name
<a href="#">WMSProperties</a>	<a href="#">getProperties()</a> Get properties
boolean	<a href="#">isVisited()</a> Has this vHostItem been visited during load of VHosts.xml file.
void	<a href="#">reset()</a> Reset vHostItem to empty state
void	<a href="#">setConfigDir(String configDir)</a> Set configuration path for vHost.
void	<a href="#">setConnectionLimit(int connectionLimit)</a> Set connection limit of this vHost item.
void	<a href="#">setName(String name)</a> Set vHost name
void	<a href="#">setProperties(WMSProperties properties)</a> Set properties
void	<a href="#">setVisited(boolean visited)</a> Set is visited.
String	<a href="#">toString()</a> Format vHost item

**Methods inherited from class** `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,`  
`wait`

## Constructors

### VHostItem

```
public VHostItem()
```

Create empty vHostItem

## Methods

### reset

```
public void reset()
```

Reset vHostItem to empty state

### getConfigDir

```
public String getConfigDir()
```

Get configuration path for vHost.

**Returns:**

configuration path for vHost

### setConfigDir

```
public void setConfigDir(String configDir)
```

Set configuration path for vHost.

**Parameters:**

`configDir` - configuration path for vHost

### getName

```
public String getName()
```

Get vHost name

**Returns:**

vHost name

### setName

```
public void setName(String name)
```

Set vHost name

**Parameters:**



(continued from last page)

name - vHost name

---

## getProperties

```
public WMSPProperties getProperties()
```

Get properties

**Returns:**

properties

---

## setProperties

```
public void setProperties(WMSPProperties properties)
```

Set properties

**Parameters:**

properties - properties

---

## isVisited

```
public boolean isVisited()
```

Has this vHostItem been visited during load of VHosts.xml file. Internally used to track and delete vHost definitions on reload of VHosts.xml.

**Returns:**

Has this vHostItem been visited during load

---

## setVisited

```
public void setVisited(boolean visited)
```

Set is visited.

**Parameters:**

visited - is visited

---

## getConnectionLimit

```
public int getConnectionLimit()
```

Get connection limit of this vHost item.

**Returns:**

connection limit of this vHost item

---

## setConnectionLimit

```
public void setConnectionLimit(int connectionLimit)
```

Set connection limit of this vHost item.

**Parameters:**

connectionLimit - connection limit of this vHost item

(continued from last page)

**toString**

```
public String toString()
```

Format vHost item

## com.wowza.wms.vhost Class VHostList

java.lang.Object

└─com.wowza.wms.vhost.VHostList

public class **VHostList**  
extends Object

VHostList: list of VHost items. Result of parsing VHosts.xml at server startup or VHosts.xml reload. This interface can keep track of reloads and carefully mark items for deletion.

### Constructor Summary

public	<a href="#"><u>VHostList()</u></a> Create empty vHostList
--------	--

### Method Summary

void	<a href="#"><u>addVHostItemListener()</u></a> ( <a href="#"><u>IVHostItemNotify</u></a> vHostItemListener) Add vHostItem listener.
java.util.List	<a href="#"><u>getVHostItems()</u></a> Get a list of vHostItems.
java.util.Map	<a href="#"><u>getVHostMap()</u></a> Get the Map of vHostItem definitions.
java.util.List	<a href="#"><u>getVHostNames()</u></a> Get a list of vHost names.
void	<a href="#"><u>loadConfig()</u></a>
void	<a href="#"><u>notifyVHostItemCreate()</u></a> ( <a href="#"><u>VHostItem</u></a> vhostItem) Notify vHostItem listener of item create.
void	<a href="#"><u>notifyVHostItemDestroy()</u></a> ( <a href="#"><u>VHostItem</u></a> vhostItem) Notify vHostItem listener of item destroy.
void	<a href="#"><u>notifyVHostItemUpdate()</u></a> ( <a href="#"><u>VHostItem</u></a> vhostItem) Notify vHostItem listener of item update.
void	<a href="#"><u>reloadConfig()</u></a> Reload VHosts.xml file.
void	<a href="#"><u>removeVHostItemListener()</u></a> ( <a href="#"><u>IVHostItemNotify</u></a> vHostItemListener) Remove vHostItem listener.

### Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

---

## Constructors

### VHostList

```
public VHostList()
```

Create empty vHostList

---

## Methods

### loadConfig

```
public void loadConfig()
```

---

### reloadConfig

```
public void reloadConfig()
```

Reload VHosts.xml file.

---

### getVHostMap

```
public java.util.Map getVHostMap()
```

Get the Map of vHostItem defintions.

**Returns:**

Map of vHostItem defintions

---

### addVHostItemListener

```
public void addVHostItemListener(IVHostItemNotify vHostItemListener)
```

Add vHostItem listener. vHostItem listeners will receive the following events: onVHostItemCreate, onVHostItemUpdate, onVHostItemDestroy.

**Parameters:**

vHostItemListener - vHostItem listener

---

### removeVHostItemListener

```
public void removeVHostItemListener(IVHostItemNotify vHostItemListener)
```

Remove vHostItem listener.

**Parameters:**

vHostItemListener - vHostItem listener

---

### notifyVHostItemCreate

```
public void notifyVHostItemCreate(VHostItem vhostItem)
```

Notify vHostItem listener of item create.

(continued from last page)

**Parameters:**

vhostItem - vHostItem

---

**notifyVHostItemUpdate**

```
public void notifyVHostItemUpdate(VHostItem vhostItem)
```

Notify vHostItem listener of item update.

**Parameters:**

vhostItem - vHostItem

---

**notifyVHostItemDestroy**

```
public void notifyVHostItemDestroy(VHostItem vhostItem)
```

Notify vHostItem listener of item destroy.

**Parameters:**

vhostItem - vHostItem

---

**getVHostNames**

```
public java.util.List getVHostNames()
```

Get a list of vHost names. Creates a copy of list.

**Returns:**

list of vHost names

---

**getVHostItems**

```
public java.util.List getVHostItems()
```

Get a list of vHostItems. Create a shallow copy of list.

**Returns:**

list of vHostItems

## com.wowza.wms.vhost Class VHostSingleton

java.lang.Object

└─com.wowza.wms.vhost.VHostSingleton

public class **VHostSingleton**  
extends Object

VHostSingleton: singleton that provide access to running vHosts.

### Constructor Summary

public	<a href="#">VHostSingleton()</a>
--------	----------------------------------

### Method Summary

static void	<a href="#">addVHostListener</a> ( <a href="#">IVHostNotify</a> vhostListener) Add a vHost listener.
static <a href="#">IVHost</a>	<a href="#">getInstance</a> (String vhostName) Get vHost by name.
static <a href="#">IVHost</a>	<a href="#">getInstance</a> (String vhostName, boolean doCreate) Get vHost by name.
static java.util.List	<a href="#">getVHostNames</a> () Get a list of vHost names.
static void	<a href="#">init</a> (String vhostName, String configHome) Initialize vhost by name.
static void	<a href="#">notifyVHostClientConnect</a> ( <a href="#">IVHost</a> vhost, <a href="#">IClient</a> inClient, com.wowza.wms.request.RequestFunction function, <a href="#">AMFDataList</a> params) Notify vhost client connect
static void	<a href="#">notifyVHostCreate</a> ( <a href="#">IVHost</a> vhost) Notify vHost listener of create.
static void	<a href="#">notifyVHostInit</a> ( <a href="#">IVHost</a> vhost) Notify vHost listener of ini.
static void	<a href="#">notifyVHostShutdownComplete</a> ( <a href="#">IVHost</a> vhost) Notify vHost listener of destruction.
static void	<a href="#">notifyVHostShutdownStart</a> ( <a href="#">IVHost</a> vhost) Notify vHost listener of destruction.
static void	<a href="#">remove</a> (String vhostName) Remove a vHost from list of running vHosts.
static void	<a href="#">removeApplicationListener</a> ( <a href="#">IVHostNotify</a> vhostListener) Remove vHost listener

static void	<a href="#">setServer</a> ( <a href="#">IServer</a> server) Set a reference to the current running server.
static void	<a href="#">shutdown</a> (String vhostName) Shutdown a vHost by name.

Methods inherited from class `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

## Constructors

### VHostSingleton

```
public VHostSingleton()
```

## Methods

### getInstance

```
public static IVHost getInstance(String vhostName)
```

Get vHost by name. Do NOT create if does not exist.

**Parameters:**

vhostName - vHost name

**Returns:**

vHost

### getInstance

```
public static IVHost getInstance(String vhostName,  
    boolean doCreate)
```

Get vHost by name. Create if does not exist.

**Parameters:**

vhostName - vhost name

doCreate - if true, create if does not exist

**Returns:**

vHost

### init

```
public static void init(String vhostName,  
    String configHome)
```

Initialize vhost by name.

**Parameters:**

vhostName - vHost name

(continued from last page)

configHome - configuration path, path to VHost.xml

---

## setServer

```
public static void setServer(IServer server)
```

Set a reference to the current running server.

### Parameters:

server - server

---

## shutdown

```
public static void shutdown(String vhostName)
```

Shutdown a vHost by name.

### Parameters:

vhostName - vhost name

---

## getVHostNames

```
public static java.util.List getVHostNames()
```

Get a list of vHost names. Return copy of list.

### Returns:

vHost names

---

## remove

```
public static void remove(String vhostName)
```

Remove a vHost from list of running vHosts.

### Parameters:

vhostName - vhost name

---

## addVHostListener

```
public static void addVHostListener(IVHostNotify vhostListener)
```

Add a vHost listener. A vHost listener receives the following events: onVHostCreate, onVHostInit, onVHostDestroy

### Parameters:

vhostListener - vHost listener

---

## removeApplicationListener

```
public static void removeApplicationListener(IVHostNotify vhostListener)
```

Remove vHost listener

### Parameters:

vhostListener - vHost listener

---



(continued from last page)

---

## notifyVHostClientConnect

```
public static void notifyVHostClientConnect(IVHost vhost,  
      IClient inClient,  
      com.wowza.wms.request.RequestFunction function,  
      AMFDataList params)
```

Notify vhost client connect

### Parameters:

vhost - vHost  
inClient - client  
function - function  
params - parameters

---

## notifyVHostCreate

```
public static void notifyVHostCreate(IVHost vhost)
```

Notify vHost listener of create.

### Parameters:

vhost - vHost

---

## notifyVHostInit

```
public static void notifyVHostInit(IVHost vhost)
```

Notify vHost listener of ini.

### Parameters:

vhost - vHost

---

## notifyVHostShutdownStart

```
public static void notifyVHostShutdownStart(IVHost vhost)
```

Notify vHost listener of destruction.

### Parameters:

vhost - vHost

---

## notifyVHostShutdownComplete

```
public static void notifyVHostShutdownComplete(IVHost vhost)
```

Notify vHost listener of destruction.

### Parameters:

vhost - vHost

---

# Index

## A

ABSOLUTE\_FORMAT 683  
ABSOLUTE\_TIME\_PATTERN 683  
acceptConnection 328, 345  
ACCEPTORS\_ACCEPTOR 1486  
ACCEPTORS\_HANDLERADAPTER 1486  
acceptSession 586, 998  
acquire 833, 840, 841, 842, 1104, 1128  
acquireAndRelease 833, 841  
acquireMediaCaster 847  
acquireSocketAddress 966  
acquireUDPPortPair 966, 967  
actionListeners 996  
activateOptions 693  
add 80, 140, 141, 142, 175, 176, 177, 952, 1461  
addAcceptConnectionAttribute 359  
addAcceptorListener 1492  
addActionListener 1007  
addApplicationInstanceListener 237  
addApplicationListener 1492  
addAudioCodecConfigPacket 1204  
addAudioData 1189, 1324, 1325  
addAudioDataInc 1324  
addBody 949  
addBouncyCastleSecurityProvider 102  
addBytes 949  
addCallbackListener 1212  
addChunk 208  
addClient 1104, 1128  
addClientListener 262, 1195, 1196  
addConnectionListener 327  
addContentDescriptor 786  
addData 219  
addDataData 1189, 1325  
addDataDataInc 1326  
addDataEx 223  
addDifference 80  
addDvrChunkListener 510  
addDvrRecorderListener 300  
addDvrRecordingListener 499  
addDvrStoreListener 498  
addDvrStreamManagerListener 300

addFirstABSTRequest 617  
addHTTPListener 303  
addHttpProvider 1458  
addHTTPStreamerAdapterID 1459  
addHTTPStreamerSession 288  
addIdleWorkerListener 1498  
addIOPerformance 582, 1004  
addIOPerformance2 582, 1004  
addItem 1312  
addLicense 1274  
addListener 643, 658, 1343  
addLiveStreamPacketizerListener 296  
addLiveStreamTranscoderListener 297  
addManifestEntries 498, 509  
addMediaCasterListener 266  
addMediaReaderListener 293  
addMediaStreamListener 264, 1271  
addMediaWriterListener 291  
addMember 202  
addMetaDataListener 855  
addModuleListener 270  
addNameGroup 1273  
addObject 157  
addOverlay 1427  
addOverlayImage 1426  
addPlayReadyDecryptorKey 1255  
addPlayStreamByName 268  
addPublisher 285  
addQueryStrRemoveList 568  
addRange 398  
addRendition 875  
addRepeaterHeartBeatItem 500  
addRTPIncomingDatagramPortAll 288  
addRTPIncomingDatagramPortRange 288  
addRTPLListener 303  
addRTPSession 280  
addRTSPStream 999  
addSegment 861  
addServerListener 1072, 1089  
addSession 1018  
addSessionListener 1018  
addSharedObjectListener 264, 1116  
addSlotListener 1108, 1132  
addSorterPacket 1433  
addStartupStream 1505

addStreamAttribute 1037  
addStreamDomainStr 590  
addStreamDomainStrs 590  
addStreamInfo 1037  
addStreamSrcToMediaCaster 843  
addString 156  
addToCache 411  
addToChunk 476, 603  
addToManifest 463  
addToPlaylist 1340, 1341  
addTrack 1034  
addTrackId 1035  
addTrackInternal 1034  
addTrailingZero 790  
addTrait 157  
addUserHTTPHeaders 594  
addVHostItemListener 1528  
addVHostListener 1532  
addVideoCodecConfigPacket 1204  
addVideoData 1188, 1323, 1324  
addVideoDataInc 1324  
addVideoH264SEILListener 1212  
adjustFirstPacketTCs 66  
alphas 32  
AMF3Utils 117  
AMF\_LEVEL0 128  
AMF\_LEVEL3 128  
AMF\_TEXTTYPE\_ON\_TEXT\_DATA 1398  
AMFData 129  
AMFDataArray 138, 139  
AMFDataByteArray 149, 150  
AMFDataContextDeserialize 155  
AMFDataContextSerialize 160  
AMFDataItem 166, 167, 168  
AMFDataList 174, 175  
AMFDataMixedArray 186, 187  
AMFDataObj 194, 195  
AMFDataTrait 202  
AMFDEBUGHEADERSIZE 207  
AMFObj 207  
AMFObjChunk 214  
AMFPacket 218  
AMFUtils 13  
announce 1041  
append 694  
appendParamsToUrl 107  
appInstance 652, 937, 994, 1265  
appInstanceShutdown 994  
APPLICATION\_KEY 682  
applicationExists 1500  
ARCHIVE\_STRATEGY\_APPEND 429  
ARCHIVE\_STRATEGY\_DELETE 429  
ARCHIVE\_STRATEGY\_VERSION 429  
artifact 379, 401  
assembleQueryStr 73  
attachToWMSSession 1041  
audioCodecId 866  
audioCodecStringToId 58  
audioCodecToMetaDataString 59  
audioCodecToString 59  
audioCodecTypeToString 93  
audioPacketizers 997  
AUDIOSAMPLE\_ACCESS\_ALL 341  
AUDIOSAMPLE\_ACCESS\_NONE 341  
AUDIOSAMPLEACCESS 1172  
authenticateHandler 522  
authenticateHTTPProvider 318  
authenticateHTTPProviderHandler 522  
authenticatePlayHandler 994  
authenticatePublishHandler 994  
authenticateRTSP 319  
authenticateSIP 320  
AuthenticateUsernamePasswordProviderBase 314  
authenticationMethod 522  
AUTHMETHOD\_PLAY 993  
AUTHMETHOD\_PUBLISH 993  
AUTHMETHOD\_UNKNOWN 993  
AVSYNCMETHODS\_RTPTIMECODE 1032  
AVSYNCMETHODS\_SENDERREPORT 1031  
AVSYNCMETHODS\_SYSTEMCLOCK 1031  
AVSYNCMETHODS\_UNKNOWN 1031  
avSyncNameToId 1047  
  
**B**  
  
badStreams 938  
BASE\_NAME\_TAG 677  
baseFilePath 653  
bind 979  
bitrateAudio 866

- bitrateTotal 866
- bitrateVideo 866
- booleanValue 169
- broadcastPlayMessage 1271
- broadcastGetObjectEncoding 1271
- broadcastMsg 267
- buffer 214
- BufferUtils 32
- byteArrayToFile 44
- byteArrayToInt 34, 35
- byteArrayToIntSafeSync 795
- byteArrayToLong 33, 34
- byteArrayToLongSafeSync 795
- byteArrayToShort 35, 36
- byteArrayToString 33
- byteStringLen 764
- byteValue 169
  
- C
  
- cacheRTPStream 967
- calcBitrate 478
- calcParity 1387
- calcTotalPacketSize 222
- calculateChunkGroupTime 410
- call 348
- CALLBACK\_PARAM1 901
- CALLBACK\_PARAM10 902
- CALLBACK\_PARAM2 901
- CALLBACK\_PARAM3 901
- CALLBACK\_PARAM4 901
- CALLBACK\_PARAM5 901
- CALLBACK\_PARAM6 901
- CALLBACK\_PARAM7 901
- CALLBACK\_PARAM8 902
- CALLBACK\_PARAM9 902
- canHandle 523, 530, 561, 1064
- canPlay 506
- canRecord 496, 506
- canRecordAudio 476, 1280
- canRecordData 476, 1281
- canRecordVideo 476, 1281
- CAT\_ALL 736
- CAT\_application 725
- CAT\_cupertino 725
- CAT\_dvrchunk 726
- CAT\_mpegdash 726
- CAT\_rtsp 725
- CAT\_sanjose 725
- CAT\_server 724
- CAT\_session 725
- CAT\_smoothstreaming 725
- CAT\_stream 725
- CAT\_transcoder 726
- CAT\_vhost 725
- CAT\_webm 726
- CEA608\_EXTENDED\_FR\_SP\_MAP 1386
- CEA608\_EXTENDED\_NA\_MAP 1386
- CEA608\_EXTENDED\_PORT\_GERMAN\_DANISH\_MAP 1387
- CEA608\_MUSICAL\_NOTE 1386
- CEA608\_SOLID\_BLOCK 1386
- cea608CharToCharUTF8 1387
- cea608ExtendedCharacterToUTF8 1388
- CHANNEL1 1369
- CHANNEL2 1369
- charUTF8ToCAE608 1387
- checkAndSetPlayLogged 581
- checkParity 1387, 1388
- checkSendMetadata 1042
- cleanUp 693
- clear 80, 741, 953, 1109, 1127, 1202, 1514
- clearByteContainer 211
- clearFastPlaySettings 350, 1192
- clearIntData 156
- clearLoggingValues 545, 584, 609, 616, 622, 1007, 1201
- clearOverlay 1427
- clearProperty 821, 1517
- clearRTSPSessionExtraLines 1059
- clearSegments 861, 875
- clearStreamName 1268
- clearStreamSrcToMediaCaster 843
- clearTracks 1035
- client 314
- clone 80, 202, 218, 458, 1141
- cloneProperties 308
- close 9, 29, 693, 1104, 1133, 1145, 1152, 1191, 1237, 1299, 1307, 1326, 1331, 1334, 1342
- closeAndWait 1342
- ClosedCaptionCEA608Utils 374, 1387

- 
- closeHostPort 1502
  - closeQuietly 51
  - closeStream 921
  - CODEC\_AUDIO\_AAC 1483
  - CODEC\_AUDIO\_AC3 1482
  - CODEC\_AUDIO\_G711\_ALAW 1482
  - CODEC\_AUDIO\_G711\_MULAW 1483
  - CODEC\_AUDIO\_MP3 1482
  - CODEC\_AUDIO\_MP3\_8 1483
  - CODEC\_AUDIO\_NELLYMOSER 1482
  - CODEC\_AUDIO\_NELLYMOSER\_16MONO 1482
  - CODEC\_AUDIO\_NELLYMOSER\_8MONO 1482
  - CODEC\_AUDIO\_PCM\_BE 1482
  - CODEC\_AUDIO\_PCM\_LE 1482
  - CODEC\_AUDIO\_PCM\_SWF 1482
  - CODEC\_AUDIO\_RESERVED 1483
  - CODEC\_AUDIO\_SPEEX 1483
  - CODEC\_AUDIO\_UNKNOWN 1481
  - CODEC\_AUDIO\_VORBIS 1483
  - CODEC\_STREAM\_MP2T 1483
  - CODEC\_STREAM\_UNKNOWN 1483
  - CODEC\_TYPE 462
  - CODEC\_VIDEO\_H263 1481
  - CODEC\_VIDEO\_H264 1481
  - CODEC\_VIDEO\_MPEG2 1481
  - CODEC\_VIDEO\_MPEG4 1481
  - CODEC\_VIDEO\_SCREEN 1480
  - CODEC\_VIDEO\_SCREEN2 1481
  - CODEC\_VIDEO\_SPARK 1480
  - CODEC\_VIDEO\_UNKNOWN 1480
  - CODEC\_VIDEO\_VP6 1480
  - CODEC\_VIDEO\_VP6A 1481
  - CODEC\_VIDEO\_VP8 1481
  - CODECSTR\_FORMAT\_VIDEO\_POSTIOS4 93
  - CODECSTR\_FORMAT\_VIDEO\_PREIOS4 93
  - CODECSTR\_FORMAT\_VIDEO\_UNKNOWN 92
  - CODES\_HREF 683
  - COL0\_BLUE 1368
  - COL0\_CYAN 1369
  - COL0\_GREEN 1368
  - COL0\_HIBYTE 1374
  - COL0\_LOWBYTE 1375
  - COL0\_MAGENTA 1369
  - COL0\_RED 1369
  - COL0\_WHITE 1368
  - COL0\_YELLOW 1369
  - COL\_0 1375
  - COL\_12 1375
  - COL\_16 1375
  - COL\_20 1375
  - COL\_24 1375
  - COL\_28 1376
  - COL\_4 1375
  - COL\_5 1375
  - COLN\_LOWBYTE 1376
  - compareTo 1451
  - compress 152
  - CONFIGURATOR\_CLASS\_KEY 682
  - configureSocketAcceptor 1458
  - ConnectionCounter 327
  - connectionHolder 995
  - containsDvrRecorder 284
  - containsHeader 539
  - containsHTTPStreamer 283
  - containsIndex 544, 608, 615, 622
  - containsKey 195, 225
  - containsLiveStreamPacketizer 284
  - containsLiveStreamTranscoder 298
  - containsProperty 1109, 1129
  - containsSlot 1110, 1129
  - containsStreamDomainStr 590
  - containsStreamNameParts 588
  - containsTime 518
  - CONTENTTYPE\_ACKBANDWIDTH 1484
  - CONTENTTYPE\_AUDIO 1485
  - CONTENTTYPE\_BUFFERSIZE 1484
  - CONTENTTYPE\_CHORD 783
  - CONTENTTYPE\_DATA 1485
  - CONTENTTYPE\_DATA0 1485
  - CONTENTTYPE\_DATA3 1485
  - CONTENTTYPE\_EVENTS 783
  - CONTENTTYPE\_FUNCTION 1486
  - CONTENTTYPE\_FUNCTION0 1486
  - CONTENTTYPE\_FUNCTION3 1486
  - CONTENTTYPE\_LYRICS 783
  - CONTENTTYPE\_MEDIA 1149
  - CONTENTTYPE\_MEDIACHUNK 1486
  - CONTENTTYPE\_MEDIALIST 1149
  - CONTENTTYPE\_MOVEMENT 783
  - CONTENTTYPE\_OTHER 783
-

CONTENTTYPE\_PLAYCALLBACK 1486  
CONTENTTYPE\_SETBANDWIDTH 1485  
CONTENTTYPE\_SETCHUNKSIZE 1484  
CONTENTTYPE\_SHAREDOBJECTS 1485  
CONTENTTYPE\_SHAREDOBJECTS0 1485  
CONTENTTYPE\_SHAREDOBJECTS3 1485  
CONTENTTYPE\_TRANSCRIPTION 783  
CONTENTTYPE\_TRIVIA 784  
CONTENTTYPE\_UNKNOWN 1484  
CONTENTTYPE\_URLIMAGES 784  
CONTENTTYPE\_URLWEBPAGES 784  
CONTENTTYPE\_VIDEO 1485  
CONTENTTYPE\_WATCHDOG 1484  
contextStr 654  
CONTROLCODES\_AOF 1370  
CONTROLCODES\_AON 1370  
CONTROLCODES\_BAO 1373  
CONTROLCODES\_BAS 1373  
CONTROLCODES\_BBO 1372  
CONTROLCODES\_BBS 1372  
CONTROLCODES\_BCO 1372  
CONTROLCODES\_BCS 1372  
CONTROLCODES\_BGO 1372  
CONTROLCODES\_BGS 1372  
CONTROLCODES\_BMO 1373  
CONTROLCODES\_BMS 1373  
CONTROLCODES\_BRO 1372  
CONTROLCODES\_BRS 1372  
CONTROLCODES\_BS 1370  
CONTROLCODES\_BT 1373  
CONTROLCODES\_BWO 1371  
CONTROLCODES\_BWS 1372  
CONTROLCODES\_BYO 1373  
CONTROLCODES\_BYS 1373  
CONTROLCODES\_CR 1371  
CONTROLCODES\_DER 1370  
CONTROLCODES\_EDM 1371  
CONTROLCODES\_ENM 1371  
CONTROLCODES\_EOC 1371  
CONTROLCODES\_FA 1373  
CONTROLCODES\_FAU 1373  
CONTROLCODES\_FON 1370  
CONTROLCODES\_RCL 1369  
CONTROLCODES\_RDC 1370  
CONTROLCODES\_RTD 1371  
CONTROLCODES\_RU2 1370  
CONTROLCODES\_RU3 1370  
CONTROLCODES\_RU4 1370  
CONTROLCODES\_TO1 1371  
CONTROLCODES\_TO2 1371  
CONTROLCODES\_TO3 1371  
CONTROLCODES\_TR 1371  
convertParams 13  
COOKIEDATEFORMAT 72  
cookieStr 994  
copyFile 50  
copyFile2 50  
COUNT\_COLS 1374  
COUNT\_ROWS 1374  
COUNTER\_HTTPCUPERTINO 1479  
COUNTER\_HTTPDVRCHUNKS 1480  
COUNTER\_HTTPMPEGDASH 1480  
COUNTER\_HTTPSANJOSE 1479  
COUNTER\_HTTPSMOOTH 1479  
COUNTER\_HTTPWEBM 1480  
COUNTER\_RTMP 1479  
COUNTER\_RTP 1479  
COUNTER\_TOTAL 1480  
createApplication 1506  
createBroadcastMessage 948  
createConnectMessage 948  
createContextDeserialize 132  
createContextSerialize 132  
createDefaultMessage 948  
createDvrAudioChunk 473  
createDvrDataChunk 474  
createDvrOnMetadataChunk 474  
createDvrVideoChunk 473  
createEnhancedSeekMessage 949  
createHTTPSessionInstance 558  
createIndexLive 608, 616  
createInstance 1321, 1322, 1339  
createPlayStatusMessage 948  
createSeekMessage 948  
createSegmentSchedule 655  
createSOMessage 949  
createStream 919, 1039, 1323  
cronEventWorker 653  
CrontabEvent 1448  
CTRL\_playlist\_node 730

currentDuration 653  
currentOutputFile 654  
currentSize 653

## D

data 401  
DATA\_TYPE\_AMF3 126  
DATA\_TYPE\_AMF3\_ARRAY 128  
DATA\_TYPE\_AMF3\_BOOLEAN\_FALSE 127  
DATA\_TYPE\_AMF3\_BOOLEAN\_TRUE 127  
DATA\_TYPE\_AMF3\_BYTEARRAY 128  
DATA\_TYPE\_AMF3\_DATE 128  
DATA\_TYPE\_AMF3\_INTEGER 127  
DATA\_TYPE\_AMF3\_NULL 127  
DATA\_TYPE\_AMF3\_NUMBER 127  
DATA\_TYPE\_AMF3\_OBJECT 128  
DATA\_TYPE\_AMF3\_STRING 127  
DATA\_TYPE\_AMF3\_UNDEFINED 127  
DATA\_TYPE\_AMF3\_XML\_LEGACY 128  
DATA\_TYPE\_AMF3\_XML\_TOP 128  
DATA\_TYPE\_ARRAY 125  
DATA\_TYPE\_AS\_OBJECT 126  
DATA\_TYPE\_BOOLEAN 124  
DATA\_TYPE\_BYTEARRAY 126  
DATA\_TYPE\_CUSTOM\_CLASS 126  
DATA\_TYPE\_DATE 125  
DATA\_TYPE\_INTEGER 126  
DATA\_TYPE\_LONG\_STRING 126  
DATA\_TYPE\_MIXED\_ARRAY 125  
DATA\_TYPE\_MOVIE\_CLIP 125  
DATA\_TYPE\_NULL 125  
DATA\_TYPE\_NUMBER 124  
DATA\_TYPE\_OBJECT 125  
DATA\_TYPE\_OBJECT\_END 125  
DATA\_TYPE\_RECORDSET 126  
DATA\_TYPE\_REFERENCE\_OBJECT 125  
DATA\_TYPE\_STRING 124  
DATA\_TYPE\_UNDEFINED 125  
DATA\_TYPE\_UNKNOWN 124  
DATA\_TYPE\_XML 126  
DATA\_TYPE\_XML\_TOP 127  
DATE\_AND\_TIME\_FORMAT 683  
DATE\_AND\_TIME\_PATTERN 683  
DATEFORMAT 166  
DATETIME\_FORMAT 677  
dateValue 169  
DAY 1448  
debug 659, 704, 705  
debugLog 654  
debugRTSPSession 997  
DebugUtils 41  
debugWOWZProtocol 1085  
DECODE 18  
decode 21  
DECODE\_OBJ\_REF 193  
DECODE\_TRAITS 193  
DECODE\_TRAITS\_EXT 193  
DECODE\_TRAITS\_REF 193  
DECODE\_UNDEFINED 193  
decodeFileToFile 23  
decodeFromFile 22  
decodeHexString 33  
decodeRangeHeader 1436  
decodeS 1094  
decodeSS 1094  
decodeStorageDir 283, 1087  
decodeStreamInfo 1439, 1440  
decodeString 23  
decodeToFile 22  
decodeToObject 21  
decodeValue 107  
decompress 153  
decrement 329  
DEFAULT\_AMF\_CONVERTER\_TEXT\_TYPE 1408  
DEFAULT\_AMF\_CONVERTER\_TRACK\_INDEX 1408  
DEFAULT\_APPINSTANCE\_NAME 258  
DEFAULT\_APPLICATION\_NAME 235  
DEFAULT\_CAPTION\_CHARACTER\_SET 1406  
DEFAULT\_CHUNK\_MEMORY\_CACHESIZE 437  
DEFAULT\_CONFIGURATION\_FILE 682  
DEFAULT\_CONFIGURATION\_KEY 682  
DEFAULT\_CUPERTINO\_PLAYLIST\_GZIP\_THRESHOLD 450  
DEFAULT\_MAXIMUM\_CAPTION\_DURATION 1405  
DEFAULT\_PORT 693  
DEFAULT\_PROPERTY\_ALLOWABLE\_AV\_PACKET\_DELTA 433  
DEFAULT\_PROPERTY\_APPEND\_DISCONTINUITY\_DELTA 427

- DEFAULT\_PROPERTY\_AUDIO\_ONLY\_CHUNK\_TARGET\_DURATION 435
- DEFAULT\_PROPERTY\_BREAK\_ONPTS 435
- DEFAULT\_PROPERTY\_CAPTION\_LANGUAGES 1400
- DEFAULT\_PROPERTY\_CAPTION\_FILE\_NAMING\_RULE 1404
- DEFAULT\_PROPERTY\_CAPTION\_PATH\_NAMING\_RULE 1405
- DEFAULT\_PROPERTY\_CHUNK\_CACHE\_CLASS 431
- DEFAULT\_PROPERTY\_CHUNK\_DURATION\_MINIMUM 436
- DEFAULT\_PROPERTY\_CHUNK\_GROUPING\_SECONDS 427
- DEFAULT\_PROPERTY\_CHUNK\_READER\_CLASS 429
- DEFAULT\_PROPERTY\_CHUNK\_WRITER\_CLASS 430
- DEFAULT\_PROPERTY\_DEBUG\_MAX\_INVALID\_CHUNKS\_LOGGED 440
- DEFAULT\_PROPERTY\_DEBUG\_MAX\_RAW\_PACKETS 442
- DEFAULT\_PROPERTY\_DEBUG\_MAX\_VALID\_CHUNKS\_LOGGED 441
- DEFAULT\_PROPERTY\_DEBUG\_RAW\_PACKETS 442
- DEFAULT\_PROPERTY\_DVR\_MAX\_CHUNK\_LOG 443
- DEFAULT\_PROPERTY\_FILE\_SYSTEM\_CLASS 430
- DEFAULT\_PROPERTY\_MANIFEST\_PERSISTER\_CLASS 430
- DEFAULT\_PROPERTY\_MAX\_RECALC\_DURATION\_LOG 443
- DEFAULT\_PROPERTY\_MAX\_RECORDING\_LENGTH 439
- DEFAULT\_PROPERTY\_MBR\_ALTERNATIVE\_MATCH\_DELTA 437
- DEFAULT\_PROPERTY\_MBR\_MINIMUM\_PACKET\_TIME\_GAP\_SIZE 438
- DEFAULT\_PROPERTY\_MBR\_MINIMUM\_UTCTIME\_GAP\_SIZE 438
- DEFAULT\_PROPERTY\_MEDIACACHE\_READER\_CLASS 439
- DEFAULT\_PROPERTY\_PACKET\_DELTA\_TO\_NOTIFY 434
- DEFAULT\_PROPERTY\_PACKET\_DELTA\_TO\_RESET\_TIME 433
- DEFAULT\_PROPERTY\_PACKET\_DURATION\_MAXIMUM 438
- DEFAULT\_PROPERTY\_PACKET\_SORT\_TIME 435
- DEFAULT\_PROPERTY\_RECORDINGS\_LOADER\_CLASS 431
- DEFAULT\_PROPERTY\_REPEATER\_HEARTBEAT\_DURATION 436
- DEFAULT\_PROPERTY\_SANJOSE\_ABST\_DURATION\_TOLERANCE 449
- DEFAULT\_PROPERTY\_SANJOSE\_ABST\_TIMESCALE 449
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_PAUSE 451
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_SEEK 450
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_MAJOR\_VERSION 452
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_MINOR\_VERSION 452
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_PAUSE 451
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_SEEK 451
- DEFAULT\_PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_SPECIFY\_DURATION 452
- DEFAULT\_PROPERTY\_STORAGE\_DIRECTORY 428
- DEFAULT\_PROPERTY\_TEXT\_READER\_CLASS 432
- DEFAULT\_PROPERTY\_TEXT\_WRITER\_CLASS 432
- DEFAULT\_RANDOMACCESSREADER 1149
- DEFAULT\_RANDOMACCESSREADEROPTIMIZER 1149
- DEFAULT\_REPOSITORY\_NAME 681
- DEFAULT\_XML\_CONFIGURATION\_FILE 682
- DefaultDvrStreamVersionHandler 376
- defaultLocale 101
- defaultTimeZone 101
- deleteArchivedStore 497
- deleteDirectory 51
- deleteSlot 1105, 1129
- deleteStream 920
- describe 1051
- deserialize 134, 146, 152, 169, 181, 187, 198, 199, 393, 396, 398, 472
- deserializeBody 748, 768, 771, 774, 777, 779, 785, 790, 793, 798
- deserializeDate 117
- deserializeFrame 765
- deserializeInnerObject 132
- deserializeInt 117
- deserializeString 118, 765



- detachFromWMSSession 1041
- determineChunkGroupIdentifier 410
- determineExistingStoreForPlaying 377, 513
- determineExistingStoreForRecording 377, 512
- determineStreamVersion 478
- determineUtcTime 413
- directOutput 1442
- disconnect 329, 1107, 1116, 1132
- doBreak 946
- doCRC32 38
- doesStackContainMethod 45
- doHTTPAuthentication 524
- doIdle 850, 1015
- DONOTHING\_BYTE 1369
- DONOTHING\_SHORT 1369
- DONT\_BREAK\_LINES 18
- doSessionRedirect 594
- doSet 81
- doubleValue 168
- doWatchdog 807, 832, 839, 964, 1087
- DT\_FORMAT 1447
- dummy 86
- dump 1451
- DVR\_DEFAULT\_FILESTORE 426
- DVR\_DEFAULT\_RECORDER\_ID 426
- DVR\_REPEATER\_PACKETIZER\_ID 426
- DVR\_STREAMING\_PACKETIZER\_ID 426
- DVR\_TIME 454
- DVR\_WINDOW\_DURATION\_UNLIMITED 428
- DvrManifestChunkEntry 379
- DvrManifestCodecEntry 383
- DvrManifestEntry 390
- DvrManifestEntryFactory 393
- DvrManifestEntryRange 394
- DvrManifestEntryRangeGroup 397
- DvrManifestOnMetadataEntry 401
- DvrManifestTimeMapEntry 404
- dvrRecorders 1265
- dvrStart 389
- dvrStop 389
- dvrStreamStorageDeleted 489
- dvrStreamStorageLoaded 489
- dvrStreamStoreCreate 488
- dvrStreamStoreDestroy 488
- dvrStreamStoreInit 488
- dvrToPt 518
- dvrToUtc 518
- E
- elapsedTime 996
- ElapsedTimer 47
- ENCODE 17
- encodeBytes 19, 20, 392
- encodeFileToFile 23
- encodeFromFile 22
- encodeHexString 32
- encodeObject 18, 19
- encodeString 23
- encodeToFile 22
- encodeValue 107
- ENCRYPTION\_TYPE\_CUPERTINO 456
- ENCRYPTION\_TYPE\_MPEGDASH 457
- ENCRYPTION\_TYPE\_PLAYREADY 456
- encryptions 379
- end 104
- endChunk 476, 602
- equals 99
- error 702, 703
- EVT\_ALL 737
- EVT\_announce 729
- EVT\_app\_start 729
- EVT\_app\_stop 729
- EVT\_comment 729
- EVT\_connect 726
- EVT\_connect\_burst 726
- EVT\_connect\_pending 726
- EVT\_create 727
- EVT\_decoderaudiostart 729
- EVT\_decoderaudiostop 729
- EVT\_decodervideostart 729
- EVT\_decodervideostop 730
- EVT\_describe 729
- EVT\_destroy 727
- EVT\_disconnect 726
- EVT\_encoderaudiostart 730
- EVT\_encoderaudiostop 730
- EVT\_encodervideostart 730
- EVT\_encodervideostop 730
- EVT\_pause 727

EVT\_play 727  
EVT\_publish 727  
EVT\_record 728  
EVT\_recordstop 728  
EVT\_seek 728  
EVT\_server\_start 728  
EVT\_server\_stop 728  
EVT\_setbuffertime 727  
EVT\_setstreamtype 727  
EVT\_stop 728  
EVT\_unpause 727  
EVT\_unpublish 727  
EVT\_vhost\_start 728  
EVT\_vhost\_stop 728  
execute 1522  
exists 10, 1115  
existsRTSPtunnelingSession 968  
expandEndTime 409, 471  
expandEnvironmentVariables 101, 102  
expandStartTime 409, 471  
expandToPortPair 967  
extractCodecConfigFromTrackInfo 1042  
extractHTTPRequestInfo 592

F

fastDateFormat 166  
FastPlaySettings 1137  
fatal 703, 704  
FCPublish 925  
FCSubscribe 926  
fcSubscribe 365  
FCUnPublish 925  
FCUnpublish 926  
FCUnSubscribe 927  
FCUnsubscribe 927  
fcUnSubscribe 365  
fcUnSubscribeAll 365  
FD\_ALL 736  
FD\_c\_client\_id 722  
FD\_c\_ip 721  
FD\_c\_proto 721  
FD\_c\_referrer 721  
FD\_c\_user\_agent 721  
FD\_cs\_bytes 722  
FD\_cs\_bytes\_inc 689  
FD\_cs\_stream\_bytes 722  
FD\_cs\_stream\_bytes\_inc 689  
FD\_cs\_uri\_query 723  
FD\_cs\_uri\_stem 723  
FD\_date 720  
FD\_s\_ip 723  
FD\_s\_port 724  
FD\_s\_uri 721  
FD\_sc\_bytes 722  
FD\_sc\_bytes\_inc 689  
FD\_sc\_stream\_bytes 723  
FD\_sc\_stream\_bytes\_inc 689  
FD\_time 720  
FD\_tz 720  
FD\_x\_app 721  
FD\_x\_appinst 721  
FD\_x\_category 720  
FD\_x\_comment 724  
FD\_x\_ctx 720  
FD\_x\_ctx\_override 721  
FD\_x\_duration 723  
FD\_x\_duration\_inc 689  
FD\_x\_event 720  
FD\_x\_file\_ext 724  
FD\_x\_file\_length 722  
FD\_x\_file\_name 723  
FD\_x\_file\_size 722  
FD\_x\_severity 724  
FD\_x\_sname 722  
FD\_x\_sname\_query 723  
FD\_x\_spos 722  
FD\_x\_status 723  
FD\_x\_stream\_id 724  
FD\_x\_suri 724  
FD\_x\_suri\_query 724  
FD\_x\_suri\_stem 724  
FD\_x\_vhost 721  
file 653  
FILEEXTENSION 1101  
FILEFORMAT\_FLV 1484  
FILEFORMAT\_MP4 1484  
FILEFORMAT\_UNKNOWN 1484  
fileToByteArray 50  
FileUtils 49

- fileVersionDelegate 652
- filterQueryStr 568
- filters 522
- FLAGS\_DEFAULT 764
- floatValue 168
- flush 1105, 1116, 1133, 1205, 1326
- flushBase64 29
- FLV\_CHUNKHEADER\_BUFFER\_SIZE 57
- FLV\_CHUNKHEADER\_FIRSTBYTE 56
- FLV\_CHUNKHEADER\_HEADERSIZE 57
- FLV\_CHUNKHEADER\_ISIZE 56
- FLV\_CHUNKHEADER\_ITIMECODE 56
- FLV\_CHUNKHEADER\_ITYPE 56
- FLV\_CHUNKHEADER\_SECONDBYTE 56
- FLV\_CHUNKHEADER\_VALUESIZE 57
- FLV\_DFRAME 57
- FLV\_KFRAME 57
- FLV\_PFRAME 57
- FLV\_TCINDEXAUDIO 57
- FLV\_TCINDEXDATA 58
- FLV\_TCINDEXVIDEO 58
- FLV\_UFRAME 57
- FLVUtils 58
- forceNewLoggerInstance 708
- forceReset 807
- FORMAT\_COLOR 1376
- FORMAT\_FLASH 1376
- FORMAT\_FLV 631
- FORMAT\_ITALICS 1376
- FORMAT\_ITALICS\_UNDERLINE 1376
- FORMAT\_MP4 631
- FORMAT\_UNKNOWN 631
- formatBytes 42
- formatBytesInSingleRow 43
- formatBytesShort 41
- formatBytesStruct 43
- formatDeleteCookie 74
- formatH264CodecConfig 1440
- formatH264CodecConfigPacket 1440
- formatMilliseconds 44
- formatRTPIInfo 1053
- formatSeconds 44
- formatSetCookie 75
- formatUtcTime 45
- FORWARD 8
- frameTypeToString 59
- fS 1094
- G**
  - generateAuth 88, 89, 90
  - generateAuthHTTP 89
  - generateHash 91
  - generateHashBytes 90, 91
  - get 143, 179, 196, 227, 228, 1114, 1462
  - getAbsTimecode 210, 221
  - getAccess 1134, 1203
  - getActiveCount 1522
  - getAdapterName 562
  - getAddress 1456
  - getAddressCount 982
  - getAddressRawStr 1456
  - getAddressStr 1456
  - getAdminAgent 1085
  - getAdminGUID 1091
  - getAdminInterfaceObjectList 1073, 1090
  - getAllAsStrings 310
  - getAllowDomains 273
  - getAndClearNotifyCreate 596
  - getAndClearPendingFrameGrabs 1424
  - getAndClearPendingOverlays 1428
  - getAndSetStartStream 1292
  - getAppInstance 236, 342, 505, 566, 582, 805, 908, 1002, 1039, 1270, 1279, 1300, 1323
  - getAppInstanceName 1043, 1270
  - getAppInstanceNames 238
  - getAppInstanceProperty 942
  - getApplication 259, 342, 694, 908, 1488
  - getApplicationFolderNames 1499
  - getApplicationInstance 839, 1292
  - getApplicationInstanceTouchTimeout 292
  - getApplicationLock 1496
  - getApplicationNames 1499
  - getApplicationPath 236
  - getApplicationProperty 941
  - getApplicationTimeout 270, 1494
  - getAppName 1043, 1270
  - getArchiveStrategy 377, 495, 513
  - getArtifactsTextRepresentation 381, 402
  - getAudioCodec 60, 68, 383

getAudioCodecConfigPacket 1204  
getAudioCodecId 869  
getAudioHost 973  
getAudioMissing 1188  
getAudioMP3Layer 67  
getAudioPacketizerItem 964, 1012  
getAudioPort 972  
getAudioSize 1173  
getAudioTC 1176  
getAudioTrack 1036  
getAuthenticatePlayHandler 1001  
getAuthenticatePublishHandler 1001  
getAuthenticationList 1500  
getAuthenticationMethod 524, 530  
getAutoAllocateInterleavePorts 1054  
getAVSyncMethod 1046  
getBaseClass 822, 1516  
getBaseFilePath 642, 656  
getBasePath 10  
getBitrate 600  
getBitrateAudio 868  
getBitrateTotal 868  
getBitrateVideo 869  
getBodySize 748, 769, 772, 774, 777, 779, 785, 791, 793, 798  
getBoolean 145, 181, 197, 198, 230, 232  
getBuffer 556  
getBufferSize 780  
getBufferTime 352, 1173  
getBurstStartStop 1200  
getByte 144, 181, 197, 198, 230, 231  
getByteAllocation 76  
getByteContainerLevel 211  
getCacheName 1198  
getCallbackParamCount 904  
getCEACaptionConversionContext 1494  
getChecksum 1141  
getChunkCounter 213  
getChunker 506  
getChunkGroupDuration 410  
getChunkIndex 404  
getChunks 208  
getClassName 200, 203  
getClient 261, 315, 322, 1179, 1487, 1488  
getClientById 261  
getClientCount 261, 1491  
getClientCountTotal 260  
getClientID 922  
getClientId 341, 1179  
getClientIdGenerator 1074, 1091  
getClientIdGeneratorRecycleDelaySize 1093  
getClientIdGeneratorRecycleSize 1093  
getClientIdGeneratorTimeout 1093  
getClientIdleFrequency 273, 1497  
getClientProperty 942  
getClients 261, 1103, 1128  
getClientsLockObj 281  
getClientTimeout 1487  
getClientUpdates 1131  
getClosestStartTime 408, 470, 511  
getCodecEntryForTime 465  
getCodecId 869  
getCommandInterface 1089  
getCommandInterfaceCommandHandler 1076, 1093  
getCommandInterfaceHostPort 1072, 1089  
getCommittedVirtualMemory 1092  
getCommonInitialTextRepString 392  
getConfigDir 1524  
getConfigPath 236  
getConfiguration 1458  
getConnectionCounter 237, 266, 1071, 1088, 1493  
getConnectionHolder 582, 1004  
getConnectionLimit 1494, 1525  
getConnectionTimeout 822  
getConnectionValidator 1088  
getConnectLastAttempt 809  
getConnectLastForceReset 809  
getConnectLastSuccess 809  
getConnectTime 350  
getContentDescriptors 786  
getContentLength 533  
getContentType 534, 785  
getContextStr 290, 492, 505, 1209, 1302  
getCookieStr 587, 1011  
getCoreHandlerPoolSize 1073, 1090, 1489  
getCoreTransportPoolSize 1073, 1090, 1489  
getCount 1269  
getCpuTime 102  
getCryptoPoolActiveCount 1092  
getCryptoPoolMaxSize 1092  
getCurrent 329

getCurrentDuration 642, 655  
getCurrentFile 642, 656  
getCurrentHeapSize 1092  
getCurrentItem 1340  
getCurrentSize 641, 655  
currentTime 480  
getData 222, 401, 772, 775, 1119  
getDataBuffer 222  
getDataMissing 1188  
getDataSize 1174  
getDataTC 1177  
getDataType 1178  
getDate 47, 145, 181, 197, 198, 230, 232  
getDateStarted 238, 266, 351, 1071, 1088, 1493  
getDateString 48  
getDefaultStreamingStore 494  
getDePacketizerList 967  
getDePacketizerName 968  
getDescription 749, 769, 772, 822, 1518  
getDirection 1138  
getDirecton 9  
getDouble 145, 180, 197, 198, 229, 231  
getDuration 391, 1039, 1154, 1252, 1332, 1334  
getDvrApplicationContext 299  
getDvrArtifact 380, 401  
getDvrChunkAtTime 510  
getDvrChunkByIndex 510  
getDvrChunkNearTime 511  
getDvrFileSystemClass 495  
getDvrManager 505, 1280  
getDvrPlaylistRequest 478  
getDvrProperties 299  
getDvrRecorder 1206, 1210, 1273  
getDvrRecorderId 1280  
getDvrRecorderList 299, 1206, 1506  
getDvrRecorders 1274  
getDvrRepeater 1210  
getDvrSessionInfo 592  
getDvrStorageDir 494  
getDvrStorageWindowSeconds 494, 504  
getDvrStoreList 1506  
getDvrTime 469  
getDynamicLogProperties 1074, 1091, 1501  
getElapsedTime 364, 590, 1013, 1207  
getEmbeddedFlag 780  
getEncInfo 1158  
getEncMethod 1255  
getEncoding 694  
getEncryptionDelegate 495  
getEncryptionRepeaterSharedSecret 495  
getEncryptions 380  
getEncryptionsTextRepresentation 381  
getEncryptionType 457  
getEndIndex 395  
getEntriesToPurge 465  
getEventHandler 1450  
getEventStr 1450  
getExecutor 1522  
getExt 1201  
getExtent 1140  
getFastPlaySettings 349, 1192  
getField 1449  
getFileExtension 1322  
getFileInBytes 84  
getFileInBytesRate 86  
getFileInfo 589  
getFileIOPoolSize 1490  
getFilename 644, 678  
getFileOutBytes 85  
getFileOutBytesRate 86  
getFilePath 638, 656  
getFilePointer 9  
getFileSystem 506  
getFileTemplate 678  
getFileVersionDelegate 641, 656  
getFirstByte 222  
getFirstEntry 409, 467  
getFirstIndex 409  
getFirstRendition 875  
getFirstSegment 861  
getFlags 766, 798  
getFlashVer 342  
getFloat 145, 180, 197, 198, 229, 232  
getFps 1137  
getFrameCount 1432  
getFrameIdentifier 772  
getFrameMapIds 742  
getFrames 742  
getFrameType 60  
getGlobalLogValue 710

getGUID 1091  
getHandler 979  
getHandlerThreadPool 1074, 1090, 1491  
getHeader 532, 539  
getHeaderBytes 536  
getHeaderMap 532  
getHeaderNames 533  
getHeaders 539  
getHeaderSize 540, 1203  
getHeight 870  
getHighestVersionedStore 493  
getHomePath 1489  
getHost 972, 1038  
getHostPortsList 1490  
getHostType 974  
getHTTPHeader 592  
getHTTPHeaderMap 592  
getHTTPHeaderNames 592  
getHTTPIdent2Response 1459  
getHTTPIdentResponse 1459  
getHTTPIntHeader 592  
getHTTPOriginMode 567  
getHttpProviders 1458  
getHTTPStreamerAdapter 582, 1504  
getHTTPStreamerAdapterIDs 1459, 1504  
getHTTPStreamerApplicationContext 288  
getHTTPStreamerContext 1500  
getHTTPStreamerItem 561  
getHTTPStreamerList 283, 1504  
getHTTPStreamerMaxPathLen 1507  
getHTTPStreamerProperties 282  
getHTTPStreamerRequestValidator 1507  
getHTTPStreamerSession 1146, 1207  
getHTTPStreamerSessionCount 286, 287  
getHTTPStreamerSessionCountsByName 286  
getHTTPStreamerSessions 286, 287  
getID 563  
getId 208  
getIdleCheckFrequency 1497  
getIdleFrequency 355, 562, 1009  
getIdleHandler 1005  
getIdleMinimumWaitTime 1501  
getIdleTimeout 806  
getIdleWorkerCount 1498  
getIdleWorkers 1501  
getIdStr 765, 797  
getIdString 823  
getIndex 391, 545, 609, 616, 622, 1315  
getIndexLive 609, 616  
getIndexMap 407  
getInIpAddress 978  
getInitialRepeaterItems 500  
getInnerObj 203  
getInPort 979  
getInputStream 535  
getInstance 709, 1085, 1531  
getInt 144, 180, 197, 198, 228, 231  
getIntData 155  
getIntHeader 533, 540  
getIOPerformanceCounter 268, 589, 1011  
getIoPerformanceCounter 238, 1070, 1071, 1087, 1088, 1492, 1493  
getIOScheduler 1492  
getIoSession 1014  
getIp 349, 1002  
getIpAddress 583  
getItems 1311  
getJmxRemoteConfig 1090  
getKeepAliveTime 823  
getKeepAliveTimeout 1498  
getKey 196, 227  
getKeys 196, 227  
getLanguage 785, 871  
getLastAccessed 1141  
getLastAudioTimecode 1326  
getLastAuthenticateMethod 1001  
getLastClientId 1121  
getLastConnectAcceptedStamp 330  
getLastConnectAcceptedStampString 330  
getLastConnectAcceptedTime 330  
getLastConnectAcceptedTimeString 330  
getLastConnectRejectedByReasonStamp 331  
getLastConnectRejectedByReasonStampString 331  
getLastConnectRejectedByReasonTime 331  
getLastConnectRejectedByReasonTimeString 331  
getLastConnectRejectedStamp 330  
getLastConnectRejectedStampString 330  
getLastConnectRejectedTime 330  
getLastConnectRejectedTimeString 331  
getLastDataTimecode 1327

getLastDisconnectStamp 332  
getLastDisconnectStampString 332  
getLastDisconnectTime 332  
getLastDisconnectTimeString 332  
getLastKeyFrame 1189  
getLastLiveEntry 409, 467  
getLastOperation 1121  
getLastPacket 1190  
getLastPacketsByType 1050  
getLastPurgeTime 480  
getLastRecordedEntry 409, 464  
getLastRecordedIndex 406, 469  
getLastRequest 596  
getLastRun 1450  
getLastStreamId 920  
getLastTC 67  
getLastTouchTime 292  
getLastValidateTime 360  
getLastVideoTimecode 1326  
getLength 1155, 1315  
getLicenseCounter 1093  
getLicenseHolder 1283, 1301  
getLicenseTracker 1094  
getLicenseValidator 1088  
getLiveDuration 408, 469  
getLiveEntries 408, 467  
getLiveEntriesWithLimit 408, 468  
getLivePlaylist 622  
getLiveRangeEndingBeforeTime 409  
getLiveRepeaterCapabilities 364  
getLiveStreamDvrRecorderControl 299  
getLiveStreamingPacketizer 583  
getLiveStreamPacketizer 833, 923, 1206, 1207, 1272  
getLiveStreamPacketizerControl 289  
getLiveStreamPacketizerId 1290  
getLiveStreamPacketizerList 283, 363, 1205, 1504  
getLiveStreamPacketizerLock 1272  
getLiveStreamPacketizerProperties 281  
getLiveStreamRepeater 834, 1208  
getLiveStreamTranscoder 1211  
getLiveStreamTranscoderControl 298  
getLiveStreamTranscoderItem 1300  
getLiveStreamTranscoderList 298, 364, 1206, 1504  
getLiveStreamTranscoders 1211  
getLiveTailEntries 408  
getLiveThreads 1092  
getLocale 536  
getLocalListeners 658  
getLock 580, 741, 810, 830, 839, 862, 868, 876, 966, 1339  
getLockCount 832, 846  
getLogger 699, 710, 910  
getLoggerObj 708, 710  
getLong 144, 180, 197, 198, 229, 231  
getMACAddress 102  
getManifest 505  
getManifestChannel 470  
getManifestRepresentation 380, 383, 391, 402, 404  
getMapIdStr 748, 766, 797  
getMaxHeapSize 1092  
getMaximumPendingReadBytes 272, 1496  
getMaximumPendingWriteBytes 271, 363, 1495  
getMaximumSetBufferTime 272, 363, 1496  
getMaxRTCPWaitTime 1046  
getMaxStorageDirDepth 282  
getMaxTimecode 1189, 1326  
getMediaCaster 831, 840, 1223  
getMediaCasterCount 839  
getMediaCasterDef 806, 826  
getMediaCasterDefs 825  
getMediaCasterHostPortConfig 827  
getMediaCasterId 805, 831  
getMediaCasterList 1499  
getMediaCasterNames 825, 839  
getMediaCasterProcessorCount 828  
getMediaCasterProperties 281  
getMediaCasterRTSPRTSPRTPTransportMode 302  
getMediaCasterSettings 1499  
getMediaCasterStreamItem 807  
getMediaCasterStreams 269  
getMediaCasterType 810, 1038  
getMediaCasterValidator 291  
getMediaExtension 10, 1146, 1155  
getMediaIOPerformance 1193  
getMediaIOPerformanceCounter 342  
getMediaList 876, 1146  
getMediaListProvider 301  
getMediaListSegment 868  
getMediaName 10  
getMediaReader 1055  
getMediaReaderContentType 301, 1506

getMediaReaderProperties 281  
getMediaReaders 1494  
getMediaWriterProperties 281  
getMediaWriters 1494  
getMember 203  
getMemberCount 202  
getMembers 202  
getMessagesInBytes 84  
getMessagesInBytesRate 85  
getMessagesInCount 84  
getMessagesInCountRate 85  
getMessagesLossBytes 85  
getMessagesLossBytesRate 86  
getMessagesLossCount 84  
getMessagesLossCountRate 85  
getMessagesOutBytes 84  
getMessagesOutBytesRate 86  
getMessagesOutCount 84  
getMessagesOutCountRate 85  
getMetadata 1152  
getMetadataEntryForTime 465  
getMetadataPacket 956, 1042  
getMetaDataProvider 1203  
getMethod 533  
getMimeType 749  
getMinimumAvailableChunks 494  
getMissing 219  
getMode 1051  
getModFunctions 269  
getModuleInstance 270  
getModuleList 270  
getMp3TagMap 1494  
getMPEGTSAudioBitrate 1061  
getMPEGTSAudioLanguage 1047  
getMPEGTSAudioPID 1048  
getMPEGTSProgramID 1047  
getMPEGTSVideoBitrate 1061  
getMPEGTSVideoPID 1048  
getMsgBytes 537  
getMultiplier 1137  
getName 236, 259, 821, 862, 870, 975, 1107, 1120, 1132, 1175, 1313, 1315, 1342, 1491, 1516, 1524  
getNameGroupByGroupName 1273  
getNameGroups 1273  
getNameGroupStreamNames 1273  
getNetConnection 812, 1179  
getNetConnectionHostPortConfig 1499  
getNetConnectionIdleFrequency 1497  
getNetConnectionProcessorCount 1491  
getNextChunkIndex 469  
getNextCodecIndex 470  
getNextMetadataIndex 470  
getNextNameGroupId 1273  
getNextNetConnectionId 1487  
getNextRun 1450  
getNextSessionId 1017  
getNextStreamIndex 1268, 1269  
getNextTimeMapIndex 470  
getNodeByTagName 110  
getNodeValue 111  
getNodeValueByTagName 110  
getNormalizedNTPTimecode 1052  
getNumberLiveEntries 408, 466  
getNumberRecordedEntries 408, 466  
getObject 145, 157, 181, 197, 198, 230, 232  
getObjectEncoding 156, 160, 212, 362  
getObjectNames 1114  
getObjectReference 161  
getOffset 556  
getOffsetToNextTag 780  
getOnMetadataData 70  
getOrCreate 1114  
getOutHost 1050  
getOutIpAddress 979  
getOutPort 979  
getOutputStream 538  
getOverlayImages 1426  
getOwnerIdentifier 774  
getPacketizerName 493  
getPacketStartTime 390  
getPacketType 557  
getPageUrl 354, 926  
getParam 904  
getParamBoolean 907, 908  
getParamCount 904  
getParamDate 906  
getParamDouble 906, 907  
getParameter 534  
getParameterMap 535  
getParameterNames 534



getParameterValues 535  
getParamInt 906  
getParamLong 907  
getParamMixedArray 905  
getParamObj 905  
getParamString 905  
getParamType 904  
getParamValue 108  
getParent 1110, 1134, 1238  
getPassword 321  
getPath 11, 523, 536, 1145, 1155  
getPeakThreads 1092  
getPictureData 749  
getPictureType 749  
getPingRoundTripTime 351  
getPingTimeout 271, 360, 1495  
getPlayClass 1517  
getPlayDuration 593, 871  
getPlayer 1188  
getPlayerCount 832, 846  
getPlaylist 1340  
getPlaylistAlignment 478  
getPlayPackets 665, 669, 674, 1189  
getPlayReadyDecryptorKey 1255  
getPlayStart 593, 871  
getPlayStreamCount 269  
getPlayStreamCountsByName 269  
getPlayStreams 343  
getPlayStreamsByName 269  
getPollingInterval 1343  
getPort 695, 1456  
getProcessorCount 1457  
getProperties 237, 260, 344, 504, 561, 566, 591, 822, 862, 868, 876, 1003, 1074, 1091, 1189, 1280, 1289, 1301, 1489, 1517, 1525  
getProperty 309, 821, 1106, 1129, 1487, 1517  
getPropertyBoolean 309  
getPropertyDouble 310  
getPropertyInt 310  
getPropertyLong 310  
getPropertyStr 309  
getProtocol 355, 535  
getProtocolUsage 240, 302, 1094, 1507  
getProtocolUsageTracker 1094  
getPublishAudioCodecId 1208  
getPublisher 1343  
getPublisherCount 285  
getPublishers 285  
getPublishStreamNames 290, 1266  
getPublishStreams 343  
getPublishVideoCodecId 1208  
getPurgeController 506  
getQueryStr 353, 586, 1006, 1201  
getQueryString 533  
getQueueSize 1522  
getRange 395  
getReceiveVideoFPS 1193  
getReconnectWaitTime 809  
getRecordedDuration 407, 469  
getRecordedEntries 406, 407, 463, 468  
getRecordedEntriesInRange 407, 464  
getRecordedEntriesMap 464  
getRecordedEntriesWithLimit 407, 468, 510  
getRecordedEntryByIndex 407, 464, 510  
getRecordedEntryByTime 510  
getRecordedEntryByTimeKey 407, 464  
getRecordedEntryStartingBeforeTime 407  
getRecordingName 1283  
getRecordingStreamStore 494  
getRedirectSessionBody 595  
getRedirectSessionCode 594, 1014  
getRedirectSessionContentType 596  
getRedirectSessionMessage 1014  
getRedirectSessionURL 595, 1014  
getRefCount 1104, 1128  
getReference 131  
getReferrer 354, 585, 926, 1006  
getRemoteAddr 536  
getRemoteHost 536, 694  
getRendition 875  
getRenditions 875  
getRepeat 1312, 1342  
getRepeaterItemsDvr 500  
getRepeaterLastSequence 1290  
getRepeaterMediaCasterDef 566  
getRepeaterOriginUrl 272, 360, 925  
getRepeaterQueryString 273  
getRequestFilters 523, 530  
getRequestURI 533  
getRequestURL 534  
getRespAMFAudioObj 353, 1200

getRespAMFDataObj 353, 1200  
getRespAMFVideoObj 353, 1200  
getRespFunctions 350  
getResponseAMFObj 353  
getRsoStorageDir 275  
getRsoStoragePath 275  
getRTPAVSyncMethod 278  
getRTPContext 1033, 1500  
getRTPDatagramConfigIncoming 1500  
getRTPDatagramConfigOutgoing 1500  
getRTPDestination 1059  
getRTPIdleFrequency 274, 1497  
getRTPInfo 1052  
getRTPMaxRTCPWaitTime 279  
getRTPPlayAuthenticationMethod 278  
getRTPProperties 281  
getRTPPublishAuthenticationMethod 278  
getRTPSession 314, 322, 984  
getRTPSessionCount 280  
getRTPSessionCountsByName 280  
getRTPSessions 279  
getRTPStream 362, 1204  
getRTPStreamContext 1062  
getRTPWriteListener 1004  
getRTSPBindIpAddress 294, 1056  
getRTSPConnectionAddressType 295, 1056  
getRTSPConnectionIpAddress 294, 1056  
getRTSPMaximumPendingWriteBytes 292, 1055  
getRTSPMaxPathLen 1508  
getRTSPOriginAddressType 295, 1057  
getRTSPOriginIpAddress 295, 1057  
getRTSPPlayRangeStart 1010  
getRTSPPlayRangeStop 1010  
getRTSPRequestValidator 1507  
getRTSPSessionDescription 1053  
getRTSPSessionExtraLines 1059  
getRTSPSessionName 1053  
getRTSPSessionTimeout 292, 1055  
getRTSPStream 999  
getRTSPTunnelingLock 968  
getRTSPTunnelingSession 968  
getRTSPTunnelingSessionId 1010  
getSample 557  
getScheme 535  
getSDPData 983  
getSDPLang 1060  
getSecondByte 222  
getSegment 861, 862  
getSegmentDuration 641, 655  
getSegmentNumber 642, 656  
getSegmentSchedule 642, 655  
getSegmentSize 641, 655  
getSeq 221  
getSerializeSize 457  
getServerGUID 1091  
getServerHostPort 355  
getServerIp 584, 1005  
getServerName 535  
getServerPort 536, 585, 1005  
getSession 1017, 1036  
getSessionDescriptionData 849  
getSessionGUID 1091  
getSessionId 578, 998  
getSessionIds 1017  
getSessionProtocol 563, 584  
getSessions 965  
getSessionTimeout 581  
getSessionTracker 627  
getSessionType 583  
getSharedObjectReadAccess 277, 356  
getSharedObjects 261, 262  
getSharedObjectWriteAccess 277, 356  
getShort 144, 180, 197, 198, 229, 231  
getSize 208, 218, 557, 742, 766, 798, 871  
getSlot 1103, 1127  
getSlotNames 1103, 1127  
getSlots 1109, 1127  
getSlotVersion 1120  
getSoVersion 1120  
getSpeed 1335  
getSplitType 641, 655  
getSrc 209, 220, 1174  
getSSLConfig 1459  
getSslFactoryClass 1457  
getStart 1315  
getStartIndex 395  
getStartLiveOnPreviousBufferTime 1345  
getStartOnPreviousBufferTime 1332  
getStartTC 1138  
getStartTCOffset 1138

getStartTime 642, 657  
getStartTimecode 390  
getStartupStreams 1505  
getStopTimecode 390  
getStorageDir 1108, 1116, 1133  
getStream 580, 805, 910, 1036, 1266, 1267, 1279, 1322  
getStreamArray 835  
getStreamAttributes 1047  
getStreamAudioSampleAccess 276, 357  
getStreamBaseName 493  
getStreamBitrate 924, 1442  
getStreamClientless 1266  
getStreamCount 269  
getStreamDef 1520  
getStreamDefs 1519  
getStreamExt 587, 833, 1043  
getStreamFile 351, 352  
getStreamFileForRead 1199  
getStreamFileForWrite 1199  
getStreamFileMapper 282  
getStreamId 1036  
getStreamInfo 1037, 1047  
getStreamKeyDir 274  
getStreamKeyPath 275  
getStreamLastSeq 808  
getStreamLength 924, 1442  
getStreamList 836  
getStreamListLock 1265  
getStreamLock 1034  
getStreamManager 839  
getStreamMissingTime 807  
getStreamName 505, 587, 642, 656, 1043, 1300  
getStreamNameAliasProvider 285  
getStreamNameLock 1266  
getStreamNameLogging 1044  
getStreamNameParts 588  
getStreamNames 846  
getStreamPacketizerItem 965, 1012  
getStreamPort 973  
getStreamPosition 588, 1155  
getStreamProperties 281  
getStreamProperty 943  
getStreamQueryStr 1049  
getStreamReadAccess 276, 358  
getStreams 259, 1180, 1266  
getStreamSessionId 1044  
getStreamSessionIp 1045  
getStreamSessionVersion 1044  
getStreamStorageDir 274  
getStreamStoragePath 275  
getStreamStore 493  
getStreamStores 493  
getStreamTimeout 807  
getStreamTimeoutLastReset 808  
getStreamTimeoutLastTime 808  
getStreamTimeoutReason 808  
getStreamTrack 1037  
getStreamType 260, 344, 820, 923, 1042, 1190, 1322  
getStreamTypeNames 1520  
getStreamTypes 1487  
getStreamTypeStr 566  
getStreamVersionHandler 495  
getStreamVideoSampleAccess 275, 357  
getStreamWriteAccess 277, 359  
getString 144, 157, 179, 196, 197, 228, 230  
getStringReference 161  
getSystemTime 103  
getTarget 1449  
getTargetEncoding 160  
getTextEncoding 748, 769, 785, 791, 794  
getThreadPool 1073, 1090, 1490  
getTime 48  
getTimecode 209, 220, 787, 949  
getTimedTextProperties 284  
getTimedTextProviderConfig 1505  
getTimeMap 472, 517  
getTimeMapEntries 517  
getTimeMapper 505  
getTimeMapping 404  
getTimeOffsetBetweenItems 1345  
getTimeRunning 238, 267, 351, 591, 1013, 1071, 1088, 1493  
getTimeRunningSeconds 238, 267, 351, 591, 1013, 1071, 1089, 1493  
getTimeSeconds 48  
getTimeStampFormat 785  
getTimeString 48  
getTotal 332  
getTotalAccepted 332  
getTotalIOPerformanceCounter 342  
getTotalRejected 333

getTrack 978, 1035  
getTrackId 1035  
getTrackNames 1036  
getTrait 157, 200  
getTraitReference 161  
getTranscoderApplicationContext 299  
getTranscoderName 1300  
getTranscoderProperties 282  
getTranscoderType 1302  
getTranscoderVODContext 1507  
getTranscoderVODDestination 600  
getTranscoderVODIndex 597, 598  
getTranscoderVODIndexDestinationsMap 598  
getTranscoderVODIndexDestinationsOrder 597  
getTranscoderVODSession 597  
getTransportMode 1052  
getTransportThreadPool 1073, 1090, 1490  
getTTL 974, 981  
getType 129, 179, 209, 220, 391, 395, 406, 870, 950  
getTypeAsString 868  
getUDPManagedDeliveryCount 1060  
getUDPManagedDeliveryDelay 1060  
getUDPPortManager 1075, 1092  
getUDPPortSharingManager 1075, 1092  
getUDPTransport 978, 1046  
getUDPTransportManager 966, 1503  
getUniqueId 831  
getUniqueStreamIdStr 1207  
getUnsignedShort 38  
getUri 354, 585, 1006  
getURL 772, 793  
getUserAgent 585, 1000  
getUserAgents 1072, 1089  
getUserHTTPHeaderHeaders 568, 593  
getUserQueryStr 591  
getUserTime 103  
getUtcStartTime 390  
getValidationFrequency 271, 1495  
getValue 134, 146, 151, 169, 183, 199, 769, 788, 791  
getVersion 922, 1070, 1086, 1105, 1129  
getVHost 237, 260, 314, 322, 347, 562, 566, 579, 804, 909, 966, 1000, 1018, 1037, 1270  
getVHostItems 1529  
getVHostList 1074, 1091  
getVHostMap 1528  
getVHostNames 1529, 1532  
getVideoCodec 60, 68, 383  
getVideoCodecConfigPacket 1204  
getVideoCodecId 869  
getVideoFrameType 68  
getVideoHost 973  
getVideoMissing 1188  
getVideoPacketizerItem 965, 1012  
getVideoPort 972  
getVideoSize 1174  
getVideoTC 1177  
getVideoTimecodeOffset 68  
getVideoTrack 1037  
getVODLastTimeTC 1058  
getVODPlayLen 1058  
getVODSpeed 1346  
getVODStartTimeTC 1057  
getVODTimedTextProviderList 284  
getVODTimedTextProviderSet 284  
getVODTranscodeNGRP 597, 871  
getWidth 870  
getWowzSession 366  
getWriteListener 359  
getWriteLock 641, 657  
getXMLPropertyBool 113  
getXMLPropertyDouble 113  
getXMLPropertyExists 112  
getXMLPropertyInt 112  
getXMLPropertyIntSize 112  
getXMLPropertyLong 112  
getXMLPropertyLongSize 113  
getXMLPropertyStr 111  
gmtTimeZone 101  
grabFrame 1424  
GZIP 18

## H

handleArchivedStream 377, 513  
handleCallback 1194  
handleMessage 955, 981  
handleOnMetadata 1299  
handlePacket 1279, 1290, 1299  
hasAudio 471, 507  
hasCodecData 471

- 
- hasData 471, 507
  - hasEncryption 507
  - hasOnMetadata 471, 507
  - hasTimeMapData 472
  - hasVideo 471, 507
  - HEADERSIZE 756
  - height 867
  - hexadecimal 32
  - HOSTNAME\_KEY 682
  - HostPort 1455
  - HostPortList 1461
  - HOUR 1448
  - HTMLEncode 632
  - HTTPLiveStreamRecord 631
  - HTTPORIGINMODE\_AUTO 565
  - HTTPORIGINMODE\_OFF 565
  - HTTPORIGINMODE\_ON 565
  - HTTPRequestToByteArray 72, 73
  - HTTPRequestToFile 72
  - HTTPProvider2Base 522
  - HTTPStreamerSessionCupertino 544
  - HTTPStreamerSessionDirect 554
  - HTTPStreamerSessionMPEGDash 608
  - HTTPStreamerSessionSanJose 615
  - HTTPStreamerSessionSmoothStreamer 621
  - HTTPStreamerSessionWebM 627
  - HTTPUtils 72
  - I
  - ID3FOOTER\_SIZE 740
  - ID3Frames 741
  - ID3HEADER\_SIZE 740
  - ID3HEADER\_VERSION 740
  - ID3HEADERFLAGS\_DEFAULT 740
  - ID3HEADERFLAGS\_EXPERIMENTAL 741
  - ID3HEADERFLAGS\_EXTENDED 741
  - ID3HEADERFLAGS\_FOOTERPRESENT 741
  - ID3HEADERFLAGS\_UNSYNC 741
  - ID3V2FrameAttachedPicture 748
  - ID3V2FrameBase 764
  - ID3V2FrameComment 768
  - ID3V2FrameLinkedInformation 771
  - ID3V2FramePrivate 774
  - ID3V2FrameRawBytes 777
  - ID3V2FrameRecommendedBufferSize 779
  - ID3V2FrameSynchronizedText 784
  - ID3V2FrameSynchronizedTextDescriptor 787
  - ID3V2FrameTextInformation 790
  - ID3V2FrameURLLink 793
  - ID3V2Utils 795
  - idle 1050, 1179
  - idleFrequency 997
  - idleHandler 996
  - idStringToName 823
  - importManifest 470
  - incAbsTimecode 211
  - incByteContainerLevel 211
  - incClientCountTotal 261
  - incrementAccept 328
  - incrementBytesIn 81
  - incrementBytesLoss 83
  - incrementBytesOut 83
  - incrementFileIn 81
  - incrementFileOut 82
  - incrementMediaInBytes 1035, 1194
  - incrementMediaLossBytes 1194
  - incrementMediaOutBytes 1193
  - incrementMessagesIn 81, 82
  - incrementMessagesLoss 82, 83, 84
  - incrementMessagesOut 82, 83
  - incrementReject 328
  - incSlotVersion 1120
  - index 389
  - indexOf 39
  - indexOfDifferent 39
  - indexTranscoderVOD 545, 598, 610, 617, 623
  - info 701, 702
  - init 8, 316, 317, 411, 413, 479, 484, 504, 515, 516, 523, 530, 562, 565, 632, 638, 654, 804, 831, 849, 964, 1119, 1144, 1151, 1172, 1234, 1259, 1278, 1289, 1298, 1486, 1522, 1531
  - initContextLogging 709
  - initialAttributes 500
  - initialize 463
  - initializeLogging 709
  - initialManifest 500
  - initialManifestEnd 500
  - initLiveStreamRepeating 923, 1208, 1238
  - initProperties 1039
  - initStream 920
-

InputStream 25  
interleavePackets 63, 64  
interruptPlay 1237  
intToByteArray 36, 37  
intToByteArraySafeSync 796  
intToHexStr 97  
intToStr 97  
intValue 168  
invoke 1064  
invokePrevious 910, 911  
IOPerformanceCounter 80  
ioPerformanceCounter 995  
ioSession 998  
ip 994  
isAcceptConnection 260, 345  
isAcceptSession 587  
isAcceptWOWZConnections 1076, 1094  
isActive 580, 694, 1280, 1289  
isAddressMulticast 94  
isAMF0 156, 161  
isAMF3 156, 161  
isAMF3Start 130  
isAnnounce 995, 1003  
isAnnounceOrDescribe 1004  
isAppend 1187  
isAppendFile 640, 657  
isAppInstanceLoaded 236  
isApplicationLoaded 1489  
isArrayStart 130  
isAudio 221  
isAudioCodecConfig 67  
isAVSyncNonSR 1046  
isBlockUDPOut 982, 1061  
isByteArrayStart 131  
isByteContainerEmpty 211  
isByteContainerFull 211  
isCheckIpAddr 1045  
isCheckSSRC 1045  
isClient 1103, 1128  
isClustered 1198  
isConnected 344, 996, 1004  
isDebugAppTimeout 302  
isDebugEnabled 700  
isDebugLog 86  
isDebugOn 1450  
isDebugRTSPSession 1009  
isDescribe 995, 1003  
isDynamic 203  
isDynamicLogContextLoaded 1074, 1091  
isEmpty 97, 396, 398, 406, 741  
isEnabledFor 700  
isEncoderInUse 1432  
isEncrypted 355  
isErrorEnabled 699  
isExpired 1451  
isFileInfo 589  
isFirstABSTRequest 617  
isFlashMediaLiveEncoder 361  
isFlashVersion10 361  
isFlashVersion90115 361  
isFlashVersionH264Capable 361  
isForceAMF0 950  
isForceMPEGTSOut 1061  
isForceRTSPInterleaved 1052  
isGlobalLogValueSet 710  
isHeadRequest 537  
isHeadResponse 540  
isHitEnd 1142  
isHTTPOrigin 596  
isHTTPOriginOn 567  
isInfoEnabled 700  
isInitiateWOWZConnections 1076, 1095  
isInMulticast 981  
isInRange 396, 398  
isIntData 155  
isLastSentAbsTimecode 212  
isLive 509, 1054  
isLiveRepeater 360  
isLiveStreamPacketize 1295  
isLiveStreamTranscode 1303  
isLoaded 506  
isLoggedConnect 1002  
isLongTimecode 212  
isMatch 1449  
isMediaCasterPlay 1209  
isMember 202  
isMergeOnMetadata 1209  
isMixedArrayStart 131  
isModePlay 1049  
isModePublish 1049

isModeUnknown 1049  
isMoveFirstVideoFrameToZero 641, 658  
isMoveToNextIfLiveStreamMissing 1345  
isMPEGTSOut 1054  
isMulticast 971, 981  
isNew 210  
ISO8601\_FORMAT 684  
ISO8601\_PATTERN 684  
isObjectEncodingAMF0 212, 362  
isObjectEncodingAMF3 212, 361  
isObjEnd 131  
isObjStart 130  
isOnMetadataPacket 69  
isOpen 9, 1145, 1152, 1191  
isOutMulticast 981  
isOverlayAvailable 1427  
isPacketizeAudio 603, 1291  
isPacketizeData 603, 1292  
isPacketizeVideo 603, 1291  
isPaused 1039  
isPending 953  
isPersistent 1104, 1115, 1128  
isPlay 1178  
isPlaying 1173  
isPlaylistReady 477, 478  
isPlayLogged 581  
isPublishDataEvents 1327  
isPublishStreamReady 1038, 1209  
isPurgingEnabled 479  
isReceiveAudio 1192  
isReceiveVideo 1193  
isRecord 1178  
isRecordData 640, 657  
isRecording 496, 509, 1282  
isRecordingPaused 496, 509, 1282  
isRecordOnMetaData 674  
isRedirectSession 594, 1013  
isRepeaterEdge 1291  
isResetPlayStream 1040  
isResyncAudioVideoOnSR 1041  
isRTPIgnoreProfileLevelId 1060  
isRTPIgnoreSPropParameterSets 1061  
isRTPIncomingDatagramPortValid 288  
isRTPWrapped 974  
isRTSP 1048  
isRTSPAlwaysUseSDPPorts 1059  
isRTSPPull 1049  
isRunning 1432  
isSecure 355, 536  
isSendOnMetadata 1309, 1329, 1344  
isSendPlayStopLogEvent 1202  
isSendPublishStopLogEvent 1203  
isSendRecordStopLogEvent 1202  
isSendResult 908  
isSendSDESEvents 1053  
isSession 808  
isSessionValid 994, 1001  
isShutdownClient 1011  
isShutdownOnRelease 833  
isShuttingDown 1501  
isSSL 355  
isStartLiveOnPreviousKeyFrame 1344  
isStartOnKeyFrame 638, 657  
isStartOnPreviousKeyFrame 1332  
isStartStartupStreams 1505  
isStopIfStreamMissing 1332  
isStream 808, 972  
isStreamDomainProtectionActive 567  
isStreamIsRunning 809  
isStreamStarted 1058  
isSuspended 1075, 1087, 1459, 1502  
isSwitchLog 1344  
isTemplateLoaded 1301  
isTimeout 579, 1056  
isTimeoutSession 580  
isTimesInMilliseconds 1344  
isTraceEnabled 700  
isTranscoderActive 1301  
isTranscodeResult 1211  
isUnpublishOnEnd 1346  
isValid 831, 1159  
isValidated 581  
isValidFMLEConnections 296, 365  
isValidAudioCodec 603  
isValidStreamDomainStr 589  
isValidVideoCodec 603  
isVersionFile 640, 657, 1251  
isVHostRunning 1086  
isVideo 222  
isVideoCodecConfig 67

isVideoH264SEIListenerEmpty 1212

isVideoKeyFrame 67, 69

isVisited 1525

isWaitForVideoKeyFrame 1251

isWarnEnabled 699

isWowzaAudioOnly 869

## J

JNDI\_CONTEXT\_NAME 683

## K

KEYDATA\_MODE\_ENCRYPT 885

KEYDATA\_MODE\_INIT 884

KEYDATA\_MODE\_PLAYLIST 885

killClient 1488

killRTSPSession 1488

## L

LANG\_ASCII 1373

LANG\_ASCII\_DBL 1374

LANG\_GB231280 1374

LANG\_KSC56011987 1374

LANG\_PRIV1 1374

LANG\_PRIV2 1374

LANG\_REG1 1374

LANGUAGE\_ID\_ENGLISH 1398

LANGUAGE\_LOCALE 1398

lastAuthenticateMethod 994

lastModified 10

len 214

length 11, 98, 1201, 1237

LICENSECOUNTER\_DRM\_BUYDRM\_LIVE 1478

LICENSECOUNTER\_DRM\_BUYDRM\_VOD 1478

LICENSECOUNTER\_DRM\_EZDRM\_LIVE 1477

LICENSECOUNTER\_DRM\_EZDRM\_VOD 1477

LICENSECOUNTER\_DRM\_VERIMATRIX\_LIVE 1477

LICENSECOUNTER\_DRM\_VERIMATRIX\_VOD 1477

LICENSECOUNTER\_NDVR 1477

LICENSECOUNTER\_PUBLISHER 1476

LICENSECOUNTER\_PUBLISHERTRANSCODER 1477

LICENSECOUNTER\_TOTAL 1479

LICENSECOUNTER\_TRANSCODE\_DECODE 1477

LICENSECOUNTER\_TRANSCODE\_DECODECOUNTAU  
DIO 1478

LICENSECOUNTER\_TRANSCODE\_DECODECOUNTAU  
DIOVIDEO 1478

LICENSECOUNTER\_TRANSCODE\_DECODECOUNTVID  
EO 1478

LICENSECOUNTER\_TRANSCODE\_DECODEPOLLING  
1478

LICENSECOUNTER\_TRANSCODE\_ENCODE 1477

LICENSECOUNTER\_TRANSCODE\_ENCODECOUNTAU  
DIO 1479

LICENSECOUNTER\_TRANSCODE\_ENCODECOUNTAU  
DIOVIDEO 1479

LICENSECOUNTER\_TRANSCODE\_ENCODECOUNTVID  
EO 1479

LICENSECOUNTER\_TRANSCODE\_ENCODEPOLLING  
1478

LICENSECOUNTER\_TRANSCODE\_STREAMNAMES  
1478

listeners 653

liveStreamPacketizers 1265

LiveStreamRecorderBase 654

LiveStreamRecorderFLV 663

LiveStreamRecorderMediaWriter 668

LiveStreamRecorderMP4 673

LiveStreamRecordFileVersionDelegate 678

load 1117, 1133

loadArchivedRecordings 484

loadArchivedStore 497

loadConfig 1528

loadConfigFile 1439, 1444

loadConfigProperties 111

loadFile 750

lock 860, 865, 874, 998, 1110, 1133

lockRepeaterStreams 586, 1038

log 700, 701

LOG4J\_ID\_KEY 682

LOG4J\_PACKAGE\_NAME 681

logDebug 914

logError 914

loggedConnect 995

LOGGERNAME\_SERVER 708

logInfo 914

logLiveChunk 545, 609, 616

logLiveFragment 622



logNotifier 1084  
LogNotifyCalculateIncremental 689  
logVODChunk 545, 609, 616  
logVODFragment 622  
logWarn 914  
longToByteArray 37, 38  
longToHexStr 97  
longToStr 97  
longValue 168

## M

main 18, 1085  
makeNewLoggerInstance 709  
MANIFEST\_TAGNAME\_CAN\_PLAY 462  
MANIFEST\_TAGNAME\_CAN\_RECORD 462  
MANIFEST\_TAGNAME\_CHUNK\_GROUPING 463  
MANIFEST\_TAGNAME\_CURRENT\_TIME 463  
MANIFEST\_TAGNAME\_HAS\_ENCRYPTION 462  
MANIFEST\_TAGNAME\_PURGE\_TIME 463  
MANIFESTFILE\_KEY\_ARTIFACT 388  
MANIFESTFILE\_KEY\_AUDIO\_CODEC 388  
MANIFESTFILE\_KEY\_CHUNKINDEX 388  
MANIFESTFILE\_KEY\_DVRTIME 388  
MANIFESTFILE\_KEY\_ENCRYPTIONS 389  
MANIFESTFILE\_KEY\_INDEX 387  
MANIFESTFILE\_KEY\_METADATA 389  
MANIFESTFILE\_KEY\_NAME 388  
MANIFESTFILE\_KEY\_PACKETTIME 388  
MANIFESTFILE\_KEY\_SIZE 388  
MANIFESTFILE\_KEY\_START 387  
MANIFESTFILE\_KEY\_STOP 387  
MANIFESTFILE\_KEY\_TYPE 387  
MANIFESTFILE\_KEY\_UTCTIME 388  
MANIFESTFILE\_KEY\_VIDEO\_CODEC 388  
MAX\_CCCOUNT 1368  
MAXSTREAMINDEX 1263  
md5Digest 88  
MD5DigestUtils 88  
md5Lock 88  
MEDIACACHE\_PREFIX 427  
MediaCasterItem 820  
MediaCasterList 825  
MediaCasterSettings 827  
MediaCasterStreamItem 830  
MediaCasterStreamManager 835  
MediaCasterStreamMap 838  
MEDIACASTERTYPE\_LIVEREPEATER 804  
MEDIACASTERTYPE\_RTPLIVE 804  
MEDIACASTERTYPE\_SHOUTCAST 804  
MEDIACASTERTYPE\_UNKNOWN 804  
MediaList 860  
mediaList 874  
MediaListRendition 867  
MediaListSegment 874  
mediaListSegment 866  
MediaReaderEncInfo 1255  
MediaStreamBase 1259  
mediaStreamListeners 1265  
MediaStreamMap 1265  
MediaUtils 93  
members 194  
METHOD\_NONE 1254  
METHOD\_SAMPLE\_PLAYREADY 1255  
MILLS\_PER\_HOUR 128  
MIMETYPE\_VIDEO\_MP4 448  
MIMETYPES\_JPEG 747  
MIMETYPES\_PNG 747  
MIMETYPES\_URL 747  
MINUTE 1448  
MISSING 1140  
MODE\_PLAY 1031  
MODE\_PUBLISH 1031  
MODE\_UNKNOWN 1031  
ModuleBase 904  
ModuleClientLogging 914  
ModuleCore 919  
ModuleFastPlay 928  
ModuleMediaCaster 845  
ModuleMediaCasterStreamMonitorAdvanced 938  
ModuleProperties 941  
monitors 937  
MONTH 1448  
moveFirstVideoFrameToZero 652  
msb0baseTime 101  
msb1baseTime 101  
MSG\_STARTSTREAM 569  
MSG\_SWITCHSTREAM 569

## N

name 860, 866  
nameGroupId 1264  
nameGroups 1264  
NetworkUtils 94  
newValue 104  
newXPathFactory 113  
next 1342  
nextStreamId 1265  
NO\_OPTIONS 17  
notifyActionOnCodecInfoAudio 1198  
notifyActionOnCodecInfoVideo 1198  
notifyActionOnMetaData 1197  
notifyActionPause 1197  
notifyActionPauseRaw 1197  
notifyActionPlay 1196  
notifyActionPublish 1197  
notifyActionSeek 1197  
notifyActionStop 1198  
notifyActionUnPublish 1197  
notifyDvrStreamManagerCreate 301  
notifyDvrStreamManagerDestroy 301  
notifyDvrStreamManagerInit 301  
notifyDvrStreamStorageDeleted 499  
notifyDvrStreamStoreCreate 499  
notifyDvrStreamStoreDestroy 499  
notifyDvrStreamStoreInit 499  
notifyDvrStreamStoreLoaded 499  
notifyHTTPSessionCreate 304, 545, 559, 609, 617, 622  
notifyHTTPSessionDestroy 304, 545, 559, 610, 617, 623  
notifyLiveStreamDvrRecorderCreate 300  
notifyLiveStreamDvrRecorderDestroy 300  
notifyLiveStreamDvrRecorderInit 300  
notifyLiveStreamPacketizerCreate 296  
notifyLiveStreamPacketizerDestroy 296  
notifyLiveStreamPacketizerInit 296  
notifyLiveStreamTranscoderCreate 297  
notifyLiveStreamTranscoderDestroy 297  
notifyLiveStreamTranscoderInit 297  
notifyMediaReaderClose 294  
notifyMediaReaderCreate 293  
notifyMediaReaderExtractMetaData 294  
notifyMediaReaderInit 293  
notifyMediaReaderOpen 293  
notifyMediaStreamCreate 1271

notifyMediaStreamDestroy 1272  
notifyMediaWriterOnFLVAddMetadata 291  
notifyMediaWriterOnWriteComplete 291  
notifyPlayPublish 1271  
notifyPlayUnpublish 1270  
notifyRTPSessionCreate 303  
notifyRTPSessionDestroy 303  
notifySegmentEnd 659  
notifySegmentStart 659  
notifySessionCreate 1019  
notifySessionDestroy 1019  
notifySlotDelete 1133  
notifySlotSetValue 1133  
notifyTimeReset 499  
notifyVHostClientConnect 1532  
notifyVHostCreate 1533  
notifyVHostInit 1533  
notifyVHostItemCreate 1528  
notifyVHostItemDestroy 1529  
notifyVHostItemUpdate 1529  
notifyVHostShutdownComplete 1533  
notifyVHostShutdownStart 1533  
notifyVideoH264Packet 1212

## O

ODDPARITY 1368  
offset 214  
ON\_METADATA\_TYPE 462  
ON\_TEXT\_DATA 1414  
onAACEncodeInfo 856  
onAcceptConnection 369  
onAcceptorCreate 1463  
onAcceptorDestroy 1463  
onAfterDecodeFrame 1429  
onAfterEncodeFrame 1431  
onAfterScaleFrame 1429  
onAnnounce 959, 1007  
onApplicationCreate 306  
onApplicationDestroy 306  
onApplicationInstanceCreate 305  
onApplicationInstanceDestroy 305  
onAppStart 845, 880, 938  
onAppStop 845, 880, 938  
onBeforeDecodeFrame 1429

onBeforeEncodeFrame 1431  
onBeforeScaleFrame 1429  
onBind 524, 526, 632  
onCalculateSourceAudioBitrate 1419  
onCalculateSourceVideoBitrate 1419  
onCall 881  
onCallback 1219  
onClientAccept 367  
onClientConnect 367  
onClientDisconnect 367  
onClientReject 368  
onCodecConfigAAC 853  
onCodecInfoAudio 1218  
onCodecInfoVideo 1218  
onConnect 882  
onConnectAccept 882  
onConnectFailure 816  
onConnectReject 883  
onConnectStart 815  
onConnectSuccess 815  
onCreate 547  
onCronEvent 658, 1452  
onData 811  
onDescribe 959, 1007  
onDestroy 549  
onDisconnect 370, 851, 882  
onDvrStreamManagerCreate 1276  
onDvrStreamManagerDestroy 1276  
onDvrStreamManagerInit 1276  
onFile 77  
onFillChunkDataPacket 550  
onFillChunkEnd 549  
onFillChunkStart 549  
onFLVAddMetadata 1253  
onFrameAAC 853  
onFrameMP3 853  
onGetParameter 959, 1007  
onGrabFrame 1425  
onHeaderData 854, 856  
onHTTPCupertinoEncryptionKeyCreateLive 886  
onHTTPCupertinoEncryptionKeyCreateVOD 885  
onHTTPCupertinoEncryptionKeyData 885  
onHTTPCupertinoEncryptionKeyLiveChunk 886  
onHTTPCupertinoEncryptionKeyRequest 885  
onHTTPCupertinoEncryptionKeyVODChunk 886  
onHTTPCupertinoStreamingSessionCreate 887  
onHTTPCupertinoStreamingSessionDestroy 887  
onHTTPRequest 526, 632  
onHTTPSanJoseStreamingSessionCreate 888  
onHTTPSanJoseStreamingSessionDestroy 888  
onHTTPSessionCreate 889  
onHTTPSessionDestroy 889  
onHTTPSmoothStreamingPlayReadyCreateLive 890  
onHTTPSmoothStreamingPlayReadyCreateVOD 890  
onHTTPSmoothStreamingSessionCreate 891  
onHTTPSmoothStreamingSessionDestroy 891  
onHTTPStreamerSessionCreate 599  
onHTTPStreamerSessionDestroy 599  
onIndex 548  
onInit 548  
onInitAfterLoadTemplate 1419  
onInitBeforeLoadTemplate 1419  
onInitStart 1418  
onInitStop 1419  
onLiveStreamDvrRecorderCreate 1284  
onLiveStreamDvrRecorderDestroy 1284  
onLiveStreamDvrRecorderInit 1284  
onLiveStreamPacketizerCreate 1293  
onLiveStreamPacketizerDestroy 1293  
onLiveStreamPacketizerInit 1293  
onLiveStreamTranscoderCreate 1304  
onLiveStreamTranscoderDestroy 1304  
onLiveStreamTranscoderInit 1304  
onLog 686, 690  
onMediaCasterCreate 813  
onMediaCasterDestroy 813  
onMediaReaderClose 1157  
onMediaReaderCreate 1156  
onMediaReaderExtractMetaData 1157  
onMediaReaderInit 1156  
onMediaReaderOpen 1156  
onMediaStreamCreate 1229  
onMediaStreamDestroy 1229  
onMetaData 854, 856, 1217  
onModuleLoad 879  
onModuleUnload 879  
onMP3EncodeInfo 856  
onNewVHost 1088  
onOpen 548  
onOptions 959, 1008

onPause 646, 960, 1008, 1215  
onPauseRaw 1217  
onPlay 647, 960, 1008, 1214  
onPlaylistItemStart 1310  
onPlaylistItemStop 1310  
onPublish 640, 647, 660, 665, 669, 673, 1215  
onRecord 960, 1008  
onRedirect 960, 1008  
onRegisterPlayer 813  
onRegisterStreamNameGroup 1422  
onRejectConnection 369  
onResetMediaCaster 818, 939  
onResetStream 1423  
onResponseWriteStart 1066  
onResponseWriteStop 1066  
onResult 878, 894  
onRTPSessionCreate 892, 957  
onRTPSessionDestroy 892, 957  
onSeek 647, 1215  
onSegmentEnd 645  
onSegmentStart 645  
onServerConfigLoaded 1079  
onServerCreate 1077  
onServerInit 1077  
onServerShutdownComplete 1078  
onServerShutdownStart 1077  
onSessionAudioDecodeCodecInfo 1422  
onSessionAudioEncodeCodecInfo 1421  
onSessionAudioEncodeCreate 1420  
onSessionAudioEncodeInit 1420  
onSessionAudioEncodeSetup 1421  
onSessionDataEncodeCreate 1420  
onSessionDataEncodeInit 1421  
onSessionDestinationCreate 1419  
onSessionVideoDecodeCodecInfo 1422  
onSessionVideoEncodeCodecInfo 1421  
onSessionVideoEncodeCreate 1420  
onSessionVideoEncodeInit 1420  
onSessionVideoEncodeSetup 1421  
onSetParameter 959, 1008  
onSetSourceStream 814  
onSetup 961, 1009  
onSharedObjectConnect 1111  
onSharedObjectCreate 1111  
onSharedObjectDestroy 1111  
onSharedObjectDisconnect 1112  
onShutdownStart 1422  
onShutdownStop 1423  
onSlotDelete 1122  
onSlotSetValue 1122  
onStartRecord 632  
onStop 647, 1215  
onStopRecord 632  
onStreamCreate 893, 938  
onStreamDestroy 893, 938  
onStreamStart 816, 1224  
onStreamStop 816  
onSwitchRecord 632  
onTeardown 961, 1009  
onTrim 854  
onUnbind 524, 527  
onUnPublish 640, 647, 660, 665, 669, 673, 1215  
onUnRegisterPlayer 814  
onUnregisterStreamNameGroup 1422  
onValidateMediaCaster 817, 938  
onValidateMediaCastersStart 817, 938  
onValidateMediaCastersStop 817, 939  
onVHostClientConnect 1512  
onVHostCreate 1511  
onVHostInit 1511  
onVHostItemCreate 1510  
onVHostItemDestroy 1510  
onVHostItemUpdate 1510  
onVHostShutdownComplete 1512  
onVHostShutdownStart 1511  
onVideoH264Packet 1222  
onWriteComplete 1253  
open 8, 1145, 1151, 1312  
order 194  
ORDERED 18  
output 953  
OUTPUT\_TYPE\_AMF 1398  
OUTPUT\_TYPE\_CEA608 1398  
OUTPUT\_TYPE\_TTML 1398  
OutputStream 28  
  
P  
  
p 1259  
PACKET\_TIME 455

- 
- packetComplete 1180
  - packetizerLicenses 1264
  - packetOutput 1443
  - packetTime 389
  - PARAM1 899
  - PARAM10 901
  - PARAM2 900
  - PARAM3 900
  - PARAM4 900
  - PARAM5 900
  - PARAM6 900
  - PARAM7 900
  - PARAM8 900
  - PARAM9 900
  - PARAMMETHODNAME 899
  - parseAllowDomains 273
  - parseBodyForParams 534
  - parseCommaSeparatedLanguages 872
  - parseIdString 823
  - parseQueryStr 108
  - PASSWORDFILEFORMAT\_CLEAR 316
  - PASSWORDFILEFORMAT\_UNKNOWN 316
  - pathToFileURL 106
  - pause 922, 1041, 1235
  - PAUSE\_PAUSE 1232
  - PAUSE\_PLAY 1232
  - PAUSE\_TOGGLE 1232
  - pauseRaw 926, 1235
  - pauseRecording 497, 508, 1282
  - peekByte 129
  - PICTUREMAXFILESIZE 747
  - PICTURETYPE\_ARTISTLOGO 747
  - PICTURETYPE\_COVERBACK 747
  - PICTURETYPE\_COVERFRONT 746
  - PICTURETYPE\_FILEICON 746
  - PICTURETYPE\_ILLUSTRATION 747
  - PICTURETYPE\_MOVIESCREENCAPTURE 747
  - PICTURETYPE\_OTHER 746
  - PICTURETYPE\_OTHERFILEICON 746
  - PICTURETYPE\_PUBLISHERLOGO 747
  - ping 348
  - play 921, 1040, 1041, 1234, 1235, 1307, 1331, 1334, 1340, 1341, 1342
  - play2 921
  - playDuration 867
  - PLAYEVENT\_AFTERBUFFERFILL 1150
  - PLAYEVENT\_AFTERMETADATA 1150
  - PLAYEVENT\_BEFOREBUFFERFILL 1150
  - PLAYEVENT\_BEFOREMETADATA 1150
  - PLAYEVENT\_STARTPLAYBACK 1150
  - Playlist 1311
  - PlaylistItem 1314
  - PLAYSIZES\_AUDIO\_BYTES 1233
  - PLAYSIZES\_AUDIO\_COUNT 1233
  - PLAYSIZES\_DATA\_BYTES 1233
  - PLAYSIZES\_DATA\_COUNT 1233
  - PLAYSIZES\_LOSS\_BYTES 1233
  - PLAYSIZES\_LOSS\_COUNT 1234
  - PLAYSIZES\_SIZE 1234
  - PLAYSIZES\_VIDEO\_BYTES 1233
  - PLAYSIZES\_VIDEO\_COUNT 1233
  - playStart 867
  - PLAYSTATUSTYPE\_COMPLETE 1233
  - PLAYSTATUSTYPE\_STOP 1233
  - PLAYSTATUSTYPE\_SWITCH 1232
  - PLAYTRANSITION\_APPEND 903
  - PLAYTRANSITION\_APPEND\_IMMEDIATE 903
  - PLAYTRANSITION\_RESET 903
  - PLAYTRANSITION\_RESET\_IMMEDIATE 903
  - PLAYTRANSITION\_STOP 903
  - PLAYTRANSITION\_SWAP 903
  - PLAYTRANSITION\_SWITCH 903
  - PLAYTRANSITION\_UNKNOWN 903
  - PLAYTRANSITIONSTR\_APPEND 902
  - PLAYTRANSITIONSTR\_RESET 902
  - PLAYTRANSITIONSTR\_STOP 902
  - PLAYTRANSITIONSTR\_SWAP 902
  - PLAYTRANSITIONSTR\_SWITCH 902
  - PLAYTRANSITIONSTR\_UNKNOWN 902
  - postChunkAdded 486
  - postChunksPurged 487
  - preChunkAdded 486
  - preChunksPurged 486
  - previous 1343
  - PROP\_3GPP\_CAPTION\_CHARACTER\_SET 1406
  - PROP\_AMF\_CONVERTER\_INSERT\_ERASES\_IN\_GAPS 1409
  - PROP\_AMF\_CONVERTER\_TEXT\_TYPE 1408
  - PROP\_AMF\_CONVERTER\_TRACK\_INDEX 1408
  - PROP\_CAPTION\_CHARACTER\_SET 1406
-

- PROP\_CAPTION\_FILE\_NAMING\_RULE 1403
- PROP\_CAPTION\_FILENAME\_QUERY\_PARAMETER 1413
- PROP\_CAPTION\_LANGUAGE\_QUERY\_PARAMETER 1413
- PROP\_CAPTION\_LANGUAGES 1400
- PROP\_CAPTION\_PATH\_NAMING\_RULE 1404
- PROP\_CEA608\_CONVERTER\_CHARACTER\_SET 1407
- PROP\_CEA608\_CONVERTER\_CHARS\_PER\_LINE 1407
- PROP\_CEA608\_CONVERTER\_COLOR 1407
- PROP\_CUPERTINO\_CAPTION\_LANGUAGES 1400
- PROP\_CUPERTINO\_LIVE\_USE\_WEBVTT 1408
- PROP\_CUPERTINO\_VOD\_CAPTIONS\_ENABLED 1399
- PROP\_CUPERTINO\_VOD\_REMOVE\_EXISTING\_CEA608 1407
- PROP\_CUPERTINO\_VOD\_USE\_WEBVTT 1408
- PROP\_DEBUG\_3GPP\_CAPTION\_PARSER 1412
- PROP\_DEBUG\_3GPP\_CAPTION\_PARSER\_TIME 1412
- PROP\_DEBUG\_CUPERTINO\_VOD\_CAPTION\_LANGUAGE\_SELECTION 1401
- PROP\_DEBUG\_CUPERTINO\_VOD\_CAPTION\_PROVIDER\_DETERMINATION 1402
- PROP\_DEBUG\_LIVE\_CAPTION\_INGEST 1414
- PROP\_DEBUG\_LIVE\_CAPTION\_ONTEXTDATA\_INGEST 1414
- PROP\_DEBUG\_RTMP\_VOD\_CAPTION\_LANGUAGE\_SELECTION 1401
- PROP\_DEBUG\_RTMP\_VOD\_CAPTION\_PROVIDER\_DETERMINATION 1403
- PROP\_DEBUG\_SANJOSE\_VOD\_CAPTION\_LANGUAGE\_SELECTION 1402
- PROP\_DEBUG\_SANJOSE\_VOD\_CAPTION\_PROVIDER\_DETERMINATION 1403
- PROP\_DEBUG\_SCC\_CAPTION\_PARSER 1412
- PROP\_DEBUG\_SCC\_CAPTION\_PARSER\_TIME 1412
- PROP\_DEBUG\_SCC\_VOD\_CAPTION\_COMPANION\_FILES 1411
- PROP\_DEBUG\_SRT\_CAPTION\_PARSER 1410
- PROP\_DEBUG\_SRT\_CAPTION\_PARSER\_TIME 1411
- PROP\_DEBUG\_SRT\_VOD\_CAPTION\_COMPANION\_FILES 1410
- PROP\_DEBUG\_TTML\_CAPTION\_PARSER 1409
- PROP\_DEBUG\_TTML\_CAPTION\_PARSER\_TIME 1410
- PROP\_DEBUG\_TTML\_VOD\_CAPTION\_COMPANION\_FILES 1409
- PROP\_DEBUG\_VOD\_CAPTION\_COMPANION\_FILES 1403
- PROP\_DEBUG\_VOD\_CAPTION\_LANGUAGE\_SELECTION 1401
- PROP\_DEBUG\_VOD\_CAPTION\_PROVIDER\_DETERMINATION 1402
- PROP\_DEBUG\_WEBVTT\_CAPTION\_PARSER 1411
- PROP\_DEBUG\_WEBVTT\_CAPTION\_PARSER\_TIME 1411
- PROP\_DEBUG\_WEBVTT\_VOD\_CAPTION\_COMPANION\_FILES 1411
- PROP\_LIVE\_CAPTION\_DEFAULT\_LANGUAGES 1414
- PROP\_LIVE\_CAPTION\_INGEST\_AMF\_ID\_STRING 1413
- PROP\_LIVE\_CAPTION\_INGEST\_TYPE 1414
- PROP\_LIVE\_CAPTION\_USE\_STREAM\_NAME\_GROUPS 1413
- PROP\_MAXIMUM\_CAPTION\_DURATION 1405
- PROP\_RTMP\_CAPTION\_LANGUAGES 1400
- PROP\_RTMP\_VOD\_CAPTIONS\_ENABLED 1399
- PROP\_SANJOSE\_CAPTION\_LANGUAGES 1401
- PROP\_SANJOSE\_VOD\_CAPTIONS\_ENABLED 1399
- PROP\_SRT\_CAPTION\_CHARACTER\_SET 1406
- PROP\_TTML\_CAPTION\_CHARACTER\_SET 1406
- PROP\_TTML\_INLINE\_TAGS\_IN\_TEXT 1410
- PROP\_UNDEFINED\_LANG\_CODE 1403
- PROP\_VOD\_CAPTIONS\_ENABLED 1399
- PROP\_WEBVTT\_CONVERTER\_INSERT\_ERASES\_IN\_GAPS 1409
- properties 522, 860, 866, 874, 995
- PROPERTY\_ALLOWABLE\_AV\_PACKET\_DELTA 432
- PROPERTY\_APPEND\_DISCONTINUITY\_DELTA 427
- PROPERTY\_ARCHIVE\_STRATEGY 428
- PROPERTY\_AUDIO\_ONLY\_CHUNK\_TARGET\_DURATION 434
- PROPERTY\_BREAK\_ON\_PTS 435
- PROPERTY\_CHUNK\_CACHE\_CLASS 431
- PROPERTY\_CHUNK\_DURATION\_MINIMUM 436
- PROPERTY\_CHUNK\_GROUPING\_SECONDS 427
- PROPERTY\_CHUNK\_MEMORY\_CACHESIZE 436
- PROPERTY\_CHUNK\_READER\_CLASS 429
- PROPERTY\_CHUNK\_WRITER\_CLASS 429
- PROPERTY\_CUPERTINO\_ON\_CHUNK\_START\_RESET\_COUNTER 450
- PROPERTY\_CUPERTINO\_PLAYLIST\_ALLOW\_CACHING 450
- PROPERTY\_CUPERTINO\_PLAYLIST\_FORCE\_LIVE 449

- PROPERTY\_CUPERTINO\_PLAYLIST\_FORCE\_NONLIVE 449
- PROPERTY\_CUPERTINO\_PLAYLIST\_GZIP\_THRESHOLD 449
- PROPERTY\_CUPERTINO\_PLAYLIST\_USE\_GZIP 449
- PROPERTY\_DEBUG\_CHUNK\_RETRIEVALS 442
- PROPERTY\_DEBUG\_CUPERTINO\_PLAYER\_ADAPTER 444
- PROPERTY\_DEBUG\_FAILED\_CHUNK\_RETRIEVALS 443
- PROPERTY\_DEBUG\_LOG\_INVALID\_CHUNK\_DETAILS 439
- PROPERTY\_DEBUG\_LOG\_INVALID\_CHUNK\_MATCHER 440
- PROPERTY\_DEBUG\_LOG\_VALID\_CHUNK\_DETAILS 440
- PROPERTY\_DEBUG\_LOG\_VALID\_CHUNK\_MATCHER 441
- PROPERTY\_DEBUG\_MAX\_INVALID\_CHUNKS\_LOGGED 440
- PROPERTY\_DEBUG\_MAX\_VALID\_CHUNKS\_LOGGED 441
- PROPERTY\_DEBUG\_MAXIMUM\_RAW\_PACKETS 442
- PROPERTY\_DEBUG\_MBR\_ALIGNMENT 445
- PROPERTY\_DEBUG\_MBR\_ALIGNMENT\_RESOLUTION 445
- PROPERTY\_DEBUG\_MBR\_DETAILS\_WHEN\_RECORDING 445
- PROPERTY\_DEBUG\_MBR\_PLAYER\_ADAPTER 445
- PROPERTY\_DEBUG\_MBR\_PLAYER\_ADAPTER\_IF\_SHIFTED\_EMPTY 445
- PROPERTY\_DEBUG\_METHODS 444
- PROPERTY\_DEBUG\_PLAYER\_ADAPTER 444
- PROPERTY\_DEBUG\_PLAYLIST\_REQUEST 446
- PROPERTY\_DEBUG\_RAW\_PACKETS 441
- PROPERTY\_DEBUG\_RAW\_PACKETS\_MATCHER 442
- PROPERTY\_DEBUG\_REPEATERS 444
- PROPERTY\_DEBUG\_SANJOSE\_PLAYER\_ADAPTER 444
- PROPERTY\_DEBUG\_SMOOTH\_PLAYER\_ADAPTER 444
- PROPERTY\_DEBUG\_STATE\_CHANGE 442
- PROPERTY\_DEBUG\_TOSSED\_HOLDERS 441
- PROPERTY\_ENCRYPTION\_INFO\_DELEGATE 446
- PROPERTY\_FILE\_SYSTEM\_CLASS 430
- PROPERTY\_MANIFEST\_PERSISTENT\_CLASS 430
- PROPERTY\_MAX\_CHUNK\_LOG 443
- PROPERTY\_MAX\_RECALC\_DURATION\_LOG 443
- PROPERTY\_MAX\_RECORDING\_LENGTH 439
- PROPERTY\_MBR\_ALTERNATIVE\_MATCH\_DELTA 437
- PROPERTY\_MBR\_MINIMUM\_PACKETTIME\_GAP\_SIZE 437
- PROPERTY\_MBR\_MINIMUM\_UTCTIME\_GAP\_SIZE 438
- PROPERTY\_MBR\_USE\_UTC\_FOR\_ALIGNMENT 437
- PROPERTY\_MEDIACACHE\_ENABLED 439
- PROPERTY\_MEDIACACHE\_READER\_CLASS 439
- PROPERTY\_PACKET\_DELTA\_TO\_NOTIFY 433
- PROPERTY\_PACKET\_DELTA\_TO\_RESET\_TIME 433
- PROPERTY\_PACKET\_DURATION\_MAXIMUM 438
- PROPERTY\_PACKET\_SORT\_TIME 435
- PROPERTY\_PLAYLIST\_REQUEST\_DELEGATE 446
- PROPERTY\_RECORD\_AUDIO 434
- PROPERTY\_RECORD\_DATA 434
- PROPERTY\_RECORD\_VIDEO 434
- PROPERTY\_RECORDINGS\_LOADER\_CLASS 431
- PROPERTY\_REPEATERS\_HEARTBEAT\_DURATION 436
- PROPERTY\_REPEATERS\_SHARED\_SECRET 436
- PROPERTY\_SANJOSE\_ABST\_DURATION\_TOLERANCE 448
- PROPERTY\_SANJOSE\_ABST\_TIMESCALE 448
- PROPERTY\_SANJOSE\_PLAYLIST\_DELIVERYTYPE 446
- PROPERTY\_SANJOSE\_PLAYLIST\_LIVE\_STREAMTYPE 447
- PROPERTY\_SANJOSE\_PLAYLIST\_MIMETYPE 446
- PROPERTY\_SANJOSE\_PLAYLIST\_RECORDED\_STREAMTYPE 447
- PROPERTY\_SANJOSE\_PLAYLIST\_VERSION 446
- PROPERTY\_SMOOTH\_MANIFEST\_H264\_CODEC 452
- PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_PAUSE 450
- PROPERTY\_SMOOTH\_MANIFEST\_LIVE\_CAN\_SEEK 450
- PROPERTY\_SMOOTH\_MANIFEST\_MAJOR\_VERSION 452
- PROPERTY\_SMOOTH\_MANIFEST\_MINOR\_VERSION 452
- PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_PAUSE 451
- PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_CAN\_SEEK 451
- PROPERTY\_SMOOTH\_MANIFEST\_RECORDED\_SPECIFY\_DURATION 451

PROPERTY\_SMOOTH\_MANIFEST\_VERBOSE\_DURATION 452  
PROPERTY\_START\_RECORDING\_ON\_STARTUP 434  
PROPERTY\_STORAGE\_DIRECTORY 428  
PROPERTY\_STREAM\_DATA 453  
PROPERTY\_TEXT\_READER\_CLASS 432  
PROPERTY\_TEXT\_WRITER\_CLASS 432  
PROPERTY\_WINDOW\_DURATION 428  
PROTOCOLUSAGE\_CUPERTINO 257  
PROTOCOLUSAGE\_MPEGDASH 257  
PROTOCOLUSAGE\_ORIGINCUPERTINO 257  
PROTOCOLUSAGE\_ORIGINMPEGDASH 258  
PROTOCOLUSAGE\_ORIGINSANJOSE 258  
PROTOCOLUSAGE\_ORIGINSMOOTH 258  
PROTOCOLUSAGE\_RTMP 256  
PROTOCOLUSAGE\_RTMPE 256  
PROTOCOLUSAGE\_RTMPS 256  
PROTOCOLUSAGE\_RTMPT 256  
PROTOCOLUSAGE\_RTMPTE 256  
PROTOCOLUSAGE\_RTMPTS 256  
PROTOCOLUSAGE\_RTP 256  
PROTOCOLUSAGE\_SANJOSE 257  
PROTOCOLUSAGE\_SMOOTH 257  
PROTOCOLUSAGE\_TOTAL 258  
PROTOCOLUSAGE\_WEBM 257  
PROTOCOLUSAGE\_WOWZ 257  
PROTOCOLUSAGE\_WOWZE 257  
PROTOCOLUSAGE\_WOWZS 257  
PROTO\_HTTPCUPERTINO 735  
PROTO\_HTTPDVRCHUNK 736  
PROTO\_HTTPMPEGDASH 736  
PROTO\_HTTPSANJOSE 735  
PROTO\_HTTPSCUPERTINO 736  
PROTO\_HTTPSDVRCHUNK 736  
PROTO\_HTTPSMOOTH 735  
PROTO\_HTTPSSANJOSE 736  
PROTO\_HTTPSSMOOTH 736  
PROTO\_HTTPSSTREAMER 736  
PROTO\_HTTPSTREAMER 735  
PROTO\_RTMP 734  
PROTO\_RTMPE 734  
PROTO\_RTMPS 734  
PROTO\_RTMPT 734  
PROTO\_RTMPTE 734  
PROTO\_RTMPTS 734

PROTO\_RTSP 735  
PROTO\_WOWZ 735  
PROTO\_WOWZE 735  
PROTO\_WOWZS 735  
ptToDvr 518  
publish 920, 1194, 1259, 1322, 1323  
PublishingProviderBase 1328  
PublishingProviderLive 1331  
PublishingProviderMediaReader 1334  
purge 1109, 1127  
purgeEntries 465, 509  
purgeManifestEntries 498  
put 195, 196, 226, 227, 1114  
putAll 308  
putAudioPacketizerItem 964, 1012  
putDvrRecorder 1210  
putFileInfo 589  
putFrame 742  
putGlobalLogValue 710  
putHTTPStreamerAdapter 1504  
putLiveStreamTranscoder 1211  
putMetaData 1252  
putRTSPSessionExtraLine 1059  
putRTSPTunnelingSession 969  
putSlot 1103, 1128  
putStreamNameParts 588  
putStreamPacketizerItem 965, 1013  
putVideoPacketizerItem 965, 1013

## Q

QUERY\_PARAM\_DVR 477  
queryStr 996  
QUERYSTR\_CAPTION\_FILENAME 1413  
QUERYSTR\_CAPTIONLANGUAGES 1413

## R

ranges 397  
read 9, 25  
READ\_ACCESS\_ALL 341  
READ\_ACCESS\_NONE 341  
READACCESS 1126, 1172  
readAppConfig 239  
readAppInstConfig 289



readChunk 61  
readChunkHeader 61  
readConfig 1075, 1093  
readHeader 61, 62  
readPrevChunkHeader 61  
readVHostConfig 1506  
readXMLConfig 1093  
receiveAudio 924  
RECEIVER\_NAME\_KEY 682  
receiveVideo 924  
record 1040  
recordingPaused 482  
recordingReset 483  
recordingResumed 482  
recordingStarted 482  
recordingStopped 483  
recordStartTime 654  
redirectConnection 346, 347  
redirectSession 595, 997, 1014  
redirectSessionCode 997  
redirectSessionMessage 998  
redirectSessionURL 998  
referrer 996  
refreshManifest 463  
registerCallback 1195  
registerLiveStreamTranscoder 1094  
registerOnPlayStatus 1195  
registerOnStatus 1195  
registerPlayer 806, 832, 843  
registerPlayRTPSession 280  
rejectConnection 328, 345, 346  
rejectSession 586, 998  
release 833, 842, 1104, 1128  
releaseMediaCaster 847  
releaseSessionId 1017  
releaseSocketAddress 966  
releaseStream 920  
releaseUDPPortPair 967  
reloadConfig 1528  
reloadVHostConfig 1070, 1086  
remove 139, 175, 196, 228, 842, 1115, 1532  
removeAcceptorListener 1492  
removeActionListener 1007  
removeAppInstance 239  
removeApplication 1506  
removeApplicationInstanceListener 237  
removeApplicationListener 1492, 1532  
removeCallbackListener 1212  
removeClient 1104, 1116, 1128, 1488  
removeClientListener 263, 1196  
removeConnectionListener 327  
removeDvrChunkListener 510  
removeDvrRecorder 1210, 1274  
removeDvrRecorderListener 300  
removeDvrRecordingListener 499  
removeDvrStoreListener 498  
removeDvrStreamManagerListener 301  
removeFrame 742  
removeFromPlaylist 1341  
removeGlobalLogValue 710  
removeGlobalLogValues 709  
removeHeader 539  
removeHTTPListener 304  
removeHTTPStreamerSession 288  
removeIdleWorkerListener 1499  
removeItem 1312  
removeListener 643, 658, 1343  
removeLiveStreamPacketizer 1272  
removeLiveStreamPacketizerListener 296  
removeLiveStreamTranscoder 1211  
removeLiveStreamTranscoderListener 297  
removeMediaCasterListener 266  
removeMediaReaderListener 293  
removeMediaStreamListener 264, 1271  
removeMediaWriterListener 291  
removeMetaDataListener 855  
removeModuleListener 270  
removeNameGroup 1273  
removePlayStreamByName 268  
removePublisher 285  
removeRendition 875  
removeRTPLListener 303  
removeRTPSession 280  
removeRTSPStream 999  
removeRTSPTunnelingSession 968  
removeSegment 861  
removeServerListener 1072, 1089  
removeSession 1018  
removeSessionListener 1019  
removeSharedObjectListener 265, 1116

removeSlotListener 1108, 1133  
removeStream 1269  
removeStreamDomainStr 590  
removeTrack 1034  
removeTrackInternal 1034  
removeVHostItemListener 1528  
removeVideoH264SEILListener 1212  
renditions 874  
reparentClient 363, 1501  
ReplaceItem 104  
requestFilters 522  
requiresLayout 694  
reset 504, 832, 861, 1234, 1514, 1524  
resetMDC 709  
resetMediaCasterStream 289  
resetNoLookup 1234  
resetSentMetadataFlag 1042  
resetStream 476, 496, 603, 846, 1279, 1290, 1299  
resetTimecodes 1239  
resolveMediaList 1143  
resolvePlayAlias 1225, 1226, 1227  
resolveStreamAlias 1225, 1227  
ResponseFunction 946, 947  
ResponseFunctions 952  
resumeEncoding 29  
resumeRecording 497, 508, 1282  
retrieveRawChunk 411, 481  
REVERSE 8  
rewind 1152  
RTMPENABLED 1065  
RTPContext 964  
RTPDestination 971  
RTPPort 978  
RTPPushPublishSession 983  
RTPSession 998  
rtpSession 314  
RTPSessions 1017  
RTPStream 1033  
RTPUtils 1436  
rtpWriteListener 995  
rtspPlayRangeStart 997  
rtspPlayRangeStop 997  
rtspTunnelingSessionId 993  
run 1340

## S

SANJOSE\_F4M\_STREAMINGTYPE\_STREAMING 448  
SANJOSE\_F4M\_STREAMTYPE\_DVR 447  
SANJOSE\_F4M\_STREAMTYPE\_LIVE 447  
SANJOSE\_F4M\_STREAMTYPE\_LIVEORRECORDED 448  
SANJOSE\_F4M\_STREAMTYPE\_RECORDED 447  
SANJOSE\_F4M\_VERSION\_1\_0 448  
SANJOSE\_F4M\_VERSION\_2\_0 448  
SDPLOCATION\_AUDIO 1031  
SDPLOCATION\_STREAM 1030  
SDPLOCATION\_VIDEO 1031  
seek 9, 921, 1152, 1235, 1308, 1331, 1334  
SEEK\_EXACT 1151  
SEEK\_KEYCLOSE 1151  
SEEK\_KEYDOWN 1151  
SEEK\_KEYUP 1150  
SEEKTARGET\_AUDIO 1150  
SEEKTARGET\_ENHANCED 1150  
SEEKTARGET\_VIDEOKEYFRAME 1150  
SEGMENT\_NUMBER\_TAG 677  
SEGMENT\_TIME\_TAG 677  
segmentNumber 653  
segments 860  
SEL\_PAYLOADTYPE 1361  
SEL\_STARTCODE 1368  
SEL\_USERDATATYPECODE 1362  
send 1108, 1132, 1191  
sendAMF3 1191  
sendClientOnStatusError 911  
sendControlBytes 1200  
sendDirect 1190, 1191  
sendDirectAMF3 1190  
sendInternal 1132  
sendLivePlaySeek 1181  
sendLivePlayStart 1180  
sendLivePlaySwitch 1181  
sendMessage 980  
sendOnMetadata 475, 1328  
sendPauseNotify 1186  
sendPlayReset 1182  
sendPlaySeek 1183  
sendPlayStart 1183, 1184, 1185  
sendPlayStatus 1185, 1186  
sendPlayStop 1182

sendPlaySwitch 1184  
sendResponse 980  
sendResult 909, 910  
sendStreamNotFound 1180  
sendStreamOnStatusError 911  
sendUnpauseNotify 1186, 1187  
sendVODPlaySwitch 1181  
sendZeroLengthPacket 1154  
serialize 133, 146, 152, 169, 170, 182, 187, 199, 380, 383, 391, 396, 398, 402, 404, 457, 472, 743, 765, 798  
SERIALIZE\_CURRENT\_VERSION 389  
serializeBody 748, 768, 771, 774, 777, 779, 784, 790, 793, 798  
serializeDate 117  
serializeFooter 742  
serializeHeader 742  
serializeInt 117  
serializeString 119, 765  
serializeStringLen 765  
serializeStringNoLength 119  
serializeTags 742  
serializeZeroLengthString 118  
Server 1085  
serverIp 996  
serverPort 996  
service 561  
sessionClosed 807, 981  
sessionId 993  
sessionOpened 806, 981  
SESSIONPROTOCOL\_COUNT 578  
SESSIONPROTOCOL\_CUPERTINOSTREAMING 578  
SESSIONPROTOCOL\_DIRECTSTREAMING 578  
SESSIONPROTOCOL\_DVRCHUNKSTREAMING 578  
SESSIONPROTOCOL\_MPEGDASHSTREAMING 578  
SESSIONPROTOCOL\_SANJOSESTREAMING 578  
SESSIONPROTOCOL\_SMOOTHSTREAMING 578  
SESSIONPROTOCOL\_UNKNOWN 577  
SESSIONPROTOCOL\_WEBMSTREAMING 578  
sessionStart 849  
sessionStop 849  
SESSIONTYPE\_LIVE 577  
SESSIONTYPE\_LIVEDVR 577  
SESSIONTYPE\_UNKNOWN 577  
SESSIONTYPE\_VOD 577  
set 142, 143, 178, 179  
setAbsTimecode 221  
setAbsTimecodeLong 210  
setAbsTimecodeShort 210  
setAcceptConnection 260, 363  
setAcceptConnectionDescription 362  
setAcceptConnectionExObj 362  
setAcceptConnectionObj 362  
setAcceptSession 587  
setAcceptWOWZConnections 1076, 1095  
setActive 580  
setAddressCount 982  
setAdminInterfaceHostPort 1491  
setAllowDomains 273  
setAnnounce 1003  
setAppend 1187  
setAppendFile 657  
setAppInstance 583, 805, 1002, 1300  
setAppInstanceName 1043  
setAppInstanceProperty 942  
setApplication 694  
setApplicationInstanceTouchTimeout 292  
setApplicationProperty 941  
setApplicationTimeout 270, 1495  
setAppName 1043  
setAudioCodecId 869  
setAudioHost 974  
setAudioPort 973  
setAudioSize 1174  
setAudioTC 1176, 1177  
setAuthenticatePlayHandler 1001  
setAuthenticatePublishHandler 1001  
setAuthenticationMethod 524, 530  
setAVSyncMethod 1046  
setBandwidthLimit 921  
setBaseClass 822, 1516  
setBaseFilePath 656  
setBitrate 600  
setBitrateAudio 869  
setBitrateTotal 868  
setBitrateVideo 869  
setBlockUDPOut 982, 1061  
setBody 949  
setBuffer 556  
setBufferSize 780  
setBufferTime 352, 922, 1173, 1236  
setByteContainerLevel 211

setCanPlay 507  
setCanRecord 506  
setCheckIpAddr 1046  
setCheckSSRC 1045  
setChecksum 1141  
setChunkCounter 213  
setChunkGroupDuration 410  
setClassName 200, 203  
setClient 315, 322, 1180  
setClientIdleFrequency 274, 1497  
setClientProperty 942  
setClientTimeout 1490  
setClustered 1198  
setCodecInfoAudio 476, 603  
setCodecInfoVideo 476, 603  
setCommandInterface 1089  
setCommandInterfaceHostPort 1072, 1089  
setConfigDir 1524  
setConnected 1004  
setConnectionLimit 1525  
setConnectionTimeout 822  
setConnectionValidator 327  
setContentfType 786  
setCookieStr 587, 1011  
setCoreHandlerPoolSize 1073, 1090, 1490  
setCoreTransportPoolSize 1073, 1090, 1489  
setCurrentDvrTime 479  
setData 772, 775, 1119  
setDataBuffer 219  
setDataSize 1174  
setDataTC 1177, 1178  
setDatafType 1178  
setDebug 1450  
setDebugAppTimeout 303  
setDebugLog 86  
setDebugRTSPSession 1010  
setDefaultStreamingStore 494  
setDescribe 1003  
setDescription 749, 769, 772, 822, 1518  
setDirection 1138  
setDirecton 10  
setDomainName 1456  
setDuration 1308, 1332, 1335  
setDvrRecorder 1210  
setDvrRecorderId 1280  
setDvrRecorderList 300, 1206  
setDvrSessionInfo 591  
setDynamic 203  
setDynamicLogProperties 1074, 1091, 1502  
setEmbeddedFlag 780  
setEncMethod 1255  
setEncoding 694  
setEncryptions 380  
setEventHandler 1450  
setEventStr 1449  
setExt 1202  
setFastPlay 929  
setFastPlaySettings 349, 1192  
setField 1449  
setFileExtension 1322  
setFileIOPoolSize 1490  
setFilePath 656  
setFileTemplate 678  
setFileVersionDelegate 641, 656  
setFlags 766, 798  
setFlashVer 342  
setForceAMF0 950  
setForceMPEGTSOut 1061  
setForceRTSPInterleaved 1052  
setFps 1137  
setFrameCount 1432  
setFrameIdentifier 772  
setHandler 980  
setHasEncryption 507  
setHeader 539  
setHeaderSize 1204  
setHeadResponse 540  
setHeight 870  
setHost 972, 1038  
setHostType 974  
setHTTPIdent2Response 1460  
setHTTPIdentResponse 1459  
setHTTPOrigin 596  
setHTTPOriginMode 567  
setHTTPStreamerAdapter 582  
setHTTPStreamerItem 562  
setHTTPStreamerList 283  
setHTTPStreamerMaxPathLen 1507  
setHTTPStreamerRequestValidator 1507  
setHTTPStreamerSession 1146, 1207

setID 563  
setId 208  
setIdleCheckFrequency 1498  
setIdleFrequency 356, 1009  
setIdleHandler 1005  
setIdleMinimumWaitTime 1501  
setIdleWorkerCount 1498  
setIdStr 765, 797  
setIndex 1315  
setInitiateWOWZConnections 1076, 1095  
setInnerObj 204  
setIntData 155  
setIntHeader 539  
setIOPerformanceCounter 1011  
setIoPerformanceCounter 1088  
setIoSession 1015  
setIp 1003  
setIpAddress 584, 1456  
setIsPlaying 1173  
setKeepAliveTime 823  
setKeepAliveTimeout 1498  
setLanguage 785, 871  
setLastAccessed 1141  
setLastAuthenticateMethod 1002  
setLastClientId 1121  
setLastOperation 1121  
setLastRun 1450  
setLastSentAbsTimecode 212  
setLastValidateTime 360  
setLive 1055  
setLivePlaylist 622  
setLiveRepeaterCapabilities 364  
setLiveStreamDvrRecorderControl 299  
setLiveStreamingPacketizer 583  
setLiveStreamPacketizer 834, 922, 1207  
setLiveStreamPacketizerControl 289  
setLiveStreamPacketizerId 1290  
setLiveStreamPacketizerList 283, 364, 1205  
setLiveStreamRepeater 834, 1208  
setLiveStreamTranscoderControl 298  
setLiveStreamTranscoderItem 1301  
setLiveStreamTranscoderList 298, 364, 1206  
setLock 868, 876  
setLoggedConnect 1002  
setLongTimecode 212  
setMaximumPendingReadBytes 272, 1496  
setMaximumPendingWriteBytes 271, 1496  
setMaximumSetBufferTime 272, 1496  
setMaxRTCPWaitTime 1047  
setMaxStorageDirDepth 282  
setMediaCasterDef 806  
setMediaCasterHostPortConfig 828  
setMediaCasterId 805  
setMediaCasterItem 1223  
setMediaCasterPlay 1209  
setMediaCasterProcessorCount 828  
setMediacasterRTPRTSPRTPTransportMode 302  
setMediaCasterType 810  
setMediaCasterValidator 291  
setMediaList 876  
setMediaListProvider 302  
setMediaListSegment 868  
setMediaReaderItem 1145, 1151  
setMediaWriterItem 1251  
setMediaWriterType 668  
setMergeOnMetadata 1210  
setMessageBytes 948  
setMetaDataProvider 1203  
setMimeType 749  
setMode 1051  
setMoveFirstVideoFrameToZero 641, 658  
setMoveToNextIfLiveStreamMissing 1346  
setMPEGTSAudioBitrate 1061  
setMPEGTSAudioLanguage 1047  
setMPEGTSAudioPID 1048  
setMPEGTSOut 1054  
setMPEGTSProgramID 1048  
setMPEGTSVideoBitrate 1061  
setMPEGTSVideoPID 1048  
setMultiplier 1137  
setName 236, 259, 821, 862, 870, 975, 1107, 1120, 1132, 1175, 1236, 1516, 1524  
setNetConnection 1179  
setNetConnectionIdleFrequency 1497  
setNetConnectionProcessorCount 1491  
setNew 210  
setObjectEncoding 156, 160, 212, 362  
setOffset 557  
setOffsetToNextTag 780  
setOpen 1192

setOutHost 1050  
setOwnerIdentifier 775  
setPacketizeAudio 1291  
setPacketizeData 1292  
setPacketizeVideo 1291  
setPacketType 557  
setParent 1134, 1251  
setPersistent 1105, 1115, 1129  
setPictureData 749  
setPictureDataAsURL 749  
setPictureType 749  
setPingTimeout 271, 1495  
setPlay 1179  
setPlayClass 1517  
setPlayDuration 593, 871  
setPlayer 1188  
setPlayLogged 581  
setPlayStart 593, 871  
setPollingInterval 1343  
setPort 695, 1457  
setProcessorCount 1457  
setProperties 524, 527, 561, 1145, 1155, 1525  
setProperty 309, 821, 1106, 1107, 1129, 1130, 1517  
setPublishAudioCodecId 1208  
setPublishDataEvents 1327  
setPublishVideoCodecId 1208  
setQueryStr 586, 1006, 1201  
setRange 395  
setRealTimeStartTime 1308, 1332, 1335  
setReceiveAudio 1192  
setReceiveVideo 1193  
setReceiveVideoFPS 1193  
setReconnectWaitTime 809  
setRecord 1178  
setRecordAudio 1281  
setRecordData 640, 657, 1281  
setRecordingName 1282  
setRecordingStreamStore 494  
setRecordOnMetaData 674  
setRecordVideo 1281  
setRedirectSession 594, 1013  
setRedirectSessionBody 596  
setRedirectSessionCode 595, 1014  
setRedirectSessionContentType 596  
setRedirectSessionMessage 1014  
setRedirectSessionURL 595, 1014  
setReferrer 586, 1006  
setRemoteHost 694  
setRepeat 1312, 1342  
setRepeaterEdge 1291  
setRepeaterMediaCasterDef 566  
setRepeaterOriginUrl 272, 360, 925  
setRepeaterQueryString 273  
setRequestFilters 523, 530  
setResetPlayStream 1040  
setResponseCode 540  
setResyncAudioVideoOnSR 1042  
setRetAMFNumber 949  
setRsoStorageDir 275  
setRTPAVSyncMethod 279  
setRTPDestination 1059  
setRTPIdleFrequency 274, 1497  
setRTPIgnoreProfileLevelId 1060  
setRTPIgnoreSPropParameterSets 1061  
setRTPMaxRTCPWaitTime 279  
setRTPPlayAuthenticationMethod 278  
setRTPPublishAuthenticationMethod 278  
setRTPSession 315, 322, 984  
setRTPStream 1205  
setRTPStreamContext 1062  
setRTPWrapped 974  
setRTSP 1048  
setRTSPAlwaysUseSDPPorts 1059  
setRTSPBindIpAddress 294, 1056  
setRTSPConnectionAddressType 295, 1057  
setRTSPConnectionIpAddress 294, 1056  
setRTSPMaximumPendingWriteBytes 293, 1055  
setRTSPMaxPathLen 1508  
setRTSPOriginAddressType 295, 1057  
setRTSPOriginIpAddress 295, 1057  
setRTSPPlayRangeStart 1010  
setRTSPPlayRangeStop 1010  
setRTSPPull 1049  
setRTSPRequestValidator 1508  
setRTSPSessionDescription 1053  
setRTSPSessionName 1053  
setRTSPSessionTimeout 292, 1055  
setRTSPTunnelingSessionId 1010  
setSample 557  
setSDPData 984

setSDPLang 1060  
setSegmentDuration 642, 655  
setSegmentSize 642, 655  
setSendOnMetadata 1308, 1329, 1344  
setSendPlayStopLogEvent 1202  
setSendPublishStopLogEvent 1203  
setSendRecordStopLogEvent 1202  
setSendSDESEvents 1054  
setSeq 221  
setServer 1532  
setServerIp 584, 1005  
setServerPort 585, 1005  
setSession 1036  
setSessionId 579, 999  
setSessionProtocol 563, 584  
setSessionTimeout 581  
setSessionTracker 627  
setSessionType 583  
setSessionValid 1001  
setSharedObjectReadAccess 277, 356  
setSharedObjectWriteAccess 278, 356  
setShutdownClient 363, 1011  
setShutdownOnRelease 833  
setShuttingDown 1501  
setSize 208, 219, 557, 870  
setSlotValue 1130, 1131  
setSlotVersion 1120  
setSoVersion 1120  
setSpeed 1335  
setSrc 209, 220, 947, 1174  
setSSLConfig 1459  
setSslFactoryClass 1457  
setStartLiveOnPreviousBufferTime 1345  
setStartLiveOnPreviousKeyFrame 1345  
setStartOnKeyFrame 639, 657  
setStartOnPreviousBufferTime 1332  
setStartOnPreviousKeyFrame 1332  
setStartRecordingOnStartup 1283  
setStartStartupStreams 1505  
setStartTC 1138  
setStartTCOffset 1138  
setStopIfStreamMissing 1332  
setStorageDir 1108, 1116, 1133  
setStream 580, 805  
setStreamAudioSampleAccess 276, 358  
setStreamDomainProtectionActive 567  
setStreamExt 588, 833, 1043  
setStreamFileMapper 282  
setStreamKeyDir 274  
setStreamName 587, 1044, 1268, 1300  
setStreamNameAliasProvider 285  
setStreamNameLogging 1044  
setStreamPort 973  
setStreamPosition 589, 1155  
setStreamProperty 942  
setStreamQueryStr 1049  
setStreamReadAccess 276, 358  
setStreamRunning 810  
setStreamSessionId 1044  
setStreamSessionIp 1045  
setStreamSessionVersion 1045  
setStreamStorageDir 274  
setStreamTimeout 807  
setStreamType 260, 345, 820, 923, 1042, 1190, 1322  
setStreamTypeStr 567  
setStreamVersionHandler 495  
setStreamVideoSampleAccess 276, 357  
setStreamWriteAccess 277, 359  
setSuspended 1459  
setSwitchLog 1344  
setTarget 1449  
setTargetEncoding 160  
setTextEncoding 748, 769, 785, 791, 794  
setThreadContext 365  
setTimecode 209, 221, 788, 950  
setTimecodes 220  
setTimeOffsetBetweenItems 1345  
setTimeoutSession 581  
setTimesInMilliseconds 1344  
setTimeStampFormat 785  
setTrack 978  
setTranscodeResult 1211  
setTranscoderName 1300  
setTranscoderType 1302  
setTranscoderVODDestination 600  
setTranscoderVODIndex 597  
setTranscoderVODSession 597  
setTransportMode 1052  
setTTL 974, 981  
setType 129, 209, 220, 870, 950

setUDPMangedDeliveryCount 1060  
setUDPMangedDeliveryDelay 1060  
setUnpublishOnEnd 1346  
setUri 585, 1006  
setURL 772, 794  
setUserAgent 585, 1000  
setUserAgents 1072, 1089  
setUserHTTPHeader 567, 593  
setUserQueryStr 591  
setValid 831  
setValidateFMLEConnections 297, 365  
setValidationFrequency 271, 1495  
setValue 769, 788, 791  
setVersion 1105, 1129  
setVersionFile 640, 657, 1251  
setVHost 314, 322, 562, 579, 1000  
setVideoCodecId 869  
setVideoHost 973  
setVideoPort 972  
setVideoSize 1174  
setVideoTC 1177  
setVisited 1525  
setVODLastTimeTC 1058  
setVODPlayLen 1058  
setVODSpeed 1346  
setVODStartTimeTC 1058  
setVODTimedTextProviderList 284  
setVODTranscodeNGRP 597, 871  
setWaitForVideoKeyFrame 1251  
setWidth 870  
setWowzaAudioOnly 870  
setWowzSession 366  
SharedObject 1126, 1127  
SHARED\_OBJECT\_CMD\_CONNECT 1101  
SHARED\_OBJECT\_CMD\_CONNECTSUCCESS 1102  
SHARED\_OBJECT\_CMD\_DELETE 1102  
SHARED\_OBJECT\_CMD\_DISCONNECT 1101  
SHARED\_OBJECT\_CMD\_ERROR 1102  
SHARED\_OBJECT\_CMD\_SEND 1102  
SHARED\_OBJECT\_CMD\_SETVALUE 1101  
SHARED\_OBJECT\_STATUS\_CHANGE 1102  
SHARED\_OBJECT\_STATUS\_CLEAR 1102  
SHARED\_OBJECT\_STATUS\_DELETE 1102  
SHARED\_OBJECT\_STATUS\_SUCCESS 1102  
shortValue 168  
shouldDeleteArchivedStream 377, 514  
shouldDvrRecord 1286  
shouldLoadArchivedStream 377, 514  
shouldLoadStream 484  
shouldLoadStreamVersion 485  
shouldStartRecordingOnStartup 1283  
shutdown 235, 258, 504, 544, 580, 608, 615, 621, 627, 806, 832, 839, 964, 979, 1000, 1039, 1176, 1234, 1279, 1289, 1299, 1487, 1532  
shutdownAppInstance 239  
shutdownApplication 1502  
shutdownClient 258, 344, 997  
shutdownRTPSession 969  
shutdownSession 562  
shutdownStream 846  
sinfo 1259  
size 140, 150, 175, 195, 1104, 1114, 1127, 1201, 1237, 1458, 1462  
skipByte 130  
sloppyGetTrack 1035  
SMIL\_PARAM\_IS\_WOWZA\_CAPTION\_STREAM 1415  
SMIL\_PARAM\_WOWZA\_CAPTION\_INGEST\_TYPE 1414  
SOURCE\_TYPE\_3GPP 1397  
SOURCE\_TYPE\_AMF 1397  
SOURCE\_TYPE\_SCC 1398  
SOURCE\_TYPE\_SRT 1397  
SOURCE\_TYPE\_TTML 1397  
SOURCE\_TYPE\_WEBVTT 1398  
SPLIT\_ON\_DISCONTINUITY\_ALWAYS 638  
SPLIT\_ON\_DISCONTINUITY\_DEFAULT 638  
SPLIT\_ON\_DISCONTINUITY\_NEVER 638  
SPLIT\_TYPE\_BY\_DURATION 638  
SPLIT\_TYPE\_BY\_SCHEDULE 637  
SPLIT\_TYPE\_BY\_SIZE 637  
SPLIT\_TYPE\_NONE 637  
splitCookie 74  
splitNow 653  
splitOnTcDiscontinuity 654  
splitPragmas 73  
splitQueryStr 73  
splitRecordingNow 641, 658, 669  
splitType 653  
stackTraceToSingleLineString 45  
stackTraceToString 45  
stampToString 98  
stampToStringNoUnits 98



start 104, 1085, 1448  
START\_TIME\_TAG 677  
startApplicationInstance 1503  
startAudioData 1324  
startAudioPacket 1205  
startChunk 475, 602  
startCommandInterface 1069, 1086  
startDataData 1326  
startDataPacket 1205  
startMediaCasterStream 290  
startPlay 1237  
startPlayback 1154  
startPublishing 1199  
startRecording 496, 508, 638, 639, 659, 664, 668, 669, 673, 674, 1281  
startRecordingSegmentByDuration 639, 660, 664, 668, 673  
startRecordingSegmentBySchedule 639, 660, 664, 668, 673  
startRecordingSegmentBySize 639, 660, 664, 668, 673  
startRTPPull 1437, 1438  
startServer 1086  
startStartupStreams 1505  
startStream 836, 1279, 1290  
startsWith 39  
startVHost 1070, 1087  
startVHosts 1070, 1087  
startVideoData 1324  
startVideoPacket 1205  
STAT\_connect\_application\_not\_available 730  
STAT\_connect\_application\_not\_found 731  
STAT\_connect\_bad\_gateway 732  
STAT\_connect\_internal\_error 731  
STAT\_connect\_license\_limit 731  
STAT\_connect\_pending\_wating 730  
STAT\_connect\_redirect 731  
STAT\_connect\_rejected\_by\_application 731  
STAT\_connect\_rejected\_by\_module 731  
STAT\_connect\_resource\_limit 731  
STAT\_connect\_service\_unavailable 732  
STAT\_connect\_successful 730  
STAT\_connect\_unknown\_protocol 731  
STAT\_general\_internal\_error 734  
STAT\_general\_successful 734  
STAT\_play\_bad\_request 732  
STAT\_play\_internal\_error 733  
STAT\_play\_rejected\_by\_application 732  
STAT\_play\_rejected\_by\_module 732  
STAT\_play\_stream\_not\_found 732  
STAT\_play\_successful 732  
STAT\_play\_unsupported\_media\_type 732  
STAT\_publish\_bad\_request 733  
STAT\_publish\_in\_use 733  
STAT\_publish\_internal\_error 733  
STAT\_publish\_rejected\_by\_application 733  
STAT\_publish\_successful 733  
STAT\_publish\_unsupported\_media\_type 733  
STAT\_stop\_client\_disconnect 733  
STAT\_stop\_successful 733  
stateChange 500  
statusCodeToStr 75  
stop 1449  
stopAdminAgent 1075, 1085  
stopCommandInterface 1070, 1086  
stopMediaCasterStream 290  
stopName 1176, 1236  
stopPublishing 1199  
stopRecording 496, 508, 639, 660, 665, 669, 674, 1282  
stopRTPPull 1437  
stopServer 1085  
stopStartupStreams 1505  
stopStream 836  
stopVHost 1070, 1086  
stopVHosts 1070, 1086  
storeChunks 498, 509  
storeOnMetadata 498, 509  
Stream 1338  
stream 652  
STREAM\_NAME\_TAG 677  
streamCodecToString 58  
streamExists 836, 1038  
STREAMINFO\_SESSIONATTRIBUTES 1033  
STREAMINFO\_SESSIONBANDWIDTH 1033  
STREAMINFO\_SESSIONCONNECTIONDATA 1033  
STREAMINFO\_SESSIONEMAILADDRESS 1032  
STREAMINFO\_SESSIONINFORMATION 1032  
STREAMINFO\_SESSIONNAME 1032  
STREAMINFO\_SESSIONPHONENUMBER 1032  
STREAMINFO\_SESSIONPORIGIN 1032  
STREAMINFO\_SESSIONPROTOCOLVERSION 1032  
STREAMINFO\_SESSIONREPEATTIMES 1033  
STREAMINFO\_SESSIONTIMEZONES 1033

STREAMINFO\_SESSIONTIMING 1033  
STREAMINFO\_SESSIONURI 1032  
StreamItem 1516  
streamLicenses 1264  
StreamList 1519  
streamLock 1264  
streamMonitorAudioStartTimeout 937  
streamMonitorAudioTCNegTolerance 936  
streamMonitorAudioTCPosTolerance 936  
streamMonitorAudioTCToleranceEnable 936  
streamMonitorAudioTimeout 937  
streamMonitorAVSyncTolerance 937  
streamMonitorAVSyncToleranceEnable 937  
streamMonitorDataTCNegTolerance 936  
streamMonitorDataTCPosTolerance 936  
streamMonitorDataTCToleranceEnable 936  
streamMonitorDebug 937  
streamMonitorResetNameGroups 937  
streamMonitorStreamStartTimeout 935  
streamMonitorStreamTimeout 935  
streamMonitorVideoStartTimeout 937  
streamMonitorVideoTCNegTolerance 936  
streamMonitorVideoTCPosTolerance 936  
streamMonitorVideoTCToleranceEnable 936  
streamMonitorVideoTimeout 937  
streamNames 1264  
streamNamesLock 1264  
streamNameToGroup 1264  
streamNameToValidFilename 50  
streamNotifier 652  
streamPacketizers 997  
streams 993, 1264  
streamsOrder 993  
streamSrcToMediaCaster 842  
STREAMTIMEOUTREASON\_GOOD 803  
STREAMTIMEOUTREASON\_MISSING 804  
STREAMTIMEOUTREASON\_NORTSPSESSION 803  
STREAMTIMEOUTREASON\_NOSESSION 803  
STREAMTIMEOUTREASON\_NOSTREAM 803  
STREAMTIMEOUTREASON\_NOTIMEOUT 803  
STREAMTIMEOUTREASON\_NOURL 803  
STREAMTIMEOUTREASON\_RECONNECTRUNNING 803  
STREAMTIMEOUTREASON\_UNKNOWN 802  
streamToFileForRead 1220  
streamToFileForWrite 1221  
streamToIndex 1268  
StreamUtils 1441  
stringToMilliseconds 98  
StringUtils 97  
suspendAllHostPorts 1502  
suspendAllVHosts 1075, 1087  
suspendCommandInterface 1086  
suspendEncoding 29  
suspendServer 1075, 1087  
switchName 1175, 1236  
switchPlay 1237  
switchSetupToMPEGTS 1051  
SystemUtils 101

## T

TAG\_APIC 757  
TAG\_COMM 764  
TAG\_LINK 757  
TAG\_PRIV 757  
TAG\_RBUF 757  
TAG\_SYLT 757  
TAG\_TALB 757  
TAG\_TBPM 758  
TAG\_TCOM 758  
TAG\_TCON 758  
TAG\_TCOP 758  
TAG\_TDEN 758  
TAG\_TDLY 758  
TAG\_TDOR 758  
TAG\_TDRC 758  
TAG\_TDRL 759  
TAG\_TDTG 759  
TAG\_TENC 759  
TAG\_TEXT 759  
TAG\_TFLT 759  
TAG\_TIPL 759  
TAG\_TIT1 759  
TAG\_TIT2 759  
TAG\_TIT3 759  
TAG\_TKEY 760  
TAG\_TLAN 760  
TAG\_TLEN 760  
TAG\_TMCL 760

TAG\_TMED 760  
TAG\_TMOO 760  
TAG\_TOAL 760  
TAG\_TOFN 760  
TAG\_TOLY 761  
TAG\_TOPE 761  
TAG\_TOWN 761  
TAG\_TPE1 761  
TAG\_TPE2 761  
TAG\_TPE3 761  
TAG\_TPE4 761  
TAG\_TPOS 761  
TAG\_TPRO 762  
TAG\_TPUB 762  
TAG\_TRCK 762  
TAG\_TRSN 762  
TAG\_TRSO 762  
TAG\_TSOA 762  
TAG\_TSOP 762  
TAG\_TSOT 762  
TAG\_TSRC 762  
TAG\_TSSE 763  
TAG\_TSST 763  
TAG\_TXXX 764  
TAG\_UNKN 757  
TAG\_WCOM 763  
TAG\_WCOP 763  
TAG\_WOAF 763  
TAG\_WOAR 763  
TAG\_WOAS 763  
TAG\_WORS 764  
TAG\_WPAY 764  
TAG\_WPUB 764  
TAG\_WXXX 764  
TAGS\_TEXTINFORMATION 763  
TEMP\_CONSOLE\_APPENDER\_NAME 683  
TEMP\_LIST\_APPENDER\_NAME 683  
terminate 1522  
testFlashVersion 361  
testNextByte 129  
TEXTENCODING\_ISO\_8859\_1 756  
TEXTENCODING\_UTF16 756  
TEXTENCODING\_UTF16BE 756  
TEXTENCODING\_UTF8 757  
ThreadPool 1521  
TIME\_MAP\_TYPE 462  
timeCreated 995  
TIMED\_TEXT\_TYPE\_CAPTION 1397  
timeReset 483  
TIMESTAMP\_RULE\_FORMAT 682  
TIMESTAMPFORMAT\_MILLISECONDS 784  
TIMESTAMPFORMAT\_MPEG 784  
toArray 151  
toByteBuffer 151  
toDvr 518  
toHex 43  
toLong 44  
toNTPTIME 102  
toSMILString 861, 867, 875  
toString 147, 153, 169, 183, 187, 199, 209, 220, 310, 381, 383,  
396, 399, 402, 404, 823, 860, 867, 874, 971, 1315, 1457, 1458,  
1518, 1525  
toStringList 99  
totalIOPerformance2Last 995  
totalIOPerformanceLast 995  
touch 292, 344, 579, 1000, 1056, 1142, 1279, 1291  
touchApplicationInstance 1502, 1503  
toValidFilename 50  
trait 194  
TRANSCODERTYPE\_LIVE 1298  
TRANSCODERTYPE\_VOD 1298  
transportFindBestMatch 1054  
traverseDirectory 51  
triggerAMF3Switch 134  
trim 1194, 1259  
trimTrailingZero 765  
truncatePacket 219  
type 129, 389, 866  
  
U  
  
UDPAppender 693  
unbind 979  
unbindAllHostPorts 1502  
unbindAllVHosts 1075, 1087  
uncacheRTPStream 967  
unlock 1110, 1134  
unlockRepeaterStreams 1038  
unpublish 1323  
unregisterCallback 1194

unregisterLiveStreamTranscoder 1094  
unregisterOnPlayStatus 1195  
unregisterOnStatus 1195  
unregisterPlayer 806, 832, 843  
updateIOPerformance 1087  
updateLoggingDuration 1089, 1201, 1494  
updateLoggingValues 545, 584, 609, 616, 622, 1006, 1201, 1237  
updateOnCuePointTimecode 69  
updateSDPDestination 1436  
uri 996  
URL\_SAFE 18  
urlToId 107  
URLUtils 106  
userAgent 994  
userExists 321  
useSimpleFileVersionNaming 654  
UTC\_TIME 455  
utcTime 389  
utcToDvr 518  
UTF8\_BRITISH\_POUND 1385  
UTF8\_BULLET 1362  
UTF8\_CENTS 1385  
UTF8\_CLOSING\_DOUBLE\_QUOTE 1362  
UTF8\_CLOSING\_GUILLEMETS 1362  
UTF8\_CONNECTING\_VERTICAL\_BAR 1362  
UTF8\_COPYRIGHT 1362  
UTF8\_CURRENCY 1362  
UTF8\_DASH 1377  
UTF8\_DEGREE 1362  
UTF8\_DOUBLEQUOTE 1377  
UTF8\_EM\_DASH 1362  
UTF8\_EXCLAMATION 1377  
UTF8\_GREATERTHAN 1378  
UTF8\_INVERTED\_EXCLAMATION 1363  
UTF8\_LEFT\_SINGLE\_QUOTATION 1363  
UTF8\_LEFTPAREN 1377  
UTF8\_LESSTHAN 1377  
UTF8\_LOWER\_A 1378  
UTF8\_LOWER\_A\_WITH\_CIRCUMFLEX 1384  
UTF8\_LOWER\_A\_WITH\_DIAERESIS 1363  
UTF8\_LOWER\_A\_WITH\_GRAVE 1385  
UTF8\_LOWER\_A\_WITH\_RING 1364  
UTF8\_LOWER\_A\_WITH\_TILDE 1364  
UTF8\_LOWER\_B 1378  
UTF8\_LOWER\_C 1378  
UTF8\_LOWER\_D 1378  
UTF8\_LOWER\_E 1378  
UTF8\_LOWER\_E\_WITH\_CIRCUMFLEX 1384  
UTF8\_LOWER\_E\_WITH\_DIAERESIS 1364  
UTF8\_LOWER\_E\_WITH\_GRAVE 1385  
UTF8\_LOWER\_F 1379  
UTF8\_LOWER\_G 1379  
UTF8\_LOWER\_H 1379  
UTF8\_LOWER\_I 1379  
UTF8\_LOWER\_I\_WITH\_CIRCUMFLEX 1384  
UTF8\_LOWER\_I\_WITH\_DIAERESIS 1364  
UTF8\_LOWER\_I\_WITH\_GRAVE 1364  
UTF8\_LOWER\_J 1379  
UTF8\_LOWER\_K 1379  
UTF8\_LOWER\_L 1379  
UTF8\_LOWER\_M 1379  
UTF8\_LOWER\_N 1380  
UTF8\_LOWER\_O 1380  
UTF8\_LOWER\_O\_WITH\_CIRCUMFLEX 1385  
UTF8\_LOWER\_O\_WITH\_DIAERESIS 1364  
UTF8\_LOWER\_O\_WITH\_GRAVE 1364  
UTF8\_LOWER\_O\_WITH\_STROKE 1364  
UTF8\_LOWER\_O\_WITH\_TILDE 1365  
UTF8\_LOWER\_P 1380  
UTF8\_LOWER\_Q 1380  
UTF8\_LOWER\_R 1380  
UTF8\_LOWER\_S 1380  
UTF8\_LOWER\_T 1380  
UTF8\_LOWER\_U 1380  
UTF8\_LOWER\_U\_WITH\_CIRCUMFLEX 1385  
UTF8\_LOWER\_U\_WITH\_DIAERESIS 1365  
UTF8\_LOWER\_U\_WITH\_GRAVE 1365  
UTF8\_LOWER\_V 1380  
UTF8\_LOWER\_W 1381  
UTF8\_LOWER\_X 1381  
UTF8\_LOWER\_Y 1381  
UTF8\_LOWER\_Z 1381  
UTF8\_MINUSHYPHEN 1378  
UTF8\_MUSICAL\_NOTE 1385  
UTF8\_NBSP 1385  
UTF8\_NOTMATCH 1376  
UTF8\_ONE\_HALF 1386  
UTF8\_OPENING\_DOUBLE\_QUOTE 1363  
UTF8\_OPENING\_GUILLEMETS 1363  
UTF8\_PERIOD 1376

UTF8\_PIPE 1378  
UTF8\_QUESTION 1377  
UTF8\_REGISTERED\_MARK 1363  
UTF8\_REVERSE\_QUERY 1386  
UTF8\_RIGHTPAREN 1377  
UTF8\_SERVICE\_MARK 1363  
UTF8\_SINGLEQUOTE 1376  
UTF8\_SPACE 1377  
UTF8\_TRADEMARK 1386  
UTF8\_UNDERSCORE 1377  
UTF8\_UPPER\_A 1381  
UTF8\_UPPER\_A\_WITH\_ACUTE 1365  
UTF8\_UPPER\_A\_WITH\_CURCUMFLEX 1365  
UTF8\_UPPER\_A\_WITH\_DIAERESIS 1365  
UTF8\_UPPER\_A\_WITH\_GRAVE 1365  
UTF8\_UPPER\_A\_WITH\_RING 1365  
UTF8\_UPPER\_A\_WITH\_TILDE 1365  
UTF8\_UPPER\_B 1381  
UTF8\_UPPER\_C 1381  
UTF8\_UPPER\_C\_WITH\_CEDILLA 1366  
UTF8\_UPPER\_D 1381  
UTF8\_UPPER\_E 1382  
UTF8\_UPPER\_E\_WITH\_ACUTE 1366  
UTF8\_UPPER\_E\_WITH\_CIRCUMFLEX 1366  
UTF8\_UPPER\_E\_WITH\_DIAERESIS 1366  
UTF8\_UPPER\_E\_WITH\_GRAVE 1366  
UTF8\_UPPER\_F 1382  
UTF8\_UPPER\_G 1382  
UTF8\_UPPER\_H 1382  
UTF8\_UPPER\_I 1382  
UTF8\_UPPER\_I\_WITH\_CIRCUMFLEX 1366  
UTF8\_UPPER\_I\_WITH\_DIAERESIS 1366  
UTF8\_UPPER\_I\_WITH\_GRAVE 1366  
UTF8\_UPPER\_I\_WITH\_TILDE 1367  
UTF8\_UPPER\_J 1382  
UTF8\_UPPER\_K 1382  
UTF8\_UPPER\_L 1382  
UTF8\_UPPER\_M 1383  
UTF8\_UPPER\_N 1383  
UTF8\_UPPER\_O 1383  
UTF8\_UPPER\_O\_WITH\_ACUTE 1367  
UTF8\_UPPER\_O\_WITH\_CIRCUMFLEX 1367  
UTF8\_UPPER\_O\_WITH\_DIAERESIS 1367  
UTF8\_UPPER\_O\_WITH\_GRAVE 1367  
UTF8\_UPPER\_O\_WITH\_STROKE 1367  
UTF8\_UPPER\_O\_WITH\_TILDE 1367  
UTF8\_UPPER\_P 1383  
UTF8\_UPPER\_Q 1383  
UTF8\_UPPER\_R 1383  
UTF8\_UPPER\_S 1383  
UTF8\_UPPER\_T 1383  
UTF8\_UPPER\_U 1383  
UTF8\_UPPER\_U\_WITH\_ACUTE 1367  
UTF8\_UPPER\_U\_WITH\_CIRCUMFLEX 1368  
UTF8\_UPPER\_U\_WITH\_DIAERESIS 1368  
UTF8\_UPPER\_U\_WITH\_GRAVE 1368  
UTF8\_UPPER\_V 1384  
UTF8\_UPPER\_W 1384  
UTF8\_UPPER\_X 1384  
UTF8\_UPPER\_Y 1384  
UTF8\_UPPER\_Z 1384  
UTF8\_YEN 1363  
UTF8MAP 1386  
UTF8MAP\_INDEX\_OFFSET 1386

V

validateHTTPStreamerRequest 1509  
validateNewConnection 327  
validateRTSPRequest 1513  
validStreamDomainToString 590  
valueOf 98, 455  
values 455  
versionFile 51  
vhost 314, 993  
VHOST\_DEFAULT 1476  
VHostItem 1524  
VHostList 1528  
VHostSingleton 1531  
videoCodecId 866  
videoCodecStringToId 59  
videoCodecToMetaDataString 58  
videoCodecToString 59  
videoCodecTypeToString 93  
videoPacketizers 997  
VIDEOSAMPLE\_ACCESS\_ALL 340  
VIDEOSAMPLE\_ACCESS\_NONE 341  
VIDEOSAMPLEACCESS 1172  
vodTranscodeNGRP 867

## W

warn 705, 706  
WEEKDAY 1448  
width 867  
WMSLogger 699  
WMSLoggerFactory 708  
WMSLoggerIDs 737  
WMSProperties 308  
work 640, 661, 665, 669, 674  
worker 652  
workStop 640, 660, 665, 669, 674  
wowzaAudioOnly 867  
WOWZDEBUGHEADERSIZE 207  
wrap 151  
write 29, 950, 951  
WRITE\_ACCESS\_ALL 341  
WRITE\_ACCESS\_NONE 341  
WRITEACCESS 1126, 1172  
writeAppConfig 240  
writeAppInstConfig 289  
writeChunk 63  
writeCodecConfig 1439  
writeConfig 1076, 1093  
writeDeleteError 1109, 1131  
writeDuration 66  
writeError 1131  
writeGeneratedKeyFrame 1153  
writeHeader 62  
writeLock 652  
writePackets 65, 66, 1152, 1153, 1250  
writeSetValueError 1108, 1131  
writeShortHeader 62  
writeString 161  
writeVHostConfig 1506  
writeXMLConfig 1093

## X

XMLUtils 110

## Y

YEAR 1448