



Wowza Media Server® 3

Server Side API

Wowza Media Server 3: Server Side API



Copyright © 2006 – 2011 Wowza Media Systems, Inc.
<http://www.wowza.com>

This document is for informational purposes only and in no way shall be interpreted or construed to create any warranties of any kind, either express or implied, regarding the information contained herein.

Third Party Information

This document contains links to third party websites that are not under the control of Wowza Media Systems, Inc. (“Wowza”) and Wowza is not responsible for the content on any linked site. If you access a third party website mentioned in this document, then you do so at your own risk. Wowza provides these links only as a convenience, and the inclusion of any link does not imply that Wowza endorses or accepts any responsibility for the content on third party sites.

This document also refers to other third party software that is not licensed, sold, distributed or otherwise endorsed by Wowza. Please ensure that any and all use of Wowza® software and third party software is properly licensed.

Trademarks

Wowza, Wowza Media Systems, Wowza Media Server and related logos are either registered trademarks or trademarks of Wowza Media System, Inc. in the United States and/or other countries.

Adobe and Flash are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Microsoft and Silverlight are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

QuickTime, iPhone, iPad and iPod are either registered trademarks or trademarks of Apple, Inc. in the United States and/or other countries.

Other product names, logos, designs, titles, words or phrases mentioned may be third party registered trademarks or trademarks in the United States and/or other countries.

Third party trademarks are used solely to identify and describe third party products as being compatible with Wowza products. Wowza is in no way sponsored, endorsed by or otherwise affiliated with any such third party trademark owners.

Third Party Copyright Notices

Log4j and Mina: Copyright © 2006, The Apache Software Foundation

Java Service Wrapper: Copyright © 1999, 2006, Tanuki Software, Inc.

Silver Egg Technology: Copyright © 2001, Silver Egg Technology

Java ID3 Tag Library and JLayer 1.0 (classic): Copyright © 1991, 1999, Free Software Foundation, Inc.

Bouncy Castle Crypto API: Copyright © 2000 – 2008, The Legion Of The Bouncy Castle

Apache Commons Lang libraries and Modeler libraries: Copyright © 2001-2008, The Apache Software Foundation

WebM VP8 Codec libraries: Copyright © 2010, Google Inc. All rights reserved.

Vorbis/Ogg libraries: Copyright © 2011, Xiph.org Foundation

Libgcc s-4 library and Libstdc++ library: Copyright © 2011, Free Software Foundation, Inc.

Speex Codec: Copyright © 2002-2003, Jean-Marc Valin/Xiph.org Foundation

Package

com.wowza.io

com.wowza.io Interface IRandomAccessReader

public interface **IRandomAccessReader**
extends

Field Summary

public static final	<u>FORWARD</u> Value: 1
public static final	<u>REVERSE</u> Value: -1

Method Summary

void	<u>close()</u> Close the media asset
boolean	<u>exists()</u> Does the media asset exist
String	<u>getBasePath()</u> Get the basePath for the random access reader
int	<u>getDirecton()</u> Get the current direction hint for the random access reader.
long	<u>getFilePointer()</u> Get the current byte location in the media asset
String	<u>getMediaExtension()</u> Get the media extension
String	<u>getMediaName()</u> Get the media name
String	<u>getPath()</u> Get the unique path to the media asset item
void	<u>init(IApplicationInstance appInstance, IMediaStream stream, String basePath, String mediaName, String mediaExtension)</u> Intialize RandomAccessReader
boolean	<u>isOpen()</u> Is the media asset open
long	<u>lastModified()</u> Return the lastModified date (same format as File.lastModified)
long	<u>length()</u> Get the media asset length in bytes

void	<code>open()</code> Open the media asset
int	<code>read(byte[] buf, int off, int size)</code> Read bytes from the media asset
void	<code>seek(long pos)</code> Seek to a position in the media asset
void	<code>setDirecton(int directon)</code> Set the current direction hint

Fields

FORWARD

```
public static final int FORWARD
```

Constant value: **1**

REVERSE

```
public static final int REVERSE
```

Constant value: **-1**

Methods

init

```
public void init(IApplicationInstance appInstance,
IMediaStream stream,
String basePath,
String mediaName,
String mediaExtension)
```

Intialize RandomAccessReader

Parameters:

appInstance - application instance
stream - parent stream if one exists
basePath - basePath for IApplicationInstance
mediaName - media name
mediaExtension - media extension from mediaReaders

open

```
public void open()
throws java.io.IOException
```

Open the media asset

Throws:

IOException

close

```
public void close()  
    throws java.io.IOException
```

Close the media asset

Throws:

IOException

isOpen

```
public boolean isOpen()
```

Is the media asset open

Returns:

true if media asset is open

getFilePointer

```
public long getFilePointer()
```

Get the current byte location in the media asset

Returns:

current byte location in the media asset

seek

```
public void seek(long pos)
```

Seek to a position in the media asset

Parameters:

pos - position to seek to

read

```
public int read(byte[] buf,  
               int off,  
               int size)
```

Read bytes from the media asset

Parameters:

buf - buffer to fill

off - offset in buffer

size - size of block to read

Returns:

number of bytes read, -1 if failure

getDirecton

```
public int getDirecton()
```

(continued on next page)

(continued from last page)

Get the current direction hint for the random access reader. The underlying system will call `setDirection` to hint at the current direction the media assets is being read.

Returns:

current direction hint for the random access reader

setDirecton

```
public void setDirecton(int directon)
```

Set the current direction hint

Parameters:

`directon` - current direction hint for the random access reader

getBasePath

```
public String getBasePath()
```

Get the `basePath` for the random access reader

Returns:

`basePath` for the random access reader

getMediaName

```
public String getMediaName()
```

Get the media name

Returns:

media name

getMediaExtension

```
public String getMediaExtension()
```

Get the media extension

Returns:

media extension

exists

```
public boolean exists()
```

Does the media asset exist

Returns:

true if media assets exists

lastModified

```
public long lastModified()
```

Return the `lastModified` date (same format as `File.lastModified`)

Returns:

`lastModified` date (same format as `File.lastModified`)

length

```
public long length()
```

Get the media asset length in bytes

Returns:

media asset length in bytes

getPath

```
public String getPath()
```

Get the unique path to the media asset item

Returns:

unique path to the media asset item

Package

com.wowza.util

com.wowza.util Class AMFUtils

java.lang.Object

└─com.wowza.util.AMFUtils

public class **AMFUtils**
extends Object

Utilities for the conversion between Java and AMF

Constructor Summary

public [AMFUtils\(\)](#)

Method Summary

static [AMFData\[\]](#) [convertParams](#)(Object[] params)
Converts an array of Java native data values and class to AMF data types.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AMFUtils

public **AMFUtils**()

Methods

convertParams

public static [AMFData\[\]](#) **convertParams**(Object[] params)

(continued from last page)

Converts an array of Java native data values and class to AMF data types. It will box primitive data types into wrapper classes. Supported input data types are:

- null
- Double
- Float
- Long
- Integer
- Short
- Byte
- Number
- Date
- Boolean
- String
- StringBuffer
- byte[] - assumed to be raw AMFData
- ByteBuffer - assumed to be raw AMFData
- AMFData
- AMFDataMixedArray
- AMFDataArray
- AMFDataItem
- AMFDataList
- AMFDataObj

Parameters:

params - Array of Java

Returns:

Array of AMFData[] objects

com.wowza.util Class Base64

```
java.lang.Object
|
+-com.wowza.util.Base64
```

public class **Base64**
extends Object

Encodes and decodes to and from Base64 notation.

Homepage: <http://iharder.net/base64>.

Change Log:

- v2.2.1 - Fixed bug using URL_SAFE and ORDERED encodings. Fixed bug when using very small files (~< 40 bytes).
- v2.2 - Added some helper methods for encoding/decoding directly from one file to the next. Also added a main() method to support command line encoding/decoding from one file to the next. Also added these Base64 dialects:
 1. The default is RFC3548 format.
 2. Calling Base64.setFormat(Base64.BASE64_FORMAT.URLSAFE_FORMAT) generates URL and file name friendly format as described in Section 4 of RFC3548. <http://www.faqs.org/rfcs/rfc3548.html>
 3. Calling Base64.setFormat(Base64.BASE64_FORMAT.ORDERED_FORMAT) generates URL and file name friendly format that preserves lexical ordering as described in <http://www.faqs.org/qa/rfcc-1940.html>
 Special thanks to Jim Kellerman at <http://www.powerset.com/> for contributing the new Base64 dialects.
- v2.1 - Cleaned up javadoc comments and unused variables and methods. Added some convenience methods for reading and writing to and from files.
- v2.0.2 - Now specifies UTF-8 encoding in places where the code fails on systems with other encodings (like EBCDIC).
- v2.0.1 - Fixed an error when decoding a single byte, that is, when the encoded data was a single byte.
- v2.0 - I got rid of methods that used booleans to set options. Now everything is more consolidated and cleaner. The code now detects when data that's being decoded is gzip-compressed and will decompress it automatically. Generally things are cleaner. You'll probably have to change some method calls that you were making to support the new options format (ints that you "OR" together).
- v1.5.1 - Fixed bug when decompressing and decoding to a byte[] using decode(String s, boolean gzipCompressed). Added the ability to "suspend" encoding in the Output Stream so you can turn on and off the encoding if you need to embed base64 data in an otherwise "normal" stream (like an XML file).
- v1.5 - Output stream pases on flush() command but doesn't do anything itself. This helps when using GZIP streams. Added the ability to GZip-compress objects before encoding them.
- v1.4 - Added helper methods to read/write files.
- v1.3.6 - Fixed OutputStream.flush() so that 'position' is reset.
- v1.3.5 - Added flag to turn on and off line breaks. Fixed bug in input stream where last buffer being read, if not completely full, was not returned.
- v1.3.4 - Fixed when "improperly padded stream" error was thrown at the wrong time.
- v1.3.3 - Fixed I/O streams which were totally messed up.

I am placing this code in the Public Domain. Do with it as you will. This software comes with no guarantees or warranties but with plenty of well-wishing instead! Please visit <http://iharder.net/base64> periodically to check for updates or to contribute improvements.

Nested Class Summary

class	Base64.InputStream Base64.InputStream
class	Base64.OutputStream Base64.OutputStream

Field Summary

<code>public static final</code>	<u>DECODE</u> Specify decoding. Value: 0
<code>public static final</code>	<u>DONT_BREAK_LINES</u> Don't break lines when encoding (violates strict Base64 specification) Value: 8
<code>public static final</code>	<u>ENCODE</u> Specify encoding. Value: 1
<code>public static final</code>	<u>GZIP</u> Specify that data should be gzip-compressed. Value: 2
<code>public static final</code>	<u>NO_OPTIONS</u> No options specified. Value: 0
<code>public static final</code>	<u>ORDERED</u> Encode using the special "ordered" dialect of Base64 described here: http://www.faqs.org/qa/rfcc-1940.html . Value: 32
<code>public static final</code>	<u>URL_SAFE</u> Encode using Base64-like encoding that is URL- and Filename-safe as described in Section 4 of RFC3548: http://www.faqs.org/rfcs/rfc3548.html . Value: 16

Method Summary

<code>static byte[]</code>	<u>decode</u> (byte[] source, int off, int len, int options) Very low-level access to decoding ASCII characters in the form of a byte array.
<code>static byte[]</code>	<u>decode</u> (String s) Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.
<code>static byte[]</code>	<u>decode</u> (String s, int options) Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.
<code>static void</code>	<u>decodeFileToFile</u> (String infile, String outfile) Reads infile and decodes it to outfile.
<code>static byte[]</code>	<u>decodeFromFile</u> (String filename) Convenience method for reading a base64-encoded file and decoding it.
<code>static boolean</code>	<u>decodeToFile</u> (String dataToDecode, String filename) Convenience method for decoding data to a file.
<code>static Object</code>	<u>decodeToObject</u> (String encodedObject) Attempts to decode Base64 data and deserialize a Java Object within.

static String	<code>encodeBytes</code> (byte[] source) Encodes a byte array into Base64 notation.
static String	<code>encodeBytes</code> (byte[] source, int options) Encodes a byte array into Base64 notation.
static String	<code>encodeBytes</code> (byte[] source, int off, int len) Encodes a byte array into Base64 notation.
static String	<code>encodeBytes</code> (byte[] source, int off, int len, int options) Encodes a byte array into Base64 notation.
static void	<code>encodeFileToFile</code> (String infile, String outfile) Reads infile and encodes it to outfile.
static String	<code>encodeFromFile</code> (String filename) Convenience method for reading a binary file and base64-encoding it.
static String	<code>encodeObject</code> (java.io.Serializable serializableObject) Serializes an object and returns the Base64-encoded version of that serialized object.
static String	<code>encodeObject</code> (java.io.Serializable serializableObject, int options) Serializes an object and returns the Base64-encoded version of that serialized object.
static boolean	<code>encodeToFile</code> (byte[] dataToEncode, String filename) Convenience method for encoding data to a file.
static void	<code>main</code> (String[] args) Encodes or decodes two files from the command line; feel free to delete this method (in fact you probably should) if you're embedding this code into a larger program.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

NO_OPTIONS

```
public static final int NO_OPTIONS
```

No options specified. Value is zero.
Constant value: **0**

ENCODE

```
public static final int ENCODE
```

Specify encoding.
Constant value: **1**

DECODE

```
public static final int DECODE
```

Specify decoding.

(continued from last page)

Constant value: **0**

GZIP

```
public static final int GZIP
```

Specify that data should be gzip-compressed.
Constant value: **2**

DONT_BREAK_LINES

```
public static final int DONT_BREAK_LINES
```

Don't break lines when encoding (violates strict Base64 specification)
Constant value: **8**

URL_SAFE

```
public static final int URL_SAFE
```

Encode using Base64-like encoding that is URL- and Filename-safe as described in Section 4 of RFC3548: <http://www.faqs.org/rfcs/rfc3548.html>. It is important to note that data encoded this way is *not* officially valid Base64, or at the very least should not be called Base64 without also specifying that it was encoded using the URL- and Filename-safe dialect.
Constant value: **16**

ORDERED

```
public static final int ORDERED
```

Encode using the special "ordered" dialect of Base64 described here: <http://www.faqs.org/qa/rfc-1940.html>.
Constant value: **32**

Methods

main

```
public final static void main(String[] args)
```

Encodes or decodes two files from the command line; **feel free to delete this method** (in fact you probably should) if you're embedding this code into a larger program.

encodeObject

```
public static String encodeObject(java.io.Serializable serializableObject)
```

Serializes an object and returns the Base64-encoded version of that serialized object. If the object cannot be serialized or there is another error, the method will return null. The object is not GZip-compressed before being encoded.

Parameters:

`serializableObject` - The object to encode

Returns:

The Base64-encoded object

encodeObject

```
public static String encodeObject(java.io.Serializable serializableObject,  
int options)
```


(continued from last page)

Serializes an object and returns the Base64-encoded version of that serialized object. If the object cannot be serialized or there is another error, the method will return null.

Valid options:

GZIP: gzip-compresses object before encoding it.
DONT_BREAK_LINES: don't break lines at 76 characters
Note: Technically, this makes your encoding non-compliant.

Example: `encodeObject(myObj, Base64.GZIP)` or

Example: `encodeObject(myObj, Base64.GZIP | Base64.DONT_BREAK_LINES)`

Parameters:

`serializableObject` - The object to encode
`options` - Specified options

Returns:

The Base64-encoded object

See Also:

[GZIP](#)

[DONT_BREAK_LINES](#)

encodeBytes

```
public static String encodeBytes(byte[] source)
```

Encodes a byte array into Base64 notation. Does not GZip-compress data.

Parameters:

`source` - The data to convert

encodeBytes

```
public static String encodeBytes(byte[] source,  
    int options)
```

Encodes a byte array into Base64 notation.

Valid options:

GZIP: gzip-compresses object before encoding it.
DONT_BREAK_LINES: don't break lines at 76 characters
Note: Technically, this makes your encoding non-compliant.

Example: `encodeBytes(myData, Base64.GZIP)` or

Example: `encodeBytes(myData, Base64.GZIP | Base64.DONT_BREAK_LINES)`

(continued from last page)

Parameters:

source - The data to convert
options - Specified options

See Also:[GZIP](#)[DONT_BREAK_LINES](#)

encodeBytes

```
public static String encodeBytes(byte[] source,  
    int off,  
    int len)
```

Encodes a byte array into Base64 notation. Does not GZip-compress data.

Parameters:

source - The data to convert
off - Offset in array where conversion should begin
len - Length of data to convert

encodeBytes

```
public static String encodeBytes(byte[] source,  
    int off,  
    int len,  
    int options)
```

Encodes a byte array into Base64 notation.

Valid options:

GZIP: gzip-compresses object before encoding it.
DONT_BREAK_LINES: don't break lines at 76 characters
Note: Technically, this makes your encoding non-compliant.

Example: `encodeBytes(myData, Base64.GZIP)` or

Example: `encodeBytes(myData, Base64.GZIP | Base64.DONT_BREAK_LINES)`

Parameters:

source - The data to convert
off - Offset in array where conversion should begin
len - Length of data to convert
options - Specified options, alphabet type is pulled from this (standard, url-safe, ordered)

See Also:[GZIP](#)[DONT_BREAK_LINES](#)

(continued from last page)

decode

```
public static byte[] decode(byte[] source,  
    int off,  
    int len,  
    int options)
```

Very low-level access to decoding ASCII characters in the form of a byte array. Does not support automatically gunzipping or any other "fancy" features.

Parameters:

source - The Base64 encoded data
off - The offset of where to begin decoding
len - The length of characters to decode

Returns:

decoded data

decode

```
public static byte[] decode(String s)
```

Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.

Parameters:

s - the string to decode

Returns:

the decoded data

decode

```
public static byte[] decode(String s,  
    int options)
```

Decodes data from Base64 notation, automatically detecting gzip-compressed data and decompressing it.

Parameters:

s - the string to decode
options - encode options such as URL_SAFE

Returns:

the decoded data

decodeToObject

```
public static Object decodeToObject(String encodedObject)
```

Attempts to decode Base64 data and deserialize a Java Object within. Returns null if there was an error.

Parameters:

encodedObject - The Base64 data to decode

Returns:

The decoded and deserialized object

(continued from last page)

encodeToFile

```
public static boolean encodeToFile(byte[] dataToEncode,  
    String filename)
```

Convenience method for encoding data to a file.

Parameters:

dataToEncode - byte array of data to encode in base64 form

filename - Filename for saving encoded data

Returns:

true if successful, false otherwise

decodeToFile

```
public static boolean decodeToFile(String dataToDecode,  
    String filename)
```

Convenience method for decoding data to a file.

Parameters:

dataToDecode - Base64-encoded data as a string

filename - Filename for saving decoded data

Returns:

true if successful, false otherwise

decodeFromFile

```
public static byte[] decodeFromFile(String filename)
```

Convenience method for reading a base64-encoded file and decoding it.

Parameters:

filename - Filename for reading encoded data

Returns:

decoded byte array or null if unsuccessful

encodeFromFile

```
public static String encodeFromFile(String filename)
```

Convenience method for reading a binary file and base64-encoding it.

Parameters:

filename - Filename for reading binary data

Returns:

base64-encoded string or null if unsuccessful

encodeFileToFile

```
public static void encodeFileToFile(String infile,  
    String outfile)
```

Reads infile and encodes it to outfile.

(continued from last page)

Parameters:

infile - Input file
outfile - Output file

decodeFileToFile

```
public static void decodeFileToFile(String infile,  
                                     String outfile)
```

Reads infile and decodes it to outfile.

Parameters:

infile - Input file
outfile - Output file

com.wowza.util Class Base64.InputStream

```

java.lang.Object
  |
  +- java.io.InputStream
        |
        +- java.io.FilterInputStream
              |
              +- com.wowza.util.Base64.InputStream
  
```

All Implemented Interfaces:

java.io.Closeable

public static class **Base64.InputStream**
extends java.io.FilterInputStream

A [Base64.InputStream](#) will read data from another java.io.InputStream, given in the constructor, and encode/decode to/from Base64 notation on the fly.

See Also:

[Base64](#)

Fields inherited from class java.io.FilterInputStream

in

Constructor Summary

public	Base64.InputStream (java.io.InputStream in) Constructs a Base64.InputStream in DECODE mode.
public	Base64.InputStream (java.io.InputStream in, int options) Constructs a Base64.InputStream in either ENCODE or DECODE mode.

Method Summary

int	read () Reads enough of the input stream to convert to/from Base64 and returns the next byte.
int	read (byte[] dest, int off, int len) Calls read() repeatedly until the end of stream is reached or len bytes are read.

Methods inherited from class java.io.FilterInputStream

available, close, mark, markSupported, read, read, read, reset, skip

Methods inherited from class java.io.InputStream

available, close, mark, markSupported, read, read, read, reset, skip

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.io.Closeable

```
close
```

Constructors

Base64.InputStream

```
public Base64.InputStream(java.io.InputStream in)
```

Constructs a [Base64.InputStream](#) in DECODE mode.

Parameters:

in - the java.io.InputStream from which to read data.

Base64.InputStream

```
public Base64.InputStream(java.io.InputStream in,  
                           int options)
```

Constructs a [Base64.InputStream](#) in either ENCODE or DECODE mode.

Valid options:

```
ENCODE or DECODE: Encode or Decode as data is read.  
DONT_BREAK_LINES: don't break lines at 76 characters  
    (only meaningful when encoding)  
Note: Technically, this makes your encoding non-compliant.
```

Example: new Base64.InputStream(in, Base64.DECODE)

Parameters:

in - the java.io.InputStream from which to read data.

options - Specified options

See Also:

[Base64.ENCODE](#)

[Base64.DECODE](#)

[Base64.DONT_BREAK_LINES](#)

Methods

read

```
public int read()  
    throws java.io.IOException
```

Reads enough of the input stream to convert to/from Base64 and returns the next byte.

Returns:

next byte

(continued from last page)

read

```
public int read(byte[] dest,  
               int off,  
               int len)  
throws java.io.IOException
```

Calls [read\(\)](#) repeatedly until the end of stream is reached or len bytes are read. Returns number of bytes read into array or -1 if end of stream is encountered.

Parameters:

dest - array to hold values
off - offset for array
len - max number of bytes to read into array

Returns:

bytes read into array or -1 if end of stream is encountered.

com.wowza.util Class Base64.OutputStream

```

java.lang.Object
  |
  +- java.io.OutputStream
        |
        +- java.io.FilterOutputStream
              |
              +- com.wowza.util.Base64.OutputStream
  
```

All Implemented Interfaces:

java.io.Flushable, java.io.Closeable

public static class **Base64.OutputStream**
extends java.io.FilterOutputStream

A [Base64.OutputStream](#) will write data to another java.io.OutputStream, given in the constructor, and encode/decode to/from Base64 notation on the fly.

See Also:

[Base64](#)

Fields inherited from class java.io.FilterOutputStream

out

Constructor Summary

public	Base64.OutputStream (java.io.OutputStream out) Constructs a Base64.OutputStream in ENCODE mode.
public	Base64.OutputStream (java.io.OutputStream out, int options) Constructs a Base64.OutputStream in either ENCODE or DECODE mode.

Method Summary

void	close () Flushes and closes (I think, in the superclass) the stream.
void	flushBase64 () Method added by PHIL.
void	resumeEncoding () Resumes encoding of the stream.
void	suspendEncoding () Suspends encoding of the stream.
void	write (byte[] theBytes, int off, int len) Calls write(int) repeatedly until len bytes are written.
void	write (int theByte) Writes the byte to the output stream after converting to/from Base64 notation.

Methods inherited from class java.io.FilterOutputStream

```
close, flush, write, write, write
```

Methods inherited from class `java.io.OutputStream`

```
close, flush, write, write, write
```

Methods inherited from class `java.lang.Object`

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Methods inherited from interface `java.io.Closeable`

```
close
```

Methods inherited from interface `java.io.Flushable`

```
flush
```

Constructors

Base64.OutputStream

```
public Base64.OutputStream(java.io.OutputStream out)
```

Constructs a [Base64.OutputStream](#) in ENCODE mode.

Parameters:

out - the java.io.OutputStream to which data will be written.

Base64.OutputStream

```
public Base64.OutputStream(java.io.OutputStream out,  
                           int options)
```

Constructs a [Base64.OutputStream](#) in either ENCODE or DECODE mode.

Valid options:

```
ENCODE or DECODE: Encode or Decode as data is read.  
DONT_BREAK_LINES: don't break lines at 76 characters  
    (only meaningful when encoding)  
Note: Technically, this makes your encoding non-compliant.
```

Example: new Base64.OutputStream(out, Base64.ENCODE)

Parameters:

out - the java.io.OutputStream to which data will be written.
options - Specified options.

(continued from last page)

See Also:[Base64.ENCODER](#)[Base64.DECODER](#)[Base64.DONT_BREAK_LINES](#)

Methods

write

```
public void write(int theByte)
    throws java.io.IOException
```

Writes the byte to the output stream after converting to/from Base64 notation. When encoding, bytes are buffered three at a time before the output stream actually gets a `write()` call. When decoding, bytes are buffered four at a time.

Parameters:

`theByte` - the byte to write

write

```
public void write(byte[] theBytes,
    int off,
    int len)
    throws java.io.IOException
```

Calls [write\(int\)](#) repeatedly until `len` bytes are written.

Parameters:

`theBytes` - array from which to read bytes

`off` - offset for array

`len` - max number of bytes to read into array

flushBase64

```
public void flushBase64()
    throws java.io.IOException
```

Method added by PHIL. [Thanks, PHIL. -Rob] This pads the buffer without closing the stream.

close

```
public void close()
    throws java.io.IOException
```

Flushes and closes (I think, in the superclass) the stream.

suspendEncoding

```
public void suspendEncoding()
    throws java.io.IOException
```

Suspends encoding of the stream. May be helpful if you need to embed a piece of base64-encoded data in a stream.

resumeEncoding

```
public void resumeEncoding()
```

Resumes encoding of the stream. May be helpful if you need to embed a piece of base64-encoded data in a stream.

com.wowza.util Class BufferUtils

java.lang.Object

└─com.wowza.util.BufferUtils

public class **BufferUtils**
extends Object

BufferUtils: utilities for converting between binary data and Java primitive types. Faster than Java runtime equivalents

Constructor Summary

public	<u>BufferUtils()</u>
--------	--------------------------------------

Method Summary

static int	<u>byteArrayToInt</u> (byte[] b) Convert byte array to int
static int	<u>byteArrayToInt</u> (byte[] b, int offset) Convert byte array to int with offset
static int	<u>byteArrayToInt</u> (byte[] b, int offset, int count) Convert byte array to int with offset.
static int	<u>byteArrayToInt</u> (byte[] b, int offset, int count, boolean isReverse) Convert byte array to int with offset.
static long	<u>byteArrayToLong</u> (byte[] b) Convert byte array to long
static long	<u>byteArrayToLong</u> (byte[] b, int offset) Convert byte array to long with offset
static long	<u>byteArrayToLong</u> (byte[] b, int offset, int count) Convert byte array to long with offset.
static long	<u>byteArrayToLong</u> (byte[] b, int offset, int count, boolean isReverse) Convert byte array to long with offset.
static int	<u>byteArrayToShort</u> (byte[] b) Convert byte array to int
static int	<u>byteArrayToShort</u> (byte[] b, int offset) Convert byte array to int with offset
static int	<u>byteArrayToShort</u> (byte[] b, int offset, int count) Convert byte array to int with offset.
static int	<u>byteArrayToShort</u> (byte[] b, int offset, int count, boolean isReverse) Convert byte array to int with offset.

static String	<code>byteArrayToString</code> (byte[] b) Convert a byte array to a String (UTF-8 encoding assumed)
static String	<code>byteArrayToString</code> (byte[] b, int offset, int count) Convert a byte array to a String (UTF-8 encoding assumed)
static byte[]	<code>decodeHexString</code> (String hexStr) Decode a string as a byte array
static int	<code>doCRC32</code> (int crc, byte[] buffer, int offset, int len) Calculate an IEEE CRC32 value for MPEG transport stream from a starting crc value
static String	<code>encodeHexString</code> (byte[] bytes) Encode a byte array as a string
static String	<code>encodeHexString</code> (byte[] bytes, int offset, int len) Encode a byte array as a string
static int	<code>getUnsignedShort</code> (java.nio.ByteBuffer buffer)
static int	<code>indexOf</code> (byte[] source, byte[] pattern) Finds the first occurrence of a byte pattern in a byte buffer.
static int	<code>indexOfDifferent</code> (byte[] buffer1, byte[] buffer2) Compare two byte buffers, and return the index of the first byte that is different.
static byte[]	<code>intToByteArray</code> (int value) Convert a int value to a byte array in network order
static void	<code>intToByteArray</code> (int value, byte[] buffer, int offset, int size) Convert a int value to a byte array in network order
static void	<code>intToByteArray</code> (int value, byte[] buffer, int offset, int size, boolean isReverse) Convert a int value to a byte array in network order
static byte[]	<code>intToByteArray</code> (int value, int size) Convert a int value to a byte array in network order
static byte[]	<code>longToByteArray</code> (long value) Convert a long value to a byte array in network order
static void	<code>longToByteArray</code> (long value, byte[] buffer, int offset, int size) Convert a long value to a byte array in network order
static void	<code>longToByteArray</code> (long value, byte[] buffer, int offset, int size, boolean isReverse) Convert a long value to a byte array in network order
static byte[]	<code>longToByteArray</code> (long value, int size) Convert a long value to a byte array in network order
static boolean	<code>startsWith</code> (byte[] source, byte[] pattern)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

BufferUtils

```
public BufferUtils()
```

Methods

encodeHexString

```
public static String encodeHexString(byte[] bytes)
```

Encode a byte array as a string

Parameters:

bytes - byte array

Returns:

string

encodeHexString

```
public static String encodeHexString(byte[] bytes,  
    int offset,  
    int len)
```

Encode a byte array as a string

Parameters:

bytes - byte array

offset - offset

len - length

Returns:

string

decodeHexString

```
public static byte[] decodeHexString(String hexStr)
```

Decode a string as a byte array

Parameters:

hexStr - string

Returns:

byte array

byteArrayToString

```
public static String byteArrayToString(byte[] b)
```

Convert a byte array to a String (UTF-8 encoding assumed)

(continued from last page)

Parameters:

b - byte array

Returns:resultant string

byteArrayToString

```
public static String byteArrayToString(byte[] b,  
    int offset,  
    int count)
```

Convert a byte array to a String (UTF-8 encoding assumed)

Parameters:

b - byte array
offset - offset
count - len

Returns:resultant string

byteArrayToLong

```
public static long byteArrayToLong(byte[] b)
```

Convert byte array to long

Parameters:

b - byte array (8 bytes)

Returns:long value

byteArrayToLong

```
public static long byteArrayToLong(byte[] b,  
    int offset)
```

Conver byte array to long with offset

Parameters:

b - byte array (8 bytes)
offset - offset

Returns:long value

byteArrayToLong

```
public static long byteArrayToLong(byte[] b,  
    int offset,  
    int count)
```

Convert byte array to long with offset. Count is the number of bytes. Can be less than 8. If less than 8 just fills lower bits in value.

Parameters:

b - byte array
offset - offset

(continued from last page)

count - number of bytes

Returns:

long value

byteArrayToLong

```
public static long byteArrayToLong(byte[] b,  
    int offset,  
    int count,  
    boolean isReverse)
```

Convert byte array to long with offset. Count is the number of bytes. Can be less than 8. If less than 8 just fills lower bits in value. The reverse flag allows data to be in reverse order.

Parameters:

b - byte array
offset - offset
count - number of bytes
isReverse - is data in reverse order

Returns:

long value

byteArrayToInt

```
public static int byteArrayToInt(byte[] b)
```

Convert byte array to int

Parameters:

b - byte array (4 bytes)

Returns:

int value

byteArrayToInt

```
public static int byteArrayToInt(byte[] b,  
    int offset)
```

Conver byte array to int with offset

Parameters:

b - byte array (4 bytes)
offset - offset

Returns:

int value

byteArrayToInt

```
public static int byteArrayToInt(byte[] b,  
    int offset,  
    int count)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 4. If less than 4 just fills lower bits in value.

Parameters:

b - byte array

(continued from last page)

offset - offset
count - number of bytes

Returns:

int value

byteArrayToInt

```
public static int byteArrayToInt(byte[] b,  
    int offset,  
    int count,  
    boolean isReverse)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 4. If less than 4 just fills lower bits in value. The reverse flag allows data to be in reverse order.

Parameters:

b - byte array
offset - offset
count - number of bytes
isReverse - is data in reverse order

Returns:

int value

byteArrayToShort

```
public static int byteArrayToShort(byte[] b)
```

Convert byte array to int

Parameters:

b - byte array (2 bytes)

Returns:

int value

byteArrayToShort

```
public static int byteArrayToShort(byte[] b,  
    int offset)
```

Conver byte array to int with offset

Parameters:

b - byte array (2 bytes)
offset - offset

Returns:

int value

byteArrayToShort

```
public static int byteArrayToShort(byte[] b,  
    int offset,  
    int count)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 2. If less than 2 just fills lower bits in value.

Parameters:

(continued from last page)

b - byte array
offset - offset
count - number of bytes

Returns:

int value

byteArrayToShort

```
public static int byteArrayToShort(byte[] b,  
    int offset,  
    int count,  
    boolean isReverse)
```

Convert byte array to int with offset. Count is the number of bytes. Can be less than 2. If less than 2 just fills lower bits in value. The reverse flag allows data to be in reverse order.

Parameters:

b - byte array
offset - offset
count - number of bytes
isReverse - is data in reverse order

Returns:

int value

intToByteArray

```
public static byte[] intToByteArray(int value)
```

Convert a int value to a byte array in network order

Parameters:

value - value

Returns:

4-byte array with value

intToByteArray

```
public static byte[] intToByteArray(int value,  
    int size)
```

Convert a int value to a byte array in network order

Parameters:

value - value
size - size of resultant byte array

Returns:

size-byte array with value

intToByteArray

```
public static void intToByteArray(int value,  
    byte[] buffer,  
    int offset,  
    int size)
```

Convert a int value to a byte array in network order

(continued from last page)

Parameters:

value - value
buffer - destination byte array
offset - starting offset in byte array
size - number of bytes to write

intToByteArray

```
public static void intToByteArray(int value,  
    byte[] buffer,  
    int offset,  
    int size,  
    boolean isReverse)
```

Convert a int value to a byte array in network order

Parameters:

value - value
buffer - destination byte array
offset - starting offset in byte array
size - number of bytes to write
isReverse - is data in reverse order

longToByteArray

```
public static byte[] longToByteArray(long value)
```

Convert a long value to a byte array in network order

Parameters:

value - value

Returns:

8-byte array with value

longToByteArray

```
public static byte[] longToByteArray(long value,  
    int size)
```

Convert a long value to a byte array in network order

Parameters:

value - value
size - size of resultant byte array

Returns:

size-byte array with value

longToByteArray

```
public static void longToByteArray(long value,  
    byte[] buffer,  
    int offset,  
    int size)
```

Convert a long value to a byte array in network order

Parameters:

(continued from last page)

value - value
buffer - destination byte array
offset - starting offset in byte array
size - number of bytes to write

longToByteArray

```
public static void longToByteArray(long value,  
    byte[] buffer,  
    int offset,  
    int size,  
    boolean isReverse)
```

Convert a long value to a byte array in network order

Parameters:

value - value
buffer - destination byte array
offset - starting offset in byte array
size - number of bytes to write
isReverse - is data in reverse order

getUnsignedShort

```
public static int getUnsignedShort(java.nio.ByteBuffer buffer)
```

doCRC32

```
public static int doCRC32(int crc,  
    byte[] buffer,  
    int offset,  
    int len)
```

Calculate an IEEE CRC32 value for MPEG transport stream from a starting crc value

Parameters:

crc - starting crc value
buffer - buffer
offset - offset
len - len

Returns:

crc value

indexOf

```
public static int indexOf(byte[] source,  
    byte[] pattern)
```

Finds the first occurrence of a byte pattern in a byte buffer.

Note: If we want to improve the performance, we could implement the Knuth-Morris-Pratt algorithm. But I don't need the speed nor do I have time today!

Parameters:

source - The source byte buffer
pattern - the pattern we're looking for.

(continued from last page)

Returns:

the index of source where the pattern is found, else -1

indexOfDifferent

```
public static int indexOfDifferent(byte[] buffer1,  
    byte[] buffer2)
```

Compare two byte buffers, and return the index of the first byte that is different.

Parameters:

buffer1 - byte array1

buffer2 - byte array2

Returns:

index where buffers differ, or -1.

startsWith

```
public static boolean startsWith(byte[] source,  
    byte[] pattern)
```

com.wowza.util Class DebugUtils

java.lang.Object

└─com.wowza.util.DebugUtils

public final class **DebugUtils**
extends Object

DebugUtils: Debugging utilities.

Constructor Summary

public	DebugUtils()
--------	------------------------------

Method Summary

static java.io.File	byteArrayToFile (byte[] data, String filePath) Dump a buffer of bytes to a file.
static boolean	doesStackContainMethod (String methodName) Examine current stack trace to determine if the specified method name in the the trace.
static String	formatBytes (byte[] data) Format byte array for printing.
static String	formatBytes (byte[] data, boolean showIndex) Format byte array for printing.
static String	formatBytes (byte[] data, int offset, int len) Format byte array for printing.
static String	formatBytes (byte[] data, int offset, int len, boolean showIndex) Format byte array for printing.
static String	formatBytesShort (byte[] data) Format byte array for printing.
static String	formatBytesShort (byte[] data, int offset, int len) Format byte array for printing.
static String	formatBytesStruct (byte[] data)
static String	formatBytesStruct (byte[] data, int offset, int len) Format byte array for printing.
static String	formatMilliseconds (long ms) Give a time in seconds, return a String representing the time in hh:mm:ss.mmm.
static String	formatSeconds (long t) Give a time in seconds, return a String representing the time in hh:mm:ss.

static String	formatUtcTime (long newRealTime)
static String	stackTraceToString (Throwable e)
static String	toHex (byte value) Format a byte value to a 0xff format
static String	toHex (int value) Format a byte value to a 0xffffffff format
static String	toLong (long value) Format a long value to a 0xffffffffffffffff format

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

DebugUtils

public **DebugUtils**()

Methods

formatBytesShort

public static String **formatBytesShort**(byte[] data)

Format byte array for printing. Simple format as rows of hex values (16 values per row)

Parameters:

data - byte array

Returns:

formatted string

formatBytesShort

public static String **formatBytesShort**(byte[] data,
int offset,
int len)

Format byte array for printing. Simple format as rows of hex values (16 values per row)

Parameters:

data - byte array

offset - offset in array

len - data len

Returns:

formatted string

formatBytes

```
public static String formatBytes(byte[] data)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

Parameters:

data - byte array

Returns:

formatted string

formatBytes

```
public static String formatBytes(byte[] data,  
    boolean showIndex)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

Parameters:

data - byte array

Returns:

formatted string

formatBytes

```
public static String formatBytes(byte[] data,  
    int offset,  
    int len)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

Parameters:

data - byte array

offset - start index in array

len - length to format

Returns:

formatted string

formatBytes

```
public static String formatBytes(byte[] data,  
    int offset,  
    int len,  
    boolean showIndex)
```

Format byte array for printing. Format as rows of hex values (16 values per row) along with text representation of data.

Parameters:

data - byte array

offset - start index in array

len - length to format

Returns:

formatted string

formatBytesStruct

```
public static String formatBytesStruct(byte[] data)
```

formatBytesStruct

```
public static String formatBytesStruct(byte[] data,  
    int offset,  
    int len)
```

Format byte array for printing. Format as Java primitive byte values (8 per row).

Parameters:

data - byte array

Returns:

formatted string

toHex

```
public static String toHex(byte value)
```

Format a byte value to a 0xff format

Parameters:

value - byte value

Returns:

return string

toHex

```
public static String toHex(int value)
```

Format a byte value to a 0xffffffff format

Parameters:

value - int value

Returns:

return string

toLong

```
public static String toLong(long value)
```

Format a long value to a 0xffffffffffffffff format

Parameters:

value - long value

Returns:

return string

(continued from last page)

byteArrayToFile

```
public static java.io.File byteArrayToFile(byte[] data,  
      String filePath)
```

Dump a buffer of bytes to a file. Useful for debugging.

Parameters:

data - a buffer of bytes
filePath - The path and filename

formatSeconds

```
public static String formatSeconds(long t)
```

Give a time in seconds, return a String representing the time in hh:mm:ss.

123 s --> 00:02:03

Parameters:

t

Returns:

time representation

formatMilliseconds

```
public static String formatMilliseconds(long ms)
```

Give a time in seconds, return a String representing the time in hh:mm:ss.mmm.

123456 ms --> 00:02:03.456

Parameters:

ms

Returns:

time representation

formatUtcTime

```
public static String formatUtcTime(long newRealTime)
```

stackTraceToString

```
public static String stackTraceToString(Throwable e)
```

doesStackContainMethod

```
public static boolean doesStackContainMethod(String methodName)
```

Examine current stack trace to determine if the specified method name in the the trace.

Could be enhanced quite a bit by also checking for Class and method. But simple for now.

Parameters:

(continued from last page)

methodName

Returns:

true if in trace, else false

com.wowza.util Class ElapsedTimer

java.lang.Object

└─com.wowza.util.ElapsedTimer

public class **ElapsedTimer**
extends Object

ElapsedTimer: Utility class for keep track of the duration an object has been in existence.

Constructor Summary

public	ElapsedTimer() Construct a new ElapsedTimer and start the clock
--------	------------------------------------------------------------------------------------

Method Summary

java.util.Date	getDate() Get the date the object was created
String	getDateString() Get the date object was created as formatted String
long	getTime() Get elapsed time object in existence (milliseconds)
double	getTimeSeconds() Get elapsed time object in seconds
String	getTimeString() Get elapsed time object in existence as formatted String (Ex: 3 days 2 minutes 5 seconds)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ElapsedTimer

public **ElapsedTimer()**

Construct a new ElapsedTimer and start the clock

Methods

(continued from last page)

getDate

```
public java.util.Date getDate()
```

Get the date the object was created

Returns:

date object created

getDateString

```
public String getDateString()
```

Get the date object was created as formatted String

Returns:

date object created as formatted String

getTime

```
public long getTime()
```

Get elapsed time object in existence (milliseconds)

Returns:

elapsed time (milliseconds)

getTimeSeconds

```
public double getTimeSeconds()
```

Get elapsed time object in seconds

Returns:

elapsed time in seconds

getTimeString

```
public String getTimeString()
```

Get elapsed time object in existence as formatted String (Ex: 3 days 2 minutes 5 seconds)

Returns:

elapsed time as formatted String

com.wowza.util Class FileUtils

java.lang.Object

└─com.wowza.util.FileUtils

public class **FileUtils**
extends Object

FileUtils: File utilities

Constructor Summary

public	FileUtils()
--------	-----------------------------

Method Summary

static void	copyFile (java.io.File fromFile, java.io.File toFile) Simple file copy routine
static void	copyFile2 (java.io.File in, java.io.File out)
static boolean	deleteDirectory (java.io.File path)
static byte[]	fileToByteArray (java.io.File file)
static String	streamNameToValidFilename (String name) Encode a stream name (deal with path elements) to a valid filename.
static String	toValidFilename (String name) Encode a name to a valid filename.
static void	traverseDirectory (java.io.File dir, IFileProcess fileNotify) Traverse a directory recursively calling fileNotify for each file and folder encountered
static java.io.File	versionFile (java.io.File newFile) Rename a file using the file format [original-name]_#[.ext].

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

FileUtils

public **FileUtils**()

(continued from last page)

Methods

fileToByteArray

```
public static byte[] fileToByteArray(java.io.File file)
```

streamNameToValidFilename

```
public static String streamNameToValidFilename(String name)
```

Encode a stream name (deal with path elements) to a valid filename.

Parameters:

name - stream name

Returns:

encoded filename

toValidFilename

```
public static String toValidFilename(String name)
```

Encode a name to a valid filename.

Parameters:

name

Returns:

encoded filename

copyFile

```
public static void copyFile(java.io.File fromFile,  
                             java.io.File toFile)
```

Simple file copy routine

Parameters:

fromFile - from file

toFile - to file

copyFile2

```
public static void copyFile2(java.io.File in,  
                             java.io.File out)  
    throws java.io.IOException
```

deleteDirectory

```
public static boolean deleteDirectory(java.io.File path)
```

versionFile

```
public static java.io.File versionFile(java.io.File newFile)
```

Rename a file using the file format [original-name]_#[.ext].

Parameters:

newFile - input file

Returns:

renamed file

traverseDirectory

```
public static void traverseDirectory(java.io.File dir,  
    IFileProcess fileNotify)
```

Traverse a directory recursively calling fileNotify for each file and folder encountered

Parameters:

dir - starting directory

fileNotify - file notify object

com.wowza.util Class FLVUtils

java.lang.Object

└─com.wowza.util.FLVUtils

public final class **FLVUtils**
extends Object

FLVUtils: utility for reading and writing .flv files.

Field Summary

public static final	<u>FLV_CHUNKHEADER_BUFFER_SIZE</u> Size of temporary buffer needed for flv reading (byte[]) Value: 13
public static final	<u>FLV_CHUNKHEADER_FIRST_BYTE</u> Header values: first byte of packet data Value: 3
public static final	<u>FLV_CHUNKHEADER_HEADER_SIZE</u> Size of packet header (byte[]) Value: 11
public static final	<u>FLV_CHUNKHEADER_I_SIZE</u> Header values: packet size Value: 1
public static final	<u>FLV_CHUNKHEADER_I_TIMECODE</u> Header values: timecode (milliseconds) Value: 2
public static final	<u>FLV_CHUNKHEADER_I_TYPE</u> Header values: packet type Value: 0
public static final	<u>FLV_CHUNKHEADER_SECOND_BYTE</u> Header values: second byte of packet data Value: 4
public static final	<u>FLV_CHUNKHEADER_VALUES_SIZE</u> Size of header values array (long[]) Value: 5
public static final	<u>FLV_DFRAME</u> D video frame type (partial frame based on key frame) Value: 3
public static final	<u>FLV_KFRAME</u> Key video frame type Value: 1

public static final	FLV_PFRAME P video frame type (partial frame based on previous frame) Value: 2
public static final	FLV_TCINDEXAUDIO Value: 0
public static final	FLV_TCINDEXDATA Value: 2
public static final	FLV_TCINDEXVIDEO Value: 1
public static final	FLV_UFRAME Unknown video frame type Value: 0

Constructor Summary

public	FLVUtils()
--------	----------------------------

Method Summary

static long	adjustFirstPacketTCs (java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs) Align list of timecode for each data type.
static int	audioCodecStringToId (String codecString) Parse a string to get the codec ID defined by IVHost.CODEC_AUDIO_*
static String	audioCodecToMetaDataString (int codec) Get a printable string representation of the audio codecs defined as IVHost.CODEC_AUDIO_* as the string used in the onMetaData event
static String	audioCodecToString (int codec) Get a printable string representation of the audio codecs defined as IVHost.CODEC_AUDIO_*
static String	frameTypeToString (int frameType)
static int	getAudioCodec (AMFPacket packet) Get the codec id for this audio packet.
static int	getAudioCodec (int value) Return the codec portion of the first byte of an audio packet.
static int	getAudioMP3Layer (AMFPacket packet) Audio marked as MP3 is really MPEG1 Layer 1-3.
static int	getFrameType (byte value) Given the first byte of a video packet, determine the frame type (FLV_*FRAME)
static int	getFrameType (int value) Given the first byte of a video packet, determine the frame type (FLV_*FRAME)

static int	<u>getFrameType</u> (int[] values) Given the headers values (including first byte of the packet), determine the type of video frame (FLV_*FRAME)
static long	<u>getLastTC</u> (java.io.File file) Get the duration of an .flv file.
static int	<u>getVideoCodec</u> (<u>AMFPacket</u> packet) Get the codec id for this video packet.
static int	<u>getVideoCodec</u> (int value) Return the codec portion of the first byte of an video packet.
static int	<u>getVideoTimecodeOffset</u> (<u>AMFPacket</u> packet) Get the timecode offset in milliseconds between the PTS and DTS for this frame.
static int	<u>getVideoTimecodeOffset</u> (byte[] buffer) Get the timecode offset in milliseconds between the PTS and DTS for this frame.
static java.util.List	<u>interleavePackets</u> (java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, long[] currentTCs) This is a utility function primarily used for IMediaWriters.
static java.util.List	<u>interleavePackets</u> (java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, long[] currentTCs) This is a utility function primarily used for IMediaWriters.
static boolean	<u>isAudioCodecConfig</u> (<u>AMFPacket</u> packet) Returns true if the packet is a video codec config packet
static boolean	<u>isOnMetadataPacket</u> (<u>AMFPacket</u> packet) Returns true if packet is onMetaData or [@setDataFrame, onMetaData] data packet.
static boolean	<u>isVideoCodecConfig</u> (<u>AMFPacket</u> packet) Returns true if the packet is a video codec config packet
static boolean	<u>isVideoKeyFrame</u> (<u>AMFPacket</u> packet) Returns true if the packet is a video key frame
static boolean	<u>isVideoKeyFrame</u> (byte[] buffer) Returns true if the packet is a video key frame
static boolean	<u>isVideoKeyFrame</u> (java.nio.ByteBuffer buffer) Returns true if the packet is a video key frame
static boolean	<u>isVideoKeyFrame</u> (int[] chunkHeaderValues) Returns true if the packet is a video key frame
static <u>AMFPacket</u>	<u>readChunk</u> (java.io.DataInput is) Read a packets worth of .flv data from an InputStream and return as an AMFPacket
static <u>AMFPacket</u>	<u>readChunk</u> (java.io.InputStream is) Read a packets worth of .flv data from an InputStream and return as an AMFPacket
static void	<u>readChunkHeader</u> (java.io.RandomAccessFile is, byte[] buffer, int[] values) Read packet header.

static boolean	readHeader (java.io.DataInput is) Read file header.
static boolean	readHeader (java.io.InputStream is) Read file header.
static void	readPrevChunkHeader (java.io.RandomAccessFile is, byte[] buffer, int[] values) Back up one packet from current position in the file and read the packet header.
static String	streamCodecToString (int codec) Get a printable string representation of the stream codecs defined as IVHost.CODEC_STREAM_*
static AMFPacket	updateOnCuePointTimecode (AMFPacket packet, long timecode)
static java.nio.ByteBuffer	updateOnCuePointTimecode (java.nio.ByteBuffer data, int dataType, long timecode)
static int	videoCodecStringToId (String codecString) Parse a string to get the codec ID defined by IVHost.CODEC_VIDEO_*
static String	videoCodecToMetaDataString (int codec) Get a printable string representation of the video codecs defined as IVHost.CODEC_VIDEO_* as the string used in the onMetaData event
static String	videoCodecToString (int codec) Get a printable string representation of the video codecs defined as IVHost.CODEC_VIDEO_*
static void	writeChunk (java.io.DataOutput ds, java.nio.ByteBuffer data, int size, long timecode, byte type)
static void	writeChunk (java.io.OutputStream ds, java.nio.ByteBuffer data, int size, long timecode, byte type) Write a packets worth of data.
static void	writeDuration (java.io.File file, double duration) Write the duration to an existing .flv file.
static void	writeHeader (java.io.OutputStream ds, double duration, int audiocodecid, int videocodecid, String createdBy, java.util.Map extraMetadata) Write file header including onMetaData packet.
static void	writeHeader (java.io.OutputStream ds, double duration, java.util.Map extraMetadata) Write file header including onMetaData packet.
static void	writePackets (java.io.OutputStream ds, java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, long[] currentTCs) Write a bunch of packets to .flv file all at once.
static void	writePackets (java.io.OutputStream ds, java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, long[] currentTCs, IFLVWriterAdjustTimecode dataPacketTimecodeAdjuster) Write a bunch of packets to .flv file all at once.

static void	writePackets (java.io.OutputStream ds, java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, long[] currentTCs) Write a bunch of packets to .flv file all at once.
static void	writePackets (java.io.OutputStream ds, java.util.List packetList, long tcOffset) Write audio/video/data packets to an .flv file.
static void	writeShortHeader (java.io.DataOutput ds)
static void	writeShortHeader (java.io.OutputStream ds) Write just the FLV file header (without the metadata packet)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

FLV_CHUNKHEADER_ITYPE

public static final int **FLV_CHUNKHEADER_ITYPE**

Header values: packet type
Constant value: **0**

FLV_CHUNKHEADER_ISIZE

public static final int **FLV_CHUNKHEADER_ISIZE**

Header values: packet size
Constant value: **1**

FLV_CHUNKHEADER_IMECODE

public static final int **FLV_CHUNKHEADER_IMECODE**

Header values: timecode (milliseconds)
Constant value: **2**

FLV_CHUNKHEADER_FIRSTBYTE

public static final int **FLV_CHUNKHEADER_FIRSTBYTE**

Header values: first byte of packet data
Constant value: **3**

FLV_CHUNKHEADER_SECONDBYTE

public static final int **FLV_CHUNKHEADER_SECONDBYTE**

Header values: second byte of packet data
Constant value: **4**

FLV_CHUNKHEADER_HEADERSIZE

```
public static final int FLV_CHUNKHEADER_HEADERSIZE
```

Size of packet header (byte[])
Constant value: **11**

FLV_CHUNKHEADER_BUFFERSIZE

```
public static final int FLV_CHUNKHEADER_BUFFERSIZE
```

Size of temporary buffer needed for flv reading (byte[])
Constant value: **13**

FLV_CHUNKHEADER_VALUESIZE

```
public static final int FLV_CHUNKHEADER_VALUESIZE
```

Size of header values array (long[])
Constant value: **5**

FLV_UFRAME

```
public static final int FLV_UFRAME
```

Unknown video frame type
Constant value: **0**

FLV_KFRAME

```
public static final int FLV_KFRAME
```

Key video frame type
Constant value: **1**

FLV_DFRAME

```
public static final int FLV_DFRAME
```

D video frame type (partial frame based on key frame)
Constant value: **3**

FLV_PFRAME

```
public static final int FLV_PFRAME
```

P video frame type (partial frame based on previous frame)
Constant value: **2**

FLV_TCINDEXAUDIO

```
public static final int FLV_TCINDEXAUDIO
```

Constant value: **0**

(continued from last page)

FLV_TCINDEXVIDEO

```
public static final int FLV_TCINDEXVIDEO
```

Constant value: **1**

FLV_TCINDEXDATA

```
public static final int FLV_TCINDEXDATA
```

Constant value: **2**

Constructors

FLVUtils

```
public FLVUtils()
```

Methods

streamCodecToString

```
public static String streamCodecToString(int codec)
```

Get a printable string representation of the stream codecs defined as IVHost.CODEC_STREAM_*

Parameters:

codec - codec id defined IVHost.CODEC_STREAM_*

Returns:

codec name

audioCodecStringToId

```
public static int audioCodecStringToId(String codecString)
```

Parse a string to get the codec ID defined by IVHost.CODEC_AUDIO_*

Parameters:

codecString - codec string

Returns:

codec ID

videoCodecToMetaDataString

```
public static String videoCodecToMetaDataString(int codec)
```

Get a printable string representation of the video codecs defined as IVHost.CODEC_VIDEO_* as the string used in the onMetaData event

Parameters:

codec - codec id defined IVHost.CODEC_VIDEO_*

Returns:

(continued from last page)

codec name

audioCodecToMetaDataString

```
public static String audioCodecToMetaDataString(int codec)
```

Get a printable string representation of the audio codecs defined as IVHost.CODEC_AUDIO_* as the string used in the onMetaData event

Parameters:

codec - codec id defined IVHost.CODEC_AUDIO_*

Returns:

codec name

audioCodecToString

```
public static String audioCodecToString(int codec)
```

Get a printable string representation of the audio codecs defined as IVHost.CODEC_AUDIO_*

Parameters:

codec - codec id defined IVHost.CODEC_AUDIO_*

Returns:

codec name

videoCodecStringToId

```
public static int videoCodecStringToId(String codecString)
```

Parse a string to get the codec ID defined by IVHost.CODEC_VIDEO_*

Parameters:

codecString - codec string

Returns:

codec ID

videoCodecToString

```
public static String videoCodecToString(int codec)
```

Get a printable string representation of the video codecs defined as IVHost.CODEC_VIDEO_*

Parameters:

codec - codec id defined IVHost.CODEC_VIDEO_*

Returns:

codec name

frameTypeToString

```
public static String frameTypeToString(int frameType)
```

(continued from last page)

getFrameType

```
public static int getFrameType(int[] values)
```

Given the headers values (including first byte of the packet), determine the type of video frame (FLV_*FRAME)

Parameters:

values - header values

Returns:

type of video frame (FLV_*FRAME)

getFrameType

```
public static int getFrameType(int value)
```

Given the first byte of a video packet, determine the frame type (FLV_*FRAME)

Parameters:

value - first byte of packet

Returns:

type of video frame (FLV_*FRAME)

getAudioCodec

```
public static int getAudioCodec(int value)
```

Return the codec portion of the first byte of an audio packet. Return should be one of IVHost.CODEC_AUDIO_*

Parameters:

value - first byte of audio packet

Returns:

codec id

getVideoCodec

```
public static int getVideoCodec(int value)
```

Return the codec portion of the first byte of an video packet. Return should be one of IVHost.CODEC_VIDEO_*

Parameters:

value - first byte of audio packet

Returns:

codec id

getFrameType

```
public static int getFrameType(byte value)
```

Given the first byte of a video packet, determine the frame type (FLV_*FRAME)

Parameters:

value - first byte of packet

Returns:

type of video frame (FLV_*FRAME)

readChunk

```
public static AMFPacket readChunk(java.io.InputStream is)
```

Read a packets worth of .flv data from an InputStream and return as an AMFPacket

Parameters:

is - InputStream

Returns:

AMFPacket of data or null if unsuccessful or end of file

readChunk

```
public static AMFPacket readChunk(java.io.DataInput is)
```

Read a packets worth of .flv data from an InputStream and return as an AMFPacket

Parameters:

is - InputStream

Returns:

AMFPacket of data or null if unsuccessful or end of file

readPrevChunkHeader

```
public static void readPrevChunkHeader(java.io.RandomAccessFile is,  
    byte[] buffer,  
    int[] values)
```

Back up one packet from current position in the file and read the packet header. This includes reading the first byte of the packet data. The file pointer will be positioned at the first byte of the packet data. values[FLV_CHUNKHEADER_ITYPE] will be set to 0x7f if failure or start of file.

Parameters:

is - RandomAccessFile

buffer - temporary buffer byte[FLV_CHUNKHEADER_BUFFERSIZE]

values - header values long[FLV_CHUNKHEADER_VALUESIZE]

readChunkHeader

```
public static void readChunkHeader(java.io.RandomAccessFile is,  
    byte[] buffer,  
    int[] values)
```

Read packet header. This includes reading the first byte of the packet data. The file pointer will be positioned at the first byte of the packet data. values[FLV_CHUNKHEADER_ITYPE] will be set to 0x7f if failure or end of file.

Parameters:

is - RandomAccessFile

buffer - temporary buffer byte[FLV_CHUNKHEADER_BUFFERSIZE]

values - header values long[FLV_CHUNKHEADER_VALUESIZE]

readHeader

```
public static boolean readHeader(java.io.InputStream is)
```

Read file header. Return true if successful. Basically this just skips first 13 bytes in file.

readHeader

```
public static boolean readHeader(java.io.DataInput is)
```

Read file header. Return true if successful. Basically this just skips first 13 bytes in file.

writeShortHeader

```
public static void writeShortHeader(java.io.OutputStream ds)
```

Write just the FLV file header (without the metadata packet)

Parameters:

ds - OutputStream

writeShortHeader

```
public static void writeShortHeader(java.io.DataOutput ds)
```

writeHeader

```
public static void writeHeader(java.io.OutputStream ds,  
    double duration,  
    java.util.Map extraMetadata)
```

Write file header including onMetaData packet.

Parameters:

ds - OutputStream

duration - duration of .flv file in seconds

extraMetadata - Map of name/value pairs of metadata that will be appended to the onMetaData block

writeHeader

```
public static void writeHeader(java.io.OutputStream ds,  
    double duration,  
    int audiocodecid,  
    int videocodecid,  
    String createdBy,  
    java.util.Map extraMetadata)
```

(continued from last page)

Write file header including onMetaData packet.

With this method you can provide a Map of metadata to write to the file. This map can include a mixture of simple types like: int, long, String, boolean. These types will be wrapped in AMFData classes before they are written to the file. This map can also contain AMFData items. For example if you wanted to insert an array of **cuePoints** the code would look like:

```
Map extraMetadata = new HashMap();

AMFDataArray amfArray = new AMFDataArray();
for(int i=0;i
```

Parameters:

ds - OutputStream
duration - duration of .flv file in seconds
audiocodecid - audio codec ID see IVHost.CODEC_AUDIO_* (-1 for now audio)
videocodecid - video codec ID see IVHost.CODEC_VIDEO_* (-1 for now video)
createdBy - created by string (null for empty)
extraMetadata - Map of name/value pairs of metadata that will be appended to the onMetaData block

writeChunk

```
public static void writeChunk(java.io.OutputStream ds,
    java.nio.ByteBuffer data,
    int size,
    long timecode,
    byte type)
```

Write a packets worth of data.

Parameters:

ds - OutputStream
data - packet data
size - size of the packet
timecode - timecode (milliseconds)
type - type of packet IVHost.CONTENT_TYPE_*

writeChunk

```
public static void writeChunk(java.io.DataOutput ds,
    java.nio.ByteBuffer data,
    int size,
    long timecode,
    byte type)
```

(continued from last page)

interleavePackets

```
public static java.util.List interleavePackets(java.util.List audioPackets,
        java.util.List videoPackets,
        java.util.List dataPackets,
        java.util.List audioTCs,
        java.util.List videoTCs,
        java.util.List dataTCs,
        long[] currentTCs)
```

This is a utility function primarily used for IMediaWriters. It is a way of taking the discrete audio/video/data packets and timecodes and interleaving them into a single list of AMFPacket objects. The currentTCs array is an array of longs containing the last timecode for each of the packet types FLV_TCINDEX* (long[3]). This array will be used to calculate the absolute timecode for a given packet. For example if the relative timecode for an audio packet is 26 and the currentTCs value for the audio channel is 1003 then the absolute timecode for that packet will be 1029. The currentTCs array will be updated after this call to reflect the absolute timecode of the last packet processed of each type.

Parameters:

audioPackets - list of audio packets (ByteBuffer)
 videoPackets - list of video packets (ByteBuffer)
 dataPackets - list of data packets (ByteBuffer)
 audioTCs - list of relative audio timecodes (Long)
 videoTCs - list of relative video timecodes (Long)
 dataTCs - list of relative data timecodes (Long)
 currentTCs - array of longs containing last TCs written for each packet type FLV_TCINDEX* (long[3]). Last timecode written for each packet type will be returned in this same array.

Returns:

List of AMFPacket objects sorted by timecodes

interleavePackets

```
public static java.util.List interleavePackets(java.util.List audioPackets,
        java.util.List videoPackets,
        java.util.List dataPackets,
        java.util.List audioTCs,
        java.util.List videoTCs,
        java.util.List dataTCs,
        java.util.List dataTypes,
        long[] currentTCs)
```

This is a utility function primarily used for IMediaWriters. It is a way of taking the discrete audio/video/data packets and timecodes and interleaving them into a single list of AMFPacket objects. The currentTCs array is an array of longs containing the last timecode for each of the packet types FLV_TCINDEX* (long[3]). This array will be used to calculate the absolute timecode for a given packet. For example if the relative timecode for an audio packet is 26 and the currentTCs value for the audio channel is 1003 then the absolute timecode for that packet will be 1029. The currentTCs array will be updated after this call to reflect the absolute timecode of the last packet processed of each type.

Parameters:

audioPackets - list of audio packets (ByteBuffer)
 videoPackets - list of video packets (ByteBuffer)
 dataPackets - list of data packets (ByteBuffer)
 audioTCs - list of relative audio timecodes (Long)
 videoTCs - list of relative video timecodes (Long)
 dataTCs - list of relative data timecodes (Long)
 dataTypes - list of integer packets types (IVHost.CONTENTTYPE_DATA0, IVHost.CONTENTTYPE_DATA3) - if null assumed to be IVHost.CONTENTTYPE_DATA0
 currentTCs - array of longs containing last TCs written for each packet type FLV_TCINDEX* (long[3]). Last timecode written for each packet type will be returned in this same array.

Returns:

List of AMFPacket objects sorted by timecodes

writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List packetList,
    long tcOffset)
```

Write audio/video/data packets to an .flv file. They will be written in the packetList order.

Parameters:

ds - OutputStream
 packetList - List of AMFPacket objects
 tcOffset - timecode offset

writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    long[] currentTCs)
```

Write a bunch of packets to .flv file all at once. The packets will be sorted by timecode as written

Parameters:

ds - OutputStream
 audioPackets - list of audio packets (ByteBuffer)
 videoPackets - list of video packets (ByteBuffer)
 dataPackets - list of data packets (ByteBuffer)
 audioTCs - list of relative audio timecodes (Long)
 videoTCs - list of relative video timecodes (Long)
 dataTCs - list of relative data timecodes (Long)
 currentTCs - array of longs containing last TCs written for each packet type FLV_TCINDEX* (long[3]). Last timecode written for each packet type will be returned in this same array.

writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    java.util.List dataTypes,
    long[] currentTCs)
```

Write a bunch of packets to .flv file all at once. The packets will be sorted by timecode as written

Parameters:

ds - OutputStream
 audioPackets - list of audio packets (ByteBuffer)
 videoPackets - list of video packets (ByteBuffer)
 dataPackets - list of data packets (ByteBuffer)
 audioTCs - list of relative audio timecodes (Long)
 videoTCs - list of relative video timecodes (Long)
 dataTCs - list of relative data timecodes (Long)
 dataTypes - list of integer packets types (IVHost.CONTENTTYPE_DATA0, IVHost.CONTENTTYPE_DATA3) - if null assumed to be IVHost.CONTENTTYPE_DATA0

(continued from last page)

`currentTCs` - array of longs containing last TCs written for each packet type `FLV_TCINDEX*` (`long[3]`). Last timecode written for each packet type will be returned in this same array.

writePackets

```
public static void writePackets(java.io.OutputStream ds,
    java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    java.util.List dataTypes,
    long[] currentTCs,
    IFLVWriterAdjustTimecode dataPacketTimecodeAdjuster)
```

Write a bunch of packets to .flv file all at once. The packets will be sorted by timecode as written

Parameters:

`ds` - OutputStream
`audioPackets` - list of audio packets (ByteBuffer)
`videoPackets` - list of video packets (ByteBuffer)
`dataPackets` - list of data packets (ByteBuffer)
`audioTCs` - list of relative audio timecodes (Long)
`videoTCs` - list of relative video timecodes (Long)
`dataTCs` - list of relative data timecodes (Long)
`dataTypes` - list of integer packets types (IVHost.CONTENTTYPE_DATA0, IVHost.CONTENTTYPE_DATA3) - if null assumed to be IVHost.CONTENTTYPE_DATA0
`currentTCs` - array of longs containing last TCs written for each packet type `FLV_TCINDEX*` (`long[3]`). Last timecode written for each packet type will be returned
`dataPacketTimecodeAdjuster` - class that implements the `IFLVWriterAdjustTimecode` interface for adjusting timecodes in this same array.

adjustFirstPacketTCs

```
public static long adjustFirstPacketTCs(java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs)
```

Align list of timecode for each data type. Assume first entry in each list is absolute timecode. When done lowest entry in three lists will be zero and other lists will be offset accordingly.

Parameters:

`audioTCs` - list of audio timecodes
`videoTCs` - list of video timecodes
`dataTCs` - list of data timecodes

Returns:

lowest of three absolute timecodes

writeDuration

```
public static void writeDuration(java.io.File file,
    double duration)
```

Write the duration to an existing .flv file. This routine will hunt through the .flv file for the `onMetaData` packet and the duration metadata. It will rewrite the value if found. If not found it will do nothing.

Parameters:

`file` - .flv file
`duration` - new duration value (seconds)

getLastTC

```
public static long getLastTC(java.io.File file)
```

Get the duration of an .flv file. This routine will find the onMetaData packet and the duration metadata and return the value. If not found it will read the last packet in the file and return the timecode of that packet.

Parameters:

file

Returns:

duration (milliseconds)

isVideoKeyFrame

```
public static boolean isVideoKeyFrame(AMFPacket packet)
```

Returns true if the packet is a video key frame

Parameters:

packet - packet

Returns:

true if is video key frame

isVideoCodecConfig

```
public static boolean isVideoCodecConfig(AMFPacket packet)
```

Returns true if the packet is a video codec config packet

Parameters:

packet

Returns:

true if the packet is a video codec config packet

isAudioCodecConfig

```
public static boolean isAudioCodecConfig(AMFPacket packet)
```

Returns true if the packet is a video codec config packet

Parameters:

packet

Returns:

true if the packet is a video codec config packet

getAudioMP3Layer

```
public static int getAudioMP3Layer(AMFPacket packet)
```

Audio marked as MP3 is really MPEG1 Layer 1-3. Only MPEG1 Layer 3 is truly MP3. This function will return the layer number for this packet.

Parameters:

packet - amf packet

(continued from last page)

Returns:

layer number

getAudioCodec

```
public static int getAudioCodec(AMFPacket packet)
```

Get the codec id for this audio packet. Returns IVHost.CODEC_AUDIO_UNKNOWN is unknown or not audio packet

Parameters:

packet - packet

Returns:

codec id IVHost.CODEC_AUDIO_*

getVideoCodec

```
public static int getVideoCodec(AMFPacket packet)
```

Get the codec id for this video packet. Returns IVHost.CODEC_VIDEO_UNKNOWN is unknown or not video packet

Parameters:

packet - packet

Returns:

codec id IVHost.CODEC_VIDEO_*

getVideoTimecodeOffset

```
public static int getVideoTimecodeOffset(AMFPacket packet)
```

Get the timecode offset in milliseconds between the PTS and DTS for this frame.

Parameters:

packet - AMFPacket

Returns:

timecode offset in milliseconds (can be negative)

getVideoTimecodeOffset

```
public static int getVideoTimecodeOffset(byte[] buffer)
```

Get the timecode offset in milliseconds between the PTS and DTS for this frame.

Parameters:

buffer - video packet buffer

Returns:

timecode offset in milliseconds (can be negative)

isVideoKeyFrame

```
public static boolean isVideoKeyFrame(java.nio.ByteBuffer buffer)
```

Returns true if the packet is a video key frame

(continued from last page)

Parameters:

buffer - packet data (only need first two bytes of data)

Returns:

true if is video key frame

isVideoKeyFrame

```
public static boolean isVideoKeyFrame(byte[] buffer)
```

Returns true if the packet is a video key frame

Parameters:

buffer - packet data (only need first two bytes of data)

Returns:

true if is video key frame

isVideoKeyFrame

```
public static boolean isVideoKeyFrame(int[] chunkHeaderValues)
```

Returns true if the packet is a video key frame

Parameters:

chunkHeaderValues - chunk header values returned by FLVUtils.readChunkHeader

Returns:

true if is video key frame

updateOnCuePointTimecode

```
public static AMFPacket updateOnCuePointTimecode(AMFPacket packet,  
long timecode)
```

updateOnCuePointTimecode

```
public static java.nio.ByteBuffer updateOnCuePointTimecode(java.nio.ByteBuffer data,  
int dataType,  
long timecode)
```

isOnMetadataPacket

```
public static boolean isOnMetadataPacket(AMFPacket packet)
```

Returns true if packet is onMetaData or [@setDataFrame, onMetaData] data packet.

Parameters:

packet - packet

Returns:

true if onMetaData packet

com.wowza.util Class HTTPUtils

java.lang.Object

└─com.wowza.util.HTTPUtils

public class **HTTPUtils**
extends Object

HTTPUtils: utility class for making http requests.

Field Summary

public static final	COOKIEFORMAT
---------------------	------------------------------

Constructor Summary

public	HTTPUtils()
--------	-----------------------------

Method Summary

static String	assembleQueryStr (java.util.Map queryMap) Assemble a map of name value pairs into a single query string.
static String	formatDeleteCookie (String name, String path, String domain) Formats a cookie header value that is in the past to delete a cookie
static String	formatSetCookie (String name, String value, int timeoffset, String path, String domain, boolean isSecure) Format a HTTP header Set-Cookie value
static byte[]	HTTPRequestToByteArray (String inUrl, String method, String data, java.util.Map headers) Make a HTTP request and return the result as a byte array
static byte[]	HTTPRequestToByteArray (String inUrl, String method, String data, java.util.Map inHeaders, java.util.Map outHeaders, long dataLimit) Make a HTTP request and return the result as a byte array
static boolean	HTTPRequestToFile (java.io.File file, String inUrl, String method, String data, java.util.List headers) Make a HTTP request and have the result saved to a file.
static java.util.List	splitCookie (String str) Breaks Cookies header value into a list of name/value pairs.
static String[]	splitPragmas (String str) Split HTTP Pragma values at commas that separate values.
static java.util.Map	splitQueryStr (String queryStr) Split a query string into a map and URL decode the values

static String

[statusCodeToStr](#)(int statusCode)

Convert an HTTP status code to a string

Methods inherited from class `java.lang.Object`

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

COOKIEDATEFORMAT

public static final org.apache.commons.lang.time.FastDateFormat **COOKIEDATEFORMAT**

Constructors

HTTPUtils

public **HTTPUtils**()

Methods

HTTPRequestToFile

```
public static boolean HTTPRequestToFile(java.io.File file,
    String inUrl,
    String method,
    String data,
    java.util.List headers)
```

Make a HTTP request and have the result saved to a file.

Parameters:

file - destination
inUrl - url (will work with http and https)
method - method (POST, GET)
data - post data
headers - map of headers (Content-type...)

Returns:

true if successful

HTTPRequestToByteArray

```
public static byte[] HTTPRequestToByteArray(String inUrl,
    String method,
    String data,
    java.util.Map headers)
```

Make a HTTP request and return the result as a byte array

Parameters:

inUrl - url (will work with http and https)

(continued from last page)

method - method (POST, GET)
data - post data
headers - map of headers (Content-type...)

Returns:

byte array of result or null if not successful

HTTPRequestToByteArray

```
public static byte[] HTTPRequestToByteArray(String inUrl,  
      String method,  
      String data,  
      java.util.Map inHeaders,  
      java.util.Map outHeaders,  
      long dataLimit)
```

Make a HTTP request and return the result as a byte array

Parameters:

inUrl - url (will work with http and https)
method - method (POST, GET)
data - data
inHeaders - map of headers (Content-type...)
outHeaders - response headers
dataLimit - maximum number of bytes to read, zero for no limit

Returns:

byte array of result or null if not successful

assembleQueryStr

```
public static String assembleQueryStr(java.util.Map queryMap)
```

Assemble a map of name value pairs into a single query string. URL encode query string values.

Parameters:

queryMap - name value pairs

Returns:

query string

splitQueryStr

```
public static java.util.Map splitQueryStr(String queryStr)
```

Split a query string into a map and URL decode the values

Parameters:

queryStr - query string

Returns:

map of name value pairs

splitPragmas

```
public static String[] splitPragmas(String str)
```

(continued from last page)

Split HTTP Pragma values at commas that separate values. It deals with internal commas in strings. Example:

```
no-cache, client-id=1485578017, features="seekable, stridable", timeout=6
```

Result:

```
no-cache  
client-id=1485578017  
features="seekable, stridable"  
timeout=6
```

Parameters:

str - Pragma value

Returns:

array of strings broken at commas

splitCookie

```
public static java.util.List splitCookie(String str)
```

Breaks Cookies header value into a list of name/value pairs. The Cookie string: "name1=value1;name2;name1=value3" is returned as: List(item({"name1", "value1"}), item("name2", null), item("name1", "value3"))

Parameters:

str - input string

Returns:

List of name value pairs

formatDeleteCookie

```
public static String formatDeleteCookie(String name,  
    String path,  
    String domain)
```

Formats a cookie header value that is in the past to delete a cookie

Parameters:

name - variable name
path - path
domain - domain

Returns:

formatted cookie string

formatSetCookie

```
public static String formatSetCookie(String name,  
    String value,  
    int timeoffset,  
    String path,  
    String domain,  
    boolean isSecure)
```

Format a HTTP header Set-Cookie value

Parameters:

name - variable name
value - variable value - null if no value
timeoffset - expiration time in seconds
path - cookie path
domain - cookie domain
isSecure - is cookie secure

Returns:

formatted cookie string

statusCodeToStr

```
public static String statusCodeToStr(int statusCode)
```

Convert an HTTP status code to a string

Parameters:

statusCode - HTTP status code

Returns:

string

com.wowza.util Interface IBandwidthThrottler

public interface **IBandwidthThrottler**
extends

Method Summary

long	<code>getBytesAllocation</code> (long request) Requests bytes from the bandwidth throttler interface.
------	--------------------------------------------------------------------------------------------------------------------------

Methods

getBytesAllocation

public long **getBytesAllocation**(long request)

Requests bytes from the bandwidth throttler interface. Return value is the number of bytes allocated

Parameters:

request - request number of bytes

Returns:

allocated number of bytes

com.wowza.util Interface IFileProcess

public interface **IFileProcess**
extends

Used by FileUtils.traverseDirectory

Method Summary

void	onFile (java.io.File file) Triggered for each file encountered in FileUtils.traverseDirectory
------	------------------------------------------------------------------------------------------------------------------

Methods

onFile

public void **onFile**(java.io.File file)

Triggered for each file encountered in FileUtils.traverseDirectory

Parameters:

file - file descriptor

com.wowza.util Class IOPerformanceCounter

java.lang.Object

└-com.wowza.util.IOPerformanceCounter

public class **IOPerformanceCounter**
extends Object

IOPerformanceCounter: data object that tracks the server performance of a particular component (client, vHost, server, stream). It tracks bytes and messages sent to and from the object being measured.

Constructor Summary

public	<u>IOPerformanceCounter</u> () Create an empty performance counter.
--------	-----------------------------------------------------------------------------------------

Method Summary

void	<u>add</u> (<u>IOPerformanceCounter</u> value) Add (value) to this counter.
void	<u>addDifference</u> (<u>IOPerformanceCounter</u> current, <u>IOPerformanceCounter</u> last) Add the result of (current-last) to this counter.
void	<u>clear</u> () Clear or reset this counter back to zero.
<u>IOPerformanceCounter</u>	<u>clone</u> () Create a deep clone (copy) if this object.
void	<u>doSet</u> (<u>IOPerformanceCounter</u> value) Set this object to value.
void	<u>dummy</u> ()
long	<u>getFileInBytes</u> () Get file in bytes
double	<u>getFileInBytesRate</u> () Get estimate of file byte-in byte rate.
long	<u>getFileOutBytes</u> () Get file byte-out bytes (not implemented)
double	<u>getFileOutBytesRate</u> () Get estimate of file byte-out message byte rate (not implemented).
long	<u>getMessagesInBytes</u> () Get byte-in bytes
double	<u>getMessagesInBytesRate</u> () Get estimate of byte-in message byte rate.

long	<u>getMessagesInCount</u> () Get byte-in message count
long	<u>getMessagesInCountRate</u> () Get estimate of byte-in message count rate.
long	<u>getMessagesLossBytes</u> () Get byte-loss bytes
double	<u>getMessagesLossBytesRate</u> () Get estimate of byte-loss message byte rate.
long	<u>getMessagesLossCount</u> () Get byte-loss message count
long	<u>getMessagesLossCountRate</u> () Get estimate of byte-loss message count rate.
long	<u>getMessagesOutBytes</u> () Get byte-out bytes
double	<u>getMessagesOutBytesRate</u> () Get estimate of byte-out message byte rate.
long	<u>getMessagesOutCount</u> () Get byte-out message count
long	<u>getMessagesOutCountRate</u> () Get estimate of byte-out message count rate.
long	<u>incrementBytesIn</u> (long bytes) Increment bytes-in by bytes and increment message count by 0.
long	<u>incrementBytesLoss</u> (long bytes) Increment bytes-loss by bytes and increment message count by 0.
long	<u>incrementBytesOut</u> (long bytes) Increment bytes-out by bytes and increment message count by 0.
long	<u>incrementFileIn</u> (long bytes) Increment file-bytes-in by bytes.
long	<u>incrementFileOut</u> (long bytes) Increment file bytes-out by bytes.
long	<u>incrementMessagesIn</u> () Increment byte-in message count by 1.
long	<u>incrementMessagesIn</u> (long bytes) Increment bytes-in by bytes and increment message count by 1.
long	<u>incrementMessagesIn</u> (long bytes, long count) Increment bytes-in by bytes and message count by count.
long	<u>incrementMessagesLoss</u> () Increment byte-loss message count by 1.
long	<u>incrementMessagesLoss</u> (long bytes) Increment bytes-loss by bytes and increment message count by 1.

long	<code>incrementMessagesLoss</code> (long bytes, long count) Increment bytes-loss by bytes and message count by count.
long	<code>incrementMessagesOut</code> () Increment byte-out message count by 1.
long	<code>incrementMessagesOut</code> (long bytes) Increment bytes-out by bytes and increment message count by 1.
long	<code>incrementMessagesOut</code> (long bytes, long count) Increment bytes-out by bytes and message count by count.
boolean	<code>isDebugLog</code> ()
void	<code>setDebugLog</code> (boolean debugLog)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

IOPerformanceCounter

```
public IOPerformanceCounter()
```

Create an empty performance counter.

Methods

clone

```
public IOPerformanceCounter clone()
```

Create a deep clone (copy) if this object.

addDifference

```
public void addDifference(IOPerformanceCounter current,  
                          IOPerformanceCounter last)
```

Add the result of (current-last) to this counter. Used internally to efficiently track object performance on a timer.

Parameters:

current - current counter

last - last counter

clear

```
public void clear()
```

Clear or reset this counter back to zero.

(continued from last page)

add

```
public void add(IOPerformanceCounter value)
```

Add (value) to this counter.

Parameters:

value - value to add

doSet

```
public void doSet(IOPerformanceCounter value)
```

Set this object to value.

Parameters:

value - value to set

incrementMessagesIn

```
public long incrementMessagesIn(long bytes)
```

Increment bytes-in by bytes and increment message count by 1.

Parameters:

bytes - number of bytes

Returns:

bytes-in bytes

incrementFileIn

```
public long incrementFileIn(long bytes)
```

Increment file-bytes-in by bytes.

Parameters:

bytes - number of bytes

Returns:

bytes-in bytes

incrementMessagesIn

```
public long incrementMessagesIn(long bytes,  
    long count)
```

Increment bytes-in by bytes and message count by count.

Parameters:

bytes - number of bytes
count - number of messages

Returns:

bytes-in bytes

(continued from last page)

incrementBytesIn

```
public long incrementBytesIn(long bytes)
```

Increment bytes-in by bytes and increment message count by 0.

Parameters:

bytes

Returns:

bytes-in bytes

incrementMessagesIn

```
public long incrementMessagesIn()
```

Increment byte-in message count by 1.

Returns:

bytes-in message count

incrementMessagesOut

```
public long incrementMessagesOut(long bytes)
```

Increment bytes-out by bytes and increment message count by 1.

Parameters:

bytes - number of bytes

Returns:

bytes-out bytes

incrementFileOut

```
public long incrementFileOut(long bytes)
```

Increment file bytes-out by bytes.

Parameters:

bytes - number of bytes

Returns:

bytes-out bytes

incrementMessagesLoss

```
public long incrementMessagesLoss(long bytes)
```

Increment bytes-loss by bytes and increment message count by 1.

Parameters:

bytes - number of bytes

Returns:

bytes-loss bytes

(continued from last page)

incrementMessagesOut

```
public long incrementMessagesOut(long bytes,  
    long count)
```

Increment bytes-out by bytes and message count by count.

Parameters:

bytes - number of bytes
count - number of messages

Returns:

bytes-out bytes

incrementMessagesLoss

```
public long incrementMessagesLoss(long bytes,  
    long count)
```

Increment bytes-loss by bytes and message count by count.

Parameters:

bytes - number of bytes
count - number of messages

Returns:

bytes-loss bytes

incrementBytesOut

```
public long incrementBytesOut(long bytes)
```

Increment bytes-out by bytes and increment message count by 0.

Parameters:

bytes

Returns:

bytes-out bytes

incrementBytesLoss

```
public long incrementBytesLoss(long bytes)
```

Increment bytes-loss by bytes and increment message count by 0.

Parameters:

bytes

Returns:

bytes-loss bytes

incrementMessagesOut

```
public long incrementMessagesOut()
```

Increment byte-out message count by 1.

Returns:

(continued from last page)

bytes-out message count

incrementMessagesLoss

```
public long incrementMessagesLoss()
```

Increment byte-loss message count by 1.

Returns:

bytes-loss message count

getMessagesInCount

```
public long getMessagesInCount()
```

Get byte-in message count

Returns:

byte-in message count

getMessagesOutCount

```
public long getMessagesOutCount()
```

Get byte-out message count

Returns:

byte-out message count

getMessagesLossCount

```
public long getMessagesLossCount()
```

Get byte-loss message count

Returns:

byte-loss message count

getMessagesInBytes

```
public long getMessagesInBytes()
```

Get byte-in bytes

Returns:

byte-in bytes

getFileInBytes

```
public long getFileInBytes()
```

Get file in bytes

Returns:

file in bytes

(continued from last page)

getMessagesOutBytes

```
public long getMessagesOutBytes()
```

Get byte-out bytes

Returns:

byte-out bytes

getFileOutBytes

```
public long getFileOutBytes()
```

Get file byte-out bytes (not implemented)

Returns:

byte-out bytes

getMessagesLossBytes

```
public long getMessagesLossBytes()
```

Get byte-loss bytes

Returns:

byte-loss bytes

getMessagesInCountRate

```
public long getMessagesInCountRate()
```

Get estimate of byte-in message count rate.

Returns:

estimate of byte-in message count rate (messages per second)

getMessagesOutCountRate

```
public long getMessagesOutCountRate()
```

Get estimate of byte-out message count rate.

Returns:

estimate of byte-out message count rate (messages per second)

getMessagesLossCountRate

```
public long getMessagesLossCountRate()
```

Get estimate of byte-loss message count rate.

Returns:

estimate of byte-loss message count rate (messages per second)

getMessagesInBytesRate

```
public double getMessagesInBytesRate()
```

(continued from last page)

Get estimate of byte-in message byte rate.

Returns:

estimate of byte-in message byte rate (bytes per second)

getFileInBytesRate

```
public double getFileInBytesRate()
```

Get estimate of file byte-in byte rate.

Returns:

estimate of file byte-in byte rate (bytes per second)

getMessagesOutBytesRate

```
public double getMessagesOutBytesRate()
```

Get estimate of byte-out message byte rate.

Returns:

estimate of byte-out message byte rate (bytes per second)

getFileOutBytesRate

```
public double getFileOutBytesRate()
```

Get estimate of file byte-out message byte rate (not implemented).

Returns:

estimate of file byte-out message byte rate (bytes per second)

getMessagesLossBytesRate

```
public double getMessagesLossBytesRate()
```

Get estimate of byte-loss message byte rate.

Returns:

estimate of byte-loss message byte rate (bytes per second)

dummy

```
public void dummy()
```

isDebugLog

```
public boolean isDebugLog()
```

setDebugLog

```
public void setDebugLog(boolean debugLog)
```

com.wowza.util Class MD5DigestUtils

java.lang.Object

└─com.wowza.util.MD5DigestUtils

public class **MD5DigestUtils**
extends Object

MD5DigestUtils: MD5 hash utilities.

Field Summary

protected static	md5Digest
protected static	md5Lock

Constructor Summary

public	MD5DigestUtils()
--------	----------------------------------

Method Summary

static String	generateAuth (String method, String uri, String username, String password, String realm, String nonce) Generate an HTTP authorization response
static String	generateAuth (String a2Hash, String alHash, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	generateAuth (String method, String uri, String alHash, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	generateAuth (String method, String uri, String username, String password, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	generateAuthHTTP (String method, String uri, String username, String password, String realm, String nonce, String qop, String nonceCount, String cnonce) Generate an HTTP authorization response
static String	generateHash (String value) Generate MD5 hash
static byte[]	generateHashBytes (byte[] value) Generate MD5 hash
static byte[]	generateHashBytes (String value) Generate MD5 hash

Methods inherited from class `java.lang.Object``clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Fields

md5Digest

`protected static java.security.MessageDigest md5Digest`

md5Lock

`protected static java.lang.Object md5Lock`

Constructors

MD5DigestUtils

`public MD5DigestUtils()`

Methods

generateAuth

```
public static String generateAuth(String method,
    String uri,
    String username,
    String password,
    String realm,
    String nonce)
```

Generate an HTTP authorization response

Parameters:

method - method
uri - URI
username - username
password - password
realm - realm
nonce - nonce

Returns:

auth response

(continued from last page)

generateAuth

```
public static String generateAuth(String method,  
    String uri,  
    String username,  
    String password,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

Parameters:

method - method
uri - URI
username - username
password - password
realm - realm
nonce - nonce
qop - qop
nonceCount - nonceCount
cnonce - cnonce

Returns:

auth response

generateAuthHTTP

```
public static String generateAuthHTTP(String method,  
    String uri,  
    String username,  
    String password,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

Parameters:

method - method
uri - URI
username - username
password - password
realm - realm
nonce - nonce
qop - qop
nonceCount - nonceCount
cnonce - cnonce

Returns:

response

(continued from last page)

generateAuth

```
public static String generateAuth(String method,  
    String uri,  
    String alHash,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

Parameters:

method - method
uri - URI
alHash - alHash
realm - realm
nonce - nonce
qop - qop
nonceCount - nonceCount
cnonce - cnonce

Returns:

auth

generateAuth

```
public static String generateAuth(String a2Hash,  
    String alHash,  
    String realm,  
    String nonce,  
    String qop,  
    String nonceCount,  
    String cnonce)
```

Generate an HTTP authorization response

Parameters:

a2Hash - a2Hash
alHash - alHash
realm - realm
nonce - nonce
qop - qop
nonceCount - nonceCount
cnonce - cnonce

Returns:

auth

generateHashBytes

```
public static byte[] generateHashBytes(byte[] value)
```

Generate MD5 hash

Parameters:

value - byte array to hash

Returns:

byte array result

generateHashBytes

```
public static byte[] generateHashBytes(String value)
```

Generate MD5 hash

Parameters:

value - in string converted to byte array (UTF-8)

Returns:

byte array result

generateHash

```
public static String generateHash(String value)
```

Generate MD5 hash

Parameters:

value - in string converted to byte array (UTF-8)

Returns:

hash as binhex string

com.wowza.util Class MediaUtils

java.lang.Object

└─com.wowza.util.MediaUtils

public class **MediaUtils**
extends Object

MediaUtils: Media utilities.

Constructor Summary

public	MediaUtils()
--------	------------------------------

Method Summary

static String	audioCodecTypeToString (int codecType) Audio codec ID to string.
static String	videoCodecTypeToString (int codecType) Video codec ID to string.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

MediaUtils

public **MediaUtils**()

Methods

audioCodecTypeToString

public static String **audioCodecTypeToString**(int codecType)

Audio codec ID to string. See IVHost.CODEC_AUDIO_*

Parameters:

codecType - codec id. See IVHost.CODEC_AUDIO_*

Returns:

codec string

videoCodecTypeToString

```
public static String videoCodecTypeToString(int codecType)
```

Video codec ID to string. See IVHost.CODEC_VIDEO_*

Parameters:

codecType - codec id. See IVHost.CODEC_VIDEO_*

Returns:

codec string

com.wowza.util Class NetworkUtils

```
java.lang.Object
|
+-com.wowza.util.NetworkUtils
```

```
public class NetworkUtils
extends Object
```

NetworkUtils: Networking utilities.

Constructor Summary

public	NetworkUtils()
--------	--------------------------------

Method Summary

static boolean	isAddressMulticast(String IpAddress) Returns true if IP address is multicast address
----------------	---------------------------------------------------------------------------------------------------------

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

NetworkUtils

```
public NetworkUtils()
```

Methods

isAddressMulticast

```
public static boolean isAddressMulticast(String IpAddress)
```

Returns true if IP address is multicast address

Parameters:

IpAddress - IP address

Returns:

true if IP address is multicast address

com.wowza.util Interface NoMBean

public interface **NoMBean**
extends Annotation

Annotation for excluding a method from the JMX interface. Below is an example of how it would be used

```
import com.wowza.util.NoMBean;
import com.wowza.wms.module.*;

class MyClass extends ModuleBase
{
    @NoMBean public void myMethod()
    {
    }
}
```

Methods inherited from interface <code>java.lang.annotation.Annotation</code>

<code>annotationType, equals, hashCode, toString</code>

com.wowza.util Class StringUtils

java.lang.Object

└─com.wowza.util.StringUtils

public class **StringUtils**
extends Object

StringUtils: utility class of String utilities.

Constructor Summary

public	StringUtils()
--------	-------------------------------

Method Summary

static boolean	equals (String s1, String s2) Checks if 2 strings are equals, accounting for null cases.
static boolean	isEmpty (String s) Checks if string is empty, handling null String case.
static int	length (String s) Returns string length, handling null String case as length of 0.
static String	stampToString (long stamp) Convert a duration (milliseconds) to a formatted string.
static String	valueOf (String s) Returns string, handling null String case as "".

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

StringUtils

public **StringUtils**()

Methods

isEmpty

public static boolean **isEmpty**(String s)

(continued from last page)

Checks if string is empty, handling null String case.

Parameters:

s

Returns:

false if string is null or "", true otherwise

length

```
public static int length(String s)
```

Returns string length, handling null String case as length of 0.

Parameters:

s

Returns:

0 if string is null, or length of string.

valueOf

```
public static String valueOf(String s)
```

Returns string, handling null String case as "".

Parameters:

s

Returns:

"" if string is null, or string value.

stampToString

```
public static String stampToString(long stamp)
```

Convert a duration (milliseconds) to a formatted string.

Parameters:

stamp - duration (milliseconds)

Returns:

formatted string (example: 3 days 4 minutes 1 seconds)

equals

```
public static boolean equals(String s1,  
    String s2)
```

Checks if 2 strings are equals, accounting for null cases.

Parameters:

s1 - string one

s2 - string 2

Returns:

true if the 2 strings are equal

com.wowza.util Class SystemUtils

java.lang.Object

└─com.wowza.util.SystemUtils

public class **SystemUtils**
extends Object

Nested Class Summary

class	SystemUtils.ReplaceItem SystemUtils.ReplaceItem
-------	--------------------------------------------------------------------

Field Summary

public static final	defaultLocale
public static final	defaultTimeZone
public static final	gmtTimeZone
protected static final	msb0baseTime Value: 2085978496000
protected static final	msblbaseTime Value: -2208988800000

Constructor Summary

public	SystemUtils()
--------	-------------------------------

Method Summary

static void	addBouncyCastleSecurityProvider() Load bouncy castle providers, Internal use.
static String	expandEnvironmentVariables (String inValue) Expand system level Java properties in a String in the form \${property-name}
static String	expandEnvironmentVariables (String inValue, java.util.Map valueMap) Expand system level Java properties in a String in the form \${property-name}.
static long	getCpuTime () Get CPU time in nanoseconds.
static byte[]	getMACAddress () Get MAC address of localhost interface (only works on Java 6 or greater)

static long	<code>getSystemTime()</code> Get system time in nanoseconds.
static long	<code>getUserTime()</code> Get user time in nanoseconds.
static long	<code>toNTPTime(long t)</code> Convert a timecode value in milliseconds to NTP time

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

`defaultTimeZone`

`public static final java.util.TimeZone defaultTimeZone`

`gmtTimeZone`

`public static final java.util.TimeZone gmtTimeZone`

`defaultLocale`

`public static final java.util.Locale defaultLocale`

`msb0baseTime`

`protected static final long msb0baseTime`

Constant value: **2085978496000**

`msb1baseTime`

`protected static final long msb1baseTime`

Constant value: **-2208988800000**

Constructors

`SystemUtils`

`public SystemUtils()`

(continued from last page)

Methods

expandEnvironmentVariables

```
public static String expandEnvironmentVariables(String inValue)
```

Expand system level Java properties in a String in the form `${property-name}`

Parameters:

inValue - string with properties

Returns:

expanded string

expandEnvironmentVariables

```
public static String expandEnvironmentVariables(String inValue,  
        java.util.Map valueMap)
```

Expand system level Java properties in a String in the form `${property-name}`. You can also pass in a map of name/value pairs that will expand the list of available properties

Parameters:

inValue - string with properties

valueMap - name/value pair map

Returns:

expanded string

getMACAddress

```
public static byte[] getMACAddress()
```

Get MAC address of localhost interface (only works on Java 6 or greater)

Returns:

MAC address of localhost interface

addBouncyCastleSecurityProvider

```
public static void addBouncyCastleSecurityProvider()
```

Load bouncy castle providers, Internal use.

toNTPTime

```
public static long toNTPTime(long t)
```

Convert a timecode value in milliseconds to NTP time

Parameters:

t - timecode value in milliseconds

Returns:

NTP time

(continued from last page)

getCpuTime

```
public static long getCpuTime()
```

Get CPU time in nanoseconds.

getUserTime

```
public static long getUserTime()
```

Get user time in nanoseconds.

getSystemTime

```
public static long getSystemTime()
```

Get system time in nanoseconds.

com.wowza.util Class SystemUtils.ReplaceItem

java.lang.Object

└─com.wowza.util.SystemUtils.ReplaceItem

public static class **SystemUtils.ReplaceItem**
extends Object

Field Summary

public	end
public	newValue
public	start

Constructor Summary

public	SystemUtils.ReplaceItem (int start, int stop, String newValue)
--------	--------------------------------------------------------------------------------

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

start

public int **start**

end

public int **end**

newValue

public java.lang.String **newValue**

Constructors

(continued from last page)

SystemUtils.ReplaceItem

```
public SystemUtils.ReplaceItem(int start,  
                               int stop,  
                               String newValue)
```

com.wowza.util Class URLUtils

java.lang.Object

└─com.wowza.util.URLUtils

public final class **URLUtils**
extends Object

Class to deal with URLs

Constructor Summary

public	URLUtils()
--------	----------------------------

Method Summary

static String	appendParamsToUrl (String url, String params) Convenience call to add parameters to a url.
static String	decodeValue (String val) Wrapper for URLDecoder.decode(val, "UTF-8");
static String	encodeValue (String val) Wrapper for URLEncoder.encode(val, "UTF-8");
static String	getParamValue (java.util.Map params, String key) Helper funtion to get single value from multiple value parameter Map
static java.util.Map	parseQueryStr (String queryString, boolean doDecode) Parse query string part of url into Map of Lists (to support multiple values) of query parameters
static String	pathToFileURL (String basePath) Convert a path to a url (file://[path])
static String	urlToId (java.net.URL url) Create a MD5 message digest hash of a url

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

URLUtils

public **URLUtils**()

(continued from last page)

Methods

pathToFileURL

```
public static String pathToFileURL(String basePath)
```

Convert a path to a url (file://[path])

Parameters:

basePath - path

Returns:

file url

urlToId

```
public static String urlToId(java.net.URL url)
```

Create a MD5 message digest hash of a url

Parameters:

url - url to hash

Returns:

hashed url

appendParamsToUrl

```
public static String appendParamsToUrl(String url,  
    String params)
```

Convenience call to add parameters to a url. If already has ? add &.

Parameters:

url - input url

params - parameters in the form param1=val1¶m2=val2

Returns:

appended url

encodeValue

```
public static String encodeValue(String val)
```

Wrapper for URLEncoder.encode(val, "UTF-8");

Parameters:

val - value to encode

Returns:

encoded value

decodeValue

```
public static String decodeValue(String val)
```

Wrapper for URLDecoder.decode(val, "UTF-8");

(continued from last page)

Parameters:

val - value to decode

Returns:decoded value

parseQueryStr

```
public static java.util.Map parseQueryStr(String queryString,  
                                           boolean doDecode)
```

Parse query string part of url into Map of Lists (to support multiple values) of query parameters

Parameters:

queryString - query string

doDecode - true to use URLDecoder.decode() to decode parameters

Returns:Map of Lists

getParamValue

```
public static String getParamValue(java.util.Map params,  
                                     String key)
```

Helper funtion to get single value from multiple value parameter Map

Parameters:

params - params Map

key - key string

Returns:first value

com.wowza.util Class XMLUtils

java.lang.Object

└─com.wowza.util.XMLUtils

public class **XMLUtils**
extends Object

XMLUtils: utility class for parsing XML files.

Constructor Summary

public	XMLUtils()
--------	----------------------------

Method Summary

static org.w3c.dom.Node	getNodeByTagName (org.w3c.dom.Element node, String name) Return a child Node by tag name.
static String	getNodeValue (org.w3c.dom.Node node) Return the text value of a node.
static String	getNodeValueByTagName (org.w3c.dom.Element node, String name) Get a child Node value by tag name.
static boolean	getXMLPropertyBool (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, boolean defaultVal) Get a boolean int value pointed to by xpath or defaultVal if not found.
static double	getXMLPropertyDouble (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, double defaultVal) Get a single double value pointed to by xpath or defaultVal if not found.
static boolean	getXMLPropertyExists (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root)
static int	getXMLPropertyInt (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, int defaultVal) Get a single int value pointed to by xpath or defaultVal if not found.
static long	getXMLPropertyLong (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, long defaultVal) Get a single long value pointed to by xpath or defaultVal if not found.
static String	getXMLPropertyStr (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root) Get a single string value pointed to by xpath or null if not found.
static String	getXMLPropertyStr (javax.xml.xpath.XPath xpath, String xpathStr, org.w3c.dom.Element root, String defaultVal) Get a single string value pointed to by xpath or defaultVal if not found.

static void	loadConfigProperties (org.w3c.dom.Element root, String propertiesXPath, WMSProperties properties) Loads <Properties> elemnt by xpath into properties object.
static void	loadConfigProperties (org.w3c.dom.NodeList resultList, WMSProperties properties) Given a nodeList load children as properties.
static javax.xml.xpath.XPath Factory	newXPathFactory () Get a new XPath factory object.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

XMLUtils

public **XMLUtils**()

Methods

getNodeValueByTagName

public static String **getNodeValueByTagName**(org.w3c.dom.Element node, String name)

Get a child Node value by tag name. Return null if does not exist.

Parameters:

node - parent node
name - tag name

Returns:

node value or null if does not exist

getNodeByTagName

public static org.w3c.dom.Node **getNodeByTagName**(org.w3c.dom.Element node, String name)

Return a child Node by tag name. Return null if does not exist.

Parameters:

node - parent node
name - tag name

Returns:

Node or null if does not exist

(continued from last page)

getNodeValue

```
public static String getNodeValue(org.w3c.dom.Node node)
```

Return the text value of a node. Return concatenated value of all children nodes that are text nodes.

Parameters:

node - parent node

Returns:

concatenated text nodes or empty string if not found or no children

loadConfigProperties

```
public static void loadConfigProperties(org.w3c.dom.Element root,  
    String propertiesXPath,  
    WMSProperties properties)
```

Loads <Properties> elemnt by xpath into properties object.

Parameters:

root - root node

propertiesXPath - xpath to search for <Properties> element

properties - properties to add values to

loadConfigProperties

```
public static void loadConfigProperties(org.w3c.dom.NodeList resultList,  
    WMSProperties properties)
```

Given a nodeList load children as properties.

Parameters:

resultList - node list

properties - properties to add values to

getXMLPropertyStr

```
public static String getXMLPropertyStr(javax.xml.xpath.XPath xpath,  
    String xpathStr,  
    org.w3c.dom.Element root)
```

Get a single string value pointed to by xpath or null if not found.

Parameters:

xpath - XPath interface

xpathStr - xpath string

root - root node to start search

Returns:

single string value pointed to by xpath or null if not found

getXMLPropertyStr

```
public static String getXMLPropertyStr(javax.xml.xpath.XPath xpath,  
    String xpathStr,  
    org.w3c.dom.Element root,  
    String defaultVal)
```

Get a single string value pointed to by xpath or defaultVal if not found.

(continued from last page)

Parameters:

xpath - XPath interface
xpathStr - xpath string
root - node to start search
defaultVal - default value

Returns:

single string value pointed to by xpath or defaultVal if not found

getXMLPropertyExists

```
public static boolean getXMLPropertyExists( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root)
```

getXMLPropertyInt

```
public static int getXMLPropertyInt( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root,
      int defaultVal)
```

Get a single int value pointed to by xpath or defaultVal if not found.

Parameters:

xpath - XPath interface
xpathStr - xpath string
root - node to start search
defaultVal - default value

Returns:

int value or defaultVal if not found

getXMLPropertyLong

```
public static long getXMLPropertyLong( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root,
      long defaultVal)
```

Get a single long value pointed to by xpath or defaultVal if not found.

Parameters:

xpath - XPath interface
xpathStr - xpath string
root - node to start search
defaultVal - default value

Returns:

long value or defaultVal if not found

getXMLPropertyDouble

```
public static double getXMLPropertyDouble( javax.xml.xpath.XPath xpath,
      String xpathStr,
      org.w3c.dom.Element root,
      double defaultVal)
```

(continued from last page)

Get a single double value pointed to by xpath or defaultVal if not found.

Parameters:

xpath - XPath interface
xpathStr - xpath string
root - node to start search
defaultVal - default value

Returns:

double value or defaultVal if not found

getXMLPropertyBool

```
public static boolean getXMLPropertyBool( javax.xml.xpath.XPath xpath,  
    String xpathStr,  
    org.w3c.dom.Element root,  
    boolean defaultVal )
```

Get a boolean int value pointed to by xpath or defaultVal if not found.

Parameters:

xpath - XPath interface
xpathStr - xpath string
root - node to start search
defaultVal - default value

Returns:

boolean value or defaultVal if not found

newXPathFactory

```
public static javax.xml.xpath.XPathFactory newXPathFactory()
```

Get a new XPath factory object. There is a bug in certain implementations of the Sun VM that forces an explicit creation of the "com.sun.org.apache.xpath.internal.jaxp.XPathFactoryImpl". This method will try the correct method for creation and if fails will directly create "com.sun.org.apache.xpath.internal.jaxp.XPathFactoryImpl" object.

Returns:

XPathFactory or null if not found

Package

com.wowza.wms.amf

com.wowza.wms.amf

Class AMF3Utils

java.lang.Object

└─com.wowza.wms.amf.AMF3Utils

public class **AMF3Utils**
extends Object

AMF3 utilities

Constructor Summary

public	AMF3Utils()
--------	-----------------------------

Method Summary

static java.util.Date	deserializeDate (java.nio.ByteBuffer data) Deserialize date type
static int	deserializeInt (java.nio.ByteBuffer data) Deserialize int
static String	deserializeString (java.nio.ByteBuffer data) Deserialize string
static String	deserializeString (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Deserialize string
static String	deserializeString (java.nio.ByteBuffer data, int utflen) Deserialize string
static int	serializeDate (java.io.DataOutputStream out, java.util.Date date) Serialize a date object
static int	serializeInt (java.io.DataOutputStream out, int val) Serialize int value
static int	serializeString (java.io.DataOutputStream out, String str) Serialize a string value
static int	serializeStringNoLength (java.io.DataOutputStream out, String str) Serialize string but do not write the length
static void	serializeZeroLengthString (java.io.DataOutputStream out) Serialize empty string

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AMF3Utils

```
public AMF3Utils()
```

Methods

deserializeDate

```
public static java.util.Date deserializeDate(java.nio.ByteBuffer data)
```

Deserialize date type

Parameters:

data - buffer

Returns:

date

serializeDate

```
public static int serializeDate(java.io.DataOutputStream out,  
    java.util.Date date)
```

Serialize a date object

Parameters:

out - output stream

date - date

Returns:

number of bytes written

deserializeInt

```
public static int deserializeInt(java.nio.ByteBuffer data)
```

Deserialize int

Parameters:

data - buffer

Returns:

int value

serializeInt

```
public static int serializeInt(java.io.DataOutputStream out,  
    int val)
```

Serialize int value

Parameters:

(continued from last page)

out - output stream
val - int value

Returns:
number of bytes written

deserializeString

```
public static String deserializeString(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)  
    throws java.io.IOException
```

Deserialize string

Parameters:
data - data
context - AMF context

Returns:
string value

Throws:
IOException

deserializeString

```
public static String deserializeString(java.nio.ByteBuffer data)  
    throws java.io.IOException
```

Deserialize string

Parameters:
data - data

Returns:
string value

Throws:
IOException

deserializeString

```
public static String deserializeString(java.nio.ByteBuffer data,  
    int utflen)  
    throws java.io.IOException
```

Deserialize string

Parameters:
data - data
utflen - len of the string

Returns:
string value

Throws:
IOException

(continued from last page)

serializeZeroLengthString

```
public static void serializeZeroLengthString(java.io.DataOutputStream out)
```

Serialize empty string

Parameters:

out - output stream

serializeStringNoLength

```
public static int serializeStringNoLength(java.io.DataOutputStream out,  
    String str)  
throws java.io.IOException
```

Serialize string but do not write the length

Parameters:

out - output stream

str - string value

Returns:

number of bytes written

Throws:

IOException

serializeString

```
public static int serializeString(java.io.DataOutputStream out,  
    String str)  
throws java.io.IOException
```

Serialize a string value

Parameters:

out - output stream

str - string value

Returns:

number of bytes written

Throws:

IOException

com.wowza.wms.amf

Class AMFData

```
java.lang.Object
```

```
└--com.wowza.wms.amf.AMFData
```

Direct Known Subclasses:

[AMFDataObj](#), [AMFDataList](#), [AMFDataItem](#), [AMFDataByteArray](#), [AMFDataArray](#)

```
public abstract class AMFData
extends Object
```

Base abstract class for data in Action Message Format (AMF). Data is sent between the Flash client and the Wowza Media Server using the AMF format. This class cannot be instantiated. It serves as the base class for all AMFData objects.

Field Summary

public static final	AMF_LEVEL0 Value: 0
public static final	AMF_LEVEL3 Value: 3
public static final	DATA_TYPE_AMF3 Value: 17
public static final	DATA_TYPE_AMF3_ARRAY Value: 9
public static final	DATA_TYPE_AMF3_BOOLEAN_FALSE Value: 2
public static final	DATA_TYPE_AMF3_BOOLEAN_TRUE Value: 3
public static final	DATA_TYPE_AMF3_BYTEARRAY Value: 12
public static final	DATA_TYPE_AMF3_DATE Value: 8
public static final	DATA_TYPE_AMF3_INTEGER Value: 4
public static final	DATA_TYPE_AMF3_NULL Value: 1

public static final	<u>DATA_TYPE_AMF3_NUMBER</u> Value: 5
public static final	<u>DATA_TYPE_AMF3_OBJECT</u> Value: 10
public static final	<u>DATA_TYPE_AMF3_STRING</u> Value: 6
public static final	<u>DATA_TYPE_AMF3_UNDEFINED</u> Value: 0
public static final	<u>DATA_TYPE_AMF3_XML_LEGACY</u> Value: 7
public static final	<u>DATA_TYPE_AMF3_XML_TOP</u> Value: 11
public static final	<u>DATA_TYPE_ARRAY</u> Value: 10
public static final	<u>DATA_TYPE_AS_OBJECT</u> Value: 13
public static final	<u>DATA_TYPE_BOOLEAN</u> Value: 1
public static final	<u>DATA_TYPE_BYTEARRAY</u> Value: 33
public static final	<u>DATA_TYPE_CUSTOM_CLASS</u> Value: 16
public static final	<u>DATA_TYPE_DATE</u> Value: 11
public static final	<u>DATA_TYPE_INTEGER</u> Value: 32
public static final	<u>DATA_TYPE_LONG_STRING</u> Value: 12
public static final	<u>DATA_TYPE_MIXED_ARRAY</u> Value: 8
public static final	<u>DATA_TYPE_MOVIE_CLIP</u> Value: 4

public static final	DATA_TYPE_NULL Value: 5
public static final	DATA_TYPE_NUMBER Value: 0
public static final	DATA_TYPE_OBJECT Value: 3
public static final	DATA_TYPE_OBJECT_END Value: 9
public static final	DATA_TYPE_RECORDSET Value: 14
public static final	DATA_TYPE_REFERENCE_OBJECT Value: 7
public static final	DATA_TYPE_STRING Value: 2
public static final	DATA_TYPE_UNDEFINED Value: 6
public static final	DATA_TYPE_UNKNOWN Value: -1
public static final	DATA_TYPE_XML Value: 15
public static final	DATA_TYPE_XML_TOP Value: 34
public static final	MILLS_PER_HOUR Number of milliseconds in an hour Value: 60000
protected	type

Constructor Summary

public	AMFData()
--------	---------------------------

Method Summary

static AMFDataContextDeserialize	createContextDeserialize() Create an AMF3 deserialization context
-----------------------------------------------------	--------------------------------------------------------------------------------------

static AMFDataContextDeserialize	createContextDeserialize (int objectEncoding) Create an AMF3 deserialization context
static AMFDataContextSerialize	createContextSerialize () Create an AMF3 serialization context
static AMFDataContextSerialize	createContextSerialize (int objectEncoding) Create an AMF3 serialization context
abstract void	deserialize (java.nio.ByteBuffer data) Deserialize data in byte buffer
abstract void	deserialize (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Deserialize data in byte buffer
static AMFData	deserializeInnerObject (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Deserialize next item
static AMFData	getReference (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Get AMF3 object reference
int	getType () Returns the data type for this object
abstract Object	getValue () Convert object to Java native class
static boolean	isAMF3Start (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Returns true if next byte in data is AMF3 start
static boolean	isArrayStart (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Returns true if next byte in data is an array start
static boolean	isByteArrayStart (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Returns true if next byte is ByteArray start
static boolean	isMixedArrayStart (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Returns true if next byte in data is mixed array start
static boolean	isObjEnd (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Returns true if next byte is object end
static boolean	isObjStart (java.nio.ByteBuffer data, AMFDataContextDeserialize context) Returns true if next byte in data is object start
static int	peekByte (java.nio.ByteBuffer data) Return the next byte in the buffer without incrementing the data position
abstract byte[]	serialize () Serial object to byte array
abstract byte[]	serialize (AMFDataContextSerialize context) Serial object to byte array

abstract void	serialize (java.io.DataOutputStream out) Serialize object to output stream
abstract void	serialize (java.io.DataOutputStream out, AMFDataContextSerialize context) Serialize object to output stream
abstract void	serialize (java.io.DataOutputStream out, int objectEncoding) Serialize object to output stream
abstract byte[]	serialize (int objectEncoding) Serial object to byte array
void	setType (int type) Sets the the data type for this object
static int	skipByte (java.nio.ByteBuffer data) Skip forward one byte in the byte buffer
static boolean	testNextByte (java.nio.ByteBuffer data, int test) Peek at the next value in data to see if its the test value
static boolean	triggerAMF3Switch (AMFData data) Return true if the object is serialized differently in AMF3

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

DATA_TYPE_UNKNOWN

```
public static final byte DATA_TYPE_UNKNOWN
```

Constant value: **-1**

DATA_TYPE_NUMBER

```
public static final byte DATA_TYPE_NUMBER
```

Constant value: **0**

DATA_TYPE_BOOLEAN

```
public static final byte DATA_TYPE_BOOLEAN
```

Constant value: **1**

DATA_TYPE_STRING

```
public static final byte DATA_TYPE_STRING
```

(continued from last page)

Constant value: **2**

DATA_TYPE_OBJECT

```
public static final byte DATA_TYPE_OBJECT
```

Constant value: **3**

DATA_TYPE_MOVIE_CLIP

```
public static final byte DATA_TYPE_MOVIE_CLIP
```

Constant value: **4**

DATA_TYPE_NULL

```
public static final byte DATA_TYPE_NULL
```

Constant value: **5**

DATA_TYPE_UNDEFINED

```
public static final byte DATA_TYPE_UNDEFINED
```

Constant value: **6**

DATA_TYPE_REFERENCE_OBJECT

```
public static final byte DATA_TYPE_REFERENCE_OBJECT
```

Constant value: **7**

DATA_TYPE_MIXED_ARRAY

```
public static final byte DATA_TYPE_MIXED_ARRAY
```

Constant value: **8**

DATA_TYPE_OBJECT_END

```
public static final byte DATA_TYPE_OBJECT_END
```

Constant value: **9**

DATA_TYPE_ARRAY

```
public static final byte DATA_TYPE_ARRAY
```

Constant value: **10**

(continued from last page)

DATA_TYPE_DATE

```
public static final byte DATA_TYPE_DATE
```

Constant value: **11**

DATA_TYPE_LONG_STRING

```
public static final byte DATA_TYPE_LONG_STRING
```

Constant value: **12**

DATA_TYPE_AS_OBJECT

```
public static final byte DATA_TYPE_AS_OBJECT
```

Constant value: **13**

DATA_TYPE_RECORDSET

```
public static final byte DATA_TYPE_RECORDSET
```

Constant value: **14**

DATA_TYPE_XML

```
public static final byte DATA_TYPE_XML
```

Constant value: **15**

DATA_TYPE_CUSTOM_CLASS

```
public static final byte DATA_TYPE_CUSTOM_CLASS
```

Constant value: **16**

DATA_TYPE_AMF3

```
public static final byte DATA_TYPE_AMF3
```

Constant value: **17**

DATA_TYPE_INTEGER

```
public static final byte DATA_TYPE_INTEGER
```

Constant value: **32**

DATA_TYPE_BYTEARRAY

```
public static final byte DATA_TYPE_BYTEARRAY
```

(continued from last page)

Constant value: **33**

DATA_TYPE_XML_TOP

```
public static final byte DATA_TYPE_XML_TOP
```

Constant value: **34**

DATA_TYPE_AMF3_UNDEFINED

```
public static final byte DATA_TYPE_AMF3_UNDEFINED
```

Constant value: **0**

DATA_TYPE_AMF3_NULL

```
public static final byte DATA_TYPE_AMF3_NULL
```

Constant value: **1**

DATA_TYPE_AMF3_BOOLEAN_FALSE

```
public static final byte DATA_TYPE_AMF3_BOOLEAN_FALSE
```

Constant value: **2**

DATA_TYPE_AMF3_BOOLEAN_TRUE

```
public static final byte DATA_TYPE_AMF3_BOOLEAN_TRUE
```

Constant value: **3**

DATA_TYPE_AMF3_INTEGER

```
public static final byte DATA_TYPE_AMF3_INTEGER
```

Constant value: **4**

DATA_TYPE_AMF3_NUMBER

```
public static final byte DATA_TYPE_AMF3_NUMBER
```

Constant value: **5**

DATA_TYPE_AMF3_STRING

```
public static final byte DATA_TYPE_AMF3_STRING
```

Constant value: **6**

DATA_TYPE_AMF3_XML_LEGACY

```
public static final byte DATA_TYPE_AMF3_XML_LEGACY
```

Constant value: **7**

DATA_TYPE_AMF3_DATE

```
public static final byte DATA_TYPE_AMF3_DATE
```

Constant value: **8**

DATA_TYPE_AMF3_ARRAY

```
public static final byte DATA_TYPE_AMF3_ARRAY
```

Constant value: **9**

DATA_TYPE_AMF3_OBJECT

```
public static final byte DATA_TYPE_AMF3_OBJECT
```

Constant value: **10**

DATA_TYPE_AMF3_XML_TOP

```
public static final byte DATA_TYPE_AMF3_XML_TOP
```

Constant value: **11**

DATA_TYPE_AMF3_BYTEARRAY

```
public static final byte DATA_TYPE_AMF3_BYTEARRAY
```

Constant value: **12**

AMF_LEVEL0

```
public static final byte AMF_LEVEL0
```

Constant value: **0**

AMF_LEVEL3

```
public static final byte AMF_LEVEL3
```

Constant value: **3**

(continued from last page)

MILLS_PER_HOUR

```
public static final int MILLS_PER_HOUR
```

Number of milliseconds in an hour
Constant value: **60000**

type

```
protected int type
```

Constructors

AMFData

```
public AMFData()
```

Methods

getType

```
public int getType()
```

Returns the data type for this object

Returns:

object type DATA_TYPE_*

setType

```
public void setType(int type)
```

Sets the the data type for this object

Parameters:

type - type DATA_TYPE_*

testNextByte

```
public static boolean testNextByte(java.nio.ByteBuffer data,  
int test)
```

Peek at the next value in data to see if its the test value

Parameters:

data - binary data being deserialized
test - value being tested

Returns:

return true if the next byte in the buffer equals the test value

peekByte

```
public static int peekByte(java.nio.ByteBuffer data)
```

(continued from last page)

Return the next byte in the buffer without incrementing the data position

Parameters:

data - binary data being deserialized

Returns:

next byte in buffer

skipByte

```
public static int skipByte(java.nio.ByteBuffer data)
```

Skip forward one byte in the byte buffer

Parameters:

data - binary data being deserialized

Returns:

next byte in buffer

isObjStart

```
public static boolean isObjStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is object start

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

Returns true if next byte in data is object start

isAMF3Start

```
public static boolean isAMF3Start(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is AMF3 start

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

Returns true if next byte in data is object start

isArrayStart

```
public static boolean isArrayStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is an array start

Parameters:

data - binary data being deserialized
context - deserialization context

(continued from last page)

Returns:

Returns true if next byte in data is and array start

isMixedArrayStart

```
public static boolean isMixedArrayStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte in data is mixed array start

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

Returns true if next byte in data is mixed array start

isObjEnd

```
public static boolean isObjEnd(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte is object end

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

Returns true if next byte in object end

isByteArrayStart

```
public static boolean isByteArrayStart(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Returns true if next byte is ByteArray start

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

true if next byte in object end

getReference

```
public static AMFData getReference(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Get AMF3 object reference

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

null if not a reference else referenced object

deserializeInnerObject

```
public static AMFData deserializeInnerObject( java.nio.ByteBuffer data,  
        AMFDataContextDeserialize context)  
    throws java.io.IOException
```

Deserialize next item

Parameters:

data - binary data being deserialized
context - deserialization context

Returns:

deserialized object

Throws:

IOException

createContextSerialize

```
public static AMFDataContextSerialize createContextSerialize()
```

Create an AMF3 serialization context

Returns:

AMF3 serialization context

createContextSerialize

```
public static AMFDataContextSerialize createContextSerialize(int objectEncoding)
```

Create an AMF3 serialization context

Parameters:

objectEncoding - object encoding level (see AMF_LEVEL*)

Returns:

AMF3 serialization context

createContextDeserialize

```
public static AMFDataContextDeserialize createContextDeserialize()
```

Create an AMF3 deserialization context

Returns:

AMF3 deserialization context

createContextDeserialize

```
public static AMFDataContextDeserialize createContextDeserialize(int objectEncoding)
```

Create an AMF3 deserialization context

Parameters:

objectEncoding - object encoding level (see AMF_LEVEL*)

Returns:

(continued from last page)

AMF3 deserialization context

serialize

```
public abstract void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

Parameters:

out - Output stream

serialize

```
public abstract void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

Parameters:

out - Output stream

objectEncoding - object encoding level (see AMF_LEVEL*)

serialize

```
public abstract void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

Parameters:

out - Output stream

context - serialization context used by AMF3

serialize

```
public abstract byte[] serialize()
```

Serial object to byte array

Returns:

serialized byte array

serialize

```
public abstract byte[] serialize(int objectEncoding)
```

Serial object to byte array

Parameters:

objectEncoding - object encoding level (see AMF_LEVEL*)

Returns:

serialized byte array

serialize

```
public abstract byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

(continued from last page)

Parameters:

context - serialization context used by AMF3

Returns:

serialized byte array

deserialize

```
public abstract void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

Parameters:

data - binary data

deserialize

```
public abstract void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

Parameters:

data - binary data

context - deserialization context used by AMF3

getValue

```
public abstract Object getValue()
```

Convert object to Java native class

Returns:

java native class

triggerAMF3Switch

```
public static boolean triggerAMF3Switch(AMFData data)
```

Return true if the object is serialized differently in AMF3

Parameters:


data - AMF object

Returns:

true if the object is serialized differently in AMF3

com.wowza.wms.amf Class AMFDataArray

java.lang.Object



```
public class AMFDataArray
extends AMFData
```

AMFDataArray: class for marshalling data between Wowza Pro server and Flash client. This class is a simple ordered array of items.

Create Array of Strings

```
AMFDataArray amfDataArray = new AMFDataArray();

amfDataArray.add("item1");
amfDataArray.add("item2");
amfDataArray.add("item3");
```

Iterate Items In Array

```
AMFDataArray amfDataArray;

for(int i=0;i<amfDataArray.size();i++)
{
    AMFData amfData = amfDataArray.get(i);
    WMSLoggerFactory.getLogger(null).debug("amfData.getType(): "+amfData.getType());
}
```

NOTE: There is a slight difference between this class and AMFDataList. This class when serialized/deserialized does include the DATA_TYPE_ARRAY header (byte) and array size (int).

NOTE: Simple arrays created in the Flash player client and sent to the Wowza Pro server are of type [AMFDataMixedArray](#).

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF_LEVEL0](#), [AMF_LEVEL3](#), [DATA_TYPE_AMF3](#), [DATA_TYPE_AMF3_ARRAY](#), [DATA_TYPE_AMF3_BOOLEAN_FALSE](#),
[DATA_TYPE_AMF3_BOOLEAN_TRUE](#), [DATA_TYPE_AMF3_BYTEARRAY](#), [DATA_TYPE_AMF3_DATE](#),
[DATA_TYPE_AMF3_INTEGER](#), [DATA_TYPE_AMF3_NULL](#), [DATA_TYPE_AMF3_NUMBER](#), [DATA_TYPE_AMF3_OBJECT](#),
[DATA_TYPE_AMF3_STRING](#), [DATA_TYPE_AMF3_UNDEFINED](#), [DATA_TYPE_AMF3_XML_LEGACY](#),
[DATA_TYPE_AMF3_XML_TOP](#), [DATA_TYPE_ARRAY](#), [DATA_TYPE_AS_OBJECT](#), [DATA_TYPE_BOOLEAN](#),
[DATA_TYPE_BYTEARRAY](#), [DATA_TYPE_CUSTOM_CLASS](#), [DATA_TYPE_DATE](#), [DATA_TYPE_INTEGER](#),
[DATA_TYPE_LONG_STRING](#), [DATA_TYPE_MIXED_ARRAY](#), [DATA_TYPE_MOVIE_CLIP](#), [DATA_TYPE_NULL](#),
[DATA_TYPE_NUMBER](#), [DATA_TYPE_OBJECT](#), [DATA_TYPE_OBJECT_END](#), [DATA_TYPE_RECORDSET](#),
[DATA_TYPE_REFERENCE_OBJECT](#), [DATA_TYPE_STRING](#), [DATA_TYPE_UNDEFINED](#), [DATA_TYPE_UNKNOWN](#),
[DATA_TYPE_XML](#), [DATA_TYPE_XML_TOP](#), [MILLS_PER_HOUR](#), [type](#)

Constructor Summary

public	AMFDataArray () Create empty AMFDataArray object
public	AMFDataArray (byte[] data) Deserialize entire data array and create AMFDataArray object
public	AMFDataArray (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataArray object
public	AMFDataArray (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataArray object
public	AMFDataArray (java.nio.ByteBuffer data, AMFDataContextDeserialize context)

Method Summary

void	add (AMFData data) Append a new item onto the array
void	add (boolean data) Append a boolean (will be wrapped in an AMFDataItem object)
void	add (java.util.Date data) Append a date (will be wrapped in an AMFDataItem object)
void	add (double data) Append a double (will be wrapped in an AMFDataItem object)
void	add (int data) Append a int (will be wrapped in an AMFDataItem object)
void	add (int index, AMFData data) Insert an item into the array
void	add (int index, boolean data) Insert a boolean value (will be wrapped in an AMFDataItem object)
void	add (int index, java.util.Date data) Insert a date value (will be wrapped in an AMFDataItem object)
void	add (int index, double data) Insert a double value (will be wrapped in an AMFDataItem object)

void	add (int index, int data) Insert a int value (will be wrapped in an AMFDataItem object)
void	add (int index, long data) Insert a long value (will be wrapped in an AMFDataItem object)
void	add (int index, String data) Insert a string value (will be wrapped in an AMFDataItem object)
void	add (long data) Append a long (will be wrapped in an AMFDataItem object)
void	add (String data) Append a string (will be wrapped in an AMFDataItem object)
void	deserialize (java.nio.ByteBuffer data)
void	deserialize (java.nio.ByteBuffer data, AMFDataContextDeserialize context)
AMFData	get (int index) Get item at index
boolean	getBoolean (int index) Get item at index return as boolean
byte	getBytes (int index) Get item at index return as byte
java.util.Date	getDate (int index) Get item at index return as Date
double	getDouble (int index) Get item at index return as double
float	getFloat (int index) Get item at index return as float
int	getInt (int index) Get item at index return as int
long	getLong (int index) Get item at index return as long
AMFDataObj	getObject (int index) Get item at index return as AMFDataObj
short	getShort (int index) Get item at index return as short
String	getString (int index) Get item at index return as String
Object	getValue ()
AMFData	remove (int index) Remove an item from the array

byte[]	serialize()
byte[]	serialize() (AMFDataContextSerialize context)
void	serialize() (java.io.DataOutputStream out)
void	serialize() (java.io.DataOutputStream out, AMFDataContextSerialize context)
void	serialize() (java.io.DataOutputStream out, int objectEncoding)
byte[]	serialize() (int objectEncoding)
void	set() (int index, AMFData data) Set an array item
void	set() (int index, boolean data) Set an boolean value (will be wrapped in an AMFDataItem object)
void	set() (int index, java.util.Date data) Set an date value (will be wrapped in an AMFDataItem object)
void	set() (int index, double data) Set an double value (will be wrapped in an AMFDataItem object)
void	set() (int index, int data) Set an int value (will be wrapped in an AMFDataItem object)
void	set() (int index, long data) Set an long value (will be wrapped in an AMFDataItem object)
void	set() (int index, String data) Set an string value (will be wrapped in an AMFDataItem object)
int	size() Returns the number of items in array
String	toString() Return object as formatted string

Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

(continued from last page)

AMFDataArray

```
public AMFDataArray()
```

Create empty AMFDataArray object

AMFDataArray

```
public AMFDataArray(byte[] data)
```

Deserialize entire data array and create AMFDataArray object

Parameters:

data - binary data

AMFDataArray

```
public AMFDataArray(byte[] data,  
                    int offset,  
                    int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataArray object

Parameters:

data - binary data

offset - starting offset into data

size - size of data to deserialize

AMFDataArray

```
public AMFDataArray(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataArray object

Parameters:

data - binary data

AMFDataArray

```
public AMFDataArray(java.nio.ByteBuffer data,  
                   AMFDataContextDeserialize context)
```

Methods

remove

```
public AMFData remove(int index)
```

Remove an item from the array

Parameters:

index - index

Returns:

delete item or null if not found

size

```
public int size()
```

Returns the number of items in array

Returns:

number of items in array

add

```
public void add(AMFData data)
```

Append a new item onto the array

Parameters:

data - AMFData object

add

```
public void add(String data)
```

Append a string (will be wrapped in an AMFDataItem object)

Parameters:

data - string value

add

```
public void add(double data)
```

Append a double (will be wrapped in an AMFDataItem object)

Parameters:

data - double value

add

```
public void add(int data)
```

Append a int (will be wrapped in an AMFDataItem object)

Parameters:

data - int value

add

```
public void add(long data)
```

Append a long (will be wrapped in an AMFDataItem object)

Parameters:

data - long value

add

```
public void add(java.util.Date data)
```

(continued from last page)

Append a date (will be wrapped in an AMFDataItem object)

Parameters:

data - date value

add

```
public void add(boolean data)
```

Append a boolean (will be wrapped in an AMFDataItem object)

Parameters:

data - boolean value

add

```
public void add(int index,  
    AMFData data)
```

Insert an item into the array

Parameters:

index - index

data - AMFData object

add

```
public void add(int index,  
    String data)
```

Insert a string value (will be wrapped in an AMFDataItem object)

Parameters:

index - index

data - string value

add

```
public void add(int index,  
    double data)
```

Insert a double value (will be wrapped in an AMFDataItem object)

Parameters:

index - index

data - double value

add

```
public void add(int index,  
    int data)
```

Insert a int value (will be wrapped in an AMFDataItem object)

Parameters:

index - index

data - int value

add

```
public void add(int index,  
                long data)
```

Insert a long value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - long value

add

```
public void add(int index,  
                java.util.Date data)
```

Insert a date value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - date value

add

```
public void add(int index,  
                boolean data)
```

Insert a boolean value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - boolean value

set

```
public void set(int index,  
                AMFData data)
```

Set an array item

Parameters:

index - index
data - AMFData object

set

```
public void set(int index,  
                String data)
```

Set an string value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - string value

set

```
public void set(int index,  
                double data)
```

(continued from last page)

Set an double value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - double value

set

```
public void set(int index,  
                int data)
```

Set an int value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - int value

set

```
public void set(int index,  
                long data)
```

Set an long value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - long value

set

```
public void set(int index,  
                java.util.Date data)
```

Set an date value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - date value

set

```
public void set(int index,  
                boolean data)
```

Set an boolean value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - boolean value

get

```
public AMFData get(int index)
```

Get item at index

Parameters:

index

(continued from last page)

Returns:

Returns AMFData object or null if out of bounds

getString

```
public String getString(int index)
```

Get item at index return as String

Parameters:

index

Returns:

Return item as String or null if out of bounds

getInt

```
public int getInt(int index)
```

Get item at index return as int

Parameters:

index

Returns:

Return item as int or 0 if out of bounds

getLong

```
public long getLong(int index)
```

Get item at index return as long

Parameters:

index

Returns:

Return item as long or 0 if out of bounds

getShort

```
public short getShort(int index)
```

Get item at index return as short

Parameters:

index

Returns:

Return item as short or 0 if out of bounds

getByte

```
public byte getByte(int index)
```

Get item at index return as byte

Parameters:

(continued from last page)

index

Returns:

Return item as byte or 0 if out of bounds

getBoolean

```
public boolean getBoolean(int index)
```

Get item at index return as boolean

Parameters:

index

Returns:

Return item as boolean or false if out of bounds

getDate

```
public java.util.Date getDate(int index)
```

Get item at index return as Date

Parameters:

index

Returns:

Return item as Date or null if out of bounds

getObject

```
public AMFDataObj getObject(int index)
```

Get item at index return as AMFDataObj

Parameters:

index

Returns:

Return item as AMFDataObj or null if out of bounds

getDouble

```
public double getDouble(int index)
```

Get item at index return as double

Parameters:

index

Returns:

Return item as double or 0 if out of bounds

getFloat

```
public float getFloat(int index)
```

Get item at index return as float

(continued from last page)

Parameters:

index

Returns:

Return item as float or 0 if out of bounds

deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

serialize

```
public byte[] serialize()
```

Serial object to byte array

serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

(continued from last page)

getValue

```
public Object getValue()
```

Convert object to Java native class

toString


```
public String toString()
```

Return object as formatted string

com.wowza.wms.amf

Class AMFDataByteArray

java.lang.Object



public class **AMFDataByteArray**
 extends [AMFData](#)

AMFDataByteArray: class for marshalling data between Wowza Pro server and Flash client. This class is a simple byte array.

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF_LEVEL0](#), [AMF_LEVEL3](#), [DATA_TYPE_AMF3](#), [DATA_TYPE_AMF3_ARRAY](#), [DATA_TYPE_AMF3_BOOLEAN_FALSE](#), [DATA_TYPE_AMF3_BOOLEAN_TRUE](#), [DATA_TYPE_AMF3_BYTEARRAY](#), [DATA_TYPE_AMF3_DATE](#), [DATA_TYPE_AMF3_INTEGER](#), [DATA_TYPE_AMF3_NULL](#), [DATA_TYPE_AMF3_NUMBER](#), [DATA_TYPE_AMF3_OBJECT](#), [DATA_TYPE_AMF3_STRING](#), [DATA_TYPE_AMF3_UNDEFINED](#), [DATA_TYPE_AMF3_XML_LEGACY](#), [DATA_TYPE_AMF3_XML_TOP](#), [DATA_TYPE_ARRAY](#), [DATA_TYPE_AS_OBJECT](#), [DATA_TYPE_BOOLEAN](#), [DATA_TYPE_BYTEARRAY](#), [DATA_TYPE_CUSTOM_CLASS](#), [DATA_TYPE_DATE](#), [DATA_TYPE_INTEGER](#), [DATA_TYPE_LONG_STRING](#), [DATA_TYPE_MIXED_ARRAY](#), [DATA_TYPE_MOVIE_CLIP](#), [DATA_TYPE_NULL](#), [DATA_TYPE_NUMBER](#), [DATA_TYPE_OBJECT](#), [DATA_TYPE_OBJECT_END](#), [DATA_TYPE_RECORDSET](#), [DATA_TYPE_REFERENCE_OBJECT](#), [DATA_TYPE_STRING](#), [DATA_TYPE_UNDEFINED](#), [DATA_TYPE_UNKNOWN](#), [DATA_TYPE_XML](#), [DATA_TYPE_XML_TOP](#), [MILLS_PER_HOUR](#), [type](#)

Constructor Summary

public	AMFDataByteArray() Create empty AMFDataByteArray object
public	AMFDataByteArray(byte[] data) Deserialize entire byte array and create AMFDataByteArray object.
public	AMFDataByteArray(byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataByteArray object.
public	AMFDataByteArray(java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataByteArray object.
public	AMFDataByteArray(java.nio.ByteBuffer data, AMFDataContextDeserialize context) Deserialize entire data array and create AMFDataByteArray object.

Method Summary

int	compress() Compress the internal buffer using the ZLIB compression library
int	decompress() Decompress the internal buffer using the ZLIB compression library
void	deserialize(java.nio.ByteBuffer data)

void	deserialize (java.nio.ByteBuffer data, AMFDataContextDeserialize context)
Object	getValue () Returns the underlying byte[] data buffer
byte[]	serialize ()
byte[]	serialize (AMFDataContextSerialize context)
void	serialize (java.io.DataOutputStream out)
void	serialize (java.io.DataOutputStream out, AMFDataContextSerialize context)
void	serialize (java.io.DataOutputStream out, int objectEncoding)
byte[]	serialize (int objectEncoding)
int	size () Returns the number of bytes in the byte array
byte[]	toArray () Returns the underlying data buffer (not a copy)
java.nio.ByteBuffer	toByteBuffer () Wraps the underlying data buffer with a ByteBuffer object.
String	toString () Return object as formatted string
static AMFDataByteArray	wrap (byte[] data) Wraps a byte[] into a AMFDataByteArray.
static AMFDataByteArray	wrap (java.nio.ByteBuffer data) Wraps a ByteBuffer into a AMFDataByteArray.

Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

(continued from last page)

AMFDataByteArray

```
public AMFDataByteArray( )
```

Create empty AMFDataByteArray object

AMFDataByteArray

```
public AMFDataByteArray(byte[] data)
```

Deserialize entire byte array and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMFDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

Parameters:

data - binary data

AMFDataByteArray

```
public AMFDataByteArray(byte[] data,  
                        int offset,  
                        int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMFDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

Parameters:

data - binary data

offset - starting offset into data

size - size of data to deserialize

AMFDataByteArray

```
public AMFDataByteArray(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMFDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

Parameters:

data - binary data

AMFDataByteArray

```
public AMFDataByteArray(java.nio.ByteBuffer data,  
                        AMFDataContextDeserialize context)
```

Deserialize entire data array and create AMFDataByteArray object. Note: This is for AMF3 deserialization and cannot be used to create an AMFDataByteArray with the passed in data. To create a new AMFDataByteArray from either a byte[] or ByteBuffer, use the static wrap method.

Parameters:

data - binary data

context - deserialization context (used for AMF3 decoding)

Methods

(continued from last page)

size

```
public int size()
```

Returns the number of bytes in the byte array

Returns:

number of bytes in the array

toArray

```
public byte[] toArray()
```

Returns the underlying data buffer (not a copy)

Returns:

data buffer (not a copy)

toByteBuffer

```
public java.nio.ByteBuffer toByteBuffer()
```

Wraps the underlying data buffer with a ByteBuffer object.

Returns:

byte[] wrapped as ByteBuffer

wrap

```
public static AMFDataByteArray wrap(byte[] data)
```

Wraps a byte[] into a AMFDataByteArray. Note: This method does not copy the array.

Parameters:

data - byte[] data

Returns:

wrapped byte[]

wrap

```
public static AMFDataByteArray wrap(java.nio.ByteBuffer data)
```

Wraps a ByteBuffer into a AMFDataByteArray. Note: This method only copies the ByteBuffer data if the ByteBuffer.array() method fails.

Parameters:

data - ByteBuffer data

Returns:

wrapped ByteBuffer

getValue

```
public Object getValue()
```

Returns the underlying byte[] data buffer

deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

serialize

```
public byte[] serialize()
```

Serial object to byte array

serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

compress

```
public int compress()
```

Compress the internal buffer using the ZLIB compression library

Returns:

(continued from last page)

size of compressed buffer

decompress

```
public int decompress()
```

Decompress the internal buffer using the ZLIB compression library

Returns:

size of decompressed buffer

toString

```
public String toString()
```

Return object as formatted string

com.wowza.wms.amf

Class AMFDataContextDeserialize

java.lang.Object

└─com.wowza.wms.amf.AMFDataContextDeserialize

public class **AMFDataContextDeserialize**
extends Object

AMF context used for deserialization

Constructor Summary

public	AMFDataContextDeserialize() Constructor
public	AMFDataContextDeserialize(int objectEncoding) Constructor with encoding

Method Summary

void	addObject(Object obj) Add an object to the object cache
void	addString(String str) Add a string to the string cache
void	addTrait(AMFDataTrait obj) Add a trait to the trait cache
int	clearIntData() Internal use, get and clear int data
int	getIntData() Internal use, get int data
Object	getObject(int index) Get an object from the object cache
int	getObjectEncoding() Get object encoding, see AMFData.AMF_LEVEL*
String	getString(int index) Get a string from the string cache
AMFDataTrait	getTrait(int index) Get a trait from the trait cache
boolean	isAMF0() Is context AMF0
boolean	isAMF3() Is context AMF3

boolean	<code>isIntData()</code> Internal use, get int data
void	<code>setIntData(int intData)</code> Internal use, set int data
void	<code>setObjectEncoding(int objectEncoding)</code> Set object encoding, see <code>AMFData.AMF_LEVEL*</code>

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

AMFDataContextDeserialize

```
public AMFDataContextDeserialize()
```

Constructor

AMFDataContextDeserialize

```
public AMFDataContextDeserialize(int objectEncoding)
```

Constructor with encoding

Parameters:

`objectEncoding` - object encoding, see `AMFData.AMF_LEVEL*`

Methods

isIntData

```
public boolean isIntData()
```

Internal use, get int data

Returns:

returns true if pending int data

setIntData

```
public void setIntData(int intData)
```

Internal use, set int data

Parameters:

`intData` - int data

getIntData

```
public int getIntData()
```

Internal use, get int data

(continued from last page)

Returns:

int data

clearIntData

```
public int clearIntData()
```

Internal use, get and clear int data

Returns:

int data

getObjectEncoding

```
public int getObjectEncoding()
```

Get object encoding, see AMFData.AMF_LEVEL*

Returns:

object encoding, see AMFData.AMF_LEVEL*

setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

Set object encoding, see AMFData.AMF_LEVEL*

Parameters:

objectEncoding - object encoding, see AMFData.AMF_LEVEL*

isAMF3

```
public boolean isAMF3()
```

Is context AMF3

Returns:

true, if AMF3

isAMF0

```
public boolean isAMF0()
```

Is context AMF0

Returns:

true, if AMF0

addString

```
public void addString(String str)
```

Add a string to the string cache

Parameters:

str - string value

getString

```
public String getString(int index)  
    throws IndexOutOfBoundsException
```

Get a string from the string cache

Parameters:

index - index

Returns:

string value

Throws:

IndexOutOfBoundsException

addObject

```
public void addObject(Object obj)
```

Add an object to the object cache

Parameters:

obj - object value

getObject

```
public Object getObject(int index)  
    throws IndexOutOfBoundsException
```

Get an object from the object cache

Parameters:

index - index

Returns:

object value

Throws:

IndexOutOfBoundsException

addTrait

```
public void addTrait(AMFDataTrait obj)
```

Add a trait to the trait cache

Parameters:

obj - trait object

getTrait

```
public AMFDataTrait getTrait(int index)  
    throws IndexOutOfBoundsException
```

Get a trait from the trait cache

Parameters:

(continued from last page)

index - index

Returns:

trait object

Throws:

IndexOutOfBoundsException

com.wowza.wms.amf

Class AMFDataContextSerialize

java.lang.Object

└─com.wowza.wms.amf.AMFDataContextSerialize

public class **AMFDataContextSerialize**
extends Object

AMF context used for serialization

Constructor Summary

public	AMFDataContextSerialize() Constructor
public	AMFDataContextSerialize(int objectEncoding) Contructor with object encoding, see AMFData.AMF_LEVEL*

Method Summary

int	getObjectEncoding() Get object encoding, see AMFData.AMF_LEVEL*
int	getObjectReference(Object obj) Get index of object in object cache
int	getStringReference(String str) Get index of string item in string cache
int	getTargetEncoding() Get target encoding, see AMFData.AMF_LEVEL*
int	getTraitReference(AMFDataTrait obj) Get index of trait object in trait cache
boolean	isAMF0() Is context AMF0
boolean	isAMF3() Is context AMF3
void	setObjectEncoding(int objectEncoding) Set object encoding, see AMFData.AMF_LEVEL*
void	setTargetEncoding(int targetEncoding) Set target encoding, , see AMFData.AMF_LEVEL*
void	writeString(java.io.DataOutputStream out, String str) Write a stream to the output buffer

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AMFDataContextSerialize

```
public AMFDataContextSerialize()
```

Constructor

AMFDataContextSerialize

```
public AMFDataContextSerialize(int objectEncoding)
```

Constructor with object encoding, see AMFData.AMF_LEVEL*

Parameters:

objectEncoding - object encoding, see AMFData.AMF_LEVEL*

Methods

getObjectEncoding

```
public int getObjectEncoding()
```

Get object encoding, see AMFData.AMF_LEVEL*

Returns:

object encoding, see AMFData.AMF_LEVEL*

setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

Set object encoding, see AMFData.AMF_LEVEL*

Parameters:

objectEncoding - object encoding, see AMFData.AMF_LEVEL*

getTargetEncoding

```
public int getTargetEncoding()
```

Get target encoding, see AMFData.AMF_LEVEL*

Returns:

target encoding, see AMFData.AMF_LEVEL*

setTargetEncoding

```
public void setTargetEncoding(int targetEncoding)
```

Set target encoding, , see AMFData.AMF_LEVEL*

(continued from last page)

Parameters:

targetEncoding - target encoding, , see AMFData.AMF_LEVEL*

isAMF3

```
public boolean isAMF3()
```

Is context AMF3

Returns:

true, if AMF3

isAMF0

```
public boolean isAMF0()
```

Is context AMF0

Returns:

true, if AMF0

getStringReference

```
public int getStringReference(String str)
```

Get index of string item in string cache

Parameters:

str - string value

Returns:

index

getObjectReference

```
public int getObjectReference(Object obj)
```

Get index of object in object cache

Parameters:

obj - object value

Returns:

index

getTraitReference

```
public int getTraitReference(AMFDataTrait obj)
```

Get index of trait object in trait cache

Parameters:

obj - trait object

Returns:

index

(continued from last page)

writeString

```
public void writeString(java.io.DataOutputStream out,  
    String str)
```

Write a stream to the output buffer

Parameters:

out - output buffer

str - string value

com.wowza.wms.amf

Class AMFDataItem

```
java.lang.Object
  |
  +--com.wowza.wms.amf.AMFData
        |
        +--com.wowza.wms.amf.AMFDataItem
```

```
public class AMFDataItem
extends AMFData
```

AMFDataItem: class for marshalling data between Wowza Pro server and Flash client. The type wraps native Java data types.

- DATA_TYPE_NUMBER = int, long, short, double, float
- DATA_TYPE_STRING = String
- DATA_TYPE_BOOLEAN = boolean
- DATA_TYPE_DATE = Date
- DATA_TYPE_NULL = 'null'

Create Native Java Types

```
AMFDataItem amfDataString = new AMFDataItem("here is my string"); // String
AMFDataItem amfDataLong = new AMFDataItem(1234L); // long
AMFDataItem amfDataDouble = new AMFDataItem(1.234); // double
AMFDataItem amfDataBoolean = new AMFDataItem(true); // boolean
AMFDataItem amfDataNull = new AMFDataItem(); // null
```

Get Native Java Types

```
String dataString = amfDataString.getType()==AMFData.DATA_TYPE_LONG_STRING?
    amfDataString.toString():"";

long dataLong = amfDataLong.getType()==AMFData.DATA_TYPE_NUMBER?
    amfDataLong.longValue():0;

double dataDouble = amfDataDouble.getType()==AMFData.DATA_TYPE_NUMBER?
    amfDataLong.doubleValue():0.0;

boolean dataBoolean = amfDataBoolean.getType()==AMFData.DATA_TYPE_BOOLEAN?
    amfDataLong.booleanValue():false;

Object dataNull = amfDataNull.getType()==AMFData.DATA_TYPE_NULL?
    null:null;
```

Field Summary

public static final	DATEFORMAT Value: EEE, dd MMM yyyy HH:mm:ss
protected	fastDateFormat

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF_LEVEL0](#), [AMF_LEVEL3](#), [DATA_TYPE_AMF3](#), [DATA_TYPE_AMF3_ARRAY](#), [DATA_TYPE_AMF3_BOOLEAN_FALSE](#),
[DATA_TYPE_AMF3_BOOLEAN_TRUE](#), [DATA_TYPE_AMF3_BYTEARRAY](#), [DATA_TYPE_AMF3_DATE](#),
[DATA_TYPE_AMF3_INTEGER](#), [DATA_TYPE_AMF3_NULL](#), [DATA_TYPE_AMF3_NUMBER](#), [DATA_TYPE_AMF3_OBJECT](#),
[DATA_TYPE_AMF3_STRING](#), [DATA_TYPE_AMF3_UNDEFINED](#), [DATA_TYPE_AMF3_XML_LEGACY](#),
[DATA_TYPE_AMF3_XML_TOP](#), [DATA_TYPE_ARRAY](#), [DATA_TYPE_AS_OBJECT](#), [DATA_TYPE_BOOLEAN](#),
[DATA_TYPE_BYTEARRAY](#), [DATA_TYPE_CUSTOM_CLASS](#), [DATA_TYPE_DATE](#), [DATA_TYPE_INTEGER](#),
[DATA_TYPE_LONG_STRING](#), [DATA_TYPE_MIXED_ARRAY](#), [DATA_TYPE_MOVIE_CLIP](#), [DATA_TYPE_NULL](#),
[DATA_TYPE_NUMBER](#), [DATA_TYPE_OBJECT](#), [DATA_TYPE_OBJECT_END](#), [DATA_TYPE_RECORDSET](#),
[DATA_TYPE_REFERENCE_OBJECT](#), [DATA_TYPE_STRING](#), [DATA_TYPE_UNDEFINED](#), [DATA_TYPE_UNKNOWN](#),
[DATA_TYPE_XML](#), [DATA_TYPE_XML_TOP](#), [MILLS_PER_HOUR](#), [type](#)

Constructor Summary

public	AMFDataItem () Construct AMF type DATA_TYPE_NULL object
public	AMFDataItem (String value) Construct AMF type DATA_TYPE_STRING object
public	AMFDataItem (int value) Construct AMF type DATA_TYPE_NUMBER object
public	AMFDataItem (long value) Construct AMF type DATA_TYPE_NUMBER object
public	AMFDataItem (double value) Construct AMF type DATA_TYPE_NUMBER object
public	AMFDataItem (boolean value) Construct AMF type DATA_TYPE_BOOLEAN
public	AMFDataItem (java.util.Date value) Construct AMF type DATA_TYPE_DATE
public	AMFDataItem (byte[] data) Deserialize entire data array and create AMFDataItem object
public	AMFDataItem (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataItem object
public	AMFDataItem (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataItem object
public	AMFDataItem (java.nio.ByteBuffer data, AMFDataContextDeserialize context)

Method Summary

boolean	booleanValue() Return object as boolean.
byte	byteValue() Return object as byte.
java.util.Date	dateValue() Return object as Date.
void	deserialize() (java.nio.ByteBuffer data)
void	deserialize() (java.nio.ByteBuffer data, AMFDataContextDeserialize context)
double	doubleValue() Return object as double.
float	floatValue() Return object as float.
Object	getValue() Return value as Java class
int	intValue() Return object as int.
long	longValue() Return object as long.
byte[]	serialize()
byte[]	serialize() (AMFDataContextSerialize context)
void	serialize() (java.io.DataOutputStream out)
void	serialize() (java.io.DataOutputStream out, AMFDataContextSerialize context)
void	serialize() (java.io.DataOutputStream out, int objectEncoding)
byte[]	serialize() (int objectEncoding)
short	shortValue() Return object as short.
String	toString() Return object as formatted string

Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

DATEFORMAT

`public static final java.lang.String DATEFORMAT`

Constant value: **EEE, dd MMM yyyy HH:mm:ss**

fastDateFormat

`protected org.apache.commons.lang.time.FastDateFormat fastDateFormat`

Constructors

AMFDataItem

`public AMFDataItem()`

Construct AMF type DATA_TYPE_NULL object

AMFDataItem

`public AMFDataItem(String value)`

Construct AMF type DATA_TYPE_STRING object

Parameters:

value - String value

AMFDataItem

`public AMFDataItem(int value)`

Construct AMF type DATA_TYPE_NUMBER object

Parameters:

value - int value

AMFDataItem

`public AMFDataItem(long value)`

(continued from last page)

Construct AMF type DATA_TYPE_NUMBER object

Parameters:

value - long value

AMFDataItem

```
public AMFDataItem(double value)
```

Construct AMF type DATA_TYPE_NUMBER object

Parameters:

value - double value

AMFDataItem

```
public AMFDataItem(boolean value)
```

Construct AMF type DATA_TYPE_BOOLEAN

Parameters:

value - boolean value

AMFDataItem

```
public AMFDataItem(java.util.Date value)
```

Construct AMF type DATA_TYPE_DATE

Parameters:

value - Date value

AMFDataItem

```
public AMFDataItem(byte[] data)
```

Deserialize entire data array and create AMFDataItem object

Parameters:

data - binary data

AMFDataItem

```
public AMFDataItem(byte[] data,  
                  int offset,  
                  int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataItem object

Parameters:

data - binary data

offset - starting offset into data

size - size of data to deserialize

AMFDataItem

```
public AMFDataItem(java.nio.ByteBuffer data)
```

(continued from last page)

Deserialize entire data array and create AMFDataItem object

Parameters:

data - binary data

AMFDataItem

```
public AMFDataItem(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Methods

longValue

```
public long longValue()
```

Return object as long. Valid object types are DATA_TYPE_NUMBER and DATA_TYPE_STRING.

Returns:

long value or 0 if failure

intValue

```
public int intValue()
```

Return object as int. Valid object types are DATA_TYPE_NUMBER and DATA_TYPE_STRING.

Returns:

int value or 0 if failure

doubleValue

```
public double doubleValue()
```

Return object as double. Valid object types are DATA_TYPE_NUMBER and DATA_TYPE_STRING.

Returns:

double value or 0 if failure

floatValue

```
public float floatValue()
```

Return object as float. Valid object types are DATA_TYPE_NUMBER and DATA_TYPE_STRING.

Returns:

float value or 0 if failure

shortValue

```
public short shortValue()
```

Return object as short. Valid object types are DATA_TYPE_NUMBER and DATA_TYPE_STRING.

Returns:

short value or 0 if failure

byteValue

```
public byte byteValue()
```

Return object as byte. Valid object types are DATA_TYPE_NUMBER and DATA_TYPE_STRING.

Returns:

byte value or 0 if failure

dateValue

```
public java.util.Date dateValue()
```

Return object as Date. Valid object types are DATA_TYPE_DATE.

Returns:

Date value or null if failure

booleanValue

```
public boolean booleanValue()
```

Return object as boolean. Valid object types are DATA_TYPE_BOOLEAN and DATA_TYPE_STRING.

Returns:

boolean value or false if failure

deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

getValue

```
public Object getValue()
```

Return value as Java class

toString

```
public String toString()
```

Return object as formatted string

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

serialize

```
public byte[] serialize()
```

Serial object to byte array

serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

serialize


```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

com.wowza.wms.amf

Class AMFDataList

java.lang.Object



public class **AMFDataList**
 extends [AMFData](#)

AMFDataItem: class for marshalling data between Wowza Pro server and Flash client. This class is for internal server marshalling of AMF event messages between the Flash client and Wowza Pro server.

NOTE: There is a slight difference between this class and AMFDataArray. This class when serialized/deserialized does NOT include the DATA_TYPE_ARRAY header (byte) and array size (int). AMF formatted functions use this class since they do not include these elements.

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF_LEVEL0](#), [AMF_LEVEL3](#), [DATA_TYPE_AMF3](#), [DATA_TYPE_AMF3_ARRAY](#), [DATA_TYPE_AMF3_BOOLEAN_FALSE](#), [DATA_TYPE_AMF3_BOOLEAN_TRUE](#), [DATA_TYPE_AMF3_BYTEARRAY](#), [DATA_TYPE_AMF3_DATE](#), [DATA_TYPE_AMF3_INTEGER](#), [DATA_TYPE_AMF3_NULL](#), [DATA_TYPE_AMF3_NUMBER](#), [DATA_TYPE_AMF3_OBJECT](#), [DATA_TYPE_AMF3_STRING](#), [DATA_TYPE_AMF3_UNDEFINED](#), [DATA_TYPE_AMF3_XML_LEGACY](#), [DATA_TYPE_AMF3_XML_TOP](#), [DATA_TYPE_ARRAY](#), [DATA_TYPE_AS_OBJECT](#), [DATA_TYPE_BOOLEAN](#), [DATA_TYPE_BYTEARRAY](#), [DATA_TYPE_CUSTOM_CLASS](#), [DATA_TYPE_DATE](#), [DATA_TYPE_INTEGER](#), [DATA_TYPE_LONG_STRING](#), [DATA_TYPE_MIXED_ARRAY](#), [DATA_TYPE_MOVIE_CLIP](#), [DATA_TYPE_NULL](#), [DATA_TYPE_NUMBER](#), [DATA_TYPE_OBJECT](#), [DATA_TYPE_OBJECT_END](#), [DATA_TYPE_RECORDSET](#), [DATA_TYPE_REFERENCE_OBJECT](#), [DATA_TYPE_STRING](#), [DATA_TYPE_UNDEFINED](#), [DATA_TYPE_UNKNOWN](#), [DATA_TYPE_XML](#), [DATA_TYPE_XML_TOP](#), [MILLS_PER_HOUR](#), [type](#)

Constructor Summary

public	AMFDataList () Create empty AMFDataList object
public	AMFDataList (byte[] data) Deserialize entire data array and create AMFDataList object
public	AMFDataList (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataList object
public	AMFDataList (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataList object
public	AMFDataList (java.nio.ByteBuffer data, AMFDataContextDeserialize context)

Method Summary

void	add (AMFData data) Append a new item onto the array
------	-----------------------------------------------------------------------------------------

void	add (boolean data) Append a boolean (will be wrapped in an AMFDataItem object)
void	add (java.util.Date data) Append a date (will be wrapped in an AMFDataItem object)
void	add (double data) Append a double (will be wrapped in an AMFDataItem object)
void	add (int data) Append a int (will be wrapped in an AMFDataItem object)
void	add (int index, AMFData data) Insert an item into the array
void	add (int index, boolean data) Insert a boolean value (will be wrapped in an AMFDataItem object)
void	add (int index, java.util.Date data) Insert a date value (will be wrapped in an AMFDataItem object)
void	add (int index, double data) Insert a double value (will be wrapped in an AMFDataItem object)
void	add (int index, int data) Insert a int value (will be wrapped in an AMFDataItem object)
void	add (int index, long data) Insert a long value (will be wrapped in an AMFDataItem object)
void	add (int index, String data) Insert a string value (will be wrapped in an AMFDataItem object)
void	add (long data) Append a long (will be wrapped in an AMFDataItem object)
void	add (String data) Append a string (will be wrapped in an AMFDataItem object)
void	deserialize (java.nio.ByteBuffer data)
void	deserialize (java.nio.ByteBuffer data, AMFDataContextDeserialize context)
AMFData	get (int index) Get item at index
boolean	getBoolean (int index) Get item at index return as boolean
byte	getBytes (int index) Get item at index return as byte
java.util.Date	getDate (int index) Get item at index return as Date
double	getDouble (int index) Get item at index return as double

float	<code>getFloat(int index)</code> Get item at index return as float
int	<code>getInt(int index)</code> Get item at index return as int
long	<code>getLong(int index)</code> Get item at index return as long
<code>AMFDataObj</code>	<code>getObject(int index)</code> Get item at index return as AMFDataObj
short	<code>getShort(int index)</code> Get item at index return as short
String	<code>getString(int index)</code> Get item at index return as String
int	<code>getType(int index)</code> Get type of item at index.
Object	<code>getValue()</code>
<code>AMFData</code>	<code>remove(int index)</code> Remove an element from the AMFDataList object
byte[]	<code>serialize()</code>
byte[]	<code>serialize(AMFDataContextSerialize context)</code>
byte[]	<code>serialize(AMFDataContextSerialize context, byte[] prepend)</code>
void	<code>serialize(java.io.DataOutputStream out)</code>
void	<code>serialize(java.io.DataOutputStream out, AMFDataContextSerialize context)</code>
void	<code>serialize(java.io.DataOutputStream out, AMFDataContextSerialize context, byte[] prepend)</code>
void	<code>serialize(java.io.DataOutputStream out, int objectEncoding)</code>
byte[]	<code>serialize(int objectEncoding)</code>
void	<code>set(int index, AMFData data)</code> Set an array item
void	<code>set(int index, boolean data)</code> Set an boolean value (will be wrapped in an AMFDataItem object)
void	<code>set(int index, java.util.Date data)</code> Set an date value (will be wrapped in an AMFDataItem object)
void	<code>set(int index, double data)</code> Set an double value (will be wrapped in an AMFDataItem object)

void	<u>set</u> (int index, int data) Set an int value (will be wrapped in an AMFDataItem object)
void	<u>set</u> (int index, long data) Set an long value (will be wrapped in an AMFDataItem object)
void	<u>set</u> (int index, String data) Set an string value (will be wrapped in an AMFDataItem object)
int	<u>size</u> () Returns the number of items in array
String	<u>toString</u> () Return object as formatted string

Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

AMFDataList

```
public AMFDataList()
```

Create empty AMFDataList object

AMFDataList

```
public AMFDataList(byte[] data)
```

Deserialize entire data array and create AMFDataList object

Parameters:

data - binary data

AMFDataList

```
public AMFDataList(byte[] data,  
                   int offset,  
                   int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataList object

Parameters:

data - binary data

offset - starting offset into data

(continued from last page)

size - size of data to deserialize

AMFDataList

```
public AMFDataList(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataList object

Parameters:

data - binary data

AMFDataList

```
public AMFDataList(java.nio.ByteBuffer data,  
                   AMFDataContextDeserialize context)
```

Methods

remove

```
public AMFData remove(int index)
```

Remove an element from the AMFDataList object

Parameters:

index - index

Returns:

removed element

size

```
public int size()
```

Returns the number of items in array

Returns:

number of items in array

add

```
public void add(AMFData data)
```

Append a new item onto the array

Parameters:

data - AMFData object

add

```
public void add(String data)
```

Append a string (will be wrapped in an AMFDataItem object)

Parameters:

data - string value

add

```
public void add(double data)
```

Append a double (will be wrapped in an AMFDataItem object)

Parameters:

data - double value

add

```
public void add(int data)
```

Append a int (will be wrapped in an AMFDataItem object)

Parameters:

data - int value

add

```
public void add(long data)
```

Append a long (will be wrapped in an AMFDataItem object)

Parameters:

data - long value

add

```
public void add(java.util.Date data)
```

Append a date (will be wrapped in an AMFDataItem object)

Parameters:

data - date value

add

```
public void add(boolean data)
```

Append a boolean (will be wrapped in an AMFDataItem object)

Parameters:

data - boolean value

add

```
public void add(int index,  
    AMFData data)
```

Insert an item into the array

Parameters:

index - index

data - AMFData object

(continued from last page)

add

```
public void add(int index,  
                String data)
```

Insert a string value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - string value

add

```
public void add(int index,  
                double data)
```

Insert a double value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - double value

add

```
public void add(int index,  
                int data)
```

Insert a int value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - int value

add

```
public void add(int index,  
                long data)
```

Insert a long value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - long value

add

```
public void add(int index,  
                java.util.Date data)
```

Insert a date value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - date value

add

```
public void add(int index,  
                boolean data)
```

(continued from last page)

Insert a boolean value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - boolean value

set

```
public void set(int index,  
    AMFData data)
```

Set an array item

Parameters:

data - AMFData object

set

```
public void set(int index,  
    String data)
```

Set an string value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - string value

set

```
public void set(int index,  
    double data)
```

Set an double value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - double value

set

```
public void set(int index,  
    int data)
```

Set an int value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - int value

set

```
public void set(int index,  
    long data)
```

Set an long value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - long value

set

```
public void set(int index,  
               java.util.Date data)
```

Set an date value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - date value

set

```
public void set(int index,  
               boolean data)
```

Set an boolean value (will be wrapped in an AMFDataItem object)

Parameters:

index - index
data - boolean value

getType

```
public int getType(int index)
```

Get type of item at index. Return AMFData.DATA_TYPE_UNKNOWN if item does not exist

Parameters:

index

Returns:

type of item at index

get

```
public AMFData get(int index)
```

Get item at index

Parameters:

index

Returns:

Returns AMFData object or null if out of bounds

getString

```
public String getString(int index)
```

Get item at index return as String

Parameters:

index

Returns:

Return item as String or null if out of bounds

getInt

```
public int getInt(int index)
```

Get item at index return as int

Parameters:

index

Returns:

Return item as int or 0 if out of bounds

getLong

```
public long getLong(int index)
```

Get item at index return as long

Parameters:

index

Returns:

Return item as long or 0 if out of bounds

getDouble

```
public double getDouble(int index)
```

Get item at index return as double

Parameters:

index

Returns:

Return item as double or 0 if out of bounds

getFloat

```
public float getFloat(int index)
```

Get item at index return as float

Parameters:

index

Returns:

Return item as float or 0 if out of bounds

getShort

```
public short getShort(int index)
```

Get item at index return as short

Parameters:

index

(continued from last page)

Returns:

Return item as short or 0 if out of bounds

getBytes

```
public byte getBytes(int index)
```

Get item at index return as byte

Parameters:

index

Returns:

Return item as byte or 0 if out of bounds

getBoolean

```
public boolean getBoolean(int index)
```

Get item at index return as boolean

Parameters:

index

Returns:

Return item as boolean or false if out of bounds

getDate

```
public java.util.Date getDate(int index)
```

Get item at index return as Date

Parameters:

index

Returns:

Return item as Date or null if out of bounds

getObject

```
public AMFDataObj getObject(int index)
```

Get item at index return as AMFDataObj

Parameters:

index

Returns:

Return item as AMFDataObj or null if out of bounds

deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

(continued from last page)

deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context,  
    byte[] prepend)
```

serialize

```
public byte[] serialize()
```

Serial object to byte array

serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

serialize

```
public byte[] serialize(AMFDataContextSerialize context,  
    byte[] prepend)
```

getValue

public Object **getValue()**

Convert object to Java native class

toString

public String **toString()**

Return object as formatted string

com.wowza.wms.amf

Class AMFDataMixedArray

```

java.lang.Object
|
+-com.wowza.wms.amf.AMFData
|   |
|   +-com.wowza.wms.amf.AMFDataObj
|       |
|       +-com.wowza.wms.amf.AMFDataMixedArray

```

All Implemented Interfaces:

[IAMFDataObj](#)

```

public class AMFDataMixedArray
extends AMFDataObj

```

AMFDataMixedArray: class for marshalling data between Wowza Pro server and Flash client. Array of mixed data types. An Array object created in the Flash client is wrapped in this data type when sent to the Wowza Pro server.

Create Array of Strings

```

AMFDataMixedArray amfDataMixedArray = new AMFDataMixedArray();

amfDataMixedArray.put("0", "item1");
amfDataMixedArray.put("1", "item2");
amfDataMixedArray.put("2", "item3");

```

Iterate Mixed Array

```

AMFDataMixedArray amfDataMixedArray;

int len = amfDataMixedArray.size();
for(int i=0;i<len;i++)
{
    String value = amfDataMixedArray.getString(i);
    int itemType = amfDataMixedArray.getType(i);
    WMSLoggerFactory.getLogger(null).debug("item:
["+i+": "+amfDataMixedArray.getKey(i)+"]="+value+" type:"+itemType);
}

```

NOTE: A AMFDataMixedArray is exactly the same as a AMFDataObj except its type is DATA_TYPE_MIXED_ARRAY.

This objects acts like a Map and a List at the same time. As items are added by key the order and position of each object is recorded. Objects can be retrieved either by key or by index.

Fields inherited from class [com.wowza.wms.amf.AMFDataObj](#)

[DECODE_OBJ_REF](#), [DECODE_TRAITS](#), [DECODE_TRAITS_EXT](#), [DECODE_TRAITS_REF](#), [DECODE_UNDEFINED](#), [members](#), [order](#), [trait](#)

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF_LEVEL0](#), [AMF_LEVEL3](#), [DATA_TYPE_AMF3](#), [DATA_TYPE_AMF3_ARRAY](#), [DATA_TYPE_AMF3_BOOLEAN_FALSE](#), [DATA_TYPE_AMF3_BOOLEAN_TRUE](#), [DATA_TYPE_AMF3_BYTEARRAY](#), [DATA_TYPE_AMF3_DATE](#), [DATA_TYPE_AMF3_INTEGER](#), [DATA_TYPE_AMF3_NULL](#), [DATA_TYPE_AMF3_NUMBER](#), [DATA_TYPE_AMF3_OBJECT](#), [DATA_TYPE_AMF3_STRING](#), [DATA_TYPE_AMF3_UNDEFINED](#), [DATA_TYPE_AMF3_XML_LEGACY](#), [DATA_TYPE_AMF3_XML_TOP](#), [DATA_TYPE_ARRAY](#), [DATA_TYPE_AS_OBJECT](#), [DATA_TYPE_BOOLEAN](#), [DATA_TYPE_BYTEARRAY](#), [DATA_TYPE_CUSTOM_CLASS](#), [DATA_TYPE_DATE](#), [DATA_TYPE_INTEGER](#), [DATA_TYPE_LONG_STRING](#), [DATA_TYPE_MIXED_ARRAY](#), [DATA_TYPE_MOVIE_CLIP](#), [DATA_TYPE_NULL](#), [DATA_TYPE_NUMBER](#), [DATA_TYPE_OBJECT](#), [DATA_TYPE_OBJECT_END](#), [DATA_TYPE_RECORDSET](#), [DATA_TYPE_REFERENCE_OBJECT](#), [DATA_TYPE_STRING](#), [DATA_TYPE_UNDEFINED](#), [DATA_TYPE_UNKNOWN](#), [DATA_TYPE_XML](#), [DATA_TYPE_XML_TOP](#), [MILLS_PER_HOUR](#), [type](#)

Constructor Summary

public	AMFDataMixedArray() Create empty AMFDataMixedArray object
public	AMFDataMixedArray (byte[] data) Deserialize entire data array and create AMFDataMixedArray object
public	AMFDataMixedArray (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataMixedArray object
public	AMFDataMixedArray (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataMixedArray object
public	AMFDataMixedArray (java.nio.ByteBuffer data, AMFDataContextDeserialize context)

Method Summary

void	deserialize (java.nio.ByteBuffer data)
void	deserialize (java.nio.ByteBuffer data, AMFDataContextDeserialize context)
void	serialize (java.io.DataOutputStream out)
void	serialize (java.io.DataOutputStream out, AMFDataContextSerialize context)
void	serialize (java.io.DataOutputStream out, int objectEncoding)
String	toString () Return object as formatted string

Methods inherited from class [com.wowza.wms.amf.AMFDataObj](#)

[containsKey](#), [deserialize](#), [deserialize](#), [get](#), [get](#), [getBoolean](#), [getBoolean](#), [getBytes](#), [getBytes](#), [getClassName](#), [getDate](#), [getDate](#), [getDouble](#), [getDouble](#), [getFloat](#), [getFloat](#), [getInt](#), [getInt](#), [getKey](#), [getKeys](#), [getLong](#), [getLong](#), [getObject](#), [getObject](#), [getShort](#), [getShort](#), [getString](#), [getString](#), [getTrait](#), [getValue](#), [put](#), [put](#), [put](#), [put](#), [put](#), [put](#), [put](#), [remove](#), [remove](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setClassName](#), [size](#), [toString](#)

Methods inherited from class [com.wowza.wms.amf.AMFData](#)

[createContextDeserialize](#), [createContextDeserialize](#), [createContextSerialize](#), [createContextSerialize](#), [deserialize](#), [deserialize](#), [deserializeInnerObject](#), [getReference](#), [getType](#), [getValue](#), [isAMF3Start](#), [isArrayStart](#), [isByteArrayStart](#), [isMixedArrayStart](#), [isObjEnd](#), [isObjStart](#), [peekByte](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [serialize](#), [setType](#), [skipByte](#), [testNextByte](#), [triggerAMF3Switch](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.amf.IAMFDataObj](#)

[containsKey](#), [get](#), [get](#), [getBoolean](#), [getBoolean](#), [getBytes](#), [getBytes](#), [getDate](#), [getDate](#), [getDouble](#), [getDouble](#), [getFloat](#), [getFloat](#), [getInt](#), [getInt](#), [getKey](#), [getKeys](#), [getLong](#), [getLong](#), [getObject](#), [getObject](#), [getShort](#), [getShort](#), [getString](#), [getString](#), [put](#), [put](#), [put](#), [put](#), [put](#), [put](#), [remove](#), [remove](#)

Constructors

AMFDataMixedArray

```
public AMFDataMixedArray()
```

Create empty AMFDataMixedArray object

AMFDataMixedArray

```
public AMFDataMixedArray(byte[] data)
```

Deserialize entire data array and create AMFDataMixedArray object

Parameters:

data - binary data

AMFDataMixedArray

```
public AMFDataMixedArray(byte[] data,  
                           int offset,  
                           int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataMixedArray object

Parameters:

data - binary data

(continued from last page)

offset - starting offset into data
size - size of data to deserialize

AMFDataMixedArray

```
public AMFDataMixedArray( java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataMixedArray object

Parameters:

data - binary data

AMFDataMixedArray

```
public AMFDataMixedArray( java.nio.ByteBuffer data,  
                           AMFDataContextDeserialize context)
```

Methods

deserialize

```
public void deserialize( java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

deserialize

```
public void deserialize( java.nio.ByteBuffer data,  
                           AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

serialize

```
public void serialize( java.io.DataOutputStream out)
```

Serialize object to output stream

serialize

```
public void serialize( java.io.DataOutputStream out,  
                       int objectEncoding)
```

Serialize object to output stream

serialize

```
public void serialize( java.io.DataOutputStream out,  
                           AMFDataContextSerialize context)
```

Serialize object to output stream

toString

```
public String toString()
```

Return object as formatted string

com.wowza.wms.amf

Class AMFDataObj

```
java.lang.Object
|
+-com.wowza.wms.amf.AMFData
|   |
|   +-com.wowza.wms.amf.AMFDataObj
```

All Implemented Interfaces:

[IAMFDataObj](#)

Direct Known Subclasses:

[AMFDataMixedArray](#)

```
public class AMFDataObj
extends AMFData
implements IAMFDataObj
```

AMFDataObj: class for marshalling data between Wowza Pro server and Flash client. Object with attributes. Implementation is very similar to a java.util.Map. Each parameter is an item in the map.

Create AMFDataObj

```
AMFDataObj amfDataObj = new AMFDataObj();

amfDataObj.put("key1", "item1");
amfDataObj.put("key2", "item2");
amfDataObj.put("key3", "item3");
```

Iterate AMFDataObj

```
AMFDataObj amfDataObj;

List keys = amfDataObj.getKeys();
Iterator iter = keys.iterator();
while(iter.hasNext())
{
    String key = (String)iter.next();
    AMFData value = amfDataObj.get(key);
    int itemType = value.getType();
    WMSLoggerFactory.getLogger(null).debug(key+"="+value.toString()+"
(type:"+itemType+")");
}
```

Direct Access To Attributes

```
AMFDataObj amfDataObj;

// If you know the type you can access it directly
String dataString = amfDataObj.getString("stringData");
long dataLong = amfDataObj.getLong("longData");
double dataDouble = amfDataObj.getDouble("doubleData");
boolean dataBoolean = amfDataObj.getBoolean("booleanData");

// This illustrate how to decode the value if
// you don't know the type
AMFData myItemKey1 = amfDataObj.get("theData");
switch (myItemKey1.getType())
{
default:
case AMFDataItem.DATA_TYPE_UNDEFINED:
case AMFDataItem.DATA_TYPE_UNKNOWN:
case AMFDataItem.DATA_TYPE_NULL:
    // the value is null or undefined
    break;
case AMFDataItem.DATA_TYPE_NUMBER:
    double amfDataDouble = ((AMFDataItem)myItemKey1).doubleValue();
    break;
case AMFDataItem.DATA_TYPE_BOOLEAN:
    boolean amfDataBoolean = ((AMFDataItem)myItemKey1).booleanValue();
    break;
case AMFDataItem.DATA_TYPE_STRING:
    String amfDataString = ((AMFDataItem)myItemKey1).toString();
    break;
case AMFDataItem.DATA_TYPE_DATE:
    Date amfDataDate = ((AMFDataItem)myItemKey1).dateValue();
    break;
case AMFDataItem.DATA_TYPE_OBJECT:
    AMFDataObj amfDataValObj = (AMFDataObj)myItemKey1;
    break;
case AMFDataItem.DATA_TYPE_MIXED_ARRAY:
    AMFDataMixedArray amfDataMixedArray = (AMFDataMixedArray)myItemKey1;
    break;
case AMFDataItem.DATA_TYPE_ARRAY:
    AMFDataArray amfDataArray = (AMFDataArray)myItemKey1;
    break;
}
```

NOTE: A AMFDataObj is exactly the same as a AMFDataMixedArray except its type is DATA_TYPE_OBJECT.

Field Summary

public static final	DECODE_OBJ_REF Value: 1
public static final	DECODE_TRAITS Value: 4
public static final	DECODE_TRAITS_EXT Value: 3
public static final	DECODE_TRAITS_REF Value: 2
public static final	DECODE_UNDEFINED Value: 0
protected	members
protected	order
protected	trait

Fields inherited from class [com.wowza.wms.amf.AMFData](#)

[AMF_LEVEL0](#), [AMF_LEVEL3](#), [DATA_TYPE_AMF3](#), [DATA_TYPE_AMF3_ARRAY](#), [DATA_TYPE_AMF3_BOOLEAN_FALSE](#),
[DATA_TYPE_AMF3_BOOLEAN_TRUE](#), [DATA_TYPE_AMF3_BYTEARRAY](#), [DATA_TYPE_AMF3_DATE](#),
[DATA_TYPE_AMF3_INTEGER](#), [DATA_TYPE_AMF3_NULL](#), [DATA_TYPE_AMF3_NUMBER](#), [DATA_TYPE_AMF3_OBJECT](#),
[DATA_TYPE_AMF3_STRING](#), [DATA_TYPE_AMF3_UNDEFINED](#), [DATA_TYPE_AMF3_XML_LEGACY](#),
[DATA_TYPE_AMF3_XML_TOP](#), [DATA_TYPE_ARRAY](#), [DATA_TYPE_AS_OBJECT](#), [DATA_TYPE_BOOLEAN](#),
[DATA_TYPE_BYTEARRAY](#), [DATA_TYPE_CUSTOM_CLASS](#), [DATA_TYPE_DATE](#), [DATA_TYPE_INTEGER](#),
[DATA_TYPE_LONG_STRING](#), [DATA_TYPE_MIXED_ARRAY](#), [DATA_TYPE_MOVIE_CLIP](#), [DATA_TYPE_NULL](#),
[DATA_TYPE_NUMBER](#), [DATA_TYPE_OBJECT](#), [DATA_TYPE_OBJECT_END](#), [DATA_TYPE_RECORDSET](#),
[DATA_TYPE_REFERENCE_OBJECT](#), [DATA_TYPE_STRING](#), [DATA_TYPE_UNDEFINED](#), [DATA_TYPE_UNKNOWN](#),
[DATA_TYPE_XML](#), [DATA_TYPE_XML_TOP](#), [MILLS_PER_HOUR](#), [type](#)

Constructor Summary

public	AMFDataObj () Create empty AMFDataObj object
public	AMFDataObj (byte[] data) Deserialize entire data array and create AMFDataObj object
public	AMFDataObj (byte[] data, int offset, int size) Deserialize data array starting at offset for size bytes and create AMFDataObj object
public	AMFDataObj (java.nio.ByteBuffer data) Deserialize entire data array and create AMFDataObj object
public	AMFDataObj (java.nio.ByteBuffer data, AMFDataContextDeserialize context)

Method Summary

boolean	<u>containsKey</u> (String name)
void	<u>deserialize</u> (java.nio.ByteBuffer data)
void	<u>deserialize</u> (java.nio.ByteBuffer data, <u>AMFDataContextDeserialize</u> context)
<u>AMFData</u>	<u>get</u> (int index)
<u>AMFData</u>	<u>get</u> (String name)
boolean	<u>getBoolean</u> (int index)
boolean	<u>getBoolean</u> (String name)
byte	<u>getBytes</u> (int index)
byte	<u>getBytes</u> (String name)
String	<u>getClassName</u> ()
java.util.Date	<u>getDate</u> (int index)
java.util.Date	<u>getDate</u> (String name)
double	<u>getDouble</u> (int index)
double	<u>getDouble</u> (String name)
float	<u>getFloat</u> (int index)
float	<u>getFloat</u> (String name)
int	<u>getInt</u> (int index)
int	<u>getInt</u> (String name)
String	<u>getKey</u> (int index)
java.util.List	<u>getKeys</u> ()
long	<u>getLong</u> (int index)
long	<u>getLong</u> (String name)
<u>AMFDataObj</u>	<u>getObject</u> (int index)

AMFDataObj	getObject (String name)
short	getShort (int index)
short	getShort (String name)
String	getString (int index)
String	getString (String name)
AMFDataTrait	getTrait ()
Object	getValue ()
void	put (String name, AMFData data)
void	put (String name, boolean data)
void	put (String name, java.util.Date data)
void	put (String name, double data)
void	put (String name, int data)
void	put (String name, long data)
void	put (String name, String data)
AMFData	remove (int index)
AMFData	remove (String name)
byte[]	serialize ()
byte[]	serialize (AMFDataContextSerialize context)
void	serialize (java.io.DataOutputStream out)
void	serialize (java.io.DataOutputStream out, AMFDataContextSerialize context)
void	serialize (java.io.DataOutputStream out, int objectEncoding)
byte[]	serialize (int objectEncoding)
void	setClassName (String className)
int	size () Return the number of members of this object/array

String	toString() Return object as formatted string
--------	-----------------------------------------------------------------

Methods inherited from class com.wowza.wms.amf.AMFData
createContextDeserialize , createContextDeserialize , createContextSerialize , createContextSerialize , deserialize , deserialize , deserializeInnerObject , getReference , getType , getValue , isAMF3Start , isArrayStart , isByteArrayStart , isMixedArrayStart , isObjEnd , isObjStart , peekByte , serialize , serialize , serialize , serialize , serialize , setType , skipByte , testNextByte , triggerAMF3Switch

Methods inherited from class java.lang.Object
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface com.wowza.wms.amf.IAMFDataObj
containsKey , get , get , getBoolean , getBoolean , getBytes , getBytes , getDate , getDate , getDouble , getDouble , getFloat , getFloat , getInt , getInt , getKey , getKeys , getLong , getLong , getObject , getObject , getShort , getShort , getString , getString , put , put , put , put , put , put , remove , remove

Fields

DECODE_UNDEFINED

public static final int **DECODE_UNDEFINED**

Constant value: 0

DECODE_OBJ_REF

public static final int **DECODE_OBJ_REF**

Constant value: 1

DECODE_TRAITS_REF

public static final int **DECODE_TRAITS_REF**

Constant value: 2

DECODE_TRAITS_EXT

public static final int **DECODE_TRAITS_EXT**

Constant value: 3

DECODE_TRAITS

public static final int **DECODE_TRAITS**

(continued from last page)

Constant value: **4**

members

protected java.util.Map **members**

order

protected java.util.List **order**

trait

protected com.wowza.wms.amf.AMFDataTrait **trait**

Constructors

AMFDataObj

```
public AMFDataObj()
```

Create empty AMFDataObj object

AMFDataObj

```
public AMFDataObj(byte[] data)
```

Deserialize entire data array and create AMFDataObj object

Parameters:

data - binary data

AMFDataObj

```
public AMFDataObj(byte[] data,  
                  int offset,  
                  int size)
```

Deserialize data array starting at offset for size bytes and create AMFDataObj object

Parameters:

data - binary data

offset - starting offset into data

size - size of data to deserialize

AMFDataObj

```
public AMFDataObj(java.nio.ByteBuffer data)
```

Deserialize entire data array and create AMFDataObj object

Parameters:

(continued from last page)

data - binary data

AMFDataObj

```
public AMFDataObj(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Methods

size

```
public int size()
```

Return the number of members of this object/array

Returns:

number of members

containsKey

```
public boolean containsKey(String name)
```

put

```
public void put(String name,  
    AMFData data)
```

put

```
public void put(String name,  
    String data)
```

put

```
public void put(String name,  
    double data)
```

put

```
public void put(String name,  
    int data)
```

put

```
public void put(String name,  
    long data)
```

(continued from last page)

put

```
public void put(String name,  
               java.util.Date data)
```

put

```
public void put(String name,  
               boolean data)
```

getKeys

```
public java.util.List getKeys()
```

getKey

```
public String getKey(int index)
```

get

```
public AMFData get(String name)
```

get

```
public AMFData get(int index)
```

remove

```
public AMFData remove(String name)
```

remove

```
public AMFData remove(int index)
```

getString

```
public String getString(String name)
```

getInt

```
public int getInt(String name)
```

getLong

```
public long getLong(String name)
```

getShort

```
public short getShort(String name)
```

getDouble

```
public double getDouble(String name)
```

getFloat

```
public float getFloat(String name)
```

getByte

```
public byte getByte(String name)
```

getBoolean

```
public boolean getBoolean(String name)
```

getDate

```
public java.util.Date getDate(String name)
```

getObject

```
public AMFDataObj getObject(String name)
```

getString

```
public String getString(int index)
```

(continued from last page)

getInt

```
public int getInt(int index)
```

getLong

```
public long getLong(int index)
```

getShort

```
public short getShort(int index)
```

getBytes

```
public byte getBytes(int index)
```

getDouble

```
public double getDouble(int index)
```

getFloat

```
public float getFloat(int index)
```

getBoolean

```
public boolean getBoolean(int index)
```

getDate

```
public java.util.Date getDate(int index)
```

getObject

```
public AMFDataObj getObject(int index)
```

(continued from last page)

deserialize

```
public void deserialize(java.nio.ByteBuffer data)
```

Deserialize data in byte buffer

deserialize

```
public void deserialize(java.nio.ByteBuffer data,  
    AMFDataContextDeserialize context)
```

Deserialize data in byte buffer

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    int objectEncoding)
```

Serialize object to output stream

serialize

```
public void serialize(java.io.DataOutputStream out,  
    AMFDataContextSerialize context)
```

Serialize object to output stream

serialize

```
public byte[] serialize()
```

Serial object to byte array

serialize

```
public byte[] serialize(int objectEncoding)
```

Serial object to byte array

serialize

```
public byte[] serialize(AMFDataContextSerialize context)
```

Serial object to byte array

getValue

```
public Object getValue()
```

Convert object to Java native class

(continued from last page)

toString

```
public String toString()
```

Return object as formatted string

getClassName

```
public String getClassName()
```

setClassName

```
public void setClassName(String className)
```

getTrait

```
public AMFDataTrait getTrait()
```

com.wowza.wms.amf

Class AMFDataTrait

java.lang.Object

└─com.wowza.wms.amf.AMFDataTrait

public class **AMFDataTrait**
extends Object

AMF trait used to describe an AMF class in AMF3

Constructor Summary

public	AMFDataTrait () Constructor
--------	-------------------------------------------------

Method Summary

void	addMember (String member) Add a member
AMFDataTrait	clone () clone the trait
String	getClassName () Get class name
AMFData	getInnerObj () Get inner object
String	getMember (int i) Get member by index
int	getMemberCount () Get the number of members
java.util.List	getMembers () Get a list of trait members
boolean	isDynamic () Is class dynamic
boolean	isMember (String member) Return true if member of this trait
void	setClassName (String className) Set class name
void	setDynamic (boolean isDynamic) Set isDynamic
void	setInnerObj (AMFData innerObj) Set inner object

Methods inherited from class `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructors

AMFDataTrait

```
public AMFDataTrait()
```

Constructor

Methods

clone

```
public AMFDataTrait clone()
```

clone the trait

addMember

```
public void addMember(String member)
```

Add a member

Parameters:

member - member name

isMember

```
public boolean isMember(String member)
```

Return true if member of this trait

Parameters:

member - member name

Returns:

true, if member

getMembers

```
public java.util.List getMembers()
```

Get a list of trait members

Returns:

list of trait members

getMemberCount

```
public int getMemberCount()
```

(continued from last page)

Get the number of members

Returns:

number of members

getMember

```
public String getMember(int i)
```

Get member by index

Parameters:

i - index

Returns:

member name

getClassName

```
public String getClassName()
```

Get class name

Returns:

class name

setClassName

```
public void setClassName(String className)
```

Set class name

Parameters:

className - class name

isDynamic

```
public boolean isDynamic()
```

Is class dynamic

Returns:

true, if dynamic

setDynamic

```
public void setDynamic(boolean isDynamic)
```

Set isDynamic

Parameters:

isDynamic - true, if dynamic

getInnerObj

```
public AMFData getInnerObj()
```

Get inner object

(continued from last page)

Returns:

inner object

setInnerObj

```
public void setInnerObj(AMFData innerObj)
```

Set inner object

Parameters:

innerObj - inner object

com.wowza.wms.amf

Class AMFObj

java.lang.Object

└─com.wowza.wms.amf.AMFObj

public class **AMFObj**
extends Object

AMFObj: class that stores the state of channel between the client and the server.

Constructor Summary

public	AMFObj(int id) Create new AMFObj for a given channel (id)
public	AMFObj(int id, int objectEncoding) Create new AMFObj for a given channel (id)

Method Summary

void	addChunk(byte[] buffer, int offset, int len) Add a chunk to the chunk list
void	clearByteContainer() Clear the byte container
long	getAbsTimecode() Get the absolute time code
int	getByteContainerLevel() Fake container for processing
long	getChunkCounter()
java.util.List	getChunks() Get the chunks that make up this packet
int	getId() Get channel id
int	getObjectEncoding()
int	getSize() Get packet size
int	getSrc() Get stream id (0 if not stream data)
long	getTimecode() Get timecode (milliseconds) sometimes relative

int	<u>getType()</u> Get content type IVHost.CONTENTTYPE_*
long	<u>incAbsTimecode(long absTimecode)</u> Increment the absolute timecode
void	<u>incByteContainerLevel(int byteContainerLevel)</u> Fake container for processing
boolean	<u>isByteContainerEmpty()</u> Fake container for processing
boolean	<u>isByteContainerFull()</u> Fake container for processing
boolean	<u>isLastSentAbsTimecode()</u>
boolean	<u>isLongTimecode()</u> Get is a 32 bit timecode
boolean	<u>isNew()</u> Is this a new packet.
boolean	<u>isObjectEncodingAMF0()</u>
boolean	<u>isObjectEncodingAMF3()</u>
long	<u>setAbsTimecodeLong(long absTimecode)</u> Set the absolute timecode
long	<u>setAbsTimecodeShort(long absTimecode)</u> Set the absolute timecode
void	<u>setByteContainerLevel(int byteContainerLevel)</u> Fake container for processing
void	<u>setChunkCounter(long chunkCounter)</u>
void	<u>setId(int id)</u> Set channel id
void	<u>setLastSentAbsTimecode(boolean isLastSentAbsTimecode)</u>
void	<u>setLongTimecode(boolean isLongTimecode)</u> Set is a 32 bit timecode
void	<u>setNew(boolean isNew)</u> Set is new packet
void	<u>setObjectEncoding(int objectEncoding)</u>
void	<u>setSize(int size)</u> Set packet size
void	<u>setSrc(int src)</u> Set stream id (0 if not stream data)

void	<code>setTimecode</code> (long timecode) Set timecode (milliseconds) sometimes relative
void	<code>setType</code> (int type) Set content type IVHost.CONTENTTYPE_*
String	<code>toString</code> () Return object as formatted string

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

AMFObj

```
public AMFObj(int id)
```

Create new AMFObj for a given channel (id)

Parameters:

id - channel id

AMFObj

```
public AMFObj(int id,  
               int objectEncoding)
```

Create new AMFObj for a given channel (id)

Parameters:

id - channel id

objectEncoding - object encoding level (AMF0 or AMF3)

Methods

getChunks

```
public java.util.List getChunks()
```

Get the chunks that make up this packet

Returns:

chunks that make up this packet

addChunk

```
public void addChunk(byte[] buffer,  
                     int offset,  
                     int len)
```

Add a chunk to the chunk list

Parameters:

(continued from last page)

buffer - buffer
offset - offset
len - length

getId

```
public int getId()
```

Get channel id

Returns:

channel id

setId

```
public void setId(int id)
```

Set channel id

Parameters:

id - channel id

getSize

```
public int getSize()
```

Get packet size

Returns:

packet size

setSize

```
public void setSize(int size)
```

Set packet size

Parameters:

size - packet size

getType

```
public int getType()
```

Get content type IVHost.CONTENTTYPE_*

Returns:

content type

setType

```
public void setType(int type)
```

Set content type IVHost.CONTENTTYPE_*

Parameters:

type - content type

getSrc

```
public int getSrc()
```

Get stream id (0 if not stream data)

Returns:

stream id

setSrc

```
public void setSrc(int src)
```

Set stream id (0 if not stream data)

Parameters:

src - stream id

toString

```
public String toString()
```

Return object as formatted string

getTimecode

```
public long getTimecode()
```

Get timecode (milliseconds) sometimes relative

Returns:

timecode (milliseconds)

setTimecode

```
public void setTimecode(long timecode)
```

Set timecode (milliseconds) sometimes relative

Parameters:

timecode - timecode (milliseconds)

isNew

```
public boolean isNew()
```

Is this a new packet. If new entire packet header needs to be sent

Returns:

is new packet

setNew

```
public void setNew(boolean isNew)
```

Set is new packet

(continued from last page)

Parameters:

isNew - is new packet

getAbsTimecode

```
public long getAbsTimecode()
```

Get the absolute time code

Returns:

absolute timecode

setAbsTimecodeLong

```
public long setAbsTimecodeLong(long absTimecode)
```

Set the absolute timecode

Parameters:

absTimecode - absolute timecode

Returns:

absolute timecode

setAbsTimecodeShort

```
public long setAbsTimecodeShort(long absTimecode)
```

Set the absolute timecode

Parameters:

absTimecode

Returns:

absolute timecode

incAbsTimecode

```
public long incAbsTimecode(long absTimecode)
```

Increment the absolute timecode

Parameters:

absTimecode - absolute timecode

Returns:

absolute timecode

getByteContainerLevel

```
public int getByteContainerLevel()
```

Fake container for processing

Returns:

current container level

(continued from last page)

clearByteContainer

```
public void clearByteContainer()
```

Clear the byte container

setByteContainerLevel

```
public void setByteContainerLevel(int byteContainerLevel)
```

Fake container for processing

Parameters:

byteContainerLevel - current container level

incByteContainerLevel

```
public void incByteContainerLevel(int byteContainerLevel)
```

Fake container for processing

Parameters:

byteContainerLevel - current container level

isByteContainerEmpty

```
public boolean isByteContainerEmpty()
```

Fake container for processing

Returns:

is container full

isByteContainerFull

```
public boolean isByteContainerFull()
```

Fake container for processing

Returns:

is container full

isLongTimecode

```
public boolean isLongTimecode()
```

Get is a 32 bit timecode

Returns:

true if 32 bit timecode

setLongTimecode

```
public void setLongTimecode(boolean isLongTimecode)
```

Set is a 32 bit timecode

Parameters:

(continued from last page)

isLongTimecode - is a 32 bit timecode

isLastSentAbsTimecode

```
public boolean isLastSentAbsTimecode()
```

setLastSentAbsTimecode

```
public void setLastSentAbsTimecode(boolean isLastSentAbsTimecode)
```

isObjectEncodingAMF3

```
public boolean isObjectEncodingAMF3()
```

isObjectEncodingAMF0

```
public boolean isObjectEncodingAMF0()
```

setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

getObjectEncoding

```
public int getObjectEncoding()
```

getChunkCounter

```
public long getChunkCounter()
```

setChunkCounter

```
public void setChunkCounter(long chunkCounter)
```

com.wowza.wms.amf Class AMFObjChunk

java.lang.Object

└─com.wowza.wms.amf.AMFObjChunk

```
public class AMFObjChunk
extends Object
```

Field Summary

public	buffer
public	len
public	offset

Constructor Summary

public	AMFObjChunk (byte[] buffer, int offset, int len)
--------	------------------------------------------------------------------

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

buffer

```
public byte buffer
```

offset

```
public int offset
```

len

```
public int len
```

Constructors

(continued from last page)

AMFObjChunk

```
public AMFObjChunk(byte[] buffer,  
                  int offset,  
                  int len)
```

com.wowza.wms.amf

Class AMPacket

java.lang.Object

└─com.wowza.wms.amf.AMPacket

public class **AMFPacket**
extends Object

AMFPacket: data container for data being transferred to and from the server from the Flash client. AMFPacket is also used to store data read/written to/from an flv file.

Constructor Summary

public	AMFPacket() Create new empty packet
public	AMFPacket(int type, int src, int size) Create new packet with given values

Method Summary

int	addData(byte[] data, int offset, int size) Add data to the packet
int	addDataEx(byte[] srcData, int srcOffset, int destOffset, int srcBytes) Add data to the packet
static int	calcTotalPacketSize(int packetSize, int headerSize, int chunkSize, int amfNumber, boolean isLongTimecode) Calculate the total packet size for given packet parameters
AMFPacket	clone()
long	getAbsTimecode() Get absolute timecode (milliseconds)
byte[]	getData() Get data as byte[]
java.nio.ByteBuffer	getDataBuffer() Get data as ByteBuffer
int	getFirstByte() Get first byte of data (used to peek into packet)
int	getMissing() Get the number of bytes remaining unfilled in the packet
int	getSecondByte() Get second byte of data (used to peek into packet)

long	<code>getSeq()</code> Get packet sequence number.
int	<code>getSize()</code> Get packet size
int	<code>getSrc()</code> Get stream id (0 if not stream data)
long	<code>getTimecode()</code> Get timecode (milliseconds) relative to the <i>previous</i> packet.
int	<code>getType()</code> Get content type IVHost.CONTENTTYPE_*
boolean	<code>isAudio()</code> Is this an audio packet IVHost.CONTENTTYPE_AUDIO
boolean	<code>isVideo()</code> Is this an audio packet IVHost.CONTENTTYPE_VIDEO
void	<code>setAbsTimecode(long absTimecode)</code> Set absolute timecode (milliseconds)
void	<code>setDataBuffer(byte[] data)</code> Set the data buffer to a byte array
void	<code>setDataBuffer(java.nio.ByteBuffer data)</code> Set the data for this packet
void	<code>setSeq(long seq)</code> Set packet sequence.
void	<code>setSize(int size)</code> Set packet size
void	<code>setSrc(int src)</code> Set stream id (0 if not stream data)
void	<code>setTimecode(long timecode)</code> Set timecode (milliseconds) relative,
void	<code>setTimecodes(long timecode, long absTimecode)</code> Set both relative and absolute timecode in one call (milliseconds)
void	<code>setType(int type)</code> Set content type IVHost.CONTENTTYPE_*
String	<code>toString()</code> Return object as formatted string
void	<code>truncatePacket(int newSize)</code>

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

AMFPacket

```
public AMFPacket()
```

Create new empty packet

AMFPacket

```
public AMFPacket(int type,  
                 int src,  
                 int size)
```

Create new packet with given values

Parameters:

type - packet content type: IVHost.CONTENT*TYPE_*

src - stream id

size - packet size (bytes)

Methods

clone

```
public AMFPacket clone()
```

getSize

```
public int getSize()
```

Get packet size

Returns:

packet size

setSize

```
public void setSize(int size)
```

Set packet size

Parameters:

size - packet size

truncatePacket

```
public void truncatePacket(int newSize)
```

getMissing

```
public int getMissing()
```

(continued from last page)

Get the number of bytes remaining unfilled in the packet

Returns:

number of bytes unfilled in packet

setDataBuffer

```
public void setDataBuffer(java.nio.ByteBuffer data)
```

Set the data for this packet

Parameters:

data - byte buffer that holds packet data

setDataBuffer

```
public void setDataBuffer(byte[] data)
```

Set the data buffer to a byte array

Parameters:

data - data buffer byte array

addData

```
public int addData(byte[] data,  
                  int offset,  
                  int size)
```

Add data to the packet

Parameters:

data - byte buffer with data
offset - offset in byte buffer
size - size of data

Returns:

number of bytes unfilled in packet

getType

```
public int getType()
```

Get content type IVHost.CONTENTTYPE_*

Returns:

content type

setType

```
public void setType(int type)
```

Set content type IVHost.CONTENTTYPE_*

Parameters:

type - content type

(continued from last page)

getSrc

```
public int getSrc()
```

Get stream id (0 if not stream data)

Returns:

stream id

setSrc

```
public void setSrc(int src)
```

Set stream id (0 if not stream data)

Parameters:

src - stream id

toString

```
public String toString()
```

Return object as formatted string

getTimecode

```
public long getTimecode()
```

Get timecode (milliseconds) relative to the *previous* packet.

Returns:

timecode (milliseconds)

setTimecodes

```
public void setTimecodes(long timecode,  
    long absTimecode)
```

Set both relative and absolute timecode in one call (milliseconds)

Note this time is relative to the *previous* packet.

Parameters:

timecode - relative timecode (milliseconds)

absTimecode - absolute timecode (milliseconds)

setTimecode

```
public void setTimecode(long timecode)
```

Set timecode (milliseconds) relative,

Note this time is relative to the *previous* packet.

Parameters:

timecode - timecode (milliseconds)

(continued from last page)

getAbsTimecode

```
public long getAbsTimecode()
```

Get absolute timecode (milliseconds)

Returns:

absolute timecode

setAbsTimecode

```
public void setAbsTimecode(long absTimecode)
```

Set absolute timecode (milliseconds)

Parameters:

absTimecode - absolute timecode

getSeq

```
public long getSeq()
```

Get packet sequence number. Used for live streams to keep track of packet ordering.

Returns:

packet sequence

setSeq

```
public void setSeq(long seq)
```

Set packet sequence. Used for live streams to keep track of packet ordering.

Parameters:

seq - packet sequence

isAudio

```
public boolean isAudio()
```

Is this an audio packet IVHost.CONTENTTYPE_AUDIO

Returns:

true if audio packet

isVideo

```
public boolean isVideo()
```

Is this an audio packet IVHost.CONTENTTYPE_VIDEO

Returns:

true if video packet

getDataBuffer

```
public java.nio.ByteBuffer getDataBuffer()
```

(continued from last page)

Get data as ByteBuffer

Returns:

data as ByteBuffer

getData

```
public byte[] getData()
```

Get data as byte[]

Returns:

data as byte[] null if no data

getFirstByte

```
public int getFirstByte()
```

Get first byte of data (used to peek into packet)

Returns:

first byte of data in packet

getSecondByte

```
public int getSecondByte()
```

Get second byte of data (used to peek into packet)

Returns:

second byte of data in packet

calcTotalPacketSize

```
public static int calcTotalPacketSize(int packetSize,  
    int headerSize,  
    int chunkSize,  
    int amfNumber,  
    boolean isLongTimecode)
```

Calculate the total packet size for given packet parameters

Parameters:

packetSize - data size
headerSize - header size
chunkSize - chunk size
amfNumber - amf number
isLongTimecode - is long timecode

Returns:

total bytes

addDataEx

```
public int addDataEx(byte[] srcData,  
    int srcOffset,  
    int destOffset,  
    int srcBytes)
```

Add data to the packet

(continued from last page)

Parameters:

srcData -- source byte buffer with data
srcOffset -- start copying from source buffer at this offset
destOffset -- copy into destination buffer from this offset
srcBytes -- size of data to copy

Returns:

number of bytes unfilled in packet

com.wowza.wms.amf Interface IAMFDataObj

All Known Implementing Classes:

[AMFDataObj](#)

public interface **IAMFDataObj**
extends

Method Summary

boolean	containsKey (String name) Return true if the object/array contains key
AMFData	get (int index) Return the object at a particular index.
AMFData	get (String name) Return the object at a particular key.
boolean	getBoolean (int index) Get item at index return as boolean
boolean	getBoolean (String name) Get item at key return as boolean
byte	getBytes (int index) Get item at index return as byte
byte	getBytes (String name) Get item at key return as byte
java.util.Date	getDate (int index) Get item at index return as Date
java.util.Date	getDate (String name) Get item at key return as Date
double	getDouble (int index) Get item at index return as double
double	getDouble (String name) Get item at key return as double
float	getFloat (int index) Get item at index return as float
float	getFloat (String name) Get item at key return as float
int	getInt (int index) Get item at index return as int
int	getInt (String name) Get item at key return as int

String	<u>getKey</u> (int index) Return the key at a particular index.
java.util.List	<u>getKeys</u> () Return a list of all the keys (the list is a copy)
long	<u>getLong</u> (int index) Get item at index return as long
long	<u>getLong</u> (String name) Get item at key return as long
<u>AMFDataObj</u>	<u>getObject</u> (int index) Get item at index return as AMFDataObj
<u>AMFDataObj</u>	<u>getObject</u> (String name) Get item at key return as AMFDataObj
short	<u>getShort</u> (int index) Get item at index return as short
short	<u>getShort</u> (String name) Get item at key return as short
String	<u>getString</u> (int index) Get item at index return as String
String	<u>getString</u> (String name) Get item at key return as String
void	<u>put</u> (String name, <u>AMFData</u> data) Put or replace object at key
void	<u>put</u> (String name, boolean data) Put or replace boolean value at key (data will be wrapped in an AMFDataItem object)
void	<u>put</u> (String name, java.util.Date data) Put or replace date value at key (data will be wrapped in an AMFDataItem object)
void	<u>put</u> (String name, double data) Put or replace double value at key (data will be wrapped in an AMFDataItem object)
void	<u>put</u> (String name, int data) Put or replace int value at key (data will be wrapped in an AMFDataItem object)
void	<u>put</u> (String name, long data) Put or replace long value at key (data will be wrapped in an AMFDataItem object)
void	<u>put</u> (String name, String data) Put or replace string value at key (data will be wrapped in an AMFDataItem object)
<u>AMFData</u>	<u>remove</u> (int index) Remove element by index
<u>AMFData</u>	<u>remove</u> (String name) Remove element by key

(continued from last page)

Methods

containsKey

```
public boolean containsKey(String name)
```

Return true if the object/array contains key

Parameters:

name - key

Returns:

Return true the object/array contains key

put

```
public void put(String name,  
    AMFData data)
```

Put or replace object at key

Parameters:

name - key

data - object

put

```
public void put(String name,  
    String data)
```

Put or replace string value at key (data will be wrapped in an AMFDataItem object)

Parameters:

name - key

data - string value

put

```
public void put(String name,  
    double data)
```

Put or replace double value at key (data will be wrapped in an AMFDataItem object)

Parameters:

name - key

data - double value

put

```
public void put(String name,  
    int data)
```

Put or replace int value at key (data will be wrapped in an AMFDataItem object)

Parameters:

name - key

data - int value

put

```
public void put(String name,  
               long data)
```

Put or replace long value at key (data will be wrapped in an AMFDataItem object)

Parameters:

name - key
data - long value

put

```
public void put(String name,  
               java.util.Date data)
```

Put or replace date value at key (data will be wrapped in an AMFDataItem object)

Parameters:

name - key
data - date value

put

```
public void put(String name,  
               boolean data)
```

Put or replace boolean value at key (data will be wrapped in an AMFDataItem object)

Parameters:

name - key
data - boolean value

getKeys

```
public java.util.List getKeys()
```

Return a list of all the keys (the list is a copy)

Returns:

new list that contains one entry for each key

getKey

```
public String getKey(int index)
```

Return the key at a particular index.

Parameters:

index

Returns:

Return key at index or null if out of bounds

get

```
public AMFData get(String name)
```

(continued from last page)

Return the object at a particular key.

Parameters:

name - key

Returns:

Return object or null if out of bounds

get

```
public AMFData get(int index)
```

Return the object at a particular index.

Parameters:

index - index

Returns:

Return object or null if out of bounds

remove

```
public AMFData remove(String name)
```

Remove element by key

Parameters:

name - key

Returns:

removed object or null if not found

remove

```
public AMFData remove(int index)
```

Remove element by index

Parameters:

index - index

Returns:

removed object or null if not found

getString

```
public String getString(String name)
```

Get item at key return as String

Parameters:

name - key

Returns:

Return item as String or null if out of bounds

(continued from last page)

getInt

```
public int getInt(String name)
```

Get item at key return as int

Parameters:

name - key

Returns:

Return item as int or 0 if out of bounds

getLong

```
public long getLong(String name)
```

Get item at key return as long

Parameters:

name - key

Returns:

Return item as long or 0 if out of bounds

getShort

```
public short getShort(String name)
```

Get item at key return as short

Parameters:

name - key

Returns:

Return item as short or 0 if out of bounds

getDouble

```
public double getDouble(String name)
```

Get item at key return as double

Parameters:

name - key

Returns:

Return item as double or 0 if out of bounds

getFloat

```
public float getFloat(String name)
```

Get item at key return as float

Parameters:

name - key

Returns:

Return item as float or 0 if out of bounds

getBytes

```
public byte getBytes(String name)
```

Get item at key return as byte

Parameters:

name - key

Returns:

Return item as byte or 0 if out of bounds

getBoolean

```
public boolean getBoolean(String name)
```

Get item at key return as boolean

Parameters:

name - key

Returns:

Return item as boolean or false if out of bounds

getDate

```
public java.util.Date getDate(String name)
```

Get item at key return as Date

Parameters:

name - key

Returns:

Return item as Date or null if out of bounds

getObject

```
public AMFDataObj getObject(String name)
```

Get item at key return as AMFDataObj

Parameters:

name - key

Returns:

Return item as AMFDataObj or null if out of bounds

getString

```
public String getString(int index)
```

Get item at index return as String

Parameters:

index - index

(continued from last page)

Returns:

Return item as String or null if out of bounds

getInt

```
public int getInt(int index)
```

Get item at index return as int

Parameters:

index - index

Returns:

Return item as int or 0 if out of bounds

getLong

```
public long getLong(int index)
```

Get item at index return as long

Parameters:

index - index

Returns:

Return item as long or 0 if out of bounds

getShort

```
public short getShort(int index)
```

Get item at index return as short

Parameters:

index - index

Returns:

Return item as short or 0 if out of bounds

getByte

```
public byte getByte(int index)
```

Get item at index return as byte

Parameters:

index - index

Returns:

Return item as byte or 0 if out of bounds

getDouble

```
public double getDouble(int index)
```

Get item at index return as double

Parameters:

(continued from last page)

index - index

Returns:

Return item as double or 0 if out of bounds

getFloat

```
public float getFloat(int index)
```

Get item at index return as float

Parameters:

index - index

Returns:

Return item as float or 0 if out of bounds

getBoolean

```
public boolean getBoolean(int index)
```

Get item at index return as boolean

Parameters:

index - index

Returns:

Return item as boolean or false if out of bounds

getDate

```
public java.util.Date getDate(int index)
```

Get item at index return as Date

Parameters:

index - index

Returns:

Return item as Date or null if out of bounds

getObject

```
public AMFDataObj getObject(int index)
```

Get item at index return as AMFDataObj

Parameters:

index - index

Returns:

Return item as AMFDataObj or null if out of bounds

Package

com.wowza.wms.application

com.wowza.wms.application Interface IApplication

public interface **IApplication**
extends

IApplication: public interface to Application object

Field Summary

public static final	<u>DEFAULT_APPLICATION_NAME</u> Value: _defapp_
---------------------	---------------------------------------------------------------------------

Method Summary

void	<u>addApplicationInstanceListener</u> (<u>IApplicationInstanceNotify</u> applicationInstanceListener) Add applicationInstance listener.
<u>IApplicationInstance</u>	<u>getAppInstance</u> (String name) Get applicationInstance object by name
java.util.List	<u>getAppInstanceNames</u> () Get a list of application instance names
String	<u>getApplicationPath</u> () Get the root path for application
String	<u>getConfigPath</u> () Get full path to Application.xml file
<u>ConnectionCounter</u>	<u>getConnectionCounter</u> () Get the connectionCounter for application
ConnectionCounterSimple	<u>getConnectionCounter</u> (int counterIndex) Get the connectionCounter for application for application for a specific technology (see IVHost.COUNTER_*)
String	<u>getDateStarted</u> () Get date application started
<u>IOPerformanceCounter</u>	<u>getIoPerformanceCounter</u> () Get the performance counter for application
<u>IOPerformanceCounter</u>	<u>getIoPerformanceCounter</u> (int counterIndex) Get the performance counter for application for a specific technology (see IVHost.COUNTER_*)
String	<u>getName</u> () Get the name of application
<u>WMSProperties</u>	<u>getProperties</u> () Get application properties

String	<u>getTimeRunning()</u> Get time application running
double	<u>getTimeRunningSeconds()</u> Get time running in seconds
<u>IVHost</u>	<u>getVHost()</u> Get the parent vHost object
boolean	<u>isAppInstanceLoaded()</u> (String name) Return true if application instance is loaded
String	<u>readAppConfig()</u> (String sName) Method to read xml config file..
void	<u>removeAppInstance()</u> (<u>IApplicationInstance</u> appInstance) Disconnect all clients connected to an application instance and remove it from the IApplication application list.
void	<u>removeApplicationInstanceListener()</u> (<u>IApplicationInstanceNotify</u> applicationInstanceListener) Remove applicationInstance listener.
void	<u>setName()</u> (String name) Set name of application
void	<u>shutdown()</u> (boolean isServerShutdown) shutdown application
void	<u>shutdownAppInstance()</u> (String appInstanceName) Shutdown an application instance by name.
boolean	<u>writeAppConfig()</u> (String sName, String data) Method to write xml config file..

Fields

DEFAULT_APPLICATION_NAME

```
public static final java.lang.String DEFAULT_APPLICATION_NAME
```

Constant value: **_defapp_**

Methods

shutdown

```
public void shutdown(boolean isServerShutdown)
```

shutdown application

Parameters:

isServerShutdown - true if due to shutdown of server

(continued from last page)

getApplicationPath

```
public String getApplicationPath()
```

Get the root path for application

Returns:

root path for application

getConfigPath

```
public String getConfigPath()
```

Get full path to Application.xml file

Returns:

full path to Application.xml file

getAppInstance

```
public IApplicationInstance getAppInstance(String name)
```

Get applicationInstance object by name

Parameters:

name - applicationInstance name

Returns:

appliationInstance object

isAppInstanceLoaded

```
public boolean isAppInstanceLoaded(String name)
```

Return true if application instance is loaded

Parameters:

name - applicationInstance name

Returns:

true if application instance is loaded

getName

```
public String getName()
```

Get the name of application

Returns:

name of application

setName

```
public void setName(String name)
```

Set name of application

Parameters:

(continued from last page)

name - name of application

getVHost

```
public IVHost getVHost( )
```

Get the parent vHost object

Returns:

parent vHost

getProperties

```
public WMSProperties getProperties( )
```

Get application properties

Returns:

application properties

addApplicationInstanceListener

```
public void addApplicationInstanceListener( IApplicationInstanceNotify  
applicationInstanceListener )
```

Add applicationInstance listener. Will be invoked each time applicationInstance created/deleted

Parameters:

applicationInstanceListener - applicationInstance listener

removeApplicationInstanceListener

```
public void removeApplicationInstanceListener( IApplicationInstanceNotify  
applicationInstanceListener )
```

Remove applicationInstance listener. Will be invoked each time applicationInstance created/deleted

Parameters:

applicationInstanceListener - applicationInstance listener

getConnectionCounter

```
public ConnectionCounter getConnectionCounter( )
```

Get the connectionCounter for application

Returns:

connectionCounter for application

getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get the connectionCounter for application for application for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

Returns:

(continued from last page)

connection ocunter

getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter()
```

Get the performance counter for application

Returns:

performance counter for application

getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

Get the performance counter for application for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

Returns:

performance counter

getDateStarted

```
public String getDateStarted()
```

Get date application started

Returns:

date application started

getTimeRunning

```
public String getTimeRunning()
```

Get time application running

Returns:

time application running

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

Returns:

time running in seconds

getAppInstanceNames

```
public java.util.List getAppInstanceNames()
```

Get a list of application instance names

Returns:

list of application instance names

removeAppInstance

public void **removeAppInstance**([IApplicationInstance](#) appInstance)

Disconnect all clients connected to an application instance and remove it from the IApplication application list. The proper way to call this is:

```
public void shutdownAppInstance(IApplicationInstance appInstance)
{
    IVHost vhost = appInstance.getVHost();
    IApplication app = appInstance.getApplication();

    WMSReadWriteLock appLock = vhost.getApplicationLock();
    appLock.writeLock().lock();
    try
    {
        app.removeAppInstance(appInstance);
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(Application.class).error("Application.shutdownAppInstance: "+
            e.toString());
    }
    finally
    {
        appLock.writeLock().unlock();
    }
}
```

Parameters:

appInstance - application instance to remove

shutdownAppInstance

public void **shutdownAppInstance**(String appInstanceName)

Shutdown an application instance by name. This will disconnect all clients connected to this application instance.

Parameters:

appInstanceName - application instance name

readAppConfig

public String **readAppConfig**(String sName)

Method to read xml config file..

(continued from last page)

writeAppConfig

```
public boolean writeAppConfig(String sName,  
                               String data)
```

Method to write xml config file..

com.wowza.wms.application Interface IApplicationInstance

public interface **IApplicationInstance**
extends

IApplicationInstance: public interface to ApplicationInstance object

Field Summary

public static final	<u>DEFAULT_APPINSTANCE_NAME</u> Value: _definst_
---------------------	----------------------------------------------------------------------------

Method Summary

void	<u>addClientListener</u> (<u>IClientNotify</u> clientListener) Add client listener.
void	<u>addDvrRecorderListener</u> (<u>ILiveStreamDvrRecorderActionNotify</u> listener) Add a Dvr Recorder listener (see: <u>ILiveStreamDvrRecorderActionNotify</u>)
void	<u>addDvrStreamManagerListener</u> (<u>IDvrStreamManagerActionNotify</u> listener) Add a Dvr Application Store Manager listener (see: <u>IDvrStoreActionNotify</u>)
void	<u>addHTTPStreamerSession</u> (<u>IHTTPStreamerSession</u> httpStreamerSession) Add a HTTPStreamerSession to this application instance
void	<u>addLiveStreamPacketizerListener</u> (<u>ILiveStreamPacketizerActionNotify</u> <u>liveStreamPacketizerListener</u>) Add a Live Stream Packetizer listener (see: <u>ILiveStreamPacketizerActionNotify</u>)
void	<u>addLiveStreamTranscoderListener</u> (<u>ILiveStreamTranscoderNotify</u> <u>liveStreamTranscoderListener</u>) Add a live stream transcoder listener
void	<u>addMediaCasterListener</u> (<u>IMediaCasterNotify</u> mediaCasterListener) Add mediaCaster listener.
void	<u>addMediaCasterListener</u> (<u>IMediaCasterNotify2</u> mediaCasterListener) Add mediaCaster listener.
void	<u>addMediaReaderListener</u> (<u>IMediaReaderActionNotify</u> mediaReaderListener) Add media reader listener.
void	<u>addMediaStreamListener</u> (<u>IMediaStreamNotify</u> mediaStreamListener) Add mediaStream listener.
void	<u>addMediaWriterListener</u> (<u>IMediaWriterActionNotify</u> listener) Add a MediaWriter listener class.
void	<u>addModuleListener</u> (<u>IModuleNotify</u> moduleListener) Add module listener.

void	<u>addPlayStreamByName</u> (<u>IMediaStream</u> stream, String name) Add a media stream to the list of streams that are listening for a published stream
void	<u>addPublisher</u> (<u>Publisher</u> publisher) Add a server side publisher to this application instance
void	<u>addRTPIncomingDatagramPortAll</u> () Allow all incoming RTP UDP ports for this application instance
void	<u>addRTPIncomingDatagramPortRange</u> (int startPort, int endPort) Add a port range to the list of valid incoming RTP UDP ports
void	<u>addRTPSession</u> (<u>RTPSession</u> rtpSession) Add an RTP session to this application instance
void	<u>addSharedObjectListener</u> (<u>ISharedObjectNotify</u> sharedObjectListener, boolean isPersistent) Add sharedObject listener.
void	<u>broadcastMsg</u> (java.util.List clientList, String handlerName) Broadcast a message to a specific list of clients connected to this application instance
void	<u>broadcastMsg</u> (java.util.List clientList, String handlerName, Object[] params) Broadcast a message to a specific list of clients connected to this application instance
void	<u>broadcastMsg</u> (String handlerName, Object[] params) Broadcast a message to all clients connected to this applicationInstance
boolean	<u>containsDvrRecorder</u> (String dvrRecorder) Does this application instance contain a references to this DVR recorder.
boolean	<u>containsHTTPStreamer</u> (String httpStreamer) Does this application instance allow streaming of a given HTTPStreamer
boolean	<u>containsLiveStreamPacketizer</u> (String liveStreamPacketizer) Does this application instance contain a references to this live stream packetizer.
boolean	<u>containsLiveStreamTranscoder</u> (String liveStreamTranscoder) Return true if this application instance contains the transcoder name
String	<u>decodeStorageDir</u> (String storageDir) This function will take a storage path that uses variables and expand the variables based on the context.
String[]	<u>getAllowDomains</u> () Get the list of domain names used to control access to this application.
<u>IApplication</u>	<u>getApplication</u> () Get parent application
int	<u>getApplicationInstanceTouchTimeout</u> () Get the application instance touch timeout (milliseconds).
int	<u>getApplicationTimeout</u> () Get application timeout (milliseconds)
<u>IClient</u>	<u>getClient</u> (int index) Deprecated. Get the client connection at index. This method is deprecated. It is best to use <u>getClient()</u> to return a List objects.

<u>IClient</u>	<u>getClientById</u> (int index) Get a client connection by the client Id
int	<u>getClientCount</u> () Get number of client connections currently connected to applicationInstance
int	<u>getClientCountTotal</u> () Get number of client connections in total that have connected to this applicationInstance
int	<u>getClientIdleFrequency</u> () Get default client idle frequency (milliseconds)
java.util.List	<u>getClients</u> () Get the set of clients currently connected to this application instance (replaces getClient(index))
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<u>getClientsLockObj</u> () Get the read/write lock for this application instance
<u>ConnectionCounter</u>	<u>getConnectionCounter</u> () Get the connectionCounter for applicationInstance
ConnectionCounterSimple	<u>getConnectionCounter</u> (int counterIndex) Get the connectionCounter for applicationInstance for a specific technology (see IVHost.COUNTER_*)
String	<u>getContextStr</u> () Returns the application context string in the form [application]/[appInstance].
String	<u>getDateStarted</u> () Get date applicationInstance started
DvrApplicationContext	<u>getDvrApplicationContext</u> () Get live stream dvr application context
<u>WMSProperties</u>	<u>getDvrProperties</u> () Get the property collection of DVR settings that are specific to this application instance.
String	<u>getDvrRecorderList</u> () Get the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)
<u>IHTTPStreamerApplicationContext</u>	<u>getHTTPStreamerApplicationContext</u> (String httpStreamName, boolean doCreate) Get the HTTPStreamer application context for a given HTTPStreamer adapter
String	<u>getHTTPStreamerList</u> () Get the comma separated list of HTTPStreamers names being used by this application (see conf/HTTPStreamers.xml)
<u>WMSProperties</u>	<u>getHTTPStreamerProperties</u> () Get the property collection of HTTPStreamer settings that are specific to this application instance
int	<u>getHTTPStreamerSessionCount</u> () Get the current number of HTTPStreamerSessions associated with this application instance
int	<u>getHTTPStreamerSessionCount</u> (int protocol) Get the current number of HTTPStreamerSessions associated with this application instance by protocol.

int	<code>getHTTPStreamerSessionCount</code> (int protocol, String streamName) Get the current number of HTTPStreamerSessions associated with this application instance and stream name by protocol .
int	<code>getHTTPStreamerSessionCount</code> (String streamName) Get the current number of HTTPStreamerSessions associated with this application instance and stream name
java.util.Map	<code>getHTTPStreamerSessionCountsByName</code> (int protocol) Get a map of session counts by name for a given protocol
java.util.List	<code>getHTTPStreamerSessions</code> () Get the HTTPStreamerSessions associated with this application instance
java.util.List	<code>getHTTPStreamerSessions</code> (int protocol) Get the HTTPStreamerSessions associated with this application instance by protocol.
java.util.List	<code>getHTTPStreamerSessions</code> (int protocol, String streamName) Get the HTTPStreamerSessions associated with this application instance for a stream name by protocol.
java.util.List	<code>getHTTPStreamerSessions</code> (String streamName) Get the HTTPStreamerSessions associated with this application instance for a stream name
<code>IOPerformanceCounter</code>	<code>getIOPerformanceCounter</code> () Get the performance counter for applicationInstance
<code>IOPerformanceCounter</code>	<code>getIOPerformanceCounter</code> (int counterIndex) Get the performance counter for applicationInstance for a specific technology (see IVHost.COUNTER_*)
long	<code>getLastTouchTime</code> () Get the last time the instance was touched (milliseconds)
<code>ILiveStreamDvrRecorderControl</code>	<code>getLiveStreamDvrRecorderControl</code> () Get the Live Stream DVR Recorder Controller.
<code>ILiveStreamPacketizerControl</code>	<code>getLiveStreamPacketizerControl</code> () Get the Live Stream Packetizer Controller.
String	<code>getLiveStreamPacketizerList</code> () Get the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)
<code>WMSProperties</code>	<code>getLiveStreamPacketizerProperties</code> () Get the property collection of LiveStreamPacketizer settings that are specific to this application instance
<code>ILiveStreamTranscoderControl</code>	<code>getLiveStreamTranscoderControl</code> () Get the Live Stream Transcoder Controller.
String	<code>getLiveStreamTranscoderList</code> () Get comma separated list of transcoders to use for this application instance
int	<code>getMaximumPendingReadBytes</code> () Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
int	<code>getMaximumPendingWriteBytes</code> () Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.

int	<u>getMaximumSetBufferTime()</u> Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
int	<u>getMaxStorageDirDepth()</u> Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths
<u>WMSProperties</u>	<u>getMediaCasterProperties()</u> Get the property collection of media caster settings that are specific to this application instance
<u>MediaCasterStreamMap</u>	<u>getMediaCasterStreams()</u> Get the media caster streams attached to this application instance
<u>IMediaCasterValidateMediaCaster</u>	<u>getMediaCasterValidator()</u> Get the MediaCaster validator interface for this application instance
<u>IMediaListProvider</u>	<u>getMediaListProvider()</u> Get the current media list provider.
int	<u>getMediaReaderContentType()</u> (String mediaType) Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE_*)
<u>WMSProperties</u>	<u>getMediaReaderProperties()</u> Get the property collection of media reader settings that are specific to this application instance
<u>WMSProperties</u>	<u>getMediaWriterProperties()</u> Get the property collection of media reader settings that are specific to this application instance
ModuleFunctions	<u>getModFunctions()</u> Get list of application modules
Object	<u>getModuleInstance()</u> (String name) Get the instance of the module class for this application instance.
ModuleList	<u>getModuleList()</u> Get the list of loaded modules.
String	<u>getName()</u> Get applicationInstance name
int	<u>getPingTimeout()</u> Get ping timeout (milliseconds)
int	<u>getPlayStreamCount()</u> (String streamName) Get the number of Flash players playing a given stream name
java.util.Map	<u>getPlayStreamCountsByName()</u> Get a map of stream names to number of Flash players playing the stream name
java.util.List	<u>getPlayStreamsByName()</u> (String name) Get a list of media streams that are listening for published stream.
<u>WMSProperties</u>	<u>getProperties()</u> Get applicationInstance properties
int	<u>getPublisherCount()</u> Get the current number of server side publishers
java.util.List	<u>getPublishers()</u> Get the set of server side publishers

java.util.List	<u>getPublishStreamNames()</u> Get the list of live stream names currently being published.
String	<u>getRepeaterOriginUrl()</u> Get the Repeater Origin URL used by the Live Stream Repeater
String	<u>getRepeaterQueryString()</u> Get the Repeater query string that is used to connect to the origin.
String	<u>getRsoStorageDir()</u> Get remote shared object storage path
String	<u>getRsoStoragePath()</u> Get the resolved storage path to the shared objects
int	<u>getRTPAVSyncMethod()</u> Get RTP audio/video sync method (RTPStream.AVSYNCMETHODS_SENDERREPORT, RTPStream.AVSYNCMETHODS_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS_RTPTIMECODE)
int	<u>getRTPIdleFrequency()</u> Set the default RTP idle frequency (milliseconds)
int	<u>getRTPMaxRTCPWaitTime()</u> Get the maximum time to wait for RTCP packets (milliseconds)
String	<u>getRTPPlayAuthenticationMethod()</u> Get the RTP play authentication method (as defined in conf/Authentication.xml)
<u>WMSProperties</u>	<u>getRTPProperties()</u> Get the property collection of RTP settings that are specific to this application instance
String	<u>getRTPPublishAuthenticationMethod()</u> Get the RTP publish authentication method (as defined in conf/Authentication.xml)
int	<u>getRTPSessionCount()</u> Get the number of RTP sessions running under this application instance
int	<u>getRTPSessionCount(String streamName)</u> Get the number of RTP player streams playing a given stream name
java.util.Map	<u>getRTPSessionCountsByName()</u> Get a map of stream names and session counts of RTP sessions
java.util.List	<u>getRTPSessions()</u> Get a list of RTP sessions running under this application instance
java.util.List	<u>getRTPSessions(String streamName)</u> Get a list of RTP sessions running under this application instance playing a given stream name
String	<u>getRTSPBindIpAddress()</u> Set the IP address to which UDP ports will be bound for RTSP/RTP sessions
String	<u>getRTSPConnectionAddressType()</u> Get the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
String	<u>getRTSPConnectionIpAddress()</u> Get the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

int	<u>getRTSPMaximumPendingWriteBytes()</u> Get the maximum number of pending write bytes for an RTSP session
String	<u>getRTSPOriginAddressType()</u> Get the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
String	<u>getRTSPOriginIpAddress()</u> Get the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
int	<u>getRTSPSessionTimeout()</u> Get the RTSP session timeout (milliseconds)
String	<u>getSharedObjectReadAccess()</u> Get the default shared object read access
<u>ISharedObjects</u>	<u>getSharedObjects()</u> Get non-persistent shared object collection
<u>ISharedObjects</u>	<u>getSharedObjects(boolean isPersistent)</u> Get either persistent or non-persistent shared object collection
String	<u>getSharedObjectWriteAccess()</u> Get the default shared object write access
String	<u>getStreamAudioSampleAccess()</u> Get the default stream audio sample access
int	<u>getStreamCount()</u> Get the total number of open streams attached to this application instance
<u>IMediaStreamFileMapper</u>	<u>getStreamFileMapper()</u> Get the stream file mapper.
String	<u>getStreamKeyDir()</u> Get the stream key path
String	<u>getStreamKeyPath()</u> Get the resolved key path to the MediaStreams encryption keys
<u>IMediaStreamNameAliasProvider</u>	<u>getStreamNameAliasProvider()</u> Get the stream name alias provider
<u>WMSProperties</u>	<u>getStreamProperties()</u> Get the property collection of stream settings that are specific to this application instance
String	<u>getStreamReadAccess()</u> Get the default stream read access
<u>MediaStreamMap</u>	<u>getStreams()</u> Get all the mediaStream objects attached to this applicationInstance
String	<u>getStreamStorageDir()</u> Get stream storage path
String	<u>getStreamStoragePath()</u> Get the resolved storage path to the MediaStreams

String	<u>getStreamType()</u> Get default streamType for application.
String	<u>getStreamVideoSampleAccess()</u> Get the default stream video sample access
String	<u>getStreamWriteAccess()</u> Get the default stream write access
String	<u>getTimeRunning()</u> Get time applicationInstance running
double	<u>getTimeRunningSeconds()</u> Get time running in seconds
LiveStreamTranscoderApplicationContext	<u>getTranscoderApplicationContext()</u> Get live stream transcoder application context
<u>WMSProperties</u>	<u>getTranscoderProperties()</u> Get the property collection of Transcoder settings that are specific to this application instance
int	<u>getValidationFrequency()</u> Get time between validation pings (milliseconds)
<u>IVHost</u>	<u>getVHost()</u> Get parent vHost
void	<u>incClientCountTotal()</u> Increment the total number of connected client counter by one
boolean	<u>isAcceptConnection()</u> Is auto accept connection on/off
boolean	<u>isRTPIncomingDatagramPortValid(int port)</u> Check a port number to be sure it is a valid RTP UDP port for this application instance
boolean	<u>isValidateFMLEConnections()</u> Returns true if validating FMLE connection (default is false)
void	<u>notifyDvrStreamManagerCreate(IDvrStreamManager dvrStoreManager)</u> Notify listeners that Dvr Application Store Manager has been created.
void	<u>notifyDvrStreamManagerDestroy(IDvrStreamManager dvrManager)</u> Notify listeners that Dvr Application Store Manager has been destroyed.
void	<u>notifyDvrStreamManagerInit(IDvrStreamManager dvrStoreManager)</u> Notify listeners that Dvr Application Store Manager has been initialized.
void	<u>notifyLiveStreamDvrRecorderCreate(ILiveStreamDvrRecorder dvr, String streamName)</u> Notify Dvr Recorder Create
void	<u>notifyLiveStreamDvrRecorderDestroy(ILiveStreamDvrRecorder dvr)</u> Notify DVR Recorder has been destroyed.
void	<u>notifyLiveStreamDvrRecorderInit(ILiveStreamDvrRecorder dvr, String streamName)</u> Notify DVR Recorder has been initialized.

void	<u>notifyLiveStreamPacketizerCreate(ILiveStreamPacketizer liveStreamPacketizer, String streamName)</u> Notify Live Stream Packetizer Create
void	<u>notifyLiveStreamPacketizerDestroy(ILiveStreamPacketizer liveStreamPacketizer)</u> Notify Live Stream Packetizer Destory
void	<u>notifyLiveStreamPacketizerInit(ILiveStreamPacketizer liveStreamPacketizer, String streamName)</u> Notify Live Stream Packetizer Init
void	<u>notifyLiveStreamTranscoderCreate(ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream)</u> Notify live stream transcoder create
void	<u>notifyLiveStreamTranscoderDestroy(ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream)</u> Notify live stream transcoder destroy
void	<u>notifyLiveStreamTranscoderInit(ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream)</u> Notify live stream transcoder init
void	<u>notifyMediaReaderClose(IMediaReader mediaReader, IMediaStream stream)</u> Notify media reader notifyMediaReaderClose
void	<u>notifyMediaReaderCreate(IMediaReader mediaReader)</u> Notify media reader notifyMediaReaderCreate
void	<u>notifyMediaReaderExtractMetaData(IMediaReader mediaReader, IMediaStream stream)</u> Notify media reader notifyMediaReaderExtractMetaData
void	<u>notifyMediaReaderInit(IMediaReader mediaReader, IMediaStream stream)</u> Notify media reader notifyMediaReaderInit
void	<u>notifyMediaReaderOpen(IMediaReader mediaReader, IMediaStream stream)</u> Notify media reader notifyMediaReaderOpen
void	<u>notifyMediaWriterOnFLVAddMetadata(IMediaStream stream, java.util.Map extraMetadata)</u> Notify all MediaWriter listeners of onFLVAddMetadata
void	<u>notifyMediaWriterOnWriteComplete(IMediaStream stream, java.io.File file)</u> Notify all MediaWriter listeners of onWriteComplete
void	<u>parseAllowDomains(String domainFilterStr)</u> Parse a comma delimited list of domain names used to control access to this application.
String	<u>readAppInstConfig(String sName)</u> Method to read xml config file..
void	<u>registerPlayRTPSession(RTPSession rtpSession)</u> Register an RTP session as a play session
void	<u>removeClientListener(IClientNotify clientListener)</u> Remove client listener.
void	<u>removeDvrRecorderListener(ILiveStreamDvrRecorderActionNotify listener)</u> Remove a Dvr Recorder listener (see: ILiveStreamDvrRecorderActionNotify)

void	<u>removeDvrStreamManagerListener</u> (<u>IDvrStreamManagerActionNotify</u> listener) Remove a Dvr Application Store Manager listener (see: IDvrStoreActionNotify)
void	<u>removeHTTPStreamerSession</u> (<u>IHTTPStreamerSession</u> httpStreamerSession) Remove a HTTPStreamerSession from this application instance
void	<u>removeLiveStreamPacketizerListener</u> (<u>ILiveStreamPacketizerActionNotify</u> liveStreamPacketizerListener) Remove a Live Stream Packetizer listener (see: ILiveStreamPacketizerActionNotify)
void	<u>removeLiveStreamTranscoderListener</u> (<u>ILiveStreamTranscoderNotify</u> liveStreamTranscoderListener) Remove a live stream transcoder listener
void	<u>removeMediaCasterListener</u> (<u>IMediaCasterNotify</u> mediaCasterListener) Remove mediaCaster listener.
void	<u>removeMediaReaderListener</u> (<u>IMediaReaderActionNotify</u> mediaReaderListener) Remove media reader listener.
void	<u>removeMediaStreamListener</u> (<u>IMediaStreamNotify</u> mediaStreamListener) Remove mediaStream listener.
void	<u>removeMediaWriterListener</u> (<u>IMediaWriterActionNotify</u> listener) remove MediaWriter listener class.
void	<u>removeModuleListener</u> (<u>IModuleNotify</u> moduleListener) Remove module listener
void	<u>removePlayStreamByName</u> (<u>IMediaStream</u> stream) Remove media stream from the list of streams that are listening for a published stream
void	<u>removePublisher</u> (<u>Publisher</u> publisher) Remove a server side publisher from this application instance
void	<u>removeRTPSession</u> (<u>RTPSession</u> rtpSession) Remove an RTP session from this application instance
void	<u>removeSharedObjectListener</u> (<u>ISharedObjectNotify</u> sharedObjectListener, boolean isPersistent) Remove sharedObject listener.
boolean	<u>resetMediaCasterStream</u> (String streamName) Reset a media caster stream
boolean	<u>resetMediaCasterStream</u> (String streamName, String streamExt) Reset a media caster stream
void	<u>setAcceptConnection</u> (boolean acceptConnection) Set is auto accept connection
void	<u>setAllowDomains</u> (String[] domainFilter) Set the list of domain names used to control access to this application.
void	<u>setApplicationInstanceTouchTimeout</u> (int applicationInstanceTouchTimeout) Set the application instance touch timeout (milliseconds).
void	<u>setApplicationTimeout</u> (int applicationTimeout) Set application timeout (milliseconds)

void	<u>setClientIdleFrequency</u> (int clientIdleFrequency) Set default client idle frequency (milliseconds)
void	<u>setDvrRecorderList</u> (String recorderList) Set the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)
void	<u>setHTTPStreamerList</u> (String httpStreamerList) Set the comma separated list of HTTPStreamer names being used by this application (see conf/HTTPStreamers.xml)
void	<u>setLiveStreamDvrRecorderControl</u> (<u>ILiveStreamDvrRecorderControl</u> controller) Set the Live Stream DVR Controller.
void	<u>setLiveStreamPacketizerControl</u> (<u>ILiveStreamPacketizerControl</u> liveStreamPacketizerControl) Set the Live Stream Packetizer Contoller.
void	<u>setLiveStreamPacketizerList</u> (String liveStreamPacketizerList) Set the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)
void	<u>setLiveStreamTranscoderControl</u> (<u>ILiveStreamTranscoderControl</u> liveStreamTranscoderControl) Set the Live Stream Transcoder Contoller.
void	<u>setLiveStreamTranscoderList</u> (String liveStreamTranscoderList) Set comma separated list of transcoders to use for this application instance
void	<u>setMaximumPendingReadBytes</u> (int maximumPendingReaderBytes) Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
void	<u>setMaximumPendingWriteBytes</u> (int maximumPendingWriteBytes) Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
void	<u>setMaximumSetBufferTime</u> (int maximumSetBufferTime) Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
void	<u>setMaxStorageDirDepth</u> (int maxStorageDirDepth) Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths
void	<u>setMediaCasterValidator</u> (<u>IMediaCasterValidateMediaCaster</u> mediaCasterValidator) Set the MediaCaster validator interface for this application instance
void	<u>setMediaListProvider</u> (<u>IMediaListProvider</u> mediaListProvider) Set the current media list provider.
void	<u>setName</u> (String name) Set applicationInstance name
void	<u>setPingTimeout</u> (int pingTimeout) Set ping timeout (milliseconds)
void	<u>setRepeaterOriginUrl</u> (String repeaterOriginUrl) Set the Repeater Origin URL used by the Live Stream Repeater

void	<u>setRepeaterQueryString</u> (String repeaterQueryString) Set the Repeater query string that is used to connect to the origin.
void	<u>setRsoStorageDir</u> (String rsoStorageDir) Set remote shared object storage path
void	<u>setRTPAVSyncMethod</u> (int rtpAVSyncMethod) Set RTP audio/video sync method (RTPStream.AVSYNCMETHODS_SENDERREPORT, RTPStream.AVSYNCMETHODS_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS_RTPTIMECODE)
void	<u>setRTPIIdleFrequency</u> (int rtspIdleFrequency) Get the default RTP idle frequency (milliseconds)
void	<u>setRTSPMaxRTCPWaitTime</u> (int rtpMaxRTCPWaitTime) Set the maximum time to wait for RTCP packets (milliseconds)
void	<u>setRTSPPlayAuthenticationMethod</u> (String rtpPlayAuthenticationMethod) Set the RTP play authentication method (as defined in conf/Authentication.xml)
void	<u>setRTSPPublishAuthenticationMethod</u> (String rtpPublishAuthenticationMethod) Set the RTP publish authentication method (as defined in conf/Authentication.xml)
void	<u>setRTSPBindIpAddress</u> (String rtspBindIpAddress) Get the IP address to which UDP ports will be bound for RTSP/RTP sessions
void	<u>setRTSPConnectionAddressType</u> (String rtspConnectionAddressType) Set the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<u>setRTSPConnectionIpAddress</u> (String rtspConnectionIpAddress) Set the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<u>setRTSPMaximumPendingWriteBytes</u> (int rtspMaximumPendingWriteBytes) Set the maximum number of pending write bytes for an RTSP session
void	<u>setRTSPOriginAddressType</u> (String rtspOriginAddressType) Set the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<u>setRTSPOriginIpAddress</u> (String rtspOriginIpAddress) Set the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session
void	<u>setRTSPSessionTimeout</u> (int rtspSessionTimeout) Set the RTSP session timeout (milliseconds)
void	<u>setSharedObjectReadAccess</u> (String sharedObjectReadAccess) Set the default shared object read access
void	<u>setSharedObjectWriteAccess</u> (String sharedObjectWriteAccess) Set the default shared object write access
void	<u>setStreamAudioSampleAccess</u> (String streamAudioSampleAccess) Set the default stream audio sample access
void	<u>setStreamFileMapper</u> (IMediaStreamFileMapper streamFileMapper) Set the stream file mapper.

void	<u>setStreamKeyDir</u> (String keyStorageDir) Set the stream key path
void	<u>setStreamNameAliasProvider</u> (<u>IMediaStreamNameAliasProvider</u> streamNameAliasProvider) Set the stream name alias provider
void	<u>setStreamReadAccess</u> (String streamReadAccess) Set the default stream read access
void	<u>setStreamStorageDir</u> (String streamStorageDir) Set stream storage path
void	<u>setStreamType</u> (String streamType) Set default stream type for application.
void	<u>setStreamVideoSampleAccess</u> (String streamVideoSampleAccess) Set the default stream video sample access
void	<u>setStreamWriteAccess</u> (String streamWriteAccess) Set the default stream write access
void	<u>setValidateFMLEConnections</u> (boolean validateFMLEConnections) Returns true if validating FMLE connection (default is false)
void	<u>setValidationFrequency</u> (int validationFrequency) Set time between validation pings (milliseconds)
void	<u>shutdown</u> (boolean isServerShutdown, boolean isAppShutdown) shutdown applicationInstance
void	<u>shutdownClient</u> (<u>IClient</u> client) shutdown a client connection immediately
boolean	<u>startMediaCasterStream</u> (String streamName, String mediaCasterType) Start a media caster stream
boolean	<u>startMediaCasterStream</u> (String streamName, String streamExt, String mediaCasterType) Start a media caster stream
void	<u>stopMediaCasterStream</u> (String streamName) Stop a media caster stream
void	<u>touch</u> () Touch the application instance so that it stays loaded for at least applicationInstanceTouchTimeout
boolean	<u>writeAppInstConfig</u> (String sName, String data) Method to write xml config file..

Fields

DEFAULT_APPINSTANCE_NAME

```
public static final java.lang.String DEFAULT_APPINSTANCE_NAME
```

(continued from last page)

Constant value: **_definst_**

Methods

shutdownClient

```
public void shutdownClient(IClient client)
```

shutdown a client connection immediately

Parameters:

client - client connection

shutdown

```
public void shutdown(boolean isServerShutdown,  
    boolean isAppShutdown)
```

shutdown applicationInstance

Parameters:

isServerShutdown - true if due to shutdown of server

isAppShutdown - true if due to shutdown of application

getApplication

```
public IApplication getApplication()
```

Get parent application

Returns:

parent application

getName

```
public String getName()
```

Get applicationInstance name

Returns:

applicationInstance name

setName

```
public void setName(String name)
```

Set applicationInstance name

Parameters:

name - applicationInstance name

getStreams

```
public MediaStreamMap getStreams()
```

(continued from last page)

Get all the mediaStream objects attached to this applicationInstance

Get Stream By StreamId

```
IClient client;
int streamId;

MediaStreamMap streams = client.getAppInstance().getStreams();
IMediaStream stream = streams.getStream((IClient)null, streamId);
```

Returns:

collection of mediaStream objects

getVHost

```
public IVHost getVHost()
```

Get parent vHost

Returns:

parent vHost

getProperties

```
public WMSProperties getProperties()
```

Get applicationInstance properties

Returns:

applicationInstance properties

getStreamType

```
public String getStreamType()
```

Get default streamType for application.

Returns:

streamType name

setStreamType

```
public void setStreamType(String streamType)
```

Set default stream type for application.

Parameters:

streamType - streamType name

isAcceptConnection

```
public boolean isAcceptConnection()
```

Is auto accept connection on/off

Returns:

auto accept connection

setAcceptConnection

```
public void setAcceptConnection(boolean acceptConnection)
```

Set is auto accept connection

Parameters:

acceptConnection - auto accept connection

getClientCountTotal

```
public int getClientCountTotal()
```

Get number of client connections in total that have connected to this applicationInstance

Returns:

number of client connections

incClientCountTotal

```
public void incClientCountTotal()
```

Increment the total number of connected client counter by one

getClientCount

```
public int getClientCount()
```

Get number of client connections currently connected to applicationInstance

Returns:

number of client connections

getClientById

```
public IClient getClientById(int index)
```

Get a client connection by the client Id

Parameters:

index - client Id

Returns:

client connection

getClients

```
public java.util.List getClients()
```

(continued from last page)

Get the set of clients currently connected to this application instance (replaces getClient(index))

Returns:

set of clients

getClient

```
public IClient getClient(int index)
```

Deprecated. *Get the client connection at index. This method is deprecated. It is best to use getClient() to return a List objects.*

Parameters:

index - index

Returns:

client connection

getSharedObjects

```
public ISharedObjects getSharedObjects()
```

Get non-persistent shared object collection

Returns:

collection of non-persistent shared objects

getSharedObjects

```
public ISharedObjects getSharedObjects(boolean isPersistent)
```

Get either persistent or non-persistent shared object collection

Parameters:

isPersistent

Returns:

collection of shared objects

addClientListener

```
public void addClientListener(IClientNotify clientListener)
```

(continued from last page)

Add client listener. Listens for connects, disconnect, accepts and reject

Add a Client Listener

```
IApplicationInstance appInstance;

class ClientListener implements IClientNotify
{
    public void onClientConnect(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientConnect: "+
            client.getClientId());
    }

    public void onClientDisconnect(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientDisconnect: "+
            client.getClientId());
    }

    public void onClientAccept(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientAccept: "+
            client.getClientId());
    }

    public void onClientReject(IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onClientReject: "+
            client.getClientId());
    }
}

appInstance.addClientListener(new ClientListener());
```

Parameters:

clientListener - client listener

removeClientListener

public void **removeClientListener**([IClientNotify](#) clientListener)

Remove client listener. Listens for connects, disconnect, accepts and reject

Parameters:

clientListener - client listener

addMediaStreamListener

public void **addMediaStreamListener**([IMediaStreamNotify](#) mediaStreamListener)

Add mediaStream listener. Listens for create and destroy

Add a MediaStream Listener

```
IApplicationInstance appInstance;

class MediaStreamListener implements IMediaStreamNotify
{
    public void onMediaStreamCreate(IMediaStream stream)
    {
        WMSLoggerFactory.getLogger(null).debug("onMediaStreamCreate: "+
            stream.getSrc());
    }

    public void onMediaStreamDestroy(IMediaStream stream)
    {
        WMSLoggerFactory.getLogger(null).debug("onMediaStreamDestroy: "+
            stream.getSrc());
    }
}

appInstance.addMediaStreamListener(new MediaStreamListener());
```

Parameters:

mediaStreamListener - mediaStream listener

removeMediaStreamListener

public void **removeMediaStreamListener**([IMediaStreamNotify](#) mediaStreamListener)

Remove mediaStream listener. Listens for create and destroy

Parameters:

mediaStreamListener - mediaStream listener

addSharedObjectListener

public void **addSharedObjectListener**([ISharedObjectNotify](#) sharedObjectListener,
boolean isPersistent)

(continued from last page)

Add sharedObject listener. Listens for create, destroy, clientConnect, clientDisconnect

Add SharedObject Listener

```
IApplicationInstance appInstance;

class SharedObjectListener implements ISharedObjectNotify
{
    public void onSharedObjectCreate(ISharedObject sharedObject)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectCreate: "+
            sharedObject.getName());
    }

    public void onSharedObjectDestroy(ISharedObject sharedObject)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectDestroy: "+
            sharedObject.getName());
    }

    public void onSharedObjectConnect(ISharedObject sharedObject, IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectConnect: "+
            sharedObject.getName());
    }

    public void onSharedObjectDisconnect(ISharedObject sharedObject, IClient client)
    {
        WMSLoggerFactory.getLogger(null).debug("onSharedObjectDisconnect: "+
            sharedObject.getName());
    }
}

appInstance.addSharedObjectListener(new SharedObjectListener(), false);
```

Parameters:

sharedObjectListener - sharedObject listener
isPersistent

removeSharedObjectListener

```
public void removeSharedObjectListener(ISharedObjectNotify sharedObjectListener,
    boolean isPersistent)
```

Remove sharedObject listener. Listens for create, destroy, clientConnect, clientDisconnect

Parameters:

(continued from last page)

sharedObjectListener - sharedObject listener
isPersistent

addMediaCasterListener

```
public void addMediaCasterListener(IMediaCasterNotify mediaCasterListener)
```

Add mediaCaster listener. Listens for create, destroy, registerPlayer, unregisterPlayer, setSourceStream

Parameters:

mediaCasterListener

addMediaCasterListener

```
public void addMediaCasterListener(IMediaCasterNotify2 mediaCasterListener)
```

Add mediaCaster listener. Listens for create, destroy, registerPlayer, unregisterPlayer, setSourceStream

Parameters:

mediaCasterListener

removeMediaCasterListener

```
public void removeMediaCasterListener(IMediaCasterNotify mediaCasterListener)
```

Remove mediaCaster listener. Listens for create, destroy, registerPlayer, unregisterPlayer, setSourceStream

Parameters:

mediaCasterListener

getConnectionCounter

```
public ConnectionCounter getConnectionCounter()
```

Get the connectionCounter for applicationInstance

Returns:

connection counter

getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get the connectionCounter for applicationInstance for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index

Returns:

connection counter

getDateStarted

```
public String getDateStarted()
```

Get date applicationInstance started

Returns:

(continued from last page)

date applicationInstance started

getTimeRunning

```
public String getTimeRunning()
```

Get time applicationInstance running

Returns:

time applicationInstance running

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

Returns:

time running in seconds

broadcastMsg

```
public void broadcastMsg(java.util.List clientList,  
                          String handlerName)
```

Broadcast a message to a specific list of clients connected to this application instance

Parameters:

clientList - list of client

handlerName - handler name

broadcastMsg

```
public void broadcastMsg(java.util.List clientList,  
                          String handlerName,  
                          Object[] params)
```

Broadcast a message to a specific list of clients connected to this application instance

Parameters:

clientList - list of client

handlerName - handler name

params - parameters

broadcastMsg

```
public void broadcastMsg(String handlerName,  
                          Object[] params)
```

(continued from last page)

Broadcast a message to all clients connected to this applicationInstance

Broadcast Message to All Clients

```
IApplicationInstance appInstance;  
appInstance.broadcastMsg("onNotify", "Hello World", 1.2345, false, new Date());
```

Parameters:

handlerName - handler name

params - variable list of arguments (Java primitive and Strings will be wrapped in AMFData objects)

getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter()
```

Get the performance counter for applicationInstance

Returns:

io performance counter

getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter(int counterIndex)
```

Get the performance counter for applicationInstance for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

Returns:

connection counter

addPlayStreamByName

```
public void addPlayStreamByName(IMediaStream stream,  
String name)
```

Add a media stream to the list of streams that are listening for a published stream

Parameters:

stream - media stream

name - stream name

removePlayStreamByName

```
public void removePlayStreamByName(IMediaStream stream)
```

Remove media stream from the list of streams that are listening for a published stream

Parameters:

(continued from last page)

stream - media stream

getPlayStreamCountsByName

```
public java.util.Map getPlayStreamCountsByName( )
```

Get a map of stream names to number of Flash players playing the stream name

Returns:

map of stream names to number of Flash players playing the stream name

getPlayStreamCount

```
public int getPlayStreamCount(String streamName)
```

Get the number of Flash players playing a given stream name

Parameters:

streamName - stream name

Returns:

number of players

getPlayStreamsByName

```
public java.util.List getPlayStreamsByName(String name)
```

Get a list of media streams that are listening for published stream.

Parameters:

name - stream name

Returns:

list of streams or null if no listeners

getMediaCasterStreams

```
public MediaCasterStreamMap getMediaCasterStreams( )
```

Get the media caster streams attached to this application instance

Returns:

media caster streams attached to this application instance

getStreamCount

```
public int getStreamCount( )
```

Get the total number of open streams attached to this application instance

Returns:

the total number of open streams attached to this application instance

getModFunctions

```
public ModuleFunctions getModFunctions( )
```

Get list of application modules

(continued from last page)

Returns:

list of application modules

addModuleListener

```
public void addModuleListener(IModuleNotify moduleListener)
```

Add module listener. Listens for onModuleLoad and onModuleUnload events. See IModuleNotify.

Parameters:

moduleListener - module listener

removeModuleListener

```
public void removeModuleListener(IModuleNotify moduleListener)
```

Remove module listener

Parameters:

moduleListener - module listener

getModuleList

```
public ModuleList getModuleList()
```

Get the list of loaded modules.

Returns:

list of loaded modules

getModuleInstance

```
public Object getModuleInstance(String name)
```

Get the instance of the module class for this application instance.

Parameters:

name - module name as defined in Application.xml

Returns:

instance of class for this application instance

getApplicationTimeout

```
public int getApplicationTimeout()
```

Get application timeout (milliseconds)

Returns:

application timeout (milliseconds)

setApplicationTimeout

```
public void setApplicationTimeout(int applicationTimeout)
```

Set application timeout (milliseconds)

(continued from last page)

Parameters:

applicationTimeout - application timeout (milliseconds)

getPingTimeout

```
public int getPingTimeout()
```

Get ping timeout (milliseconds)

Returns:

ping timeout (milliseconds)

setPingTimeout

```
public void setPingTimeout(int pingTimeout)
```

Set ping timeout (milliseconds)

Parameters:

pingTimeout - ping timeout (milliseconds)

getValidationFrequency

```
public int getValidationFrequency()
```

Get time between validation pings (milliseconds)

Returns:

time between validation pings (milliseconds)

setValidationFrequency

```
public void setValidationFrequency(int validationFrequency)
```

Set time between validation pings (milliseconds)

Parameters:

validationFrequency - time between validation pings (milliseconds)

getMaximumPendingWriteBytes

```
public int getMaximumPendingWriteBytes()
```

Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

Returns:

maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

setMaximumPendingWriteBytes

```
public void setMaximumPendingWriteBytes(int maximumPendingWriteBytes)
```

Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

Parameters:

maximumPendingWriteBytes - maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

getMaximumPendingReadBytes

```
public int getMaximumPendingReadBytes()
```

Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

Returns:

maximum number of bytes a client connection can have waiting to be written before the connection is terminated

setMaximumPendingReadBytes

```
public void setMaximumPendingReadBytes(int maximumPendingReaderBytes)
```

Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

Parameters:

maximumPendingReaderBytes - maximum number of bytes a client connection can have waiting to be written before the connection is terminated

setMaximumSetBufferTime

```
public void setMaximumSetBufferTime(int maximumSetBufferTime)
```

Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

Parameters:

maximumSetBufferTime - maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

getMaximumSetBufferTime

```
public int getMaximumSetBufferTime()
```

Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

Returns:

maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

getRepeaterOriginUrl

```
public String getRepeaterOriginUrl()
```

Get the Repeater Origin URL used by the Live Stream Repeater

Returns:

URL used by the Live Stream Repeater

setRepeaterOriginUrl

```
public void setRepeaterOriginUrl(String repeaterOriginUrl)
```

Set the Repeater Origin URL used by the Live Stream Repeater

Parameters:

repeaterOriginUrl - URL used by the Live Stream Repeater

getRepeaterQueryString

```
public String getRepeaterQueryString()
```

Get the Repeater query string that is used to connect to the origin. This value can be used to pass secure URL parameters to the origin for security validation.

Returns:

Repeater query string

setRepeaterQueryString

```
public void setRepeaterQueryString(String repeaterQueryString)
```

Set the Repeater query string that is used to connect to the origin. This value can be used to pass secure URL parameters to the origin for security validation.

Parameters:

repeaterQueryString - Repeater query string

getAllowDomains

```
public String[] getAllowDomains()
```

Get the list of domain names used to control access to this application. Upon connection, if this list is non-null the client.referrer value is checked to make sure the referrer is from a domain in this list.

Returns:

list of domain names used to control access to this application

setAllowDomains

```
public void setAllowDomains(String[] domainFilter)
```

Set the list of domain names used to control access to this application. Upon connection, if this list is non-null the client.referrer value is checked to make sure the referrer is from a domain in this list.

Parameters:

domainFilter - list of domain names used to control access to this application

parseAllowDomains

```
public void parseAllowDomains(String domainFilterStr)
```

Parse a comma delimited list of domain names used to control access to this application. Upon connection, if this list is non-null the client.referrer value is checked to make sure the referrer is from a domain in this list.

Parameters:

domainFilterStr - comma delimited list of domain names

getClientIdleFrequency

```
public int getClientIdleFrequency()
```

Get default client idle frequency (milliseconds)

Returns:

default client idle frequency (milliseconds)

setClientIdleFrequency

```
public void setClientIdleFrequency(int clientIdleFrequency)
```

Set default client idle frequency (milliseconds)

Parameters:

clientIdleFrequency - default client idle frequency (milliseconds)

getRTPIdeFrequency

```
public int getRTPIdeFrequency( )
```

Set the default RTP idle frequency (milliseconds)

Returns:

default RTP idle frequency (milliseconds)

setRTPIdeFrequency

```
public void setRTPIdeFrequency(int rtspIdleFrequency)
```

Get the default RTP idle frequency (milliseconds)

Parameters:

rtspIdleFrequency - default RTP idle frequency (milliseconds)

getStreamStorageDir

```
public String getStreamStorageDir( )
```

Get stream storage path

Returns:

stream storage path

setStreamStorageDir

```
public void setStreamStorageDir(String streamStorageDir)
```

Set stream storage path

Parameters:

streamStorageDir - stream storage path

getStreamKeyDir

```
public String getStreamKeyDir( )
```

Get the stream key path

Returns:

stream key path

setStreamKeyDir

```
public void setStreamKeyDir(String keyStorageDir)
```

(continued from last page)

Set the stream key path

Parameters:

keyStorageDir - stream key path

getRsoStorageDir

```
public String getRsoStorageDir()
```

Get remote shared object storage path

Returns:

remote shared object storage path

setRsoStorageDir

```
public void setRsoStorageDir(String rsoStorageDir)
```

Set remote shared object storage path

Parameters:

rsoStorageDir - remote shared object storage path

getStreamKeyPath

```
public String getStreamKeyPath()
```

Get the resolved key path to the MediaStreams encryption keys

Returns:

resolved key path to the MediaStreams encryption keys

getStreamStoragePath

```
public String getStreamStoragePath()
```

Get the resolved storage path to the MediaStreams

Returns:

resolved storage path to the MediaStreams

getRsoStoragePath

```
public String getRsoStoragePath()
```

Get the resolved storage path to the shared objects

Returns:

resolved storage path to the shared objects

getStreamVideoSampleAccess

```
public String getStreamVideoSampleAccess()
```

Get the default stream video sample access

Returns:

default stream video sample access

(continued from last page)

See Also:

[IClient.getStreamVideoSampleAccess\(\)](#)

setStreamVideoSampleAccess

```
public void setStreamVideoSampleAccess(String streamVideoSampleAccess)
```

Set the default stream video sample access

Parameters:

streamVideoSampleAccess - default stream video sample access

See Also:

[IClient.setStreamVideoSampleAccess\(String\)](#)

getStreamAudioSampleAccess

```
public String getStreamAudioSampleAccess()
```

Get the default stream audio sample access

Returns:

default stream audio sample access

See Also:

[IClient.getStreamAudioSampleAccess\(\)](#)

setStreamAudioSampleAccess

```
public void setStreamAudioSampleAccess(String streamAudioSampleAccess)
```

Set the default stream audio sample access

Parameters:

streamAudioSampleAccess

See Also:

[IClient.setStreamAudioSampleAccess\(String\)](#)

getStreamReadAccess

```
public String getStreamReadAccess()
```

Get the default stream read access

Returns:

default stream read access

See Also:

[IClient.getStreamReadAccess\(\)](#)

setStreamReadAccess

```
public void setStreamReadAccess(String streamReadAccess)
```

Set the default stream read access

(continued from last page)

Parameters:

streamReadAccess - default stream read access

See Also:[IClient.setStreamReadAccess\(String\)](#)

getStreamWriteAccess

```
public String getStreamWriteAccess()
```

Get the default stream write access

Returns:

default stream write access

See Also:[IClient.getStreamWriteAccess\(\)](#)

setStreamWriteAccess

```
public void setStreamWriteAccess(String streamWriteAccess)
```

Set the default stream write access

Parameters:

streamWriteAccess - default stream write access

See Also:[IClient.setStreamWriteAccess\(String\)](#)

getSharedObjectReadAccess

```
public String getSharedObjectReadAccess()
```

Get the default shared object read access

Returns:

default shared object read access

See Also:[IClient.getSharedObjectReadAccess\(\)](#)

setSharedObjectReadAccess

```
public void setSharedObjectReadAccess(String sharedObjectReadAccess)
```

Set the default shared object read access

Parameters:

sharedObjectReadAccess - default shared object read access

See Also:[IClient.setSharedObjectReadAccess\(String\)](#)

getSharedObjectWriteAccess

```
public String getSharedObjectWriteAccess()
```


(continued from last page)

Get the default shared object write access

Returns:

default shared object write access

See Also:

[IClient.getSharedObjectWriteAccess\(\)](#)

setSharedObjectWriteAccess

```
public void setSharedObjectWriteAccess(String sharedObjectWriteAccess)
```

Set the default shared object write access

Parameters:

sharedObjectWriteAccess - default shared object write access

See Also:

[IClient.setSharedObjectWriteAccess\(String\)](#)

getRTPPublishAuthenticationMethod

```
public String getRTPPublishAuthenticationMethod()
```

Get the RTP publish authentication method (as defined in conf/Authentication.xml)

Returns:

RTP publish authentication method

setRTPPublishAuthenticationMethod

```
public void setRTPPublishAuthenticationMethod(String rtpPublishAuthenticationMethod)
```

Set the RTP publish authentication method (as defined in conf/Authentication.xml)

Parameters:

rtpPublishAuthenticationMethod - RTP publish authentication method

getRTPPlayAuthenticationMethod

```
public String getRTPPlayAuthenticationMethod()
```

Get the RTP play authentication method (as defined in conf/Authentication.xml)

Returns:

RTP play authentication method

setRTPPlayAuthenticationMethod

```
public void setRTPPlayAuthenticationMethod(String rtpPlayAuthenticationMethod)
```

Set the RTP play authentication method (as defined in conf/Authentication.xml)

Parameters:

rtpPlayAuthenticationMethod - RTP play authentication method

(continued from last page)

getRTPAVSyncMethod

```
public int getRTPAVSyncMethod( )
```

Get RTP audio/video sync method (RTPStream.AVSYNCMETHODS_SENDERREPORT, RTPStream.AVSYNCMETHODS_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS_RTPTIMECODE)

Returns:

RTP audio/video sync method

setRTPAVSyncMethod

```
public void setRTPAVSyncMethod(int rtpAVSyncMethod)
```

Set RTP audio/video sync method (RTPStream.AVSYNCMETHODS_SENDERREPORT, RTPStream.AVSYNCMETHODS_SYSTEMCLOCK, RTPStream.AVSYNCMETHODS_RTPTIMECODE)

Parameters:

rtpAVSyncMethod - RTP audio/video sync method

getRTPMaxRTCPWaitTime

```
public int getRTPMaxRTCPWaitTime( )
```

Get the maximum time to wait for RTCP packets (milliseconds)

Returns:

maximum time to wait for RTCP packets (milliseconds)

setRTPMaxRTCPWaitTime

```
public void setRTPMaxRTCPWaitTime(int rtpMaxRTCPWaitTime)
```

Set the maximum time to wait for RTCP packets (milliseconds)

Parameters:

rtpMaxRTCPWaitTime - maximum time to wait for RTCP packets (milliseconds)

getRTPSessions

```
public java.util.List getRTPSessions(String streamName)
```

Get a list of RTP sessions running under this application instance playing a given stream name

Parameters:

streamName - stream name

Returns:

list of RTP sessions running under this application instance playing a given stream name

getRTPSessions

```
public java.util.List getRTPSessions( )
```

Get a list of RTP sessions running under this application instance

Returns:

list of RTP sessions running under this application instance

getRTPSessionCountsByName

```
public java.util.Map getRTPSessionCountsByName()
```

Get a map of stream names and session counts of RTP sessions

Returns:

map of stream names and session counts

getRTPSessionCount

```
public int getRTPSessionCount(String streamName)
```

Get the number of RTP player streams playing a given stream name

Parameters:

streamName - stream name

Returns:

the number of RTP sessions

getRTPSessionCount

```
public int getRTPSessionCount()
```

Get the number of RTP sessions running under this application instance

Returns:

the number of RTP sessions running under this application instance

addRTPSession

```
public void addRTPSession(RTPSession rtpSession)
```

Add an RTP session to this application instance

Parameters:

rtpSession - RTP session to add

registerPlayRTPSession

```
public void registerPlayRTPSession(RTPSession rtpSession)
```

Register an RTP session as a play session

Parameters:

rtpSession - RTP session to register

removeRTPSession

```
public void removeRTPSession(RTPSession rtpSession)
```

Remove an RTP session from this application instance

Parameters:

rtpSession - RTP session to remove

getClientsLockObj

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
getClientsLockObj()
```

Get the read/write lock for this application instance

Returns:

read/write lock for this application instance

getStreamProperties

```
public WMSProperties getStreamProperties()
```

Get the property collection of stream settings that are specific to this application instance

Returns:

property collection of stream settings

getMediaCasterProperties

```
public WMSProperties getMediaCasterProperties()
```

Get the property collection of media caster settings that are specific to this application instance

Returns:

property collection of media caster settings

getMediaReaderProperties

```
public WMSProperties getMediaReaderProperties()
```

Get the property collection of media reader settings that are specific to this application instance

Returns:

property collection of media reader settings

getMediaWriterProperties

```
public WMSProperties getMediaWriterProperties()
```

Get the property collection of media reader settings that are specific to this application instance

Returns:

property collection of media reader settings

getRTPProperties

```
public WMSProperties getRTPProperties()
```

Get the property collection of RTP settings that are specific to this application instance

Returns:

property collection of RTP settings

(continued from last page)

getLiveStreamPacketizerProperties

```
public WMSProperties getLiveStreamPacketizerProperties()
```

Get the property collection of LiveStreamPacketizer settings that are specific to this application instance

Returns:

property collection of LiveStreamPacketizer settings

getTranscoderProperties

```
public WMSProperties getTranscoderProperties()
```

Get the property collection of Transcoder settings that are specific to this application instance

Returns:

property collection of Transcoder settings

getHTTPStreamerProperties

```
public WMSProperties getHTTPStreamerProperties()
```

Get the property collection of HTTPStreamer settings that are specific to this application instance

Returns:

property collection of HTTPStreamer settings

getMaxStorageDirDepth

```
public int getMaxStorageDirDepth()
```

Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths

Returns:

folder depth

setMaxStorageDirDepth

```
public void setMaxStorageDirDepth(int maxStorageDirDepth)
```

Maximum folder depth allowed for the StreamStorageDir and SharedObjectStorageDir paths

Parameters:

maxStorageDirDepth - folder depth

getStreamFileMapper

```
public IMediaStreamFileMapper getStreamFileMapper()
```

Get the stream file mapper. See IMediaStreamFileMapper

Returns:

streamFileMapper stream file mapper

setStreamFileMapper

```
public void setStreamFileMapper(IMediaStreamFileMapper streamFileMapper)
```

(continued from last page)

Set the stream file mapper. See IMediaStreamFileMapper

Parameters:

streamFileMapper - stream file mapper

decodeStorageDir

```
public String decodeStorageDir(String storageDir)
```

This function will take a storage path that uses variables and expand the variables based on the context. It supports the following variables (as well as any system variables): `${com.wowza.wms.AppHome}`: Application home directory `${com.wowza.wms.ConfigHome}`: Configuration home directory `${com.wowza.wms.context.VHostConfigHome}`: Virtual configuration path `${com.wowza.wms.context.VHost}`: Virtual host name `${com.wowza.wms.context.Application}`: Application name `${com.wowza.wms.context.ApplicationInstance}`: Application instance name

getLiveStreamPacketizerList

```
public String getLiveStreamPacketizerList()
```

Get the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)

Returns:

comma separated list of LiveStreamPacketizers names

getHTTPStreamerList

```
public String getHTTPStreamerList()
```

Get the comma separated list of HTTPStreamers names being used by this application (see conf/HTTPStreamers.xml)

Returns:

comma separated list of HTTPStreamers names

setLiveStreamPacketizerList

```
public void setLiveStreamPacketizerList(String liveStreamPacketizerList)
```

Set the comma separated list of LiveStreamPacketizers names being used by this application (see conf/LiveStreamPacketizers.xml)

Parameters:

liveStreamPacketizerList - comma separated list of LiveStreamPacketizers names

setHTTPStreamerList

```
public void setHTTPStreamerList(String httpStreamerList)
```

Set the comma separated list of HTTPStreamer names being used by this application (see conf/HTTPStreamers.xml)

Parameters:

httpStreamerList - comma separated list of HTTPStreamer names

containsHTTPStreamer

```
public boolean containsHTTPStreamer(String httpStreamer)
```

Does this application instance allow streaming of a given HTTPStreamer

Parameters:

(continued from last page)

httpStreamer - HTTP Streamer name

Returns:

true is this type of streaming is allowed

containsLiveStreamPacketizer

```
public boolean containsLiveStreamPacketizer(String liveStreamPacketizer)
```

Does this application instance contain a references to this live stream packetizer. If it is true we consider this a live stream source for the HTTP streamer. If false then we consider this a video on demand source.

Parameters:

liveStreamPacketizer - live stream packetizer name

Returns:

true if contains reference to it

containsDvrRecorder

```
public boolean containsDvrRecorder(String dvrRecorder)
```

Does this application instance contain a references to this DVR recorder. If it is true we consider this a DVR source for the HTTP streamer.

Parameters:

dvrRecorder - DVR recorder name

Returns:

true if contains reference to it

getStreamNameAliasProvider

```
public IMediaStreamNameAliasProvider getStreamNameAliasProvider()
```

Get the stream name alias provider

Returns:

stream name alias provider

setStreamNameAliasProvider

```
public void setStreamNameAliasProvider(IMediaStreamNameAliasProvider  
streamNameAliasProvider)
```

Set the stream name alias provider

Parameters:

streamNameAliasProvider - stream name alias provider

getPublishers

```
public java.util.List getPublishers()
```

Get the set of server side publishers

Returns:

set of server side publishers

getPublisherCount

```
public int getPublisherCount()
```

Get the current number of server side publishers

Returns:

number of server side publishers

addPublisher

```
public void addPublisher(Publisher publisher)
```

Add a server side publisher to this application instance

Parameters:

publisher - server side publisher

removePublisher

```
public void removePublisher(Publisher publisher)
```

Remove a server side publisher from this application instance

Parameters:

publisher - server side publisher

getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions(int protocol,  
String streamName)
```

Get the HTTPStreamerSessions associated with this application instance for a stream name by protocol. See (IHTTPStreamerSession.SESSIONPROTOCOL_*) for protocols

Parameters:

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL_*)
streamName - stream name

Returns:

HTTPStreamerSessions associated with this application instance

getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions(String streamName)
```

Get the HTTPStreamerSessions associated with this application instance for a stream name

Parameters:

streamName - stream name

Returns:

HTTPStreamerSessions associated with this application instance

getHTTPStreamerSessionCountsByName

```
public java.util.Map getHTTPStreamerSessionCountsByName(int protocol)
```


(continued from last page)

Get a map of session counts by name for a given protocol

Parameters:

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL_*)

Returns:

map of session counts by name

getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount(String streamName)
```

Get the current number of HTTPStreamerSessions associated with this application instance and stream name

Parameters:

streamName - stream name

Returns:

number of HTTPStreamerSessions associated with this application instance

getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount(int protocol,  
    String streamName)
```

Get the current number of HTTPStreamerSessions associated with this application instance and stream name by protocol . See (IHTTPStreamerSession.SESSIONPROTOCOL_*) for protocols

Parameters:

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL_*)

streamName - stream name

Returns:

HTTPStreamerSessions associated with this application instance

getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions()
```

Get the HTTPStreamerSessions associated with this application instance

Returns:

HTTPStreamerSessions associated with this application instance

getHTTPStreamerSessions

```
public java.util.List getHTTPStreamerSessions(int protocol)
```

Get the HTTPStreamerSessions associated with this application instance by protocol. See (IHTTPStreamerSession.SESSIONPROTOCOL_*) for protocols

Parameters:

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL_*)

Returns:

HTTPStreamerSessions associated with this application instance

(continued from last page)

getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount()
```

Get the current number of HTTPStreamerSessions associated with this application instance

Returns:

current number of HTTPStreamerSessions associated with this application instance

getHTTPStreamerSessionCount

```
public int getHTTPStreamerSessionCount(int protocol)
```

Get the current number of HTTPStreamerSessions associated with this application instance by protocol. See (IHTTPStreamerSession.SESSIONPROTOCOL_*) for protocols

Parameters:

protocol - streaming protocol (IHTTPStreamerSession.SESSIONPROTOCOL_*)

Returns:

current number of HTTPStreamerSessions associated with this application instance

addHTTPStreamerSession

```
public void addHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Add a HTTPStreamerSession to this application instance

Parameters:

httpStreamerSession - HTTPStreamerSession

removeHTTPStreamerSession

```
public void removeHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Remove a HTTPStreamerSession from this application instance

Parameters:

httpStreamerSession - HTTPStreamerSession

getHTTPStreamerApplicationContext

```
public IHTTPStreamerApplicationContext getHTTPStreamerApplicationContext(String  
httpStreamName,  
boolean doCreate)
```

Get the HTTPStreamer application context for a given HTTPStreamer adapter

Parameters:

httpStreamName - HTTPStreamer adapter name
doCreate - create if it does not exist

Returns:

HTTPStreamer application context

addRTPIncomingDatagramPortRange

```
public void addRTPIncomingDatagramPortRange(int startPort,  
int endPort)
```

(continued from last page)

Add a port range to the list of valid incoming RTP UDP ports

Parameters:

startPort - starting port number
endPort - end port number

addRTPIncomingDatagramPortAll

```
public void addRTPIncomingDatagramPortAll()
```

Allow all incoming RTP UDP ports for this application instance

isRTPIncomingDatagramPortValid

```
public boolean isRTPIncomingDatagramPortValid(int port)
```

Check a port number to be sure it is a valid RTP UDP port for this application instance

Parameters:

port - port number

Returns:

true if the port is valid

readAppInstConfig

```
public String readAppInstConfig(String sName)
```

Method to read xml config file..

writeAppInstConfig

```
public boolean writeAppInstConfig(String sName,  
    String data)
```

Method to write xml config file..

getLiveStreamPacketizerControl

```
public ILiveStreamPacketizerControl getLiveStreamPacketizerControl()
```

Get the Live Stream Packetizer Controller. This class will get called each time a stream is to be packetized using the LiveStreamPacketizer mechanism.

Returns:

Live Stream Packetizer Controller

setLiveStreamPacketizerControl

```
public void setLiveStreamPacketizerControl(ILiveStreamPacketizerControl  
liveStreamPacketizerControl)
```

Set the Live Stream Packetizer Controller. This class will get called each time a stream is to be packetized using the LiveStreamPacketizer mechanism.

Parameters:

liveStreamPacketizerControl - Live Stream Packetizer Controller

resetMediaCasterStream

```
public boolean resetMediaCasterStream(String streamName)
```

Reset a media caster stream

Parameters:

streamName - stream name

Returns:

true if successful

resetMediaCasterStream

```
public boolean resetMediaCasterStream(String streamName,  
String streamExt)
```

Reset a media caster stream

Parameters:

streamName - stream name

streamExt - stream extension

Returns:

true if successful

startMediaCasterStream

```
public boolean startMediaCasterStream(String streamName,  
String streamExt,  
String mediaCasterType)
```

Start a media caster stream

Parameters:

streamName - stream name

streamExt - stream extension

mediaCasterType - media caster stream type

Returns:

true if successful

startMediaCasterStream

```
public boolean startMediaCasterStream(String streamName,  
String mediaCasterType)
```

Start a media caster stream

Parameters:

streamName - stream name

mediaCasterType - media caster stream type

Returns:

true if successful

(continued from last page)

stopMediaCasterStream

```
public void stopMediaCasterStream(String streamName)
```

Stop a media caster stream

Parameters:

streamName - stream name

getContextStr

```
public String getContextStr()
```

Returns the application context string in the form [application]/[appInstance].

Returns:

application context string

getPublishStreamNames

```
public java.util.List getPublishStreamNames()
```

Get the list of live stream names currently being published.

Returns:

list of live stream names currently being published

addMediaWriterListener

```
public void addMediaWriterListener(IMediaWriterActionNotify listener)
```

Add a MediaWriter listener class. See IMediaWriterActionNotify

Parameters:

listener - MediaWriter listener class

removeMediaWriterListener

```
public void removeMediaWriterListener(IMediaWriterActionNotify listener)
```

remove MediaWriter listener class. See IMediaWriterActionNotify

Parameters:

listener - MediaWriter listener class

notifyMediaWriterOnWriteComplete

```
public void notifyMediaWriterOnWriteComplete(IMediaStream stream,  
java.io.File file)
```

Notify all MediaWriter listeners of onWriteComplete

Parameters:

stream - media stream

file - file that was written

(continued from last page)

notifyMediaWriterOnFLVAddMetadata

```
public void notifyMediaWriterOnFLVAddMetadata(IMediaStream stream,  
        java.util.Map extraMetadata)
```

Notify all MediaWriter listeners of onFLVAddMetadata

Parameters:

stream - media stream
extraMetadata - meta to add to the file

getMediaCasterValidator

```
public IMediaCasterValidateMediaCaster getMediaCasterValidator()
```

Get the MediaCaster validator interface for this application instance

Returns:

MediaCaster validator interface

setMediaCasterValidator

```
public void setMediaCasterValidator(IMediaCasterValidateMediaCaster  
mediaCasterValidator)
```

Set the MediaCaster validator interface for this application instance

Parameters:

mediaCasterValidator - MediaCaster validator interface

touch

```
public void touch()
```

Touch the application instance so that it stays loaded for at least applicationInstanceTouchTimeout

getLastTouchTime

```
public long getLastTouchTime()
```

Get the last time the instance was touched (milliseconds)

Returns:

last time the instance was touched (milliseconds)

getApplicationInstanceTouchTimeout

```
public int getApplicationInstanceTouchTimeout()
```

Get the application instance touch timeout (milliseconds). Default is 5000.

Returns:

application instance touch timeout (milliseconds)

setApplicationInstanceTouchTimeout

```
public void setApplicationInstanceTouchTimeout(int applicationInstanceTouchTimeout)
```

Set the application instance touch timeout (milliseconds). Default is 5000.

(continued from last page)

Parameters:

applicationInstanceTouchTimeout - application instance touch timeout (milliseconds)

getRTSPSessionTimeout

```
public int getRTSPSessionTimeout()
```

Get the RTSP session timeout (milliseconds)

Returns:

RTSP session timeout (milliseconds)

setRTSPSessionTimeout

```
public void setRTSPSessionTimeout(int rtspSessionTimeout)
```

Set the RTSP session timeout (milliseconds)

Parameters:

rtspSessionTimeout - RTSP session timeout (milliseconds)

getRTSPMaximumPendingWriteBytes

```
public int getRTSPMaximumPendingWriteBytes()
```

Get the maximum number of pending write bytes for an RTSP session

Returns:

maximum number of pending write bytes for an RTSP session

setRTSPMaximumPendingWriteBytes

```
public void setRTSPMaximumPendingWriteBytes(int rtspMaximumPendingWriteBytes)
```

Set the maximum number of pending write bytes for an RTSP session

Parameters:

rtspMaximumPendingWriteBytes - maximum number of pending write bytes for an RTSP session

addMediaReaderListener

```
public void addMediaReaderListener(IMediaReaderActionNotify mediaReaderListener)
```

Add media reader listener. see IMediaReaderActionNotify

Parameters:

mediaReaderListener - media reader listener

removeMediaReaderListener

```
public void removeMediaReaderListener(IMediaReaderActionNotify mediaReaderListener)
```

Remove media reader listener. see IMediaReaderActionNotify

Parameters:

mediaReaderListener - media reader listener

notifyMediaReaderCreate

```
public void notifyMediaReaderCreate(IMediaReader mediaReader)
```

Notify media reader notifyMediaReaderCreate

Parameters:

mediaReader - media reader

notifyMediaReaderInit

```
public void notifyMediaReaderInit(IMediaReader mediaReader,  
    IMediaStream stream)
```

Notify media reader notifyMediaReaderInit

Parameters:

mediaReader - media reader

stream - media stream

notifyMediaReaderOpen

```
public void notifyMediaReaderOpen(IMediaReader mediaReader,  
    IMediaStream stream)
```

Notify media reader notifyMediaReaderOpen

Parameters:

mediaReader - media reader

stream - media stream

notifyMediaReaderExtractMetaData

```
public void notifyMediaReaderExtractMetaData(IMediaReader mediaReader,  
    IMediaStream stream)
```

Notify media reader notifyMediaReaderExtractMetaData

Parameters:

mediaReader - media reader

stream - media stream

notifyMediaReaderClose

```
public void notifyMediaReaderClose(IMediaReader mediaReader,  
    IMediaStream stream)
```

Notify media reader notifyMediaReaderClose

Parameters:

mediaReader - media reader

stream - media stream

getRTSPBindIpAddress

```
public String getRTSPBindIpAddress()
```

Set the IP address to which UDP ports will be bound for RTSP/RTP sessions

(continued from last page)

Returns:

IP address to which UDP ports will be bound for RTSP/RTP sessions

setRTSPBindIpAddress

```
public void setRTSPBindIpAddress(String rtspBindIpAddress)
```

Get the IP address to which UDP ports will be bound for RTSP/RTP sessions

Parameters:

rtspBindIpAddress - IP address to which UDP ports will be bound for RTSP/RTP sessions

getRTSPConnectionIpAddress

```
public String getRTSPConnectionIpAddress()
```

Get the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Returns:

connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

setRTSPConnectionIpAddress

```
public void setRTSPConnectionIpAddress(String rtspConnectionIpAddress)
```

Set the connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Parameters:

rtspConnectionIpAddress - connection IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

getRTSPConnectionAddressType

```
public String getRTSPConnectionAddressType()
```

Get the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Returns:

the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

setRTSPConnectionAddressType

```
public void setRTSPConnectionAddressType(String rtspConnectionAddressType)
```

Set the connection IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Parameters:

rtspConnectionAddressType

getRTSPOriginIpAddress

```
public String getRTSPOriginIpAddress()
```

Get the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Returns:

(continued from last page)

origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

setRTSPOriginIpAddress

```
public void setRTSPOriginIpAddress(String rtspOriginIpAddress)
```

Set the origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Parameters:

rtspOriginIpAddress - origin IP address to used in the Session Description Protocol data exchanged for an RTSP/RTP session

getRTSPOriginAddressType

```
public String getRTSPOriginAddressType()
```

Get the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Returns:

origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

setRTSPOriginAddressType

```
public void setRTSPOriginAddressType(String rtspOriginAddressType)
```

Set the origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

Parameters:

rtspOriginAddressType - origin IP address type (IP4) to used in the Session Description Protocol data exchanged for an RTSP/RTP session

addLiveStreamPacketizerListener

```
public void addLiveStreamPacketizerListener(ILiveStreamPacketizerActionNotify liveStreamPacketizerListener)
```

Add a Live Stream Packetizer listener (see: [ILiveStreamPacketizerActionNotify](#))

Parameters:

liveStreamPacketizerListener - Live Stream Packetizer listener

removeLiveStreamPacketizerListener

```
public void removeLiveStreamPacketizerListener(ILiveStreamPacketizerActionNotify liveStreamPacketizerListener)
```

Remove a Live Stream Packetizer listener (see: [ILiveStreamPacketizerActionNotify](#))

Parameters:

liveStreamPacketizerListener - Live Stream Packetizer listener

notifyLiveStreamPacketizerCreate

```
public void notifyLiveStreamPacketizerCreate(ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Notify Live Stream Packetizer Create

Parameters:

(continued from last page)

liveStreamPacketizer - Live Stream Packetizer listener

notifyLiveStreamPacketizerDestroy

```
public void notifyLiveStreamPacketizerDestroy(ILiveStreamPacketizer liveStreamPacketizer)
```

Notify Live Stream Packetizer Destory

Parameters:

liveStreamPacketizer - Live Stream Packetizer listener

notifyLiveStreamPacketizerInit

```
public void notifyLiveStreamPacketizerInit(ILiveStreamPacketizer liveStreamPacketizer, String streamName)
```

Notify Live Stream Packetizer Init

Parameters:

liveStreamPacketizer - Live Stream Packetizer listener

isValidFMLEConnections

```
public boolean isValidFMLEConnections()
```

Returns true if validating FMLE connection (default is false)

Returns:

true if validating FMLE connection

setValidateFMLEConnections

```
public void setValidateFMLEConnections(boolean validateFMLEConnections)
```

Returns true if validating FMLE connection (default is false)

Parameters:

validateFMLEConnections - true if validating FMLE connection

addLiveStreamTranscoderListener

```
public void addLiveStreamTranscoderListener(ILiveStreamTranscoderNotify liveStreamTranscoderListener)
```

Add a live stream transcoder listener

Parameters:

liveStreamTranscoderListener - live stream transcoder listener

removeLiveStreamTranscoderListener

```
public void removeLiveStreamTranscoderListener(ILiveStreamTranscoderNotify liveStreamTranscoderListener)
```

Remove a live stream transcoder listener

Parameters:

liveStreamTranscoderListener - live stream transcoder listener

notifyLiveStreamTranscoderCreate

```
public void notifyLiveStreamTranscoderCreate(ILiveStreamTranscoder liveStreamTranscoder,  
                                             IMediaStream stream)
```

Notify live stream transcoder create

Parameters:

liveStreamTranscoder - live stream transcoder
stream - stream

notifyLiveStreamTranscoderDestroy

```
public void notifyLiveStreamTranscoderDestroy(ILiveStreamTranscoder liveStreamTranscoder,  
                                              IMediaStream stream)
```

Notify live stream transcoder destroy

Parameters:

liveStreamTranscoder - live stream transcoder
stream - stream

notifyLiveStreamTranscoderInit

```
public void notifyLiveStreamTranscoderInit(ILiveStreamTranscoder liveStreamTranscoder,  
                                           IMediaStream stream)
```

Notify live stream transcoder init

Parameters:

liveStreamTranscoder - live stream transcoder
stream - stream

containsLiveStreamTranscoder

```
public boolean containsLiveStreamTranscoder(String liveStreamTranscoder)
```

Return true if this application instance contains the transcoder name

Parameters:

liveStreamTranscoder - transcoder name

Returns:

true if this application instance contains the transcoder name

getLiveStreamTranscoderList

```
public String getLiveStreamTranscoderList()
```

Get comma separated list of transcoders to use for this application instance

Returns:

comma separated list of transcoders

(continued from last page)

setLiveStreamTranscoderList

```
public void setLiveStreamTranscoderList(String liveStreamTranscoderList)
```

Set comma separated list of transcoders to use for this application instance

Parameters:

liveStreamTranscoderList - comma separated list of transcoders

getLiveStreamTranscoderControl

```
public ILiveStreamTranscoderControl getLiveStreamTranscoderControl()
```

Get the Live Stream Transcoder Contoller. This class will get called each time a stream is to be transcoded using the LiveStreamTranscoder mechanism.

Returns:

Live Stream Transcoder Contoller

setLiveStreamTranscoderControl

```
public void setLiveStreamTranscoderControl(ILiveStreamTranscoderControl liveStreamTranscoderControl)
```

Set the Live Stream Transcoder Contoller. This class will get called each time a stream is to be transcoded using the LiveStreamTranscoder mechanism.

Parameters:

liveStreamTranscoderControl - Live Stream Transcoder Contoller

getTranscoderApplicationContext

```
public LiveStreamTranscoderApplicationContext getTranscoderApplicationContext()
```

Get live stream transcoder application context

Returns:

live stream transcoder application context

getDvrProperties

```
public WMSProperties getDvrProperties()
```

Get the property collection of DVR settings that are specific to this application instance. These are defined in Application/DVR/Properties tag in Application.xml

Returns:

property collection of DVR settings

getDvrApplicationContext

```
public DvrApplicationContext getDvrApplicationContext()
```

Get live stream dvr application context

Returns:

live stream dvr application context

(continued from last page)

getLiveStreamDvrRecorderControl

```
public ILiveStreamDvrRecorderControl getLiveStreamDvrRecorderControl()
```

Get the Live Stream DVR Recorder Controller. This class will get called each time a stream is to be DVR-ed.

Returns:

Live Stream DVR Controller

setLiveStreamDvrRecorderControl

```
public void setLiveStreamDvrRecorderControl(ILiveStreamDvrRecorderControl controller)
```

Set the Live Stream DVR Controller.

Parameters:

controller - Live Stream DVR Controller

getDvrRecorderList

```
public String getDvrRecorderList()
```

Get the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)

Returns:

comma separated list of Dvr Recorder names

setDvrRecorderList

```
public void setDvrRecorderList(String recorderList)
```

Set the comma separated list of Dvr Recorder names being used by this application (see conf/Dvr.xml)

Parameters:

recorderList - comma separated list of Dvr Recorder names

addDvrRecorderListener

```
public void addDvrRecorderListener(ILiveStreamDvrRecorderActionNotify listener)
```

Add a Dvr Recorder listener (see: [ILiveStreamDvrRecorderActionNotify](#))

Parameters:

listener - Dvr Recorder listener

removeDvrRecorderListener

```
public void removeDvrRecorderListener(ILiveStreamDvrRecorderActionNotify listener)
```

Remove a Dvr Recorder listener (see: [ILiveStreamDvrRecorderActionNotify](#))

Parameters:

listener - Dvr Recorder listener

notifyLiveStreamDvrRecorderCreate

```
public void notifyLiveStreamDvrRecorderCreate(ILiveStreamDvrRecorder dvr,  
String streamName)
```

(continued from last page)

Notify Dvr Recorder Create

Parameters:

dvr - DVR Recorder listener
streamName - stream Name

notifyLiveStreamDvrRecorderInit

```
public void notifyLiveStreamDvrRecorderInit(ILiveStreamDvrRecorder dvr,  
String streamName)
```

Notify DVR Recorder has been initialized.

Parameters:

dvr - DVR Recorder listener * @param streamName stream Name

notifyLiveStreamDvrRecorderDestroy

```
public void notifyLiveStreamDvrRecorderDestroy(ILiveStreamDvrRecorder dvr)
```

Notify DVR Recorder has been destroyed.

Parameters:

dvr - DVR Recorder listener

addDvrStreamManagerListener

```
public void addDvrStreamManagerListener(IDvrStreamManagerActionNotify listener)
```

Add a Dvr Application Store Manager listener (see: IDvrStoreActionNotify)

Parameters:

listener - Dvr Application Store Manager listener

removeDvrStreamManagerListener

```
public void removeDvrStreamManagerListener(IDvrStreamManagerActionNotify listener)
```

Remove a Dvr Application Store Manager listener (see: IDvrStoreActionNotify)

Parameters:

listener - Dvr Application Store Manager listener

notifyDvrStreamManagerCreate

```
public void notifyDvrStreamManagerCreate(IDvrStreamManager dvrStoreManager)
```

Notify listeners that Dvr Application Store Manager has been created.

Parameters:

dvrStoreManager - Dvr Application Store Manager

notifyDvrStreamManagerInit

```
public void notifyDvrStreamManagerInit(IDvrStreamManager dvrStoreManager)
```

Notify listeners that Dvr Application Store Manager has been initialized.

(continued from last page)

Parameters:

dvrStoreManager - Dvr Application Store Manager

notifyDvrStreamManagerDestroy

```
public void notifyDvrStreamManagerDestroy(IDvrStreamManager dvrManager)
```

Notify listeners that Dvr Application Store Manager has been destroyed.

Parameters:

dvrManager - Dvr Application Store Manager

getMediaReaderContentType

```
public int getMediaReaderContentType(String mediaType)
```

Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE_*)

Parameters:

mediaType - mediaType (such as flv or smil)

Returns:

content type (see IMediaReader.CONTENTTYPE_*)

getMediaListProvider

```
public IMediaListProvider getMediaListProvider( )
```

Get the current media list provider. The media list provider is used to resolve amlst:streamname requests to a media list (equivalent to a SMIL file).

Returns:

media list provider

setMediaListProvider

```
public void setMediaListProvider(IMediaListProvider mediaListProvider)
```

Set the current media list provider. The media list provider is used to resolve amlst:streamname requests to a media list (equivalent to a SMIL file).

Parameters:

mediaListProvider - media list provider

com.wowza.wms.application Interface IApplicationInstanceNotify

public interface **IApplicationInstanceNotify**
extends

IApplicationInstanceNotify: listener interface used by IApplication addApplicationInstanceListener

Method Summary

void	onApplicationInstanceCreate (IApplicationInstance applicationInstance) Triggered when applicationInstance created
void	onApplicationInstanceDestroy (IApplicationInstance applicationInstance) Triggered when applicationInstance destroyed

Methods

onApplicationInstanceCreate

public void **onApplicationInstanceCreate**([IApplicationInstance](#) applicationInstance)

Triggered when applicationInstance created

Parameters:

applicationInstance - applicationInstance

onApplicationInstanceDestroy

public void **onApplicationInstanceDestroy**([IApplicationInstance](#) applicationInstance)

Triggered when applicationInstance destroyed

Parameters:

applicationInstance - applicationInstance

com.wowza.wms.application Interface IApplicationNotify

public interface **IApplicationNotify**
extends

IApplicationNotify: listener interface used by IVHost addApplicationListener

Method Summary

void	onApplicationCreate (IApplication application) Triggered when application created
void	onApplicationDestroy (IApplication application) Triggered when application destroyed

Methods

onApplicationCreate

public void **onApplicationCreate**([IApplication](#) application)

Triggered when application created

Parameters:

application - application

onApplicationDestroy

public void **onApplicationDestroy**([IApplication](#) application)

Triggered when application destroyed

Parameters:

application - application

com.wowza.wms.application Class WMSProperties

```

java.lang.Object
  |-- java.util.AbstractMap
        |-- java.util.HashMap
              |-- com.wowza.wms.application.WMSProperties

```

All Implemented Interfaces:

java.util.Map, java.io.Serializable, Cloneable, java.util.Map

```

public class WMSProperties
extends java.util.HashMap

```

WMSProperties: generic properties container used by many class to store extended property information. Acts like a simple Map with some simple utilities for performing type conversion.

Constructor Summary

public	WMSProperties()
--------	---------------------------------

Method Summary

static void	cloneProperties (WMSProperties from, WMSProperties to) Copy all properties from "from" properties object to "to" properties object.
String[]	getAllAsStrings() Return all properties as String[].
Object	getProperty (String name) Get property value as generic object.
boolean	getPropertyBoolean (String name, boolean defaultVal) Get property as boolean, return default value if does not exist.
double	getPropertyDouble (String name, double defaultVal) Get property as double, return default value if does not exist.
int	getPropertyInt (String name, int defaultVal) Get property as int, return default value if does not exist.
long	getPropertyLong (String name, long defaultVal) Get property as long, return default value if does not exist.
String	getPropertyStr (String name) Get property as String
String	getPropertyStr (String name, String defaultVal) Get property as String, return default value if does not exist.
void	setProperty (String name, Object value) Set property to generic object.

String	toString()
--------	----------------------------

Methods inherited from class java.util.HashMap

clear, clone, containsKey, containsValue, entrySet, get, isEmpty, keySet, put, putAll, remove, size, values

Methods inherited from class java.util.AbstractMap

clear, clone, containsKey, containsValue, entrySet, equals, get, hashCode, isEmpty, keySet, put, putAll, remove, size, toString, values

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface java.util.Map

clear, containsKey, containsValue, entrySet, equals, get, hashCode, isEmpty, keySet, put, putAll, remove, size, values

Methods inherited from interface java.util.Map

clear, containsKey, containsValue, entrySet, equals, get, hashCode, isEmpty, keySet, put, putAll, remove, size, values

Constructors

WMSProperties

```
public WMSProperties()
```

Methods

cloneProperties

```
public static void cloneProperties(WMSProperties from,
    WMSProperties to)
```

Copy all properties from "from" properties object to "to" properties object.

Parameters:

from - source properties

to - destination properties

setProperty

```
public void setProperty(String name,
    Object value)
```

Set property to generic object.

(continued from last page)

Parameters:

name - property name
value - value

getProperty

```
public Object getProperty(String name)
```

Get property value as generic object.

Parameters:

name - property name

Returns:

value, null if does not exist

getPropertyStr

```
public String getPropertyStr(String name)
```

Get property as String

Parameters:

name - property name

Returns:

value as String, null if does not exist

getPropertyStr

```
public String getPropertyStr(String name,  
                               String defaultVal)
```

Get property as String, return default value if does not exist.

Parameters:

name - property name
defaultVal - default value

Returns:

value as String, defaultVal if does not exist

getPropertyBoolean

```
public boolean getPropertyBoolean(String name,  
                                    boolean defaultVal)
```

Get property as boolean, return default value if does not exist.

Parameters:

name - property name
defaultVal - default value

Returns:

value as boolean, defaultVal if does not exist

(continued from last page)

getPropertyInt

```
public int getPropertyInt(String name,  
    int defaultVal)
```

Get property as int, return default value if does not exist.

Parameters:

name - property name
defaultVal - default value

Returns:

value as boolean, defaultVal if does not exist

getPropertyLong

```
public long getPropertyLong(String name,  
    long defaultVal)
```

Get property as long, return default value if does not exist.

Parameters:

name - property name
defaultVal - default value

Returns:

value as long, defaultVal if does not exist

getPropertyDouble

```
public double getPropertyDouble(String name,  
    double defaultVal)
```

Get property as double, return default value if does not exist.

Parameters:

name - property name
defaultVal - default value

Returns:

value as double, defaultVal if does not exist

getAllAsStrings

```
public String[] getAllAsStrings()
```

Return all properties as String[]. Format is "key=value".

Returns:

all properties as String[]

toString

```
public String toString()
```

Package

com.wowza.wms.authentication

com.wowza.wms.authentication

Class AuthenticateUsernamePasswordProviderBase

java.lang.Object

└--com.wowza.wms.authentication.AuthenticateUsernamePasswordProviderBase

All Implemented Interfaces:

[IAuthenticateUsernamePasswordProvider](#)

public abstract class **AuthenticateUsernamePasswordProviderBase**

extends Object

implements [IAuthenticateUsernamePasswordProvider](#)

Base class for implementing HTTP and RTSP based custom authentication class.

Field Summary

protected	client
protected	rtpSession
protected	vhost

Constructor Summary

public	AuthenticateUsernamePasswordProviderBase()
--------	------------------------------------------------------------

Method Summary

IClient	getClient() Get client
RTPSession	getRTPSession() Get RTP Session
IVHost	getVHost() Get vhost
void	setClient(IClient client) Set client
void	setRTPSession(RTPSession rtpSession) Set RTP Session
void	setVHost(IVHost vhost) Set vhost

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface[com.wowza.wms.authentication.IAuthenticateUsernamePasswordProvider](#)[getClient](#), [getPassword](#), [getRTPSession](#), [getVHost](#), [setClient](#), [setRTPSession](#), [setVHost](#), [userExists](#)

Fields

vhostprotected com.wowza.wms.vhost.IVHost **vhost****client**protected com.wowza.wms.client.IClient **client****rtpSession**protected com.wowza.wms.rtp.model.RTPSession **rtpSession**

Constructors

AuthenticateUsernamePasswordProviderBasepublic **AuthenticateUsernamePasswordProviderBase**()

Methods

getVHostpublic [IVHost](#) **getVHost**()

Get vhost

Returns:

vhost

setVHostpublic void **setVHost**([IVHost](#) vhost)

Set vhost

Parameters:

vhost - vhost

(continued from last page)

getRTPSession

```
public RTPSession getRTPSession()
```

Get RTP Session

Returns:

RTP Session

setRTPSession

```
public void setRTPSession(RTPSession rtpSession)
```

Set RTP Session

Parameters:

rtpSession - RTP Session

getClient

```
public IClient getClient()
```

Get client

Returns:

client

setClient

```
public void setClient(IClient client)
```

Set client

Parameters:

client - client

com.wowza.wms.authentication Interface IAuthenticate

public interface **IAuthenticate**
extends

IAuthenticate: HTTP and RTSP authentication interface

Field Summary

public static final	PASSWORDFILEFORMAT_CLEAR Value: 1
public static final	PASSWORDFILEFORMAT_UNKNOWN Value: 0

Method Summary

void	init (IApplicationInstance appInstance, AuthenticationItem authenticationItem) Initialize authentication class when instantiated as part of an application instance
void	init (IVHost vhost, AuthenticationItem authenticationItem) Initialize authentication class when instantiated as part of a vhost

Fields

PASSWORDFILEFORMAT_UNKNOWN

public static final int **PASSWORDFILEFORMAT_UNKNOWN**

Constant value: **0**

PASSWORDFILEFORMAT_CLEAR

public static final int **PASSWORDFILEFORMAT_CLEAR**

Constant value: **1**

Methods

init

public void **init**([IApplicationInstance](#) appInstance,
AuthenticationItem authenticationItem)

Initialize authentication class when instantiated as part of an application instance

(continued from last page)

Parameters:

appInstance - application instance
authenticationItem - authentication item

init

```
public void init(IVHost vhost,  
                AuthenticationItem authenticationItem)
```

Initialize authentication class when instantiated as part of a vhost

Parameters:

vhost - vhost
authenticationItem - authentication item

com.wowza.wms.authentication Interface IAuthenticateHTTPProvider

public interface **IAuthenticateHTTPProvider**
extends

IAuthenticateHTTPProvider: HTTP authentication provider

Method Summary

boolean	authenticateHTTPProvider (IVHost vhost, IHTTPRequest req, IHTTPResponse resp) Called for each HTTP authentication
---------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

authenticateHTTPProvider

```
public boolean authenticateHTTPProvider(IVHost vhost,  
    IHTTPRequest req,  
    IHTTPResponse resp)
```

Called for each HTTP authentication

Parameters:

vhost - virtual host
req - HTTP request
resp - HTTP response

Returns:

true if authentication was successful

com.wowza.wms.authentication Interface IAuthenticateRTSP

public interface **IAuthenticateRTSP**
extends

IAuthenticateRTSP: RTSP authentication provider

Method Summary

boolean	<code>authenticateRTSP(RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp)</code> Called for each RTSP authentication
---------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

authenticateRTSP

```
public boolean authenticateRTSP(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Called for each RTSP authentication

Parameters:

`rtspSession` - RTP session
`req` - RTSP request
`resp` - RTSP response

Returns:

true if authentication was successful

com.wowza.wms.authentication Interface IAuthenticateUsernamePasswordProvider

All Known Implementing Classes:

[AuthenticateUsernamePasswordProviderBase](#)

public interface **IAuthenticateUsernamePasswordProvider**
extends

IAuthenticateUsernamePasswordProvider: HTTP and RTSP username/password validator interface

Method Summary

IClient	getClient() Get client
String	getPassword(String username) Get password for a given user
RTPSession	getRTPSession() Get RTP session
IVHost	getVHost() Get vhost
void	setClient(IClient client) Set client
void	setRTPSession(RTPSession rtpSession) Set RTP session
void	setVHost(IVHost vhost) Set vhost
boolean	userExists(String username) Return true if user exists

Methods

userExists

public boolean **userExists**(String username)

Return true if user exists

Parameters:

username - username

Returns:

true if user exists

(continued from last page)

getPassword

```
public String getPassword(String username)
```

Get password for a given user

Parameters:

username - username

Returns:

password

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:

vhost

setVHost

```
public void setVHost(IVHost vhost)
```

Set vhost

Parameters:

vhost - vhost

getClient

```
public IClient getClient()
```

Get client

Returns:

client

setClient

```
public void setClient(IClient client)
```

Set client

Parameters:

client - client

getRTPSession

```
public RTPSession getRTPSession()
```

Get RTP session

Returns:

RTP session

(continued from last page)

setRTPSession

```
public void setRTPSession(RTPSession rtpSession)
```

Set RTP session

Parameters:

rtpSession - RTP session

Package

com.wowza.wms.client

com.wowza.wms.client Class ConnectionCounter

```

java.lang.Object
  |
  +--com.wowza.wms.client.ConnectionCounterBase
        |
        +--com.wowza.wms.client.ConnectionCounter
  
```

```

public class ConnectionCounter
extends ConnectionCounterBase
  
```

Fields inherited from class com.wowza.wms.client.ConnectionCounterBase

DATEFORMATSTR, NEVERSTR, REJECTREASON_APPLICATION, REJECTREASON_COUNT, REJECTREASON_LICENSE

Constructor Summary

public	ConnectionCounter() Create empty ConnectionCounter
--------	-----------------------------------------------------------------------

Method Summary

void	acceptConnection (ConnectionHolder connectionHolder, byte[] license) Accept a new connection.
void	addConnectionListener (IConnectionNotify connectionNotify) Add a connection listener.
void	decrement (ConnectionHolder connectionHolder, boolean isValid, java.util.Date date, long stamp, byte[] license) Decrement connection counters.
void	disconnect (ConnectionHolder connectionHolder, byte[] license) Disconnect connection.
long	getCurrent () Get total number of client currently conencted to this object.
long	getLastConnectAcceptedStamp () Get time (milliseconds) of the last conenction to this object.
String	getLastConnectAcceptedStampString () Get time (milliseconds) of the last conenction to this object as formatted string.
java.util.Date	getLastConnectAcceptedTime () Get time (milliseconds) of the last accepted conenction to this object.
String	getLastConnectAcceptedTimeString () Get time (milliseconds) of the last accepted conenction to this object as formatted string.
long	getLastConnectRejectedByReasonStamp (int reason) Get time (milliseconds) of the last rejected conenction by reason to this object.

String	<u>getLastConnectRejectedByReasonStampString</u> (int reason) Get time (milliseconds) of the last rejected connection by reason to this object as formatted string.
java.util.Date	<u>getLastConnectRejectedByReasonTime</u> (int reason) Get date and time of last rejected connection by reason to this object as Date object.
String	<u>getLastConnectRejectedByReasonTimeString</u> (int reason) Get date and time of last rejected connection by reason to this object as formatted string.
long	<u>getLastConnectRejectedStamp</u> () Get time (milliseconds) of the last rejected connection to this object.
String	<u>getLastConnectRejectedStampString</u> () Get time (milliseconds) of the last rejected connection to this object as formatted string.
java.util.Date	<u>getLastConnectRejectedTime</u> () Get date and time of last rejected connection to this object as Date object.
String	<u>getLastConnectRejectedTimeString</u> () Get date and time of last rejected connection to this object as formatted string.
long	<u>getLastDisconnectStamp</u> () Get time (milliseconds) of the last disconnected connection to this object.
String	<u>getLastDisconnectStampString</u> () Get time (milliseconds) of the last disconnected connection to this object as formatted string.
java.util.Date	<u>getLastDisconnectTime</u> () Get date and time of last disconnected connection to this object as Date object.
String	<u>getLastDisconnectTimeString</u> () Get date and time of last disconnected connection to this object as Date object as formatted string.
long	<u>getTotal</u> () Get total number of connection attempts to this object.
long	<u>getTotalAccepted</u> () Get total number of accepted connections to this object.
long	<u>getTotalRejected</u> () Get total number of rejected connections to this object.
void	<u>incrementAccept</u> (ConnectionHolder connectionHolder, java.util.Date date, long stamp, byte[] license) Increment accepted connections.
void	<u>incrementReject</u> (ConnectionHolder connectionHolder, int reason, java.util.Date date, long stamp, byte[] license) Increment reject connection.
void	<u>rejectConnection</u> (ConnectionHolder connectionHolder, int reason, byte[] license) Reject connection.
void	<u>removeConnectionListener</u> (IConnectionNotify connectionNotify) Remove connection listener
void	<u>setConnectionValidator</u> (IConnectionValidator connectionValidator) Set the connection validator.

boolean	validateNewConnection (ConnectionHolder connectionHolder, byte[] license) Validate a new connection.
---------	-------------------------------------------------------------------------------------------------------------------------

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ConnectionCounter

```
public ConnectionCounter()
```

Create empty ConnectionCounter

Methods

addConnectionListener

```
public void addConnectionListener(IConnectionNotify connectionNotify)
```

Add a connection listener. Receives following events: onClientConnect, onClientDisconnect, onClientAccept and onClientReject.

Parameters:

connectionNotify - connection listener

removeConnectionListener

```
public void removeConnectionListener(IConnectionNotify connectionNotify)
```

Remove connection listener

Parameters:

connectionNotify - connection listener

setConnectionValidator

```
public void setConnectionValidator(IConnectionValidator connectionValidator)
```

Set the connection validator.

Parameters:

connectionValidator - connection validator

validateNewConnection

```
public boolean validateNewConnection(ConnectionHolder connectionHolder,  
byte[] license)
```

Validate a new connection.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

(continued from last page)

Parameters:

connectionHolder - connection holder
license - security data

Returns:

true if connection is accepted

acceptConnection

```
public void acceptConnection(ConnectionHolder connectionHolder,  
    byte[] license)
```

Accept a new connection.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

Parameters:

connectionHolder - connection holder
license - security data

incrementAccept

```
public void incrementAccept(ConnectionHolder connectionHolder,  
    java.util.Date date,  
    long stamp,  
    byte[] license)
```

Increment accepted connections.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

Parameters:

connectionHolder - connection holder
date - date the connection occurred
stamp - time stamp connection occurred (milliseconds)
license - security data

rejectConnection

```
public void rejectConnection(ConnectionHolder connectionHolder,  
    int reason,  
    byte[] license)
```

Reject connection.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

Parameters:

connectionHolder - connection holder
reason - reason the connection was refused. See REJECTREASON_*
license - security data

(continued from last page)

incrementReject

```
public void incrementReject(ConnectionHolder connectionHolder,  
    int reason,  
    java.util.Date date,  
    long stamp,  
    byte[] license)
```

Increment reject connection.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

Parameters:

connectionHolder - connection holder
reason - reason the connection was refused. See REJECTREASON_*
date - date the connection occurred
stamp - time stamp connection occurred (milliseconds)
license - security data

disconnect

```
public void disconnect(ConnectionHolder connectionHolder,  
    byte[] license)
```

Disconnect connection.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

Parameters:

connectionHolder - connection holder
license - security data

decrement

```
public void decrement(ConnectionHolder connectionHolder,  
    boolean isValid,  
    java.util.Date date,  
    long stamp,  
    byte[] license)
```

Decrement connection counters.

NOTE: This is a private internal call. Server will not work properly if this method is not called properly using internal security mechanism.

Parameters:

connectionHolder - connection holder
isValid - is a valid connection
date - date the connection occurred
stamp - time stamp connection occurred (milliseconds)
license - security data

getCurrent

```
public long getCurrent()
```

Get total number of client currently connected to this object.

Returns:

total number of client currently connected to this object

getLastConnectAcceptedStamp

```
public long getLastConnectAcceptedStamp()
```

Get time (milliseconds) of the last conenction to this object.

Returns:

time (milliseconds) of the last conenction to this object

getLastConnectAcceptedStampString

```
public String getLastConnectAcceptedStampString()
```

Get time (milliseconds) of the last conenction to this object as formatted string.

Returns:

time (milliseconds) of the last conenction to this object as formatted string

getLastConnectAcceptedTime

```
public java.util.Date getLastConnectAcceptedTime()
```

Get time (milliseconds) of the last accepeted conenction to this object.

Returns:

time (milliseconds) of the last accepeted conenction to this object

getLastConnectAcceptedTimeString

```
public String getLastConnectAcceptedTimeString()
```

Get time (milliseconds) of the last accepeted conenction to this object as formatted string.

Returns:

time (milliseconds) of the last accepeted conenction to this object as formatted string

getLastConnectRejectedStamp

```
public long getLastConnectRejectedStamp()
```

Get time (milliseconds) of the last rejected conenction to this object.

Returns:

time (milliseconds) of the last rejected conenction to this object

getLastConnectRejectedStampString

```
public String getLastConnectRejectedStampString()
```

Get time (milliseconds) of the last rejected conenction to this object as formatted string.

Returns:

time (milliseconds) of the last rejected conenction to this object as formatted string

getLastConnectRejectedTime

```
public java.util.Date getLastConnectRejectedTime()
```

(continued from last page)

Get date and time of last rejected connection to this object as Date object.

Returns:

date and time of last reject connection to this object as Date object

getLastConnectRejectedTimeString

```
public String getLastConnectRejectedTimeString()
```

Get date and time of last rejected connection to this object as formatted string.

Returns:

date and time of last reject connection to this object as formatted string

getLastConnectRejectedByReasonStampString

```
public String getLastConnectRejectedByReasonStampString(int reason)
```

Get time (milliseconds) of the last rejected connection by reason to this object as formatted string.

Parameters:

reason - reason, see REJECTREASON_*

Returns:

time (milliseconds) of the last rejected connection by reason to this object as formatted string

getLastConnectRejectedByReasonStamp

```
public long getLastConnectRejectedByReasonStamp(int reason)
```

Get time (milliseconds) of the last rejected connection by reason to this object.

Parameters:

reason - reason, see REJECTREASON_*

Returns:

time (milliseconds) of the last rejected connection by reason to this object

getLastConnectRejectedByReasonTime

```
public java.util.Date getLastConnectRejectedByReasonTime(int reason)
```

Get date and time of last rejected connection by reason to this object as Date object.

Parameters:

reason - reason, see REJECTREASON_*

Returns:

date and time of last reject connection by reason to this object as Date object

getLastConnectRejectedByReasonTimeString

```
public String getLastConnectRejectedByReasonTimeString(int reason)
```

Get date and time of last rejected connection by reason to this object as formatted string.

Parameters:

reason - reason, see REJECTREASON_*

(continued from last page)

Returns:

date and time of last rejected connection by reason to this object as formatted string

getLastDisconnectStampString

```
public String getLastDisconnectStampString( )
```

Get time (milliseconds) of the last disconnected connection to this object as formatted string.

Returns:

time (milliseconds) of the last disconnected connection to this object as formatted string

getLastDisconnectStamp

```
public long getLastDisconnectStamp( )
```

Get time (milliseconds) of the last disconnected connection to this object.

Returns:

time (milliseconds) of the last disconnected connection to this object

getLastDisconnectTime

```
public java.util.Date getLastDisconnectTime( )
```

Get date and time of last disconnected connection to this object as Date object.

Returns:

date and time of last disconnected connection to this object as Date object

getLastDisconnectTimeString

```
public String getLastDisconnectTimeString( )
```

Get date and time of last disconnected connection to this object as Date object as formatted string.

Returns:

date and time of last disconnected connection to this object as Date object as formatted string

getTotal

```
public long getTotal( )
```

Get total number of connection attempts to this object.

Returns:

total number of connection attempts to this object

getTotalAccepted

```
public long getTotalAccepted( )
```

Get total number of accepted connections to this object.

Returns:

total number of accepted connections to this object

getTotalRejected

```
public long getTotalRejected()
```

Get total number of rejected connections to this object.

Returns:

total number of rejected connections to this object

com.wowza.wms.client Interface IClient

public interface **IClient**
extends

IClient: public interface to Client object.

Field Summary

public static final	AUDIOSAMPLE_ACCESS_ALL Value: *
public static final	AUDIOSAMPLE_ACCESS_NONE Value:
public static final	READ_ACCESS_ALL Value: *
public static final	READ_ACCESS_NONE Value:
public static final	VIDEOSAMPLE_ACCESS_ALL Value: *
public static final	VIDEOSAMPLE_ACCESS_NONE Value:
public static final	WRITE_ACCESS_ALL Value: *
public static final	WRITE_ACCESS_NONE Value:

Method Summary

void	acceptConnection () Accept connection
void	acceptConnection (AMFData successObj) Accept connection
void	acceptConnection (String successStr) Accept connection
void	addAcceptConnectionAttribute (String key, AMFDataObj item) Add and attribute to the resultObj that gets passed back to the client on successful connection

void	<u>addAcceptConnectionAttribute</u> (String key, String item) Add and attribute to the resultObj that gets passed back to the client on successful connection
void	<u>call</u> (String handlerName) Simplified call client method/handler call.
void	<u>call</u> (String handlerName, <u>IModuleCallResult</u> resultObj, Object[] params) Call client method/handler.
void	<u>clearFastPlaySettings</u> () Force clear the fastPlay settings
void	<u>fcSubscribe</u> (String streamName) Subscribe to a live stream (for live stream repeater to start start from edge to origin)
void	<u>fcSubscribe</u> (String streamName, String mediaCasterType) Subscribe to a live stream (use a particular mediaCasterType)
void	<u>fcUnSubscribe</u> (String streamName) UnSubscribe from a stream
void	<u>fcUnSubscribeAll</u> () UnSubscribe to all streams that this client is current subscribed to
<u>IApplicationInstance</u>	<u>getAppInstance</u> () Get parent applicationInstance.
<u>IApplication</u>	<u>getApplication</u> () Get parent application.
int	<u>getBufferTime</u> () Get default buffer time for newly created mediaStream objects
int	<u>getClientId</u> () Get client id.
long	<u>getConnectTime</u> () Get time in milliseconds the client connected to the server.
String	<u>getDateStarted</u> () Get date and time of client connection
<u>ElapsedTimer</u>	<u>getElapsedTime</u> () Get elapsed time client has been connected.
<u>FastPlaySettings</u>	<u>getFastPlaySettings</u> () Get the current fastPlay settings.
String	<u>getFlashVer</u> () Get client flash version (same as FMS getAgent())
int	<u>getIdleFrequency</u> () Get client idle frequency (milliseconds)
String	<u>getIp</u> () Client ip address
long	<u>getLastValidateTime</u> () Get last time (millisecond) the connection was validated with a ping

int	<u>getLiveRepeaterCapabilities()</u> Get the live repeater capabilities of this connection
String	<u>getLiveStreamPacketizerList()</u> Get the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)
String	<u>getLiveStreamTranscoderList()</u> Get the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)
int	<u>getMaximumPendingWriteBytes()</u> Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
int	<u>getMaximumSetBufferTime()</u> Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
<u>IOPerformanceCounter</u>	<u>getMediaIOPerformanceCounter()</u> Get performance counter for media bytes transferred to this client.
int	<u>getObjectEncoding()</u> Get the object encoding level
String	<u>getPageUrl()</u> Get the pageUrl for this connection.
long	<u>getPingRoundTripTime()</u> Get turn around time (milliseconds) of last ping request
int	<u>getPingTimeout()</u> Get the ping timeout (milliseconds)
java.util.List	<u>getPlayStreams()</u> Get a collection of all play streams.
<u>WMSProperties</u>	<u>getProperties()</u> Get client properties
int	<u>getProtocol()</u> Get connection protocol (1 = RTMP, 3 = RTMPT)
java.util.List	<u>getPublishStreams()</u> Get a collection of publish streams.
String	<u>getQueryStr()</u> Get the query string part of the connection string.
String	<u>getReferrer()</u> Get the referrer data for this connection.
String	<u>getRepeaterOriginUrl()</u> Get the origin URL used by the Live Stream Repeater
<u>AMFObj</u>	<u>getRespAMFAudioObj()</u> (<u>IMediaStream</u> stream) Get the audio response AMFObj for a given mediaStream
<u>AMFObj</u>	<u>getRespAMFDataObj()</u> (<u>IMediaStream</u> stream) Get the data response AMFObj for a given mediaStream

AMFObj	getRespAMFVideoObj (IMediaStream stream) Get the video response AMFObj for a given mediaStream
ResponseFunctions	getRespFunctions () Get client responseFunctions object.
AMFObj	getResponseAMFObj (int index) Get the response channel AMFObj for channel index.
RTPStream	getRTPStream () If this client was created due to an RTP connection to the server return the underlying RTPStream object
HostPort	getServerHostPort () Get the hostPort object for the connection that is servicing this client
String	getSharedObjectReadAccess () Get the shared object read access value.
String	getSharedObjectWriteAccess () Get the shared object write access value.
String	getStreamAudioSampleAccess () Get the audio sample access value.
java.io.File	getStreamFile (String streamName) Get File object for stream with given name.
java.io.File	getStreamFile (String streamName, String streamExt) Get File object for stream with given name and extension.
java.io.File	getStreamFile (String streamName, String streamExt, boolean doCreateFolder) Get File object for stream with given name and extension.
String	getStreamReadAccess () Get the stream read access value.
String	getStreamType () Get default streamType
String	getStreamVideoSampleAccess () Get the video sample access value.
String	getStreamWriteAccess () Get the stream write access value.
String	getTimeRunning () Get elapsed time of connection
double	getTimeRunningSeconds () Get time running in seconds
IOPerformanceCounter	getTotalIOPerformanceCounter () Get performance counter for all bytes transferred to this client.
String	getUri () Get the full URI of the connection string

IVHost	getVHost() Get parent vHost
ClientWriteListener	getWriteListener() Object that tracks write operations
boolean	isAcceptConnection() Is auto accept connection
boolean	isConnected() Is this client connected
boolean	isEncrypted() Is this connection encrypted (RTMPE or RTMPTE)
boolean	isFlashMediaLiveEncoder() Returns true if this connection is the Flash Media Live Encoder
boolean	isFlashVersion10() Returns true if the Flash version is equal or greater than 10.x.x.x
boolean	isFlashVersion90115() Returns true if the Flash version is equal or greater than 9.0.115.x
boolean	isFlashVersionH264Capable() Returns true if the connected client is capable of playing H.264 video (Flash player 9.0.45.x or greater)
boolean	isLiveRepeater() Returns true if this connection is from the live stream repeater
boolean	isObjectEncodingAMF0() Is the object encoding for this client AMF0
boolean	isObjectEncodingAMF3() Is the object encoding for this client AMF3
boolean	isSecure() Is this connection protected by either SSL or encryption (RTMPE, RTMPTE, RTMPS)
boolean	isSSL() Is this connection SSL (RTMPS)
boolean	isValidFMLEConnections() Returns true if validating FMLE connection (default is false)
int	ping(IModulePingResult pingResult) Ping client.
void	redirectConnection(String url) Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)
void	redirectConnection(String url, String description) Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)
void	redirectConnection(String url, String description, AMFData errorObj) Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302).

void	<u>redirectConnection</u> (String url, String description, String errorStr) Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)
void	<u>rejectConnection</u> () Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<u>rejectConnection</u> (<u>AMFData</u> errorObj) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<u>rejectConnection</u> (String errorStr) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<u>rejectConnection</u> (String description, <u>AMFData</u> errorObj) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<u>rejectConnection</u> (String description, String errorStr) Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)
void	<u>reparentClient</u> (<u>IVHost</u> vhost) Move a client object to a new vhost.
void	<u>setAcceptConnection</u> (boolean acceptConnection) Set the default for accept connection
void	<u>setAcceptConnectionDescription</u> (String description) Call this method from onConnect to set the info.description property returned in NetConnection onStatus handler
void	<u>setAcceptConnectionExObj</u> (<u>AMFDataObj</u> acceptConnectionExObj) Call this method from onConnect to set the info.ex property returned in NetConnection onStatus handler
void	<u>setAcceptConnectionObj</u> (<u>AMFData</u> acceptConnectionObj) Call this method from onConnect to add an "application" property to the info object that is passed back to the Flash client in the onStatus handler.
void	<u>setBufferTime</u> (int bufferTime) Set default buffer time for newly created mediaStream objects
void	<u>setFastPlaySettings</u> (<u>FastPlaySettings</u> fastPlaySettings) Set fastPlay settings
void	<u>setFlashVer</u> (String flashVer) Set client flash version
void	<u>setIdleFrequency</u> (int idleFrequency) Set client idle frequency (milliseconds)
void	<u>setLastValidateTime</u> (long lastValidateTime) Set the last time (milliseconds) the connection was validated with ping
void	<u>setLiveRepeaterCapabilities</u> (int liveRepeaterCapabilities) Set the live repeater capabilities of this connection

void	<u>setLiveStreamPacketizerList</u> (String liveStreamPacketizerList) Set the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)
void	<u>setLiveStreamTranscoderList</u> (String liveStreamTranscoderList) Set the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)
void	<u>setObjectEncoding</u> (int objectEncoding) Set the object encoding level
void	<u>setRepeaterOriginUrl</u> (String repeaterOriginUrl) Set the origin URL used by the Live Stream Repeater
void	<u>setSharedObjectReadAccess</u> (String sharedObjectReadAccess) Set the shared object read access value.
void	<u>setSharedObjectWriteAccess</u> (String sharedObjectWriteAccess) Set the shared object write access value.
void	<u>setShutdownClient</u> (boolean shutdownClient) Gracefully and forcefully shutdown a client.
void	<u>setStreamAudioSampleAccess</u> (String audioSampleAccess) Set the stream audio sample access value.
void	<u>setStreamReadAccess</u> (String streamReadAccess) Set the stream object read access value.
void	<u>setStreamType</u> (String streamType) Set default streamType
void	<u>setStreamVideoSampleAccess</u> (String videoSampleAccess) Set the stream video sample access value.
void	<u>setStreamWriteAccess</u> (String streamWriteAccess) Set the stream object write access value.
void	<u>setThreadContext</u> () Set the thread logging context to this client
void	<u>setValidateFMLEConnections</u> (boolean validateFMLEConnections) Returns true if validating FMLE connection (default is false)
void	<u>shutdownClient</u> () Gracefully shutdown a client.
int	<u>testFlashVersion</u> (int[] version) Test to see if the connected client flash version is equal to or greater than a given value.
void	<u>touch</u> () Update the last touch time for client

Fields

(continued from last page)

VIDEOSAMPLE_ACCESS_ALL

```
public static final java.lang.String VIDEOSAMPLE_ACCESS_ALL
```

Constant value: *

VIDEOSAMPLE_ACCESS_NONE

```
public static final java.lang.String VIDEOSAMPLE_ACCESS_NONE
```

Constant value:

AUDIOSAMPLE_ACCESS_ALL

```
public static final java.lang.String AUDIOSAMPLE_ACCESS_ALL
```

Constant value: *

AUDIOSAMPLE_ACCESS_NONE

```
public static final java.lang.String AUDIOSAMPLE_ACCESS_NONE
```

Constant value:

READ_ACCESS_ALL

```
public static final java.lang.String READ_ACCESS_ALL
```

Constant value: *

READ_ACCESS_NONE

```
public static final java.lang.String READ_ACCESS_NONE
```

Constant value:

WRITE_ACCESS_ALL

```
public static final java.lang.String WRITE_ACCESS_ALL
```

Constant value: *

WRITE_ACCESS_NONE

```
public static final java.lang.String WRITE_ACCESS_NONE
```

Constant value:

Methods

(continued from last page)

getClientId

```
public int getClientId()
```

Get client id. Assigned by server and connection time.

Returns:

client id

getFlashVer

```
public String getFlashVer()
```

Get client flash version (same as FMS getAgent())

Returns:

client flash version string

setFlashVer

```
public void setFlashVer(String flashVer)
```

Set client flash version

Parameters:

flashVer - client flash version string

getTotalIOPerformanceCounter

```
public IOPerformanceCounter getTotalIOPerformanceCounter()
```

Get performance counter for all bytes transferred to this client. This includes function calls.

Returns:

performance counter

getMediaIOPerformanceCounter

```
public IOPerformanceCounter getMediaIOPerformanceCounter()
```

Get performance counter for media bytes transferred to this client. Only includes bytes to mediaStream objects

Returns:

performance counter

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get parent applicationInstance. Is null if connection reject or before accepted.

Returns:

parent applicationInstance

getApplication

```
public IApplication getApplication()
```

(continued from last page)

Get parent application. Is null if connection reject or before accepted.

Returns:

application

getPlayStreams

```
public java.util.List getPlayStreams()
```

Get a collection of all play streams. Play streams are streams that are created due to a call to play.

Iterate Play Streams

```
IClient client;

List playStreams = client.getPlayStreams();
Iterator iter = playStreams.iterator();
while(iter.hasNext())
{
    IMediaStream stream = (IMediaStream)iter.next();
    WMSLoggerFactory.getLogger(null).debug("stream: "+stream.getName());
}
```

Returns:

collection of play streams

getPublishStreams

```
public java.util.List getPublishStreams()
```

(continued from last page)

Get a collection of publish streams. Publish streams are streams that are created due to a call to publish.

Iterate Public Streams

```
IClient client;

List publishStreams = client.getPublishStreams();
Iterator iter = publishStreams.iterator();
while(iter.hasNext())
{
    IMediaStream stream = (IMediaStream)iter.next();
    WMSLoggerFactory.getLogger(null).debug("stream: "+stream.getName());
}
```

Returns:

collection of publish stream

shutdownClient

```
public void shutdownClient()
```

Gracefully shutdown a client. Only use this method to shutdown a client if you know the client is connected to Wowza Pro. If the client may be disconnected from Wowza Pro, use `IClient.setShutdownClient(true)`

touch

```
public void touch()
```

Update the last touch time for client

isConnected

```
public boolean isConnected()
```

Is this client connected

Returns:

is connected

getProperties

```
public WMSProperties getProperties()
```

Get client properties

Returns:

collection of client properties

(continued from last page)

getStreamType

```
public String getStreamType()
```

Get default streamType

Returns:

streamType

setStreamType

```
public void setStreamType(String streamType)
```

Set default streamType

Parameters:

streamType - streamType

isAcceptConnection

```
public boolean isAcceptConnection()
```

Is auto accept connection

Returns:

auto accept connection

acceptConnection

```
public void acceptConnection()
```

Accept connection

acceptConnection

```
public void acceptConnection(String successStr)
```

Accept connection

Parameters:

successStr - application property value added to NetConnection.Connect.Success event object

acceptConnection

```
public void acceptConnection(AMFData successObj)
```

Accept connection

Parameters:

successObj - application property value added to NetConnection.Connect.Success event object

rejectConnection

```
public void rejectConnection()
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

(continued from last page)

rejectConnection

```
public void rejectConnection(String errorStr)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

Parameters:

errorStr - error (returned in onStatus handler in info.application parameter)

rejectConnection

```
public void rejectConnection(AMFData errorObj)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

Parameters:

errorObj - error AMFData (returned in onStatus handler in info.application parameter)

rejectConnection

```
public void rejectConnection(String description,  
    String errorStr)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

Parameters:

description - description (returned in onStatus handler in info.description parameter)

errorStr - error (returned in onStatus handler in info.application parameter)

rejectConnection

```
public void rejectConnection(String description,  
    AMFData errorObj)
```

Reject connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected)

Parameters:

description - description (returned in onStatus handler in info.description parameter)

errorObj - error AMFData (returned in onStatus handler in info.application parameter)

redirectConnection

```
public void redirectConnection(String url)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

Parameters:

url - url (returned in onStatus handler in info.ex.redirect parameter)

redirectConnection

```
public void redirectConnection(String url,  
    String description)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

Parameters:

(continued from last page)

url - url (returned in onStatus handler in info.ex.redirect parameter)

description - description (returned in onStatus handler in info.description parameter)

redirectConnection

```
public void redirectConnection(String url,
    String description,
    String errorStr)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302)

Parameters:

url - url (returned in onStatus handler in info.ex.redirect parameter)

description - description (returned in onStatus handler in info.description parameter)

errorStr - error (returned in onStatus handler in info.application parameter)

redirectConnection

```
public void redirectConnection(String url,
    String description,
    AMFData errorObj)
```

Redirection connection (NetConnection.onStatus handler returns info.code of NetConnection.Connect.Rejected and info.ex.code of 302). Code must be added client side to capture the NetConnection.Connect.Rejected message, look for the info.ex.code value of 302 and attempt a reconnect to the info.ex.redirect url. Client side example:

```
public function ncOnStatus(infoObject:NetStatusEvent)
{
    if (infoObject.info.code == "NetConnection.Connect.Rejected")
    {
        if (infoObject.info.ex.code == 302)
        {
            trace("Connection redirected: "+infoObject.info.ex.redirect);
            nc.connect(infoObject.info.ex.redirect);
        }
        else
            trace("Connection rejected");
    }
}
nc.addEventListener(NetStatusEvent.NET_STATUS, ncOnStatus);
```

Parameters:

url - url (returned in onStatus handler in info.ex.redirect parameter)

description - description (returned in onStatus handler in info.description parameter)

errorObj - error AMFData (returned in onStatus handler in info.application parameter)

getVHost

```
public IVHost getVHost( )
```

Get parent vHost

(continued from last page)

Returns:

vHost object

call

```
public void call(String handlerName,  
    IModuleCallResult resultObj,  
    Object[] params)
```

Call client method/handler. You can call any method/handler attached to NetConnection object. Such as netConnection.myFunc

Call Client Handler Method With Result Object

```
IClient client;  
  
class ReturnObj implements IModuleCallResult  
{  
    public void onResult(IClient client, RequestFunction function,  
        AMFDataList params)  
    {  
        WMSLoggerFactory.getLogger(null).debug("onResult");  
    }  
}  
  
client.call("onCustomMethod", new ReturnObj(), "param1", 1.2345, false, new Date());
```

Parameters:

handlerName - handler name

resultObj - if client method returns data this object will receive callback, null if don't care or no return on client method/handler.

params - variable list of argument. Will be automatically wrapped in AMFData objects

call

```
public void call(String handlerName)
```

Simplified call client method/handler call. No resultObj. No parameters

Parameters:

handlerName - handler name

ping

```
public int ping(IModulePingResult pingResult)
```

(continued from last page)

Ping client. Unlike FMS this ping is asynchronous. pingResult object will be notified of successful response by client or timeout.

Ping Client and Kill Connection If Client Has Died

```
class PingResult implements IModulePingResult
{
    public void onResult(IClient client, long pingTime, int pingId, boolean result)
    {
        WMSLogger log = WMSLoggerFactory.getLogger(null);
        log.debug("onResult: result:"+result);
        if (!result)
        {
            // client has died lets kill it
            client.getAppInstance().shutdownClient(client);
        }
        else
            log.debug("lastPingTime: "+client.getPingRoundTripTime());
    }
}
client.ping(new PingResult());
```

Parameters:

pingResult - ping result object. Will receive callback on result of ping or timeout. Can be null.

Returns:

ping id

getIp

```
public String getIp()
```

Client ip address

Returns:

client ip address

getFastPlaySettings

```
public FastPlaySettings getFastPlaySettings()
```

Get the current fastPlay settings. FastPlay settings when set from the client are immediately cleared on the next call to seek/unpause/play.

Returns:

fastPlay settings

(continued from last page)

setFastPlaySettings

```
public void setFastPlaySettings(FastPlaySettings fastPlaySettings)
```

Set fastPlay settings

Parameters:

fastPlaySettings - fastPlay settings

clearFastPlaySettings

```
public void clearFastPlaySettings()
```

Force clear the fastPlay settings

getRespFunctions

```
public ResponseFunctions getRespFunctions()
```

Get client responseFunctions object. The responseFunctions object is the method by which events are sent to the client. This code snippet shows how to send an onStatus event for a mediaStream (stream) to the client.

Send Status Message to Client

```
ResponseFunctions respFunctions = client.getRespFunctions();

ResponseFunction resp = new ResponseFunction();
resp.createDefaultMessage("onStatus", 0.0);
resp.setRetAMFObj(stream.getRespAMFDataObj());
resp.setSrc(stream.getSrc());

AMFDataObj data = new AMFDataObj();
data.put("level", new AMFDataItem("status"));
data.put("code", new AMFDataItem("NetStream.Publish.Success"));
data.put("description", new AMFDataItem(stream.getName()+" is now unpublished.));
data.put("clientId", new AMFDataItem(clientID));
resp.addBody(data);

respFunctions.add(resp);
```

Returns:

responseFunctions object

getConnectTime

```
public long getConnectTime()
```

(continued from last page)

Get time in milliseconds the client connected to the server. To get the duration of time in milliseconds that the client has been connected to the server us the following formula: `(System.currentTimeMillis() - client.getConnectTime())`

Returns:

duration connected (milliseconds)

getPingRoundTripTime

```
public long getPingRoundTripTime()
```

Get turn around time (milliseconds) of last ping request

Returns:

time (milliseconds)

getDateStarted

```
public String getDateStarted()
```

Get date and time of client connection

Returns:

date and time of connection

getTimeRunning

```
public String getTimeRunning()
```

Get elapsed time of connection

Returns:

elapsed time of connection

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

Returns:

time running in seconds

getStreamFile

```
public java.io.File getStreamFile(String streamName)
```

Get File object for stream with given name. Assumes file extension is .flv.

Parameters:

streamName - stream name

Returns:

file

getStreamFile

```
public java.io.File getStreamFile(String streamName,  
    String streamExt)
```

(continued from last page)

Get File object for stream with given name and extension. For example test.flv would be `getStreamFile("test", "flv");`

Get File Descriptor

```
IClient client;
File file = client.getStreamFile("test", "flv");
WMSLogger log = WMSLoggerFactory.getLogger(null);
if (file != null)
{
    if (file.exists())
        log.debug("getStreamFile: " + file.getPath());
}
```

Parameters:

streamName - stream name
streamExt - stream extension

Returns:

file

getStreamFile

```
public java.io.File getStreamFile(String streamName,
    String streamExt,
    boolean doCreateFolder)
```

Get File object for stream with given name and extension. If doCreateFolder is true, create folder necessary to make path exist. For example test.flv would be `getStreamFile("test", "flv");`

Parameters:

streamName - stream name
streamExt - stream extension
doCreateFolder - create folders if needed

Returns:

file

getBufferTime

```
public int getBufferTime()
```

Get default buffer time for newly created mediaStream objects

Returns:

default buffer time (milliseconds)

setBufferTime

```
public void setBufferTime(int bufferTime)
```

(continued from last page)

Set default buffer time for newly created mediaStream objects

Parameters:

bufferTime - bufer time (milliseconds)

getResponseAMFObj

```
public AMFObj getResponseAMFObj(int index)
```

Get the response channel AMFObj for channel index.

Parameters:

index - channel index

Returns:

AMFObj

getRespAMFAudioObj

```
public AMFObj getRespAMFAudioObj(IMediaStream stream)
```

Get the audio response AMFObj for a given mediaStream

Parameters:

stream - mediaStream

Returns:

response channel AMFObj

getRespAMFVideoObj

```
public AMFObj getRespAMFVideoObj(IMediaStream stream)
```

Get the video response AMFObj for a given mediaStream

Parameters:

stream - mediaStream

Returns:

response channel AMFObj

getRespAMFDataObj

```
public AMFObj getRespAMFDataObj(IMediaStream stream)
```

Get the data response AMFObj for a given mediaStream

Parameters:

stream - mediaStream

Returns:

response channel AMFObj

getQueryStr

```
public String getQueryStr()
```

(continued from last page)

Get the query string part of the connection string. If the connection string where:
rtmp://localhost/app/appInst?data1=myData1&data2=myData2, then query string would be
data1=myData1&data2=myData2

Returns:query string

getReferrer

```
public String getReferrer()
```

Get the referrer data for this connection. The referrer in Wowza Media Server terms is the full url to the Flash movie that connected to the server. Checking referre upon connection is a great way to secure server connections and only allow your Flash movies to connect to the server.

Only Allow Your .swf Files to Connect to Wowza Pro server

```
public class MyModule extends ModuleBase
{
    static public void onConnect(IClient client, RequestFunction function,
        AMFDataList params)
    {
        String referrer = client.getReferrer();

        if (referrer.indexOf("www.mycompany.com") >= 0 &&
            referrer.indexOf("mycoolflash.swf") >= 0)
            client.acceptConnection("valid referrer");
        else
            client.rejectConnection("invalid referrer: "+referrer);
    }
}
```

Returns:referrer

getPageUrl

```
public String getPageUrl()
```

Get the pageUrl for this connection.

Returns:pageUrl for this connection

getUri

```
public String getUri()
```

Get the full URI of the connection string

(continued from last page)

Returns:

URI of connection string

getProtocol

```
public int getProtocol()
```

Get connection protocol (1 = RTMP, 3 = RTMPT)

Returns:

connection protocol (1 = RTMP, 3 = RTMPT)

getServerHostPort

```
public HostPort getServerHostPort()
```

Get the hostPort object for the connection that is servicing this client

Returns:

vHost hostPort servicing request

isSecure

```
public boolean isSecure()
```

Is this connection protected by either SSL or encryption (RTMPE, RTMPTE, RTMPS)

Returns:

is connection protected by either SSL or encryption (RTMPE, RTMPTE, RTMPS)

isSSL

```
public boolean isSSL()
```

Is this connection SSL (RTMPS)

Returns:

is connection (RTMPS)

isEncrypted

```
public boolean isEncrypted()
```

Is this connection encrypted (RTMPE or RTMPTE)

Returns:

is connection encrypted (RTMPE or RTMPTE)

getIdleFrequency

```
public int getIdleFrequency()
```

Get client idle frequency (milliseconds)

Returns:

client idle frequency (milliseconds)

setIdleFrequency

```
public void setIdleFrequency(int idleFrequency)
```

Set client idle frequency (milliseconds)

Parameters:

idleFrequency - client idle frequency (milliseconds)

getSharedObjectReadAccess

```
public String getSharedObjectReadAccess()
```

Get the shared object read access value. see setSharedObjectReadAccess for more information.

Returns:

shared object read access value

setSharedObjectReadAccess

```
public void setSharedObjectReadAccess(String sharedObjectReadAccess)
```

Set the shared object read access value. This list is a semi-colon delimited list of shared objects that this client has access to. By default the value is set to IClient.READ_ACCESS_ALL which indicates this client can read all shared objects. If you want to disable read access to all shared objects set this value to IClient.READ_ACCESS_NONE. If this value is set to anything other than IClient.READ_ACCESS_ALL or IClient.READ_ACCESS_NONE then each item in the semi-color delimited list is compared against incoming shared object read requests. If any item in the list completely matches the shared object name or the start of the shared object name, then access is allowed. For example, if the sharedObjectReadAccess list is set to "testa/testb;testc" then the following requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

Parameters:

sharedObjectReadAccess - shared object read access value

getSharedObjectWriteAccess

```
public String getSharedObjectWriteAccess()
```

Get the shared object write access value. see setSharedObjectWriteAccess for more information.

Returns:

shared object write access value

setSharedObjectWriteAccess

```
public void setSharedObjectWriteAccess(String sharedObjectWriteAccess)
```

(continued from last page)

Set the shared object write access value. This list is a semi-colon delimited list of shared objects that this client has access to. By default the value is set to IClient.WRITE_ACCESS_ALL which indicates this client can write all shared objects. If you want to disable write access to all shared objects set this value to IClient.WRITE_ACCESS_NONE. If this value is set to anything other than IClient.WRITE_ACCESS_ALL or IClient.WRITE_ACCESS_NONE then each item in the semi-color delimited list is compared against incoming shared object write requests. If any item in the list completely matches the shared object name or the start of the shared object name, then access is allowed. For example, if the sharedObjectWriteAccess list is set to "testa/testb;testc" then the following requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

Parameters:

sharedObjectWriteAccess

getStreamVideoSampleAccess

```
public String getStreamVideoSampleAccess()
```

Get the video sample access value. see setVideoStreamAccess for more information.

Returns:

video sample access

setStreamVideoSampleAccess

```
public void setStreamVideoSampleAccess(String videoSampleAccess)
```

Set the stream video sample access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.VIDEOSTREAM_ACCESS_NONE which indicates this client can access no stream data client side. If you want to enable access to all stream names set this value to IClient.VIDEOSTREAM_ACCESS_ALL. If this value is set to anything other than IClient.VIDEOSTREAM_ACCESS_ALL or IClient.VIDEOSTREAM_ACCESS_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamVideoSampleAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

Parameters:

videoSampleAccess

getStreamAudioSampleAccess

```
public String getStreamAudioSampleAccess()
```

Get the audio sample access value. see setVideoStreamAccess for more information.

Returns:

(continued from last page)

audio sample access

setStreamAudioSampleAccess

```
public void setStreamAudioSampleAccess(String audioSampleAccess)
```

Set the stream audio sample access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.AUDIOSTREAM_ACCESS_NONE which indicates this client can access no stream data client side. If you want to enable access to all stream names set this value to IClient.AUDIOSTREAM_ACCESS_ALL. If this value is set to anything other than IClient.AUDIOSTREAM_ACCESS_ALL or IClient.AUDIOSTREAM_ACCESS_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamAudioSampleAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

Parameters:

audioSampleAccess

getStreamReadAccess

```
public String getStreamReadAccess()
```

Get the stream read access value. see setStreamReadAccess for more information.

Returns:

stream read access value

setStreamReadAccess

```
public void setStreamReadAccess(String streamReadAccess)
```

Set the stream object read access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to IClient.READ_ACCESS_ALL which indicates this client can play all streams. If you want to disable read access to all stream names set this value to IClient.READ_ACCESS_NONE. If this value is set to anything other than IClient.READ_ACCESS_ALL or IClient.READ_ACCESS_NONE then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the streamReadAccess list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

Parameters:

streamReadAccess - shared object read access value

getStreamWriteAccess

```
public String getStreamWriteAccess()
```

Get the stream write access value. see `setStreamWriteAccess` for more information.

Returns:

stream write access value

setStreamWriteAccess

```
public void setStreamWriteAccess(String streamWriteAccess)
```

Set the stream object write access value. This list is a semi-colon delimited list of stream names that this client has access to. By default the value is set to `IClient.WRITE_ACCESS_ALL` which indicates this client can play all streams. If you want to disable write access to all stream names set this value to `IClient.WRITE_ACCESS_NONE`. If this value is set to anything other than `IClient.WRITE_ACCESS_ALL` or `IClient.WRITE_ACCESS_NONE` then each item in the semi-color delimited list is compared against incoming stream play requests. If any item in the list completely matches the stream name or the start of the stream name, then access is allowed. For example, if the `streamWriteAccess` list is set to "testa/testb;testc" then the following play requests would be granted the following access:

- testc: Granted Access
- testc/test: Granted Access
- testC/test: Denied Access (incorrect case)
- testa/testb: Granted Access
- testa/testb123: Granted Access
- testa/testb/file123: Granted Access
- testa/test: Denied Access (incomplete match)

Values in this list are always case sensitive.

Parameters:

`streamWriteAccess` - shared object read access value

getWriteListener

```
public ClientWriteListener getWriteListener()
```

Object that tracks write operations

Returns:

Object that tracks write operations

addAcceptConnectionAttribute

```
public void addAcceptConnectionAttribute(String key,  
    AMFDataObj item)
```

Add and attribute to the `resultObj` that gets passed back to the client on successful connection

Parameters:

`key` - key
`item` - item to add

addAcceptConnectionAttribute

```
public void addAcceptConnectionAttribute(String key,  
    String item)
```

Add and attribute to the `resultObj` that gets passed back to the client on successful connection

(continued from last page)

Parameters:

key - key
item - item to add

getRepeaterOriginUrl

```
public String getRepeaterOriginUrl()
```

Get the origin URL used by the Live Stream Repeater

Returns:

URL used by the Live Stream Repeater

setRepeaterOriginUrl

```
public void setRepeaterOriginUrl(String repeaterOriginUrl)
```

Set the origin URL used by the Live Stream Repeater

Parameters:

repeaterOriginUrl - URL used by the Live Stream Repeater

getLastValidateTime

```
public long getLastValidateTime()
```

Get last time (millisecond) the connection was validated with a ping

Returns:

last time (millisecond) the connection was validated with a ping

setLastValidateTime

```
public void setLastValidateTime(long lastValidateTime)
```

Set the last time (milliseconds) the connection was validated with ping

Parameters:

lastValidateTime - last time (milliseconds) the connection was validated with ping

getPingTimeout

```
public int getPingTimeout()
```

Get the ping timeout (milliseconds)

Returns:

ping timeout (milliseconds)

isLiveRepeater

```
public boolean isLiveRepeater()
```

Returns true if this connection is from the live stream repeater

Returns:

true if this connection is from the live stream repeater

isFlashVersionH264Capable

```
public boolean isFlashVersionH264Capable()
```

Returns true if the connected client is capable of playing H.264 video (Flash player 9.0.45.x or greater)

Returns:

returns true if the connected client is capable of playing H.264 video (Flash player 9.0.45.x or greater)

isFlashVersion90115

```
public boolean isFlashVersion90115()
```

Returns true if the Flash version is equal or greater than 9.0.115.x

Returns:

returns true if the Flash version is equal or greater than 9.0.115.x

isFlashVersion10

```
public boolean isFlashVersion10()
```

Returns true if the Flash version is equal or greater than 10.x.x.x

Returns:

returns true if the Flash version is equal or greater than 10.x.x.x

isFlashMediaLiveEncoder

```
public boolean isFlashMediaLiveEncoder()
```

Returns true if this connection is the Flash Media Live Encoder

Returns:

true if this connection is the Flash Media Live Encoder

testFlashVersion

```
public int testFlashVersion(int[] version)
```

Test to see if the connected client flash version is equal to or greater than a given value. Example: int isGood = testFlashVersion({ 9, 0, 5, 12});

Parameters:

version - array of version values

Returns:

1 if greater, 0 if equal, -1 if less then

isObjectEncodingAMF3

```
public boolean isObjectEncodingAMF3()
```

Is the object encoding for this client AMF3

Returns:

true of the object encoding for this client is AMF3

isObjectEncodingAMF0

```
public boolean isObjectEncodingAMF0()
```

Is the object encoding for this client AMF0

Returns:

true of the object encoding for this client is AMF0

setObjectEncoding

```
public void setObjectEncoding(int objectEncoding)
```

Set the object encoding level

Parameters:

objectEncoding - object encoding level

getObjectEncoding

```
public int getObjectEncoding()
```

Get the object encoding level

Returns:

object encoding level

setAcceptConnectionObj

```
public void setAcceptConnectionObj(AMFData acceptConnectionObj)
```

Call this method from onConnect to add an "application" property to the info object that is passed back to the Flash client in the onStatus handler.

Parameters:

acceptConnectionObj - connection object

setAcceptConnectionDescription

```
public void setAcceptConnectionDescription(String description)
```

Call this method from onConnect to set the info.description property returned in NetConnection onStatus handler

Parameters:

description - description

setAcceptConnectionExObj

```
public void setAcceptConnectionExObj(AMFDataObj acceptConnectionExObj)
```

Call this method from onConnect to set the info.ex property returned in NetConnection onStatus handler

Parameters:

acceptConnectionExObj - exObj AMFData item return in info.ex property of NetConnection onStatus handler

(continued from last page)

getRTPStream

```
public RTPStream getRTPStream( )
```

If this client was created due to an RTP connection to the server return the underlying RTPStream object

Returns:

underlying RTPStream object

setAcceptConnection

```
public void setAcceptConnection(boolean acceptConnection)
```

Set the default for accept connection

Parameters:

acceptConnection - default for accept connection

setShutdownClient

```
public void setShutdownClient(boolean shutdownClient)
```

Gracefully and forcefully shutdown a client.

Parameters:

shutdownClient - set to true to gracefully and forcefully shutdown a client

reparentClient

```
public void reparentClient(IVHost vhost)
```

Move a client object to a new vhost. This can only be done right after the handshake process has completed. See [IVHostNotify.onVHostClientConnect](#).

Parameters:

vhost - new vhost

getMaximumSetBufferTime

```
public int getMaximumSetBufferTime( )
```

Get maximum number of milliseconds allowed for the [NetStream.setBufferTime\(secs\)](#) call. If set to zero this feature is turned off.

Returns:

maximum number of milliseconds allowed for the [NetStream.setBufferTime\(secs\)](#) call

getMaximumPendingWriteBytes

```
public int getMaximumPendingWriteBytes( )
```

Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

Returns:

maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

(continued from last page)

getLiveStreamPacketizerList

```
public String getLiveStreamPacketizerList()
```

Get the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)

Returns:

comma separated list of LiveStreamPacketizers names

setLiveStreamPacketizerList

```
public void setLiveStreamPacketizerList(String liveStreamPacketizerList)
```

Set the comma separated list of LiveStreamPacketizers names being used by this client (see conf/LiveStreamPacketizers.xml)

Parameters:

liveStreamPacketizerList - comma separated list of LiveStreamPacketizers names

getLiveStreamTranscoderList

```
public String getLiveStreamTranscoderList()
```

Get the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)

Returns:

comma separated list of LiveStreamTranscoders names

setLiveStreamTranscoderList

```
public void setLiveStreamTranscoderList(String liveStreamTranscoderList)
```

Set the comma separated list of LiveStreamTranscoders names being used by this client (see conf/LiveStreamTranscoders.xml)

Parameters:

liveStreamTranscoderList - comma separated list of LiveStreamTranscoders names

getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get elapsed time client has been connected.

Returns:

elapsed time client has been connected.

getLiveRepeaterCapabilities

```
public int getLiveRepeaterCapabilities()
```

Get the live repeater capabilities of this connection

Returns:

live repeater capabilities of this connection

setLiveRepeaterCapabilities

```
public void setLiveRepeaterCapabilities(int liveRepeaterCapabilities)
```

(continued from last page)

Set the live repeater capabilities of this connection

Parameters:

liveRepeaterCapabilities - live repeater capabilities of this connection

fcSubscribe

```
public void fcSubscribe(String streamName)
```

Subscribe to a live stream (for live stream repeater to start start from edge to origin)

Parameters:

streamName - stream name

fcSubscribe

```
public void fcSubscribe(String streamName,  
    String mediaCasterType)
```

Subscribe to a live stream (use a particular mediaCasterType)

Parameters:

streamName - stream name

mediaCasterType - media caster type name

fcUnSubscribeAll

```
public void fcUnSubscribeAll()
```

UnSubscribe to all streams that this client is current subscribed to

fcUnSubscribe

```
public void fcUnSubscribe(String streamName)
```

UnSubscribe from a stream

Parameters:

streamName - stream name

isValidateFMLEConnections

```
public boolean isValidateFMLEConnections()
```

Returns true if validating FMLE connection (default is false)

Returns:

true if validating FMLE connection

setValidateFMLEConnections

```
public void setValidateFMLEConnections(boolean validateFMLEConnections)
```

Returns true if validating FMLE connection (default is false)

Parameters:

validateFMLEConnections - true if validating FMLE connection

(continued from last page)

setThreadContext

```
public void setThreadContext( )
```

Set the thread logging context to this client

com.wowza.wms.client Interface IClientNotify

public interface **IClientNotify**
extends

IClientNotify: listener interface used by [IApplicationInstance.addClientListener\(IClientNotify\)](#)

See Also:

[IApplicationInstance.addClientListener\(IClientNotify\)](#)

Method Summary

void	onClientAccept (IClient client) Triggered when client connection accepted
void	onClientConnect (IClient client) Triggered when client attempt connection
void	onClientDisconnect (IClient client) Triggered when client disconnected
void	onClientReject (IClient client) Triggered when client connection rejected

Methods

onClientConnect

public void **onClientConnect**([IClient](#) client)

Triggered when client attempt connection

Parameters:

client - client

onClientDisconnect

public void **onClientDisconnect**([IClient](#) client)

Triggered when client disconnected

Parameters:

client - client

onClientAccept

public void **onClientAccept**([IClient](#) client)

Triggered when client connection accepted

Parameters:

client - client

onClientReject

```
public void onClientReject(IClient client)
```

Triggered when client connection rejected

Parameters:

client - client

com.wowza.wms.client Interface IConnectionNotify

public interface **IConnectionNotify**
extends

IConnectionNotify: internal class to manage connection counting

Method Summary

void	onAcceptConnection (ConnectionCounter connectionCounter, ConnectionHolder connectionHolder, java.util.Date date, long stamp) Triggered when client connection accepted
void	onDisconnect (ConnectionCounter connectionCounter, ConnectionHolder connectionHolder, boolean isValid, java.util.Date date, long stamp) Triggered when client disconnected
void	onRejectConnection (ConnectionCounter connectionCounter, ConnectionHolder connectionHolder, int reason, java.util.Date date, long stamp) Triggered when client connection rejected

Methods

onAcceptConnection

```
public void onAcceptConnection(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    java.util.Date date,  
    long stamp)
```

Triggered when client connection accepted

Parameters:

connectionCounter
connectionHolder
date
stamp

onRejectConnection

```
public void onRejectConnection(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    int reason,  
    java.util.Date date,  
    long stamp)
```

Triggered when client connection rejected

Parameters:

connectionCounter
connectionHolder
reason

(continued from last page)

date
stamp

onDisconnect

```
public void onDisconnect(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    boolean isValid,  
    java.util.Date date,  
    long stamp)
```

Triggered when client disconnected

Parameters:

connectionCounter
connectionHolder
isValid
date
stamp

com.wowza.wms.client Interface IConnectionValidator

public interface **IConnectionValidator**
extends

IConnectionValidator: callback for validating connections

Method Summary

boolean	validateConnection (ConnectionCounter connectionCounter, ConnectionHolder connectionHolder, byte[] license) Triggered on connection
---------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

validateConnection

```
public boolean validateConnection(ConnectionCounter connectionCounter,  
    ConnectionHolder connectionHolder,  
    byte[] license)
```

Triggered on connection

Parameters:

connectionCounter - connection counter
connectionHolder - connection holder

Returns:

isValid

com.wowza.wms.client Interface ILicenseNotify

public interface **ILicenseNotify**
extends

Method Summary

void	<code>onAcceptLicense</code> (LicenseCounter licenseCounter, LicenseHolder licenseHolder, java.util.Date date, long stamp) Triggered when license accepted
void	<code>onDisconnect</code> (LicenseCounter licenseCounter, LicenseHolder licenseHolder, boolean isValid, java.util.Date date, long stamp) Triggered when client disconnected
void	<code>onRejectLicense</code> (LicenseCounter licenseCounter, LicenseHolder licenseHolder, int reason, java.util.Date date, long stamp) Triggered when license rejected

Methods

onAcceptLicense

```
public void onAcceptLicense(LicenseCounter licenseCounter,  
    LicenseHolder licenseHolder,  
    java.util.Date date,  
    long stamp)
```

Triggered when license accepted

Parameters:

licenseCounter
licenseHolder
date
stamp

onRejectLicense

```
public void onRejectLicense(LicenseCounter licenseCounter,  
    LicenseHolder licenseHolder,  
    int reason,  
    java.util.Date date,  
    long stamp)
```

Triggered when license rejected

Parameters:

licenseCounter
licenseHolder
reason
date
stamp

onDisconnect

```
public void onDisconnect(LicenseCounter licenseCounter,  
    LicenseHolder licenseHolder,  
    boolean isValid,  
    java.util.Date date,  
    long stamp)
```

Triggered when client disconnected

Parameters:

- licenseCounter
- licenseHolder
- isValid
- date
- stamp

com.wowza.wms.client Interface ILicenseValidator

public interface **ILicenseValidator**
extends

Method Summary

boolean	validateLicense (LicenseCounter licenseCounter, LicenseHolder licenseHolder, byte[] license)
---------	--------------------------------------------------------------------------------------------------------------

Methods

validateLicense

```
public boolean validateLicense(LicenseCounter licenseCounter,  
    LicenseHolder licenseHolder,  
    byte[] license)
```

Package

com.wowza.wms.dvr

com.wowza.wms.dvr

Class DefaultDvrStreamVersionHandler

java.lang.Object

└─com.wowza.wms.dvr.DefaultDvrStreamVersionHandler

All Implemented Interfaces:

[IDvrStreamVersionHandler](#)

public class **DefaultDvrStreamVersionHandler**
 extends Object
 implements [IDvrStreamVersionHandler](#)

Default stream Version Handler. May be sub-classed

Constructor Summary

public	DefaultDvrStreamVersionHandler()
--------	--------------------------------------------------

Method Summary

IDvrStreamStore	determineExistingStoreForPlaying (IDvrStreamManager dvrMgr, String baseStreamName)
IDvrStreamStore	determineExistingStoreForRecording (IDvrStreamManager dvrMgr, String baseStreamName)
String	getArchiveStrategy (IDvrStreamManager dvrMgr, String baseStreamName)
boolean	handleArchivedStream (IDvrStreamManager dvrMgr, String baseStreamName, String vStreamName, java.util.SortedSet versions, DvrManifestHolder manifestHolder)
boolean	shouldDeleteArchivedStream (IDvrStreamManager dvrMgr, IDvrStreamStore store)
boolean	shouldLoadArchivedStream (IDvrStreamManager dvrMgr, String baseStreamName, String vStreamName, java.util.SortedSet versions, DvrManifestHolder manifest)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.dvr.IDvrStreamVersionHandler](#)

[determineExistingStoreForPlaying](#), [determineExistingStoreForRecording](#), [getArchiveStrategy](#), [handleArchivedStream](#), [shouldDeleteArchivedStream](#), [shouldLoadArchivedStream](#)

Constructors

DefaultDvrStreamVersionHandler

```
public DefaultDvrStreamVersionHandler()
```

Methods

getArchiveStrategy

```
public String getArchiveStrategy(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

determineExistingStoreForRecording

```
public IDvrStreamStore determineExistingStoreForRecording(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

determineExistingStoreForPlaying

```
public IDvrStreamStore determineExistingStoreForPlaying(IDvrStreamManager dvrMgr,  
    String baseStreamName)
```

handleArchivedStream

```
public boolean handleArchivedStream(IDvrStreamManager dvrMgr,  
    String baseStreamName,  
    String vStreamName,  
    java.util.SortedSet versions,  
    DvrManifestHolder manifestHolder)
```

shouldLoadArchivedStream

```
public boolean shouldLoadArchivedStream(IDvrStreamManager dvrMgr,  
    String baseStreamName,  
    String vStreamName,  
    java.util.SortedSet versions,  
    DvrManifestHolder manifest)
```


shouldDeleteArchivedStream

```
public boolean shouldDeleteArchivedStream(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

com.wowza.wms.dvr

Class DvrManifestChunkEntry

java.lang.Object



public class **DvrManifestChunkEntry**
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains an associated chunk.

Field Summary

protected	artifact
protected	encryptions

Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[index](#), [MANIFESTFILE_KEY_ARTIFACT](#), [MANIFESTFILE_KEY_AUDIO_CODEC](#), [MANIFESTFILE_KEY_DVRTIME](#), [MANIFESTFILE_KEY_ENCRYPTIONS](#), [MANIFESTFILE_KEY_INDEX](#), [MANIFESTFILE_KEY_METADATA](#), [MANIFESTFILE_KEY_NAME](#), [MANIFESTFILE_KEY_PACKETTIME](#), [MANIFESTFILE_KEY_PACKETTIME90](#), [MANIFESTFILE_KEY_SIZE](#), [MANIFESTFILE_KEY_START](#), [MANIFESTFILE_KEY_STOP](#), [MANIFESTFILE_KEY_TYPE](#), [MANIFESTFILE_KEY_UTCTIME](#), [MANIFESTFILE_KEY_VIDEO_CODEC](#), [start](#), [stop](#), [type](#)

Constructor Summary

public	DvrManifestChunkEntry (int type, int index, long start, long stop, DvrChunkArtifact artifact) Constructor
public	DvrManifestChunkEntry (int type, int index, long start, long stop, DvrChunkArtifact artifact, DvrEncryptionInfoHolder encryptions) Constructor

Method Summary

String	getArtifactsTextRepresentation ()
DvrChunkArtifact	getDvrArtifact () Get DVR artifact reference.
DvrEncryptionInfoHolder	getEncryptions () Get associated encryptions.
String	getEncryptionsTextRepresentation ()
String	getManifestRepresentation ()

void	<u>serialize</u> (java.io.DataOutputStream out)
void	<u>setEncryptions</u> (DvrEncryptionInfoHolder encryptions) Set associated encryptions.
String	<u>toString</u> ()

Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#),
[getManifestRepresentation](#), [getStartTimecode](#), [getStopTimecode](#), [getType](#), [serialize](#),
[serialize](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

Fields

artifact

protected com.wowza.wms.dvr.DvrChunkArtifact **artifact**

encryptions

protected com.wowza.wms.dvr.DvrEncryptionInfoHolder **encryptions**

Constructors

DvrManifestChunkEntry

```
public DvrManifestChunkEntry(int type,
                             int index,
                             long start,
                             long stop,
                             DvrChunkArtifact artifact)
```

Constructor

Parameters:

type - type
index - manifest index
start - start time (ms in DVR time scale)
stop - stop time (ms in DVR time scale)
artifact - reference to the chunk artifact

(continued from last page)

DvrManifestChunkEntry

```
public DvrManifestChunkEntry(int type,
                             int index,
                             long start,
                             long stop,
                             DvrChunkArtifact artifact,
                             DvrEncryptionInfoHolder encryptions)
```

Constructor

Parameters:

type - type
index - manifest index
start - start time (ms in DVR time scale)
stop - stop time (ms in DVR time scale)
artifact - reference to the chunk artifact
encryptions - associated encryptions

Methods

getDvrArtifact

```
public DvrChunkArtifact getDvrArtifact()
```

Get DVR artifact reference.

Returns:

DVR artifact reference.

setEncryptions

```
public void setEncryptions(DvrEncryptionInfoHolder encryptions)
```

Set associated encryptions.

Parameters:

encryptions - encryptions

getEncryptions

```
public DvrEncryptionInfoHolder getEncryptions()
```

Get associated encryptions.

Returns:

encryptions

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

getManifestRepresentation

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

getEncryptionsTextRepresentation

protected String **getEncryptionsTextRepresentation()**

getArtifactsTextRepresentation

protected String **getArtifactsTextRepresentation()**


toString

public String **toString()**

com.wowza.wms.dvr

Class DvrManifestCodecEntry

java.lang.Object



public class **DvrManifestCodecEntry**
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains codec information

Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[index](#), [MANIFESTFILE_KEY_ARTIFACT](#), [MANIFESTFILE_KEY_AUDIO_CODEC](#), [MANIFESTFILE_KEY_DVRTIME](#), [MANIFESTFILE_KEY_ENCRYPTIONS](#), [MANIFESTFILE_KEY_INDEX](#), [MANIFESTFILE_KEY_METADATA](#), [MANIFESTFILE_KEY_NAME](#), [MANIFESTFILE_KEY_PACKETTIME](#), [MANIFESTFILE_KEY_PACKETTIME90](#), [MANIFESTFILE_KEY_SIZE](#), [MANIFESTFILE_KEY_START](#), [MANIFESTFILE_KEY_STOP](#), [MANIFESTFILE_KEY_TYPE](#), [MANIFESTFILE_KEY_UTCTIME](#), [MANIFESTFILE_KEY_VIDEO_CODEC](#), [start](#), [stop](#), [type](#)

Constructor Summary

public	DvrManifestCodecEntry (int index, long start, com.wowza.wms.media.model.MediaCodecInfoAudio audioCodec, com.wowza.wms.media.model.MediaCodecInfoVideo videoCodec) Constructor
--------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Method Summary

com.wowza.wms.media.model.MediaCodecInfoAudio	getAudioCodec () Get audio codec information
String	getManifestRepresentation ()
com.wowza.wms.media.model.MediaCodecInfoVideo	getVideoCodec () Get video codec information
void	serialize (java.io.DataOutputStream out)
String	toString ()

Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#), [getManifestRepresentation](#), [getStartTimecode](#), [getStopTimecode](#), [getType](#), [serialize](#), [serialize](#)

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructors

DvrManifestCodecEntry

```
public DvrManifestCodecEntry(int index,
                             long start,
                             com.wowza.wms.media.model.MediaCodecInfoAudio audioCodec,
                             com.wowza.wms.media.model.MediaCodecInfoVideo videoCodec)
```

Constructor

Parameters:

index - manifest index
start - start time (ms in DVR time scale)
audioCodec - audio codec info
videoCodec - video codec info

Methods

getVideoCodec

```
public com.wowza.wms.media.model.MediaCodecInfoVideo getVideoCodec()
```

Get video codec information

Returns:

video codec information

getAudioCodec

```
public com.wowza.wms.media.model.MediaCodecInfoAudio getAudioCodec()
```

Get audio codec information

Returns:

audio codec information

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

getManifestRepresentation

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

toString

```
public String toString()
```

(continued from last page)

com.wowza.wms.dvr

Class DvrManifestEntry

java.lang.Object

└─com.wowza.wms.dvr.DvrManifestEntry

Direct Known Subclasses:

[DvrManifestTimeMapEntry](#), [DvrManifestOnMetadataEntry](#), [DvrManifestCodecEntry](#), [DvrManifestChunkEntry](#)

public abstract class **DvrManifestEntry**
extends Object

Abstract class representing entry in DVR manifest.

Field Summary

protected	index
public static final	MANIFESTFILE_KEY_ARTIFACT Value: artifact
public static final	MANIFESTFILE_KEY_AUDIO_CODEC Value: aCodec
public static final	MANIFESTFILE_KEY_DVRTIME Value: dvrTime
public static final	MANIFESTFILE_KEY_ENCRYPTIONS Value: enc
public static final	MANIFESTFILE_KEY_INDEX Value: index
public static final	MANIFESTFILE_KEY_METADATA Value: metadata
public static final	MANIFESTFILE_KEY_NAME Value: name
public static final	MANIFESTFILE_KEY_PACKETTIME Value: packetTime
public static final	MANIFESTFILE_KEY_PACKETTIME90 Value: packetTime90
public static final	MANIFESTFILE_KEY_SIZE Value: size

public static final	MANIFESTFILE_KEY_START Value: start
public static final	MANIFESTFILE_KEY_STOP Value: stop
public static final	MANIFESTFILE_KEY_TYPE Value: type
public static final	MANIFESTFILE_KEY_UTCTIME Value: utcTime
public static final	MANIFESTFILE_KEY_VIDEO_CODEC Value: vCodec
protected	start
protected	stop
protected	type

Constructor Summary

public	DvrManifestEntry (int type, int index, long start, long stop) Constructor Valid types include: IVHost.CONTENTTYPE_AUDIO , IVHost.CONTENTTYPE_VIDEO , IVHost.CONTENTTYPE_DATA , IDvrManifest.ON_METADATA_TYPE , IDvrManifest.CODEC_TYPE , or IDvrManifest.TIME_MAP_TYPE
--------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Method Summary

String	encodeBytes (byte[] bytes) Encode string of bytes as Base64.
String	getCommonInitialTextRepString ()
long	getDuration () Get duration
int	getIndex () Get manifest index.
abstract String	getManifestRepresentation () Get textual representation of record for textual manifest usage.
long	getStartTimecode () Get start timecode.
long	getStopTimecode () Get stop timecode.
int	getType () Get type of manifest record.

byte[]	<code>serialize()</code> Serialize manifest record.
abstract void	<code>serialize(java.io.DataOutputStream out)</code> Serialize manifest record.

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

MANIFESTFILE_KEY_INDEX

```
public static final java.lang.String MANIFESTFILE_KEY_INDEX
```

Constant value: **index**

MANIFESTFILE_KEY_TYPE

```
public static final java.lang.String MANIFESTFILE_KEY_TYPE
```

Constant value: **type**

MANIFESTFILE_KEY_START

```
public static final java.lang.String MANIFESTFILE_KEY_START
```

Constant value: **start**

MANIFESTFILE_KEY_STOP

```
public static final java.lang.String MANIFESTFILE_KEY_STOP
```

Constant value: **stop**

MANIFESTFILE_KEY_SIZE

```
public static final java.lang.String MANIFESTFILE_KEY_SIZE
```

Constant value: **size**

MANIFESTFILE_KEY_ARTIFACT

```
public static final java.lang.String MANIFESTFILE_KEY_ARTIFACT
```

Constant value: **artifact**

(continued from last page)

MANIFESTFILE_KEY_DVRTIME

```
public static final java.lang.String MANIFESTFILE_KEY_DVRTIME
```

Constant value: **dvrTime**

MANIFESTFILE_KEY_PACKETTIME

```
public static final java.lang.String MANIFESTFILE_KEY_PACKETTIME
```

Constant value: **packetTime**

MANIFESTFILE_KEY_PACKETTIME90

```
public static final java.lang.String MANIFESTFILE_KEY_PACKETTIME90
```

Constant value: **packetTime90**

MANIFESTFILE_KEY_UTCTIME

```
public static final java.lang.String MANIFESTFILE_KEY_UTCTIME
```

Constant value: **utcTime**

MANIFESTFILE_KEY_NAME

```
public static final java.lang.String MANIFESTFILE_KEY_NAME
```

Constant value: **name**

MANIFESTFILE_KEY_AUDIO_CODEC

```
public static final java.lang.String MANIFESTFILE_KEY_AUDIO_CODEC
```

Constant value: **aCodec**

MANIFESTFILE_KEY_VIDEO_CODEC

```
public static final java.lang.String MANIFESTFILE_KEY_VIDEO_CODEC
```

Constant value: **vCodec**

MANIFESTFILE_KEY_ENCRYPTIONS

```
public static final java.lang.String MANIFESTFILE_KEY_ENCRYPTIONS
```

Constant value: **enc**

MANIFESTFILE_KEY_METADATA

```
public static final java.lang.String MANIFESTFILE_KEY_METADATA
```

(continued from last page)

Constant value: **metadata**

startprotected long **start**

stopprotected long **stop**

indexprotected int **index**

typeprotected int **type**

Constructors

DvrManifestEntry

```
public DvrManifestEntry(int type,  
                        int index,  
                        long start,  
                        long stop)
```

Constructor Valid types include: [IVHost.CONTENTTYPE_AUDIO](#), [IVHost.CONTENTTYPE_VIDEO](#), [IVHost.CONTENTTYPE_DATA](#), [IDvrManifest.ON_METADATA_TYPE](#), [IDvrManifest.CODEC_TYPE](#), or [IDvrManifest.TIME_MAP_TYPE](#)

Parameters:

type - type
index - manifest index
start - start time (ms in DVR time scale)
stop - stop time (ms in DVR time scale)

Methods

getStartTimecode

```
public long getStartTimecode()
```

Get start timecode. In millisecnds, DVR time base.

Returns:

start time

(continued from last page)

getStopTimecode

```
public long getStopTimecode()
```

Get stop timecode. In millisecnds, DVR time base.

Returns:

stop time

getDuration

```
public long getDuration()
```

Get duration

Returns:

duration in ms

getType

```
public int getType()
```

Get type of manifest record. Valid types include: [IVHost.CONTENTTYPE_AUDIO](#), [IVHost.CONTENTTYPE_VIDEO](#), [IVHost.CONTENTTYPE_DATA](#), [IDvrManifest.ON_METADATA_TYPE](#), [IDvrManifest.CODEC_TYPE](#), or [IDvrManifest.TIME_MAP_TYPE](#)

Returns:

type

getIndex

```
public int getIndex()
```

Get manifest index.

Returns:

index

serialize

```
public abstract void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

Parameters:

out - output stream

serialize

```
public byte[] serialize()
```

Serialize manifest record.

Returns:

serialized data

(continued from last page)

getManifestRepresentation

```
public abstract String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

Returns:

textual representation of entry

getCommonInitialTextRepString

```
protected String getCommonInitialTextRepString()
```

encodeBytes

```
protected String encodeBytes(byte[] bytes)
```

Encode string of bytes as Base64. Provides check for null buffer or empty buffer.

Parameters:

bytes - buffer to encode.

Returns:

Base64 encoding or "".

com.wowza.wms.dvr

Class DvrManifestEntryFactory



public class **DvrManifestEntryFactory**
extends Object

Deserialize manifest entry blobs.

Constructor Summary

public	DvrManifestEntryFactory()
--------	-------------------------------------------

Method Summary

static DvrManifestEntry	deserialize (byte[] data)
static DvrManifestEntry	deserialize (java.nio.ByteBuffer buffer)

Methods inherited from class java.lang.Object
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

DvrManifestEntryFactory
public **DvrManifestEntryFactory**()

Methods

deserialize
public static [DvrManifestEntry](#) **deserialize**(byte[] data)

deserialize
public static [DvrManifestEntry](#) **deserialize**(java.nio.ByteBuffer buffer)

com.wowza.wms.dvr Class DvrManifestEntryRange

java.lang.Object

└─com.wowza.wms.dvr.DvrManifestEntryRange

public class **DvrManifestEntryRange**
extends Object

Class that compactly represents a range of indices of a certain manifest type.

Method Summary

void	<u>deserialize</u> (byte[] data) Deserialize.
int	<u>getEndIndex</u> () Get end index.
IndexRange	<u>getRange</u> () Get index range.
int	<u>getStartIndex</u> () Get start index.
int	<u>getType</u> () Get range type
boolean	<u>isEmpty</u> ()
boolean	<u>isInRange</u> (int index) Is index in range.
byte[]	<u>serialize</u> () Serialize range.
void	<u>setRange</u> (IndexRange range) Set index range.
String	<u>toString</u> ()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods

getType

public int **getType**()

(continued from last page)

Get range type

Returns:
type.

getRange

```
public IndexRange getRange()
```

Get index range.

Returns:
index range

setRange

```
public void setRange(IndexRange range)
```

Set index range.

Parameters:
range - index range.

getStartIndex

```
public int getStartIndex()
```

Get start index.

Returns:
start index (or -1 if undefined)

getEndIndex

```
public int getEndIndex()
```

Get end index.

Returns:
end index (or -1 if undefined)

isInRange

```
public boolean isInRange(int index)
```

Is index in range.

Parameters:
index - index in question.

Returns:
true if part of range.

serialize

```
public byte[] serialize()
```

Serialize range.

(continued from last page)

Returns:

out buffer containing serialized range.

deserialize

```
public void deserialize(byte[] data)
```

Deserialize. Called after no-op constructor.

Parameters:

data - buffer to deserialize.

isEmpty

```
public boolean isEmpty()
```

toString

```
public String toString()
```

com.wowza.wms.dvr Class DvrManifestEntryRangeGroup

java.lang.Object

└─com.wowza.wms.dvr.DvrManifestEntryRangeGroup

```
public class DvrManifestEntryRangeGroup
    extends Object
```

A group of Manifest Ranges. The group may contain ranges of different types.

Field Summary

public	ranges
--------	------------------------

Constructor Summary

public	DvrManifestEntryRangeGroup()
--------	----------------------------------------------

Method Summary

void	addRange(DvrManifestEntryRange range) Add an index range to the group.
void	deserialize(byte[] data) Deserialize.
boolean	isEmpty() Determine if group of ranges is empty
boolean	isInRange(int type, int index) Determine if index of given type is contained in the group of ranges.
byte[]	serialize() Serialize range group
String	toString()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

ranges

```
public java.util.List ranges
```

Constructors

DvrManifestEntryRangeGroup

```
public DvrManifestEntryRangeGroup()
```

Methods

addRange

```
public void addRange(DvrManifestEntryRange range)
```

Add an index range to the group.

Parameters:

range

isInRange

```
public boolean isInRange(int type,  
                        int index)
```

Determine if index of given type is contained in the group of ranges.

Parameters:

type - range type

index - index in question

Returns:

true iof in range.

isEmpty

```
public boolean isEmpty()
```

Determine if group of ranges is empty

Returns:

true if empty

serialize

```
public byte[] serialize()
```

Serialize range group

Returns:

bytes representing range group

deserialize

```
public void deserialize(byte[] data)
```

Deserialize. Called after no-op constructor.

(continued from last page)

Parameters:

data - buffer to deserialize.


toString

```
public String toString()
```

com.wowza.wms.dvr

Class DvrManifestOnMetadataEntry

java.lang.Object



public class **DvrManifestOnMetadataEntry**
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains onMetadata information and associated onMetadata chunk.

Field Summary

protected	artifact
protected	data

Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[index](#), [MANIFESTFILE_KEY_ARTIFACT](#), [MANIFESTFILE_KEY_AUDIO_CODEC](#), [MANIFESTFILE_KEY_DVRTIME](#), [MANIFESTFILE_KEY_ENCRYPTIONS](#), [MANIFESTFILE_KEY_INDEX](#), [MANIFESTFILE_KEY_METADATA](#), [MANIFESTFILE_KEY_NAME](#), [MANIFESTFILE_KEY_PACKETTIME](#), [MANIFESTFILE_KEY_PACKETTIME90](#), [MANIFESTFILE_KEY_SIZE](#), [MANIFESTFILE_KEY_START](#), [MANIFESTFILE_KEY_STOP](#), [MANIFESTFILE_KEY_TYPE](#), [MANIFESTFILE_KEY_UTCTIME](#), [MANIFESTFILE_KEY_VIDEO_CODEC](#), [start](#), [stop](#), [type](#)

Constructor Summary

public	DvrManifestOnMetadataEntry (int index, long start, DvrChunkArtifact artifact, byte[] data) Constructor
--------	---------------------------------------------------------------------------------------------------------------------------

Method Summary

String	getArtifactsTextRepresentation ()
byte[]	getData () Get onMetadata information.
DvrChunkArtifact	getDvrArtifact ()
String	getManifestRepresentation ()
void	serialize (java.io.DataOutputStream out)
String	toString ()

Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#), [getManifestRepresentation](#), [getStartTimecode](#), [getStopTimecode](#), [getType](#), [serialize](#), [serialize](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

artifact

protected `com.wowza.wms.dvr.DvrChunkArtifact` **artifact**

data

protected byte **data**

Constructors

DvrManifestOnMetadataEntry

```
public DvrManifestOnMetadataEntry(int index,
                                   long start,
                                   DvrChunkArtifact artifact,
                                   byte[] data)
```

Constructor

Parameters:

index - manifest index
 start - start time (ms in DVR time scale)
 artifact - reference to the chunk artifact
 data - buffer of onMetadata information

Methods

getDvrArtifact

```
public DvrChunkArtifact getDvrArtifact()
```

getData

```
public byte[] getData()
```

Get onMetadata information.

Returns:

(continued from last page)

onMetadata information.

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

getManifestRepresentation

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

getArtifactsTextRepresentation

```
protected String getArtifactsTextRepresentation()
```


toString

```
public String toString()
```

com.wowza.wms.dvr

Class DvrManifestTimeMapEntry

java.lang.Object



public class **DvrManifestTimeMapEntry**
 extends [DvrManifestEntry](#)

Entry in DVR manifest that contains time map information.

Fields inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[index](#), [MANIFESTFILE_KEY_ARTIFACT](#), [MANIFESTFILE_KEY_AUDIO_CODEC](#), [MANIFESTFILE_KEY_DVRTIME](#), [MANIFESTFILE_KEY_ENCRYPTIONS](#), [MANIFESTFILE_KEY_INDEX](#), [MANIFESTFILE_KEY_METADATA](#), [MANIFESTFILE_KEY_NAME](#), [MANIFESTFILE_KEY_PACKETTIME](#), [MANIFESTFILE_KEY_PACKETTIME90](#), [MANIFESTFILE_KEY_SIZE](#), [MANIFESTFILE_KEY_START](#), [MANIFESTFILE_KEY_STOP](#), [MANIFESTFILE_KEY_TYPE](#), [MANIFESTFILE_KEY_UTCTIME](#), [MANIFESTFILE_KEY_VIDEO_CODEC](#), [start](#), [stop](#), [type](#)

Constructor Summary

public	DvrManifestTimeMapEntry (int index, long start, TimeMapRecord timeMap) Constructor
--------	-------------------------------------------------------------------------------------------------------

Method Summary

String	getManifestRepresentation ()
TimeMapRecord	getTimeMapping () Get time map record.
void	serialize (java.io.DataOutputStream out)
String	toString ()

Methods inherited from class [com.wowza.wms.dvr.DvrManifestEntry](#)

[encodeBytes](#), [getCommonInitialTextRepString](#), [getDuration](#), [getIndex](#), [getManifestRepresentation](#), [getStartTimecode](#), [getStopTimecode](#), [getType](#), [serialize](#), [serialize](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

(continued from last page)

DvrManifestTimeMapEntry

```
public DvrManifestTimeMapEntry(int index,  
                                long start,  
                                TimeMapRecord timeMap)
```

Constructor

Parameters:

index - manifest index
start - start time (ms in DVR time scale)
timeMap - time map record

Methods

getTimeMapping

```
public TimeMapRecord getTimeMapping()
```

Get time map record.

Returns:

time map record

getManifestRepresentation

```
public String getManifestRepresentation()
```

Get textual representation of record for textual manifest usage.

serialize

```
public void serialize(java.io.DataOutputStream out)
```

Serialize manifest record.

toString

```
public String toString()
```

com.wowza.wms.dvr Interface IDvrChunker

public interface **IDvrChunker**
extends

Method Summary

long	<code>calculateChunkGroupTime</code> (long dvrTime)
String	<code>determineChunkGroupIdentifier</code> (long dvrTime)
int	<code>getChunkGroupDuration</code> ()
void	<code>setChunkGroupDuration</code> (int chunkGrouping)

Methods

`getChunkGroupDuration`

public int **getChunkGroupDuration**()

`determineChunkGroupIdentifier`

public String **determineChunkGroupIdentifier**(long dvrTime)

`calculateChunkGroupTime`

public long **calculateChunkGroupTime**(long dvrTime)

`setChunkGroupDuration`

public void **setChunkGroupDuration**(int chunkGrouping)

com.wowza.wms.dvr Interface IDvrChunkMemoryCache

All Superinterfaces:

[IDvrRawChunkProvider](#)

public interface **IDvrChunkMemoryCache**

extends [IDvrRawChunkProvider](#)

Interface for managing in-memory cache of chunks. The implementor is responsible for implementing the desired algorithm for keeping DVR chunks in memory.

Method Summary

void	addToCache (DvrManifestChunkEntry entry, DvrChunk chunk) Provide in-memory cache the opportunity to add the DVR chunk to its cache.
void	init (IDvrStreamStore store) Called to initialize the in-memory cache.
DvrChunk	retrieveRawChunk (DvrManifestChunkEntry entry)

Methods inherited from interface [com.wowza.wms.dvr.IDvrRawChunkProvider](#)

[retrieveRawChunk](#)

Methods

init

public void **init**([IDvrStreamStore](#) store)

Called to initialize the in-memory cache.

Parameters:

store - The DVR stream store associated with this cache.

retrieveRawChunk

public DvrChunk **retrieveRawChunk**([DvrManifestChunkEntry](#) entry)

addToCache

public void **addToCache**([DvrManifestChunkEntry](#) entry,
DvrChunk chunk)

Provide in-memory cache the opportunity to add the DVR chunk to its cache. The implementation may choose to cache the chunk or ignore it.

Parameters:

(continued from last page)

entry - DVR manifest entry
chunk - the chunk.

com.wowza.wms.dvr Interface IDvrConstants

public interface **IDvrConstants**
extends IDvrPrivateConstants

Field Summary

public static final	DEFAULT_CHUNK_CACHE_CLASS Default value for DVR Property "dvrChunkMemoryCacheClass". Value: com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache
public static final	DEFAULT_CHUNK_GROUPING_SECONDS Default value for DVR Property "dvrChunkGroupingSeconds". Value: 600
public static final	DEFAULT_CHUNK_READER_CLASS Default value for DVR Property "dvrChunkReaderClass". Value: com.wowza.wms.dvr.impl.io.DvrFileChunkReader
public static final	DEFAULT_CHUNK_WRITER_CLASS Default value for DVR Property "dvrChunkWriterClass". Value: com.wowza.wms.dvr.impl.io.DvrFileChunkWriter
public static final	DEFAULT_DVR_ALLOWABLE_AV_PACKET_DELTA Default value for DVR Property "dvrAllowableAVPacketDelta". Value: 2000
public static final	DEFAULT_DVR_APPEND_DISCONTINUITY_DELTA Default value for DVR Property "dvrAppendDiscontinuityDelta". Value: 0
public static final	DEFAULT_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION Default value for DVR Property "dvrAudioOnlyChunkTargetDuration". Value: 2000
public static final	DEFAULT_DVR_BREAK_ON_PTS Default value for DVR Property "dvrChunkBreakOnPTS". Value: true
public static final	DEFAULT_DVR_CHUNK_DURATION_MINIMUM Default value for DVR Property "dvrChunkDurationMinimum". Value: 1500
public static final	DEFAULT_DVR_DEBUG_MAX_RAW_PACKETS Default value for DVR Property "dvrDebugMaximumRawPackets". Value: 200
public static final	DEFAULT_DVR_DEBUG_RAW_PACKETS Default value for DVR Property "dvrDebugRawPackets". Value: false

public static final	DEFAULT_DVR_MAX_CHUNK_LOG Default value for DVR Property "dvrMaxChunkLogCount". Value: 10
public static final	DEFAULT_DVR_MAX_ILLEGAL_CHUNKS_LOGGED Default value for DVR Property "dvrMaxInvalidChunksLogged". Value: 10
public static final	DEFAULT_DVR_PACKET_DELTA_TO_NOTIFY Value: 200
public static final	DEFAULT_DVR_PACKET_DELTA_TO_RESET_TIME Default value for DVR Property "dvrResetTimePacketDelta". Value: 200
public static final	DEFAULT_DVR_PACKET_SORT_TIME Default value for DVR Property "dvrPacketSortTime". Value: 0
public static final	DEFAULT_DVR_RECORDINGS_LOADER_CLASS Default value for DVR Property "dvrRecordingsLoaderClass". Value: com.wowza.wms.dvr.DvrRecordingsLoader
public static final	DEFAULT_DVR_SANJOSE_ABST_DURATION_TOLERANCE Default value for property "dvrSanJosePlaylistAbstDurationTolerance" #see PROPKEY_DVR_SANJOSE_ABST_DURATION_TOLERANCE Value: 50
public static final	DEFAULT_DVR_SANJOSE_ABST_TIMESCALE Default value for property "dvrSanJosePlaylistAbstTimescale" #see PROPKEY_DVR_SANJOSE_ABST_TIMESCALE Value: 1000
public static final	DEFAULT_FILE_SYSTEM_CLASS Default value for DVR Property "dvrFileSystemClass". Value: com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem
public static final	DEFAULT_MANIFEST_PERSISTER_CLASS Default value for DVR Property "dvrManifestPersisterClass". Value: com.wowza.wms.dvr.impl.DvrManifestPersister
public static final	DEFAULT_TEXT_READER_CLASS Default value for DVR Property "dvrTextReaderClass". Value: com.wowza.wms.dvr.impl.io.DvrTextFileReader
public static final	DEFAULT_TEXT_WRITER_CLASS Default value for DVR Property "dvrTextWriterClass". Value: com.wowza.wms.dvr.impl.io.DvrTextFileWriter
public static final	DVR_DEFAULT_FILESTORE The default DVR store ID: "dvrfilestorage". Value: dvrfilestorage
public static final	DVR_DEFAULT_RECORDER_ID The default DVR recorder ID: "dvrrecorder". Value: dvrrecorder

public static final	<u>DVR_DEFAULT_REPEATER_PACKETIZER_ID</u> The default DVR streaming repeater ID: "dvrstreamingrepeater". Value: dvrstreamingrepeater
public static final	<u>DVR_DEFAULT_STREAMER_PACKETIZER_ID</u> The default DVR streaming packetizer ID: "dvrstreamingpacketizer". Value: dvrstreamingpacketizer
public static final	<u>DVR_STORAGE_STRATEGY_APPEND</u> Value: append
public static final	<u>DVR_STORAGE_STRATEGY_DELETE</u> Value: delete
public static final	<u>DVR_STORAGE_STRATEGY_VERSION</u> Value: version
public static final	<u>DVR_WINDOW_DURATION_UNLIMITED</u> Value: 0
public static final	<u>MIMETYPE_VIDEO_MP4</u> Constant for mime type "video/mp4" Value: video/mp4
public static final	<u>PROPKEY_CHUNK_CACHE_CLASS</u> DVR Property "dvrChunkMemoryCacheClass": for controlling the class responsible for caching DVR chunks in memory. Value: dvrChunkMemoryCacheClass
public static final	<u>PROPKEY_DVR_ALLOWABLE_AV_PACKET_DELTA</u> DVR Property "dvrAllowableAVPacketDelta": for specifying how much audio and video packets may diverge before triggering an error. Value: dvrAllowableAVPacketDelta
public static final	<u>PROPKEY_DVR_APPEND_DISCONTINUITY_DELTA</u> DVR Property "dvrAppendDiscontinuityDelta": for specifying how many milliseconds of empty space are put between individual recordings that when in append mode. Value: dvrAppendDiscontinuityDelta
public static final	<u>PROPKEY_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION</u> DVR Property "dvrAudioOnlyChunkTargetDuration": for target duration when recording audio-only. Value: dvrAudioOnlyChunkTargetDuration
public static final	<u>PROPKEY_DVR_BREAK_ON_PTS</u> DVR Property "dvrChunkBreakOnPTS": for specifying that DVR should be broken on PTS. Value: dvrChunkBreakOnPTS
public static final	<u>PROPKEY_DVR_CHUNK_DURATION_MINIMUM</u> DVR Property "dvrChunkDurationMinimum": for minimum chunk duration, in milliseconds. Value: dvrChunkDurationMinimum

public static final	<u>PROPKEY_DVR_CHUNK_GROUPING_SECONDS</u> DVR Property "dvrChunkGroupingSeconds": for determining how many seconds of DVR are stored in each stores sub-folder. Value: dvrChunkGroupingSeconds
public static final	<u>PROPKEY_DVR_CHUNK_READER_CLASS</u> DVR Property "dvrChunkReaderClass": for controlling the class responsible for reading DVR Chunks. Value: dvrChunkReaderClass
public static final	<u>PROPKEY_DVR_CHUNK_WRITER_CLASS</u> DVR Property "dvrChunkWriterClass": for controlling the class responsible for writing DVR Chunks. Value: dvrChunkWriterClass
public static final	<u>PROPKEY_DVR_DEBUG_MAXIMUM_RAW_PACKETS</u> DVR Property "dvrDebugMaximumRawPackets": for setting maximum number of logged raw packets. Value: dvrDebugMaximumRawPackets
public static final	<u>PROPKEY_DVR_DEBUG_METHODS</u> DVR Property "dvrDebugManagerLogMethods": for turning on DVR Manager debug logging. Value: dvrDebugManagerLogMethods
public static final	<u>PROPKEY_DVR_DEBUG_PLAYER_ADAPTER</u> HTTP Streamer Property "dvrDebugPlayerAdapter": for turning on DVR Player Adapter debug logging. Value: dvrDebugPlayerAdapter
public static final	<u>PROPKEY_DVR_DEBUG_RAW_PACKETS</u> DVR Property "dvrDebugRawPackets": for turning on logging of incoming raw packets. Value: dvrDebugRawPackets
public static final	<u>PROPKEY_DVR_DEBUG_TOSSED_HOLDERS</u> DVR Property "dvrDebugTossedHolders": for turning on logging of incoming raw packets. Value: dvrDebugTossedHolders
public static final	<u>PROPKEY_DVR_ENCRYPTION_INFO_DELEGATE</u> DVR Property "dvrPlaylistEncryptionInfoDelegate": used to over-ride the encryption info on the playback side. Value: dvrPlaylistEncryptionInfoDelegate
public static final	<u>PROPKEY_DVR_FILE_SYSTEM_CLASS</u> DVR Property "dvrFileSystemClass": for controlling the class responsible for managing the DVR File System. Value: dvrFileSystemClass
public static final	<u>PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS</u> DVR Property "dvrLogInvalidChunkDetails": to control detailed logging information of DVR invalid chunks Value: dvrLogInvalidChunkDetails
public static final	<u>PROPKEY_DVR_MANIFEST_PERSISTER_CLASS</u> DVR Property "dvrManifestPersisterClass": for controlling the class responsible for persisting the manifest files. Value: dvrManifestPersisterClass

public static final	<u>PROPKEY_DVR_MAX_CHUNK_LOG</u> DVR Property "dvrMaxChunkLogCount": for maximum number of DVR chunks to log. Value: dvrMaxChunkLogCount
public static final	<u>PROPKEY_DVR_MAX_ILLEGAL_CHUNKS_LOGGED</u> DVR Property "dvrMaxInvalidChunksLogged": for controlling maximum number of invalid DVR chunks logged. Value: dvrMaxInvalidChunksLogged
public static final	<u>PROPKEY_DVR_PACKET_DELTA_TO_NOTIFY</u> Value: dvrPacketDeltaToNotify
public static final	<u>PROPKEY_DVR_PACKET_DELTA_TO_RESET_TIME</u> DVR Property "dvrResetTimePacketDelta": for controlling how much Chunk start times must diverge from last chunk's end time before the DVR time gets reset. Value: dvrResetTimePacketDelta
public static final	<u>PROPKEY_DVR_PACKET_SORT_TIME</u> DVR Property "dvrPacketSortTime": for sorting incoming packets. Value: dvrPacketSortTime
public static final	<u>PROPKEY_DVR_PLAYLIST_REQUEST_DELEGATE</u> DVR Property "dvrPlaylistRequestDelegate": used to over-ride the class that generates a playlist request. Value: dvrPlaylistRequestDelegate
public static final	<u>PROPKEY_DVR_RECORDINGS_LOADER_CLASS</u> DVR Property "dvrRecordingsLoaderClass": for controlling the class responsible for loading DVR recordings. Value: dvrRecordingsLoaderClass
public static final	<u>PROPKEY_DVR_SANJOSE_ABST_DURATION_TOLERANCE</u> DVR Property "dvrSanJosePlaylistAbstDurationEqualityTolerance": used to over-ride the tolerance when determining equal chunks lengths. Value: dvrSanJosePlaylistAbstDurationTolerance
public static final	<u>PROPKEY_DVR_SANJOSE_ABST_TIMESCALE</u> DVR Property "dvrSanJosePlaylistAbstTimescale": used to over-ride the time-scale for abst files. Value: dvrSanJosePlaylistAbstTimescale
public static final	<u>PROPKEY_DVR_SANJOSE_PLAYLIST_DELIVERYTYPE</u> DVR Property "dvrSanJosePlaylistDeliveryType": used to over-ride the mime type for DVR San Jose F4m playlists. Value: dvrSanJosePlaylistDeliveryType
public static final	<u>PROPKEY_DVR_SANJOSE_PLAYLIST_LIVE_STREAMTYPE</u> DVR Property "dvrSanJosePlaylistLiveStreamType": used to over-ride the stream type for live DVR in San Jose f4m playlists. Value: dvrSanJosePlaylistLiveStreamType
public static final	<u>PROPKEY_DVR_SANJOSE_PLAYLIST_MIMETYPE</u> DVR Property "dvrSanJosePlaylistMimeType": used to over-ride the mime type for DVR San Jose F4m playlists. Value: dvrSanJosePlaylistMimeType

public static final	<u>PROPKEY_DVR_SANJOSE_PLAYLIST_RECORDED_STREAMTYPE</u> DVR Property "dvrSanJosePlaylistRecordedStreamType": used to over-ride the stream type for non-live (recorded) DVR in San Jose f4m playlists. Value: dvrSanJosePlaylistRecordedStreamType
public static final	<u>PROPKEY_DVR_SANJOSE_PLAYLIST_VERSION</u> DVR Property "dvrSanJosePlaylistVersion": used to over-ride the version of the San Jose f4m playlist. Value: dvrSanJosePlaylistVersion
public static final	<u>PROPKEY_DVR_SHARED_SECRET</u> DVR Property "dvrEncryptionSharedSecret": for encryption shared secret between origins and edges. Value: dvrEncryptionSharedSecret
public static final	<u>PROPKEY_DVR_TEXT_READER_CLASS</u> DVR Property "dvrTextReaderClass": for controlling the class responsible for reading DVR text files. Value: dvrTextReaderClass
public static final	<u>PROPKEY_DVR_TEXT_WRITER_CLASS</u> DVR Property "dvrTextWriterClass": for controlling the class responsible for writing DVR text files. Value: dvrTextWriterClass
public static final	<u>PROPKEY_DVR_WINDOW_DURATION</u> DVR Property "dvrWindowDuration": for specifying the DVR window duration, in seconds. Value: dvrWindowDuration
public static final	<u>PROPKEY_RECORD_AUDIO</u> DVR Property "recordAudio": for determining if audio should be recorded. Value: recordAudio
public static final	<u>PROPKEY_RECORD_DATA</u> DVR Property "recordData": for determining if data should be recorded. Value: recordData
public static final	<u>PROPKEY_RECORD_VIDEO</u> DVR Property "recordVideo": for determining if video should be recorded. Value: recordVideo
public static final	<u>PROPKEY_START_RECORDING_ON_STARTUP</u> DVR Property "startRecordingOnStartup": for determining if DVR recorder should start recording immediately. Value: startRecordingOnStartup
public static final	<u>SANJOSE_F4M_STREAMINGTYPE_STREAMING</u> Constant for San Jose streaming type "streaming" Value: streaming
public static final	<u>SANJOSE_F4M_STREAMTYPE_DVR</u> Constant for San Jose stream type "dvr". Value: dvr
public static final	<u>SANJOSE_F4M_STREAMTYPE_LIVE</u> Constant for San Jose stream type "live". Value: live

public static final	SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED Constant for San Jose stream type "liveOrRecorded". Value: liveOrRecorded
public static final	SANJOSE_F4M_STREAMTYPE_RECORDED Constant for San Jose stream type "recorded". Value: recorded
public static final	SANJOSE_F4M_VERSION_1_0 Constant for San Jose f4m version "1.0". Value: 1.0
public static final	SANJOSE_F4M_VERSION_2_0 Constant for San Jose f4m version "2.0". Value: 2.0

Fields inherited from interface `com.wowza.wms.dvr.IDvrPrivateConstants`

DEFAULT_DVR_AUDIO_GROUP_COUNT, DEFAULT_DVR_MANIFEST_PURGE_SIZE,
 DEFAULT_DVR_MAX_ALLOWABLE_CHUNK_DURATION, DEFAULT_DVR_MAX_SAVE HOLDER_SIZE,
 DEFAULT_DVR_MINIMUM_AVAILABLE_CHUNKS,
 DEFAULT_DVR_RECALC_DURATION_MAX_AV_DIFFERENCE_TRIGGER,
 DEFAULT_DVR_RECALC_DURATION_TRIGGER_SIZE, DEFAULT_DVR_STREAM_IDLE_TIMEOUT,
 DEFAULT_DVR_STREAM_STARTUP_TIMEOUT, DEFAULT_DVR_WAIT_FOR_CODEC_TIME,
 DEFAULT_PURGE_CONTROL_CLASS, PROPKEY_DVR_AUDIO_GROUP_COUNT,
 PROPKEY_DVR_MANIFEST_PURGE_SIZE, PROPKEY_DVR_MAX_ALLOWABLE_CHUNK_DURATION,
 PROPKEY_DVR_MAX_SAVE HOLDER_SIZE, PROPKEY_DVR_MINIMUM_AVAILABLE_CHUNKS,
 PROPKEY_DVR_RECALC_DURATION_MAX_AV_DIFFERENCE_TRIGGER,
 PROPKEY_DVR_RECALC_DURATION_TRIGGER_SIZE, PROPKEY_DVR_WAIT_FOR_CODEC_TIME,
 PROPKEY_PURGE_CONTROL_CLASS

Fields

DVR_DEFAULT_STREAMER_PACKETIZER_ID

```
public static final java.lang.String DVR_DEFAULT_STREAMER_PACKETIZER_ID
```

The default DVR streaming packetizer ID: "dvrstreamingpacketizer".

See DVR.xml and Application.xml.

Constant value: **dvrstreamingpacketizer**

DVR_DEFAULT_REPEATER_PACKETIZER_ID

```
public static final java.lang.String DVR_DEFAULT_REPEATER_PACKETIZER_ID
```

The default DVR streaming repeater ID: "dvrstreamingrepeater".

See DVR.xml and Application.xml.

Constant value: **dvrstreamingrepeater**

DVR_DEFAULT_RECORDER_ID

```
public static final java.lang.String DVR_DEFAULT_RECORDER_ID
```

(continued from last page)

The default DVR recorder ID: "dvrrecorder".

See DVR.xml and Application.xml.
Constant value: **dvrrecorder**

DVR_DEFAULT_FILESTORE

```
public static final java.lang.String DVR_DEFAULT_FILESTORE
```

The default DVR store ID: "dvrfilestorage".

See DVR.xml and Application.xml.
Constant value: **dvrfilestorage**

PROPKEY_DVR_CHUNK_GROUPING_SECONDS

```
public static final java.lang.String PROPKEY_DVR_CHUNK_GROUPING_SECONDS
```

DVR Property "dvrChunkGroupingSeconds": for determining how many seconds of DVR are stored in each stores sub-folder.

The directory naming convention is HHHH_MM_SS with H = hours, M = minutes, S = seconds. Using the defaults, first directory would be named 0000_00_00 and the second directory would be named 0000_10_00, etc.

Valid values are integers greater than 60. Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrChunkGroupingSeconds**

See Also:

[DEFAULT_CHUNK_GROUPING_SECONDS](#)

DEFAULT_CHUNK_GROUPING_SECONDS

```
public static final int DEFAULT_CHUNK_GROUPING_SECONDS
```

Default value for DVR Property "dvrChunkGroupingSeconds".

Default value is 600 seconds (10 minutes).
Constant value: **600**

See Also:

[PROPKEY_DVR_CHUNK_GROUPING_SECONDS](#)

PROPKEY_DVR_APPEND_DISCONTINUITY_DELTA

```
public static final java.lang.String PROPKEY_DVR_APPEND_DISCONTINUITY_DELTA
```

DVR Property "dvrAppendDiscontinuityDelta": for specifying how many milliseconds of empty space are put between individual recordings that when in append mode.

Valid values are integers greater than or equal to 0. Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrAppendDiscontinuityDelta**

See Also:

[DEFAULT_DVR_APPEND_DISCONTINUITY_DELTA](#)

DEFAULT_DVR_APPEND_DISCONTINUITY_DELTA

```
public static final int DEFAULT_DVR_APPEND_DISCONTINUITY_DELTA
```

(continued from last page)

Default value for DVR Property "dvrAppendDiscontinuityDelta".

Default value is 0.
Constant value: **0**

See Also:

[PROPKEY_DVR_APPEND_DISCONTINUITY_DELTA](#)

PROPKEY_DVR_WINDOW_DURATION

```
public static final java.lang.String PROPKEY_DVR_WINDOW_DURATION
```

DVR Property "dvrWindowDuration": for specifying the DVR window duration, in seconds.

Valid values are integers greater than or equal to 0. Add the property to Application/DVR/Properties section of Application.xml. The default is 0, meaning the window size is unlimited.
Constant value: **dvrWindowDuration**

See Also:

[DVR_WINDOW_DURATION_UNLIMITED](#)

DVR_WINDOW_DURATION_UNLIMITED

```
public static final int DVR_WINDOW_DURATION_UNLIMITED
```

Constant value: **0**

DVR_STORAGE_STRATEGY_DELETE

```
public static final java.lang.String DVR_STORAGE_STRATEGY_DELETE
```

Constant value: **delete**

DVR_STORAGE_STRATEGY_VERSION

```
public static final java.lang.String DVR_STORAGE_STRATEGY_VERSION
```

Constant value: **version**

DVR_STORAGE_STRATEGY_APPEND

```
public static final java.lang.String DVR_STORAGE_STRATEGY_APPEND
```

Constant value: **append**

PROPKEY_DVR_CHUNK_READER_CLASS

```
public static final java.lang.String PROPKEY_DVR_CHUNK_READER_CLASS
```

DVR Property "dvrChunkReaderClass": for controlling the class responsible for reading DVR Chunks.

The class must implement IDvrChunkReader

Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrChunkReaderClass**

See Also:

(continued from last page)

com.wowza.wms.dvr.io.IDvrChunkReader
[DEFAULT_CHUNK_READER_CLASS](#)

DEFAULT_CHUNK_READER_CLASS

```
public static final java.lang.String DEFAULT_CHUNK_READER_CLASS
```

Default value for DVR Property "dvrChunkReaderClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrFileChunkReader".
Constant value: **com.wowza.wms.dvr.impl.io.DvrFileChunkReader**

See Also:

[PROPKEY_DVR_CHUNK_READER_CLASS](#)

PROPKEY_DVR_CHUNK_WRITER_CLASS

```
public static final java.lang.String PROPKEY_DVR_CHUNK_WRITER_CLASS
```

DVR Property "dvrChunkWriterClass": for controlling the class responsible for writing DVR Chunks.

The class must implement IDvrChunkWriter

Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrChunkWriterClass**

See Also:

com.wowza.wms.dvr.io.IDvrChunkWriter
[DEFAULT_CHUNK_WRITER_CLASS](#)

DEFAULT_CHUNK_WRITER_CLASS

```
public static final java.lang.String DEFAULT_CHUNK_WRITER_CLASS
```

Default value for DVR Property "dvrChunkWriterClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrFileChunkWriter".
Constant value: **com.wowza.wms.dvr.impl.io.DvrFileChunkWriter**

See Also:

[PROPKEY_DVR_CHUNK_WRITER_CLASS](#)

PROPKEY_DVR_FILE_SYSTEM_CLASS

```
public static final java.lang.String PROPKEY_DVR_FILE_SYSTEM_CLASS
```

DVR Property "dvrFileSystemClass": for controlling the class responsible for managing the DVR File System.

The class must implement com.wowza.wms.dvr.io.IDvrFileSystem and may sub-class
com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem

Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrFileSystemClass**

See Also:

com.wowza.wms.dvr.io.IDvrFileSystem
[DEFAULT_FILE_SYSTEM_CLASS](#)

DEFAULT_FILE_SYSTEM_CLASS

```
public static final java.lang.String DEFAULT_FILE_SYSTEM_CLASS
```

(continued from last page)

Default value for DVR Property "dvrFileSystemClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem".

Constant value: **com.wowza.wms.dvr.impl.io.DvrDefaultFileSystem**

See Also:

[PROPKEY_DVR_FILE_SYSTEM_CLASS](#)

PROPKEY_DVR_MANIFEST_PERSISTER_CLASS

```
public static final java.lang.String PROPKEY_DVR_MANIFEST_PERSISTER_CLASS
```

DVR Property "dvrManifestPersisterClass": for controlling the class responsible for persisting the manifest files.

The class must implement com.wowza.wms.dvr.io.IDvrManifestPersister

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrManifestPersisterClass**

See Also:

com.wowza.wms.dvr.io.IDvrManifestPersister

[DEFAULT_MANIFEST_PERSISTER_CLASS](#)

DEFAULT_MANIFEST_PERSISTER_CLASS

```
public static final java.lang.String DEFAULT_MANIFEST_PERSISTER_CLASS
```

Default value for DVR Property "dvrManifestPersisterClass".

Default value is "com.wowza.wms.dvr.impl.DvrManifestPersister".

Constant value: **com.wowza.wms.dvr.impl.DvrManifestPersister**

See Also:

[PROPKEY_DVR_MANIFEST_PERSISTER_CLASS](#)

PROPKEY_CHUNK_CACHE_CLASS

```
public static final java.lang.String PROPKEY_CHUNK_CACHE_CLASS
```

DVR Property "dvrChunkMemoryCacheClass": for controlling the class responsible for caching DVR chunks in memory.

The class must implement [IDvrChunkMemoryCache](#) and may sub-class com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrChunkMemoryCacheClass**

See Also:

[IDvrChunkMemoryCache](#)

[DEFAULT_CHUNK_CACHE_CLASS](#)

DEFAULT_CHUNK_CACHE_CLASS

```
public static final java.lang.String DEFAULT_CHUNK_CACHE_CLASS
```

Default value for DVR Property "dvrChunkMemoryCacheClass".

Default value is "com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache".

Constant value: **com.wowza.wms.dvr.impl.DvrDefaultChunkMemoryCache**

See Also:

(continued from last page)

[PROPKEY_CHUNK_CACHE_CLASS](#)

PROPKEY_DVR_RECORDINGS_LOADER_CLASS

```
public static final java.lang.String PROPKEY_DVR_RECORDINGS_LOADER_CLASS
```

DVR Property "dvrRecordingsLoaderClass": for controlling the class responsible for loading DVR recordings.

The class must implement [IDvrRecordingsLoader](#)

Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrRecordingsLoaderClass**

See Also:

[IDvrRecordingsLoader](#)

[DEFAULT_DVR_RECORDINGS_LOADER_CLASS](#)

DEFAULT_DVR_RECORDINGS_LOADER_CLASS

```
public static final java.lang.String DEFAULT_DVR_RECORDINGS_LOADER_CLASS
```

Default value for DVR Property "dvrRecordingsLoaderClass".

Default value is "com.wowza.wms.dvr.DvrRecordingsLoader".
Constant value: **com.wowza.wms.dvr.DvrRecordingsLoader**

See Also:

[PROPKEY_DVR_RECORDINGS_LOADER_CLASS](#)

PROPKEY_DVR_TEXT_WRITER_CLASS

```
public static final java.lang.String PROPKEY_DVR_TEXT_WRITER_CLASS
```

DVR Property "dvrTextWriterClass": for controlling the class responsible for writing DVR text files.

The class must implement [IDvrTextWriter](#)

Add the property to Application/DVR/Properties section of Application.xml.
Constant value: **dvrTextWriterClass**

See Also:

[IDvrTextWriter](#)

[DEFAULT_TEXT_WRITER_CLASS](#)

DEFAULT_TEXT_WRITER_CLASS

```
public static final java.lang.String DEFAULT_TEXT_WRITER_CLASS
```

Default value for DVR Property "dvrTextWriterClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrTextFileWriter".
Constant value: **com.wowza.wms.dvr.impl.io.DvrTextFileWriter**

See Also:

[PROPKEY_DVR_TEXT_WRITER_CLASS](#)

PROPKEY_DVR_TEXT_READER_CLASS

```
public static final java.lang.String PROPKEY_DVR_TEXT_READER_CLASS
```

(continued from last page)

DVR Property "dvrTextReaderClass": for controlling the class responsible for reading DVR text files.

The class must implement [IDvrTextReader](#)

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrTextReaderClass**

See Also:

[IDvrTextReader](#)

[DEFAULT_TEXT_READER_CLASS](#)

DEFAULT_TEXT_READER_CLASS

```
public static final java.lang.String DEFAULT_TEXT_READER_CLASS
```

Default value for DVR Property "dvrTextReaderClass".

Default value is "com.wowza.wms.dvr.impl.io.DvrTextFileReader".

Constant value: **com.wowza.wms.dvr.impl.io.DvrTextFileReader**

See Also:

[PROPKEY_DVR_TEXT_READER_CLASS](#)

PROPKEY_DVR_ALLOWABLE_AV_PACKET_DELTA

```
public static final java.lang.String PROPKEY_DVR_ALLOWABLE_AV_PACKET_DELTA
```

DVR Property "dvrAllowableAVPacketDelta": for specifying how much audio and video packets may diverge before triggering an error.

Wowza nDVR expects the incoming audio and video to be aligned. Through this parameter, Wowza nDVR will try to compensate for out of alignment issues, but it cannot resolve them. This setting safeguards against audio and data video packets that are not closely aligned. The units are in ms. The default value is 2000 ms. If audio and video are out of alignment by more than this value, the audio and video chunks will be ignored in an attempt to get the streams back into alignment. If you already have an out of alignment issue, increasing the default value is likely to cause more problems. Increasing this value will increase the number of chunks not recorded which may cause the overall quality to be unacceptable.

Add the property to Application/DVR/Properties section of Application.xml.

Constant value: **dvrAllowableAVPacketDelta**

See Also:

[DEFAULT_DVR_ALLOWABLE_AV_PACKET_DELTA](#)

DEFAULT_DVR_ALLOWABLE_AV_PACKET_DELTA

```
public static final int DEFAULT_DVR_ALLOWABLE_AV_PACKET_DELTA
```

Default value for DVR Property "dvrAllowableAVPacketDelta".

Default value is 2000 ms.

Constant value: **2000**

See Also:

[PROPKEY_DVR_ALLOWABLE_AV_PACKET_DELTA](#)

PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS

```
public static final java.lang.String PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS
```

DVR Property "dvrLogInvalidChunkDetails": to control detailed logging information of DVR invalid chunks

The default is false, meaning do not log invalid chunks. Add the property to Application/DVR/Properties section of Application.xml

(continued from last page)

Constant value: **dvrLogInvalidChunkDetails**

See Also:

[PROPKEY_DVR_MAX_ILLEGAL_CHUNKS_LOGGED](#)

PROPKEY_DVR_MAX_ILLEGAL_CHUNKS_LOGGED

```
public static final java.lang.String PROPKEY_DVR_MAX_ILLEGAL_CHUNKS_LOGGED
```

DVR Property "dvrMaxInvalidChunksLogged": for controlling maximum number of invalid DVR chunks logged.

The default is 10. Logging only occurs if property [PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS](#) is true. Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrMaxInvalidChunksLogged**

See Also:

[DEFAULT_DVR_MAX_ILLEGAL_CHUNKS_LOGGED](#)

[PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS](#)

DEFAULT_DVR_MAX_ILLEGAL_CHUNKS_LOGGED

```
public static final int DEFAULT_DVR_MAX_ILLEGAL_CHUNKS_LOGGED
```

Default value for DVR Property "dvrMaxInvalidChunksLogged".

Default value is 10.

Constant value: **10**

See Also:

[PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS](#)

[PROPKEY_DVR_MAX_ILLEGAL_CHUNKS_LOGGED](#)

PROPKEY_DVR_PACKET_DELTA_TO_RESET_TIME

```
public static final java.lang.String PROPKEY_DVR_PACKET_DELTA_TO_RESET_TIME
```

DVR Property "dvrResetTimePacketDelta": for controlling how much Chunk start times must diverge from last chunk's end time before the DVR time gets reset.

Add the property to Application/DVR/Properties section of Application.xml

Constant value: **dvrResetTimePacketDelta**

See Also:

[DEFAULT_DVR_PACKET_DELTA_TO_RESET_TIME](#)

DEFAULT_DVR_PACKET_DELTA_TO_RESET_TIME

```
public static final int DEFAULT_DVR_PACKET_DELTA_TO_RESET_TIME
```

Default value for DVR Property "dvrResetTimePacketDelta".

Default value is 200 ms.

Constant value: **200**

See Also:

[PROPKEY_DVR_PACKET_DELTA_TO_RESET_TIME](#)

PROPKEY_DVR_PACKET_DELTA_TO_NOTIFY

```
public static final java.lang.String PROPKEY_DVR_PACKET_DELTA_TO_NOTIFY
```

(continued from last page)

Constant value: **dvrPacketDeltaToNotify**

DEFAULT_DVR_PACKET_DELTA_TO_NOTIFY

```
public static final int DEFAULT_DVR_PACKET_DELTA_TO_NOTIFY
```

Constant value: **200**

PROPKEY_DVR_DEBUG_TOSSED_HOLDERS

```
public static final java.lang.String PROPKEY_DVR_DEBUG_TOSSED_HOLDERS
```

DVR Property "dvrDebugTossedHolders": for turning on logging of incoming raw packets.

Valid values are "true" or "false". Default is false.

Constant value: **dvrDebugTossedHolders**

PROPKEY_DVR_DEBUG_RAW_PACKETS

```
public static final java.lang.String PROPKEY_DVR_DEBUG_RAW_PACKETS
```

DVR Property "dvrDebugRawPackets": for turning on logging of incoming raw packets.

Valid values are "true" or "false".

Constant value: **dvrDebugRawPackets**

See Also:

[PROPKEY_DVR_DEBUG_MAXIMUM_RAW_PACKETS](#)

DEFAULT_DVR_DEBUG_RAW_PACKETS

```
public static final boolean DEFAULT_DVR_DEBUG_RAW_PACKETS
```

Default value for DVR Property "dvrDebugRawPackets".

Default value is false.

Constant value: **false**

See Also:

[PROPKEY_DVR_DEBUG_RAW_PACKETS](#)

PROPKEY_DVR_DEBUG_MAXIMUM_RAW_PACKETS

```
public static final java.lang.String PROPKEY_DVR_DEBUG_MAXIMUM_RAW_PACKETS
```

DVR Property "dvrDebugMaximumRawPackets": for setting maximum number of logged raw packets.

Valid values is an integer. 0 means there is no limit.

Only affects logging if [PROPKEY_DVR_DEBUG_RAW_PACKETS](#) is true.

Constant value: **dvrDebugMaximumRawPackets**

See Also:

[PROPKEY_DVR_DEBUG_RAW_PACKETS](#)

DEFAULT_DVR_DEBUG_MAX_RAW_PACKETS

```
public static final int DEFAULT_DVR_DEBUG_MAX_RAW_PACKETS
```

(continued from last page)

Default value for DVR Property "dvrDebugMaximumRawPackets".

Default value is 200 log statements.
Constant value: **200**

See Also:

[PROPKEY_DVR_DEBUG_MAXIMUM_RAW_PACKETS](#)

PROPKEY_RECORD_DATA

```
public static final java.lang.String PROPKEY_RECORD_DATA
```

DVR Property "recordData": for determining if data should be recorded.

Set property to: true to record data of incoming stream. Default is true. Set property to: false to ignore data packets during recording.
Constant value: **recordData**

PROPKEY_RECORD_VIDEO

```
public static final java.lang.String PROPKEY_RECORD_VIDEO
```

DVR Property "recordVideo": for determining if video should be recorded.

Set property to: true to record video of incoming stream. Default is true. Set property to: false to ignore video packets during recording. Either recordVideo or recordAudio property must be set to: true
Constant value: **recordVideo**

PROPKEY_RECORD_AUDIO

```
public static final java.lang.String PROPKEY_RECORD_AUDIO
```

DVR Property "recordAudio": for determining if audio should be recorded.

Set property to: true to record audio of incoming stream. Default is true. Set property to: false to ignore audio packets during recording. Either recordVideo or recordAudio property must be set to: true
Constant value: **recordAudio**

PROPKEY_START_RECORDING_ON_STARTUP

```
public static final java.lang.String PROPKEY_START_RECORDING_ON_STARTUP
```

DVR Property "startRecordingOnStartup": for determining if DVR recorder should start recording immediately.

Set property to: true (default) to start recording immediately when stream is detected. Set property to: false to init the DVR recorder but to not start recording immediately when stream starts.
Constant value: **startRecordingOnStartup**

PROPKEY_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION

```
public static final java.lang.String PROPKEY_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION
```

DVR Property "dvrAudioOnlyChunkTargetDuration": for target duration when recording audio-only.

Applies to recording an audio-only stream and is the target chunk duration. The unit is in ms. The default value is 2000 ms. This setting is ignored if the stream contains video and audio, in which case the keyframe determines the chunk size.

Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrAudioOnlyChunkTargetDuration**

See Also:

[DEFAULT_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION](#)

DEFAULT_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION

```
public static final int DEFAULT_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION
```

Default value for DVR Property "dvrAudioOnlyChunkTargetDuration".

Default value is 2000 ms.
Constant value: **2000**

See Also:

[PROPKEY_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION](#)

PROPKEY_DVR_MAX_CHUNK_LOG

```
public static final java.lang.String PROPKEY_DVR_MAX_CHUNK_LOG
```

DVR Property "dvrMaxChunkLogCount": for maximum number of DVR chunks to log.

Maximum number of chunks to log recording information about in the wowzamedia_access.log file. Units are in chunks. The default value is 10 chunks. As recording is continued past this value, there is no feedback for normal operation in the log. View directories and files created in [install-dir]/dvr for on-going feedback that recording is occurring. Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrMaxChunkLogCount**

See Also:

[DEFAULT_DVR_PACKET_SORT_TIME](#)

DEFAULT_DVR_MAX_CHUNK_LOG

```
public static final int DEFAULT_DVR_MAX_CHUNK_LOG
```

Default value for DVR Property "dvrMaxChunkLogCount".

Default value is 10 logging statements.
Constant value: **10**

See Also:

[PROPKEY_DVR_MAX_CHUNK_LOG](#)

PROPKEY_DVR_PACKET_SORT_TIME

```
public static final java.lang.String PROPKEY_DVR_PACKET_SORT_TIME
```

DVR Property "dvrPacketSortTime": for sorting incoming packets. Specified in milliseconds.

Valid values are a integer greater than equal to 0. Zero means no sorting occurs. Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrPacketSortTime**

See Also:

[DEFAULT_DVR_PACKET_SORT_TIME](#)

DEFAULT_DVR_PACKET_SORT_TIME

```
public static final int DEFAULT_DVR_PACKET_SORT_TIME
```

Default value for DVR Property "dvrPacketSortTime".

Default value is 0 ms (i.e. no sorting).
Constant value: **0**

(continued from last page)

See Also:[PROPKEY_DVR_PACKET_SORT_TIME](#)

PROPKEY_DVR_BREAK_ON_PTS

```
public static final java.lang.String PROPKEY_DVR_BREAK_ON_PTS
```

DVR Property "dvrChunkBreakOnPTS": for specifying that DVR should be broken on PTS.

Valid values are "true" or "false" Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrChunkBreakOnPTS**

See Also:[DEFAULT_DVR_BREAK_ON_PTS](#)

DEFAULT_DVR_BREAK_ON_PTS

```
public static final boolean DEFAULT_DVR_BREAK_ON_PTS
```

Default value for DVR Property "dvrChunkBreakOnPTS".

Default value is true.
Constant value: **true**

See Also:[PROPKEY_DVR_BREAK_ON_PTS](#)

PROPKEY_DVR_DEBUG_METHODS

```
public static final java.lang.String PROPKEY_DVR_DEBUG_METHODS
```

DVR Property "dvrDebugManagerLogMethods": for turning on DVR Manager debug logging.

Valid values are "true" or "false".

Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrDebugManagerLogMethods**

PROPKEY_DVR_SHARED_SECRET

```
public static final java.lang.String PROPKEY_DVR_SHARED_SECRET
```

DVR Property "dvrEncryptionSharedSecret": for encryption shared secret between origins and edges. In Origin-Edge scenarios when Wowza is using encryption, a shared secret must be defined for both origin and edges to encrypt the information sent between origin and edge so that encryption information is not revealed.

A String values.

Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrEncryptionSharedSecret**

PROPKEY_DVR_DEBUG_PLAYER_ADAPTER

```
public static final java.lang.String PROPKEY_DVR_DEBUG_PLAYER_ADAPTER
```

HTTP Streamer Property "dvrDebugPlayerAdapter": for turning on DVR Player Adapter debug logging.

Valid values are "true" or "false". (Default is false)

Add this to the Properties section in HTTPStreamers.xml
Constant value: **dvrDebugPlayerAdapter**

PROPKEY_DVR_PLAYLIST_REQUEST_DELEGATE

```
public static final java.lang.String PROPKEY_DVR_PLAYLIST_REQUEST_DELEGATE
```

DVR Property "dvrPlaylistRequestDelegate": used to over-ride the class that generates a playlist request.

The delegate should extend DvrBasePlaylistRequestFactory

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrPlaylistRequestDelegate**

PROPKEY_DVR_ENCRYPTION_INFO_DELEGATE

```
public static final java.lang.String PROPKEY_DVR_ENCRYPTION_INFO_DELEGATE
```

DVR Property "dvrPlaylistEncryptionInfoDelegate": used to over-ride the encryption info on the playback side.

The specified delegate should extend DvrBaseEncryptionInfoDelegate

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrPlaylistEncryptionInfoDelegate**

PROPKEY_DVR_SANJOSE_PLAYLIST_MIMETYPE

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_PLAYLIST_MIMETYPE
```

DVR Property "dvrSanJosePlaylistMimeType": used to over-ride the mime type for DVR San Jose F4m playlists.

Default value is "video/mp4"

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSanJosePlaylistMimeType**

PROPKEY_DVR_SANJOSE_PLAYLIST_DELIVERYTYPE

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_PLAYLIST_DELIVERYTYPE
```

DVR Property "dvrSanJosePlaylistDeliveryType": used to over-ride the mime type for DVR San Jose F4m playlists.

Default value is "streaming"

Add this to Application/DVR/Properties section of Application.xml

Constant value: **dvrSanJosePlaylistDeliveryType**

PROPKEY_DVR_SANJOSE_PLAYLIST_VERSION

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_PLAYLIST_VERSION
```

DVR Property "dvrSanJosePlaylistVersion": used to over-ride the version of the San Jose f4m playlist.

Default value is "2.0". Valid values are "1.0" and "2.0".

Constant value: **dvrSanJosePlaylistVersion**

See Also:

[SANJOSE_F4M_VERSION_1_0](#)

[Add this to Application/DVR/Properties section of Application.xml](#)

(continued from last page)

PROPKEY_DVR_SANJOSE_PLAYLIST_RECORDED_STREAMTYPE

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_PLAYLIST_RECORDED_STREAMTYPE
```

DVR Property "dvrSanJosePlaylistRecordedStreamType": used to over-ride the stream type for non-live (recorded) DVR in San Jose f4m playlists.

Default value is #SANJOSE_F4M_STREAMTYPE_RECORDED.*
Constant value: **dvrSanJosePlaylistRecordedStreamType**

See Also:

[SANJOSE_F4M_STREAMTYPE_DVR](#)
[SANJOSE_F4M_STREAMTYPE_LIVE](#)
[SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED](#)

Add this to Application/DVR/Properties section of Application.xml

PROPKEY_DVR_SANJOSE_PLAYLIST_LIVE_STREAMTYPE

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_PLAYLIST_LIVE_STREAMTYPE
```

DVR Property "dvrSanJosePlaylistLiveStreamType": used to over-ride the stream type for live DVR in San Jose f4m playlists.

Default value is #SANJOSE_F4M_STREAMTYPE_DVR.
Constant value: **dvrSanJosePlaylistLiveStreamType**

See Also:

[SANJOSE_F4M_STREAMTYPE_DVR](#)
[SANJOSE_F4M_STREAMTYPE_LIVE](#)
[SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED](#)

Add this to Application/DVR/Properties section of Application.xml

SANJOSE_F4M_STREAMTYPE_DVR

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_DVR
```

Constant for San Jose stream type "dvr".
Constant value: **dvr**

SANJOSE_F4M_STREAMTYPE_RECORDED

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_RECORDED
```

Constant for San Jose stream type "recorded".
Constant value: **recorded**

SANJOSE_F4M_STREAMTYPE_LIVE

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_LIVE
```

Constant for San Jose stream type "live".
Constant value: **live**

SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED

```
public static final java.lang.String SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED
```

(continued from last page)

Constant for San Jose stream type "liveOrRecorded".
Constant value: **liveOrRecorded**

SANJOSE_F4M_VERSION_1_0

```
public static final java.lang.String SANJOSE_F4M_VERSION_1_0
```

Constant for San Jose f4m version "1.0".
Constant value: **1.0**

SANJOSE_F4M_VERSION_2_0

```
public static final java.lang.String SANJOSE_F4M_VERSION_2_0
```

Constant for San Jose f4m version "2.0".
Constant value: **2.0**

SANJOSE_F4M_STREAMINGTYPE_STREAMING

```
public static final java.lang.String SANJOSE_F4M_STREAMINGTYPE_STREAMING
```

Constant for San Jose streaming type "streaming".
Constant value: **streaming**

MIMETYPE_VIDEO_MP4

```
public static final java.lang.String MIMETYPE_VIDEO_MP4
```

Constant for mime type "video/mp4".
Constant value: **video/mp4**

PROPKEY_DVR_SANJOSE_ABST_TIMESCALE

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_ABST_TIMESCALE
```

DVR Property "dvrSanJosePlaylistAbstTimescale": used to over-ride the time-scale for abst files.

Default value is #SANJOSE_ABST_DEFAULT_TIMESCALE (1000), which means milliseconds.

Add this to Application/DVR/Properties section of Application.xml
Constant value: **dvrSanJosePlaylistAbstTimescale**

PROPKEY_DVR_SANJOSE_ABST_DURATION_TOLERANCE

```
public static final java.lang.String PROPKEY_DVR_SANJOSE_ABST_DURATION_TOLERANCE
```

DVR Property "dvrSanJosePlaylistAbstDurationEqualityTolerance": used to over-ride the tolerance when determining equal chunks lengths.

Default value is #SANJOSE_ABST_DEFAULT_DURATION_EQUALITY_TOLERANCE (50), which means 50 milliseconds.

Add this to Application/DVR/Properties section of Application.xml
Constant value: **dvrSanJosePlaylistAbstDurationTolerance**

DEFAULT_DVR_SANJOSE_ABST_TIMESCALE

```
public static final int DEFAULT_DVR_SANJOSE_ABST_TIMESCALE
```

Default value for property "dvrSanJosePlaylistAbstTimescale" #see [PROPKEY_DVR_SANJOSE_ABST_TIMESCALE](#)
Constant value: **1000**

DEFAULT_DVR_SANJOSE_ABST_DURATION_TOLERANCE

```
public static final int DEFAULT_DVR_SANJOSE_ABST_DURATION_TOLERANCE
```

Default value for property "dvrSanJosePlaylistAbstDurationTolerance" #see [PROPKEY_DVR_SANJOSE_ABST_DURATION_TOLERANCE](#)
Constant value: **50**

PROPKEY_DVR_CHUNK_DURATION_MINIMUM

```
public static final java.lang.String PROPKEY_DVR_CHUNK_DURATION_MINIMUM
```

DVR Property "dvrChunkDurationMinimum": for minimum chunk duration, in milliseconds.

Add the property to Application/DVR/Properties section of Application.xml
Constant value: **dvrChunkDurationMinimum**

See Also:

[DEFAULT_DVR_CHUNK_DURATION_MINIMUM](#)

DEFAULT_DVR_CHUNK_DURATION_MINIMUM

```
public static final int DEFAULT_DVR_CHUNK_DURATION_MINIMUM
```

Default value for DVR Property "dvrChunkDurationMinimum".

Default value is 1500 ms.
Constant value: **1500**

See Also:

[PROPKEY_DVR_CHUNK_DURATION_MINIMUM](#)

com.wowza.wms.dvr Interface IDvrEncryptionInfo

public interface **IDvrEncryptionInfo**
extends Cloneable

Interface for persisting encryption information for DVR.

Field Summary

public static final	<u>ENCRYPTION_TYPE_CUPERTINO</u> Cupertino AES encryption type. Value: 1
public static final	<u>ENCRYPTION_TYPE_PLAYREADY</u> Playready encryption type. Value: 2

Method Summary

Object	<u>clone()</u>
int	<u>getEncryptionType()</u> Serialize encryption info.
int	<u>getSerializeSize()</u> Return number of bytes required to serialize this encryption info.
byte[]	<u>serialize()</u> Serialize the encryption info, returning a byte buffer containing the serialized data.
int	<u>serialize(byte[] buffer, int pos)</u> Serialize the encryption info into buffer starting at position 'pos'.

Fields

ENCRYPTION_TYPE_CUPERTINO

public static final int **ENCRYPTION_TYPE_CUPERTINO**

Cupertino AES encryption type.
Constant value: **1**

ENCRYPTION_TYPE_PLAYREADY

public static final int **ENCRYPTION_TYPE_PLAYREADY**

Playready encryption type.
Constant value: **2**

Methods

(continued from last page)

getSerializeSize

```
public int getSerializeSize()
```

Return number of bytes required to serialize this encryption info.

Returns:

number of bytes to serialize.

getEncryptionType

```
public int getEncryptionType()
```

Serialize encryption info.

The encryption should consist of the following:

- version (1 byte)
- encryption type (1 byte)
- length of 'blob' (2 bytes)
- byte blob (n bytes)

Returns:

encryption type (constants defined in this class)

serialize

```
public int serialize(byte[] buffer,  
int pos)
```

Serialize the encryption info into buffer starting at position 'pos'.

Parameters:

`buffer` - buffer to serialize to
`pos` - position to start serializing

Returns:

new position into buffer

serialize

```
public byte[] serialize()
```

Serialize the encryption info, returning a byte buffer containing the serialized data.

Returns:

byte buffer of serialized data

clone

```
public Object clone()  
throws CloneNotSupportedException
```

com.wowza.wms.dvr Interface IDvrManifest

public interface **IDvrManifest**
extends

Interface for a DVR Store manifest. A DVR manifest collects type-specific manifest info, including:

- Audio manifest
- Video manifest
- data manifest
- time map manifest, to map DVR, packet and real time
- codec manifest to track codec information
- onMetadata manifest

The difference between retrieving 'recorded entries' and 'live entries' is an important one. Recorded Entries means every current manifest entry. Live Entries refers to a subset of these because a playlist will not include the very last entries, as some chunks must be available for buffering.

Field Summary	
public static final	CODEC_TYPE Constant for codec manifest type. Value: 999
public static final	MANIFEST_TAGNAME_CAN_PLAY Value: CanPlay
public static final	MANIFEST_TAGNAME_CAN_RECORD Value: CanRecord
public static final	MANIFEST_TAGNAME_CHUNK_GROUPING Value: ChunkGrouping
public static final	MANIFEST_TAGNAME_CURRENT_TIME Value: CurrentTime
public static final	MANIFEST_TAGNAME_HAS_ENCRYPTION Value: HasEncryption
public static final	MANIFEST_TAGNAME_PURGE_TIME Value: PurgeTime
public static final	ON_METADATA_TYPE Constant for 'onMetadata' manifest type. Value: 0
public static final	TIME_MAP_TYPE Constant for time map manifest type. Value: 998

Method Summary

void	<code>addToManifest</code> (java.util.List entries) Add manifest entries to the manifest
void	<code>deserialize</code> (byte[] bytes) Deserialize the manifest.
long	<code>expandEndTime</code> (int type, long dvrEndTime)
long	<code>expandStartTime</code> (int type, long dvrStartTime)
long	<code>getClosestStartTime</code> (int type, long dvrTime) Given a dvrTime and a manifest type, find the closest chunk starting time.
<code>DvrManifestCodecEntry</code>	<code>getCodecEntryForTime</code> (long dvrTime) Return most recent codec entry for a given DVR time.
long	<code>getDvrTime</code> (int type)
<code>DvrManifestEntryRangeGroup</code>	<code>getEntriesToPurge</code> (long purgeTime) Given a purge time, return a group of manifest ranges to purge.
<code>DvrManifestEntry</code>	<code>getFirstEntry</code> (int type) Given manifest type, get the first playlist manifest entry.
<code>DvrManifestEntry</code>	<code>getLastLiveEntry</code> (int type) Given manifest type, get the last playlist manifest entry.
<code>DvrManifestEntry</code>	<code>getLastRecordedEntry</code> (int type) Given manifest type and DVR time, get last entry.
int	<code>getLastRecordedIndex</code> (int type) Return last index of DVR entry for given type.
java.util.List	<code>getLiveEntries</code> (int type, long dvrStart) Given manifest type and DVR time, get a list of the live entries.
java.util.List	<code>getLiveEntries</code> (int type, long dvrStart, long dvrEnd) Given manifest type and DVR time, get a list of the live entries.
java.util.List	<code>getLiveEntriesWithLimit</code> (int type, long dvrTime, int limit) Given manifest type and DVR time, get a list of the live entries limiting number of returned items.
DvrChannelManifest	<code>getManifestChannel</code> (int type) For a given manifest type, return the channel manifest.
<code>DvrManifestOnMetadataEntry</code>	<code>getMetadataEntryForTime</code> (long dvrTime) Return most recent metadataEntry for a given DVR time.
int	<code>getNextChunkIndex</code> ()
int	<code>getNextCodecIndex</code> ()
int	<code>getNextMetadataIndex</code> ()

int	<u>getNextTimeMapIndex()</u>
int	<u>getNumberLiveEntries</u> (int type, long dvrStart) Given manifest type and DVR time, get the number of live entries at the given time.
int	<u>getNumberLiveEntries</u> (int type, long dvrStart, long dvrEnd) Given manifest type and DVR time, get the number of live entries at the given time.
int	<u>getNumberRecordedEntries</u> (int type, long dvrStart) Given manifest type and DVR time, get the number of entries at the given time.
int	<u>getNumberRecordedEntries</u> (int type, long dvrStart, long dvrEnd) Given manifest type and DVR time, get the number of live entries at the given time.
java.util.List	<u>getRecordedEntries</u> (int type) Get a copy of all manifest entries of a given type.
java.util.List	<u>getRecordedEntries</u> (int type, long dvrSartTime) Given manifest type and DVR time, get a list of recorded entries.
java.util.List	<u>getRecordedEntries</u> (int type, long dvrSartTime, long dvrEndTime) Given manifest type and DVR time, get a list of recorded entries.
java.util.List	<u>getRecordedEntriesInRange</u> (<u>DvrManifestEntryRange</u> range) Given a DvrManifestEntryRange, get a list of recorded entries in this range.
java.util.Map	<u>getRecordedEntriesMap</u> (int type) Get a copy of all manifest entries of a given type as a Map of indices.
java.util.List	<u>getRecordedEntriesWithLimit</u> (int type, long dvrTime, int limit) Given manifest type and DVR time, get a list of recorded entries limiting number of returned items.
<u>DvrManifestEntry</u>	<u>getRecordedEntryByIndex</u> (int type, int index) Get the manifest entry given a manifest type and an index.
<u>DvrManifestEntry</u>	<u>getRecordedEntryByTimeKey</u> (int type, long dvrTime) Get the manifest entry given a manifest type and a time (in DVR units)
boolean	<u>hasAudio</u> () Does manifest contain audio.
boolean	<u>hasCodecData</u> () Does manifest contain codec data.
boolean	<u>hasData</u> () Does manifest contain data.
boolean	<u>hasOnMetadata</u> () Does manifest contain onMetadata.
boolean	<u>hasTimeMapData</u> () Does manifest contain time map info.
boolean	<u>hasVideo</u> () Does manifest contain video.
void	<u>importManifest</u> (<u>IDvrManifest</u> manifest, boolean persist) Import the specified manifest into this manifest

void	<code>initialize()</code> Initialize the manifest.
java.util.List	<code>purgeEntries(DvrManifestEntryRangeGroup ranges)</code> Given a group of ranges, purge the manifest entries.
void	<code>refreshManifest()</code> Refresh the manifest.
byte[]	<code>serialize(boolean ignoreEntries)</code> Serialize the manifest.

Fields

ON_METADATA_TYPE

public static final int **ON_METADATA_TYPE**

Constant for 'onMetadata' manifest type.
Constant value: **0**

CODEC_TYPE

public static final int **CODEC_TYPE**

Constant for codec manifest type.
Constant value: **999**

TIME_MAP_TYPE

public static final int **TIME_MAP_TYPE**

Constant for time map manifest type.
Constant value: **998**

MANIFEST_TAGNAME_CAN_RECORD

public static final java.lang.String **MANIFEST_TAGNAME_CAN_RECORD**

Constant value: **CanRecord**

MANIFEST_TAGNAME_CAN_PLAY

public static final java.lang.String **MANIFEST_TAGNAME_CAN_PLAY**

Constant value: **CanPlay**

MANIFEST_TAGNAME_HAS_ENCRYPTION

public static final java.lang.String **MANIFEST_TAGNAME_HAS_ENCRYPTION**

Constant value: **HasEncryption**

(continued from last page)

MANIFEST_TAGNAME_CHUNK_GROUPING

```
public static final java.lang.String MANIFEST_TAGNAME_CHUNK_GROUPING
```

Constant value: **ChunkGrouping**

MANIFEST_TAGNAME_PURGE_TIME

```
public static final java.lang.String MANIFEST_TAGNAME_PURGE_TIME
```

Constant value: **PurgeTime**

MANIFEST_TAGNAME_CURRENT_TIME

```
public static final java.lang.String MANIFEST_TAGNAME_CURRENT_TIME
```

Constant value: **CurrentTime**

Methods

initialize

```
public void initialize()
```

Initialize the manifest. Called after the previous storage has been loaded but before any chunks are added.

refreshManifest

```
public void refreshManifest()
```

Refresh the manifest.

addToManifest

```
public void addToManifest(java.util.List entries)
```

Add manifest entries to the manifest

Parameters:

entries - list of entries.

getRecordedEntries

```
public java.util.List getRecordedEntries(int type)
```

Get a copy of all manifest entries of a given type. Valid types include: [IVHost.CONTENTTYPE_AUDIO](#), [IVHost.CONTENTTYPE_VIDEO](#), [IVHost.CONTENTTYPE_DATA](#), [ON_METADATA_TYPE](#), [CODEC_TYPE](#), or [TIME_MAP_TYPE](#)

Parameters:

type - The manifest type.

Returns:

list of entries

(continued from last page)

getRecordedEntriesMap

```
public java.util.Map getRecordedEntriesMap(int type)
```

Get a copy of all manifest entries of a given type as a Map of indices. Valid types include: [IVHost.CONTENTTYPE_AUDIO](#), [IVHost.CONTENTTYPE_VIDEO](#), [IVHost.CONTENTTYPE_DATA](#), [ON_METADATA_TYPE](#), [CODEC_TYPE](#), or [TIME_MAP_TYPE](#)

Parameters:

type - the manifest type.

Returns:

map of entries

getRecordedEntriesInRange

```
public java.util.List getRecordedEntriesInRange(DvrManifestEntryRange range)
```

Given a DvrManifestEntryRange, get a list of recorded entries in this range.

Parameters:

range - a range (which consists of a manifest type and a start and end index)

Returns:

list of entries

getLastRecordedEntry

```
public DvrManifestEntry getLastRecordedEntry(int type)
```

Given manifest type and DVR time, get last entry.

"Recorded Entries" includes those entries after the end of the playlist.

Parameters:

type - the manifest type.

Returns:

manifest entry

getRecordedEntryByTimeKey

```
public DvrManifestEntry getRecordedEntryByTimeKey(int type,  
long dvrTime)
```

Get the manifest entry given a manifest type and a time (in DVR units)

Parameters:

type - the manifest type.

dvrTime - DVR time

Returns:

manifest entry

getRecordedEntryByIndex

```
public DvrManifestEntry getRecordedEntryByIndex(int type,  
int index)
```

Get the manifest entry given a manifest type and an index.

(continued from last page)

Parameters:

type - the manifest type.
index - the index into the manifest

Returns:

manifest entry

getEntriesToPurge

```
public DvrManifestEntryRangeGroup getEntriesToPurge(long purgeTime)
```

Given a purge time, return a group of manifest ranges to purge. This method ensures that the purge entries are aligned by index so that audio and video always remain index aligned.

Parameters:

purgeTime - The DVR time to purge

Returns:

a group of ranges.

purgeEntries

```
public java.util.List purgeEntries(DvrManifestEntryRangeGroup ranges)
```

Given a group of ranges, purge the manifest entries.

Parameters:

ranges - Group of ranges

Returns:

A list of the purged items.

getMetadataEntryForTime

```
public DvrManifestOnMetadataEntry getMetadataEntryForTime(long dvrTime)
```

Return most recent metadataEntry for a given DVR time. The manifest for metadata entries is sparse-- it only stores items periodically. So for a given time t, the returned entry will exist at or before time t.

Parameters:

dvrTime - DVR time

Returns:

onMetadata Entry

getCodecEntryForTime

```
public DvrManifestCodecEntry getCodecEntryForTime(long dvrTime)
```

Return most recent codec entry for a given DVR time. The manifest for codec entries is sparse-- it only stores items periodically. So for a given time t, the returned entry will exist at or before time t.

Parameters:

dvrTime - DVR time

Returns:

Codec Entry

getNumberLiveEntries

```
public int getNumberLiveEntries(int type,  
                                long dvrStart)
```

Given manifest type and DVR time, get the number of live entries at the given time.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.
dvrStart - DVR time

Returns:

number of entries.

getNumberLiveEntries

```
public int getNumberLiveEntries(int type,  
                                long dvrStart,  
                                long dvrEnd)
```

Given manifest type and DVR time, get the number of live entries at the given time.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.
dvrStart - DVR time
dvrEnd - end DVR time

Returns:

number of entries.

getNumberRecordedEntries

```
public int getNumberRecordedEntries(int type,  
                                    long dvrStart)
```

Given manifest type and DVR time, get the number of entries at the given time.

"Recorded Entries" includes those entries after the end of the playlist.

Parameters:

type - the manifest type.
dvrStart - DVR time

Returns:

number of entries.

getNumberRecordedEntries

```
public int getNumberRecordedEntries(int type,  
                                    long dvrStart,  
                                    long dvrEnd)
```

(continued from last page)

Given manifest type and DVR time, get the number of live entries at the given time.

"Recorded Entries" includes those entries after the end of the playlist.

Parameters:

type - the manifest type.
dvrStart - DVR time
dvrEnd - end DVR time

Returns:

number of entries.

getFirstEntry

```
public DvrManifestEntry getFirstEntry(int type)
```

Given manifest type, get the first playlist manifest entry.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.

Returns:

manifest entry

getLastLiveEntry

```
public DvrManifestEntry getLastLiveEntry(int type)
```

Given manifest type, get the last playlist manifest entry.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.

Returns:

manifest entry

getLiveEntries

```
public java.util.List getLiveEntries(int type,  
    long dvrStart)
```

Given manifest type and DVR time, get a list of the live entries.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.
dvrStart - DVR time

Returns:

list of entries.

(continued from last page)

getLiveEntries

```
public java.util.List getLiveEntries(int type,  
    long dvrStart,  
    long dvrEnd)
```

Given manifest type and DVR time, get a list of the live entries.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.
dvrStart - DVR time
dvrEnd - end DVR time

Returns:

list of entries.

getLiveEntriesWithLimit

```
public java.util.List getLiveEntriesWithLimit(int type,  
    long dvrTime,  
    int limit)
```

Given manifest type and DVR time, get a list of the live entries limiting number of returned items.

"Live Entries" means that a couple of the last entries will not be included as they are too close to the live point to be part of the playlist.

Parameters:

type - the manifest type.
dvrTime - DVR time
limit - maximum number of returned items

Returns:

list of entries.

getRecordedEntriesWithLimit

```
public java.util.List getRecordedEntriesWithLimit(int type,  
    long dvrTime,  
    int limit)
```

Given manifest type and DVR time, get a list of recorded entries limiting number of returned items.

"Recorded Entries" includes those entries after the end of the playlist.

Parameters:

type - the manifest type.
dvrTime - DVR time
limit - maximum number of returned items

Returns:

list of entries.

getRecordedEntries

```
public java.util.List getRecordedEntries(int type,  
    long dvrSartTime)
```

(continued from last page)

Given manifest type and DVR time, get a list of recorded entries.

"Recorded Entries" includes those entries after the end of the playlist.

Parameters:

type - the manifest type.
dvrSartTime - DVR time

Returns:

list of entries.

getRecordedEntries

```
public java.util.List getRecordedEntries(int type,  
    long dvrSartTime,  
    long dvrEndTime)
```

Given manifest type and DVR time, get a list of recorded entries.

"Recorded Entries" includes those entries after the end of the playlist.

Parameters:

type - the manifest type.
dvrSartTime - DVR time
dvrEndTime - DVR end time

Returns:

list of entries.

getDvrTime

```
public long getDvrTime(int type)
```

getLastRecordedIndex

```
public int getLastRecordedIndex(int type)
```

Return last index of DVR entry for given type.

Parameters:

type

Returns:

index, or -1 if type does not exist

getNextChunkIndex

```
public int getNextChunkIndex()
```

getNextMetadataIndex

```
public int getNextMetadataIndex()
```

getNextCodecIndex

```
public int getNextCodecIndex()
```

getNextTimeMapIndex

```
public int getNextTimeMapIndex()
```

getManifestChannel

```
public DvrChannelManifest getManifestChannel(int type)
```

For a given manifest type, return the channel manifest.

Parameters:

type

Returns:

channel manifest

importManifest

```
public void importManifest(IDvrManifest manifest,  
    boolean persist)
```

Import the specified manifest into this manifest

Parameters:

manifest

persist

getClosestStartTime

```
public long getClosestStartTime(int type,  
    long dvrTime)
```

Given a dvrTime and a manifest type, find the closest chunk starting time.

Parameters:

type - manifest type

dvrTime - DVR time

Returns:

time that corresponds to the closest start time of the given manifest type

expandEndTime

```
public long expandEndTime(int type,  
    long dvrEndTime)
```

(continued from last page)

expandStartTime

```
public long expandStartTime(int type,  
                             long dvrStartTime)
```

hasVideo

```
public boolean hasVideo()
```

Does manifest contain video.

Returns:

true if it contains video.

hasAudio

```
public boolean hasAudio()
```

Does manifest contain audio.

Returns:

true if it contains audio.

hasData

```
public boolean hasData()
```

Does manifest contain data.

Returns:

true if it contains data.

hasOnMetadata

```
public boolean hasOnMetadata()
```

Does manifest contain onMetadata.

Returns:

true if it contains onMetadata.

hasCodecData

```
public boolean hasCodecData()
```

Does manifest contain codec data.

Returns:

true if it contains codec data

hasTimeMapData

```
public boolean hasTimeMapData()
```

Does manifest contain time map info.

Returns:

(continued from last page)

true if it contains time map info.

serialize

```
public byte[] serialize(boolean ignoreEntries)
```

Serialize the manifest.

Parameters:

`ignoreEntries` - If true, the individual manifest entries are not serialized.

Returns:

byte array of serialized data

deserialize

```
public void deserialize(byte[] bytes)
```

Deserialize the manifest. Should be called after default constructor for manifest has been called.

Parameters:

`bytes` - buffer of bytes to deserialize

com.wowza.wms.dvr Interface IDvrPacketConverter

public interface **IDvrPacketConverter**
extends

Interface for creating DVR chunks from a set of packets.

Method Summary

DvrChunk	createDvrAudioChunk (long dvrTime, int index, int duration, DvrPacketHolder holder) Create audio chunk from set of packets.
DvrChunk	createDvrDataChunk (long dvrTime, int index, int duration, DvrPacketHolder holder) Create data chunk from set of packets.
DvrChunk	createDvrOnMetadataChunk (long dvrTime, long pt, AMFPacket metaPacket) Create onMetadata chunk from set of packets.
DvrChunk	createDvrVideoChunk (long dvrTime, int index, int duration, DvrPacketHolder holder) Create video chunk from set of packets.

Methods

createDvrAudioChunk

```
public DvrChunk createDvrAudioChunk(long dvrTime,  
    int index,  
    int duration,  
    DvrPacketHolder holder)
```

Create audio chunk from set of packets.

Parameters:

dvrTime - DVR start time in milliseconds
index - index of DVR chunk
duration - Duration in milliseconds
holder - packet holder

Returns:

the created chunk or null if chunk not created.

createDvrVideoChunk

```
public DvrChunk createDvrVideoChunk(long dvrTime,  
    int index,  
    int duration,  
    DvrPacketHolder holder)
```

Create video chunk from set of packets.

Parameters:

(continued from last page)

dvrTime - DVR start time in milliseconds
index - index of DVR chunk
duration - Duration in milliseconds
holder - packet holder

Returns:

the created chunk or null if chunk not created.

createDvrDataChunk

```
public DvrChunk createDvrDataChunk(long dvrTime,  
    int index,  
    int duration,  
    DvrPacketHolder holder)
```

Create data chunk from set of packets.

Parameters:

dvrTime - DVR start time in milliseconds
index - index of DVR chunk
duration - Duration in milliseconds
holder - packet holder

Returns:

the created chunk or null if chunk not created.

createDvrOnMetadataChunk

```
public DvrChunk createDvrOnMetadataChunk(long dvrTime,  
    long pt,  
    AMFPacket metaPacket)
```

Create onMetadata chunk from set of packets.

Parameters:

dvrTime - DVR start time in milliseconds
pt - Packet time
metaPacket - metadata packet

Returns:

the created chunk or null if chunk not created.

com.wowza.wms.dvr Interface IDvrPacketWriter

public interface **IDvrPacketWriter**
extends

Interface for chunking and storing packets for DVR.

Method Summary

void	<u>addToChunk</u> (DvrPacketHolder holder)
boolean	<u>canRecordAudio</u> ()
boolean	<u>canRecordData</u> ()
boolean	<u>canRecordVideo</u> ()
void	<u>endChunk</u> (long videoEndTime, long audioEndTime)
void	<u>resetStream</u> ()
void	<u>sendOnMetadata</u> (long pt, <u>AMFPacket</u> metaPacket)
void	<u>setCodecInfoAudio</u> (com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
void	<u>setCodecInfoVideo</u> (com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
void	<u>startChunk</u> (int streamMode, int videoCodecId, int audioCodecId, long timecode)

Methods

sendOnMetadata

```
public void sendOnMetadata(long pt,
    AMFPacket metaPacket)
```

startChunk

```
public void startChunk(int streamMode,
    int videoCodecId,
    int audioCodecId,
    long timecode)
```

addToChunk

```
public void addToChunk(DvrPacketHolder holder)
```

endChunk

```
public void endChunk(long videoEndTime,  
                    long audioEndTime)
```

setCodecInfoAudio

```
public void setCodecInfoAudio(com.wowza.wms.media.model.MediaCodecInfoAudio  
codecInfoAudio)
```

setCodecInfoVideo

```
public void setCodecInfoVideo(com.wowza.wms.media.model.MediaCodecInfoVideo  
codecInfoVideo)
```

resetStream

```
public void resetStream()
```

canRecordAudio

```
public boolean canRecordAudio()
```

canRecordVideo

```
public boolean canRecordVideo()
```

canRecordData

```
public boolean canRecordData()
```

com.wowza.wms.dvr Interface IDvrPlayerAdapter

public interface **IDvrPlayerAdapter**
extends

Field Summary

public static final	QUERY_PARAM_DVR Value: DVR
---------------------	------------------------------------------------------

Method Summary

int	calcBitrate (IDvrStreamStore store, int type, long t)
String	determineStreamVersion (IDvrStreamManager dvrMgr, java.util.Map queryMap, String baseStreamName)
DvrPlaylistRequest	getDvrPlaylistRequest (IHTTPStreamerApplicationContext appContext, IDvrStreamStore store, java.util.Map queryMap)
DvrPlaylistRequest	getDvrPlaylistRequest (IHTTPStreamerApplicationContext appContext, java.util.List store, java.util.Map queryMap)
boolean	isDebug ()
boolean	isPlaylistReady (IDvrStreamStore store, DvrPlaylistRequest playlistRequest)
void	setDebug (boolean debug)

Fields

QUERY_PARAM_DVR

public static final java.lang.String **QUERY_PARAM_DVR**

Constant value: **DVR**

Methods

isPlaylistReady

public boolean **isPlaylistReady**([IDvrStreamStore](#) store, DvrPlaylistRequest playlistRequest)

determineStreamVersion

```
public String determineStreamVersion(IDvrStreamManager dvrMgr,  
    java.util.Map queryMap,  
    String baseStreamName)
```

calcBitrate

```
public int calcBitrate(IDvrStreamStore store,  
    int type,  
    long t)
```

isDebug

```
public boolean isDebug()
```

setDebug

```
public void setDebug(boolean debug)
```

getDvrPlaylistRequest

```
public DvrPlaylistRequest getDvrPlaylistRequest(IHTTPStreamerApplicationContext  
appContext,  
    IDvrStreamStore store,  
    java.util.Map queryMap)
```

getDvrPlaylistRequest

```
public DvrPlaylistRequest getDvrPlaylistRequest(IHTTPStreamerApplicationContext  
appContext,  
    java.util.List store,  
    java.util.Map queryMap)
```

com.wowza.wms.dvr Interface IDvrPurgeController

public interface **IDvrPurgeController**
extends

Interface for controlling DVR chunk purging. The purge controller is instantiated using a factory class DvrPurgeControllerFactory.
See Also:

```
com.wowza.wms.dvr.impl.DvrPurgeControllerFactory,  
IDvrPrivateConstants.PROPKEY_PURGE_CONTROL_CLASS
```

Method Summary

long	<code>getCurrentTime()</code> Get current DVR time.
long	<code>getLastPurgeTime()</code> Get the DVR time when the last purge occurred.
void	<code>init(IDvrStreamStore store)</code> Initialize the controller.
boolean	<code>isPurgingEnabled()</code> Is Purging enabled for this controller.
void	<code>setCurrentDvrTime(long newDvrTime)</code> Set the current DVR time and perform purge if necessary.

Methods

init

```
public void init(IDvrStreamStore store)
```

Initialize the controller.

Parameters:

store - the DVR stream store

isPurgingEnabled

```
public boolean isPurgingEnabled()
```

Is Purging enabled for this controller.

Returns:

true if purging is active, false otherwise.

setCurrentDvrTime

```
public void setCurrentDvrTime(long newDvrTime)
```

Set the current DVR time and perform purge if necessary. This method checks the DVR time against its internal rules for purging and performs the purge. It is also responsible for setting the last purge time and the next purge time.

(continued from last page)

Parameters:

newDvrTime

getCurrentTime

```
public long getCurrentTime()
```

Get current DVR time. The store is responsible for setting the DVR time via setCurrentDvrTime.

Returns:

current DVR time.

getLastPurgeTime

```
public long getLastPurgeTime()
```

Get the DVR time when the last purge occurred.

Returns:

DVR time of last purge

com.wowza.wms.dvr Interface IDvrRawChunkProvider

All Subinterfaces:

[IDvrChunkMemoryCache](#)

public interface **IDvrRawChunkProvider**
extends

Interface for providing raw DVR chunks based on a DVR manifest entry.

Method Summary

DvrChunk	retrieveRawChunk (DvrManifestChunkEntry entry) Given the specified manifest entry, return the raw DVR chunk.
----------	--------------------------------------------------------------------------------------------------------------------------------------------------

Methods

retrieveRawChunk

public DvrChunk **retrieveRawChunk**([DvrManifestChunkEntry](#) entry)

Given the specified manifest entry, return the raw DVR chunk.

Parameters:

entry - The DVR manifest entry

Returns:

the DVR chunk or null if not able to return the chunk.

com.wowza.wms.dvr Interface IDvrRecordingListener

public interface **IDvrRecordingListener**
extends

Listener for DVR Recording events.

See Also:

[IDvrStreamManager.addDvrRecordingListener\(IDvrRecordingListener\)](#),
[IDvrStreamManager.removeDvrRecordingListener\(IDvrRecordingListener\)](#)

Method Summary

void	recordingPaused (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback when DVR moves to paused state.
void	recordingReset (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback when DVR gets reset.
void	recordingResumed (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback when DVR moves out of paused state.
void	recordingStarted (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback when DVR moves to recording state.
void	recordingStopped (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback when DVR recording stops
void	timeReset (IDvrStreamManager dvrMgr, IDvrStreamStore store, long oldPacketTime, long oldDvrTime, long newPacketTime, long newDvrTime) Callback when DVR time is adjusted.

Methods

recordingStarted

public void **recordingStarted**([IDvrStreamManager](#) dvrMgr, [IDvrStreamStore](#) store)

Callback when DVR moves to recording state.

Parameters:

dvrMgr - DVR Application Store Manager
store - stream store

recordingPaused

public void **recordingPaused**([IDvrStreamManager](#) dvrMgr, [IDvrStreamStore](#) store)

Callback when DVR moves to paused state.

Parameters:

dvrMgr - DVR Application Store Manager

(continued from last page)

store - stream store

recordingResumed

```
public void recordingResumed(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback when DVR moves out of paused state.

Parameters:

dvrMgr - DVR Application Store Manager

store - stream store

recordingReset

```
public void recordingReset(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback when DVR gets reset. For example, if the incoming stream resets.

Parameters:

dvrMgr - DVR Application Store Manager

store - stream store

recordingStopped

```
public void recordingStopped(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback when DVR recording stops

Parameters:

dvrMgr - DVR Application Store Manager

store - stream store

timeReset

```
public void timeReset(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store,  
    long oldPacketTime,  
    long oldDvrTime,  
    long newPacketTime,  
    long newDvrTime)
```

Callback when DVR time is adjusted.

Parameters:

dvrMgr - DVR Application Store Manager

store - stream store

oldPacketTime - old packet time associated to oldDvrTime

oldDvrTime

newPacketTime - new packet time associated to newDvrTime

newDvrTime

com.wowza.wms.dvr Interface IDvrRecordingsLoader

public interface **IDvrRecordingsLoader**
extends

Interface for loading recordings during DVR Stream Manager initialization.

See Also:

[com.wowza.wms.dvr.impl.DvrRecordingsLoaderFactory](#),
[IDvrConstants.PROPKEY_DVR_RECORDINGS_LOADER_CLASS](#)

Method Summary

void	init (IDvrStreamManager dvrMgr) Initialize recordings loader
void	loadArchivedRecordings () Discover and load archived recording
boolean	shouldLoadStream (String streamName, java.util.SortedSet versions) Should the given archived streams be laoded.
boolean	shouldLoadStreamVersion (String streamName, Integer version, java.util.SortedSet versions) Should the given archived stream of specific version be laoded.

Methods

init

public void **init**([IDvrStreamManager](#) dvrMgr)

Initialize recordings loader

Parameters:

dvrMgr - the DVR Stream Manager

loadArchivedRecordings

public void **loadArchivedRecordings**()

Discover and load archived recording

shouldLoadStream

public boolean **shouldLoadStream**(String streamName,
java.util.SortedSet versions)

Should the given archived streams be laoded. The method contains logic which determines if all versions of the given stream Name should be loaded or not.

Parameters:

streamName - Stream name (unversioned)

versions - sorted set of available versions of this stream

(continued from last page)

Returns:

true if one or more of the streams should be loaded, false otherwise.

shouldLoadStreamVersion

```
public boolean shouldLoadStreamVersion(String streamName,  
    Integer version,  
    java.util.SortedSet versions)
```

Should the given archived stream of specific version be loaded. The method contains logic which determines if all versions of the given stream Name should be loaded or not.

Parameters:

streamName - Stream name (unversioned)

version - the specific version of the stream we are determining if we should load

versions - sorted set of all available versions of this stream

Returns:

true if one or more of the streams should be loaded, false otherwise.

com.wowza.wms.dvr Interface IDvrStoreChunkListener

public interface **IDvrStoreChunkListener**
extends

Listener for DVR Store chunk events.

Note that this listener traffic is very high.

See Also:

[IDvrStreamStore.addDvrChunkListener\(IDvrStoreChunkListener\)](#),
[IDvrStreamStore.removeDvrChunkListener\(IDvrStoreChunkListener\)](#)

Method Summary

void	postChunkAdded (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback after a chunk is written to DVR store
void	postChunksPurged (IDvrStreamManager dvrMgr, IDvrStreamStore store, DvrManifestEntryRangeGroup entries, java.util.List deletedEntries) Callback after DVR store performs a purge
void	preChunkAdded (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback before a chunk is written to DVR store
void	preChunksPurged (IDvrStreamManager dvrMgr, IDvrStreamStore store, DvrManifestEntryRangeGroup entries) Callback before DVR store performs a purge

Methods

preChunkAdded

```
public void preChunkAdded(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback before a chunk is written to DVR store

Parameters:

dvrMgr - the DVR Application Store Manager
store - the stream store

postChunkAdded

```
public void postChunkAdded(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback after a chunk is written to DVR store

Parameters:

dvrMgr - the DVR Application Store Manager
store - the stream store

(continued from last page)

preChunksPurged

```
public void preChunksPurged(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store,  
    DvrManifestEntryRangeGroup entries)
```

Callback before DVR store performs a purge

Parameters:

dvrMgr - the DVR Application Store Manager
store - the stream store
entries - list of DVR chunks to be purged

postChunksPurged

```
public void postChunksPurged(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store,  
    DvrManifestEntryRangeGroup entries,  
    java.util.List deletedEntries)
```

Callback after DVR store performs a purge

Parameters:

dvrMgr - the DVR Application Store Manager
store - the stream store
entries - list of DVR chunks purged
deletedEntries - list of entries deleted

com.wowza.wms.dvr Interface IDvrStoreListener

public interface **IDvrStoreListener**
extends

Listener for DVR Store lifecycle events.

See Also:

[IDvrStreamManager.addDvrStoreListener\(IDvrStoreListener\)](#),
[IDvrStreamManager.removeDvrStoreListener\(IDvrStoreListener\)](#)

Method Summary

void	dvrStreamStorageDeleted (IDvrStreamManager dvrMgr, IDvrStreamStore store, IDvrFileSystem fileSystem, boolean success) Callback after DVR store is deleted from disk.
void	dvrStreamStorageLoaded (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback after DVR store is loaded from disk.
void	dvrStreamStoreCreate (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback after DVR stream store is created.
void	dvrStreamStoreDestroy (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback after DVR stream store is destroyed.
void	dvrStreamStoreInit (IDvrStreamManager dvrMgr, IDvrStreamStore store) Callback after DVR stream store is initialized.

Methods

dvrStreamStoreCreate

```
public void dvrStreamStoreCreate(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback after DVR stream store is created.

Parameters:

dvrMgr - DVR Application Store Manager
store - stream store

dvrStreamStoreInit

```
public void dvrStreamStoreInit(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback after DVR stream store is initialized.

Parameters:

dvrMgr - DVR Application Store Manager
store - stream store

(continued from last page)

dvrStreamStoreDestroy

```
public void dvrStreamStoreDestroy(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback after DVR stream store is destroyed.

Parameters:

dvrMgr - DVR Application Store Manager

store - stream store

dvrStreamStorageLoaded

```
public void dvrStreamStorageLoaded(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store)
```

Callback after DVR store is loaded from disk.

Parameters:

dvrMgr - DVR Application Store Manager

store - stream store

dvrStreamStorageDeleted

```
public void dvrStreamStorageDeleted(IDvrStreamManager dvrMgr,  
    IDvrStreamStore store,  
    IDvrFileSystem fileSystem,  
    boolean success)
```

Callback after DVR store is deleted from disk.

Parameters:

dvrMgr - DVR Application Store Manager

store

fileSystem - stream store file system

success - whether delete succeeded or failed

com.wowza.wms.dvr Interface IDvrStreamManager

All Superinterfaces:

[ILiveStreamPacketizer](#)

public interface **IDvrStreamManager**

extends [ILiveStreamPacketizer](#)

DVR Stream manager. Manages a live stream and associated DVR stores.

Method Summary

void	addDvrRecordingListener (IDvrRecordingListener listener) Add listener to DVR recording events.
void	addDvrStoreListener (IDvrStoreListener listener) Add listener to DVR store lifecycle events.
void	addManifestEntries (String vStreamName, java.util.List entries) Add to stream stores manifest.
boolean	canRecord () Is this stream able to record.
void	deleteArchivedStore (String vStreamName) Delete archived stream store.
String	getArchiveStrategy () Get the DVR archive strategy.
String	getContextStr () Get stream context string, useful for logging.
IDvrStreamStore	getDefaultStreamingStore () Get the store to be used for streaming.
String	getDvrFileSystemClass () Get the class used for the DVR file system.
String	getDvrStorageDir () Get the storage directory.
int	getDvrStorageWindowSeconds () Get DVR window size.
DvrBaseEncryptionInfo Delegate	getEncryptionDelegate () Get the encryption delegate for providing streaming side encryption info objects.
String	getEncryptionRepeaterSharedSecret () Get the DVR encryption shared secret.
IDvrStreamStore	getHighestVersionedStore () Return stream store that is highest known version.

void	<u>getInitialRepeaterItems</u> (java.util.List items) Get initial repeater items to send to repeater receiver.
int	<u>getMinimumAvailableChunks</u> () Return number of chunks that must be available to stream.
String	<u>getPacketizerName</u> () Get live stream packetizer name.
<u>IDvrStreamStore</u>	<u>getRecordingStreamStore</u> () Get current recording store
void	<u>getRepeaterItemsDvr</u> (java.util.List items, long lastSeq)
String	<u>getStreamBaseName</u> () Get input streamName (no version info).
<u>IDvrStreamStore</u>	<u>getStreamStore</u> (String vStreamName) Given a stream name containing version info, return the associated stream store.
java.util.List	<u>getStreamStores</u> () Get list of all stream stores known to this stream manager.
<u>IDvrStreamVersionHandler</u>	<u>getStreamVersionHandler</u> () Get the stream version handler object.
void	<u>initialManifest</u> (String vStreamName, <u>IDvrManifest</u> manifest)
boolean	<u>isRecording</u> () Is this stream currently recording.
boolean	<u>isRecordingPaused</u> () Is this stream currently paused from recording.
<u>IDvrStreamStore</u>	<u>loadArchivedStore</u> (String vStreamName, DvrManifestHolder manifestHolder) Load archived stream store.
void	<u>notifyDvrStreamStorageDeleted</u> (<u>IDvrStreamStore</u> store, IDvrFileSystem FileSystem, boolean success)
void	<u>notifyDvrStreamStoreCreate</u> (<u>IDvrStreamStore</u> store)
void	<u>notifyDvrStreamStoreDestroy</u> (<u>IDvrStreamStore</u> store)
void	<u>notifyDvrStreamStoreInit</u> (<u>IDvrStreamStore</u> store)
void	<u>notifyDvrStreamStoreLoaded</u> (<u>IDvrStreamStore</u> store)
void	<u>notifyTimeReset</u> (<u>IDvrStreamStore</u> store, long oldPacketTime, long oldDvrTime, long newPacketTime, long newDvrTime)
<u>IDvrStreamStore</u>	<u>pauseRecording</u> () Request that stream recording pause.

void	<u>purgeManifestEntries</u> (String vStreamName, <u>DvrManifestEntryRangeGroup</u> rangeGroup) Purge entries from store
void	<u>removeDvrRecordingListener</u> (<u>IDvrRecordingListener</u> listener) Remove listener to DVR recording events.
void	<u>removeDvrStoreListener</u> (<u>IDvrStoreListener</u> listener) Remove listener of DVR store lifecycle events.
void	<u>resetStream</u> () Reset the stream.
<u>IDvrStreamStore</u>	<u>resumeRecording</u> () Request that stream recording resume.
void	<u>setDefaultStreamingStore</u> (<u>IDvrStreamStore</u> store) Set the store to be used for streaming.
void	<u>setRecordingStreamStore</u> (<u>IDvrStreamStore</u> store) Set the store used for recording.
void	<u>setStreamVersionHandler</u> (<u>IDvrStreamVersionHandler</u> handler) Set the stream version handler object.
<u>IDvrStreamStore</u>	<u>startRecording</u> () Request that stream recording start.
<u>IDvrStreamStore</u>	<u>stopRecording</u> () Request that stream recording stop.
long	<u>storeChunks</u> (int vDuration, DvrPacketHolder vPackets, int aDuration, DvrPacketHolder aPackets, int dDuration, DvrPacketHolder dPackets)
boolean	<u>storeOnMetadata</u> (long pt, <u>AMFPacket</u> metaPacket)

Methods inherited from interface [com.wowza.wms.stream.livepacketizer.ILiveStreamPacketizer](#)

[getApplicationInstance](#), [getLiveStreamPacketizerId](#), [getProperties](#), [getRepeaterLastSequence](#), [getStartStream](#), [handlePacket](#), [init](#), [isActive](#), [isPacketizeAudio](#), [isPacketizeData](#), [isPacketizeVideo](#), [isRepeaterEdge](#), [resetStream](#), [setLiveStreamPacketizerId](#), [setPacketizeAudio](#), [setPacketizeData](#), [setPacketizeVideo](#), [setRepeaterEdge](#), [shutdown](#), [startStream](#), [touch](#)

Methods

getContextStr

public String **getContextStr**()

Get stream context string, useful for logging.

Returns:

stream context string

(continued from last page)

getStreamBaseName

```
public String getStreamBaseName()
```

Get input streamName (no version info).

Returns:

unversioned incoming stream name

getStreamStore

```
public IDvrStreamStore getStreamStore(String vStreamName)
```

Given a stream name containing version info, return the associated stream store.

Parameters:

vStreamName - versioned stream name

Returns:

store or null

getPacketizerName

```
public String getPacketizerName()
```

Get live stream packetizer name.

Returns:

live stream packetizer name

getStreamStores

```
public java.util.List getStreamStores()
```

Get list of all stream stores known to this stream manager.

Returns:

list of stream stores.

getHighestVersionedStore

```
public IDvrStreamStore getHighestVersionedStore()
```

Return stream store that is highest known version.

Returns:

stream store

getMinimumAvailableChunks

```
public int getMinimumAvailableChunks()
```

Return number of chunks that must be available to stream.

Returns:

minimum available chunks

(continued from last page)

setRecordingStreamStore

```
public void setRecordingStreamStore(IDvrStreamStore store)
```

Set the store used for recording.

Parameters:

store - stream store, or null

getRecordingStreamStore

```
public IDvrStreamStore getRecordingStreamStore()
```

Get current recording store

Returns:

current recording store (may be null)

setDefaultStreamingStore

```
public void setDefaultStreamingStore(IDvrStreamStore store)
```

Set the store to be used for streaming.

Parameters:

store - store to stream.

getDefaultStreamingStore

```
public IDvrStreamStore getDefaultStreamingStore()
```

Get the store to be used for streaming.

Returns:

store to stream.

getDvrStorageWindowSeconds

```
public int getDvrStorageWindowSeconds()
```

Get DVR window size.

Returns:

window size in seconds (0 means infinite window size)

getDvrStorageDir

```
public String getDvrStorageDir()
```

Get the storage directory.

Returns:

storage directory

getDvrFileSystemClass

```
public String getDvrFileSystemClass()
```

(continued from last page)

Get the class used for the DVR file system.

Returns:

fully qualified class name

getArchiveStrategy

```
public String getArchiveStrategy()
```

Get the DVR archive strategy.

Returns:

The archive strategy

getEncryptionRepeaterSharedSecret

```
public String getEncryptionRepeaterSharedSecret()
```

Get the DVR encryption shared secret.

Returns:

shared secret.

getEncryptionDelegate

```
public DvrBaseEncryptionInfoDelegate getEncryptionDelegate()
```

Get the encryption delegate for providing streaming side encryption info objects.

Returns:

delegate

getStreamVersionHandler

```
public IDvrStreamVersionHandler getStreamVersionHandler()
```

Get the stream version handler object.

Returns:

stream version handler object.

setStreamVersionHandler

```
public void setStreamVersionHandler(IDvrStreamVersionHandler handler)
```

Set the stream version handler object. Must be called after the stream manager is created and before it is initialized.

Parameters:

handler - stream version handler object.

resetStream

```
public void resetStream()
```

Reset the stream.

(continued from last page)

canRecord

```
public boolean canRecord()
```

Is this stream able to record.

Returns:

true if this stream is recordable.

isRecording

```
public boolean isRecording()
```

Is this stream currently recording. If this stream is not recordable, the method returns false.

Returns:

true if has a recording stream and it is recording.

isRecordingPaused

```
public boolean isRecordingPaused()
```

Is this stream currently paused from recording. If this stream is not recording and not paused, the method returns false.

Returns:

true if has a recording is paused.

startRecording

```
public IDvrStreamStore startRecording()
```

Request that stream recording start.

Used internally. Clients should call [ILiveStreamDvrRecorder.startRecording\(\)](#). Note that this call places the DVR stream store in the recording state. If the stream store is in the paused state, DVR recording will not occur.

If there is not currently a stream store for recording, one will attempt to be created. A successful start will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingStarted\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Success only occurs if the stream canRecord [IDvrStreamStore.canRecord\(\)](#) and the stream is not already in the recording state.

Returns:

store if successful. null otherwise.

stopRecording

```
public IDvrStreamStore stopRecording()
```

Request that stream recording stop.

Used internally. Clients should call [ILiveStreamDvrRecorder.stopRecording\(\)](#). Note that this call places the DVR stream in the *not* recording state.

A successful stop will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingStopped\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Success only occurs if the stream is already in the recording state [IDvrStreamStore.isRecording\(\)](#).

Returns:

store if successful. null otherwise.

pauseRecording

```
public IDvrStreamStore pauseRecording()
```

Request that stream recording pause.

Used internally. Clients should call [ILiveStreamDvrRecorder.pauseRecording\(\)](#). The stream does not have to be actively recording to be paused. For example, it could be paused before packets start flowing.

A successful pause will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingPaused\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Returns:

store if successful. null otherwise.

resumeRecording

```
public IDvrStreamStore resumeRecording()
```

Request that stream recording resume.

Used internally. Clients should call [ILiveStreamDvrRecorder.resumeRecording\(\)](#). The stream does not have to be actively recording to be resumed. For example, it could have been paused before the stream started, and this call would move it out of the paused state.

A successful resume will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingResumed\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Returns:

store if successful. null otherwise.

loadArchivedStore

```
public IDvrStreamStore loadArchivedStore(String vStreamName,  
                                         DvrManifestHolder manifestHolder)
```

Load archived stream store.

Parameters:

vStreamName - versioned stream Name (e.g. myStream.0)

manifestHolder - manifest holder containing list of manifest properties

Returns:

stream store

deleteArchivedStore

```
public void deleteArchivedStore(String vStreamName)
```

Delete archived stream store.

Parameters:

vStreamName - versioned stream Name (e.g. myStream.0)

addManifestEntries

```
public void addManifestEntries(String vStreamName,  
                               java.util.List entries)
```

Add to stream stores manifest.

(continued from last page)

Parameters:

vStreamName - versioned stream Name (e.g. myStream.0)
entries - list of manifest entries.

purgeManifestEntries

```
public void purgeManifestEntries(String vStreamName,  
    DvrManifestEntryRangeGroup rangeGroup)
```

Purge entries from store

Parameters:

vStreamName - versioned stream Name (e.g. myStream.0)
rangeGroup - set of ranges for purging

storeChunks

```
public long storeChunks(int vDuration,  
    DvrPacketHolder vPackets,  
    int aDuration,  
    DvrPacketHolder aPackets,  
    int dDuration,  
    DvrPacketHolder dPackets)
```

storeOnMetadata

```
public boolean storeOnMetadata(long pt,  
    AMFPacket metaPacket)
```

addDvrStoreListener

```
public void addDvrStoreListener(IDvrStoreListener listener)
```

Add listener to DVR store lifecycle events.

Parameters:

listener - listener

removeDvrStoreListener

```
public void removeDvrStoreListener(IDvrStoreListener listener)
```

Remove listener of DVR store lifecycle events.

Parameters:

listener - listener

addDvrRecordingListener

```
public void addDvrRecordingListener(IDvrRecordingListener listener)
```

Add listener to DVR recording events.

Parameters:

listener - listener

removeDvrRecordingListener

```
public void removeDvrRecordingListener(IDvrRecordingListener listener)
```

Remove listener to DVR recording events.

Parameters:

listener - listener

notifyDvrStreamStoreCreate

```
public void notifyDvrStreamStoreCreate(IDvrStreamStore store)
```

notifyDvrStreamStoreInit

```
public void notifyDvrStreamStoreInit(IDvrStreamStore store)
```

notifyDvrStreamStoreDestroy

```
public void notifyDvrStreamStoreDestroy(IDvrStreamStore store)
```

notifyDvrStreamStoreLoaded

```
public void notifyDvrStreamStoreLoaded(IDvrStreamStore store)
```

notifyDvrStreamStorageDeleted

```
public void notifyDvrStreamStorageDeleted(IDvrStreamStore store,  
    IDvrFileSystem fileSystem,  
    boolean success)
```

notifyTimeReset

```
public void notifyTimeReset(IDvrStreamStore store,  
    long oldPacketTime,  
    long oldDvrTime,  
    long newPacketTime,  
    long newDvrTime)
```

getInitialRepeaterItems

```
public void getInitialRepeaterItems(java.util.List items)
```

(continued from last page)

Get initial repeater items to send to repeater receiver.

When an edge initially requests the items, instead of sending the entire manifest and all repeater items up until that point, the player sends a `DvrRepeaterHolder.REPEATER_INITIAL_MANIFEST` event followed by several `DvrRepeaterHolder.REPEATER_ADD_MANIFEST_ENTRIES` events.

This allows us to not bother sending any purged manifest entries.

Parameters:

items

getRepeaterItemsDvr

```
public void getRepeaterItemsDvr(java.util.List items,  
                                long lastSeq)
```

initialManifest

```
public void initialManifest(String vStreamName,  
                             IDvrManifest manifest)
```

com.wowza.wms.dvr Interface IDvrStreamStore

public interface **IDvrStreamStore**
extends

Method Summary

void	<u>addDvrChunkListener</u> (<u>IDvrStoreChunkListener</u> listener) Add (very fine) listener for chunk events.
void	<u>addManifestEntries</u> (java.util.List entries)
boolean	<u>canPlay</u> () Is this store capable of playing.
boolean	<u>canRecord</u> () Is this store capable of recording.
<u>IApplicationInstance</u>	<u>getAppInstance</u> () Get associated application instance.
<u>IDvrChunker</u>	<u>getChunker</u> ()
long	<u>getClosestStartTime</u> (int type, long t)
String	<u>getContextStr</u> () Get stream context string, useful for logging.
DvrChunk	<u>getDvrChunkAtTime</u> (int fragmentType, long t)
DvrChunk	<u>getDvrChunkByIndex</u> (int fragmentType, int index)
<u>IDvrStreamManager</u>	<u>getDvrManager</u> () Get DVR Stream Manager
IDvrFileSystem	<u>getFileSystem</u> ()
<u>IDvrManifest</u>	<u>getManifest</u> () Get manifest
<u>WMSProperties</u>	<u>getProperties</u> () Get stream store properties.
<u>IDvrPurgeController</u>	<u>getPurgeController</u> () Get purge controller for stream store.
java.util.List	<u>getRecordedEntriesWithLimit</u> (int fragmentType, long t, int limit)
<u>DvrManifestEntry</u>	<u>getRecordedEntryByIndex</u> (int fragmentType, int index)

String	<code>getStreamName()</code> Get versioned stream name.
DvrTimeMapper	<code>getTimeMapper()</code> Get time mapper, which maps between DVR, real and packet time.
boolean	<code>hasAudio()</code> Does this store have audio.
boolean	<code>hasData()</code> Does this store have data.
boolean	<code>hasEncryption()</code> Does this store contain encryption information
boolean	<code>hasOnMetadata()</code> Does this store have on metadata.
boolean	<code>hasVideo()</code> Does this store have video.
void	<code>init()</code> Initialize DVR stream store.
boolean	<code>isRecording()</code> Is store currently recording.
boolean	<code>isRecordingPaused()</code> Is store currently paused while recording.
boolean	<code>pauseRecording()</code> Request that stream recording pause.
void	<code>purgeEntries(DvrManifestEntryRangeGroup rangeGroup)</code> Purge entries from store
void	<code>removeDvrChunkListener(IDvrStoreChunkListener listener)</code> Remove (very fine) listener for chunk events.
void	<code>reset()</code>
boolean	<code>resumeRecording()</code> Request that stream recording resume.
void	<code>setCanPlay(boolean canPlay)</code> Set the Stream Stores ability to play.
void	<code>setCanRecord(boolean canRecord)</code> Set the Stream Stores ability to record.
void	<code>setHasEncryption(boolean hasEncryption)</code> Set whether the store has encryption.
void	<code>shutdown()</code>
boolean	<code>startRecording()</code> Request that recording start.

boolean	stopRecording() Request that stream recording stop.
long	storeChunks() (int vDuration, DvrPacketHolder vPackets, int aDuration, DvrPacketHolder aPackets, int dDuration, DvrPacketHolder dPackets)
boolean	storeOnMetadata() (long pt, AMFPacket metaPacket)

Methods

init

```
public void init()
```

Initialize DVR stream store.

reset

```
public void reset()
```

shutdown

```
public void shutdown()
```

getProperties

```
public WMSProperties getProperties()
```

Get stream store properties.

Returns:

properties

getStreamName

```
public String getStreamName()
```

Get versioned stream name.

Returns:

(versioned) stream name

getContextStr

```
public String getContextStr()
```

Get stream context string, useful for logging.

Returns:

stream context string

getDvrManager

```
public IDvrStreamManager getDvrManager()
```

Get DVR Stream Manager

Returns:

DVR Stream Manager

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get associated application instance.

Returns:

application instance.

getManifest

```
public IDvrManifest getManifest()
```

Get manifest

Returns:

manifest

getTimeMapper

```
public DvrTimeMapper getTimeMapper()
```

Get time mapper, which maps between DVR, real and packet time.

Returns:

time mapper

getPurgeController

```
public IDvrPurgeController getPurgeController()
```

Get purge controller for stream store.

Returns:

purge controller

getFileSystem

```
public IDvrFileSystem getFileSystem()
```

getChunker

```
public IDvrChunker getChunker()
```

canRecord

```
public boolean canRecord()
```

Is this store capable of recording.

Returns:

true if store can record

setCanRecord

```
public void setCanRecord(boolean canRecord)
```

Set the Stream Stores ability to record.

Note: Must be called when stream is not recording.

Parameters:

canRecord

canPlay

```
public boolean canPlay()
```

Is this store capable of playing.

Returns:

true if store can play

setCanPlay

```
public void setCanPlay(boolean canPlay)
```

Set the Stream Stores ability to play.

Note: Must be called when stream is not playing.

Parameters:

canPlay

setHasEncryption

```
public void setHasEncryption(boolean hasEncryption)
```

Set whether the store has encryption. Used internally.

Note: Must be called when stream is not playing.

Parameters:

hasEncryption - if store has encryption

hasEncryption

```
public boolean hasEncryption()
```

Does this store contain encryption information

Returns:

(continued from last page)

true if store contains encryption

hasVideo

```
public boolean hasVideo( )
```

Does this store have video.

Returns:

true if store contains video, false otherwise.

hasAudio

```
public boolean hasAudio( )
```

Does this store have audio.

Returns:

true if store contains audio, false otherwise.

hasData

```
public boolean hasData( )
```

Does this store have data.

Returns:

true if store contains data, false otherwise.

hasOnMetadata

```
public boolean hasOnMetadata( )
```

Does this store have on metadata.

Returns:

true if store contains on metadata, false otherwise.

startRecording

```
public boolean startRecording( )
```

Request that recording start.

Used internally. Clients should call [ILiveStreamDvrRecorder.startRecording\(\)](#).

Success occurs if the stream canRecord [canRecord\(\)](#) and the stream is not already in the recording state [isRecording\(\)](#).

Returns:

true if successful.

pauseRecording

```
public boolean pauseRecording( )
```

Request that stream recording pause.

Used internally. Clients should call [ILiveStreamDvrRecorder.pauseRecording\(\)](#).

Success occurs if the stream is not already paused.

(continued from last page)

Returns:

true if successful.

resumeRecording

```
public boolean resumeRecording( )
```

Request that stream recording resume.

Used internally. Clients should call [ILiveStreamDvrRecorder.resumeRecording\(\)](#).

Success occurs if the stream was previously paused.

Returns:

true if successful.

stopRecording

```
public boolean stopRecording( )
```

Request that stream recording stop. This shuts down saving of chunks

Used internally. Clients should call [ILiveStreamDvrRecorder.stopRecording\(\)](#).

Success only occurs if the stream is already in the recording state [isRecording\(\)](#).

Returns:

true if successful.

isRecordingPaused

```
public boolean isRecordingPaused( )
```

Is store currently paused while recording.

Returns:

true if recording is paused.

isRecording

```
public boolean isRecording( )
```

Is store currently recording.

Returns:

true if recording

storeChunks

```
public long storeChunks(int vDuration,  
    DvrPacketHolder vPackets,  
    int aDuration,  
    DvrPacketHolder aPackets,  
    int dDuration,  
    DvrPacketHolder dPackets)
```

(continued from last page)

storeOnMetadata

```
public boolean storeOnMetadata(long pt,  
    AMFPacket metaPacket)
```

purgeEntries

```
public void purgeEntries(DvrManifestEntryRangeGroup rangeGroup)
```

Purge entries from store

Parameters:

rangeGroup - s set of ranges for purging

addManifestEntries

```
public void addManifestEntries(java.util.List entries)
```

addDvrChunkListener

```
public void addDvrChunkListener(IDvrStoreChunkListener listener)
```

Add (very fine) listener for chunk events.

Parameters:

listener - listener

removeDvrChunkListener

```
public void removeDvrChunkListener(IDvrStoreChunkListener listener)
```

Remove (very fine) listener for chunk events.

Parameters:

listener - listener

getRecordedEntriesWithLimit

```
public java.util.List getRecordedEntriesWithLimit(int fragmentType,  
    long t,  
    int limit)
```

getRecordedEntryByIndex

```
public DvrManifestEntry getRecordedEntryByIndex(int fragmentType,  
    int index)
```

getDvrChunkByIndex

```
public DvrChunk getDvrChunkByIndex(int fragmentType,  
    int index)
```

(continued from last page)

getDvrChunkAtTime

```
public DvrChunk getDvrChunkAtTime(int fragmentType,  
    long t)
```

getClosestStartTime

```
public long getClosestStartTime(int type,  
    long t)
```

com.wowza.wms.dvr Interface IDvrStreamVersionHandler

All Known Implementing Classes:
[DefaultDvrStreamVersionHandler](#)

public interface **IDvrStreamVersionHandler**
 extends

Callback to manage (archival) versions of DVR stream stores

Method Summary

IDvrStreamStore	determineExistingStoreForPlaying (IDvrStreamManager dvrManager, String baseStreamName) When a session requests a stream store w/o specifying the version, we need gto determine the version of the stream to store.
IDvrStreamStore	determineExistingStoreForRecording (IDvrStreamManager dvrManager, String baseStreamName) After a set of versioned streams are loaded from disk, one of them may be designated the stream that will be recorded to (i.e.
String	getArchiveStrategy (IDvrStreamManager dvrManager, String baseStreamName) Determine the archive strategy for a given set of streams.
boolean	handleArchivedStream (IDvrStreamManager dvrManager, String baseStreamName, String version, java.util.SortedSet versions, DvrManifestHolder manifest) When a stream group inits, the file system is checked for older versions of the streams.
boolean	shouldDeleteArchivedStream (IDvrStreamManager dvrManager, IDvrStreamStore store) Determine if a given stream store version should be deleted.
boolean	shouldLoadArchivedStream (IDvrStreamManager dvrManager, String baseStreamName, String version, java.util.SortedSet versions, DvrManifestHolder manifest) Determine if a given stream store version should be loaded into WMS.

Methods

determineExistingStoreForRecording

```
public IDvrStreamStore determineExistingStoreForRecording(IDvrStreamManager
dvrManager,
    String baseStreamName)
```

After a set of versioned streams are loaded from disk, one of them may be designated the stream that will be recorded to (i.e. append mode).

The default implementation says that if append mode, then the highest versioned stream that has canRecord set to true is used. But this API, allows for a more detailed logic.

Parameters:

dvrManager - The DVR Stream Manager

(continued from last page)

baseStreamName - The base stream name (no version info). e.g. myStream

Returns:

stream store to append to, null if no stream in the stream group is to be appended to.

See Also:

[DefaultDvrStreamVersionHandler](#)

determineExistingStoreForPlaying

```
public IDvrStreamStore determineExistingStoreForPlaying(IDvrStreamManager dvrManager,
String baseStreamName)
```

When a session requests a stream store w/o specifying the version, we need to determine the version of the stream to store.

The default implementation first checks the recording stream. If it 'canPlay()', it is returned. Otherwise, the highest versioned stream that canRecord set to true is used.

Parameters:

dvrManager - The DVR Stream Manager

baseStreamName - The base stream name (no version info). e.g. myStream

Returns:

stream store to stream, null if no stream in the stream group can be played.

See Also:

[DefaultDvrStreamVersionHandler](#)

getArchiveStrategy

```
public String getArchiveStrategy(IDvrStreamManager dvrManager,
String baseStreamName)
```

Determine the archive strategy for a given set of streams.

Typically, this returns the archive strategy as specified in Application.xml, but this API provides a hook for more detailed logic in determining the strategy.

Parameters:

dvrManager - The DVR App Instance Manager

baseStreamName - The base stream name (no version info). e.g. myStream

Returns:

the archive strategy

See Also:

[DefaultDvrStreamVersionHandler](#)

[IDvrConstants.DVR_STORAGE_STRATEGY_APPEND](#)

[IDvrConstants.DVR_STORAGE_STRATEGY_DELETE](#)

[IDvrConstants.DVR_STORAGE_STRATEGY_VERSION](#)

handleArchivedStream

```
public boolean handleArchivedStream(IDvrStreamManager dvrManager,
String baseStreamName,
String version,
java.util.SortedSet versions,
DvrManifestHolder manifest)
```

(continued from last page)

When a stream group inits, the file system is checked for older versions of the streams. This method is called to handle the streams.

Typically, 3 things can happen: The stream is ignored, loaded, or deleted.

Parameters:

dvrManager - The DVR Stream Manager
baseStreamName - The base stream name (no version info). e.g. myStream
version - The version of the stream to be loaded.
versions - A sorted set of all the versions that are attempting to be loaded
manifest - The main manifest info of the stream

Returns:

true if handled in some manner, false if ignored (unhandled)

See Also:

[DefaultDvrStreamVersionHandler](#)

shouldLoadArchivedStream

```
public boolean shouldLoadArchivedStream(IDvrStreamManager dvrManager,  
    String baseStreamName,  
    String version,  
    java.util.SortedSet versions,  
    DvrManifestHolder manifest)
```

Determine if a given stream store version should be loaded into WMS.

Parameters:

dvrManager - The DVR Stream Manager
baseStreamName - The base stream name (no version info). e.g. myStream
version - The version of the stream to be loaded.
versions - A sorted set of all the versions that are attempting to be loaded
manifest - The main manifest info of the stream

Returns:

true if should be loaded. false if not.

See Also:

[DefaultDvrStreamVersionHandler](#)

shouldDeleteArchivedStream

```
public boolean shouldDeleteArchivedStream(IDvrStreamManager dvrManager,  
    IDvrStreamStore store)
```

Determine if a given stream store version should be deleted.

Parameters:

dvrManager - The DVR Stream Manager
store - The DVR store

Returns:

true if should be deleted. false if not.

See Also:

[DefaultDvrStreamVersionHandler](#)

com.wowza.wms.dvr Interface IDvrTextReader

public interface **IDvrTextReader**
extends [ITextReader](#)

Method Summary

void	init (IApplicationInstance appInstance, IMediaStream stream, IDvrFileSystem fileSystem, String artifactName)
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods inherited from interface [com.wowza.io.ITextReader](#)

[close](#), [exists](#), [getBasePath](#), [getMediaName](#), [getPath](#), [init](#), [isOpen](#), [lastModified](#), [length](#), [open](#), [read](#), [ready](#)

Methods

init

```
public void init(IApplicationInstance appInstance,  
                IMediaStream stream,  
                IDvrFileSystem fileSystem,  
                String artifactName)
```

com.wowza.wms.dvr Interface IDvrTextWriter

public interface **IDvrTextWriter**
extends `ITextWriter`

Method Summary

void	<code>init(IApplicationInstance appInstance, IMediaStream stream, IDvrFileSystem fileSystem, String artifactName)</code>
------	--------------------------------------------------------------------------------------------------------------------------

Methods inherited from interface `com.wowza.io.ITextWriter`

`close`, `exists`, `getBasePath`, `getMediaName`, `getPath`, `init`, `isAppend`, `isOpen`, `lastModified`, `length`, `open`, `setAppend`, `write`, `write`, `write`, `write`

Methods

init

```
public void init(IApplicationInstance appInstance,  
    IMediaStream stream,  
    IDvrFileSystem fileSystem,  
    String artifactName)
```

Package

com.wowza.wms.http

com.wowza.wms.http Class HTTPProvider2Base

java.lang.Object

└-com.wowza.wms.http.HTTPProvider2Base

All Implemented Interfaces:

[IHTTPProvider2](#)

public abstract class **HTTPProvider2Base**
extends Object
implements [IHTTPProvider2](#)

HTTPProvider2Base: base class for implementing HTTP Providers.

Simple HTTPProvider class

```
public class HTTPHelloWowza extends HTTPProvider2Base
{
    public void onHTTPRequest(IVHost vhost, IHTTPRequest req, IHTTPResponse resp)
    {
        if (!doHTTPAuthentication(vhost, req, resp))
            return;

        String retStr = "<head><title>Hello Wowza</title></head><body>Hello
Wowza</body>";
        try
        {
            OutputStream out = resp.getOutputStream();
            byte[] outBytes = retStr.getBytes();
            out.write(outBytes);
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(HTTPServerVersion.class).error("HTMLServerVersion:
"+e.toString());
        }
    }
}
```

Field Summary

protected	authenticateHandler
protected	authenticateHTTPProviderHandler
protected	authenticationMethod
protected	filters
protected	properties
protected	requestFilters

Constructor Summary

public	HTTPProvider2Base()
--------	-------------------------------------

Method Summary

boolean	canHandle (String path) Return true if can handle the request
boolean	doHTTPAuthentication (IVHost vhost, IHTTPRequest req, IHTTPResponse resp) Handle authentication request
String	getAuthenticationMethod () Get the authentication method: digest, basic, none...
String	getPath (IHTTPRequest req, boolean removeFilter) Get the request path
String	getRequestFilters () Get the request filter
void	init () Initialize the HTTPProvider
void	onBind (IVHost vhost, HostPort hostPort) Called when bind is called on port
void	onUnbind (IVHost vhost, HostPort hostPort) Called when unbind is called on port
void	setAuthenticationMethod (String authenticationMethod) Set authentication method: digest, basic, none...
void	setProperties (WMSProperties properties) Set properties
void	setRequestFilters (String requestFilters) Set the request filter

Methods inherited from class `java.lang.Object`

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.http.IHTTPProvider2](#)

[canHandle](#), [getAuthenticationMethod](#), [getRequestFilters](#), [init](#), [setAuthenticationMethod](#), [setRequestFilters](#)

Methods inherited from interface [com.wowza.wms.http.IHTTPProvider](#)

[onBind](#), [onHTTPRequest](#), [onUnbind](#), [setProperties](#)

Fields

properties

protected com.wowza.wms.application.WMSProperties **properties**

filters

protected java.util.List **filters**

requestFilters

protected java.lang.String **requestFilters**

authenticateHandler

protected com.wowza.wms.authentication.IAuthenticate **authenticateHandler**

authenticateHTTPProviderHandler

protected com.wowza.wms.authentication.IAuthenticateHTTPProvider
authenticateHTTPProviderHandler

authenticationMethod

protected java.lang.String **authenticationMethod**

Constructors

(continued from last page)

HTTPProvider2Base

```
public HTTPProvider2Base()
```

Methods

init

```
public void init()
```

Initialize the HTTPProvider

canHandle

```
public boolean canHandle(String path)
```

Return true if can handle the request

Parameters:

path - request path

Returns:

true, if can handle the request

getPath

```
public String getPath(IHTTPRequest req,  
    boolean removeFilter)
```

Get the request path

Parameters:

req - request

removeFilter - set to true to remove filter part of URL

Returns:

path

setRequestFilters

```
public void setRequestFilters(String requestFilters)
```

Set the request filter

Parameters:

requestFilters - request filter

getRequestFilters

```
public String getRequestFilters()
```

Get the request filter

Returns:

request filter

setProperty

```
public void setProperty(WMSProperties properties)
```

Set properties

Parameters:

properties - properties

onBind

```
public void onBind(IVHost vhost,  
    HostPort hostPort)
```

Called when bind is called on port

Parameters:

vhost - vhost

hostPort - host port

onUnbind

```
public void onUnbind(IVHost vhost,  
    HostPort hostPort)
```

Called when unbind is called on port

Parameters:

vhost - vhost

hostPort - host port

getAuthenticationMethod

```
public String getAuthenticationMethod()
```

Get the authentication method: digest, basic, none...

Returns:

authentication method

setAuthenticationMethod

```
public void setAuthenticationMethod(String authenticationMethod)
```

Set authentication method: digest, basic, none...

Parameters:

authenticationMethod - authentication method

doHTTPAuthentication

```
public boolean doHTTPAuthentication(IVHost vhost,  
    HttpRequest req,  
    HttpResponse resp)
```

Handle authentication request

Parameters:

(continued from last page)

vhost - vhost
req - request
resp - response

Returns:

true, if request should be handled by the HTTPProvider subclass

com.wowza.wms.http Interface IHTTPProvider

All Subinterfaces:

[IHTTPProvider2](#)

public interface **IHTTPProvider**
extends

IHTTPProvider: HTTP provider class for a given HostPort definition. Receive all HTTP requests that are not RTMPT requests. See IHTTPProvider2 for the extended version of this interface.

Method Summary

void	onBind (IVHost vhost, HostPort hostPort) Triggered after hostPort binds to socket
void	onHTTPRequest (IVHost vhost, IHTTPRequest req, IHTTPResponse resp) Triggered for each HTTP request to the given hostPort that is not an RTMPT request.
void	onUnbind (IVHost vhost, HostPort hostPort) Triggered after hostPort unbinds
void	setProperties (WMSProperties properties) Called to provide properties set in configuration files

Methods

onBind

```
public void onBind(IVHost vhost,  
                   HostPort hostPort)
```

Triggered after hostPort binds to socket

Parameters:

vhost - parent vhost
hostPort - host port definition

onHTTPRequest

```
public void onHTTPRequest(IVHost vhost,  
                           IHTTPRequest req,  
                           IHTTPResponse resp)
```

Triggered for each HTTP request to the given hostPort that is not an RTMPT request.

Parameters:

vhost - parent vhost
req - HTML request object
resp - HTML response object

onUnbind

```
public void onUnbind(IVHost vhost,  
    HostPort hostPort)
```

Triggered after hostPort unbinds

Parameters:

vhost - parent vhost

hostPort - host port definition

setProperties

```
public void setProperties(WMSProperties properties)
```

Called to provide properties set in configuration files

com.wowza.wms.http Interface IHTTPProvider2

All Superinterfaces:

[IHTTPProvider](#)

All Known Implementing Classes:

[HTTPProvider2Base](#)

public interface **IHTTPProvider2**
extends [IHTTPProvider](#)

IHTTPProvider2: Extension of IHTTPProvider that adds support for multiple HTTPProviders attached to a single HostPort along with authentication. Multiple HTTPProviders can be added to a HostPort definition. They are configured as follows:

```
<HTTPProvider>
  <BaseClass>com.wowza.wms.http.HTTPServerVersion</BaseClass>
  <RequestFilters>*serverversion</RequestFilters>
  <AuthenticationMethod>none</AuthenticationMethod>
</HTTPProvider>
```

Below is an sample implementation of the HTTPServerVersion provider:

```

import java.io.*;

import com.wowza.wms.server.*;
import com.wowza.wms.stream.*;
import com.wowza.wms.vhost.*;
import com.wowza.wms.logging.*;

public class HTTPServerVersion extends HTTPProvider2Base
{
    public void onHTTPRequest(IVHost vhost, IHTTPRequest req, IHTTPResponse resp)
    {
        if (!doHTTPAuthentication(vhost, req, resp))
            return;

        String version = MediaStreamBase.p+" "+ReleaseInfo.getVersion()+"
build"+ReleaseInfo.getBuildNumber();
        String retStr =
"<html><head><title>"+version+"</title></head><body>"+version+"</body></html>";
        try
        {
            OutputStream out = resp.getOutputStream();
            byte[] outBytes = retStr.getBytes();
            out.write(outBytes);
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(HTTPServerVersion.class).error("HTMLServerVersion:
"+e.toString());
        }
    }
}

```

Method Summary

boolean	canHandle (String path)
String	getAuthenticationMethod ()
String	getRequestFilters ()
void	init ()
void	setAuthenticationMethod (String authenticationMethod)
void	setRequestFilters (String requestFilters)

Methods inherited from interface [com.wowza.wms.http.IHTTPProvider](#)

[onBind](#), [onHTTPRequest](#), [onUnbind](#), [setProperties](#)

Methods

canHandle

```
public boolean canHandle(String path)
```

setRequestFilters

```
public void setRequestFilters(String requestFilters)
```

getRequestFilters

```
public String getRequestFilters()
```

init

```
public void init()
```

getAuthenticationMethod

```
public String getAuthenticationMethod()
```

setAuthenticationMethod

```
public void setAuthenticationMethod(String authenticationMethod)
```

com.wowza.wms.http Interface IHttpRequest

public interface **IHttpRequest**
extends

Method Summary

int	<u>getContentLength()</u> Get the content length of the body of the message
String	<u>getContentType()</u> Get the request content type
String	<u>getHeader</u> (String name) Get a HTTP header value such as 'Content-Length'
java.util.Map	<u>getHeaderMap</u> () Get a copy of the HTTP request header map
java.util.Set	<u>getHeaderNames</u> () Get a Set of the header names
java.io.InputStream	<u>getInputStream</u> () Get the body of the message as an input stream
int	<u>getIntHeader</u> (String name) Get a HTTP header value such as 'Content-Length' and return as int
java.util.Locale	<u>getLocale</u> () Get locale of request (Example: en-us)
String	<u>getMethod</u> () Get the method invocation method: GET, POST, HEAD
String	<u>getParameter</u> (String name) Get a parameter value
java.util.Map	<u>getParameterMap</u> () Get the entire parameter Map
java.util.Set	<u>getParameterNames</u> () Get a Set of parameter names
String[]	<u>getParameterValues</u> (String name) Get a multi-value parameter as an array of String
String	<u>getPath</u> () Returns the HTTP path element of the request
String	<u>getProtocol</u> () Get the request protocol (example: HTTP/1.1)
String	<u>getQueryString</u> () Get the query string part of the url (everything after the ?)

String	<code>getRemoteAddr()</code> Get the remote ip address of the request
String	<code>getRemoteHost()</code> Get the remote host name (if known) if not return ip address
String	<code>getRequestURI()</code> Get the full request URI
String	<code>getRequestURL()</code> Get the request url (same as URI minus the query string)
String	<code>getScheme()</code> Get the request scheme (Example "http")
String	<code>getServerName()</code> Get the name of the server (Example: "Wowza Media Server Pro")
int	<code>getServerPort()</code> Get the port this request was received on
boolean	<code>isSecure()</code> Returns true is the request is protected by SSL
void	<code>parseBodyForParams()</code> If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.
void	<code>parseBodyForParams(boolean doDecode)</code> If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.

Methods

getHeaderMap

```
public java.util.Map getHeaderMap()
```

Get a copy of the HTTP request header map

Returns:

copy of the HTTP request header map

getHeader

```
public String getHeader(String name)
```

Get a HTTP header value such as 'Content-Length'

Parameters:

name - header name

Returns:

header value

(continued from last page)

getIntHeader

```
public int getIntHeader(String name)
```

Get a HTTP header value such as 'Content-Length' and return as int

Parameters:

name - header name

Returns:

header value

getHeaderNames

```
public java.util.Set getHeaderNames()
```

Get a Set of the header names

Returns:

Set of header names

getMethod

```
public String getMethod()
```

Get the method invocation method: GET, POST, HEAD

Returns:

method

getQueryString

```
public String getQueryString()
```

Get the query string part of the url (everything after the ?)

Returns:

query string

getContentLength

```
public int getContentLength()
```

Get the content length of the body of the message

Returns:

content length of the body of the message

getRequestURI

```
public String getRequestURI()
```

Get the full request URI

Returns:

full request URI

(continued from last page)

getRequestURL

```
public String getRequestURL()
```

Get the request url (same as URI minus the query string)

Returns:

request url

getContentType

```
public String getContentType()
```

Get the request content type

Returns:

request content type

parseBodyForParams

```
public void parseBodyForParams(boolean doDecode)
```

If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.

Parameters:

doDecode - true to decode the params as though they are url params

parseBodyForParams

```
public void parseBodyForParams()
```

If the body of the message contains parameter data (data in name value pairs separated by & character) call this routine to decode those parameters and add them to the parameter map.

getParameter

```
public String getParameter(String name)
```

Get a parameter value

Parameters:

name - parameter name

Returns:

parameter value

getParameterNames

```
public java.util.Set getParameterNames()
```

Get a Set of parameter names

Returns:

Set of parameter names

(continued from last page)

getParameterValues

```
public String[] getParameterValues(String name)
```

Get a multi-value parameter as an array of String

Parameters:

name - parameter name

Returns:

multi-value parameter as an array of String

getParameterMap

```
public java.util.Map getParameterMap()
```

Get the entire parameter Map

Returns:

parameter Map

getInputStream

```
public java.io.InputStream getInputStream()
```

Get the body of the message as an input stream

Returns:

body of the message as an input stream

getProtocol

```
public String getProtocol()
```

Get the request protocol (example: HTTP/1.1)

Returns:

request protocol

getScheme

```
public String getScheme()
```

Get the request scheme (Example "http")

Returns:

request scheme

getServerName

```
public String getServerName()
```

Get the name of the server (Example: "Wowza Media Server Pro")

Returns:

name of the server

(continued from last page)

getServerPort

```
public int getServerPort()
```

Get the port this request was received on

Returns:

the port this request was received on

getRemoteAddr

```
public String getRemoteAddr()
```

Get the remote ip address of the request

Returns:

remote ip address of the request

getRemoteHost

```
public String getRemoteHost()
```

Get the remote host name (if known) if not return ip address

Returns:

remote host name

getLocale

```
public java.util.Locale getLocale()
```

Get locale of request (Example: en-us)

Returns:

locale of request

isSecure

```
public boolean isSecure()
```

Returns true is the request is protected by SSL

Returns:

true is the request is protected by SSL

getPath

```
public String getPath()
```

Returns the HTTP path element of the request

Returns:

HTTP path element of the request

com.wowza.wms.http Interface IHTTPResponse

public interface **IHTTPResponse**
extends

Method Summary

boolean	<code>containsHeader</code> (String name) Returns true if reponse header contains parameter name
String	<code>getHeader</code> (String name) Get header value
java.util.Map	<code>getHeaders</code> () Get the current response headers as a map
int	<code>getHeaderSize</code> () Get the size in bytes of the HTTP header
int	<code>getIntHeader</code> (String name) Get header value as int
java.io.OutputStream	<code>getOutputStream</code> () Get the output stream for the reponse.
void	<code>setHeader</code> (String name, String value) Set header value
void	<code>setIntHeader</code> (String name, int value) Set header value as int
void	<code>setResponseCode</code> (int responseCode) Set the HTTP response code

Methods

`getOutputStream`

public java.io.OutputStream **getOutputStream**()

Get the output stream for the reponse. You can then write directly into the output stream.

Returns:

output stream for the reponse

`containsHeader`

public boolean **containsHeader**(String name)

Returns true if reponse header contains parameter name

(continued from last page)

Parameters:

name - header parameter name

Returns:true if header contains value

setHeader

```
public void setHeader(String name,  
                      String value)
```

Set header value

Parameters:

name - header parameter name

value - parameter value

setIntHeader

```
public void setIntHeader(String name,  
                         int value)
```

Set header value as int

Parameters:

name - header parameter name

value - parameter value

getHeaders

```
public java.util.Map getHeaders()
```

Get the current response headers as a map

Returns:current response headers as a map

getHeader

```
public String getHeader(String name)
```

Get header value

Parameters:

name - header parameter name

Returns:parameter value

getIntHeader

```
public int getIntHeader(String name)
```

Get header value as int

Parameters:

name - header parameter name

Returns:

(continued from last page)

parameter value

setResponseCode

```
public void setResponseCode(int responseCode)
```

Set the HTTP response code

Parameters:

responseCode - HTTP response code

getHeaderSize

```
public int getHeaderSize()
```

Get the size in bytes of the HTTP header

Returns:

header size in bytes

Package

**com.wowza.wms.httpstreamer.cupertinostrea
ming.httpstreamer**

com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer Class HTTPStreamerSessionCupertino

java.lang.Object

└─com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer.HTTPStreamerSessionCupertino

All Implemented Interfaces:

[IHTTPStreamerSession](#)

public class **HTTPStreamerSessionCupertino**
extends HTTPStreamerSessionBase

Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, uri, userAgent, userHTTPHeaders, userQueryStr, vhost

Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL_COUNT](#), [SESSIONPROTOCOL_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL_SANJOSESTREAMING](#), [SESSIONPROTOCOL_SMOOTHSTREAMING](#), [SESSIONPROTOCOL_UNKNOWN](#), [SESSIONPROTOCOL_WEBMSTREAMING](#), [SESSIONTYPE_LIVE](#), [SESSIONTYPE_LIVEDVR](#), [SESSIONTYPE_UNKNOWN](#), [SESSIONTYPE_VOD](#)

Constructor Summary

public	HTTPStreamerSessionCupertino()
--------	------------------------------------------------

Method Summary

void	clearLoggingValues()
------	--------------------------------------

boolean	containsIndex (String streamName)
---------	---------------------------------------------------

static boolean	doesFileExist (IHTTPStreamerApplicationContext appContext, String rawStreamName, String streamExt, String streamName)
----------------	--------------------------------------------------------------------------------------------------------------------------------------------------------

IHTTPStreamerCupertinoIndex	getIndex (IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName, long playStart, long playDuration)
-----------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

void	logLiveChunk (LiveStreamPacketizerCupertinoChunk chunk)
void	logVODChunk (LiveStreamPacketizerCupertinoChunk chunk)
void	shutdown ()
void	updateLoggingValues ()

Methods inherited from class [com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase](#)

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr, addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues, containsStreamDomainStr, containsStreamNameParts, doSessionRedirect, extractHTTPRequestInfo, getAppInstance, getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo, getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader, getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest, getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties, getQueryStr, getRedirectSessionBody, getRedirectSessionCode, getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp, getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType, getStream, getStreamDomainStr, getStreamExt, getStreamName, getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds, getUri, getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, isAcceptSession, isActive, isFileInfo, isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated, isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts, redirectSession, redirectSession, rejectSession, removeStreamDomainStr, setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer, setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession, setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType, setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId, setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt, setStreamName, setStreamPosition, setThreadContext, setTimeoutSession, setUri, setUserAgent, setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, shutdown, touch, updateLoggingValues, validStreamDomainToString

Methods inherited from class [java.lang.Object](#)

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),
[extractHTTPRequestInfo](#), [getAppInstance](#), [getConnectionHolder](#), [getCookieStr](#),
[getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#), [getHTTPHeader](#), [getHTTPHeaderMap](#),
[getHTTPHeaderNames](#), [getHTTPIntHeader](#), [getHTTPStreamerAdapter](#),
[getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#), [getLiveStreamingPacketizer](#),
[getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#), [getQueryStr](#),
[getRedirectSessionBody](#), [getRedirectSessionCode](#), [getRedirectSessionContentType](#),
[getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#), [getServerPort](#), [getSessionId](#),
[getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#), [getStream](#), [getStreamExt](#),
[getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#), [getTimeRunning](#),
[getTimeRunningSeconds](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),
[getVHost](#), [isAcceptSession](#), [isActive](#), [isFileInfo](#), [isPlayLogged](#), [isRedirectSession](#),
[isTimeout](#), [isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#),
[lockRepeaterStreams](#), [putFileInfo](#), [putStreamNameParts](#), [redirectSession](#),
[redirectSession](#), [rejectSession](#), [removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#),
[setAppInstance](#), [setCookieStr](#), [setDvrSessionInfo](#), [setHTTPStreamerAdapter](#),
[setIpAddress](#), [setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#),
[setPlayStart](#), [setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#),
[setRedirectSessionCode](#), [setRedirectSessionContentType](#), [setRedirectSessionURL](#),
[setReferrer](#), [setServerIp](#), [setServerPort](#), [getSessionId](#), [setSessionProtocol](#),
[setSessionTimeout](#), [setSessionType](#), [setStream](#), [setStreamExt](#), [setStreamName](#),
[setStreamPosition](#), [setTimeoutSession](#), [setUri](#), [setUserAgent](#), [setUserHTTPHeader](#),
[setUserQueryStr](#), [setVHost](#), [shutdown](#), [touch](#), [updateLoggingValues](#),
[validStreamDomainToString](#)

Constructors

HTTPStreamerSessionCupertino

```
public HTTPStreamerSessionCupertino()
```

Methods

shutdown

```
public void shutdown()
```

containsIndex

```
public boolean containsIndex(String streamName)
```

doesFileExist

```
public static boolean doesFileExist(IHTTPStreamerApplicationContext appContext,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

(continued from last page)

getIndex

```
public IHTTPStreamerCupertinoIndex getIndex(IHTTPStreamerApplicationContext
appContext,
IHTTPStreamerSession httpStreamerSession,
String rawStreamName,
String streamExt,
String streamName,
long playStart,
long playDuration)
```

updateLoggingValues

```
public void updateLoggingValues()
```

clearLoggingValues

```
public void clearLoggingValues()
```

logLiveChunk

```
public void logLiveChunk(LiveStreamPacketizerCupertinoChunk chunk)
```

logVODChunk

```
public void logVODChunk(LiveStreamPacketizerCupertinoChunk chunk)
```

com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer Interface IHTTPStreamerCupertinoVODActionNotify

All Subinterfaces:

[IHTTPStreamerCupertinoVODActionNotify2](#)

public interface **IHTTPStreamerCupertinoVODActionNotify**

extends

IHTTPStreamerCupertinoVODActionNotify: listener interface for video on demand iOS streaming. See

HTTPStreamerApplicationContextCupertinoStreamer.addVODActionListener(IHTTPStreamerCupertinoVODActionNotify listener)

Method Summary

void	onCreate (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called when file index created
void	onDestroy (IHTTPStreamerCupertinoIndex fileIndex) Called after file index is destroyed
void	onFillChunkEnd (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerCupertinoIndexItem item, LiveStreamPacketizerCupertinoChunk chunk, boolean audioOnly) Called after each chunk is filled.
void	onFillChunkStart (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerCupertinoIndexItem item, LiveStreamPacketizerCupertinoChunk chunk, boolean audioOnly) Called each time a chunk is filled.
void	onIndex (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called after file is indexed
void	onInit (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called after initialized
void	onOpen (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName) Called after open

Methods

(continued from last page)

onCreate

```
public void onCreate(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called when file index created

Parameters:

fileIndex - file index
appContext - HTTP application context
httpStreamerSession - HTTP streaming session
rawStreamName - stream name
streamExt - stream extension
streamName - adjusted stream name

onInit

```
public void onInit(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called after initialized

Parameters:

fileIndex - file index
appContext - HTTP application context
httpStreamerSession - HTTP streaming session
rawStreamName - stream name
streamExt - stream extension
streamName - adjusted stream name

onOpen

```
public void onOpen(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called after open

Parameters:

fileIndex - file index
appContext - HTTP application context
httpStreamerSession - HTTP streaming session
rawStreamName - stream name
streamExt - stream extension
streamName - adjusted stream name

(continued from last page)

onIndex

```
public void onIndex(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerApplicationContext appContext,  
    IHTTPStreamerSession httpStreamerSession,  
    String rawStreamName,  
    String streamExt,  
    String streamName)
```

Called after file is indexed

Parameters:

fileIndex - file index
appContext - HTTP application context
httpStreamerSession - HTTP streaming session
rawStreamName - stream name
streamExt - stream extension
streamName - adjusted stream name

onFillChunkStart

```
public void onFillChunkStart(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerCupertinoIndexItem item,  
    LiveStreamPacketizerCupertinoChunk chunk,  
    boolean audioOnly)
```

Called each time a chunk is filled. Can be used to add ID3 data to the header of a chunk.

Parameters:

fileIndex - file index
item - index item
chunk - chunk being filled
audioOnly - is audio-only chunk

onFillChunkEnd

```
public void onFillChunkEnd(IHTTPStreamerCupertinoIndex fileIndex,  
    IHTTPStreamerCupertinoIndexItem item,  
    LiveStreamPacketizerCupertinoChunk chunk,  
    boolean audioOnly)
```

Called after each chunk is filled. Can be used to add ID3 data to the end of a chunk.

Parameters:

fileIndex - file index
item - index item
chunk - chunk being filled
audioOnly - is audio-only chunk

onDestroy

```
public void onDestroy(IHTTPStreamerCupertinoIndex fileIndex)
```

Called after file index is destroyed

Parameters:

fileIndex - file index

com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer Interface IHTTPStreamerCupertinoVODActionNotify2

All Superinterfaces:

[IHTTPStreamerCupertinoVODActionNotify](#)

public interface **IHTTPStreamerCupertinoVODActionNotify2**

extends [IHTTPStreamerCupertinoVODActionNotify](#)

Method Summary

void	onFillChunkDataPacket (IHTTPStreamerCupertinoIndex fileIndex, IHTTPStreamerCupertinoIndexItem item, LiveStreamPacketizerCupertinoChunk chunk, boolean audioOnly, AMFPacket packet, ID3Frames id3Frames) Called when data packet is encountered.
------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods inherited from interface

[com.wowza.wms.httpstreamer.cupertinostreaming.httpstreamer.IHTTPStreamerCupertinoVODActionNotify](#)

[onCreate](#), [onDestroy](#), [onFillChunkEnd](#), [onFillChunkStart](#), [onIndex](#), [onInit](#), [onOpen](#)

Methods

onFillChunkDataPacket

```
public void onFillChunkDataPacket(IHTTPStreamerCupertinoIndex fileIndex,
    IHTTPStreamerCupertinoIndexItem item,
    LiveStreamPacketizerCupertinoChunk chunk,
    boolean audioOnly,
    AMFPacket packet,
    ID3Frames id3Frames)
```

Called when data packet is encountered. Used to convert AMF events into ID3 tags for iOS streaming

Parameters:

fileIndex - file index
item - item
chunk - chunk
audioOnly - is audio-only chunk
packet - amf packet
id3Frames - ID3 frames

Package

com.wowza.wms.httpstreamer.model

com.wowza.wms.httpstreamer.model Interface IHTTPStreamerAdapter

public interface **IHTTPStreamerAdapter**
extends

IHTTPStreamerAdapter: HTTP streaming adapter interface

Method Summary

boolean	<code>canHandle(String path)</code> Return true if can handle request
String	<code>getAdapterName()</code> Get the name of this adapter
HTTPStreamerItem	<code>getHTTPStreamerItem()</code> Get the HTTP streamer item associated with this adapter
String	<code>getID()</code> Get the id of this adapter
int	<code>getIdleFrequency()</code> Get the idle frequency (milliseconds) for HTTP requests.
<code>WMSProperties</code>	<code>getProperties()</code> Get properties
<code>IVHost</code>	<code>getVHost()</code> Get the vhost associated with this adapter
void	<code>init()</code> Initialize the HTTP streaming adapter
void	<code>service(org.apache.mina.common.io.Session session, RtmpRequestMessage req, RtmpResponseMessage resp)</code> Called to service each request
void	<code>setHTTPStreamerItem(HTTPStreamerItem httpStreamerItem)</code> Set the HTTP streamer item associated with this adapter
void	<code>setID(String id)</code> Set the id of this adapter
void	<code>setProperties(WMSProperties properties)</code> Set properties
void	<code>setVHost(IVHost vhost)</code> Set the vhost associated with this adapter
void	<code>shutdownSession(IHTTPStreamerSession session)</code> Called when an HTTP streaming session is shutdown

(continued from last page)

Methods

canHandle

```
public boolean canHandle(String path)
```

Return true if can handle request

Parameters:

path - request path

Returns:

true if can handle request

service

```
public void service(org.apache.mina.common.Session session,  
    RtmpRequestMessage req,  
    RtmpResponseMessage resp)
```

Called to service each request

Parameters:

session - io session

req - request

resp - response

getProperties

```
public WMSProperties getProperties()
```

Get properties

Returns:

properties

setProperties

```
public void setProperties(WMSProperties properties)
```

Set properties

Parameters:

properties - properties

getHTTPStreamerItem

```
public HTTPStreamerItem getHTTPStreamerItem()
```

Get the HTTP streamer item associated with this adapter

Returns:

HTTP streamer item

setHTTPStreamerItem

```
public void setHTTPStreamerItem(HTTPStreamerItem httpStreamerItem)
```

(continued from last page)

Set the HTTP streamer item associated with this adapter

Parameters:

httpStreamerItem - HTTP streamer item

getVHost

```
public IVHost getVHost()
```

Get the vhost associated with this adapter

Returns:

vhost

setVHost

```
public void setVHost(IVHost vhost)
```

Set the vhost associated with this adapter

Parameters:

vhost - vhost

init

```
public void init()
```

Initialize the HTTP streaming adapter

shutdownSession

```
public void shutdownSession(IHTTPStreamerSession session)
```

Called when an HTTP streaming session is shutdown

Parameters:

session - HTTP streaming session

getIdleFrequency

```
public int getIdleFrequency()
```

Get the idle frequency (milliseconds) for HTTP requests. This is how often the session is called back while active.

Returns:

idle frequency (milliseconds)

getAdapterName

```
public String getAdapterName()
```

Get the name of this adapter

Returns:

name of this adapter

(continued from last page)

getID

```
public String getID()
```

Get the id of this adapter

Returns:

id of this adapter

setID

```
public void setID(String id)
```

Set the id of this adapter

Parameters:

id - id of this adapter

com.wowza.wms.httpstreamer.model Interface IHTTPStreamerApplicationContext

public interface **IHTTPStreamerApplicationContext**
extends

IHTTPStreamerApplicationContext: HTTP streamer application context interface. Used by HTTP streaming adapter to store per-application information.

Method Summary

IApplicationInstance	getAppInstance() Get application instance
WMSProperties	getProperties() Get properties
MediaCasterItem	getRepeaterMediaCasterDef() Get the live repeater media caster definition
String	getStreamTypeStr() Get stream type
IVHost	getVHost() Get vhost
void	init(IApplicationInstance appInstance, HTTPStreamerItem httpStreamerItem) Initialize context
void	setRepeaterMediaCasterDef(MediaCasterItem repeaterMediaCasterDef) Set the live repeater media caster definition
void	setStreamTypeStr(String streamTypeStr) Set stream type

Methods

init

```
public void init(IApplicationInstance appInstance,  
                HTTPStreamerItem httpStreamerItem)
```

Initialize context

Parameters:

[appInstance](#) - application instance
[httpStreamerItem](#) - HTTP streamer

getProperties

```
public WMSProperties getProperties()
```


(continued from last page)

Get properties

Returns:
properties

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get application instance

Returns:
application instance

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:
vhost

getRepeaterMediaCasterDef

```
public MediaCasterItem getRepeaterMediaCasterDef()
```

Get the live repeater media caster definition

Returns:
live repeater media caster definition

setRepeaterMediaCasterDef

```
public void setRepeaterMediaCasterDef(MediaCasterItem repeaterMediaCasterDef)
```

Set the live repeater media caster definition

Parameters:
repeaterMediaCasterDef - live repeater media caster definition

getStreamTypeStr

```
public String getStreamTypeStr()
```

Get stream type

Returns:
stream type

setStreamTypeStr

```
public void setStreamTypeStr(String streamTypeStr)
```

Set stream type

Parameters:
streamTypeStr - stream type

com.wowza.wms.httpstreamer.model

Interface IHTTPStreamerRepeater

public interface IHTTPStreamerRepeater
extends

IHTTPStreamerRepeater: stream switching constants

Field Summary	
public static final	MSG_STARTSTREAM Value: startStream
public static final	MSG_SWITCHSTREAM Value: switchStream

Fields

MSG_STARTSTREAM

public static final java.lang.String **MSG_STARTSTREAM**

Constant value: **startStream**

MSG_SWITCHSTREAM

public static final java.lang.String **MSG_SWITCHSTREAM**

Constant value: **switchStream**

com.wowza.wms.httpstreamer.model Interface IHTTPStreamerSession

public interface **IHTTPStreamerSession**
extends

IHTTPStreamerSession: HTTP streaming session interface

Field Summary

public static final	<u>SESSIONPROTOCOL_COUNT</u> Value: 5
public static final	<u>SESSIONPROTOCOL_CUPERTINOSTREAMING</u> Value: 1
public static final	<u>SESSIONPROTOCOL_DVRCHUNKSTREAMING</u> Value: 4
public static final	<u>SESSIONPROTOCOL_SANJOSESTREAMING</u> Value: 2
public static final	<u>SESSIONPROTOCOL_SMOOTHSTREAMING</u> Value: 0
public static final	<u>SESSIONPROTOCOL_UNKNOWN</u> Value: -1
public static final	<u>SESSIONPROTOCOL_WEBMSTREAMING</u> Value: 3
public static final	<u>SESSIONTYPE_LIVE</u> Value: 1
public static final	<u>SESSIONTYPE_LIVEDVR</u> Value: 3
public static final	<u>SESSIONTYPE_UNKNOWN</u> Value: 0
public static final	<u>SESSIONTYPE_VOD</u> Value: 2

Method Summary

void	<u>acceptSession()</u> Accept the HTTP session.
------	--------------------------------------------------------------------

void	<u>addIOPerformance</u> (<u>IOPerformanceCounter</u> totalIOPerformanceResult) Internal user, keep track of IO performance
void	<u>addIOPerformance2</u> (<u>IOPerformanceCounter</u> totalIOPerformanceResult) Internal user, keep track of IO performance
void	<u>addStreamDomainStr</u> (String streamDomainStr) Internal user, add stream name
void	<u>addStreamDomainStrs</u> (java.util.List streamNames) Internal user, add stream names
void	<u>addUserHTTPHeaders</u> (<u>IHTTPResponse</u> resp) Internal
boolean	<u>checkAndSetPlayLogged</u> () If play has not been logged return false, else returns true, sets play has been logged
void	<u>clearLoggingValues</u> () Internal user, clear logging values
boolean	<u>containsStreamDomainStr</u> (String streamDomainStr) Internal user, test stream name
boolean	<u>containsStreamNameParts</u> (String streamName) Return true if stream name in stream name parts
void	<u>doSessionRedirect</u> (<u>IHTTPResponse</u> resp) Internal
void	<u>extractHTTPRequestInfo</u> (<u>IHTTPRequest</u> req) Extract information from HTTP request
<u>IApplicationInstance</u>	<u>getAppInstance</u> () Get the application instance associated with this HTTP session
ConnectionHolder	<u>getConnectionHolder</u> () Connection holder for this session
String	<u>getCookieStr</u> () Get cookie string
DvrSessionInfo	<u>getDvrSessionInfo</u> () This information is used to manage the connection to the DVR store.
<u>ElapsedTimer</u>	<u>getElapsedTime</u> () Get the elapsed timer to see how long this session has been running
HTTPStreamerFileInfo	<u>getFileInfo</u> (String streamName) Get the file information if video on demand streaming
String	<u>getHTTPHeader</u> (String name) Get a HTTP header value such as 'Content-Length'
java.util.Map	<u>getHTTPHeaderMap</u> () Get a copy of the HTTP request header map
java.util.Set	<u>getHTTPHeaderNames</u> () Get a Set of the header names

int	<u>getHTTPIntHeader</u> (String name) Get a HTTP header value such as 'Content-Length' and return as int
<u>IHTTPStreamerAdapter</u>	<u>getHTTPStreamerAdapter</u> () Get the HTTP streaming adapter associated with this HTTP session
<u>IOPerformanceCounter</u>	<u>getIOPerformanceCounter</u> () Get IO performance counter
String	<u>getIpAddress</u> () Get the IP address
long	<u>getLastRequest</u> () Get the last timestamp of the last Io request
String	<u>getLiveStreamingPacketizer</u> () Get the live stream packetizer name
Object	<u>getLock</u> () Get the synchronization lock for this HTTP session
long	<u>getPlayDuration</u> () Get the play duration (milliseconds) for video on demand playback.
long	<u>getPlayStart</u> () Get the play start time offset (milliseconds) for video on demand playback.
<u>WMSProperties</u>	<u>getProperties</u> () Get the properties associated with this session
String	<u>getQueryStr</u> () Get query string
byte[]	<u>getRedirectSessionBody</u> () Get redirect session body
int	<u>getRedirectSessionCode</u> () Get session redirect HTTP response code (default 302)
String	<u>getRedirectSessionContentType</u> () Get redirect session HTTP Content-Type
String	<u>getRedirectSessionURL</u> () Get redirect session URL
String	<u>getReferrer</u> () Get referrer
String	<u>getServerIp</u> () Get server IP address
int	<u>getServerPort</u> () Get server port
String	<u>getSessionId</u> () Get session id
int	<u>getSessionProtocol</u> () Get protocol, see SESSIONPROTOCOL_*

int	<u>getSessionTimeout()</u> Get the session timeout for this session (milliseconds)
int	<u>getSessionType()</u> Get session type: see SESSIONTYPE_*
<u>IMediaStream</u>	<u>getStream()</u> Get the IMediaStream associated with this HTTP session
String	<u>getStreamExt()</u> Get stream extension
String	<u>getStreamName()</u> Get stream name
HTTPStreamerStreamNameParts	<u>getStreamNameParts(String streamName)</u> Break the stream name into parts
long	<u>getStreamPosition()</u> Get stream position
String	<u>getTimeRunning()</u> Get the time this session has been running (milliseconds)
double	<u>getTimeRunningSeconds()</u> Get the time this session has been running (seconds)
String	<u>getUri()</u> Get the URI associated with initial request
String	<u>getUserAgent()</u> Get user agent
java.util.Map	<u>getUserHTTPHeaders()</u> Get user HTTP header.
String	<u>getUserQueryString()</u> This query string will be added to URLs used in HTTP streaming
<u>IVHost</u>	<u>getVHost()</u> Get vhost
boolean	<u>isAcceptSession()</u> Return true if this session has not been rejected
boolean	<u>isActive()</u> Is this session active, false after shutdown
boolean	<u>isFileInfo(String streamName)</u> Return true if the is file information for a given stream name
boolean	<u>isPlayLogged()</u> true, if play has been logged
boolean	<u>isRedirectSession()</u> Is session redirect
boolean	<u>isTimeout(long timecode)</u> Return true if this session is timed out.

boolean	<u>isTimeoutSession()</u> Get is session timeout.
boolean	<u>isValidated()</u> Has this session been validated
boolean	<u>isValidStreamDomainStr()</u> (String streamDomainStr) Internal user, is stream name valid for HTTP session
void	<u>lockRepeaterStreams()</u> (java.util.List streamNames, String liveStreamPacketizer, String liveStreamRepeater, String streamTypeStr) Internal user, lock in reapter streams
void	<u>putFileInfo()</u> (String streamName, HTTPStreamerFileInfo fileInfo) Set the file information
void	<u>putStreamNameParts()</u> (String streamName, HTTPStreamerStreamNameParts streamNameParts) Add stream name to stream name parts
void	<u>redirectSession()</u> (String redirectSessionURL) Redirect session
void	<u>redirectSession()</u> (String redirectSessionURL, int redirectSessionCode) Redirect session
void	<u>rejectSession()</u> Reject this HTTP session.
void	<u>removeStreamDomainStr()</u> (String streamDomainStr) Internal user, remove stream name
void	<u>setAcceptSession()</u> (boolean acceptSession) Set to false to reject session
void	<u>setActive()</u> (boolean isActive) Set session active
void	<u>setAppInstance()</u> (<u>IApplicationInstance</u> appInstance) Set the application instance associated with this HTTP session
void	<u>setCookieStr()</u> (String cookieStr) Set cookie string
void	<u>setDvrSessionInfo()</u> (DvrSessionInfo dvr) This information is used to manage the connection to the DVR store.
void	<u>setHTTPStreamerAdapter()</u> (<u>IHTTPStreamerAdapter</u> httpStreamerAdapter) Set the HTTP streaming adapter associated with this HTTP session
void	<u>setIpAddress()</u> (String ipAddress) Set the IP address
void	<u>setLiveStreamingPacketizer()</u> (String liveStreamingPacketizer) Set the live stream packetizer name
void	<u>setPlayDuration()</u> (long playDuration) Set the play duration (milliseconds) for video on demand playback.

void	<u>setPlayLogged</u> (boolean isPlayLogged) true, if play has been logged
void	<u>setPlayStart</u> (long playStart) Set the play start time offset (milliseconds) for video on demand playback.
void	<u>setQueryStr</u> (String queryStr) Set query string
void	<u>setRedirectSession</u> (boolean redirectSession) Set session redirect
void	<u>setRedirectSessionBody</u> (byte[] redirectSessionBody) Set redirect session body
void	<u>setRedirectSessionCode</u> (int redirectSessionCode) Set session redirect HTTP response code (default 302)
void	<u>setRedirectSessionContentType</u> (String redirectSessionContentType) Set redirect session HTTP Content-Type
void	<u>setRedirectSessionURL</u> (String redirectSessionURL) Set redirect session URL
void	<u>setReferrer</u> (String referrer) Set referrer
void	<u>setServerIp</u> (String serverIp) Set server IP address
void	<u>setServerPort</u> (int serverPort) Set server port
void	<u>setSessionId</u> (String sessionId) Set session id
void	<u>setSessionProtocol</u> (int sessionProtocol) Set protocol, see SESSIONPROTOCOL_*
void	<u>setSessionTimeout</u> (int sessionTimeout) Set the session timeout for this session (milliseconds)
void	<u>setSessionType</u> (int sessionType) Set session type: see SESSIONTYPE_*
void	<u>setStream</u> (IMediaStream stream) Set the IMediaStream associated with this HTTP session
void	<u>setStreamExt</u> (String streamExt) Set stream extension
void	<u>setStreamName</u> (String streamName) Set stream name
void	<u>setStreamPosition</u> (long streamPosition) Set stream position (will not cause seek)
void	<u>setTimeoutSession</u> (boolean timeoutSession) Set is session timeout.

void	<code>setUri</code> (String uri) Set the URI associated with initial request
void	<code>setUserAgent</code> (String userAgent) Set user agent
void	<code>setUserHTTPHeader</code> (String name, String value) Set user HTTP header.
void	<code>setUserQueryStr</code> (String userQueryStr) This query string will be added to URLs used in HTTP streaming
void	<code>setVHost</code> (<code>IVHost</code> vhost) Set vhost
void	<code>shutdown</code> () Called then the HTTP session is shutting down
void	<code>touch</code> (long timecode) Touch this session to keep it active.
void	<code>updateLoggingValues</code> () Internal user, update logging values
String	<code>validStreamDomainToString</code> () Return the valid domain strings as a string

Fields

SESSIONTYPE_UNKNOWN

public static final int **SESSIONTYPE_UNKNOWN**

Constant value: **0**

SESSIONTYPE_LIVE

public static final int **SESSIONTYPE_LIVE**

Constant value: **1**

SESSIONTYPE_VOD

public static final int **SESSIONTYPE_VOD**

Constant value: **2**

SESSIONTYPE_LIVEDVR

public static final int **SESSIONTYPE_LIVEDVR**

Constant value: **3**

SESSIONPROTOCOL_UNKNOWN

```
public static final int SESSIONPROTOCOL_UNKNOWN
```

Constant value: **-1**

SESSIONPROTOCOL_SMOOTHSTREAMING

```
public static final int SESSIONPROTOCOL_SMOOTHSTREAMING
```

Constant value: **0**

SESSIONPROTOCOL_CUPERTINOSTREAMING

```
public static final int SESSIONPROTOCOL_CUPERTINOSTREAMING
```

Constant value: **1**

SESSIONPROTOCOL_SANJOSESTREAMING

```
public static final int SESSIONPROTOCOL_SANJOSESTREAMING
```

Constant value: **2**

SESSIONPROTOCOL_WEBMSTREAMING

```
public static final int SESSIONPROTOCOL_WEBMSTREAMING
```

Constant value: **3**

SESSIONPROTOCOL_DVRCHUNKSTREAMING

```
public static final int SESSIONPROTOCOL_DVRCHUNKSTREAMING
```

Constant value: **4**

SESSIONPROTOCOL_COUNT

```
public static final int SESSIONPROTOCOL_COUNT
```

Constant value: **5**

Methods

getSessionId

```
public String getSessionId()
```

Get session id

Returns:

(continued from last page)

session id

setSessionId

```
public void setSessionId(String sessionId)
```

Set session id

Parameters:

sessionId - session id

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:

vhost

setVHost

```
public void setVHost(IVHost vhost)
```

Set vhost

Parameters:

vhost - vhost

touch

```
public void touch(long timecode)
```

Touch this session to keep it active.

Parameters:

timecode - timecode of touch - System.currentTimeMillis();

isTimeout

```
public boolean isTimeout(long timecode)
```

Return true if this session is timed out.

Parameters:

timecode - last touch - System.currentTimeMillis();

Returns:

true, if timed out

getLock

```
public Object getLock()
```

Get the synchronization lock for this HTTP session

Returns:

synchronization lock

shutdown

```
public void shutdown()
```

Called then the HTTP session is shutting down

isActive

```
public boolean isActive()
```

Is this session active, false after shutdown

Returns:

true if session is active

setActive

```
public void setActive(boolean isActive)
```

Set session active

Parameters:

isActive - session active

getStream

```
public IMediaStream getStream()
```

Get the IMediaStream associated with this HTTP session

Returns:

IMediaStream associated with this HTTP session

setStream

```
public void setStream(IMediaStream stream)
```

Set the IMediaStream associated with this HTTP session

Parameters:

stream - IMediaStream associated with this HTTP session

isTimeoutSession

```
public boolean isTimeoutSession()
```

Get is session timeout.

Returns:

true if this session is timed out

setTimeoutSession

```
public void setTimeoutSession(boolean timeoutSession)
```

Set is session timeout.

(continued from last page)

Parameters:

timeoutSession - true if this session is timed out

getSessionTimeout

```
public int getSessionTimeout()
```

Get the session timeout for this session (milliseconds)

Returns:

session timeout for this session (milliseconds)

setSessionTimeout

```
public void setSessionTimeout(int sessionTimeout)
```

Set the session timeout for this session (milliseconds)

Parameters:

sessionTimeout - session timeout for this session (milliseconds)

isValidated

```
public boolean isValidated()
```

Has this session been validated

Returns:

true, if validated

checkAndSetPlayLogged

```
public boolean checkAndSetPlayLogged()
```

If play has not been logged return false, else returns true, sets play has been logged

Returns:

true, if play has been logged

isPlayLogged

```
public boolean isPlayLogged()
```

true, if play has been logged

Returns:

true, if play has been logged

setPlayLogged

```
public void setPlayLogged(boolean isPlayLogged)
```

true, if play has been logged

Parameters:

isPlayLogged - true, if play has been logged

(continued from last page)

addIOPerformance

```
public void addIOPerformance(IOPerformanceCounter totalIOPerformanceResult)
```

Internal user, keep track of IO performance

Parameters:

totalIOPerformanceResult - IO performance

addIOPerformance2

```
public void addIOPerformance2(IOPerformanceCounter totalIOPerformanceResult)
```

Internal user, keep track of IO performance

Parameters:

totalIOPerformanceResult - IO performance

getConnectionHolder

```
public ConnectionHolder getConnectionHolder()
```

Connection holder for this session

Returns:

connection holder

getHTTPStreamerAdapter

```
public IHTTPStreamerAdapter getHTTPStreamerAdapter()
```

Get the HTTP streaming adapter associated with this HTTP session

Returns:

HTTP streaming adapter

setHTTPStreamerAdapter

```
public void setHTTPStreamerAdapter(IHTTPStreamerAdapter httpStreamerAdapter)
```

Set the HTTP streaming adapter associated with this HTTP session

Parameters:

httpStreamerAdapter - HTTP streaming adapter

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get the application instance associated with this HTTP session

Returns:

application instance associated with this HTTP session

setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

(continued from last page)

Set the application instance associated with this HTTP session

Parameters:

appInstance - application instance associated with this HTTP session

getSessionType

```
public int getSessionType()
```

Get session type: see SESSIONTYPE_*

Returns:

session type: see SESSIONTYPE_*

setSessionType

```
public void setSessionType(int sessionType)
```

Set session type: see SESSIONTYPE_*

Parameters:

sessionType - session type: see SESSIONTYPE_*

getLiveStreamingPacketizer

```
public String getLiveStreamingPacketizer()
```

Get the live stream packetizer name

Returns:

live stream packetizer name

setLiveStreamingPacketizer

```
public void setLiveStreamingPacketizer(String liveStreamingPacketizer)
```

Set the live stream packetizer name

Parameters:

liveStreamingPacketizer - live stream packetizer name

getIpAddress

```
public String getIpAddress()
```

Get the IP address

Returns:

IP address

setIpAddress

```
public void setIpAddress(String ipAddress)
```

Set the IP address

Parameters:

ipAddress - IP address

updateLoggingValues

```
public void updateLoggingValues()
```

Internal user, update logging values

clearLoggingValues

```
public void clearLoggingValues()
```

Internal user, clear logging values

getSessionProtocol

```
public int getSessionProtocol()
```

Get protocol, see SESSIONPROTOCOL_*

Returns:

protocol, see SESSIONPROTOCOL_*

setSessionProtocol

```
public void setSessionProtocol(int sessionProtocol)
```

Set protocol, see SESSIONPROTOCOL_*

Parameters:

sessionProtocol - protocol, see SESSIONPROTOCOL_*

getServerIp

```
public String getServerIp()
```

Get server IP address

Returns:

server IP address

setServerIp

```
public void setServerIp(String serverIp)
```

Set server IP address

Parameters:

serverIp - server IP address

getServerPort

```
public int getServerPort()
```

Get server port

Returns:

server port

setServerPort

```
public void setServerPort(int serverPort)
```

Set server port

Parameters:

serverPort - server port

getUserAgent

```
public String getUserAgent()
```

Get user agent

Returns:

user agent

setUserAgent

```
public void setUserAgent(String userAgent)
```

Set user agent

Parameters:

userAgent - user agent

getUri

```
public String getUri()
```

Get the URI associated with initial request

Returns:

URI associated with initial request

setUri

```
public void setUri(String uri)
```

Set the URI associated with initial request

Parameters:

uri - URI associated with initial request

getReferrer

```
public String getReferrer()
```

Get referrer

Returns:

referrer

setReferrer

```
public void setReferrer(String referrer)
```

(continued from last page)

Set referrer

Parameters:

referrer - referrer

getQueryStr

```
public String getQueryStr()
```

Get query string

Returns:

query string

setQueryStr

```
public void setQueryStr(String queryStr)
```

Set query string

Parameters:

queryStr - query string

lockRepeaterStreams

```
public void lockRepeaterStreams(java.util.List streamNames,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    String streamTypeStr)
```

Internal user, lock in reapter streams

Parameters:

streamNames - list of stream names

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live repeater name

streamTypeStr - stream type

rejectSession

```
public void rejectSession()
```

Reject this HTTP session. No further processing should occur

acceptSession

```
public void acceptSession()
```

Accept the HTTP session.

isAcceptSession

```
public boolean isAcceptSession()
```

Return true if this session has not been rejected

Returns:

true if this session has not been rejected

setAcceptSession

```
public void setAcceptSession(boolean acceptSession)
```

Set to false to reject session

Parameters:

acceptSession - false to reject session

getCookieStr

```
public String getCookieStr()
```

Get cookie string

Returns:

cookie string

setCookieStr

```
public void setCookieStr(String cookieStr)
```

Set cookie string

Parameters:

cookieStr - cookie string

getStreamName

```
public String getStreamName()
```

Get stream name

Returns:

stream name

setStreamName

```
public void setStreamName(String streamName)
```

Set stream name

Parameters:

streamName - stream name

getStreamExt

```
public String getStreamExt()
```

Get stream extension

Returns:

stream extension

setStreamExt

```
public void setStreamExt(String streamExt)
```

(continued from last page)

Set stream extension

Parameters:

streamExt - stream extension

getStreamNameParts

```
public HTTPStreamerStreamNameParts getStreamNameParts(String streamName)
```

Break the stream name into parts

Parameters:

streamName - stream name

Returns:

stream name parts

containsStreamNameParts

```
public boolean containsStreamNameParts(String streamName)
```

Return true if stream name in stream name parts

Parameters:

streamName - stream name

Returns:

true if stream name in stream name parts

putStreamNameParts

```
public void putStreamNameParts(String streamName,  
    HTTPStreamerStreamNameParts streamNameParts)
```

Add stream name to stream name parts

Parameters:

streamName - stream name

streamNameParts - stream name parts

getStreamPosition

```
public long getStreamPosition()
```

Get stream position

Returns:

stream position

setStreamPosition

```
public void setStreamPosition(long streamPosition)
```

Set stream position (will not cause seek)

Parameters:

streamPosition - stream position

getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter()
```

Get IO performance counter

Returns:

IO performance counter

getFileInfo

```
public HTTPStreamerFileInfo getFileInfo(String streamName)
```

Get the file information if video on demand streaming

Parameters:

streamName - stream name

Returns:

file information

putFileInfo

```
public void putFileInfo(String streamName,  
    HTTPStreamerFileInfo fileInfo)
```

Set the file information

Parameters:

streamName - stream name

fileInfo - file information

isFileInfo

```
public boolean isFileInfo(String streamName)
```

Return true if the is file information for a given stream name

Parameters:

streamName - stream name

Returns:

true if the is file information for a given stream name

isValidStreamDomainStr

```
public boolean isValidStreamDomainStr(String streamDomainStr)
```

Internal user, is stream name valid for HTTP session

Parameters:

streamDomainStr - stream name

Returns:

true if valid

(continued from last page)

validStreamDomainToString

```
public String validStreamDomainToString()
```

Return the valid domain strings as a string

Returns:

valid domain strings as a string

containsStreamDomainStr

```
public boolean containsStreamDomainStr(String streamDomainStr)
```

Internal user, test stream name

Parameters:

streamDomainStr - stream name

Returns:

true if valid

removeStreamDomainStr

```
public void removeStreamDomainStr(String streamDomainStr)
```

Internal user, remove stream name

Parameters:

streamDomainStr - stream name

addStreamDomainStr

```
public void addStreamDomainStr(String streamDomainStr)
```

Internal user, add stream name

Parameters:

streamDomainStr - stream name

addStreamDomainStrs

```
public void addStreamDomainStrs(java.util.List streamNames)
```

Internal user, add stream names

Parameters:

streamNames - stream names

getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get the elapsed timer to see how long this session has been running

Returns:

elapsed timer (milliseconds)

(continued from last page)

getTimeRunning

```
public String getTimeRunning()
```

Get the time this session has been running (milliseconds)

Returns:

time this session has been running (milliseconds)

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get the time this session has been running (seconds)

Returns:

time this session has been running (seconds)

getProperties

```
public WMSProperties getProperties()
```

Get the properties associated with this session

Returns:

properties

getUserQueryStr

```
public String getUserQueryStr()
```

This query string will be added to URLs used in HTTP streaming

Returns:

user query string

setUserQueryStr

```
public void setUserQueryStr(String userQueryStr)
```

This query string will be added to URLs used in HTTP streaming

Parameters:

userQueryStr - user query string

setDvrSessionInfo

```
public void setDvrSessionInfo(DvrSessionInfo dvr)
```

This information is used to manage the connection to the DVR store.

Parameters:

dvr - The DVR session info.

getDvrSessionInfo

```
public DvrSessionInfo getDvrSessionInfo()
```

(continued from last page)

This information is used to manage the connection to the DVR store.

Returns:

DVR session info.

extractHTTPRequestInfo

```
public void extractHTTPRequestInfo(IHTTPRequest req)
```

Extract information from HTTP request

Parameters:

req - HTTP request

getHTTPHeaderMap

```
public java.util.Map getHTTPHeaderMap()
```

Get a copy of the HTTP request header map

Returns:

copy of the HTTP request header map

getHTTPHeader

```
public String getHTTPHeader(String name)
```

Get a HTTP header value such as 'Content-Length'

Parameters:

name - header name

Returns:

header value

getHTTPIntHeader

```
public int getHTTPIntHeader(String name)
```

Get a HTTP header value such as 'Content-Length' and return as int

Parameters:

name - header name

Returns:

header value

getHTTPHeaderNames

```
public java.util.Set getHTTPHeaderNames()
```

Get a Set of the header names

Returns:

Set of header names

(continued from last page)

getPlayStart

```
public long getPlayStart()
```

Get the play start time offset (milliseconds) for video on demand playback.

Returns:

play start time offset (milliseconds)

setPlayStart

```
public void setPlayStart(long playStart)
```

Set the play start time offset (milliseconds) for video on demand playback.

Parameters:

playStart - play start time offset (milliseconds)

getPlayDuration

```
public long getPlayDuration()
```

Get the play duration (milliseconds) for video on demand playback. A values of -1 means play to end.

Returns:

play duration (milliseconds)

setPlayDuration

```
public void setPlayDuration(long playDuration)
```

Set the play duration (milliseconds) for video on demand playback. A values of -1 means play to end.

Parameters:

playDuration - play duration (milliseconds)

setUserHTTPHeader

```
public void setUserHTTPHeader(String name,  
                               String value)
```

Set user HTTP header. This header value will be added to all HTTP responses

Parameters:

name - name

value - value

getUserHTTPHeaders

```
public java.util.Map getUserHTTPHeaders()
```

Get user HTTP header. This header value will be added to all HTTP responses

Returns:

header map

(continued from last page)

addUserHTTPHeaders

```
public void addUserHTTPHeaders(IHTTPResponse resp)
```

Internal

Parameters:

resp - response

doSessionRedirect

```
public void doSessionRedirect(IHTTPResponse resp)
```

Internal

Parameters:

resp - response

isRedirectSession

```
public boolean isRedirectSession()
```

Is session redirect

Returns:

session redirect

setRedirectSession

```
public void setRedirectSession(boolean redirectSession)
```

Set session redirect

Parameters:

redirectSession - session redirect

getRedirectSessionCode

```
public int getRedirectSessionCode()
```

Get session redirect HTTP response code (default 302)

Returns:

session redirect HTTP response code

setRedirectSessionCode

```
public void setRedirectSessionCode(int redirectSessionCode)
```

Set session redirect HTTP response code (default 302)

Parameters:

redirectSessionCode - session redirect HTTP response code

getRedirectSessionURL

```
public String getRedirectSessionURL()
```

(continued from last page)

Get redirect session URL

Returns:

redirect session URL

setRedirectSessionURL

```
public void setRedirectSessionURL(String redirectSessionURL)
```

Set redirect session URL

Parameters:

redirectSessionURL - redirect session URL

redirectSession

```
public void redirectSession(String redirectSessionURL)
```

Redirect session

Parameters:

redirectSessionURL - redirect session URL

redirectSession

```
public void redirectSession(String redirectSessionURL,  
int redirectSessionCode)
```

Redirect session

Parameters:

redirectSessionURL - redirect session URL

redirectSessionCode - redirect session response code (default 302)

getRedirectSessionBody

```
public byte[] getRedirectSessionBody()
```

Get redirect session body

Returns:

redirect session body

setRedirectSessionBody

```
public void setRedirectSessionBody(byte[] redirectSessionBody)
```

Set redirect session body

Parameters:

redirectSessionBody - redirect session body

getRedirectSessionContentType

```
public String getRedirectSessionContentType()
```

Get redirect session HTTP Content-Type

Returns:

(continued from last page)

redirect session HTTP Content-Type

setRedirectSessionContentType

```
public void setRedirectSessionContentType(String redirectSessionContentType)
```

Set redirect session HTTP Content-Type

Parameters:

redirectSessionContentType

getLastRequest

```
public long getLastRequest()
```

Get the last timestamp of the last Io request

Returns:

last timestamp of the last Io request (milliseconds)

com.wowza.wms.httpstreamer.model Interface IHTTPStreamerSessionNotify

public interface IHTTPStreamerSessionNotify
extends

IHTTPStreamerSessionNotify: HTTP session create/destroy interface

Method Summary

void	onHTTPStreamerSessionCreate (IHTTPStreamerSession httpStreamerSession) Called when an HTTP streaming session is created
void	onHTTPStreamerSessionDestroy (IHTTPStreamerSession httpStreamerSession) Called when an HTTP streaming session is destroyed

Methods

onHTTPStreamerSessionCreate

public void **onHTTPStreamerSessionCreate**([IHTTPStreamerSession](#) httpStreamerSession)

Called when an HTTP streaming session is created

Parameters:

httpStreamerSession - HTTP streaming session

onHTTPStreamerSessionDestroy

public void **onHTTPStreamerSessionDestroy**([IHTTPStreamerSession](#) httpStreamerSession)

Called when an HTTP streaming session is destroyed


Parameters:

httpStreamerSession - HTTP streaming session

Package

**com.wowza.wms.httpstreamer.sanjoestream
ing.httpstreamer**

com.wowza.wms.httpstreamer.sanjosestreaming.httpstreamer
Class HTTPStreamerSessionSanJose



public class HTTPStreamerSessionSanJose
extends HTTPStreamerSessionBase

Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase
acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, uri, userAgent, userHTTPHeaders, userQueryStr, vhost

Fields inherited from interface com.wowza.wms.httpstreamer.model.IHTTPStreamerSession
SESSIONPROTOCOL_COUNT , SESSIONPROTOCOL_CUPERTINOSTREAMING , SESSIONPROTOCOL_DVRCHUNKSTREAMING , SESSIONPROTOCOL_SANJOSESTREAMING , SESSIONPROTOCOL_SMOOTHSTREAMING , SESSIONPROTOCOL_UNKNOWN , SESSIONPROTOCOL_WEBMSTREAMING , SESSIONTYPE_LIVE , SESSIONTYPE_LIVEDVR , SESSIONTYPE_UNKNOWN , SESSIONTYPE_VOD

Constructor Summary	
public	HTTPStreamerSessionSanJose()

Method Summary	
void	addFirstABSTRequest (String streamName)
void	clearLoggingValues ()
boolean	containsIndex (String streamName)
static IHTTPStreamerSanJoseIndex	createIndexLive (IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName)

IHTTPStreamerSanJoseIndex	getIndex(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName, long playStart, long playDuration)
IHTTPStreamerSanJoseIndex	getIndexLive(IHTTPStreamerApplicationContext appContext, IHTTPStreamerSession httpStreamerSession, String rawStreamName, String streamExt, String streamName)
boolean	isFirstABSTRequest (String streamName)
void	logLiveChunk (LiveStreamPacketizerSanJoseChunk chunk)
void	logVODChunk (LiveStreamPacketizerSanJoseChunk chunk)
void	shutdown ()
void	updateLoggingValues ()

Methods inherited from class `com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase`

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr, addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues, containsStreamDomainStr, containsStreamNameParts, doSessionRedirect, extractHTTPRequestInfo, getAppInstance, getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo, getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader, getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest, getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties, getQueryStr, getRedirectSessionBody, getRedirectSessionCode, getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp, getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType, getStream, getStreamDomainStr, getStreamExt, getStreamName, getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds, getUri, getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, isAcceptSession, isActive, isFileInfo, isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated, isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts, redirectSession, redirectSession, rejectSession, removeStreamDomainStr, setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer, setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession, setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType, setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId, setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt, setStreamName, setStreamPosition, setThreadContext, setTimeoutSession, setUri, setUserAgent, setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, shutdown, touch, updateLoggingValues, validStreamDomainToString

Methods inherited from class `java.lang.Object`

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),
[extractHTTPRequestInfo](#), [getAppInstance](#), [getConnectionHolder](#), [getCookieStr](#),
[getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#), [getHTTPHeader](#), [getHTTPHeaderMap](#),
[getHTTPHeaderNames](#), [getHTTPIntHeader](#), [getHTTPStreamerAdapter](#),
[getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#), [getLiveStreamingPacketizer](#),
[getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#), [getQueryStr](#),
[getRedirectSessionBody](#), [getRedirectSessionCode](#), [getRedirectSessionContentType](#),
[getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#), [getServerPort](#), [getSessionId](#),
[getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#), [getStream](#), [getStreamExt](#),
[getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#), [getTimeRunning](#),
[getTimeRunningSeconds](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),
[getVHost](#), [isAcceptSession](#), [isActive](#), [isFileInfo](#), [isPlayLogged](#), [isRedirectSession](#),
[isTimeout](#), [isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#),
[lockRepeaterStreams](#), [putFileInfo](#), [putStreamNameParts](#), [redirectSession](#),
[redirectSession](#), [rejectSession](#), [removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#),
[setAppInstance](#), [setCookieStr](#), [setDvrSessionInfo](#), [setHTTPStreamerAdapter](#),
[setIpAddress](#), [setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#),
[setPlayStart](#), [setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#),
[setRedirectSessionCode](#), [setRedirectSessionContentType](#), [setRedirectSessionURL](#),
[setReferrer](#), [setServerIp](#), [setServerPort](#), [getSessionId](#), [setSessionProtocol](#),
[setSessionTimeout](#), [setSessionType](#), [setStream](#), [setStreamExt](#), [setStreamName](#),
[setStreamPosition](#), [setTimeoutSession](#), [setUri](#), [setUserAgent](#), [setUserHTTPHeader](#),
[setUserQueryStr](#), [setVHost](#), [shutdown](#), [touch](#), [updateLoggingValues](#),
[validStreamDomainToString](#)

Constructors

HTTPStreamerSessionSanJose

```
public HTTPStreamerSessionSanJose()
```

Methods

shutdown

```
public void shutdown()
```

containsIndex

```
public boolean containsIndex(String streamName)
```

(continued from last page)

createIndexLive

```
public static IHTTPStreamerSanJoseIndex  
createIndexLive(IHTTPStreamerApplicationContext appContext,  
                IHTTPStreamerSession httpStreamerSession,  
                String rawStreamName,  
                String streamExt,  
                String streamName)
```

getIndexLive

```
public IHTTPStreamerSanJoseIndex getIndexLive(IHTTPStreamerApplicationContext  
appContext,  
        IHTTPStreamerSession httpStreamerSession,  
        String rawStreamName,  
        String streamExt,  
        String streamName)
```

getIndex

```
public IHTTPStreamerSanJoseIndex getIndex(IHTTPStreamerApplicationContext appContext,  
        IHTTPStreamerSession httpStreamerSession,  
        String rawStreamName,  
        String streamExt,  
        String streamName,  
        long playStart,  
        long playDuration)
```

updateLoggingValues

```
public void updateLoggingValues()
```

clearLoggingValues

```
public void clearLoggingValues()
```

logLiveChunk

```
public void logLiveChunk(LiveStreamPacketizerSanJoseChunk chunk)
```

logVODChunk

```
public void logVODChunk(LiveStreamPacketizerSanJoseChunk chunk)
```

(continued from last page)

isFirstABSTRequest

```
public boolean isFirstABSTRequest(String streamName)
```

addFirstABSTRequest

```
public void addFirstABSTRequest(String streamName)
```

Package

**com.wowza.wms.httpstreamer.smoothstream
ing.httpstreamer**

com.wowza.wms.httpstreamer.smoothstreaming.httpstreamer Class HTTPStreamerSessionSmoothStreamer

java.lang.Object

└─com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└─

com.wowza.wms.httpstreamer.smoothstreaming.httpstreamer.HTTPStreamerSessionSmoothStreamer

All Implemented Interfaces:

[IHTTPStreamerSession](#)

```
public class HTTPStreamerSessionSmoothStreamer
extends HTTPStreamerSessionBase
```

Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, uri, userAgent, userHTTPHeaders, userQueryStr, vhost

Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL_COUNT](#), [SESSIONPROTOCOL_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL_SANJOSESTREAMING](#), [SESSIONPROTOCOL_SMOOTHSTREAMING](#), [SESSIONPROTOCOL_UNKNOWN](#), [SESSIONPROTOCOL_WEBMSTREAMING](#), [SESSIONTYPE_LIVE](#), [SESSIONTYPE_LIVEDVR](#), [SESSIONTYPE_UNKNOWN](#), [SESSIONTYPE_VOD](#)

Constructor Summary

public	HTTPStreamerSessionSmoothStreamer()
--------	-----------------------------------------------------

Method Summary

void	clearLoggingValues()
------	--------------------------------------

boolean	containsIndex (String streamName)
---------	---------------------------------------------------

IHTTPStreamerSmoothStreamerIndex	getIndex (IHTTPStreamerSession httpStreamerSession, IHTTPStreamerApplicationContext appContext, String streamExt, String streamName, long playStart, long playDuration)
----------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SmoothStreamingLivePlaylist	getLivePlaylist()
-----------------------------	-----------------------------------

void	logLiveFragment (SmoothStreamerFragmentId fragmentId, com.wowza.wms.rtp.depaketizer.RTPPacketFragmentList fragmentData)
void	logVODFragment (SmoothStreamerFragmentId fragmentId, com.wowza.wms.rtp.depaketizer.RTPPacketFragmentList fragmentData)
void	setLivePlaylist (SmoothStreamingLivePlaylist livePlaylist)
void	shutdown ()
void	updateLoggingValues ()

Methods inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr, addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues, containsStreamDomainStr, containsStreamNameParts, doSessionRedirect, extractHTTPRequestInfo, getAppInstance, getConnectionHolder, getCookieStr, getDvrSessionInfo, getElapsedTime, getFileInfo, getHTTPDate, getHTTPHeader, getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader, getHTTPStreamerAdapter, getIOPerformanceCounter, getIpAddress, getLastRequest, getLiveStreamingPacketizer, getLock, getPlayDuration, getPlayStart, getProperties, getQueryStr, getRedirectSessionBody, getRedirectSessionCode, getRedirectSessionContentType, getRedirectSessionURL, getReferrer, getServerIp, getServerPort, getSessionId, getSessionProtocol, getSessionTimeout, getSessionType, getStream, getStreamDomainStr, getStreamExt, getStreamName, getStreamNameParts, getStreamPosition, getTimeRunning, getTimeRunningSeconds, getUri, getUserAgent, getUserHTTPHeaders, getUserQueryStr, getVHost, isAcceptSession, isActive, isFileInfo, isPlayLogged, isRedirectSession, isTimeout, isTimeoutSession, isValidated, isValidStreamDomainStr, lockRepeaterStreams, putFileInfo, putStreamNameParts, redirectSession, redirectSession, rejectSession, removeStreamDomainStr, setAcceptSession, setActive, setAppInstance, setCookieStr, setDvrSessionInfo, setHTTPStreamerAdapter, setIpAddress, setLiveStreamingPacketizer, setPlayDuration, setPlayLogged, setPlayStart, setQueryStr, setRedirectSession, setRedirectSessionBody, setRedirectSessionCode, setRedirectSessionContentType, setRedirectSessionURL, setReferrer, setServerIp, setServerPort, setSessionId, setSessionProtocol, setSessionTimeout, setSessionType, setStream, setStreamExt, setStreamName, setStreamPosition, setThreadContext, setTimeoutSession, setUri, setUserAgent, setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, shutdown, touch, updateLoggingValues, validStreamDomainToString

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),
[extractHTTPRequestInfo](#), [getAppInstance](#), [getConnectionHolder](#), [getCookieStr](#),
[getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#), [getHTTPHeader](#), [getHTTPHeaderMap](#),
[getHTTPHeaderNames](#), [getHTTPIntHeader](#), [getHTTPStreamerAdapter](#),
[getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#), [getLiveStreamingPacketizer](#),
[getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#), [getQueryStr](#),
[getRedirectSessionBody](#), [getRedirectSessionCode](#), [getRedirectSessionContentType](#),
[getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#), [getServerPort](#), [getSessionId](#),
[getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#), [getStream](#), [getStreamExt](#),
[getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#), [getTimeRunning](#),
[getTimeRunningSeconds](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),
[getVHost](#), [isAcceptSession](#), [isActive](#), [isFileInfo](#), [isPlayLogged](#), [isRedirectSession](#),
[isTimeout](#), [isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#),
[lockRepeaterStreams](#), [putFileInfo](#), [putStreamNameParts](#), [redirectSession](#),
[redirectSession](#), [rejectSession](#), [removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#),
[setAppInstance](#), [setCookieStr](#), [setDvrSessionInfo](#), [setHTTPStreamerAdapter](#),
[setIpAddress](#), [setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#),
[setPlayStart](#), [setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#),
[setRedirectSessionCode](#), [setRedirectSessionContentType](#), [setRedirectSessionURL](#),
[setReferrer](#), [setServerIp](#), [setServerPort](#), [getSessionId](#), [setSessionProtocol](#),
[setSessionTimeout](#), [setSessionType](#), [setStream](#), [setStreamExt](#), [setStreamName](#),
[setStreamPosition](#), [setTimeoutSession](#), [setUri](#), [setUserAgent](#), [setUserHTTPHeader](#),
[setUserQueryStr](#), [setVHost](#), [shutdown](#), [touch](#), [updateLoggingValues](#),
[validStreamDomainToString](#)

Constructors

HTTPStreamerSessionSmoothStreamer

```
public HTTPStreamerSessionSmoothStreamer()
```

Methods

shutdown

```
public void shutdown()
```

containsIndex

```
public boolean containsIndex(String streamName)
```

(continued from last page)

getIndex

```
public IHTTPStreamerSmoothStreamerIndex getIndex(IHTTPStreamerSession
httpStreamerSession,
IHTTPStreamerApplicationContext appContext,
String streamExt,
String streamName,
long playStart,
long playDuration)
```

updateLoggingValues

```
public void updateLoggingValues()
```

clearLoggingValues

```
public void clearLoggingValues()
```

getLivePlaylist

```
public SmoothStreamingLivePlaylist getLivePlaylist()
```

setLivePlaylist

```
public void setLivePlaylist(SmoothStreamingLivePlaylist livePlaylist)
```

logLiveFragment

```
public void logLiveFragment(SmoothStreamerFragmentId fragmentId,
com.wowza.wms.rtp.depaketizer.RTPPacketFragmentList fragmentData)
```

logVODFragment

```
public void logVODFragment(SmoothStreamerFragmentId fragmentId,
com.wowza.wms.rtp.depaketizer.RTPPacketFragmentList fragmentData)
```

Package

**com.wowza.wms.httpstreamer.webmstreami
ng.httpstreamer**

com.wowza.wms.httpstreamer.webmstreaming.httpstreamer

Class HTTPStreamerSessionWebM

java.lang.Object

└-com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

└-com.wowza.wms.httpstreamer.webmstreaming.httpstreamer.HTTPStreamerSessionWebM

All Implemented Interfaces:

[IHTTPStreamerSession](#)

public class **HTTPStreamerSessionWebM**
extends HTTPStreamerSessionBase

Fields inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

acceptSession, appInstance, connectionHolder, cookieStr, DATEFORMAT, elapsedTime, fastDateFormat, fileInfoMap, firstCheck, httpHeaders, httpStreamerAdapter, ioPerformanceCounter, ipAddress, isActive, isPlayLogged, lastRequest, liveStreamingPacketizer, lock, mediaCasterStreamLock, playDuration, playStart, properties, queryStr, redirectSession, redirectSessionBody, redirectSessionCode, redirectSessionContentType, redirectSessionURL, referrer, serverIp, serverPort, sessionId, sessionProtocol, sessionTimeout, sessionType, stream, streamDomainStrSet, streamExt, streamName, streamNamePartMap, streamPosition, timeoutSession, totalIOPerformance2Last, totalIOPerformanceLast, uri, userAgent, userHTTPHeaders, userQueryStr, vhost

Fields inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[SESSIONPROTOCOL_COUNT](#), [SESSIONPROTOCOL_CUPERTINOSTREAMING](#), [SESSIONPROTOCOL_DVRCHUNKSTREAMING](#), [SESSIONPROTOCOL_SANJOSESTREAMING](#), [SESSIONPROTOCOL_SMOOTHSTREAMING](#), [SESSIONPROTOCOL_UNKNOWN](#), [SESSIONPROTOCOL_WEBMSTREAMING](#), [SESSIONTYPE_LIVE](#), [SESSIONTYPE_LIVEDVR](#), [SESSIONTYPE_UNKNOWN](#), [SESSIONTYPE_VOD](#)

Constructor Summary

public	HTTPStreamerSessionWebM()
--------	-------------------------------------------

Method Summary

WebMPacketizerSessionTracker	getSessionTracker()
void	setSessionTracker (WebMPacketizerSessionTracker sessionTracker)
void	shutdown()

Methods inherited from class com.wowza.wms.httpstreamer.model.HTTPStreamerSessionBase

```

acceptSession, addIOPerformance, addIOPerformance2, addStreamDomainStr,
addStreamDomainStrs, addUserHTTPHeaders, checkAndSetPlayLogged, clearLoggingValues,
containsStreamDomainStr, containsStreamNameParts, doSessionRedirect,
extractHTTPRequestInfo, getAppInstance, getConnectionHolder, getCookieStr,
getDvrSessionInfo, getElapsedTime, getFileInfo, getHTTPDate, getHTTPHeader,
getHTTPHeaderMap, getHTTPHeaderNames, getHTTPIntHeader, getHTTPStreamerAdapter,
getIOPerformanceCounter, getIpAddress, getLastRequest, getLiveStreamingPacketizer,
getLock, getPlayDuration, getPlayStart, getProperties, getQueryStr,
getRedirectSessionBody, getRedirectSessionCode, getRedirectSessionContentType,
getRedirectSessionURL, getReferrer, getServerIp, getServerPort, getSessionId,
getSessionProtocol, getSessionTimeout, getSessionType, getStream, getStreamDomainStr,
getStreamExt, getStreamName, getStreamNameParts, getStreamPosition, getTimeRunning,
getTimeRunningSeconds, getUri, getUserAgent, getUserHTTPHeaders, getUserQueryStr,
getVHost, isAcceptSession, isActive, isFileInfo, isPlayLogged, isRedirectSession,
isTimeout, isTimeoutSession, isValidated, isValidStreamDomainStr,
lockRepeaterStreams, putFileInfo, putStreamNameParts, redirectSession,
redirectSession, rejectSession, removeStreamDomainStr, setAcceptSession, setActive,
setAppInstance, setCookieStr, setDvrSessionInfo, setHTTPStreamerAdapter,
setIpAddress, setLiveStreamingPacketizer, setPlayDuration, setPlayLogged,
setPlayStart, setQueryStr, setRedirectSession, setRedirectSessionBody,
setRedirectSessionCode, setRedirectSessionContentType, setRedirectSessionURL,
setReferrer, setServerIp, setServerPort, setSessionId, setSessionProtocol,
setSessionTimeout, setSessionType, setStream, setStreamExt, setStreamName,
setStreamPosition, setThreadContext, setTimeoutSession, setUri, setUserAgent,
setUserHTTPHeader, setUserQueryStr, setValidated, setVHost, shutdown, touch,
updateLoggingValues, validStreamDomainToString

```

Methods inherited from class `java.lang.Object`

```

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

```

Methods inherited from interface [com.wowza.wms.httpstreamer.model.IHTTPStreamerSession](#)

[acceptSession](#), [addIOPerformance](#), [addIOPerformance2](#), [addStreamDomainStr](#),
[addStreamDomainStrs](#), [addUserHTTPHeaders](#), [checkAndSetPlayLogged](#), [clearLoggingValues](#),
[containsStreamDomainStr](#), [containsStreamNameParts](#), [doSessionRedirect](#),
[extractHTTPRequestInfo](#), [getAppInstance](#), [getConnectionHolder](#), [getCookieStr](#),
[getDvrSessionInfo](#), [getElapsedTime](#), [getFileInfo](#), [getHTTPHeader](#), [getHTTPHeaderMap](#),
[getHTTPHeaderNames](#), [getHTTPIntHeader](#), [getHTTPStreamerAdapter](#),
[getIOPerformanceCounter](#), [getIpAddress](#), [getLastRequest](#), [getLiveStreamingPacketizer](#),
[getLock](#), [getPlayDuration](#), [getPlayStart](#), [getProperties](#), [getQueryStr](#),
[getRedirectSessionBody](#), [getRedirectSessionCode](#), [getRedirectSessionContentType](#),
[getRedirectSessionURL](#), [getReferrer](#), [getServerIp](#), [getServerPort](#), [getSessionId](#),
[getSessionProtocol](#), [getSessionTimeout](#), [getSessionType](#), [getStream](#), [getStreamExt](#),
[getStreamName](#), [getStreamNameParts](#), [getStreamPosition](#), [getTimeRunning](#),
[getTimeRunningSeconds](#), [getUri](#), [getUserAgent](#), [getUserHTTPHeaders](#), [getUserQueryStr](#),
[getVHost](#), [isAcceptSession](#), [isActive](#), [isFileInfo](#), [isPlayLogged](#), [isRedirectSession](#),
[isTimeout](#), [isTimeoutSession](#), [isValidated](#), [isValidStreamDomainStr](#),
[lockRepeaterStreams](#), [putFileInfo](#), [putStreamNameParts](#), [redirectSession](#),
[redirectSession](#), [rejectSession](#), [removeStreamDomainStr](#), [setAcceptSession](#), [setActive](#),
[setAppInstance](#), [setCookieStr](#), [setDvrSessionInfo](#), [setHTTPStreamerAdapter](#),
[setIpAddress](#), [setLiveStreamingPacketizer](#), [setPlayDuration](#), [setPlayLogged](#),
[setPlayStart](#), [setQueryStr](#), [setRedirectSession](#), [setRedirectSessionBody](#),
[setRedirectSessionCode](#), [setRedirectSessionContentType](#), [setRedirectSessionURL](#),
[setReferrer](#), [setServerIp](#), [setServerPort](#), [getSessionId](#), [setSessionProtocol](#),
[setSessionTimeout](#), [setSessionType](#), [setStream](#), [setStreamExt](#), [setStreamName](#),
[setStreamPosition](#), [setTimeoutSession](#), [setUri](#), [setUserAgent](#), [setUserHTTPHeader](#),
[setUserQueryStr](#), [setVHost](#), [shutdown](#), [touch](#), [updateLoggingValues](#),
[validStreamDomainToString](#)

Constructors

HTTPStreamerSessionWebM

```
public HTTPStreamerSessionWebM()
```

Methods

getSessionTracker

```
public WebMPacketizerSessionTracker getSessionTracker()
```

setSessionTracker

```
public void setSessionTracker(WebMPacketizerSessionTracker sessionTracker)
```

shutdown

```
public void shutdown()
```

Package

com.wowza.wms.logging

com.wowza.wms.logging Interface Constants

public interface **Constants**
extends

Constants used internally throughout log4j.

Field Summary

public static final	<u>ABSOLUTE_FORMAT</u> ABSOLUTE string literal. Value: ABSOLUTE
public static final	<u>ABSOLUTE_TIME_PATTERN</u> SimpleTimePattern for ABSOLUTE. Value: HH:mm:ss,SSS
public static final	<u>APPLICATION_KEY</u> application string literal. Value: application
public static final	<u>CODES_HREF</u> Codes URL string literal. Value: http://logging.apache.org/log4j/docs/codes.html
public static final	<u>CONFIGURATOR_CLASS_KEY</u> log4j.configuratorClass string literal. Value: log4j.configuratorClass
public static final	<u>DATE_AND_TIME_FORMAT</u> DATE string literal. Value: DATE
public static final	<u>DATE_AND_TIME_PATTERN</u> SimpleTimePattern for DATE. Value: dd MMM yyyy HH:mm:ss,SSS
public static final	<u>DEFAULT_CONFIGURATION_FILE</u> The default property file name for automatic configuration. Value: log4j.properties
public static final	<u>DEFAULT_CONFIGURATION_KEY</u> log4j.configuration string literal. Value: log4j.configuration
public static final	<u>DEFAULT_REPOSITORY_NAME</u> The name of the default repository is "default" (without the quotes). Value: default
public static final	<u>DEFAULT_XML_CONFIGURATION_FILE</u> The default XML configuration file name for automatic configuration. Value: log4j.xml

public static final	HOSTNAME_KEY hostname string literal. Value: hostname
public static final	ISO8601_FORMAT ISO8601 string literal. Value: ISO8601
public static final	ISO8601_PATTERN SimpleTimePattern for ISO8601. Value: yyyy-MM-dd HH:mm:ss,SSS
public static final	JNDI_CONTEXT_NAME JNDI context name string literal. Value: java:comp/env/log4j/context-name
public static final	LOG4J_ID_KEY log4jid string literal. Value: log4jid
public static final	LOG4J_PACKAGE_NAME log4j package name string literal. Value: org.apache.log4j
public static final	RECEIVER_NAME_KEY receiver string literal. Value: receiver
public static final	TEMP_CONSOLE_APPENDER_NAME TEMP_CONSOLE_APPENDER string literal. Value: TEMP_CONSOLE_APPENDER
public static final	TEMP_LIST_APPENDER_NAME TEMP_LIST_APPENDER string literal. Value: TEMP_LIST_APPENDER
public static final	TIMESTAMP_RULE_FORMAT time stamp pattern string literal. Value: yyyy/MM/dd HH:mm:ss

Fields

LOG4J_PACKAGE_NAME

public static final java.lang.String **LOG4J_PACKAGE_NAME**

log4j package name string literal.
Constant value: **org.apache.log4j**

DEFAULT_REPOSITORY_NAME

public static final java.lang.String **DEFAULT_REPOSITORY_NAME**

The name of the default repository is "default" (without the quotes).
Constant value: **default**

APPLICATION_KEY

```
public static final java.lang.String APPLICATION_KEY
```

application string literal.

Constant value: **application**

HOSTNAME_KEY

```
public static final java.lang.String HOSTNAME_KEY
```

hostname string literal.

Constant value: **hostname**

RECEIVER_NAME_KEY

```
public static final java.lang.String RECEIVER_NAME_KEY
```

receiver string literal.

Constant value: **receiver**

LOG4J_ID_KEY

```
public static final java.lang.String LOG4J_ID_KEY
```

log4jid string literal.

Constant value: **log4jid**

TIMESTAMP_RULE_FORMAT

```
public static final java.lang.String TIMESTAMP_RULE_FORMAT
```

time stamp pattern string literal.

Constant value: **yyyy/MM/dd HH:mm:ss**

DEFAULT_CONFIGURATION_FILE

```
public static final java.lang.String DEFAULT_CONFIGURATION_FILE
```

The default property file name for automatic configuration.

Constant value: **log4j.properties**

DEFAULT_XML_CONFIGURATION_FILE

```
public static final java.lang.String DEFAULT_XML_CONFIGURATION_FILE
```

The default XML configuration file name for automatic configuration.

Constant value: **log4j.xml**

DEFAULT_CONFIGURATION_KEY

```
public static final java.lang.String DEFAULT_CONFIGURATION_KEY
```

log4j.configuration string literal.

Constant value: **log4j.configuration**

(continued from last page)

CONFIGURATOR_CLASS_KEY

```
public static final java.lang.String CONFIGURATOR_CLASS_KEY
```

log4j.configuratorClass string literal.

Constant value: **log4j.configuratorClass**

JNDI_CONTEXT_NAME

```
public static final java.lang.String JNDI_CONTEXT_NAME
```

JNDI context name string literal.

Constant value: **java:comp/env/log4j/context-name**

TEMP_LIST_APPENDER_NAME

```
public static final java.lang.String TEMP_LIST_APPENDER_NAME
```

TEMP_LIST_APPENDER string literal.

Constant value: **TEMP_LIST_APPENDER**

TEMP_CONSOLE_APPENDER_NAME

```
public static final java.lang.String TEMP_CONSOLE_APPENDER_NAME
```

TEMP_CONSOLE_APPENDER string literal.

Constant value: **TEMP_CONSOLE_APPENDER**

CODES_HREF

```
public static final java.lang.String CODES_HREF
```

Codes URL string literal.

Constant value: **http://logging.apache.org/log4j/docs/codes.html**

ABSOLUTE_FORMAT

```
public static final java.lang.String ABSOLUTE_FORMAT
```

ABSOLUTE string literal.

Constant value: **ABSOLUTE**

ABSOLUTE_TIME_PATTERN

```
public static final java.lang.String ABSOLUTE_TIME_PATTERN
```

SimpleTimePattern for ABSOLUTE.

Constant value: **HH:mm:ss,SSS**

DATE_AND_TIME_FORMAT

```
public static final java.lang.String DATE_AND_TIME_FORMAT
```

DATE string literal.

Constant value: **DATE**

DATE_AND_TIME_PATTERN

```
public static final java.lang.String DATE_AND_TIME_PATTERN
```

(continued from last page)

SimpleTimePattern for DATE.

Constant value: **dd MMM yyyy HH:mm:ss,SSS**

ISO8601_FORMAT

```
public static final java.lang.String ISO8601_FORMAT
```

ISO8601 string literal.

Constant value: **ISO8601**

ISO8601_PATTERN

```
public static final java.lang.String ISO8601_PATTERN
```

SimpleTimePattern for ISO8601.

Constant value: **yyyy-MM-dd HH:mm:ss,SSS**

com.wowza.wms.logging Interface ILogNotify

All Known Implementing Classes:

[LogNotifyCalculateIncremental](#)

public interface **ILogNotify**
extends

ILogNotify: Interface to add custom fields to the Wowza Pro log files. To add your own custom log fields, define a class that implements this interface. The onLog method will be called each time the Wowza Pro server logs a message. Here is an example of a simple ILogNotify class that logs the current system time in milliseconds as a Long (systime-long) and as a String (systime-string).

```
package com.wowza.wms.plugin.newlogfields;

import org.apache.log4j.*;

import com.wowza.wms.logging.*;
import com.wowza.wms.stream.*;

public class LogNotifyDocs implements ILogNotify
{
    public void onLog(Level level, String comment, IMediaStream stream, String category,
String event, int status, String context)
    {
        long systime = System.currentTimeMillis();
        WMSLoggerFactory.putGlobalLogValue("systime-long", new Long(systime));
        WMSLoggerFactory.putGlobalLogValue("systime-string", systime+"");
    }
}
```

*Note: To get any of the values currently being logged use the logging API
WMSLoggerFactory.getGlobalLogValue(WMSLoggerIDs.FD_*)*

To add your class to Wowza Pro, compile your class into a .class file, bind the class into a .jar file and copy the .jar file into the Wowza Pro server /lib folder. Next, edit:

- [install-dir]/bin/setenv.bat (Windows)
- [install-dir]/bin/setenv.sh (Linux, OSX, Solaris)

Add **-Dcom.wowza.wms.logging.LogNotify=[full-path-to-your-ILogNotify-class]** to the **JAVA_OPTS**. For example for the class above the JAVA_OPTS would look like:

```
Linux/OSX
JAVA_OPTS="-Xmx768M -
Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.plugin.newlogfields.NewLogFields"

Windows
JAVA_OPTS=-Xmx768M -
Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.plugin.newlogfields.NewLogFields
```

If on Windows, also edit `[install-dir]/bin/WowzaMediaServerPro-Service.conf` and add `wrapper.java.additional.[n]=-Dcom.wowza.wms.logging.LogNotify=[full-path-to-your-ILogNotify-class]` to the **Java Additional Parameters** section where `[n]` is the next number in the list of active parameters. For example for the class above if the last active additional parameter is 6, the entry would look like this:

```
wrapper.java.additional.7=-
Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.plugin.newlogfields.NewLogFields
```

Next, edit `[install-dir]/conf/log4j.properties` and add the new field names to any `log4j.appender.[appender-name].layout.Fields` fields lists to which you want to log these values. For example:

```
log4j.appender.stdout.layout.Fields=x-severity,x-category,x-event,x-ctx,x-comment,systemtime-long,systemtime-string
```

Method Summary

void	<code>onLog(org.apache.log4j.Level level, String comment, IMediaStream stream, String category, String event, int status, String context)</code> Called each time the server logs a message.
------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

onLog

```
public void onLog(org.apache.log4j.Level level,
    String comment,
    IMediaStream stream,
    String category,
    String event,
    int status,
    String context)
```

Called each time the server logs a message.

Parameters:

level - log level as defined by (org.apache.log4j.Level)
comment - comment part of the log statement
stream - if stream category log message it's the source stream

(continued from last page)

category - log category as defined by WMSLoggerIDs.CAT_*

event - log event as defined by WMSLoggerIDs.EVT_*

status - log status (same as HTTP status field) as defined by WMSLoggerIDs.STAT_*

context - log context value like stream name, vhost name, application name

com.wowza.wms.logging Class LogNotifyCalculateIncremental

java.lang.Object

└─com.wowza.wms.logging.LogNotifyCalculateIncremental

All Implemented Interfaces:

[ILogNotify](#)

public class **LogNotifyCalculateIncremental**
extends Object
implements [ILogNotify](#)

LogNotifyCalculateIncremental: pre-built implementation of ILogNotify that adds 5 new log fields:

- cs-bytes-inc (client to server bytes streamed since last log entry)
- sc-bytes-inc (server to client bytesstreamed since last log entry)
- cs-stream-bytes-inc (client to server stream bytesstreamed since last log entry)
- sc-stream-bytes-inc (server to client stream bytesstreamed since last log entry)
- x-duration-inc (time in seconds that have passed since the last log event)

These are incremental versions of the regular log values. To add this to Wowza Pro edit:

- [install-dir]/bin/setenv.bat (Windows)
- [install-dir]/bin/setenv.sh (Linux, OSX)

Add `-Dcom.wowza.wms.logging.LogNotify=com.wowza.wms.logging.LogNotifyCalculateIncremental` to the `JAVA_OPTS`. Also, edit `[install-dir]/conf/log4j.properties` and add these field names to any `log4j.appender.[appender-name].layout.Fields` fields lists to which you want to log these values.

*NOTE: These new log values are only accurate if all the events are included for the **session** and **stream** log categories.*

Field Summary

public static final	FD_cs_bytes_inc Value: cs-bytes-inc
public static final	FD_cs_stream_bytes_inc Value: cs-stream-bytes-inc
public static final	FD_sc_bytes_inc Value: sc-bytes-inc
public static final	FD_sc_stream_bytes_inc Value: sc-stream-bytes-inc
public static final	FD_x_duration_inc Value: x-duration-inc

Constructor Summary

public	LogNotifyCalculateIncremental()
--------	-------------------------------------------------

Method Summary

void	onLog (org.apache.log4j.Level level, String comment, IMediaStream stream, String category, String event, int status, String context)
------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods inherited from class [java.lang.Object](#)

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.logging.ILogNotify](#)

[onLog](#)

Fields

FD_cs_bytes_inc

public static final java.lang.String **FD_cs_bytes_inc**

Constant value: **cs-bytes-inc**

FD_sc_bytes_inc

public static final java.lang.String **FD_sc_bytes_inc**

Constant value: **sc-bytes-inc**

FD_cs_stream_bytes_inc

public static final java.lang.String **FD_cs_stream_bytes_inc**

Constant value: **cs-stream-bytes-inc**

FD_sc_stream_bytes_inc

public static final java.lang.String **FD_sc_stream_bytes_inc**

Constant value: **sc-stream-bytes-inc**

FD_x_duration_inc

public static final java.lang.String **FD_x_duration_inc**

Constant value: **x-duration-inc**

Constructors

(continued from last page)

LogNotifyCalculateIncremental

```
public LogNotifyCalculateIncremental()
```

Methods

onLog

```
public void onLog(org.apache.log4j.Level level,  
    String comment,  
    IMediaStream stream,  
    String category,  
    String event,  
    int status,  
    String context)
```


com.wowza.wms.logging Class UDPAppender

```

java.lang.Object
|
|--org.apache.log4j.AppenderSkeleton
|   |
|   |--com.wowza.wms.logging.UDPAppender

```

All Implemented Interfaces:

PortBased, org.apache.log4j.spi.OptionHandler, org.apache.log4j.Appender

```

public class UDPAppender
extends org.apache.log4j.AppenderSkeleton
implements org.apache.log4j.Appender, org.apache.log4j.spi.OptionHandler, PortBased

```

Sends log information as a UDP datagrams.

The UDPAppender is meant to be used as a diagnostic logging tool so that logging can be monitored by a simple UDP client.

Messages are not sent as LoggingEvent objects but as text after applying the designated Layout.

The port and remoteHost properties can be set in configuration properties. By setting the remoteHost to a broadcast address any number of clients can listen for log messages.

This was inspired and really extended/copied from SocketAppender. Please see the docs for the proper credit to the authors of that class.

Field Summary

public static final	DEFAULT_PORT The default port number for the UDP packets, 9991. Value: 9991
---------------------	----------------------------------------------------------------------------------------------------------

Fields inherited from class org.apache.log4j.AppenderSkeleton

closed, errorHandler, headFilter, layout, name, tailFilter, threshold

Constructor Summary

public	UDPAppender ()
public	UDPAppender (java.net.InetAddress address, int port) Sends UDP packets to the address and port.
public	UDPAppender (String host, int port) Sends UDP packets to the address and port.

Method Summary

void	activateOptions () Open the UDP sender for the RemoteHost and Port .
void	append (org.apache.log4j.spi.LoggingEvent event)

void	<code>cleanUp()</code> Close the UDP Socket and release the underlying connector thread if it has been created
void	<code>close()</code> Close this appender.
String	<code>getApplication()</code> Returns value of the App option.
String	<code>getEncoding()</code> Returns value of the Encoding option.
int	<code>getPort()</code> Returns value of the Port option.
String	<code>getRemoteHost()</code> Returns value of the RemoteHost option.
boolean	<code>isActive()</code>
boolean	<code>requiresLayout()</code> The UDPAppender uses layouts.
void	<code>setApplication(String app)</code> The App option takes a string value which should be the name of the application getting logged.
void	<code>setEncoding(String encoding)</code> The Encoding option specifies how the bytes are encoded.
void	<code>setPort(int port)</code> The Port option takes a positive integer representing the port where UDP packets will be sent.
void	<code>setRemoteHost(String host)</code> The RemoteHost option takes a string value which should be the host name or ipaddress to send the UDP packets.

Methods inherited from class org.apache.log4j.AppenderSkeleton

activateOptions, addFilter, append, clearFilters, doAppend, finalize, getErrorHandler, getFilter, getFirstFilter, getLayout, getName, getThreshold, isAsSevereAsThreshold, setErrorHandler, setLayout, setName, setThreshold

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface org.apache.log4j.Appender

addFilter, clearFilters, close, doAppend, getErrorHandler, getFilter, getLayout, getName, requiresLayout, setErrorHandler, setLayout, setName

Methods inherited from interface org.apache.log4j.spi.OptionHandler

activateOptions

Methods inherited from interface com.wowza.wms.logging.PortBased

```
getPort
```

Methods inherited from interface `com.wowza.wms.logging.NetworkBased`

```
getName, isActive
```

Fields

DEFAULT_PORT

```
public static final int DEFAULT_PORT
```

The default port number for the UDP packets, 9991.
Constant value: **9991**

Constructors

UDPAppender

```
public UDPAppender()
```

UDPAppender

```
public UDPAppender(java.net.InetAddress address,  
                    int port)
```

Sends UDP packets to the address and port.

UDPAppender

```
public UDPAppender(String host,  
                    int port)
```

Sends UDP packets to the address and port.

Methods

activateOptions

```
public void activateOptions()
```

Open the UDP sender for the **RemoteHost** and **Port**.

close

```
public void close()
```

Close this appender.

This will mark the appender as closed and call then [cleanUp\(\)](#) method.

(continued from last page)

cleanUp

```
public void cleanUp()
```

Close the UDP Socket and release the underlying connector thread if it has been created

append

```
public void append(org.apache.log4j.spi.LoggingEvent event)
```

isActive

```
public boolean isActive()
```

requiresLayout

```
public boolean requiresLayout()
```

The **UDPAppender** uses layouts. Hence, this method returns true.

setRemoteHost

```
public void setRemoteHost(String host)
```

The **RemoteHost** option takes a string value which should be the host name or ipaddress to send the UDP packets.

getRemoteHost

```
public String getRemoteHost()
```

Returns value of the **RemoteHost** option.

setApplication

```
public void setApplication(String app)
```

The **App** option takes a string value which should be the name of the application getting logged. If property was already set (via system property), don't set here.

getApplication

```
public String getApplication()
```

Returns value of the **App** option.

setEncoding

```
public void setEncoding(String encoding)
```

The **Encoding** option specifies how the bytes are encoded. If this option is not specified, the System encoding is used.

getEncoding

```
public String getEncoding()
```

(continued from last page)

Returns value of the **Encoding** option.

setPort

```
public void setPort(int port)
```

The **Port** option takes a positive integer representing the port where UDP packets will be sent.

getPort

```
public int getPort()
```

Returns value of the **Port** option.

com.wowza.wms.logging Class WMSLogger

```

java.lang.Object
  |
  +- org.apache.log4j.Category
      |
      +- org.apache.log4j.Logger
          |
          +- com.wowza.wms.logging.WMSLogger
  
```

All Implemented Interfaces:

org.apache.log4j.spi.AppenderAttachable

```

public class WMSLogger
extends org.apache.log4j.Logger
  
```

Fields inherited from class org.apache.log4j.Category

additive, level, name, parent, repository, resourceBundle

Constructor Summary

public	WMSLogger (String name, org.apache.log4j.Logger tmpLogger)
public	WMSLogger (String name)

Method Summary

void	debug (String comment)
void	debug (String comment, IMediaStream stream)
void	debug (String comment, IMediaStream stream, String category, String event, int status, String context)
void	debug (String comment, String category, String event)
void	debug (String comment, String category, String event, int status, String context)
void	error (String comment)
void	error (String comment, IMediaStream stream)
void	error (String comment, IMediaStream stream, String category, String event, int status, String context)
void	error (String comment, String category, String event)

void	<code>error</code> (String comment, String category, String event, int status, String context)
void	<code>fatal</code> (String comment)
void	<code>fatal</code> (String comment, <code>IMediaStream</code> stream)
void	<code>fatal</code> (String comment, <code>IMediaStream</code> stream, String category, String event, int status, String context)
void	<code>fatal</code> (String comment, String category, String event)
void	<code>fatal</code> (String comment, String category, String event, int status, String context)
static <code>WMSLogger</code>	<code>getLogger</code> (String name)
void	<code>info</code> (String comment)
void	<code>info</code> (String comment, <code>IMediaStream</code> stream)
void	<code>info</code> (String comment, <code>IMediaStream</code> stream, String category, String event, int status, String context)
void	<code>info</code> (String comment, String category, String event)
void	<code>info</code> (String comment, String category, String event, int status, String context)
boolean	<code>isDebugEnabled</code> ()
boolean	<code>isEnabledFor</code> (org.apache.log4j.Priority level)
boolean	<code>isErrorEnabled</code> ()
boolean	<code>isInfoEnabled</code> ()
boolean	<code>isTraceEnabled</code> ()
boolean	<code>isWarnEnabled</code> ()
void	<code>log</code> (org.apache.log4j.Level level, String comment)
void	<code>log</code> (org.apache.log4j.Level level, String comment, <code>IMediaStream</code> stream)
void	<code>log</code> (org.apache.log4j.Level level, String comment, <code>IMediaStream</code> stream, String category, String event)
void	<code>log</code> (org.apache.log4j.Level level, String comment, <code>IMediaStream</code> stream, String category, String event, int status, String context)

void	log (org.apache.log4j.Level level, String comment, String category, String event)
void	warn (String comment)
void	warn (String comment, IMediaStream stream)
void	warn (String comment, IMediaStream stream, String category, String event, int status, String context)
void	warn (String comment, String category, String event)
void	warn (String comment, String category, String event, int status, String context)

Methods inherited from class org.apache.log4j.Logger

getLogger, getLogger, getLogger, getRootLogger, isTraceEnabled, trace, trace

Methods inherited from class org.apache.log4j.Category

addAppender, assertLog, callAppenders, debug, debug, error, error, exists, fatal, fatal, forcedLog, getAdditivity, getAllAppenders, getAppender, getChainedPriority, getCurrentCategories, getDefaultHierarchy, getEffectiveLevel, getHierarchy, getInstance, getInstance, getLevel, getLoggerRepository, getName, getParent, getPriority, getResourceBundle, getResourceBundleString, getRoot, info, info, isAttached, isDebugEnabled, isEnabledFor, isInfoEnabled, l7dlog, l7dlog, log, log, log, removeAllAppenders, removeAppender, removeAppender, setAdditivity, setLevel, setPriority, setResourceBundle, shutdown, warn, warn

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface org.apache.log4j.spi.AppenderAttachable

addAppender, getAllAppenders, getAppender, isAttached, removeAllAppenders, removeAppender, removeAppender

Constructors

WMSLogger

```
public WMSLogger(String name,
                  org.apache.log4j.Logger tmpLogger)
```

WMSLogger

```
public WMSLogger(String name)
```


Methods

getLogger

```
public static WMSLogger getLogger(String name)
```

isWarnEnabled

```
public boolean isWarnEnabled()
```

isErrorEnabled

```
public boolean isErrorEnabled()
```

isTraceEnabled

```
public boolean isTraceEnabled()
```

isDebugEnabled

```
public boolean isDebugEnabled()
```

isInfoEnabled

```
public boolean isInfoEnabled()
```

isEnabledFor

```
public boolean isEnabledFor(org.apache.log4j.Priority level)
```

log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               IMediaStream stream,  
               String category,  
               String event,  
               int status,  
               String context)
```

(continued from last page)

log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               IMediaStream stream,  
               String category,  
               String event)
```

log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               String category,  
               String event)
```

log

```
public void log(org.apache.log4j.Level level,  
               String comment)
```

log

```
public void log(org.apache.log4j.Level level,  
               String comment,  
               IMediaStream stream)
```

info

```
public void info(String comment)
```

info

```
public void info(String comment,  
               IMediaStream stream)
```

info

```
public void info(String comment,  
               String category,  
               String event)
```

(continued from last page)

info

```
public void info(String comment,
                String category,
                String event,
                int status,
                String context)
```

info

```
public void info(String comment,
                IMediaStream stream,
                String category,
                String event,
                int status,
                String context)
```

error

```
public void error(String comment)
```

error

```
public void error(String comment,
                IMediaStream stream)
```

error

```
public void error(String comment,
                String category,
                String event)
```

error

```
public void error(String comment,
                String category,
                String event,
                int status,
                String context)
```

error

```
public void error(String comment,
                IMediaStream stream,
                String category,
                String event,
                int status,
                String context)
```

fatal

```
public void fatal(String comment)
```

fatal

```
public void fatal(String comment,  
    IMediaStream stream)
```

fatal

```
public void fatal(String comment,  
    String category,  
    String event)
```

fatal

```
public void fatal(String comment,  
    String category,  
    String event,  
    int status,  
    String context)
```

fatal

```
public void fatal(String comment,  
    IMediaStream stream,  
    String category,  
    String event,  
    int status,  
    String context)
```

debug

```
public void debug(String comment)
```

debug

```
public void debug(String comment,  
    IMediaStream stream)
```

(continued from last page)

debug

```
public void debug(String comment,  
                  String category,  
                  String event)
```

debug

```
public void debug(String comment,  
                  String category,  
                  String event,  
                  int status,  
                  String context)
```

debug

```
public void debug(String comment,  
                  IMediaStream stream,  
                  String category,  
                  String event,  
                  int status,  
                  String context)
```

warn

```
public void warn(String comment)
```

warn

```
public void warn(String comment,  
                  IMediaStream stream)
```

warn

```
public void warn(String comment,  
                  String category,  
                  String event)
```

warn

```
public void warn(String comment,  
                  String category,  
                  String event,  
                  int status,  
                  String context)
```

(continued from last page)

warn

```
public void warn(String comment,  
    IMediaStream stream,  
    String category,  
    String event,  
    int status,  
    String context)
```

com.wowza.wms.logging Class WMSLoggerFactory

java.lang.Object

└─com.wowza.wms.logging.WMSLoggerFactory

All Implemented Interfaces:

org.apache.log4j.spi.LoggerFactory

public class **WMSLoggerFactory**
 extends Object
 implements org.apache.log4j.spi.LoggerFactory

Field Summary

public static final	LOGGERNAME_SERVER Value: _Server_
---------------------	-------------------------------------------------------------

Constructor Summary

public	WMSLoggerFactory()
--------	------------------------------------

Method Summary

WMSLogger	forceNewLoggerInstance (String name, org.apache.log4j.Logger tmpLogger)
static Object	getGlobalLogValue (String key)
static WMSLoggerFactory	getInstance ()
static WMSLogger	getLogger (Class classObj)
static WMSLogger	getLoggerObj (IApplication application)
static WMSLogger	getLoggerObj (IApplicationInstance appInstance)
static WMSLogger	getLoggerObj (IVHost vhost)
WMSLogger	getLoggerObj (String name)
static void	initContextLogging (IApplication application)
static void	initContextLogging (IApplicationInstance appInstance)
static void	initContextLogging (IVHost vhost)

static WMSLogger	initializeLogging (String loggingConfigURL)
static WMSLogger	initializeLogging (String loggingConfigURL, IVHost vhost)
static boolean	isGlobalLogValueSet (String key)
org.apache.log4j.Logger	makeNewLoggerInstance (String name)
static void	putGlobalLogValue (String key, Object obj)
static void	removeGlobalLogValue (String key)
static void	removeGlobalLogValues ()
static void	resetMDC ()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface org.apache.log4j.spi.LoggerFactory

makeNewLoggerInstance

Fields

LOGGERNAME_SERVER

```
public static final java.lang.String LOGGERNAME_SERVER
```

Constant value: **_Server_**

Constructors

WMSLoggerFactory

```
public WMSLoggerFactory()
```

Methods

getLoggerObj

```
public WMSLogger getLoggerObj(String name)
```


(continued from last page)

forceNewLoggerInstance

```
public WMSLogger forceNewLoggerInstance(String name,  
    org.apache.log4j.Logger tmpLogger)
```

getInstance

```
public static WMSLoggerFactory getInstance()
```

initContextLogging

```
public static void initContextLogging(IVHost vhost)
```

initContextLogging

```
public static void initContextLogging(IApplication application)
```

initContextLogging

```
public static void initContextLogging(IApplicationInstance appInstance)
```

initializeLogging

```
public static WMSLogger initializeLogging(String loggingConfigURL)
```

initializeLogging

```
public static WMSLogger initializeLogging(String loggingConfigURL,  
    IVHost vhost)
```

makeNewLoggerInstance

```
public org.apache.log4j.Logger makeNewLoggerInstance(String name)
```

resetMDC

```
public static void resetMDC()
```

(continued from last page)

removeGlobalLogValues

```
public static void removeGlobalLogValues()
```

removeGlobalLogValue

```
public static void removeGlobalLogValue(String key)
```

isGlobalLogValueSet

```
public static boolean isGlobalLogValueSet(String key)
```

putGlobalLogValue

```
public static void putGlobalLogValue(String key,  
                                     Object obj)
```

getGlobalLogValue

```
public static Object getGlobalLogValue(String key)
```

getLoggerObj

```
public static WMSLogger getLoggerObj(IVHost vhost)
```

getLoggerObj

```
public static WMSLogger getLoggerObj(IApplication application)
```

getLoggerObj

```
public static WMSLogger getLoggerObj(IApplicationInstance appInstance)
```

getLogger

```
public static WMSLogger getLogger(Class classObj)
```

com.wowza.wms.logging

Class WMSLoggerIDs

java.lang.Object

└-com.wowza.wms.logging.WMSLoggerIDs

public class **WMSLoggerIDs**
extends Object

Field Summary

public static final	CAT_ALL
public static final	CAT_application Value: application
public static final	CAT_cupertino Value: cupertino
public static final	CAT_dvrchunk Value: dvrchunk
public static final	CAT_rtsp Value: rtsp
public static final	CAT_sanjose Value: sanjose
public static final	CAT_server Value: server
public static final	CAT_session Value: session
public static final	CAT_smoothstreaming Value: smoothstreaming
public static final	CAT_stream Value: stream
public static final	CAT_transcoder Value: transcoder
public static final	CAT_vhost Value: vhost

public static final	CAT_webm Value: webm
public static final	CTRL_playlist_node Value: CTRL-playlist-node
public static final	EVT_ALL
public static final	EVT_announce Value: announce
public static final	EVT_app_start Value: app-start
public static final	EVT_app_stop Value: app-stop
public static final	EVT_comment Value: comment
public static final	EVT_connect Value: connect
public static final	EVT_connect_burst Value: connect-burst
public static final	EVT_connect_pending Value: connect-pending
public static final	EVT_create Value: create
public static final	EVT_decoderaudiostart Value: decoder-audio-start
public static final	EVT_decoderaudiostop Value: decoder-audio-stop
public static final	EVT_decodervideostart Value: decoder-video-start
public static final	EVT_decodervideostop Value: decoder-video-stop
public static final	EVT_describe Value: describe

public static final	EVT_destroy Value: destroy
public static final	EVT_disconnect Value: disconnect
public static final	EVT_encoderaudiostart Value: encoder-audio-start
public static final	EVT_encoderaudiostop Value: encoder-audio-stop
public static final	EVT_encodervideostart Value: encoder-video-start
public static final	EVT_encodervideostop Value: encoder-video-stop
public static final	EVT_pause Value: pause
public static final	EVT_play Value: play
public static final	EVT_publish Value: publish
public static final	EVT_record Value: record
public static final	EVT_recordstop Value: recordstop
public static final	EVT_seek Value: seek
public static final	EVT_server_start Value: server-start
public static final	EVT_server_stop Value: server-stop
public static final	EVT_setbuffertime Value: setbuffertime
public static final	EVT_setstreamtype Value: setstreamtype

public static final	EVT_stop Value: stop
public static final	EVT_unpause Value: unpause
public static final	EVT_unpublish Value: unpublish
public static final	EVT_vhost_start Value: vhost-start
public static final	EVT_vhost_stop Value: vhost-stop
public static final	FD_ALL
public static final	FD_c_client_id Value: c-client-id
public static final	FD_c_ip Value: c-ip
public static final	FD_c_proto Value: c-proto
public static final	FD_c_referrer Value: c-referrer
public static final	FD_c_user_agent Value: c-user-agent
public static final	FD_cs_bytes Value: cs-bytes
public static final	FD_cs_stream_bytes Value: cs-stream-bytes
public static final	FD_cs_uri_query Value: cs-uri-query
public static final	FD_cs_uri_stem Value: cs-uri-stem
public static final	FD_date Value: date

public static final	FD_s_ip Value: s-ip
public static final	FD_s_port Value: s-port
public static final	FD_s_uri Value: s-uri
public static final	FD_sc_bytes Value: sc-bytes
public static final	FD_sc_stream_bytes Value: sc-stream-bytes
public static final	FD_time Value: time
public static final	FD_tz Value: tz
public static final	FD_x_app Value: x-app
public static final	FD_x_appinst Value: x-appinst
public static final	FD_x_category Value: x-category
public static final	FD_x_comment Value: x-comment
public static final	FD_x_ctx Value: x-ctx
public static final	FD_x_ctx_override Value: x-ctx-override
public static final	FD_x_duration Value: x-duration
public static final	FD_x_event Value: x-event
public static final	FD_x_file_ext Value: x-file-ext

public static final	FD_x_file_length Value: x-file-length
public static final	FD_x_file_name Value: x-file-name
public static final	FD_x_file_size Value: x-file-size
public static final	FD_x_severity Value: x-severity
public static final	FD_x_sname Value: x-sname
public static final	FD_x_sname_query Value: x-sname-query
public static final	FD_x_spos Value: x-spos
public static final	FD_x_status Value: x-status
public static final	FD_x_stream_id Value: x-stream-id
public static final	FD_x_suri Value: x-suri
public static final	FD_x_suri_query Value: x-suri-query
public static final	FD_x_suri_stem Value: x-suri-stem
public static final	FD_x_vhost Value: x-vhost
public static final	PROTO_HTTPCUPERTINO Value: http (cupertino)
public static final	PROTO_HTTPDVRCHUNK Value: http (dvr)
public static final	PROTO_HTTPSANJOSE Value: http (sanjose)

public static final	PROTO_HTTPSCUPERTINO Value: https (cupertino)
public static final	PROTO_HTTPSDVRCHUNK Value: https (dvr)
public static final	PROTO_HTTPSMOOTH Value: http (smooth)
public static final	PROTO_HTTPSSANJOSE Value: https (sanjose)
public static final	PROTO_HTTPSMOOTH Value: https (smooth)
public static final	PROTO_HTTPSSTREAMER Value: https (streamer)
public static final	PROTO_HTTPSTREAMER Value: http (streamer)
public static final	PROTO_RTMP Value: rtmp
public static final	PROTO_RTMPE Value: rtmpe
public static final	PROTO_RTMPs Value: rtmps
public static final	PROTO_RTMPT Value: rtmpt (HTTP-1.1)
public static final	PROTO_RTMPTe Value: rtmpte (HTTP-1.1)
public static final	PROTO_RTMPTS Value: rtmpts (HTTP-1.1)
public static final	PROTO_RTSP Value: rtsp
public static final	STAT_connect_application_not_available Value: 302
public static final	STAT_connect_application_not_found Value: 404

public static final	<u>STAT_connect_bad_gateway</u> Value: 502
public static final	<u>STAT_connect_internal_error</u> Value: 500
public static final	<u>STAT_connect_license_limit</u> Value: 413
public static final	<u>STAT_connect_pending_wating</u> Value: 100
public static final	<u>STAT_connect_redirect</u> Value: 302
public static final	<u>STAT_connect_rejected_by_application</u> Value: 401
public static final	<u>STAT_connect_rejected_by_module</u> Value: 403
public static final	<u>STAT_connect_resource_limit</u> Value: 409
public static final	<u>STAT_connect_service_unavailable</u> Value: 503
public static final	<u>STAT_connect_successful</u> Value: 200
public static final	<u>STAT_connect_unknown_protocol</u> Value: 400
public static final	<u>STAT_general_internal_error</u> Value: 500
public static final	<u>STAT_general_successful</u> Value: 200
public static final	<u>STAT_play_bad_request</u> Value: 400
public static final	<u>STAT_play_internal_error</u> Value: 500
public static final	<u>STAT_play_rejected_by_application</u> Value: 401

public static final	<u>STAT_play_rejected_by_module</u> Value: 403
public static final	<u>STAT_play_stream_not_found</u> Value: 404
public static final	<u>STAT_play_successful</u> Value: 200
public static final	<u>STAT_play_unsupported_media_type</u> Value: 415
public static final	<u>STAT_publish_bad_request</u> Value: 400
public static final	<u>STAT_publish_in_use</u> Value: 409
public static final	<u>STAT_publish_internal_error</u> Value: 500
public static final	<u>STAT_publish_rejected_by_application</u> Value: 401
public static final	<u>STAT_publish_successful</u> Value: 200
public static final	<u>STAT_publish_unsupported_media_type</u> Value: 415
public static final	<u>STAT_stop_client_disconnect</u> Value: 408
public static final	<u>STAT_stop_successful</u> Value: 200

Constructor Summary

public	<u>WMSLoggerIDs()</u>
--------	---------------------------------------

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

(continued from last page)

FD_x_event

```
public static final java.lang.String FD_x_event
```

Constant value: **x-event**

FD_x_category

```
public static final java.lang.String FD_x_category
```

Constant value: **x-category**

FD_date

```
public static final java.lang.String FD_date
```

Constant value: **date**

FD_time

```
public static final java.lang.String FD_time
```

Constant value: **time**

FD_tz

```
public static final java.lang.String FD_tz
```

Constant value: **tz**

FD_x_ctx

```
public static final java.lang.String FD_x_ctx
```

Constant value: **x-ctx**

FD_x_ctx_override

```
public static final java.lang.String FD_x_ctx_override
```

Constant value: **x-ctx-override**

FD_x_vhost

```
public static final java.lang.String FD_x_vhost
```

Constant value: **x-vhost**

(continued from last page)

FD_x_app

```
public static final java.lang.String FD_x_app
```

Constant value: **x-app**

FD_x_appinst

```
public static final java.lang.String FD_x_appinst
```

Constant value: **x-appinst**

FD_c_ip

```
public static final java.lang.String FD_c_ip
```

Constant value: **c-ip**

FD_c_proto

```
public static final java.lang.String FD_c_proto
```

Constant value: **c-proto**

FD_s_uri

```
public static final java.lang.String FD_s_uri
```

Constant value: **s-uri**

FD_c_referrer

```
public static final java.lang.String FD_c_referrer
```

Constant value: **c-referrer**

FD_c_user_agent

```
public static final java.lang.String FD_c_user_agent
```

Constant value: **c-user-agent**

FD_c_client_id

```
public static final java.lang.String FD_c_client_id
```

Constant value: **c-client-id**

FD_cs_bytes

```
public static final java.lang.String FD_cs_bytes
```

(continued from last page)

Constant value: **cs-bytes**

FD_sc_bytes

```
public static final java.lang.String FD_sc_bytes
```

Constant value: **sc-bytes**

FD_x_sname

```
public static final java.lang.String FD_x_sname
```

Constant value: **x-sname**

FD_x_file_size

```
public static final java.lang.String FD_x_file_size
```

Constant value: **x-file-size**

FD_x_file_length

```
public static final java.lang.String FD_x_file_length
```

Constant value: **x-file-length**

FD_x_spos

```
public static final java.lang.String FD_x_spos
```

Constant value: **x-spos**

FD_cs_stream_bytes

```
public static final java.lang.String FD_cs_stream_bytes
```

Constant value: **cs-stream-bytes**

FD_sc_stream_bytes

```
public static final java.lang.String FD_sc_stream_bytes
```

Constant value: **sc-stream-bytes**

FD_s_ip

```
public static final java.lang.String FD_s_ip
```

Constant value: **s-ip**

FD_x_duration

```
public static final java.lang.String FD_x_duration
```

Constant value: **x-duration**

FD_x_status

```
public static final java.lang.String FD_x_status
```

Constant value: **x-status**

FD_cs_uri_stem

```
public static final java.lang.String FD_cs_uri_stem
```

Constant value: **cs-uri-stem**

FD_cs_uri_query

```
public static final java.lang.String FD_cs_uri_query
```

Constant value: **cs-uri-query**

FD_x_sname_query

```
public static final java.lang.String FD_x_sname_query
```

Constant value: **x-sname-query**

FD_x_file_name

```
public static final java.lang.String FD_x_file_name
```

Constant value: **x-file-name**

FD_x_file_ext

```
public static final java.lang.String FD_x_file_ext
```

Constant value: **x-file-ext**

FD_x_suri_query

```
public static final java.lang.String FD_x_suri_query
```

Constant value: **x-suri-query**

(continued from last page)

FD_x_suri_stem

```
public static final java.lang.String FD_x_suri_stem
```

Constant value: **x-suri-stem**

FD_x_suri

```
public static final java.lang.String FD_x_suri
```

Constant value: **x-suri**

FD_x_severity

```
public static final java.lang.String FD_x_severity
```

Constant value: **x-severity**

FD_x_comment

```
public static final java.lang.String FD_x_comment
```

Constant value: **x-comment**

FD_s_port

```
public static final java.lang.String FD_s_port
```

Constant value: **s-port**

FD_x_stream_id

```
public static final java.lang.String FD_x_stream_id
```

Constant value: **x-stream-id**

CAT_server

```
public static final java.lang.String CAT_server
```

Constant value: **server**

CAT_vhost

```
public static final java.lang.String CAT_vhost
```

Constant value: **vhost**

CAT_application

```
public static final java.lang.String CAT_application
```

(continued from last page)

Constant value: **application**

CAT_session

```
public static final java.lang.String CAT_session
```

Constant value: **session**

CAT_stream

```
public static final java.lang.String CAT_stream
```

Constant value: **stream**

CAT_rtsp

```
public static final java.lang.String CAT_rtsp
```

Constant value: **rtsp**

CAT_cupertino

```
public static final java.lang.String CAT_cupertino
```

Constant value: **cupertino**

CAT_sanjose

```
public static final java.lang.String CAT_sanjose
```

Constant value: **sanjose**

CAT_smoothstreaming

```
public static final java.lang.String CAT_smoothstreaming
```

Constant value: **smoothstreaming**

CAT_dvrchunk

```
public static final java.lang.String CAT_dvrchunk
```

Constant value: **dvrchunk**

CAT_webm

```
public static final java.lang.String CAT_webm
```

Constant value: **webm**

CAT_transcoder

```
public static final java.lang.String CAT_transcoder
```

Constant value: **transcoder**

EVT_connect_pending

```
public static final java.lang.String EVT_connect_pending
```

Constant value: **connect-pending**

EVT_connect

```
public static final java.lang.String EVT_connect
```

Constant value: **connect**

EVT_connect_burst

```
public static final java.lang.String EVT_connect_burst
```

Constant value: **connect-burst**

EVT_disconnect

```
public static final java.lang.String EVT_disconnect
```

Constant value: **disconnect**

EVT_publish

```
public static final java.lang.String EVT_publish
```

Constant value: **publish**

EVT_unpublish

```
public static final java.lang.String EVT_unpublish
```

Constant value: **unpublish**

EVT_play

```
public static final java.lang.String EVT_play
```

Constant value: **play**

(continued from last page)

EVT_pause

```
public static final java.lang.String EVT_pause
```

Constant value: **pause**

EVT_setbuffertime

```
public static final java.lang.String EVT_setbuffertime
```

Constant value: **setbuffertime**

EVT_create

```
public static final java.lang.String EVT_create
```

Constant value: **create**

EVT_destroy

```
public static final java.lang.String EVT_destroy
```

Constant value: **destroy**

EVT_setstreamtype

```
public static final java.lang.String EVT_setstreamtype
```

Constant value: **setstreamtype**

EVT_unpause

```
public static final java.lang.String EVT_unpause
```

Constant value: **unpause**

EVT_seek

```
public static final java.lang.String EVT_seek
```

Constant value: **seek**

EVT_stop

```
public static final java.lang.String EVT_stop
```

Constant value: **stop**

EVT_record

```
public static final java.lang.String EVT_record
```

(continued from last page)

Constant value: **record**

EVT_recordstop

```
public static final java.lang.String EVT_recordstop
```

Constant value: **recordstop**

EVT_server_start

```
public static final java.lang.String EVT_server_start
```

Constant value: **server-start**

EVT_server_stop

```
public static final java.lang.String EVT_server_stop
```

Constant value: **server-stop**

EVT_vhost_start

```
public static final java.lang.String EVT_vhost_start
```

Constant value: **vhost-start**

EVT_vhost_stop

```
public static final java.lang.String EVT_vhost_stop
```

Constant value: **vhost-stop**

EVT_app_start

```
public static final java.lang.String EVT_app_start
```

Constant value: **app-start**

EVT_app_stop

```
public static final java.lang.String EVT_app_stop
```

Constant value: **app-stop**

EVT_comment

```
public static final java.lang.String EVT_comment
```

Constant value: **comment**

EVT_announce

```
public static final java.lang.String EVT_announce
```

Constant value: **announce**

EVT_describe

```
public static final java.lang.String EVT_describe
```

Constant value: **describe**

EVT_decoderaudiostart

```
public static final java.lang.String EVT_decoderaudiostart
```

Constant value: **decoder-audio-start**

EVT_decoderaudiostop

```
public static final java.lang.String EVT_decoderaudiostop
```

Constant value: **decoder-audio-stop**

EVT_decodervideostart

```
public static final java.lang.String EVT_decodervideostart
```

Constant value: **decoder-video-start**

EVT_decodervideostop

```
public static final java.lang.String EVT_decodervideostop
```

Constant value: **decoder-video-stop**

EVT_encoderaudiostart

```
public static final java.lang.String EVT_encoderaudiostart
```

Constant value: **encoder-audio-start**

EVT_encoderaudiostop

```
public static final java.lang.String EVT_encoderaudiostop
```

Constant value: **encoder-audio-stop**

(continued from last page)

EVT_encodervideostart

```
public static final java.lang.String EVT_encodervideostart
```

Constant value: **encoder-video-start**

EVT_encodervideostop

```
public static final java.lang.String EVT_encodervideostop
```

Constant value: **encoder-video-stop**

CTRL_playlist_node

```
public static final java.lang.String CTRL_playlist_node
```

Constant value: **CTRL-playlist-node**

STAT_connect_pending_wating

```
public static final int STAT_connect_pending_wating
```

Constant value: **100**

STAT_connect_successful

```
public static final int STAT_connect_successful
```

Constant value: **200**

STAT_connect_application_not_available

```
public static final int STAT_connect_application_not_available
```

Constant value: **302**

STAT_connect_unknown_protocol

```
public static final int STAT_connect_unknown_protocol
```

Constant value: **400**

STAT_connect_rejected_by_application

```
public static final int STAT_connect_rejected_by_application
```

Constant value: **401**

STAT_connect_rejected_by_module

```
public static final int STAT_connect_rejected_by_module
```

(continued from last page)

Constant value: **403**

STAT_connect_application_not_found

```
public static final int STAT_connect_application_not_found
```

Constant value: **404**

STAT_connect_resource_limit

```
public static final int STAT_connect_resource_limit
```

Constant value: **409**

STAT_connect_license_limit

```
public static final int STAT_connect_license_limit
```

Constant value: **413**

STAT_connect_redirect

```
public static final int STAT_connect_redirect
```

Constant value: **302**

STAT_connect_internal_error

```
public static final int STAT_connect_internal_error
```

Constant value: **500**

STAT_connect_bad_gateway

```
public static final int STAT_connect_bad_gateway
```

Constant value: **502**

STAT_connect_service_unavailable

```
public static final int STAT_connect_service_unavailable
```

Constant value: **503**

STAT_play_successful

```
public static final int STAT_play_successful
```

Constant value: **200**

STAT_play_bad_request

public static final int **STAT_play_bad_request**

Constant value: **400**

STAT_play_rejected_by_application

public static final int **STAT_play_rejected_by_application**

Constant value: **401**

STAT_play_rejected_by_module

public static final int **STAT_play_rejected_by_module**

Constant value: **403**

STAT_play_stream_not_found

public static final int **STAT_play_stream_not_found**

Constant value: **404**

STAT_play_unsupported_media_type

public static final int **STAT_play_unsupported_media_type**

Constant value: **415**

STAT_play_internal_error

public static final int **STAT_play_internal_error**

Constant value: **500**

STAT_publish_successful

public static final int **STAT_publish_successful**

Constant value: **200**

STAT_publish_bad_request

public static final int **STAT_publish_bad_request**

Constant value: **400**

(continued from last page)

STAT_publish_rejected_by_application

```
public static final int STAT_publish_rejected_by_application
```

Constant value: **401**

STAT_publish_in_use

```
public static final int STAT_publish_in_use
```

Constant value: **409**

STAT_publish_unsupported_media_type

```
public static final int STAT_publish_unsupported_media_type
```

Constant value: **415**

STAT_publish_internal_error

```
public static final int STAT_publish_internal_error
```

Constant value: **500**

STAT_stop_successful

```
public static final int STAT_stop_successful
```

Constant value: **200**

STAT_stop_client_disconnect

```
public static final int STAT_stop_client_disconnect
```

Constant value: **408**

STAT_general_successful

```
public static final int STAT_general_successful
```

Constant value: **200**

STAT_general_internal_error

```
public static final int STAT_general_internal_error
```

Constant value: **500**

PROTO_RTMP

```
public static final java.lang.String PROTO_RTMP
```

(continued from last page)

Constant value: **rtmp**

PROTO_RTMP

```
public static final java.lang.String PROTO_RTMP
```

Constant value: **rtmps**

PROTO_RTMP

```
public static final java.lang.String PROTO_RTMP
```

Constant value: **rtmpt (HTTP-1.1)**

PROTO_RTMP

```
public static final java.lang.String PROTO_RTMP
```

Constant value: **rtmpts (HTTP-1.1)**

PROTO_RTMP

```
public static final java.lang.String PROTO_RTMP
```

Constant value: **rtmpe**

PROTO_RTMP

```
public static final java.lang.String PROTO_RTMP
```

Constant value: **rtmpte (HTTP-1.1)**

PROTO_RTSP

```
public static final java.lang.String PROTO_RTSP
```

Constant value: **rtsp**

PROTO_HTTPSTREAMER

```
public static final java.lang.String PROTO_HTTPSTREAMER
```

Constant value: **http (streamer)**

PROTO_HTTPCUPERTINO

```
public static final java.lang.String PROTO_HTTPCUPERTINO
```

Constant value: **http (cupertino)**

PROTO_HTTPSMOOTH

```
public static final java.lang.String PROTO_HTTPSMOOTH
```

Constant value: **http (smooth)**

PROTO_HTTPSANJOSE

```
public static final java.lang.String PROTO_HTTPSANJOSE
```

Constant value: **http (sanjose)**

PROTO_HTTPDVRCHUNK

```
public static final java.lang.String PROTO_HTTPDVRCHUNK
```

Constant value: **http (dvr)**

PROTO_HTTPSSTREAMER

```
public static final java.lang.String PROTO_HTTPSSTREAMER
```

Constant value: **https (streamer)**

PROTO_HTTPSCUPERTINO

```
public static final java.lang.String PROTO_HTTPSCUPERTINO
```

Constant value: **https (cupertino)**

PROTO_HTTPSSMOOTH

```
public static final java.lang.String PROTO_HTTPSSMOOTH
```

Constant value: **https (smooth)**

PROTO_HTTPSSANJOSE

```
public static final java.lang.String PROTO_HTTPSSANJOSE
```

Constant value: **https (sanjose)**

PROTO_HTTPSDVRCHUNK

```
public static final java.lang.String PROTO_HTTPSDVRCHUNK
```

Constant value: **https (dvr)**

(continued from last page)

FD_ALL

```
public static final java.lang.String FD_ALL
```

CAT_ALL

```
public static final java.lang.String CAT_ALL
```

EVT_ALL

```
public static final java.lang.String EVT_ALL
```

Constructors

WMSLoggerIDs

```
public WMSLoggerIDs()
```

Package

com.wowza.wms.media.mp3.model.idtags

com.wowza.wms.media.mp3.model.idtags Class ID3Frames

java.lang.Object

└--com.wowza.wms.media.mp3.model.idtags.ID3Frames

public class **ID3Frames**
extends Object

Field Summary

public static final	<u>ID3FOOTER_SIZE</u> Value: 10
public static final	<u>ID3HEADER_SIZE</u> Value: 10
public static final	<u>ID3HEADER_VERSION</u> Value: 1024
public static final	<u>ID3HEADERFLAGS_DEFAULT</u> Value: 0
public static final	<u>ID3HEADERFLAGS_EXPERIMENTAL</u> Value: 32
public static final	<u>ID3HEADERFLAGS_EXTENDED</u> Value: 64
public static final	<u>ID3HEADERFLAGS_FOOTERPRESENT</u> Value: 16
public static final	<u>ID3HEADERFLAGS_UNSYNC</u> Value: 128

Constructor Summary

public	<u>ID3Frames</u> ()
--------	--------------------------------------

Method Summary

void	<u>clear</u> ()
java.util.List	<u>getFrameMapIds</u> ()

<code>java.util.List</code>	<code>getFrames()</code>
<code>Object</code>	<code>getLock()</code>
<code>int</code>	<code>getSize()</code>
<code>boolean</code>	<code>isEmpty()</code>
<code>void</code>	<code>putFrame</code> (<code>IID3V2Frame</code> frame)
<code>IID3V2Frame</code>	<code>removeFrame</code> (<code>IID3V2Frame</code> frame)
<code>byte[]</code>	<code>serialize()</code>
<code>byte[]</code>	<code>serialize</code> (boolean includeHeader, boolean includeFooter, int flags)
<code>static int</code>	<code>serializeFooter</code> (byte[] buffer, int offset, int flags, int size)
<code>static int</code>	<code>serializeHeader</code> (byte[] buffer, int offset, int flags, int size)
<code>int</code>	<code>serializeTags</code> (byte[] buffer, int offset)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

ID3HEADER_VERSION

```
public static final int ID3HEADER_VERSION
```

Constant value: **1024**

ID3HEADER_SIZE

```
public static final int ID3HEADER_SIZE
```

Constant value: **10**

ID3FOOTER_SIZE

```
public static final int ID3FOOTER_SIZE
```

Constant value: **10**

(continued from last page)

ID3HEADERFLAGS_DEFAULT

```
public static final int ID3HEADERFLAGS_DEFAULT
```

Constant value: **0**

ID3HEADERFLAGS_UNSYNC

```
public static final int ID3HEADERFLAGS_UNSYNC
```

Constant value: **128**

ID3HEADERFLAGS_EXTENDED

```
public static final int ID3HEADERFLAGS_EXTENDED
```

Constant value: **64**

ID3HEADERFLAGS_EXPERIMENTAL

```
public static final int ID3HEADERFLAGS_EXPERIMENTAL
```

Constant value: **32**

ID3HEADERFLAGS_FOOTERPRESENT

```
public static final int ID3HEADERFLAGS_FOOTERPRESENT
```

Constant value: **16**

Constructors

ID3Frames

```
public ID3Frames()
```

Methods

getLock

```
public Object getLock()
```

clear

```
public void clear()
```

(continued from last page)

isEmpty

```
public boolean isEmpty()
```

putFrame

```
public void putFrame(IID3V2Frame frame)
```

removeFrame

```
public IID3V2Frame removeFrame(IID3V2Frame frame)
```

getFrames

```
public java.util.List getFrames()
```

getFrameMapIds

```
public java.util.List getFrameMapIds()
```

getSize

```
public int getSize()
```

serializeTags

```
public int serializeTags(byte[] buffer,  
    int offset)
```

serializeHeader

```
public static int serializeHeader(byte[] buffer,  
    int offset,  
    int flags,  
    int size)
```

serializeFooter

```
public static int serializeFooter(byte[] buffer,  
    int offset,  
    int flags,  
    int size)
```

(continued from last page)

serialize

```
public byte[] serialize()
```

serialize

```
public byte[] serialize(boolean includeHeader,  
                        boolean includeFooter,  
                        int flags)
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameAttachedPicture

java.lang.Object

```

+--com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase
    |
    +--com.wowza.wms.media.mp3.model.idtags.ID3V2FrameAttachedPicture
  
```

All Implemented Interfaces:

[IID3V2Frame](#)

```

public class ID3V2FrameAttachedPicture
extends ID3V2FrameBase
  
```

Field Summary

public static final	MIMETYPES_JPEG Value: image/jpeg
public static final	MIMETYPES_PNG Value: image/png
public static final	MIMETYPES_URL Value: -->
public static	PICTUREMAXFILESIZE
public static final	PICTURETYPE_ARTISTLOGO Value: 19
public static final	PICTURETYPE_COVERBACK Value: 4
public static final	PICTURETYPE_COVERFRONT Value: 3
public static final	PICTURETYPE_FILEICON Value: 1
public static final	PICTURETYPE_ILLUSTRATION Value: 18
public static final	PICTURETYPE_MOVIESCREENCAPTURE Value: 16
public static final	PICTURETYPE_OTHER Value: 0

public static final	PICTURETYPE_OTHERFILEICON Value: 2
public static final	PICTURETYPE_PUBLISHERLOGO Value: 20

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOP](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameAttachedPicture (String idStr, int flags)
public	ID3V2FrameAttachedPicture ()

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
String	getDescription ()
String	getMapIdStr ()
String	getMimeType ()
byte[]	getPictureData ()
int	getPictureType ()
int	getTextEncoding ()
boolean	loadFile (java.io.File file)
int	serializeBody (byte[] buffer, int offset)
void	setDescription (String description)
void	setMimeType (String mimeType)

void	setPictureData (byte[] pictureData)
void	setPictureDataAsURL (String urlStr)
void	setPictureType (int pictureType)
void	setTextEncoding (int textEncoding)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Fields

PICTURETYPE_OTHER

```
public static final int PICTURETYPE_OTHER
```

Constant value: **0**

PICTURETYPE_FILEICON

```
public static final int PICTURETYPE_FILEICON
```

Constant value: **1**

PICTURETYPE_OTHERFILEICON

```
public static final int PICTURETYPE_OTHERFILEICON
```

Constant value: **2**

PICTURETYPE_COVERFRONT

```
public static final int PICTURETYPE_COVERFRONT
```

Constant value: **3**

PICTURETYPE_COVERBACK

```
public static final int PICTURETYPE_COVERBACK
```

Constant value: **4**

PICTURETYPE_MOVIESCREENCAPTURE

```
public static final int PICTURETYPE_MOVIESCREENCAPTURE
```

Constant value: **16**

PICTURETYPE_ILLUSTRATION

```
public static final int PICTURETYPE_ILLUSTRATION
```

Constant value: **18**

PICTURETYPE_ARTISTLOGO

```
public static final int PICTURETYPE_ARTISTLOGO
```

Constant value: **19**

PICTURETYPE_PUBLISHERLOGO

```
public static final int PICTURETYPE_PUBLISHERLOGO
```

Constant value: **20**

MIMETYPES_JPEG

```
public static final java.lang.String MIMETYPES_JPEG
```

Constant value: **image/jpeg**

MIMETYPES_PNG

```
public static final java.lang.String MIMETYPES_PNG
```

Constant value: **image/png**

MIMETYPES_URL

```
public static final java.lang.String MIMETYPES_URL
```

Constant value: **-->**

(continued from last page)

PICTUREMAXFILESIZE

```
public static long PICTUREMAXFILESIZE
```

Constructors

ID3V2FrameAttachedPicture

```
public ID3V2FrameAttachedPicture(String idStr,  
                                int flags)
```

ID3V2FrameAttachedPicture

```
public ID3V2FrameAttachedPicture()
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,  
                        int offset)
```

deserializeBody

```
public void deserializeBody(byte[] buffer,  
                          int offset,  
                          int len)
```

getMapIdStr

```
public String getMapIdStr()
```

getBodySize

```
public int getBodySize()
```

getTextEncoding

```
public int getTextEncoding()
```

(continued from last page)

setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

getMimeType

```
public String getMimeType()
```

setMimeType

```
public void setMimeType(String mimeType)
```

getPictureType

```
public int getPictureType()
```

setPictureType

```
public void setPictureType(int pictureType)
```

getDescription

```
public String getDescription()
```

setDescription

```
public void setDescription(String description)
```

getPictureData

```
public byte[] getPictureData()
```

setPictureData

```
public void setPictureData(byte[] pictureData)
```

setPictureDataAsURL

```
public void setPictureDataAsURL(String urlStr)
```

(continued from last page)

loadFile

```
public boolean loadFile(java.io.File file)
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameBase

java.lang.Object

└--com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase

All Implemented Interfaces:

[IID3V2Frame](#)

Direct Known Subclasses:

[ID3V2FrameURLLink](#), [ID3V2FrameTextInformation](#), [ID3V2FrameSynchronizedText](#),
[ID3V2FrameRecommendedBufferSize](#), [ID3V2FrameRawBytes](#), [ID3V2FramePrivate](#), [ID3V2FrameLinkedInformation](#),
[ID3V2FrameComment](#), [ID3V2FrameAttachedPicture](#)

public abstract class **ID3V2FrameBase**

extends Object

implements [IID3V2Frame](#)

Field Summary

public static final	FLAGS_DEFAULT Value: 0
public static final	HEADERSIZE Value: 10
public static final	TAG_APIC Value: APIC
public static final	TAG_COMM Value: COMM
public static final	TAG_LINK Value: LINK
public static final	TAG_PRIV Value: PRIV
public static final	TAG_RBUF Value: RBUF
public static final	TAG_SYLT Value: SYLT
public static final	TAG_TALB Value: TALB

public static final	TAG_TBPM Value: TBPM
public static final	TAG_TCOM Value: TCOM
public static final	TAG_TCON Value: TCON
public static final	TAG_TCOP Value: TCOP
public static final	TAG_TDEN Value: TDEN
public static final	TAG_TDLY Value: TDLY
public static final	TAG_TDOR Value: TDOR
public static final	TAG_TDRC Value: TDRC
public static final	TAG_TDRL Value: TDRL
public static final	TAG_TDTG Value: TDTG
public static final	TAG_TENC Value: TENC
public static final	TAG_TEXT Value: TEXT
public static final	TAG_TFLT Value: TFLT
public static final	TAG_TIPL Value: TIPL
public static final	TAG_TIT1 Value: TIT1
public static final	TAG_TIT2 Value: TIT2

public static final	TAG_TIT3 Value: TIT3
public static final	TAG_TKEY Value: TKEY
public static final	TAG_TLAN Value: TLAN
public static final	TAG_TLEN Value: TLEN
public static final	TAG_TMCL Value: TMCL
public static final	TAG_TMED Value: TMED
public static final	TAG_TMOO Value: TMOO
public static final	TAG_TOAL Value: TOAL
public static final	TAG_TOFN Value: TOFN
public static final	TAG_TOLY Value: TOLY
public static final	TAG_TOPE Value: TOPE
public static final	TAG_TOWN Value: TOWN
public static final	TAG_TPE1 Value: TPE1
public static final	TAG_TPE2 Value: TPE2
public static final	TAG_TPE3 Value: TPE3
public static final	TAG_TPE4 Value: TPE4

public static final	TAG_TPOS Value: TPOS
public static final	TAG_TPRO Value: TPRO
public static final	TAG_TPUB Value: TPUB
public static final	TAG_TRCK Value: TRCK
public static final	TAG_TRSN Value: TRSN
public static final	TAG_TRSO Value: TRSO
public static final	TAG_TSOA Value: TSOA
public static final	TAG_TSOP Value: TSOP
public static final	TAG_TSOT Value: TSOT
public static final	TAG_TSRC Value: TSRC
public static final	TAG_TSSE Value: TSSE
public static final	TAG_TSST Value: TSST
public static final	TAG_TXXX Value: TXXX
public static final	TAG_UNKN Value: UNKN
public static final	TAG_WCOM Value: WCOM
public static final	TAG_WCOP Value: WCOP

public static final	TAG_WOAF Value: WOAF
public static final	TAG_WOAR Value: WOAR
public static final	TAG_WOAS Value: WOAS
public static final	TAG_WORS Value: WORS
public static final	TAG_WPAY Value: WPAY
public static final	TAG_WPUB Value: WPUB
public static final	TAG_WXXX Value: WXXX
public static final	TAGS_TEXTINFORMATION
public static final	TEXTENCODING_ISO_8859_1 Value: 0
public static final	TEXTENCODING_UTF16 Value: 1
public static final	TEXTENCODING_UTF16BE Value: 2
public static final	TEXTENCODING_UTF8 Value: 3

Constructor Summary

public	ID3V2FrameBase (String idStr, int flags)
--------	----------------------------------------------------------

Method Summary

static int	byteStringLen (String value)
static ID3V2FrameBase	deserializeFrame (byte[] buffer, int offset, int len)
static String	deserializeString (byte[] buffer, int offset, int len)
int	getFlags ()

String	getIdStr()
String	getMapIdStr()
int	getSize()
int	serialize (byte[] buffer, int offset)
static int	serializeString (String value, byte[] buffer, int offset)
static int	serializeStringLen (String value)
void	setFlags (int flags)
void	setIdStr (String idStr)
static String	trimTrailingZero (String value)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.ID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Fields

HEADERSIZE

```
public static final int HEADERSIZE
```

Constant value: **10**

TEXTENCODING_ISO_8859_1

```
public static final int TEXTENCODING_ISO_8859_1
```

Constant value: **0**

TEXTENCODING_UTF16

```
public static final int TEXTENCODING_UTF16
```

Constant value: **1**

(continued from last page)

TEXTENCODING_UTF16BE

```
public static final int TEXTENCODING_UTF16BE
```

Constant value: **2**

TEXTENCODING_UTF8

```
public static final int TEXTENCODING_UTF8
```

Constant value: **3**

TAG_UNKN

```
public static final java.lang.String TAG_UNKN
```

Constant value: **UNKN**

TAG_PRIV

```
public static final java.lang.String TAG_PRIV
```

Constant value: **PRIV**

TAG_APIC

```
public static final java.lang.String TAG_APIC
```

Constant value: **APIC**

TAG_LINK

```
public static final java.lang.String TAG_LINK
```

Constant value: **LINK**

TAG_SYLT

```
public static final java.lang.String TAG_SYLT
```

Constant value: **SYLT**

TAG_RBUF

```
public static final java.lang.String TAG_RBUF
```

Constant value: **RBUF**

TAG_TALB

```
public static final java.lang.String TAG_TALB
```

(continued from last page)

Constant value: **TALB**

TAG_TBPM

```
public static final java.lang.String TAG_TBPM
```

Constant value: **TBPM**

TAG_TCOM

```
public static final java.lang.String TAG_TCOM
```

Constant value: **TCOM**

TAG_TCON

```
public static final java.lang.String TAG_TCON
```

Constant value: **TCON**

TAG_TCOP

```
public static final java.lang.String TAG_TCOP
```

Constant value: **TCOP**

TAG_TDEN

```
public static final java.lang.String TAG_TDEN
```

Constant value: **TDEN**

TAG_TDLY

```
public static final java.lang.String TAG_TDLY
```

Constant value: **TDLY**

TAG_TDOR

```
public static final java.lang.String TAG_TDOR
```

Constant value: **TDOR**

TAG_TDRC

```
public static final java.lang.String TAG_TDRC
```

Constant value: **TDRC**

TAG_TDRL

```
public static final java.lang.String TAG_TDRL
```

Constant value: **TDRL**

TAG_TDTG

```
public static final java.lang.String TAG_TDTG
```

Constant value: **TDTG**

TAG_TENC

```
public static final java.lang.String TAG_TENC
```

Constant value: **TENC**

TAG_TEXT

```
public static final java.lang.String TAG_TEXT
```

Constant value: **TEXT**

TAG_TFLT

```
public static final java.lang.String TAG_TFLT
```

Constant value: **TFLT**

TAG_TIPL

```
public static final java.lang.String TAG_TIPL
```

Constant value: **TIPL**

TAG_TIT1

```
public static final java.lang.String TAG_TIT1
```

Constant value: **TIT1**

TAG_TIT2

```
public static final java.lang.String TAG_TIT2
```

Constant value: **TIT2**

(continued from last page)

TAG_TIT3

```
public static final java.lang.String TAG_TIT3
```

Constant value: **TIT3**

TAG_TKEY

```
public static final java.lang.String TAG_TKEY
```

Constant value: **TKEY**

TAG_TLAN

```
public static final java.lang.String TAG_TLAN
```

Constant value: **TLAN**

TAG_TLEN

```
public static final java.lang.String TAG_TLEN
```

Constant value: **TLEN**

TAG_TMCL

```
public static final java.lang.String TAG_TMCL
```

Constant value: **TMCL**

TAG_TMED

```
public static final java.lang.String TAG_TMED
```

Constant value: **TMED**

TAG_TMOO

```
public static final java.lang.String TAG_TMOO
```

Constant value: **TMOO**

TAG_TOAL

```
public static final java.lang.String TAG_TOAL
```

Constant value: **TOAL**

TAG_TOFN

```
public static final java.lang.String TAG_TOFN
```

(continued from last page)

Constant value: **TOFN**

TAG_TOLY

```
public static final java.lang.String TAG_TOLY
```

Constant value: **TOLY**

TAG_TOPE

```
public static final java.lang.String TAG_TOPE
```

Constant value: **TOPE**

TAG_TOWN

```
public static final java.lang.String TAG_TOWN
```

Constant value: **TOWN**

TAG_TPE1

```
public static final java.lang.String TAG_TPE1
```

Constant value: **TPE1**

TAG_TPE2

```
public static final java.lang.String TAG_TPE2
```

Constant value: **TPE2**

TAG_TPE3

```
public static final java.lang.String TAG_TPE3
```

Constant value: **TPE3**

TAG_TPE4

```
public static final java.lang.String TAG_TPE4
```

Constant value: **TPE4**

TAG_TPOS

```
public static final java.lang.String TAG_TPOS
```

Constant value: **TPOS**

TAG_TPRO

```
public static final java.lang.String TAG_TPRO
```

Constant value: **TPRO**

TAG_TPUB

```
public static final java.lang.String TAG_TPUB
```

Constant value: **TPUB**

TAG_TRCK

```
public static final java.lang.String TAG_TRCK
```

Constant value: **TRCK**

TAG_TRSN

```
public static final java.lang.String TAG_TRSN
```

Constant value: **TRSN**

TAG_TRSO

```
public static final java.lang.String TAG_TRSO
```

Constant value: **TRSO**

TAG_TSOA

```
public static final java.lang.String TAG_TSOA
```

Constant value: **TSOA**

TAG_TSOP

```
public static final java.lang.String TAG_TSOP
```

Constant value: **TSOP**

TAG_TSOT

```
public static final java.lang.String TAG_TSOT
```

Constant value: **TSOT**

(continued from last page)

TAG_TSRC

```
public static final java.lang.String TAG_TSRC
```

Constant value: **TSRC**

TAG_TSSE

```
public static final java.lang.String TAG_TSSE
```

Constant value: **TSSE**

TAG_TSST

```
public static final java.lang.String TAG_TSST
```

Constant value: **TSST**

TAGS_TEXTINFORMATION

```
public static final java.lang.String TAGS_TEXTINFORMATION
```

TAG_WCOM

```
public static final java.lang.String TAG_WCOM
```

Constant value: **WCOM**

TAG_WCOP

```
public static final java.lang.String TAG_WCOP
```

Constant value: **WCOP**

TAG_WOAF

```
public static final java.lang.String TAG_WOAF
```

Constant value: **WOAF**

TAG_WOAR

```
public static final java.lang.String TAG_WOAR
```

Constant value: **WOAR**

TAG_WOAS

```
public static final java.lang.String TAG_WOAS
```

(continued from last page)

Constant value: **WOAS**

TAG_WORS

```
public static final java.lang.String TAG_WORS
```

Constant value: **WORS**

TAG_WPAY

```
public static final java.lang.String TAG_WPAY
```

Constant value: **WPAY**

TAG_WPUB

```
public static final java.lang.String TAG_WPUB
```

Constant value: **WPUB**

TAG_TXXX

```
public static final java.lang.String TAG_TXXX
```

Constant value: **TXXX**

TAG_COMM

```
public static final java.lang.String TAG_COMM
```

Constant value: **COMM**

TAG_WXXX

```
public static final java.lang.String TAG_WXXX
```

Constant value: **WXXX**

FLAGS_DEFAULT

```
public static final int FLAGS_DEFAULT
```

Constant value: **0**

Constructors

ID3V2FrameBase

```
public ID3V2FrameBase(String idStr,  
                       int flags)
```

Methods

byteStringLen

```
public static int byteStringLen(String value)
```

serializeStringLen

```
public static int serializeStringLen(String value)
```

trimTrailingZero

```
public static String trimTrailingZero(String value)
```

serializeString

```
public static int serializeString(String value,  
    byte[] buffer,  
    int offset)
```

deserializeString

```
public static String deserializeString(byte[] buffer,  
    int offset,  
    int len)
```

deserializeFrame

```
public static ID3V2FrameBase deserializeFrame(byte[] buffer,  
    int offset,  
    int len)
```

serialize

```
public int serialize(byte[] buffer,  
    int offset)
```

getIdStr

```
public String getIdStr()
```


(continued from last page)

setIdStr

```
public void setIdStr(String idStr)
```

getFlags

```
public int getFlags()
```

setFlags

```
public void setFlags(int flags)
```

getSize


```
public int getSize()
```

getMapIdStr

```
public String getMapIdStr()
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameComment

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

```

public class ID3V2FrameComment
extends ID3V2FrameBase
  
```

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOPI](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameComment (String idStr, int flags)
public	ID3V2FrameComment (String idStr)
public	ID3V2FrameComment ()

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
String	getDescription ()
int	getTextEncoding ()
String	getValue ()
int	serializeBody (byte[] buffer, int offset)

void	<u>setDescription</u> (String description)
void	<u>setTextEncoding</u> (int textEncoding)
void	<u>setValue</u> (String value)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Constructors

ID3V2FrameComment

```
public ID3V2FrameComment(String idStr,
                          int flags)
```

ID3V2FrameComment

```
public ID3V2FrameComment(String idStr)
```

ID3V2FrameComment

```
public ID3V2FrameComment()
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,
                          int offset)
```

(continued from last page)

deserializeBody

```
public void deserializeBody(byte[] buffer,  
    int offset,  
    int len)
```

getBodySize

```
public int getBodySize()
```

getValue

```
public String getValue()
```

setValue

```
public void setValue(String value)
```

getTextEncoding

```
public int getTextEncoding()
```

setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

getDescription

```
public String getDescription()
```


setDescription

```
public void setDescription(String description)
```

com.wowza.wms.media.mp3.model.idtags

Class ID3V2FrameLinkedInformation

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameLinkedInformation**

extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOP](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameLinkedInformation (String idStr, int flags)
public	ID3V2FrameLinkedInformation ()

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
byte[]	getData ()
String	getDescription ()
long	getFrameIdentifier ()
String	getURL ()
int	serializeBody (byte[] buffer, int offset)

void	<u>setData</u> (byte[] data)
void	<u>setDescription</u> (String description)
void	<u>setFrameIdentifier</u> (long frameIdentifier)
void	<u>setURL</u> (String url)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Constructors

ID3V2FrameLinkedInformation

```
public ID3V2FrameLinkedInformation(String idStr,
                                   int flags)
```

ID3V2FrameLinkedInformation

```
public ID3V2FrameLinkedInformation()
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,
                          int offset)
```

deserializeBody

```
public void deserializeBody(byte[] buffer,
                              int offset,
                              int len)
```

(continued from last page)

getBodySize

```
public int getBodySize()
```

getDescription

```
public String getDescription()
```

setDescription

```
public void setDescription(String description)
```

getFrameIdentifier

```
public long getFrameIdentifier()
```

setFrameIdentifier

```
public void setFrameIdentifier(long frameIdentifier)
```

getURL

```
public String getURL()
```

setURL

```
public void setURL(String url)
```

getData

```
public byte[] getData()
```


setData

```
public void setData(byte[] data)
```

com.wowza.wms.media.mp3.model.idtags

Class ID3V2FramePrivate

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FramePrivate**
 extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOPI](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FramePrivate (String idStr, int flags)
public	ID3V2FramePrivate ()

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
int	serializeBody (byte[] buffer, int offset)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Constructors

ID3V2FramePrivate

```
public ID3V2FramePrivate(String idStr,  
                           int flags)
```

ID3V2FramePrivate

```
public ID3V2FramePrivate()
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,  
                           int offset)
```

deserializeBody

```
public void deserializeBody(byte[] buffer,  
                             int offset,  
                             int len)
```


getBodySize

```
public int getBodySize()
```

com.wowza.wms.media.mp3.model.idtags

Class ID3V2FrameRawBytes

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameRawBytes**

extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOPI](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameRawBytes (String idStr, int flags)
public	ID3V2FrameRawBytes (String idStr)

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
int	serializeBody (byte[] buffer, int offset)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Constructors

ID3V2FrameRawBytes

```
public ID3V2FrameRawBytes(String idStr,  
                           int flags)
```

ID3V2FrameRawBytes

```
public ID3V2FrameRawBytes(String idStr)
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,  
                        int offset)
```

deserializeBody


```
public void deserializeBody(byte[] buffer,  
                          int offset,  
                          int len)
```

getBodySize

```
public int getBodySize()
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameRecommendedBufferSize

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameRecommendedBufferSize**
extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOPI](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameRecommendedBufferSize (String idStr, int flags)
public	ID3V2FrameRecommendedBufferSize ()

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
int	getBufferSize ()
byte	getEmbeddedFlag ()
long	getOffsetToNextTag ()
int	serializeBody (byte[] buffer, int offset)
void	setBufferSize (int bufferSize)

void	setEmbeddedFlag (byte embeddedFlag)
void	setOffsetToNextTag (long offsetToNextTag)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Constructors

ID3V2FrameRecommendedBufferSize

```
public ID3V2FrameRecommendedBufferSize(String idStr,
                                       int flags)
```

ID3V2FrameRecommendedBufferSize

```
public ID3V2FrameRecommendedBufferSize()
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,
                        int offset)
```

deserializeBody

```
public void deserializeBody(byte[] buffer,
                          int offset,
                          int len)
```

getBodySize

```
public int getBodySize()
```

(continued from last page)

getBufferSize

```
public int getBufferSize()
```

setBufferSize

```
public void setBufferSize(int bufferSize)
```

getEmbeddedFlag

```
public byte getEmbeddedFlag()
```

setEmbeddedFlag

```
public void setEmbeddedFlag(byte embeddedFlag)
```

getOffsetToNextTag

```
public long getOffsetToNextTag()
```

setOffsetToNextTag

```
public void setOffsetToNextTag(long offsetToNextTag)
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameSynchronizedText

java.lang.Object

└- [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)
└- [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameSynchronizedText](#)

All Implemented Interfaces:

[IID3V2Frame](#)

```
public class ID3V2FrameSynchronizedText
extends ID3V2FrameBase
```

Field Summary

public static final	CONTENTTYPE_CHORD Value: 5
public static final	CONTENTTYPE_EVENTS Value: 4
public static final	CONTENTTYPE_LYRICS Value: 1
public static final	CONTENTTYPE_MOVEMENT Value: 3
public static final	CONTENTTYPE_OTHER Value: 0
public static final	CONTENTTYPE_TRANSCRIPTION Value: 2
public static final	CONTENTTYPE_TRIVIA Value: 6
public static final	CONTENTTYPE_URLIMAGES Value: 8
public static final	CONTENTTYPE_URLWEBPAGES Value: 7
public static final	TIMESTAMPFORMAT_MILLISECONDS Value: 2

public static final	<u>TIMESTAMPFORMAT_MPEG</u> Value: 1
---------------------	----------------------------------------------------------------

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOPI](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	<u>ID3V2FrameSynchronizedText</u> (String idStr, int flags)
public	<u>ID3V2FrameSynchronizedText</u> ()

Method Summary

void	<u>addContentDescriptor</u> (<u>ID3V2FrameSynchronizedTextDescriptor</u> contentDescriptor)
void	<u>addContentDescriptor</u> (long timecode, String value)
void	<u>deserializeBody</u> (byte[] buffer, int offset, int len)
int	<u>getBodySize</u> ()
java.util.List	<u>getContentDescriptors</u> ()
byte	<u>getContentTypes</u> ()
String	<u>getLanguage</u> ()
int	<u>getTextEncoding</u> ()
byte	<u>getTimeStampFormat</u> ()
int	<u>serializeBody</u> (byte[] buffer, int offset)
void	<u>setContentTypes</u> (byte contentType)
void	<u>setLanguage</u> (String language)
void	<u>setTextEncoding</u> (int textEncoding)

void	<u>setTimeStampFormat</u> (byte timeStampFormat)
------	------------------------------------------------------------------

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Fields

CONTENTTYPE_OTHER

```
public static final int CONTENTTYPE_OTHER
```

Constant value: **0**

CONTENTTYPE_LYRICS

```
public static final int CONTENTTYPE_LYRICS
```

Constant value: **1**

CONTENTTYPE_TRANSCRIPTION

```
public static final int CONTENTTYPE_TRANSCRIPTION
```

Constant value: **2**

CONTENTTYPE_MOVEMENT

```
public static final int CONTENTTYPE_MOVEMENT
```

Constant value: **3**

CONTENTTYPE_EVENTS

```
public static final int CONTENTTYPE_EVENTS
```

Constant value: **4**

(continued from last page)

CONTENTTYPE_CHORD

```
public static final int CONTENTTYPE_CHORD
```

Constant value: **5**

CONTENTTYPE_TRIVIA

```
public static final int CONTENTTYPE_TRIVIA
```

Constant value: **6**

CONTENTTYPE_URLWEBPAGES

```
public static final int CONTENTTYPE_URLWEBPAGES
```

Constant value: **7**

CONTENTTYPE_URLIMAGES

```
public static final int CONTENTTYPE_URLIMAGES
```

Constant value: **8**

TIMESTAMPFORMAT_MPEG

```
public static final int TIMESTAMPFORMAT_MPEG
```

Constant value: **1**

TIMESTAMPFORMAT_MILLISECONDS

```
public static final int TIMESTAMPFORMAT_MILLISECONDS
```

Constant value: **2**

Constructors

ID3V2FrameSynchronizedText

```
public ID3V2FrameSynchronizedText(String idStr,  
                                   int flags)
```

ID3V2FrameSynchronizedText

```
public ID3V2FrameSynchronizedText()
```

Methods

(continued from last page)

serializeBody

```
public int serializeBody(byte[] buffer,  
    int offset)
```

deserializeBody

```
public void deserializeBody(byte[] buffer,  
    int offset,  
    int len)
```

getBodySize

```
public int getBodySize()
```

getTextEncoding

```
public int getTextEncoding()
```

setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

getLanguage

```
public String getLanguage()
```

setLanguage

```
public void setLanguage(String language)
```

getTimeStampFormat

```
public byte getTimeStampFormat()
```

setTimeStampFormat

```
public void setTimeStampFormat(byte timeStampFormat)
```

(continued from last page)

getContentType

```
public byte getContentType()
```

setContentType

```
public void setContentType(byte contentType)
```

getContentDescriptors

```
public java.util.List getContentDescriptors()
```

addContentDescriptor

```
public void addContentDescriptor(ID3V2FrameSynchronizedTextDescriptor  
contentDescriptor)
```

addContentDescriptor

```
public void addContentDescriptor(long timecode,  
                                String value)
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2FrameSynchronizedTextDescriptor

java.lang.Object

└-com.wowza.wms.media.mp3.model.idtags.ID3V2FrameSynchronizedTextDescriptor

public class **ID3V2FrameSynchronizedTextDescriptor**
extends Object

Constructor Summary

public	ID3V2FrameSynchronizedTextDescriptor()
public	ID3V2FrameSynchronizedTextDescriptor (long timecode, String value)

Method Summary

long	getTimecode()
String	getValue()
void	setTimecode (long timecode)
void	setValue (String value)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ID3V2FrameSynchronizedTextDescriptor

public **ID3V2FrameSynchronizedTextDescriptor**()

ID3V2FrameSynchronizedTextDescriptor

public **ID3V2FrameSynchronizedTextDescriptor**(long timecode,
String value)

Methods

(continued from last page)

getTimecode

```
public long getTimecode()
```

setTimecode

```
public void setTimecode(long timecode)
```

getValue

```
public String getValue()
```


setValue

```
public void setValue(String value)
```

com.wowza.wms.media.mp3.model.idtags

Class ID3V2FrameTextInformation

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameTextInformation**
 extends [ID3V2FrameBase](#)

Field Summary

protected	addTrailingZero
-----------	---------------------------------

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#), [TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOP](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#), [TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#), [TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#), [TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#), [TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#), [TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#), [TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#), [TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameTextInformation (String idStr, int flags)
public	ID3V2FrameTextInformation (String idStr)

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
int	getTextEncoding ()
String	getValue ()
int	serializeBody (byte[] buffer, int offset)

void	setTextEncoding (int textEncoding)
void	setValue (String value)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Fields

addTrailingZero

protected boolean **addTrailingZero**

Constructors

ID3V2FrameTextInformation

```
public ID3V2FrameTextInformation(String idStr,  
                                int flags)
```

ID3V2FrameTextInformation

```
public ID3V2FrameTextInformation(String idStr)
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,  
                        int offset)
```


(continued from last page)

deserializeBody

```
public void deserializeBody(byte[] buffer,  
    int offset,  
    int len)
```

getBodySize

```
public int getBodySize()
```

getValue

```
public String getValue()
```

setValue

```
public void setValue(String value)
```

getTextEncoding

```
public int getTextEncoding()
```


setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

com.wowza.wms.media.mp3.model.idtags

Class ID3V2FrameURLLink

java.lang.Object



All Implemented Interfaces:

[IID3V2Frame](#)

public class **ID3V2FrameURLLink**
 extends [ID3V2FrameBase](#)

Fields inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[FLAGS_DEFAULT](#), [HEADERSIZE](#), [TAG_APIC](#), [TAG_COMM](#), [TAG_LINK](#), [TAG_PRIV](#), [TAG_RBUF](#), [TAG_SYLT](#), [TAG_TALB](#),
[TAG_TBPM](#), [TAG_TCOM](#), [TAG_TCON](#), [TAG_TCOPI](#), [TAG_TDEN](#), [TAG_TDLY](#), [TAG_TDOR](#), [TAG_TDRC](#), [TAG_TDRL](#),
[TAG_TDTG](#), [TAG_TENC](#), [TAG_TEXT](#), [TAG_TFLT](#), [TAG_TIPL](#), [TAG_TIT1](#), [TAG_TIT2](#), [TAG_TIT3](#), [TAG_TKEY](#),
[TAG_TLAN](#), [TAG_TLEN](#), [TAG_TMCL](#), [TAG_TMED](#), [TAG_TMOO](#), [TAG_TOAL](#), [TAG_TOFN](#), [TAG_TOLY](#), [TAG_TOPE](#),
[TAG_TOWN](#), [TAG_TPE1](#), [TAG_TPE2](#), [TAG_TPE3](#), [TAG_TPE4](#), [TAG_TPOS](#), [TAG_TPRO](#), [TAG_TPUB](#), [TAG_TRCK](#),
[TAG_TRSN](#), [TAG_TRSO](#), [TAG_TSOA](#), [TAG_TSOP](#), [TAG_TSOT](#), [TAG_TSRC](#), [TAG_TSSE](#), [TAG_TSST](#), [TAG_TXXX](#),
[TAG_UNKN](#), [TAG_WCOM](#), [TAG_WCOP](#), [TAG_WOAF](#), [TAG_WOAR](#), [TAG_WOAS](#), [TAG_WORS](#), [TAG_WPAY](#), [TAG_WPUB](#),
[TAG_WXXX](#), [TAGS_TEXTINFORMATION](#), [TEXTENCODING_ISO_8859_1](#), [TEXTENCODING_UTF16](#),
[TEXTENCODING_UTF16BE](#), [TEXTENCODING_UTF8](#)

Constructor Summary

public	ID3V2FrameURLLink (String idStr, int flags)
public	ID3V2FrameURLLink (String idStr)

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
int	getTextEncoding ()
String	getURL ()
int	serializeBody (byte[] buffer, int offset)
void	setTextEncoding (int textEncoding)
void	setURL (String value)

Methods inherited from class [com.wowza.wms.media.mp3.model.idtags.ID3V2FrameBase](#)

[byteStringLen](#), [deserializeFrame](#), [deserializeString](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeString](#), [serializeStringLen](#), [setFlags](#), [setIdStr](#), [trimTrailingZero](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.media.mp3.model.idtags.IID3V2Frame](#)

[deserializeBody](#), [getBodySize](#), [getFlags](#), [getIdStr](#), [getMapIdStr](#), [getSize](#), [serialize](#), [serializeBody](#), [setFlags](#), [setIdStr](#)

Constructors

ID3V2FrameURLLink

```
public ID3V2FrameURLLink(String idStr,
                          int flags)
```

ID3V2FrameURLLink

```
public ID3V2FrameURLLink(String idStr)
```

Methods

serializeBody

```
public int serializeBody(byte[] buffer,
                          int offset)
```

deserializeBody

```
public void deserializeBody(byte[] buffer,
                             int offset,
                             int len)
```

getBodySize

```
public int getBodySize()
```

getURL

```
public String getURL()
```

(continued from last page)

setURL

```
public void setURL(String value)
```

getTextEncoding

```
public int getTextEncoding()
```

setTextEncoding

```
public void setTextEncoding(int textEncoding)
```

com.wowza.wms.media.mp3.model.idtags Class ID3V2Utils

java.lang.Object

└─com.wowza.wms.media.mp3.model.idtags.ID3V2Utils

public class **ID3V2Utils**
extends Object

Constructor Summary

public	ID3V2Utils()
--------	------------------------------

Method Summary

static int	byteArrayToIntSafeSync (byte[] b, int offset, int count)
static long	byteArrayToLongSafeSync (byte[] b, int offset, int count)
static void	intToByteArraySafeSync (int value, byte[] buffer, int offset, int size)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ID3V2Utils

public **ID3V2Utils**()

Methods

byteArrayToLongSafeSync

public static long **byteArrayToLongSafeSync**(byte[] b,
int offset,
int count)

(continued from last page)

byteArrayToIntSafeSync

```
public static int byteArrayToIntSafeSync(byte[] b,  
    int offset,  
    int count)
```

intToByteArraySafeSync

```
public static void intToByteArraySafeSync(int value,  
    byte[] buffer,  
    int offset,  
    int size)
```

com.wowza.wms.media.mp3.model.idtags Interface IID3V2Frame

All Known Implementing Classes:
[IID3V2FrameBase](#)

public interface **IID3V2Frame**
extends

Method Summary

void	deserializeBody (byte[] buffer, int offset, int len)
int	getBodySize ()
int	getFlags ()
String	getIdStr ()
String	getMapIdStr ()
int	getSize ()
int	serialize (byte[] buffer, int offset)
int	serializeBody (byte[] buffer, int offset)
void	setFlags (int flags)
void	setIdStr (String idStr)

Methods

getIdStr

public String **getIdStr**()

setIdStr

public void **setIdStr**(String idStr)

(continued from last page)

getMapIdStr

```
public String getMapIdStr()
```

getFlags

```
public int getFlags()
```

setFlags

```
public void setFlags(int flags)
```

getSize

```
public int getSize()
```

getBodySize

```
public int getBodySize()
```

deserializeBody

```
public void deserializeBody(byte[] buffer,  
                             int offset,  
                             int len)
```

serializeBody

```
public int serializeBody(byte[] buffer,  
                           int offset)
```

serialize

```
public int serialize(byte[] buffer,  
                     int offset)
```

Package

com.wowza.wms.mediacaster

com.wowza.wms.mediacaster Interface IMediaCaster

public interface **IMediaCaster**
extends

Field Summary

public static final	<u>MEDIACASTERTYPE_LIVEREPEATER</u> Value: 1
public static final	<u>MEDIACASTERTYPE_RTPLIVE</u> Value: 3
public static final	<u>MEDIACASTERTYPE_SHOUTCAST</u> Value: 2
public static final	<u>MEDIACASTERTYPE_UNKNOWN</u> Value: 0
public static final	<u>STREAMTIMEOUTREASON_GOOD</u> Value: 100
public static final	<u>STREAMTIMEOUTREASON_MISSING</u> Value: 101
public static final	<u>STREAMTIMEOUTREASON_NORTSPSESSION</u> Value: 6
public static final	<u>STREAMTIMEOUTREASON_NOSESSION</u> Value: 2
public static final	<u>STREAMTIMEOUTREASON_NOSTREAM</u> Value: 4
public static final	<u>STREAMTIMEOUTREASON_NOTIMEOUT</u> Value: 1
public static final	<u>STREAMTIMEOUTREASON_NOURL</u> Value: 3
public static final	<u>STREAMTIMEOUTREASON_RECONNECTRUNNING</u> Value: 5
public static final	<u>STREAMTIMEOUTREASON_UNKNOWN</u> Value: 0

Method Summary

boolean	<u>doWatchdog()</u> Idle processor
void	<u>forceReset()</u> Force a reset/reconnect of this media caster
<u>IApplicationInstance</u>	<u>getAppInstance()</u> Get the application instance this media caster is associated with
long	<u>getConnectLastAttempt()</u> Get system time in milliseconds of last connection attempt
long	<u>getConnectLastForceReset()</u> Get system time in milliseconds of last time forceReset was called
long	<u>getConnectLastSuccess()</u> Get system time in milliseconds of last connection success
int	<u>getIdleTimeout()</u> Get the idle timeout for this media caster (milliseconds)
<u>MediaCasterItem</u>	<u>getMediaCasterDef()</u> Get the media caster definition
String	<u>getMediaCasterId()</u> Get the media caster id
<u>MediaCasterStreamItem</u>	<u>getMediaCasterStreamItem()</u> Get the media caster item associated with this media caster
int	<u>getMediaCasterType()</u> Get the media caster type.
int	<u>getReconnectWaitTime()</u> Get the minimum time between reconnect attempts (milliseconds)
<u>IMediaStream</u>	<u>getStream()</u> Get the underlying stream being used by this media caster
Object	<u>getStreamIsRunningLock()</u> Get stream running lock
long	<u>getStreamLastSeq()</u> Get the AMFPacket sequence number of last watchdog processed packet
long	<u>getStreamMissingTime()</u> Get the time in milliseconds the stream has been missing
int	<u>getStreamTimeout()</u> Get the watchdog stream timeout (milliseconds)
long	<u>getStreamTimeoutLastReset()</u> Get system time in milliseconds of last time stream was reset due to stream timeout (debug)
long	<u>getStreamTimeoutLastTime()</u> Get system time in milliseconds of last time stream was considered in missing state (debug)

int	<u>getStreamTimeoutReason()</u> Get the reason the stream is in timeout condition (debug)
<u>IVHost</u>	<u>getVHost()</u> Get the virtual host associated with this media caster
void	<u>init(MediaCasterStreamItem mediaCasterStreamItem, MediaCasterItem mediaCasterDef, IApplicationInstance appInstance, String mediaCasterId, String streamExt)</u> Initialize the media caster
boolean	<u>isSession()</u> Is there current a session attached to this MediaCaster
boolean	<u>isStream()</u> Is there a stream associated with this MediaCaster
boolean	<u>isStreamIsRunning()</u> Return true if stream is currently running
void	<u>registerPlayer(IMediaStreamPlay player)</u> Register a player with this media caster
void	<u>sessionClosed(org.apache.mina.common.IoSession session)</u> sessionClosed callback
void	<u>sessionOpened(org.apache.mina.common.IoSession session)</u> sessionOpened callback
void	<u>setAppInstance(IApplicationInstance appInstance)</u> Set the application instance this media caster is assoicated with
void	<u>setMediaCasterDef(MediaCasterItem mediaCasterDef)</u> Set the media caster definition
void	<u>setMediaCasterId(String mediaCasterId)</u> Get the media caster id
void	<u>setMediaCasterType(int mediaCasterType)</u> Set the media caster type.
void	<u>setReconnectWaitTime(int reconnectWaitTime)</u> Set the minimum time between reconnect attempts (milliseconds)
void	<u>setStream(IMediaStream stream)</u> Set the underlying stream being used by this media caster
void	<u>setStreamTimeout(int streamTimeout)</u> Set the watchdog stream timeout (milliseconds)
void	<u>shutdown(boolean isAppInstanceShutdown)</u> Shutdown media caster
void	<u>unregisterPlayer(IMediaStreamPlay player)</u> Unregister a player with this media caster

Fields

(continued from last page)

STREAMTIMEOUTREASON_UNKNOWN

```
public static final int STREAMTIMEOUTREASON_UNKNOWN
```

Constant value: **0**

STREAMTIMEOUTREASON_NOTIMEOUT

```
public static final int STREAMTIMEOUTREASON_NOTIMEOUT
```

Constant value: **1**

STREAMTIMEOUTREASON_NOSESSION

```
public static final int STREAMTIMEOUTREASON_NOSESSION
```

Constant value: **2**

STREAMTIMEOUTREASON_NOURL

```
public static final int STREAMTIMEOUTREASON_NOURL
```

Constant value: **3**

STREAMTIMEOUTREASON_NOSTREAM

```
public static final int STREAMTIMEOUTREASON_NOSTREAM
```

Constant value: **4**

STREAMTIMEOUTREASON_RECONNECTRUNNING

```
public static final int STREAMTIMEOUTREASON_RECONNECTRUNNING
```

Constant value: **5**

STREAMTIMEOUTREASON_NORTSPSESSION

```
public static final int STREAMTIMEOUTREASON_NORTSPSESSION
```

Constant value: **6**

STREAMTIMEOUTREASON_GOOD

```
public static final int STREAMTIMEOUTREASON_GOOD
```

Constant value: **100**

(continued from last page)

STREAMTIMEOUTREASON_MISSING

```
public static final int STREAMTIMEOUTREASON_MISSING
```

Constant value: **101**

MEDIACASTERTYPE_UNKNOWN

```
public static final int MEDIACASTERTYPE_UNKNOWN
```

Constant value: **0**

MEDIACASTERTYPE_LIVEREPEATER

```
public static final int MEDIACASTERTYPE_LIVEREPEATER
```

Constant value: **1**

MEDIACASTERTYPE_SHOUTCAST

```
public static final int MEDIACASTERTYPE_SHOUTCAST
```

Constant value: **2**

MEDIACASTERTYPE_RTPLIVE

```
public static final int MEDIACASTERTYPE_RTPLIVE
```

Constant value: **3**

Methods

init

```
public void init(MediaCasterStreamItem mediaCasterStreamItem,  
    MediaCasterItem mediaCasterDef,  
    IApplicationInstance appInstance,  
    String mediaCasterId,  
    String streamExt)
```

Initialize the media caster

Parameters:

`mediaCasterStreamItem` - media caster item
`mediaCasterDef` - media caster definition
`appInstance` - application instance
`mediaCasterId` - media caster id
`streamExt` - stream ext or prefix

getVHost

```
public IVHost getVHost()
```

Get the virtual host associated with this media caster

(continued from last page)

Returns:

virtual host associated with this media caster

getMediaCasterId

```
public String getMediaCasterId()
```

Get the media caster id

Returns:

media caster id

setMediaCasterId

```
public void setMediaCasterId(String mediaCasterId)
```

Get the media caster id

Parameters:

mediaCasterId - media caster id

getStream

```
public IMediaStream getStream()
```

Get the underlying stream being used by this media caster

Returns:

underlying stream being used by this media caster

setStream

```
public void setStream(IMediaStream stream)
```

Set the underlying stream being used by this media caster

Parameters:

stream - underlying stream being used by this media caster

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get the application instance this media caster is associated with

Returns:

application instance this media caster is associated with

setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set the application instance this media caster is associated with

Parameters:

appInstance - application instance this media caster is associated with

(continued from last page)

getMediaCasterDef

```
public MediaCasterItem getMediaCasterDef( )
```

Get the media caster definition

Returns:

media caster definition

setMediaCasterDef

```
public void setMediaCasterDef(MediaCasterItem mediaCasterDef)
```

Set the media caster definition

Parameters:

mediaCasterDef - media caster definition

shutdown

```
public void shutdown(boolean isAppInstanceShutdown)
```

Shutdown media caster

Parameters:

isAppInstanceShutdown - is server shutdown

registerPlayer

```
public void registerPlayer(IMediaStreamPlay player)
```

Register a player with this media caster

Parameters:

player - player to register

unregisterPlayer

```
public void unregisterPlayer(IMediaStreamPlay player)
```

Unregister a player with this media caster

Parameters:

player - player to unregister

getIdleTimeout

```
public int getIdleTimeout( )
```

Get the idle timeout for this media caster (milliseconds)

Returns:

idle timeout for this media caster (milliseconds)

sessionOpened

```
public void sessionOpened(org.apache.mina.common.Session session)
```


(continued from last page)

sessionOpened callback

Parameters:

session - IO Session

sessionClosed

```
public void sessionClosed(org.apache.mina.common.Session session)
```

sessionClosed callback

Parameters:

session - IO Session

getMediaCasterStreamItem

```
public MediaCasterStreamItem getMediaCasterStreamItem()
```

Get the media caster item associated with this media caster

Returns:

media caster item associated with this media caster

forceReset

```
public void forceReset()
```

Force a reset/reconnect of this media caster

doWatchdog

```
public boolean doWatchdog()
```

Idle processor

Returns:

return true if media caster unloaded due to idle event

getStreamTimeout

```
public int getStreamTimeout()
```

Get the watchdog stream timeout (milliseconds)

Returns:

stream timeout

setStreamTimeout

```
public void setStreamTimeout(int streamTimeout)
```

Set the watchdog stream timeout (milliseconds)

Parameters:

streamTimeout - stream timeout

(continued from last page)

getStreamMissingTime

```
public long getStreamMissingTime()
```

Get the time in milliseconds the stream has been missing

Returns:

time in milliseconds the stream has been missing

getStreamLastSeq

```
public long getStreamLastSeq()
```

Get the AMFPacket sequence number of last watchdog processed packet

Returns:

AMFPacket sequence number

getStreamTimeoutReason

```
public int getStreamTimeoutReason()
```

Get the reason the stream is in timeout condition (debug)

Returns:

reason the stream is in timeout condition (debug)

getStreamTimeoutLastTime

```
public long getStreamTimeoutLastTime()
```

Get system time in milliseconds of last time stream was considered in missing state (debug)

Returns:

time in milliseconds of last time stream was considered in missing

getStreamTimeoutLastReset

```
public long getStreamTimeoutLastReset()
```

Get system time in milliseconds of last time stream was reset due to stream timeout (debug)

Returns:

time in milliseconds of last time stream was reset

isSession

```
public boolean isSession()
```

Is there current a session attached to this MediaCaster

Returns:

true is MediaCaster has session

isStream

```
public boolean isStream()
```

(continued from last page)

Is there a stream associated with this MediaCaster

Returns:

true if stream associated with this MediaCaster

getConnectLastAttempt

```
public long getConnectLastAttempt( )
```

Get system time in milliseconds of last connection attempt

Returns:

system time in milliseconds of last connection attempt

getConnectLastSuccess

```
public long getConnectLastSuccess( )
```

Get system time in milliseconds of last connection success

Returns:

system time in milliseconds of last connection success

getConnectLastForceReset

```
public long getConnectLastForceReset( )
```

Get system time in milliseconds of last time forceReset was called

Returns:

system time in milliseconds of last time forceReset was called

isStreamIsRunning

```
public boolean isStreamIsRunning( )
```

Return true if stream is currently running

Returns:

true if stream is currently running

getStreamIsRunningLock

```
public Object getStreamIsRunningLock( )
```

Get stream running lock

Returns:

stream running lock

getReconnectWaitTime

```
public int getReconnectWaitTime( )
```

Get the minimum time between reconnect attempts (milliseconds)

Returns:

minimum time between reconnect attempts (milliseconds)

setReconnectWaitTime

```
public void setReconnectWaitTime(int reconnectWaitTime)
```

Set the minimum time between reconnect attempts (milliseconds)

Parameters:

reconnectWaitTime - minimum time between reconnect attempts (milliseconds)

getMediaCasterType

```
public int getMediaCasterType()
```

Get the media caster type. See IMediaCaster.MEDIACASTERTYPE_*

Returns:

media caster type

setMediaCasterType

```
public void setMediaCasterType(int mediaCasterType)
```

Set the media caster type. See IMediaCaster.MEDIACASTERTYPE_*

Parameters:

mediaCasterType - media caster type

com.wowza.wms.mediacaster Interface IMediaCasterDataReceiver

public interface **IMediaCasterDataReceiver**
extends

IMediaCasterDataReceiver: For internal use only.

Method Summary

void	onData (org.apache.mina.common.ByteBuffer data) Data callback
------	----------------------------------------------------------------------------------

Methods

onData

public void **onData**(org.apache.mina.common.ByteBuffer data)

Data callback

Parameters:

data - data

com.wowza.wms.mediacaster Interface IMediaCasterNetConnection

public interface **IMediaCasterNetConnection**
extends

IMediaCasterNetConnection: Internal use only

Method Summary

com.wowza.wms.netconnection.NetConnection	getNetConnection() Receives the INetConnection interface for a live repeater connection
-------------------------------------------	------------------------------------------------------------------------------------------------------------

Methods

getNetConnection

public com.wowza.wms.netconnection.NetConnection **getNetConnection()**

Receives the INetConnection interface for a live repeater connection

Returns:

INetConnection interface

com.wowza.wms.mediacaster Interface IMediaCasterNotify

All Subinterfaces:

[IMediaCasterNotify2](#)

public interface **IMediaCasterNotify**
extends

IMediaCasterNotify: listener interface to MediaCaster system. See IApplicationInstance.addMediaCasterListener().

Method Summary

void	onMediaCasterCreate (IMediaCaster mediaCaster) Invoked when mediaCaster created
void	onMediaCasterDestroy (IMediaCaster mediaCaster) Invoked when MediaCaster destroyed
void	onRegisterPlayer (IMediaCaster mediaCaster, IMediaStreamPlay player) Invoked when a player is added to this mediaCaster
void	onSetSourceStream (IMediaCaster mediaCaster, IMediaStream stream) Invoked when soure stream is set (can be called with stream of null)
void	onUnRegisterPlayer (IMediaCaster mediaCaster, IMediaStreamPlay player) Invoked when a player is removed from this mediaCaster

Methods

onMediaCasterCreate

```
public void onMediaCasterCreate(IMediaCaster mediaCaster)
```

Invoked when mediaCaster created

Parameters:

mediaCaster

onMediaCasterDestroy

```
public void onMediaCasterDestroy(IMediaCaster mediaCaster)
```

Invoked when MediaCaster destroyed

Parameters:

mediaCaster

onRegisterPlayer

```
public void onRegisterPlayer(IMediaCaster mediaCaster,  
    IMediaStreamPlay player)
```

(continued from last page)

Invoked when a player is added to this mediaCaster

Parameters:

mediaCaster
player

onUnRegisterPlayer

```
public void onUnRegisterPlayer(IMediaCaster mediaCaster,  
    IMediaStreamPlay player)
```

Invoked when a player is removed from this mediaCaster

Parameters:

mediaCaster
player

onSetSourceStream

```
public void onSetSourceStream(IMediaCaster mediaCaster,  
    IMediaStream stream)
```

Invoked when source stream is set (can be called with stream of null)

Parameters:

mediaCaster
stream

com.wowza.wms.mediacaster Interface IMediaCasterNotify2

All Superinterfaces:

[IMediaCasterNotify](#)

public interface **IMediaCasterNotify2**

extends [IMediaCasterNotify](#)

Method Summary

void	onConnectFailure (IMediaCaster mediaCaster) Invoked when a connection or reconnection attempt fails
void	onConnectStart (IMediaCaster mediaCaster) Invoked when a connection or reconnection attempt is invoked
void	onConnectSuccess (IMediaCaster mediaCaster) Invoked when a connection or reconnection attempt is successful
void	onStreamStart (IMediaCaster mediaCaster) Invoked when the stream starts receiving media data from the media source.
void	onStreamStop (IMediaCaster mediaCaster) Invoked when the stream stops receiving media data from the media source after the streamTimeout value has passed.

Methods inherited from interface [com.wowza.wms.mediacaster.IMediaCasterNotify](#)

[onMediaCasterCreate](#), [onMediaCasterDestroy](#), [onRegisterPlayer](#), [onSetSourceStream](#), [onUnRegisterPlayer](#)

Methods

onConnectStart

public void **onConnectStart**([IMediaCaster](#) mediaCaster)

Invoked when a connection or reconnection attempt is invoked

Parameters:

mediaCaster

onConnectSuccess

public void **onConnectSuccess**([IMediaCaster](#) mediaCaster)

Invoked when a connection or reconnection attempt is successful

Parameters:

mediaCaster

onConnectFailure

```
public void onConnectFailure(IMediaCaster mediaCaster)
```

Invoked when a connection or reconnection attempt fails

Parameters:

mediaCaster

onStreamStart

```
public void onStreamStart(IMediaCaster mediaCaster)
```

Invoked when the stream starts receiving media data from the media source. This event will only be thrown if the MediaCaster property streamTimeout is set to a non-zero value. NOTE: This is not implemented yet (coming soon)

Parameters:

mediaCaster

onStreamStop

```
public void onStreamStop(IMediaCaster mediaCaster)
```

Invoked when the stream stops receiving media data from the media source after the streamTimeout value has passed. This event will only be thrown if the MediaCaster property streamTimeout is set to a non-zero value. NOTE: This is not implemented yet (coming soon)

Parameters:

mediaCaster

com.wowza.wms.mediacaster

Interface IMediaCasterValidateMediaCaster

All Known Implementing Classes:

[ModuleMediaCasterStreamMonitorAdvanced](#)

public interface **IMediaCasterValidateMediaCaster**
extends

IMediaCasterValidateMediaCaster: interface for implementing stream validators. See [IApplicationInstance.setMediaCasterValidator\(IMediaCasterValidateMediaCaster mediaCasterValidator\)](#)

Method Summary

boolean	onResetMediaCaster (IApplicationInstance appInstance, IMediaCaster mediaCaster) Called when media caster is reset
boolean	onValidateMediaCaster (IApplicationInstance appInstance, IMediaCaster mediaCaster) Called for each media caster to validate the media caster.
void	onValidateMediaCastersStart (IApplicationInstance appInstance) Called when validation for all streams of an application instance is starting
void	onValidateMediaCastersStop (IApplicationInstance appInstance) Called when validation for all streams of an application instance is done

Methods

onValidateMediaCastersStart

public void **onValidateMediaCastersStart**([IApplicationInstance](#) appInstance)

Called when validation for all streams of an application instance is starting

Parameters:

appInstance - application instance

onValidateMediaCastersStop

public void **onValidateMediaCastersStop**([IApplicationInstance](#) appInstance)

Called when validation for all streams of an application instance is done

Parameters:

appInstance

onValidateMediaCaster

public boolean **onValidateMediaCaster**([IApplicationInstance](#) appInstance, [IMediaCaster](#) mediaCaster)

(continued from last page)

Called for each media caster to validate the media caster. Return true if valid.

Parameters:

appInstance - application instance
mediaCaster - media caster

Returns:

true, if valid

onResetMediaCaster

```
public boolean onResetMediaCaster(IApplicationInstance appInstance,  
    IMediaCaster mediaCaster)
```

Called when media caster is reset

Parameters:

appInstance - application instance
mediaCaster - media caster

Returns:

return true

com.wowza.wms.mediacaster

Class MediaCasterItem

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterItem

public class **MediaCasterItem**
extends Object

Constructor Summary

public	MediaCasterItem (String name, String streamType, String baseClass) Media caster item constructor
--------	---------------------------------------------------------------------------------------------------------------------

Method Summary

void	clearProperty (String name) Clear property
String	getBaseClass () Get base class
int	getConnectionTimeout () Get connection timeout (milliseconds)
String	getDescription () Get description
static String	getIdString (String name, String liveStreamPacketizer, String liveStreamRepeater) Get id string for this media caster item (not used - returns name unchanged)
int	getKeepAliveTime () Get keep alive time (milliseconds)
String	getName () Get name
WMSProperties	getProperties () Get properties collection
String	getProperty (String name) Get property value
String	getStreamType () Get the stream type
String	idStringToName (String idString) Convert name to id string (not used - returns id string unchanged)
static MediaCasterStreamId	parseIdString (String idString)

void	<code>setBaseClass</code> (String baseClass) Set base class
void	<code>setConnectionTimeout</code> (int connectionTimeout) Set connection timeout (milliseconds)
void	<code>setDescription</code> (String description) Set description
void	<code>setKeepAliveTime</code> (int keepAliveTime) Set keep alive time (milliseconds)
void	<code>setName</code> (String name) Set name
void	<code>setProperty</code> (String name, String value) Set a property
void	<code>setStreamType</code> (String streamType) Set stream type
String	<code>toString</code> () toString

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

MediaCasterItem

```
public MediaCasterItem(String name,
                      String streamType,
                      String baseClass)
```

Media caster item constructor

Parameters:

name - media caster name
streamType - stream type
baseClass - base class

Methods

getStreamType

```
public String getStreamType()
```

Get the stream type

Returns:

stream type

(continued from last page)

setStreamType

```
public void setStreamType(String streamType)
```

Set stream type

Parameters:

streamType - stream type

getName

```
public String getName()
```

Get name

Returns:

name

setName

```
public void setName(String name)
```

Set name

Parameters:

name - name

setProperty

```
public void setProperty(String name,  
                        String value)
```

Set a property

Parameters:

name - name

value - value

clearProperty

```
public void clearProperty(String name)
```

Clear property

Parameters:

name - name

getProperty

```
public String getProperty(String name)
```

Get property value

Parameters:

name - name

Returns:

property value

getProperties

```
public WMSProperties getProperties()
```

Get properties collection

Returns:
properties collection

getDescription

```
public String getDescription()
```

Get description

Returns:
description

setDescription

```
public void setDescription(String description)
```

Set description

Parameters:
description - description

getBaseClass

```
public String getBaseClass()
```

Get base class

Returns:
base class

setBaseClass

```
public void setBaseClass(String baseClass)
```

Set base class

Parameters:
baseClass - base class

getConnectionTimeout

```
public int getConnectionTimeout()
```

Get connection timeout (milliseconds)

Returns:
connection timeout (milliseconds)

setConnectionTimeout

```
public void setConnectionTimeout(int connectionTimeout)
```

(continued from last page)

Set connection timeout (milliseconds)

Parameters:

connectionTimeout - connection timeout (milliseconds)

getKeepAliveTime

```
public int getKeepAliveTime()
```

Get keep alive time (milliseconds)

Returns:

keep alive time (milliseconds)

setKeepAliveTime

```
public void setKeepAliveTime(int keepAliveTime)
```

Set keep alive time (milliseconds)

Parameters:

keepAliveTime - keep alive time (milliseconds)

getIdString

```
public static String getIdString(String name,  
    String liveStreamPacketizer,  
    String liveStreamRepeater)
```

Get id string for this media caster item (not used - returns name unchanged)

Parameters:

name - name

Returns:

id string for this media caster item

parseIdString

```
public static MediaCasterStreamId parseIdString(String idString)
```

idStringToName

```
public String idStringToName(String idString)
```

Convert name to id string (not used - returns id string unchanged)

Parameters:

idString - id string

Returns:

name

toString

```
public String toString()
```

(continued from last page)

toString

com.wowza.wms.mediacaster Class MediaCasterList

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterList

public class **MediaCasterList**
extends Object

Constructor Summary

public	<u>MediaCasterList()</u> Constructor
--------	---------------------------------------------------------

Method Summary

<u>MediaCasterItem</u>	<u>getMediaCasterDef()</u> (String name) Get media caster definition by name
java.util.Map	<u>getMediaCasterDefs()</u> Get map of media caster items
java.util.List	<u>getMediaCasterNames()</u> Get list of media caster names

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

MediaCasterList

public **MediaCasterList()**

Constructor

Methods

getMediaCasterDefs

public java.util.Map **getMediaCasterDefs()**

Get map of media caster items

Returns:

map of media caster items

(continued from last page)

getMediaCasterNames

```
public java.util.List getMediaCasterNames()
```

Get list of media caster names

Returns:

list of media caster names

getMediaCasterDef

```
public MediaCasterItem getMediaCasterDef(String name)
```

Get media caster definition by name

Parameters:

name - name

Returns:

media caster definition

com.wowza.wms.mediacaster Class MediaCasterSettings

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterSettings

public class **MediaCasterSettings**
extends Object

Constructor Summary

public	MediaCasterSettings()
--------	---------------------------------------

Method Summary

HostPortConfig	getMediaCasterHostPortConfig() Get media caster host port config
int	getMediaCasterProcessorCount() Get the thread count use for this host port
void	setMediaCasterHostPortConfig (HostPortConfig mediaCasterHostPortConfig) Set media caster host port config
void	setMediaCasterProcessorCount (int mediaCasterProcessorCount) Set the thread count for this processor

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

MediaCasterSettings

public **MediaCasterSettings()**

Methods

getMediaCasterHostPortConfig

public HostPortConfig **getMediaCasterHostPortConfig()**

Get media caster host port config

Returns:

host port config

setMediaCasterHostPortConfig

```
public void setMediaCasterHostPortConfig(HostPortConfig mediaCasterHostPortConfig)
```

Set media caster host port config

Parameters:

mediaCasterHostPortConfig

getMediaCasterProcessorCount

```
public int getMediaCasterProcessorCount()
```

Get the thread count use for this host port

Returns:

thread count use for this host port

setMediaCasterProcessorCount

```
public void setMediaCasterProcessorCount(int mediaCasterProcessorCount)
```

Set the thread count for this processor

Parameters:

mediaCasterProcessorCount - thread count use for this host port

com.wowza.wms.mediacaster Class MediaCasterStreamItem

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterStreamItem

public class **MediaCasterStreamItem**
extends Object

Constructor Summary

public	<u>MediaCasterStreamItem</u> (long uniqueId) Media caster item constructor
--------	-----------------------------------------------------------------------------------------------

Method Summary

void	<u>acquire</u> () Increment acquire lock count for this media caster item
void	<u>acquireAndRelease</u> () Increment then decrement acquire lock count for this media caster item
boolean	<u>doWatchdog</u> () Do idle processing
String	<u>getLiveStreamPacketizer</u> () Get the live stream packetizer for this media caster stream item
String	<u>getLiveStreamRepeater</u> () Get the live stream repeater for this media caster stream item
Object	<u>getLock</u> ()
int	<u>getLockCount</u> () Get the current number of acquire locks on this media caster item
<u>IMediaCaster</u>	<u>getMediaCaster</u> () Get the underlying IMediaCaster interface for this MediaCaster
String	<u>getMediaCasterId</u> () Get this media caster item id
int	<u>getPlayerCount</u> () Get the current number of players associated with this media caster item
String	<u>getStreamExt</u> ()
long	<u>getUniqueId</u> ()

void	<code>init</code> (String mediaCasterId, String streamExt, <code>MediaCasterItem</code> mediaCasterDef, <code>MediaCasterStreamMap</code> parent, String liveStreamPacketizer, String liveStreamRepeater) Initialize the media caster item (internal use)
boolean	<code>isShutdownOnRelease</code> () On last release shutdown the stream even if clients are connected
boolean	<code>isValid</code> ()
void	<code>registerPlayer</code> (<code>IMediaStreamPlay</code> player) Register a player with a media caster item (internal use)
void	<code>release</code> () Decrement acquire lock count for this media caster item
void	<code>reset</code> () Force a reconnect or reset for this media caster item
void	<code>setLiveStreamPacketizer</code> (String liveStreamPacketizer) Set the live stream packetizer for this media caster stream item
void	<code>setLiveStreamRepeater</code> (String liveStreamRepeater) Set the live stream repeater for this media caster stream item
void	<code>setShutdownOnRelease</code> (boolean shutdownOnRelease) On last release shutdown the stream even if clients are connected
void	<code>setStreamExt</code> (String streamExt)
void	<code>setValid</code> (boolean isValid)
void	<code>shutdown</code> (boolean isAppInstanceShutdown) Shutdown this media caster item
void	<code>unregisterPlayer</code> (<code>IMediaStreamPlay</code> player) Unregister a player with a media caster item (internal use)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

MediaCasterStreamItem

```
public MediaCasterStreamItem(long uniqueId)
```

Media caster item constructor

Methods

(continued from last page)

getLock

```
public Object getLock()
```

getUniqueId

```
public long getUniqueId()
```

isValid

```
public boolean isValid()
```

setValid

```
public void setValid(boolean isValid)
```

init

```
public void init(String mediaCasterId,  
                String streamExt,  
                MediaCasterItem mediaCasterDef,  
                MediaCasterStreamMap parent,  
                String liveStreamPacketizer,  
                String liveStreamRepeater)
```

Initialize the media caster item (internal use)

Parameters:

mediaCasterId - media caster id
streamExt - stream extension or prefix
mediaCasterDef - media caster definition
parent - parent map

getMediaCasterId

```
public String getMediaCasterId()
```

Get this media caster item id

Returns:

media caster item id

getMediaCaster

```
public IMediaCaster getMediaCaster()
```

Get the underlying IMediaCaster interface for this MediaCaster

Returns:

underlying IMediaCaster interface

registerPlayer

```
public void registerPlayer(IMediaStreamPlay player)
```

Register a player with a media caster item (internal use)

Parameters:

player - player to register

unregisterPlayer

```
public void unregisterPlayer(IMediaStreamPlay player)
```

Unregister a player with a media caster item (internal use)

Parameters:

player - player to unregister

doWatchdog

```
public boolean doWatchdog()
```

Do idle processing

Returns:

return true if caused shutdown of item

reset

```
public void reset()
```

Force a reconnect or reset for this media caster item

shutdown

```
public void shutdown(boolean isAppInstanceShutdown)
```

Shutdown this media caster item

Parameters:

isAppInstanceShutdown - is this due to application shutdown

getPlayerCount

```
public int getPlayerCount()
```

Get the current number of players associated with this media caster item

Returns:

current number of players associated with this media caster item

getLockCount

```
public int getLockCount()
```

Get the current number of acquire locks on this media caster item

(continued from last page)

Returns:

current number of acquire locks on this media caster item

acquireAndRelease

```
public void acquireAndRelease()
```

Increment then decrement acquire lock count for this media caster item

acquire

```
public void acquire()
```

Increment acquire lock count for this media caster item

release

```
public void release()
```

Decrement acquire lock count for this media caster item

getStreamExt

```
public String getStreamExt()
```

setStreamExt

```
public void setStreamExt(String streamExt)
```

isShutdownOnRelease

```
public boolean isShutdownOnRelease()
```

On last release shutdown the stream even if clients are connected

Returns:

true if shutting down on release

setShutdownOnRelease

```
public void setShutdownOnRelease(boolean shutdownOnRelease)
```

On last release shutdown the stream even if clients are connected

Parameters:

shutdownOnRelease - true if shutting down on release

getLiveStreamPacketizer

```
public String getLiveStreamPacketizer()
```

Get the live stream packetizer for this media caster stream item

Returns:

(continued from last page)

live stream packetizer

setLiveStreamPacketizer

```
public void setLiveStreamPacketizer(String liveStreamPacketizer)
```

Set the live stream packetizer for this media caster stream item

Parameters:

liveStreamPacketizer - live stream packetizer

getLiveStreamRepeater

```
public String getLiveStreamRepeater()
```

Get the live stream repeater for this media caster stream item

Returns:

live stream repeater

setLiveStreamRepeater

```
public void setLiveStreamRepeater(String liveStreamRepeater)
```

Set the live stream repeater for this media caster stream item

Parameters:

liveStreamRepeater - live stream repeater

com.wowza.wms.mediacaster Class MediaCasterStreamManager

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterStreamManager

public class **MediaCasterStreamManager**
extends Object

Constructor Summary

public	MediaCasterStreamManager (MediaCasterStreamMap mediaCasterStreamMap)
--------	-------------------------------------------------------------------------------------------------------

Method Summary

String[]	getStreamArray () Get a list of active streams
java.util.List	getStreamList () Get a list of active streams
boolean	startStream (String streamName, String mediaCasterType) Start a stream by name
boolean	stopStream (String streamName) Stop a stream by name
boolean	streamExists (String streamName) Returns true if stream exists

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

MediaCasterStreamManager

public **MediaCasterStreamManager**([MediaCasterStreamMap](#) mediaCasterStreamMap)

Methods

getStreamArray

public String[] **getStreamArray**()

Get a list of active streams

(continued from last page)

Returns:

list of active streams

getStreamList

```
public java.util.List getStreamList()
```

Get a list of active streams

Returns:

list of active streams

streamExists

```
public boolean streamExists(String streamName)
```

Returns true if stream exists

Parameters:

streamName - stream name

Returns:

true if stream exists

stopStream

```
public boolean stopStream(String streamName)
```

Stop a stream by name

Parameters:

streamName - stream name

Returns:

true is successful

startStream

```
public boolean startStream(String streamName,  
    String mediaCasterType)
```

Start a stream by name

Parameters:

streamName - stream name

mediaCasterType - MediaCaster type as defined in the name field of conf/MediaCasters.xml

Returns:

true is successful

com.wowza.wms.mediacaster

Class MediaCasterStreamMap

java.lang.Object

└─com.wowza.wms.mediacaster.MediaCasterStreamMap

public class **MediaCasterStreamMap**
extends Object

Constructor Summary

public	MediaCasterStreamMap (IApplicationInstance appInstance) Create a new mediacaster map
--------	--------------------------------------------------------------------------------------------------------------------------

Method Summary

MediaCasterStreamItem	acquire (String streamName) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
MediaCasterStreamItem	acquire (String inStreamName, MediaCasterItem mediaCasterDef) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
MediaCasterStreamItem	acquire (String inStreamName, String streamType) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
MediaCasterStreamItem	acquire (String streamName, String liveStreamPacketizer, String liveStreamRepeater) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
MediaCasterStreamItem	acquire (String inStreamName, String liveStreamPacketizer, String liveStreamRepeater, MediaCasterItem mediaCasterDef) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
MediaCasterStreamItem	acquire (String inStreamName, String liveStreamPacketizer, String liveStreamRepeater, String streamType) Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away).
MediaCasterStreamItem	acquireAndRelease (String inStreamName, String liveStreamPacketizer, String liveStreamRepeater, MediaCasterItem mediaCasterDef) Increment and then decrement the lock count for a media caster item (so that it is loaded and will stay loaded for at least the KeepAliveTime).
void	addStreamSrcToMediaCaster (long streamSrc, String mediaCasterId)
void	clearStreamSrcToMediaCaster (long streamSrc)
void	doWatchdog () Do periodic idle time processing

<u>IApplicationInstance</u>	<u>getApplicationInstance()</u> Get the parent application instance for this map
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<u>getLock()</u> Get the read/write lock for this interface
<u>MediaCasterStreamItem</u>	<u>getMediaCaster(String streamName)</u> Get media caster item based on given stream name
<u>MediaCasterStreamItem</u>	<u>getMediaCaster(String streamName, String liveStreamPacketizer, String liveStreamRepeater)</u> Get media caster item based on given stream name
int	<u>getMediaCasterCount()</u> Get the number of mediacasters current running
java.util.List	<u>getMediaCasterNames()</u> Get a list of all the currently running media caster names
<u>MediaCasterStreamManager</u>	<u>getStreamManager()</u> Get the stream manager interface for managing the starting and stopping of streams
void	<u>registerPlayer(IMediaStreamPlay player, MediaCasterItem mediaCasterDef)</u> Register a player to a media caster item (internal use)
void	<u>release(MediaCasterStreamItem mediaCasterStreamItem)</u> Decrement lock count on media caster item
void	<u>release(MediaCasterStreamItem mediaCasterStreamItem, boolean removeIfZero)</u>
void	<u>remove(MediaCasterStreamItem mediaCasterStreamItem)</u>
void	<u>shutdown(boolean isAppInstanceShutdown)</u> Shutdown this media caster and close all running media casters
String	<u>streamSrcToMediaCaster(long streamSrc)</u>
void	<u>unregisterPlayer(IMediaStreamPlay player, MediaCasterItem mediaCasterDef)</u> Unregister a player to a media caster item (internal use)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

MediaCasterStreamMap

public **MediaCasterStreamMap**([IApplicationInstance](#) appInstance)

Create a new mediacaster map

(continued from last page)

Parameters:

appInstance - application instance

Methods

getLock

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock getLock()
```

Get the read/write lock for this interface

Returns:

read/write lock

getStreamManager

```
public MediaCasterStreamManager getStreamManager()
```

Get the stream manager interface for managing the starting and stopping of streams

Returns:

stream manager interface

getApplicationInstance

```
public IApplicationInstance getApplicationInstance()
```

Get the parent application instance for this map

Returns:

parent application instance for this map

getMediaCasterCount

```
public int getMediaCasterCount()
```

Get the number of mediacasters current running

Returns:

number of mediacasters current running

doWatchdog

```
public void doWatchdog()
```

Do periodic idle time processing

shutdown

```
public void shutdown(boolean isAppInstanceShutdown)
```

Shutdown this media caster and close all running media casters

Parameters:

isAppInstanceShutdown - is this due to application shutdown

(continued from last page)

getMediaCasterNames

```
public java.util.List getMediaCasterNames()
```

Get a list of all the currently running media caster names

Returns:

list of all the currently running media caster names

getMediaCaster

```
public MediaCasterStreamItem getMediaCaster(String streamName)
```

Get media caster item based on given stream name

Parameters:

streamName - stream name

Returns:

media caster item

getMediaCaster

```
public MediaCasterStreamItem getMediaCaster(String streamName,  
String liveStreamPacketizer,  
String liveStreamRepeater)
```

Get media caster item based on given stream name

Parameters:

streamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

Returns:

media caster item

acquire

```
public MediaCasterStreamItem acquire(String streamName,  
String liveStreamPacketizer,  
String liveStreamRepeater)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. Uses default application instance stream type.

Parameters:

streamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

Returns:

media caster item

acquire

```
public MediaCasterStreamItem acquire(String streamName)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. Uses default application instance stream type.

(continued from last page)

Parameters:

streamName - stream name

Returns:

media caster item

acquire

```
public MediaCasterStreamItem acquire(String inStreamName,  
    MediaCasterItem mediaCasterDef)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. This API allow loading of a MediaCaster into a non-MediaCaster stream type such as the "live" or "liverepeater-origin" stream type.

Parameters:

inStreamName - stream name

mediaCasterDef - MediaCaster definition

Returns:

media caster item

acquire

```
public MediaCasterStreamItem acquire(String inStreamName,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    MediaCasterItem mediaCasterDef)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded. This API allow loading of a MediaCaster into a non-MediaCaster stream type such as the "live" or "liverepeater-origin" stream type.

Parameters:

inStreamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

mediaCasterDef - MediaCaster definition

Returns:

media caster item

acquireAndRelease

```
public MediaCasterStreamItem acquireAndRelease(String inStreamName,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    MediaCasterItem mediaCasterDef)
```

Increment and then decrement the lock count for a media caster item (so that it is loaded and will stay loaded for at least the KeepAliveTime). Will load the media caster if not already loaded. This API allow loading of a MediaCaster into a non-MediaCaster stream type such as the "live" or "liverepeater-origin" stream type.

Parameters:

inStreamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

mediaCasterDef - MediaCaster definition

Returns:

(continued from last page)

media caster item

acquire

```
public MediaCasterStreamItem acquire(String inStreamName,  
    String streamType)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded.

Parameters:

inStreamName - stream name

streamType - stream type to use (null will use default application streamType)

Returns:

media caster item

acquire

```
public MediaCasterStreamItem acquire(String inStreamName,  
    String liveStreamPacketizer,  
    String liveStreamRepeater,  
    String streamType)
```

Increment the lock count for a media caster item (so that it remains loaded even if all listeners go away). Will load the media caster if not already loaded.

Parameters:

inStreamName - stream name

liveStreamPacketizer - live stream packetizer name

liveStreamRepeater - live stream repeater name

streamType - stream type to use (null will use default application streamType)

Returns:

media caster item

release

```
public void release(MediaCasterStreamItem mediaCasterStreamItem)
```

Decrement lock count on media caster item

Parameters:

mediaCasterStreamItem - media caster item to decrement

release

```
public void release(MediaCasterStreamItem mediaCasterStreamItem,  
    boolean removeIfZero)
```

remove

```
public void remove(MediaCasterStreamItem mediaCasterStreamItem)
```

(continued from last page)

streamSrcToMediaCaster

```
public String streamSrcToMediaCaster(long streamSrc)
```

addStreamSrcToMediaCaster

```
public void addStreamSrcToMediaCaster(long streamSrc,  
    String mediaCasterId)
```

clearStreamSrcToMediaCaster

```
public void clearStreamSrcToMediaCaster(long streamSrc)
```

registerPlayer

```
public void registerPlayer(IMediaStreamPlay player,  
    MediaCasterItem mediaCasterDef)
```

Register a player to a media caster item (internal use)

Parameters:

player - player to register
mediaCasterDef - media caster definition

unregisterPlayer

```
public void unregisterPlayer(IMediaStreamPlay player,  
    MediaCasterItem mediaCasterDef)
```


Unregister a player to a media caster item (internal use)

Parameters:

player - player to unregister
mediaCasterDef - media caster definition

com.wowza.wms.mediacaster Class ModuleMediaCaster

java.lang.Object



All Implemented Interfaces:

[IModuleOnApp](#)

public class **ModuleMediaCaster**
 extends [ModuleBase](#)
 implements [IModuleOnApp](#)

ModuleMediaCaster: Module for manipulating media casters through a Flash UI.

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK_PARAM1](#), [CALLBACK_PARAM10](#), [CALLBACK_PARAM2](#), [CALLBACK_PARAM3](#), [CALLBACK_PARAM4](#),
[CALLBACK_PARAM5](#), [CALLBACK_PARAM6](#), [CALLBACK_PARAM7](#), [CALLBACK_PARAM8](#), [CALLBACK_PARAM9](#), [PARAM1](#),
[PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#),
[PLAYTRANSITION_APPEND](#), [PLAYTRANSITION_APPEND_IMMEDIATE](#), [PLAYTRANSITION_RESET](#),
[PLAYTRANSITION_RESET_IMMEDIATE](#), [PLAYTRANSITION_STOP](#), [PLAYTRANSITION_SWAP](#),
[PLAYTRANSITION_SWITCH](#), [PLAYTRANSITION_UNKNOWN](#), [PLAYTRANSITIONSTR_APPEND](#),
[PLAYTRANSITIONSTR_RESET](#), [PLAYTRANSITIONSTR_STOP](#), [PLAYTRANSITIONSTR_SWAP](#),
[PLAYTRANSITIONSTR_SWITCH](#), [PLAYTRANSITIONSTR_UNKNOWN](#)

Constructor Summary

public	ModuleMediaCaster ()
--------	--------------------------------------

Method Summary

void	acquireMediaCaster (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Increment the lock count of a media caster stream.
void	getLockCount (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the current lock count for a stream
void	getPlayerCount (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the numbers of players associated with a particular media caster
void	getStreamNames (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get an array of stream names that are media casters associate with this application instance (returned as AMFDataArray)
void	onAppStart (IApplicationInstance appInstance) onAppStart

void	onAppStop (IApplicationInstance appInstance) onAppStop
void	releaseMediaCaster (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Decrement the lock count of a media caster stream
void	resetStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Reset a media caster stream
void	shutdownStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Force shutdown a media caster stream

Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.module.IModuleOnApp](#)

[onAppStart](#), [onAppStop](#)

Constructors

ModuleMediaCaster

```
public ModuleMediaCaster()
```

Methods

onAppStart

```
public void onAppStart(IApplicationInstance appInstance)
```

onAppStart

onAppStop

```
public void onAppStop(IApplicationInstance appInstance)
```

onAppStop

getLockCount

```
public void getLockCount(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the current lock count for a stream

Parameters:

client - client
function - function
params - {streamName}

getPlayerCount

```
public void getPlayerCount(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the numbers of players associated with a particular media caster

Parameters:

client - client
function - function
params - {streamName}

getStreamNames

```
public void getStreamNames(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get an array of stream names that are media casters associate with this application instance (returned as AMFDataArray)

Parameters:

client - client
function - function
params - (no params)

resetStream

```
public void resetStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Reset a media caster stream

Parameters:

client - client
function - function
params - {streamName}

shutdownStream

```
public void shutdownStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Force shutdown a media caster stream

(continued from last page)

Parameters:

client - client
function - function
params - {streamName}

acquireMediaCaster

```
public void acquireMediaCaster(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Increment the lock count of a media caster stream. If the media caster does not exists create it and connect.

Parameters:

client - client
function - function
params - {streamName, streamType [optional]}

releaseMediaCaster

```
public void releaseMediaCaster(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Decrement the lock count of a media caster stream

Parameters:

client - client
function - function
params - {streamName}

Package

com.wowza.wms.mediacaster.rtp

com.wowza.wms.mediacaster.rtp Interface IRTPSessionDescriptionDataProvider

public interface **IRTPSessionDescriptionDataProvider**
extends

IRTPSessionDescriptionDataProvider: Internal use.

Method Summary

boolean	doIdle (MediaCaster mediaCaster)
RTPSessionDescription Data	getSessionDescriptionData (IApplicationInstance appInstance, String streamName, int retryCount, IRTPSessionDescriptionSessionHandler handler, IMediaCaster mediaCaster)
void	init (MediaCaster mediaCaster)
void	sessionStart (RTPSession rtpSession)
void	sessionStop (RTPSession rtpSession)

Methods

init

```
public void init(MediaCaster mediaCaster)
```

getSessionDescriptionData

```
public RTPSessionDescriptionData getSessionDescriptionData(IApplicationInstance appInstance,  
    String streamName,  
    int retryCount,  
    IRTPSessionDescriptionSessionHandler handler,  
    IMediaCaster mediaCaster)
```

sessionStart

```
public void sessionStart(RTPSession rtpSession)
```

sessionStop

```
public void sessionStop(RTPSession rtpSession)
```

(continued from last page)

doIdle

```
public boolean doIdle(MediaCaster mediaCaster)
```

com.wowza.wms.mediacaster.rtp Interface IRTPSessionDescriptionSessionHandler

public interface **IRTPSessionDescriptionSessionHandler**
extends

IRTPSessionDescriptionSessionHandler: Internal use.

Method Summary

void	onDisconnect()
------	--------------------------------

Methods

onDisconnect

public void **onDisconnect()**

Package

com.wowza.wms.mediacaster.shoutcast

com.wowza.wms.mediacaster.shoutcast Interface IShoutCastFrameReceiver

public interface **IShoutCastFrameReceiver**
extends

IShoutCastFrameReceiver: Internal use.

Method Summary

void	<code>onCodecConfigAAC</code> (com.wowza.wms.media.aac.AACFrame frame, byte[] buffer, long offset)
void	<code>onFrameAAC</code> (com.wowza.wms.media.aac.AACFrame frame, byte[] buffer, long offset)
void	<code>onFrameMP3</code> (int frequency, int samplesPerFrame, int channels, byte[] syncHeader, byte[] packetHeader, byte[] frameData)
void	<code>onHeaderData</code> (java.util.Map headerMap)
void	<code>onMetaData</code> (java.util.Map metaMap)
void	<code>onTrim</code> ()

Methods

onFrameMP3

```
public void onFrameMP3(int frequency,
    int samplesPerFrame,
    int channels,
    byte[] syncHeader,
    byte[] packetHeader,
    byte[] frameData)
```

onCodecConfigAAC

```
public void onCodecConfigAAC(com.wowza.wms.media.aac.AACFrame frame,
    byte[] buffer,
    long offset)
```

onFrameAAC

```
public void onFrameAAC(com.wowza.wms.media.aac.AACFrame frame,
    byte[] buffer,
    long offset)
```

(continued from last page)

onTrim

```
public void onTrim()
```

onHeaderData

```
public void onHeaderData(java.util.Map headerMap)
```

onMetaData

```
public void onMetaData(java.util.Map metaMap)
```

com.wowza.wms.mediacaster.shoutcast Interface IShoutCastMetaDataListener

public interface **IShoutCastMetaDataListener**
extends

IShoutCastMetaDataListener: Internal use.

Method Summary

void	addMetaDataListener (IShoutCastMetaDataNotify listener)
boolean	removeMetaDataListener (IShoutCastMetaDataNotify listener)

Methods

addMetaDataListener

public void **addMetaDataListener**([IShoutCastMetaDataNotify](#) listener)

removeMetaDataListener

public boolean **removeMetaDataListener**([IShoutCastMetaDataNotify](#) listener)

com.wowza.wms.mediacaster.shoutcast Interface IShoutCastMetaDataNotify

public interface **IShoutCastMetaDataNotify**
extends

IShoutCastMetaDataNotify: Internal use.

Method Summary

void	onAACEncodeInfo (IMediaCaster mediaCaster, int frequency, int channels, int samplesPerFrame)
void	onHeaderData (IMediaCaster mediaCaster, java.util.Map headerMap)
void	onMetaData (IMediaCaster mediaCaster, java.util.Map metaMap)
void	onMP3EncodeInfo (IMediaCaster mediaCaster, int frequency, int channels, int samplesPerFrame)

Methods

onHeaderData

```
public void onHeaderData(IMediaCaster mediaCaster,  
    java.util.Map headerMap)
```

onMetaData

```
public void onMetaData(IMediaCaster mediaCaster,  
    java.util.Map metaMap)
```

onAACEncodeInfo

```
public void onAACEncodeInfo(IMediaCaster mediaCaster,  
    int frequency,  
    int channels,  
    int samplesPerFrame)
```

onMP3EncodeInfo

```
public void onMP3EncodeInfo(IMediaCaster mediaCaster,  
    int frequency,  
    int channels,  
    int samplesPerFrame)
```

(continued from last page)

Package

com.wowza.wms.medialist

com.wowza.wms.medialist Class MediaList

java.lang.Object

└─com.wowza.wms.medialist.MediaList

public class **MediaList**
extends Object

Field Summary

protected	lock
protected	name
protected	properties
protected	segments

Constructor Summary

public	MediaList()
--------	-----------------------------

Method Summary

void	addSegment (int index, MediaListSegment mediaListSegment)
void	addSegment (MediaListSegment mediaListSegment)
void	clearSegments ()
MediaListSegment	getFirstSegment ()
Object	getLock ()
String	getName ()
WMSProperties	getProperties ()
WMSProperties	getProperties (boolean write)
java.util.List	getSegment ()
MediaListSegment	getSegment (int index)

MediaListSegment	removeSegment (int index)
void	removeSegment (MediaListSegment mediaListSegment)
void	reset ()
void	setName (String name)
String	toSMILString ()
String	toString ()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

name

protected java.lang.String **name**

segments

protected java.util.List **segments**

properties

protected com.wowza.wms.application.WMSProperties **properties**

lock

protected java.lang.Object **lock**

Constructors

MediaList

public **MediaList**()

Methods

(continued from last page)

toString

```
public String toString()
```

toSMILString

```
public String toSMILString()
```

reset

```
public void reset()
```

getSegment

```
public java.util.List getSegment()
```

addSegment

```
public void addSegment(MediaListSegment mediaListSegment)
```

addSegment

```
public void addSegment(int index,  
    MediaListSegment mediaListSegment)
```

removeSegment

```
public void removeSegment(MediaListSegment mediaListSegment)
```

removeSegment

```
public MediaListSegment removeSegment(int index)
```

clearSegments

```
public void clearSegments()
```

(continued from last page)

getFirstSegment

```
public MediaListSegment getFirstSegment()
```

getSegment

```
public MediaListSegment getSegment(int index)
```

getLock

```
public Object getLock()
```

getProperties

```
public WMSPProperties getProperties()
```

getProperties

```
public WMSPProperties getProperties(boolean write)
```

getName

```
public String getName()
```

setName

```
public void setName(String name)
```

com.wowza.wms.medialist Class MediaListRendition

java.lang.Object

└-com.wowza.wms.medialist.MediaListRendition

public class **MediaListRendition**
extends Object

Field Summary

protected	audioCodecId
protected	bitrateAudio
protected	bitrateTotal
protected	bitrateVideo
protected	height
protected	lock
protected	mediaListSegment
protected	name
protected	playDuration
protected	playStart
protected	properties
protected	type
protected	videoCodecId
protected	width
protected	wowzaAudioOnly

Constructor Summary

public	MediaListRendition()
--------	--------------------------------------

Method Summary

String	<u>getAudioCodecId()</u>
int	<u>getBitrateAudio()</u>
int	<u>getBitrateTotal()</u>
int	<u>getBitrateVideo()</u>
String	<u>getCodecId()</u>
int	<u>getHeight()</u>
Object	<u>getLock()</u>
<u>MediaListSegment</u>	<u>getMediaListSegment()</u>
String	<u>getName()</u>
long	<u>getPlayDuration()</u>
long	<u>getPlayStart()</u>
<u>WMSProperties</u>	<u>getProperties()</u>
<u>WMSProperties</u>	<u>getProperties</u> (boolean write)
int[]	<u>getSize()</u>
int	<u>getType()</u>
String	<u>getTypeAsString()</u>
String	<u>getVideoCodecId()</u>
int	<u>getWidth()</u>
boolean	<u>isWowzaAudioOnly()</u>
void	<u>setAudioCodecId</u> (String audioCodecId)
void	<u>setBitrateAudio</u> (int bitrateAudio)
void	<u>setBitrateTotal</u> (int bitrateTotal)
void	<u>setBitrateVideo</u> (int bitrateVideo)

void	<code>setHeight</code> (int height)
void	<code>setLock</code> (Object lock)
void	<code>setMediaListSegment</code> (<code>MediaListSegment</code> mediaListSegment)
void	<code>setName</code> (String name)
void	<code>setPlayDuration</code> (long playDuration)
void	<code>setPlayStart</code> (long playStart)
void	<code>setSize</code> (int width, int height)
void	<code>setType</code> (int type)
void	<code>setVideoCodecId</code> (String videoCodecId)
void	<code>setWidth</code> (int width)
void	<code>setWowzaAudioOnly</code> (boolean wowzaAudioOnly)
String	<code>toSMILString</code> ()
String	<code>toString</code> ()

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

`lock`

protected `java.lang.Object` **`lock`**

`mediaListSegment`

protected `com.wowza.wms.medialist.MediaListSegment` **`mediaListSegment`**

`properties`

protected `com.wowza.wms.application.WMSProperties` **`properties`**

name

protected java.lang.String **name**

type

protected int **type**

bitrateTotal

protected int **bitrateTotal**

bitrateAudio

protected int **bitrateAudio**

bitrateVideo

protected int **bitrateVideo**

videoCodecId

protected java.lang.String **videoCodecId**

audioCodecId

protected java.lang.String **audioCodecId**

wowzaAudioOnly

protected boolean **wowzaAudioOnly**

width

protected int **width**

height

protected int **height**

(continued from last page)

playStart

protected long **playStart**

playDuration

protected long **playDuration**

Constructors

MediaListRendition

public **MediaListRendition**()

Methods

toString

public String **toString**()

toSMILString

public String **toSMILString**()

getTypeAsString

public String **getTypeAsString**()

getLock

public Object **getLock**()

setLock

public void **setLock**(Object lock)

getMediaListSegment

public [MediaListSegment](#) **getMediaListSegment**()

(continued from last page)

setMediaListSegment

```
public void setMediaListSegment(MediaListSegment mediaListSegment)
```

getProperties

```
public WMSProperties getProperties()
```

getProperties

```
public WMSProperties getProperties(boolean write)
```

getBitrateTotal

```
public int getBitrateTotal()
```

setBitrateTotal

```
public void setBitrateTotal(int bitrateTotal)
```

getBitrateAudio

```
public int getBitrateAudio()
```

setBitrateAudio

```
public void setBitrateAudio(int bitrateAudio)
```

getBitrateVideo

```
public int getBitrateVideo()
```

setBitrateVideo

```
public void setBitrateVideo(int bitrateVideo)
```

(continued from last page)

getVideoCodecId

```
public String getVideoCodecId()
```

setVideoCodecId

```
public void setVideoCodecId(String videoCodecId)
```

getCodecId

```
public String getCodecId()
```

getAudioCodecId

```
public String getAudioCodecId()
```

setAudioCodecId

```
public void setAudioCodecId(String audioCodecId)
```

isWowzaAudioOnly

```
public boolean isWowzaAudioOnly()
```

setWowzaAudioOnly

```
public void setWowzaAudioOnly(boolean wowzaAudioOnly)
```

getName

```
public String getName()
```

setName

```
public void setName(String name)
```

getType

```
public int getType()
```

(continued from last page)

setType

```
public void setType(int type)
```

getWidth

```
public int getWidth()
```

setWidth

```
public void setWidth(int width)
```

getHeight

```
public int getHeight()
```

setHeight

```
public void setHeight(int height)
```

setSize

```
public void setSize(int width,  
                    int height)
```

getSize

```
public int[] getSize()
```

getPlayStart

```
public long getPlayStart()
```

setPlayStart

```
public void setPlayStart(long playStart)
```

(continued from last page)

getPlayDuration

```
public long getPlayDuration()
```

setPlayDuration

```
public void setPlayDuration(long playDuration)
```

com.wowza.wms.medialist

Class MediaListSegment

java.lang.Object

└─com.wowza.wms.medialist.MediaListSegment

public class **MediaListSegment**
extends Object

Field Summary

protected	lock
protected	mediaList
protected	properties
protected	renditions

Constructor Summary

public	MediaListSegment()
--------	------------------------------------

Method Summary

void	addRendition (int index, MediaListRendition mediaListRendition)
void	addRendition (MediaListRendition mediaListRendition)
void	clearSegments ()
MediaListRendition	getFirstRendition ()
Object	getLock ()
MediaList	getMediaList ()
WMSProperties	getProperties ()
WMSProperties	getProperties (boolean write)
MediaListRendition	getRendition (int index)
java.util.List	getRenditions ()

MediaListRendition	removeRendition (int index)
void	removeRendition (MediaListRendition mediaListRendition)
void	setLock (Object lock)
void	setMediaList (MediaList mediaList)
String	toSMILString ()
String	toString ()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

lock

protected java.lang.Object **lock**

mediaList

protected com.wowza.wms.medialist.MediaList **mediaList**

renditions

protected java.util.List **renditions**

properties

protected com.wowza.wms.application.WMSProperties **properties**

Constructors

MediaListSegment

public **MediaListSegment**()

Methods

(continued from last page)

toString

```
public String toString()
```

toSMILString

```
public String toSMILString()
```

getRenditions

```
public java.util.List getRenditions()
```

addRendition

```
public void addRendition(MediaListRendition mediaListRendition)
```

addRendition

```
public void addRendition(int index,  
    MediaListRendition mediaListRendition)
```

removeRendition

```
public void removeRendition(MediaListRendition mediaListRendition)
```

removeRendition

```
public MediaListRendition removeRendition(int index)
```

clearSegments

```
public void clearSegments()
```

getFirstRendition

```
public MediaListRendition getFirstRendition()
```

(continued from last page)

getRendition

```
public MediaListRendition getRendition(int index)
```

getLock

```
public Object getLock()
```

setLock

```
public void setLock(Object lock)
```

getMediaList

```
public MediaList getMediaList()
```

setMediaList

```
public void setMediaList(MediaList mediaList)
```

getProperties

```
public WMSProperties getProperties()
```

getProperties

```
public WMSProperties getProperties(boolean write)
```

Package

com.wowza.wms.module

com.wowza.wms.module Interface IModuleCallResult

public interface **IModuleCallResult**
extends

IModuleCallResult: callback interface used by IClient call.

Method Summary

void	<code>onResult(IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params)</code> Triggered on client side result from call to IClient.call
------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

onResult

```
public void onResult(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Triggered on client side result from call to IClient.call

Parameters:

client - client
function - function object
params - result parameters

com.wowza.wms.module Interface IModuleNotify

public interface **IModuleNotify**
extends

IModuleNotify: listener interface for listening to module loading and unloading. See
IApplicationInstance.addModuleListener(IModuleNotify moduleListener)

Method Summary

void	<u>onModuleLoad</u> (ModuleItem item) Called when module loaded
void	<u>onModuleUnload</u> (ModuleItem item) Called when module unloaded

Methods

onModuleLoad

public void **onModuleLoad**(ModuleItem item)

Called when module loaded

Parameters:

item - module

onModuleUnload

public void **onModuleUnload**(ModuleItem item)

Called when module unloaded

Parameters:

item - module

com.wowza.wms.module Interface IModuleOnApp

All Known Implementing Classes:
[ModuleMediaCaster](#)

public interface **IModuleOnApp**
extends

IModuleCallResult: method interface examples for application level methods in a module.

Since module method must be implemented as static method a module cannot directly implements this interface. This interface only serves as an example of the method names and call signature needed to implement these application methods.

Method Summary

void	onAppStart (IApplicationInstance appInstance) Invoked when an application instance is started.
void	onAppStop (IApplicationInstance appInstance) Invoked when an application instance is stopped (destroyed).

Methods

onAppStart

public void **onAppStart**([IApplicationInstance](#) appInstance)

Invoked when an application instance is started.

Parameters:

appInstance - application instance

onAppStop

public void **onAppStop**([IApplicationInstance](#) appInstance)

Invoked when an application instance is stopped (destroyed).

Parameters:

appInstance - application instance

com.wowza.wms.module Interface IModuleOnCall

public interface **IModuleOnCall**
extends

IModuleOnCall: method interface example for the catch-all method handler onCall.

Since module method must be implemented as static method a module cannot directly implements this interface. This interface only serves as an example of the method name and call signature needed to implement this method. The onCall method, when defined in a module, is invoked for all handlers that are undefined in a given module. The onCall handler can also be used to catch calls to server side component calls.

Method Summary

void

[onCall](#)(String handlerName, [IClient](#) client,
com.wowza.wms.request.RequestFunction function, [AMFDataList](#) params)
Catch-all method handler.

Methods

onCall

```
public void onCall(String handlerName,  
    IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Catch-all method handler. The onCall method, when defined in a module, is invoked for all handlers that are undefined in a given module.

Parameters:

handlerName - handler name
client - client
function - function object
params - function parameters

com.wowza.wms.module Interface IModuleOnConnect

public interface **IModuleOnConnect**
extends

IModuleOnConnect: method interface examples for client level methods in a module.

Since module method must be implemented as static method a module cannot directly implements this interface. This interface only serves as an example of the method names and call signature needed to implement these client methods.

Method Summary

void	<u>onConnect</u> (<u>IClient</u> client, com.wowza.wms.request.RequestFunction function, <u>AMFDataList</u> params) Invoked when a client connection is initiated.
void	<u>onConnectAccept</u> (<u>IClient</u> client) Invoked when a client connection is accepted.
void	<u>onConnectReject</u> (<u>IClient</u> client) Invoked when a client connection is rejected.
void	<u>onDisconnect</u> (<u>IClient</u> client) Invoked when a client disconnects.

Methods

onConnect

```
public void onConnect(IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Invoked when a client connection is initiated. It is within this method that module can call to client.acceptConnection or client.rejectConnection.

Parameters:

client - client
function - function object
params - function parameters

onDisconnect

```
public void onDisconnect(IClient client)
```

Invoked when a client disconnects.

Parameters:

client - client

(continued from last page)

onConnectAccept

```
public void onConnectAccept(IClient client)
```

Invoked when a client connection is accepted.

Parameters:

client - client

onConnectReject

```
public void onConnectReject(IClient client)
```

Invoked when a client connection is rejected.

Parameters:

client - client

com.wowza.wms.module Interface IModuleOnHTTPCupertinoEncryption

public interface **IModuleOnHTTPCupertinoEncryption**
extends

IModuleOnHTTPCupertinoEncryption: listener interface for listening to AES-128 encryption events.

Field Summary

public static final	<u>KEYDATA_MODE_ENCRYPT</u> Value: 3
public static final	<u>KEYDATA_MODE_INIT</u> Value: 1
public static final	<u>KEYDATA_MODE_PLAYLIST</u> Value: 2

Method Summary

void	<u>onHTTPCupertinoEncryptionKeyCreateLive</u> (<u>IApplicationInstance</u> appInstance, String streamName, byte[] encKey) Called when live stream key is requested (per-published stream)
void	<u>onHTTPCupertinoEncryptionKeyCreateVOD</u> (<u>HTTPStreamerSessionCupertino</u> httpSession, byte[] encKey) Called when video on demand key is requested (per-session)
void	<u>onHTTPCupertinoEncryptionKeyData</u> (<u>HTTPStreamerSessionCupertino</u> httpSession, <u>IHTTPRequest</u> req, <u>IHTTPResponse</u> resp, byte[] encKeyData) Called when a key data is requested.
void	<u>onHTTPCupertinoEncryptionKeyLiveChunk</u> (<u>ILiveStreamPacketizer</u> liveStreamPacketizer, String streamName, <u>CupertinoEncInfo</u> encInfo, long chunkId, int mode) Called when live stream key is requested (per-published stream, per-chunk - for rotating keys)
void	<u>onHTTPCupertinoEncryptionKeyRequest</u> (<u>HTTPStreamerSessionCupertino</u> httpSession, <u>IHTTPRequest</u> req, <u>IHTTPResponse</u> resp) Called when a key is requested.
void	<u>onHTTPCupertinoEncryptionKeyVODChunk</u> (<u>HTTPStreamerSessionCupertino</u> httpSession, <u>IHTTPStreamerCupertinoIndex</u> index, <u>CupertinoEncInfo</u> encInfo, long chunkId, int mode) Called when video on demand key is requested (per-session).

Fields

(continued from last page)

KEYDATA_MODE_INIT

```
public static final int KEYDATA_MODE_INIT
```

Constant value: **1**

KEYDATA_MODE_PLAYLIST

```
public static final int KEYDATA_MODE_PLAYLIST
```

Constant value: **2**

KEYDATA_MODE_ENCRYPT

```
public static final int KEYDATA_MODE_ENCRYPT
```

Constant value: **3**

Methods

onHTTPCupertinoEncryptionKeyRequest

```
public void onHTTPCupertinoEncryptionKeyRequest(HTTPStreamerSessionCupertino
httpSession,
IHTTPRequest req,
IHTTPResponse resp)
```

Called when a key is requested. Call `httpSession.rejectSession` to reject the streaming session and stop delivery of the encryption key.

Parameters:

`httpSession` - HTTP session
`req` - HTTP request
`resp` - HTTP response

onHTTPCupertinoEncryptionKeyData

```
public void onHTTPCupertinoEncryptionKeyData(HTTPStreamerSessionCupertino httpSession,
IHTTPRequest req,
IHTTPResponse resp,
byte[] encKeyData)
```

Called when a key data is requested. Set `encKeyData` to the key data to be sent to the client.

Parameters:

`httpSession` - HTTP session
`req` - request
`resp` - response
`encKeyData` - key data

onHTTPCupertinoEncryptionKeyCreateVOD

```
public void onHTTPCupertinoEncryptionKeyCreateVOD(HTTPStreamerSessionCupertino
httpSession,
byte[] encKey)
```

(continued from last page)

Called when video on demand key is requested (per-session)

Parameters:

httpSession - HTTP session
encKey - encryption key

onHTTPCupertinoEncryptionKeyVODChunk

```
public void onHTTPCupertinoEncryptionKeyVODChunk(HTTPStreamerSessionCupertino
httpSession,
    IHTTPStreamerCupertinoIndex index,
    CupertinoEncInfo encInfo,
    long chunkId,
    int mode)
```

Called when video on demand key is requested (per-session). Allows setting of encryption key and URL.

Parameters:

httpSession - HTTP session
index - file index
encInfo - encryption key
mode - KEYDATA_MODE_*

onHTTPCupertinoEncryptionKeyCreateLive

```
public void onHTTPCupertinoEncryptionKeyCreateLive(IApplicationInstance appInstance,
    String streamName,
    byte[] encKey)
```

Called when live stream key is requested (per-published stream)

Parameters:

appInstance - application instance
streamName - stream name
encKey - encryption key

onHTTPCupertinoEncryptionKeyLiveChunk

```
public void onHTTPCupertinoEncryptionKeyLiveChunk(ILiveStreamPacketizer
liveStreamPacketizer,
    String streamName,
    CupertinoEncInfo encInfo,
    long chunkId,
    int mode)
```

Called when live stream key is requested (per-published stream, per-chunk - for rotating keys)

Parameters:

liveStreamPacketizer - live stream packetizer
streamName - stream name
encInfo - encryption info
chunkId - chunk ID, -1 for stream creation
mode - KEYDATA_MODE_*

com.wowza.wms.module

Interface IModuleOnHTTPCupertinoStreamingSession

public interface **IModuleOnHTTPCupertinoStreamingSession**
extends

IModuleOnHTTPSession: method interface for HTTP Cupertino Streaming session create/destroy.

Method Summary

void	onHTTPCupertinoStreamingSessionCreate (HTTPStreamerSessionCupertino httpCupertinoStreamingSession) Invoked when an HTTP Cupertino Streaming session is created.
void	onHTTPCupertinoStreamingSessionDestroy (HTTPStreamerSessionCupertino httpCupertinoStreamingSession) Invoked when an HTTP Cupertino Streaming session is destroyed.

Methods

onHTTPCupertinoStreamingSessionCreate

public void **onHTTPCupertinoStreamingSessionCreate**([HTTPStreamerSessionCupertino](#) [httpCupertinoStreamingSession](#))

Invoked when an HTTP Cupertino Streaming session is created.

Parameters:

[httpCupertinoStreamingSession](#) - [httpCupertinoStreamingSession](#)

onHTTPCupertinoStreamingSessionDestroy

public void **onHTTPCupertinoStreamingSessionDestroy**([HTTPStreamerSessionCupertino](#) [httpCupertinoStreamingSession](#))

Invoked when an HTTP Cupertino Streaming session is destroyed.

Parameters:

[httpCupertinoStreamingSession](#) - [httpCupertinoStreamingSession](#)

com.wowza.wms.module

Interface IModuleOnHTTPSanJoseStreamingSession

public interface IModuleOnHTTPSanJoseStreamingSession
extends

IModuleOnHTTPSanJoseStreamingSession: method interface for HTTP SanJose Streaming session create/destroy.

Method Summary	
void	onHTTPSanJoseStreamingSessionCreate(HTTPStreamerSessionSanJose httpSanJoseStreamingSession) Invoked when an HTTP SanJose Streaming session is created.
void	onHTTPSanJoseStreamingSessionDestroy(HTTPStreamerSessionSanJose httpSanJoseStreamingSession) Invoked when an HTTP SanJose Streaming session is destroyed.

Methods

onHTTPSanJoseStreamingSessionCreate

public void **onHTTPSanJoseStreamingSessionCreate**([HTTPStreamerSessionSanJose httpSanJoseStreamingSession](#))

Invoked when an HTTP SanJose Streaming session is created.

Parameters:

`httpSanJoseStreamingSession` - httpSanJoseStreamingSession

onHTTPSanJoseStreamingSessionDestroy

public void **onHTTPSanJoseStreamingSessionDestroy**([HTTPStreamerSessionSanJose httpSanJoseStreamingSession](#))

Invoked when an HTTP SanJose Streaming session is destroyed.

Parameters:

`httpSanJoseStreamingSession` - httpSanJoseStreamingSession

com.wowza.wms.module Interface IModuleOnHTTPSession

public interface **IModuleOnHTTPSession**
extends

IModuleOnHTTPSession: method interface for HTTP Streaming session create/destroy.

Method Summary

void	onHTTPSessionCreate (IHTTPStreamerSession httpSession) Invoked when an HTTP Session is created (both Smooth and Cupertino sessions).
void	onHTTPSessionDestroy (IHTTPStreamerSession httpSession) Invoked when an HTTP Session is destroyed (both Smooth and Cupertino sessions).

Methods

onHTTPSessionCreate

public void **onHTTPSessionCreate**([IHTTPStreamerSession](#) httpSession)

Invoked when an HTTP Session is created (both Smooth and Cupertino sessions).

Parameters:

httpSession - httpSession

onHTTPSessionDestroy

public void **onHTTPSessionDestroy**([IHTTPStreamerSession](#) httpSession)

Invoked when an HTTP Session is destroyed (both Smooth and Cupertino sessions).

Parameters:

httpSession - httpSession

com.wowza.wms.module

Interface IModuleOnHTTPSmoothStreamingPlayReady

public interface **IModuleOnHTTPSmoothStreamingPlayReady**
extends

IModuleOnHTTPSmoothStreamingPlayReady: Still working on this...

Method Summary

void	onHTTPSmoothStreamingPlayReadyCreateLive (IApplicationInstance appInstance, String streamName, com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)
void	onHTTPSmoothStreamingPlayReadyCreateVOD (HTTPStreamerSessionSmoothStreamer httpSession, com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)

Methods

onHTTPSmoothStreamingPlayReadyCreateVOD

```
public void onHTTPSmoothStreamingPlayReadyCreateVOD(HTTPStreamerSessionSmoothStreamer
httpSession,
    com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)
```

onHTTPSmoothStreamingPlayReadyCreateLive

```
public void onHTTPSmoothStreamingPlayReadyCreateLive(IApplicationInstance appInstance,
    String streamName,
    com.wowza.wms.drm.playready.PlayReadyKeyInfo playReadyKeyInfo)
```

com.wowza.wms.module

Interface IModuleOnHTTPSmoothStreamingSession

public interface IModuleOnHTTPSmoothStreamingSession
extends

IModuleOnHTTPSession: method interface for HTTP Smooth Streaming session create/destroy.

Method Summary	
void	onHTTPSmoothStreamingSessionCreate (HTTPStreamerSessionSmoothStreamer httpSmoothStreamingSession) Invoked when an HTTP Smooth Streaming session is created.
void	onHTTPSmoothStreamingSessionDestroy (HTTPStreamerSessionSmoothStreamer httpSmoothStreamingSession) Invoked when an HTTP Smooth Streaming session is destroyed.

Methods

onHTTPSmoothStreamingSessionCreate

public void **onHTTPSmoothStreamingSessionCreate**([HTTPStreamerSessionSmoothStreamer](#) [httpSmoothStreamingSession](#))

Invoked when an HTTP Smooth Streaming session is created.

Parameters:

[httpSmoothStreamingSession](#) - [httpSmoothStreamingSession](#)

onHTTPSmoothStreamingSessionDestroy

public void **onHTTPSmoothStreamingSessionDestroy**([HTTPStreamerSessionSmoothStreamer](#) [httpSmoothStreamingSession](#))

Invoked when an HTTP Smooth Streaming session is destroyed.

Parameters:

[httpSmoothStreamingSession](#) - [httpSmoothStreamingSession](#)

com.wowza.wms.module Interface IModuleOnRTPSession

public interface **IModuleOnRTPSession**
extends

IModuleOnRTPSession: method interface for RTP session create/destroy.

Method Summary

void	onRTPSessionCreate(RTPSession rtpSession) Invoked when an RTP Session is created.
void	onRTPSessionDestroy(RTPSession rtpSession) Invoked when an RTP Session is destroyed.

Methods

onRTPSessionCreate

public void **onRTPSessionCreate**([RTPSession](#) rtpSession)

Invoked when an RTP Session is created.

Parameters:

rtpSession - rtpSession

onRTPSessionDestroy

public void **onRTPSessionDestroy**([RTPSession](#) rtpSession)

Invoked when an RTP Session is destroyed.

Parameters:

rtpSession - rtpSession

com.wowza.wms.module Interface IModuleOnStream

public interface **IModuleOnStream**
extends

IModuleOnStream: method interface examples for stream level methods in a module.

Method Summary

void	onStreamCreate (IMediaStream stream) Invoked when a stream is created.
void	onStreamDestroy (IMediaStream stream) Invoked when a stream is destroyed.

Methods

onStreamCreate

public void **onStreamCreate**([IMediaStream](#) stream)

Invoked when a stream is created.

Parameters:

stream - stream object

onStreamDestroy

public void **onStreamDestroy**([IMediaStream](#) stream)

Invoked when a stream is destroyed.

Parameters:

stream - stream object

com.wowza.wms.module Interface IModulePingResult

public interface **IModulePingResult**
extends

IModulePingResult: callback interface used by IClient ping.

Method Summary

void	onResult (IClient client, long pingTime, int pingId, boolean result) Triggered on client side result from call to IClient.ping.
------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

onResult

```
public void onResult(IClient client,  
                    long pingTime,  
                    int pingId,  
                    boolean result)
```

Triggered on client side result from call to IClient.ping. This method will be called on a success or failure (ping timeout) of a ping.

Parameters:

client - client
pingTime - time in server time (milliseconds) when the ping was initiated
pingId - internal server id for the ping request
result - true is ping was successful false if failure (timeout)

com.wowza.wms.module Class ModuleBase

java.lang.Object

└-com.wowza.wms.module.ModuleBase

Direct Known Subclasses:

[ModuleProperties](#), [ModuleMediaCasterStreamMonitorAdvanced](#), [ModuleFastPlay](#), [ModuleCore](#), [ModuleClientLogging](#), [ModuleMediaCaster](#)

public abstract class **ModuleBase**
extends Object

ModuleBase: Base class that all server side modules should extend. Provides basic utility functionality for handling function parameters and return data. Also provides a simplified API for logging.

Field Summary

public static final	CALLBACK_PARAM1 Callback param: param1 Value: 1
public static final	CALLBACK_PARAM10 Callback param: param10 Value: 10
public static final	CALLBACK_PARAM2 Callback param: param2 Value: 2
public static final	CALLBACK_PARAM3 Callback param: param3 Value: 3
public static final	CALLBACK_PARAM4 Callback param: param4 Value: 4
public static final	CALLBACK_PARAM5 Callback param: param5 Value: 5
public static final	CALLBACK_PARAM6 Callback param: param6 Value: 6
public static final	CALLBACK_PARAM7 Callback param: param7 Value: 7

public static final	CALLBACK_PARAM8 Callback param: param8 Value: 8
public static final	CALLBACK_PARAM9 Callback param: param9 Value: 9
public static final	PARAM1 Method param: param1 Value: 3
public static final	PARAM10 Method param: param10 Value: 12
public static final	PARAM2 Method param: param2 Value: 4
public static final	PARAM3 Method param: param3 Value: 5
public static final	PARAM4 Method param: param4 Value: 6
public static final	PARAM5 Method param: param5 Value: 7
public static final	PARAM6 Method param: param6 Value: 8
public static final	PARAM7 Method param: param7 Value: 9
public static final	PARAM8 Method param: param8 Value: 10
public static final	PARAM9 Method param: param9 Value: 11
public static final	PARAMMETHODNAME Method: method name Value: 0
public static final	PLAYTRANSITION_APPEND Value: 0

public static final	<u>PLAYTRANSITION_APPEND_IMMEDIATE</u> Value: 2
public static final	<u>PLAYTRANSITION_RESET</u> Value: 1
public static final	<u>PLAYTRANSITION_RESET_IMMEDIATE</u> Value: 3
public static final	<u>PLAYTRANSITION_STOP</u> Value: 10
public static final	<u>PLAYTRANSITION_SWAP</u> Value: 12
public static final	<u>PLAYTRANSITION_SWITCH</u> Value: 13
public static final	<u>PLAYTRANSITION_UNKNOWN</u> Value: 14
public static final	<u>PLAYTRANSITIONSTR_APPEND</u> Play2 transition: APPEND Value: append
public static final	<u>PLAYTRANSITIONSTR_RESET</u> Play2 transition: RESET Value: reset
public static final	<u>PLAYTRANSITIONSTR_STOP</u> Play2 transition: STOP Value: stop
public static final	<u>PLAYTRANSITIONSTR_SWAP</u> Play2 transition: SWAP Value: swap
public static final	<u>PLAYTRANSITIONSTR_SWITCH</u> Play2 transition: SWITCH Value: switch
public static final	<u>PLAYTRANSITIONSTR_UNKNOWN</u> Play2 transition: UNKNOWN Value: unknown

Constructor Summary

public	<u>ModuleBase</u> ()
--------	---------------------------------------

Method Summary

static IApplicationInstance	getAppInstance (IClient client) Get applicationInstace of a client.
static IApplication	getApplication (IClient client) Get application of a client.
static int	getCallbackParamCount (AMFDataList params) Get the total number of parameters passed to callback.
static WMSLogger	getLogger () Get the logging interface.
static AMFData	getParam (AMFDataList params, int index) Get parameter by index.
static boolean	getParamBoolean (AMFDataList params, int index) Get parameter by index, Return as boolean.
static boolean	getParamBoolean (AMFDataList params, int index, boolean defaultVal) Get parameter by index, Return as boolean.
static int	getParamCount (AMFDataList params) Get the total number of parameters passed to method.
static java.util.Date	getParamDate (AMFDataList params, int index) Get parameter by index, Return as Date.
static double	getParamDouble (AMFDataList params, int index) Get parameter by index, Return as double.
static double	getParamDouble (AMFDataList params, int index, double defaultVal) Get parameter by index, Return as double.
static int	getParamInt (AMFDataList params, int index) Get parameter by index, Return as int.
static int	getParamInt (AMFDataList params, int index, int defaultVal) Get parameter by index, Return as int.
static long	getParamLong (AMFDataList params, int index) Get parameter by index, Return as long.
static long	getParamLong (AMFDataList params, int index, long defaultVal) Get parameter by index, Return as long.
static AMFDataMixedArray	getParamMixedArray (AMFDataList params, int index) Get parameter by index, Return as AMFDataMixedArray.
static AMFDataObj	getParamObj (AMFDataList params, int index) Get parameter by index, Return as Object.
static String	getParamString (AMFDataList params, int index) Get parameter by index, Return as String.
static String	getParamString (AMFDataList params, int index, String defaultVal) Get parameter by index, Return as String.
static int	getParamType (AMFDataList params, int index) Get parameter type.

static IMediaStream	getStream (IClient client, com.wowza.wms.request.RequestFunction function) For methods called from the client side object NetStream (publish, play, deleteStream) get the IMediaStream object associated with the call.
static IVHost	getVHost (IClient client) Get vHost of a client.
void	invokePrevious (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Wowza Pro will determine command priority based on the order of the modules in the module list.
static void	invokePrevious (Object instance, IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Wowza Pro will determine command priority based on the order of the modules in the module list.
static boolean	isSendResult (AMFDataList params) Is this method call expecting sendResult to be called.
static void	sendClientOnStatusError (IClient client, String code, String description) Send an error message to the client-side client.onStatus handler
static boolean	sendResult (IClient client, AMFDataList params, AMFData data) Send a result to client method call as a AMFData object.
static boolean	sendResult (IClient client, AMFDataList params, boolean value) Send a result to client method call as a single boolean value.
static boolean	sendResult (IClient client, AMFDataList params, double value) Send a result to client method call as a single double value.
static boolean	sendResult (IClient client, AMFDataList params, int value) Send a result to client method call as a single int value.
static boolean	sendResult (IClient client, AMFDataList params, String value) Send a result to client method call as a single String value.
static void	sendStreamOnStatusError (IMediaStream stream, String code, String description) Send an error to the client-side NetStream.onStatus handler

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

PARAMMETHODNAME

public static final int **PARAMMETHODNAME**

Method: method name
Constant value: 0

(continued from last page)

PARAM1

```
public static final int PARAM1
```

Method param: param1
Constant value: **3**

PARAM2

```
public static final int PARAM2
```

Method param: param2
Constant value: **4**

PARAM3

```
public static final int PARAM3
```

Method param: param3
Constant value: **5**

PARAM4

```
public static final int PARAM4
```

Method param: param4
Constant value: **6**

PARAM5

```
public static final int PARAM5
```

Method param: param5
Constant value: **7**

PARAM6

```
public static final int PARAM6
```

Method param: param6
Constant value: **8**

PARAM7

```
public static final int PARAM7
```

Method param: param7
Constant value: **9**

PARAM8

```
public static final int PARAM8
```

Method param: param8
Constant value: **10**

PARAM9

```
public static final int PARAM9
```

(continued from last page)

Method param: param9
Constant value: **11**

PARAM10

public static final int **PARAM10**

Method param: param10
Constant value: **12**

CALLBACK_PARAM1

public static final int **CALLBACK_PARAM1**

Callback param: param1
Constant value: **1**

CALLBACK_PARAM2

public static final int **CALLBACK_PARAM2**

Callback param: param2
Constant value: **2**

CALLBACK_PARAM3

public static final int **CALLBACK_PARAM3**

Callback param: param3
Constant value: **3**

CALLBACK_PARAM4

public static final int **CALLBACK_PARAM4**

Callback param: param4
Constant value: **4**

CALLBACK_PARAM5

public static final int **CALLBACK_PARAM5**

Callback param: param5
Constant value: **5**

CALLBACK_PARAM6

public static final int **CALLBACK_PARAM6**

Callback param: param6
Constant value: **6**

CALLBACK_PARAM7

public static final int **CALLBACK_PARAM7**

Callback param: param7
Constant value: **7**

CALLBACK_PARAM8

```
public static final int CALLBACK_PARAM8
```

Callback param: param8
Constant value: **8**

CALLBACK_PARAM9

```
public static final int CALLBACK_PARAM9
```

Callback param: param9
Constant value: **9**

CALLBACK_PARAM10

```
public static final int CALLBACK_PARAM10
```

Callback param: param10
Constant value: **10**

PLAYTRANSITIONSTR_APPEND

```
public static final java.lang.String PLAYTRANSITIONSTR_APPEND
```

Play2 transition: APPEND
Constant value: **append**

PLAYTRANSITIONSTR_RESET

```
public static final java.lang.String PLAYTRANSITIONSTR_RESET
```

Play2 transition: RESET
Constant value: **reset**

PLAYTRANSITIONSTR_STOP

```
public static final java.lang.String PLAYTRANSITIONSTR_STOP
```

Play2 transition: STOP
Constant value: **stop**

PLAYTRANSITIONSTR_SWAP

```
public static final java.lang.String PLAYTRANSITIONSTR_SWAP
```

Play2 transition: SWAP
Constant value: **swap**

PLAYTRANSITIONSTR_SWITCH

```
public static final java.lang.String PLAYTRANSITIONSTR_SWITCH
```

Play2 transition: SWITCH
Constant value: **switch**

(continued from last page)

PLAYTRANSITIONSTR_UNKNOWN

```
public static final java.lang.String PLAYTRANSITIONSTR_UNKNOWN
```

Play2 transition: UNKNOWN
Constant value: **unknown**

PLAYTRANSITION_APPEND

```
public static final int PLAYTRANSITION_APPEND
```

Constant value: **0**

PLAYTRANSITION_RESET

```
public static final int PLAYTRANSITION_RESET
```

Constant value: **1**

PLAYTRANSITION_APPEND_IMMEDIATE

```
public static final int PLAYTRANSITION_APPEND_IMMEDIATE
```

Constant value: **2**

PLAYTRANSITION_RESET_IMMEDIATE

```
public static final int PLAYTRANSITION_RESET_IMMEDIATE
```

Constant value: **3**

PLAYTRANSITION_STOP

```
public static final int PLAYTRANSITION_STOP
```

Constant value: **10**

PLAYTRANSITION_SWAP

```
public static final int PLAYTRANSITION_SWAP
```

Constant value: **12**

PLAYTRANSITION_SWITCH

```
public static final int PLAYTRANSITION_SWITCH
```

Constant value: **13**

PLAYTRANSITION_UNKNOWN

```
public static final int PLAYTRANSITION_UNKNOWN
```

(continued from last page)

Constant value: **14**

Constructors

ModuleBase

```
public ModuleBase( )
```

Methods

getParamCount

```
protected static int getParamCount(AMFDataList params)
```

Get the total number of parameters passed to method.

Parameters:

params - parameters

Returns:

total number of parameters

getCallbackParamCount

```
protected static int getCallbackParamCount(AMFDataList params)
```

Get the total number of parameters passed to callback.

Parameters:

params - parameters

Returns:

total number of parameters

getParamType

```
protected static int getParamType(AMFDataList params,  
int index)
```

Get parameter type.

Parameters:

params - parameters

index - parameter index

Returns:

parameter type (AMFData.DATA_TYPE_*)

getParam

```
protected static AMFData getParam(AMFDataList params,  
int index)
```

Get parameter by index. Return as AMFData object.

(continued from last page)

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as AMFData object, null if out of bounds

getParamMixedArray

```
protected static AMFDataMixedArray getParamMixedArray(AMFDataList params,  
int index)
```

Get parameter by index, Return as AMFDataMixedArray.

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as AMFDataMixedArray object, null if out of bounds

getParamObj

```
protected static AMFDataObj getParamObj(AMFDataList params,  
int index)
```

Get parameter by index, Return as Object.

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as Object object, null if out of bounds

getParamString

```
protected static String getParamString(AMFDataList params,  
int index)
```

Get parameter by index, Return as String.

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as String object, null if out of bounds

getParamString

```
protected static String getParamString(AMFDataList params,  
int index,  
String defaultVal)
```

Get parameter by index, Return as String.

Parameters:

params - parameters

(continued from last page)

index - parameter index
defaultVal - default value

Returns:

parameter value as String object, defaultVal if out of bounds

getParamDate

```
protected static java.util.Date getParamDate(AMFDataList params,  
int index)
```

Get parameter by index, Return as Date.

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as Date object, null if out of bounds

getParamInt

```
protected static int getParamInt(AMFDataList params,  
int index)
```

Get parameter by index, Return as int.

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as int, 0 if out of bounds

getParamInt

```
protected static int getParamInt(AMFDataList params,  
int index,  
int defaultVal)
```

Get parameter by index, Return as int.

Parameters:

params - parameters
index - parameter index
defaultVal - default value

Returns:

parameter value as int, defaultVal if out of bounds

getParamDouble

```
protected static double getParamDouble(AMFDataList params,  
int index)
```

Get parameter by index, Return as double.

Parameters:

params - parameters

(continued from last page)

index - parameter index

Returns:

parameter value as double, 0 if out of bounds

getParamDouble

```
protected static double getParamDouble(AMFDataList params,  
    int index,  
    double defaultVal)
```

Get parameter by index, Return as double.

Parameters:

params - parameters
index - parameter index
defaultVal - default value

Returns:

parameter value as double, 0 if out of bounds

getParamLong

```
protected static long getParamLong(AMFDataList params,  
    int index)
```

Get parameter by index, Return as long.

Parameters:

params - parameters
index - parameter index

Returns:

parameter value as long, 0 if out of bounds

getParamLong

```
protected static long getParamLong(AMFDataList params,  
    int index,  
    long defaultVal)
```

Get parameter by index, Return as long.

Parameters:

params - parameters
index - parameter index
defaultVal - default value

Returns:

parameter value as long, defaultVal if out of bounds

getParamBoolean

```
protected static boolean getParamBoolean(AMFDataList params,  
    int index)
```

Get parameter by index, Return as boolean.

Parameters:

params - parameters

(continued from last page)

index - parameter index

Returns:

parameter value as boolean, false if out of bounds

getParamBoolean

```
protected static boolean getParamBoolean(AMFDataList params,  
int index,  
boolean defaultVal)
```

Get parameter by index, Return as boolean.

Parameters:

params - parameters
index - parameter index
defaultVal - default value

Returns:

parameter value as boolean, defaultVal if out of bounds

getAppInstance

```
protected static IApplicationInstance getAppInstance(IClient client)
```

Get applicationInstance of a client.

Parameters:

client - client

Returns:

applicationInstance

getApplication

```
protected static IApplication getApplication(IClient client)
```

Get application of a client.

Parameters:

client - client

Returns:

application

isSendResult

```
protected static boolean isSendResult(AMFDataList params)
```

Is this method call expecting sendResult to be called. If on the client side the call to `NetConnection.call("handlerName", resultObj, param1...);` had a value for resultObj (non-null), then the method is expecting some type of result or return data. Calling a variant of sendResult will provide this callback.

Parameters:

params - parameters

Returns:

true if client side call is expecting call to sendResult

getVHost

protected static [IVHost](#) **getVHost**([IClient](#) client)

Get vHost of a client.

Parameters:

client - client

Returns:

vHost

sendResult

protected static boolean **sendResult**([IClient](#) client,
[AMFDataList](#) params,
String value)

Send a result to client method call as a single String value.

Parameters:

client - client

params - parameters

value - return value

Returns:

true if client side call is expecting call to sendResult

sendResult

protected static boolean **sendResult**([IClient](#) client,
[AMFDataList](#) params,
boolean value)

Send a result to client method call as a single boolean value.

Parameters:

client - client

params - parameters

value - return value

Returns:

true if client side call is expecting call to sendResult

sendResult

protected static boolean **sendResult**([IClient](#) client,
[AMFDataList](#) params,
int value)

Send a result to client method call as a single int value.

Parameters:

client - client

params - parameters

value - return value

Returns:

true if client side call is expecting call to sendResult

sendResult

```
protected static boolean sendResult(IClient client,  
    AMFDataList params,  
    double value)
```

Send a result to client method call as a single double value.

Parameters:

client - client
params - parameters
value - return value

Returns:

true if client side call is expecting call to sendResult

sendResult

```
protected static boolean sendResult(IClient client,  
    AMFDataList params,  
    AMFData data)
```

Send a result to client method call as a AMFData object. This can be a single AMFData value like new AMFDataItem((double)1.234) or a complex type like AMFDataMixedArray, AMFDataArray or AMFDataObj.

Parameters:

client - client
params - parameters
data - return value

Returns:

true if client side call is expecting call to sendResult

getLogger

```
protected static WMSLogger getLogger()
```

Get the logging interface.

See Also:

[WMSLogger](#)

getStream

```
protected static IMediaStream getStream(IClient client,  
    com.wowza.wms.request.RequestFunction function)
```

For methods called from the client side object NetStream (publish, play, deleteStream) get the IMediaStream object associated with the call.

Parameters:

client - client
function - functions

Returns:

media stream

(continued from last page)

invokePrevious

```
protected static void invokePrevious(Object instance,
    IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Wowza Pro will determine command priority based on the order of the modules in the module list. Wowza Pro by default will only invoke the last module that defines a given command. This method enables you to call the method by the same name in the previous module that defines that command. For example if you have three modules defined in the module list; ModuleCore, ModuleSecureURLParams and ModuleMyModule and all three modules implement the "play" command. When "play" is invoked it will invoke the "play" command in ModuleMyModule. If in ModuleMyModule you would like to call the "play" command in ModuleSecureURLParams, you can call: invokePrevious(this, client, function, params); and it will invoke the "play" command defined in ModuleSecureURLParams.

Parameters:

instance - instance of the current module
 client - client object passed into command
 function - function passed into command
 params - parameters passed into command

invokePrevious

```
protected void invokePrevious(IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Wowza Pro will determine command priority based on the order of the modules in the module list. Wowza Pro by default will only invoke the last module that defines a given command. This method enables you to call the method by the same name in the previous module that defines that command. For example if you have three modules defined in the module list; ModuleCore, ModuleSecureURLParams and ModuleMyModule and all three modules implement the "play" command. When "play" is invoked it will invoke the "play" command in ModuleMyModule. If in ModuleMyModule you would like to call the "play" command in ModuleSecureURLParams, you can call: this.invokePrevious(client, function, params); and it will invoke the "play" command defined in ModuleSecureURLParams.

Parameters:

client - client object passed into command
 function - function passed into command
 params - parameters passed into command

sendClientOnStatusError

```
protected static void sendClientOnStatusError(IClient client,
    String code,
    String description)
```

Send an error message to the client-side client.onStatus handler

Parameters:

client - destination client
 code - code
 description - description

sendStreamOnStatusError

```
protected static void sendStreamOnStatusError(IMediaStream stream,
    String code,
    String description)
```

Send an error to the client-side NetStream.onStatus handler


Parameters:

(continued from last page)

stream - destination stream
code - code
description - description

com.wowza.wms.module Class ModuleClientLogging

java.lang.Object



public class **ModuleClientLogging**
extends [ModuleBase](#)

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK_PARAM1](#), [CALLBACK_PARAM10](#), [CALLBACK_PARAM2](#), [CALLBACK_PARAM3](#), [CALLBACK_PARAM4](#), [CALLBACK_PARAM5](#), [CALLBACK_PARAM6](#), [CALLBACK_PARAM7](#), [CALLBACK_PARAM8](#), [CALLBACK_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION_APPEND](#), [PLAYTRANSITION_APPEND_IMMEDIATE](#), [PLAYTRANSITION_RESET](#), [PLAYTRANSITION_RESET_IMMEDIATE](#), [PLAYTRANSITION_STOP](#), [PLAYTRANSITION_SWAP](#), [PLAYTRANSITION_SWITCH](#), [PLAYTRANSITION_UNKNOWN](#), [PLAYTRANSITIONSTR_APPEND](#), [PLAYTRANSITIONSTR_RESET](#), [PLAYTRANSITIONSTR_STOP](#), [PLAYTRANSITIONSTR_SWAP](#), [PLAYTRANSITIONSTR_SWITCH](#), [PLAYTRANSITIONSTR_UNKNOWN](#)

Constructor Summary

public	ModuleClientLogging()
--------	---------------------------------------

Method Summary

static void	logDebug (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Send a debug message to the logging system NetConnection.call("logDebug", null, message);
static void	logError (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Send a error message to the logging system NetConnection.call("logError", null, message);
static void	logInfo (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Send a info message to the logging system NetConnection.call("logInfo", null, message);
static void	logWarn (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Send a warning message to the logging system NetConnection.call("logWarn", null, message);

Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

ModuleClientLogging

```
public ModuleClientLogging()
```

Methods

logDebug

```
public static void logDebug(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a debug message to the logging system `NetConnection.call("logDebug", null, message);`

Parameters:

`client` - client
`function` - function
`params` - params (message)

logInfo

```
public static void logInfo(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a info message to the logging system `NetConnection.call("logInfo", null, message);`

Parameters:

`client` - client
`function` - function
`params` - params (message)

logWarn

```
public static void logWarn(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a warning message to the logging system `NetConnection.call("logWarn", null, message);`

Parameters:

`client` - client
`function` - function
`params` - params (message)

(continued from last page)

logError

```
public static void logError(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Send a error message to the logging system `NetConnection.call("logError", null, message);`

Parameters:

client - client

function - function

params - params (message)

com.wowza.wms.module Class ModuleCore

```
java.lang.Object
|
+-com.wowza.wms.module.ModuleBase
|
+-com.wowza.wms.module.ModuleCore
```

```
public class ModuleCore
extends ModuleBase
```

ModuleCore includes all the basic commands support by the NetStream and NetConnection client side objects. Any of these methods can be overwritten in a custom module. Below is an example of custom module that overrides the play method to modify the name of the file to be played:

```
package com.wowza.wms.plugin.overrideexample;

import com.wowza.wms.amf.*;
import com.wowza.wms.client.*;
import com.wowza.wms.module.*;
import com.wowza.wms.request.*;

public class ModuleOverrideExample extends ModuleBase
{
    public void play(IClient client, RequestFunction function, AMFDataList params)
    {
        if (params.get(PARAM1).getType() == AMFData.DATA_TYPE_STRING)
        {
            String playName = params.getString(PARAM1);
            params.set(PARAM1, new AMFDataItem(playName+"_newname"));
        }
        this.invokePrevious(client, function, params);
    }
}
```

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK_PARAM1](#), [CALLBACK_PARAM10](#), [CALLBACK_PARAM2](#), [CALLBACK_PARAM3](#), [CALLBACK_PARAM4](#), [CALLBACK_PARAM5](#), [CALLBACK_PARAM6](#), [CALLBACK_PARAM7](#), [CALLBACK_PARAM8](#), [CALLBACK_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION_APPEND](#), [PLAYTRANSITION_APPEND_IMMEDIATE](#), [PLAYTRANSITION_RESET](#), [PLAYTRANSITION_RESET_IMMEDIATE](#), [PLAYTRANSITION_STOP](#), [PLAYTRANSITION_SWAP](#), [PLAYTRANSITION_SWITCH](#), [PLAYTRANSITION_UNKNOWN](#), [PLAYTRANSITIONSTR_APPEND](#), [PLAYTRANSITIONSTR_RESET](#), [PLAYTRANSITIONSTR_STOP](#), [PLAYTRANSITIONSTR_SWAP](#), [PLAYTRANSITIONSTR_SWITCH](#), [PLAYTRANSITIONSTR_UNKNOWN](#)

Constructor Summary

public	ModuleCore()
--------	------------------------------

Method Summary

static void	closeStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.close();
static void	createStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Create new server side NetStream object (internal to Flash workings).
static void	deleteStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Delete server side stream object (internal to Flash workings).
static void	FCPublish (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) FCPublish method called by FME 2.5
static void	FCSubscribe (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) FCSubscribe subscribes to a live stream (if origin edge will start the stream from the origin to the edge)
static void	FCUnpublish (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params)
static void	FCUnPublish (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) FCUnpublish method called by FME 2.5
static void	FCUnsubscribe (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) FCUnSubscribe to a live stream
static void	FCUnSubscribe (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params)
static void	getClientID (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the clientId for a client connection NetConnection.call("getClientID", resultObj);
static void	getLastStreamId (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the id for the last created stream NetConnection.call("getLastStreamId", resultObj);
static void	getLiveStreamPacketizer (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the live stream packetizer list for a client connection NetConnection.call("getLiveStreamPacketizer", resultObj);
static void	getPageUrl (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) getPageUrl returns the pageUrl from the onConnect metadata
static void	getReferrer (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) getReferrer returns the referrer from the onConnect metadata

static void	getRepeaterOriginUrl (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the Repeater Origin URL for this client
void	getStreamBitrate (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get stream bitrate in bits-per-second for a video on demand stream (will not work for live).
static void	getStreamLength (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get stream length in seconds NetConnection.call("getStreamLength", resultObj, streamName); If you pass in an array of streamNames it will return an array of durations.
static void	getStreamType (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the default stream type for a client connection NetConnection.call("getStreamType", resultObj);
static void	getVersion (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get the Wowza Pro server version and build number NetConnection.call("getVersion", resultObj);
static void	initLiveStreamRepeating (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Initialize a stream for live stream repeating
static void	initStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Create new server side NetStream object (internal to Flash workings).
static void	pause (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.pause([flag : Boolean]);
static void	pauseRaw (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) pauseRaw method introduced in Flash player 10
static void	play (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.play(name : Object [,start : Number[, len : Number[, reset : Object]]]);
static void	play2 (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.play(playOptions : NetStreamPlayOptions);
static void	publish (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.publish(name : String [, howToPublish : String]);
static void	receiveAudio (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.receiveAudio(receive : Boolean);
static void	receiveVideo (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.receiveVideo(receive : Boolean FPS : Number); FPS does not work the same as FMS.
static void	releaseStream (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params)

static void	seek (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.seek(offset : Number);
static void	setBandwidthLimit (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params)
static void	setBufferTime (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Server side implementation of NetStream.setBufferTime(bufferTime : Number);
static void	setLiveStreamPacketizer (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set the live stream packetizer for a stream
static void	setRepeaterOriginUrl (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set the Repeater Origin URL for this client
static void	setStreamType (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set the default stream type for a client connection NetConnection.call("setStreamType", null, streamType);

Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

ModuleCore

```
public ModuleCore()
```

Methods

createStream

```
public static void createStream(IClient client,
    com.wowza.wms.request.RequestFunction function,
    AMFDataList params)
```

Create new server side NetStream object (internal to Flash workings).

Parameters:

(continued from last page)

client - client
function - function
params - parameters (no params)

initStream

```
public static void initStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Create new server side NetStream object (internal to Flash workings).

Parameters:

client - client
function - function
params - parameters (streamIndex, boolean)

releaseStream

```
public static void releaseStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

getLastStreamId

```
public static void getLastStreamId(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the id for the last created stream NetConnection.call("getLastStreamId", resultObj);

Parameters:

client - client
function - client
params - params (no params)

deleteStream

```
public static void deleteStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Delete server side stream object (internal to Flash workings).

Parameters:

client - client
function - function
params - params

publish

```
public static void publish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.publish(name : String [, howToPublish : String]);

Parameters:

(continued from last page)

client - client
function - function
params - params (name [if name = "false" or "null" stop publishing], howToPublish ["record", "live", "append"])

setBandwidthLimit

```
public static void setBandwidthLimit(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

play2

```
public static void play2(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.play(playOptions : NetStreamPlayOptions);

Parameters:

client
function
params

play

```
public static void play(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.play(name : Object [,start : Number[, len : Number[, reset : Object]]]);

Parameters:

client - client
function - function
params - params (name, start, len, reset)

closeStream

```
public static void closeStream(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.close();

Parameters:

client - client
function - function
params - params (no params)

seek

```
public static void seek(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.seek(offset : Number);

Parameters:

(continued from last page)

client - client
function - function
params - params (offset)

pause

```
public static void pause(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.pause([flag : Boolean]);

Parameters:

client - client
function - function
params - params (flag)

setBufferTime

```
public static void setBufferTime(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.setBufferTime(bufferTime : Number);

Parameters:

client - client
function - function
params - params (bufferTime)

getClientID

```
public static void getClientID(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the clientId for a client connection NetConnection.call("getClientID", resultObj);

Parameters:

client - client
function - function
params - params (no params)

getVersion

```
public static void getVersion(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the Wowza Pro server version and build number NetConnection.call("getVersion", resultObj);

Parameters:

client - client
function - function
params - params (no params)

(continued from last page)

setLiveStreamPacketizer

```
public static void setLiveStreamPacketizer(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set the live stream packetizer for a stream

Parameters:

client - client
function - function
params - params (liveStreamPacketizer)

initLiveStreamRepeating

```
public static void initLiveStreamRepeating(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Initialize a stream for live stream repeating

Parameters:

client - client
function - function
params - params (liveStreamPacketizer, liveStreamRepeater)

getLiveStreamPacketizer

```
public static void getLiveStreamPacketizer(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the live stream packetizer list for a client connection `NetConnection.call("getLiveStreamPacketizer", resultObj);`

Parameters:

client - client
function - function
params - params (no params)

setStreamType

```
public static void setStreamType(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set the default stream type for a client connection `NetConnection.call("setStreamType", null, streamType);`

Parameters:

client - client
function - function
params - params (streamType)

getStreamType

```
public static void getStreamType(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the default stream type for a client connection `NetConnection.call("getStreamType", resultObj);`

(continued from last page)

Parameters:

client - client
function - function
params - params (no params)

receiveAudio

```
public static void receiveAudio(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.receiveAudio(receive : Boolean);

Parameters:

client - client
function - function
params - params (receive)

receiveVideo

```
public static void receiveVideo(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Server side implementation of NetStream.receiveVideo(receive : Boolean | FPS : Number); FPS does not work the same as FMS. Wowza Pro accepts the following values:

- true: Send all video frames
- false: Send no video
- -1: Send all video frames
- -2: Send half the frames (remove B frames) (Note: only works with Sorenson Spark video with B-frames)
- -3: Send only key frames

Parameters:

client - client
function - function
params - params (receive | FPS)

getStreamBitrate

```
public void getStreamBitrate(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get stream bitrate in bits-per-second for a video on demand stream (will not work for live). To call, NetConnection.call("getStreamBitrate", resultObj, streamName);

Parameters:

client - client
function - function
params - params (streamName:String)

getStreamLength

```
public static void getStreamLength(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

(continued from last page)

Get stream length in seconds `NetConnection.call("getStreamLength", resultObj, streamName)`; If you pass in an array of streamNames it will return an array of durations.

Parameters:

client - client
function - function
params - params (streamName:String or streamNames:Array)

getRepeaterOriginUrl

```
public static void getRepeaterOriginUrl(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get the Repeater Origin URL for this client

Parameters:

client - client
function - function
params - params

setRepeaterOriginUrl

```
public static void setRepeaterOriginUrl(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set the Repeater Origin URL for this client

Parameters:

client - client
function - function
params - params (repeaterOriginUrl)

FCPublish

```
public static void FCPublish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCPublish method called by FME 2.5

Parameters:

client - client
function - function
params - params

FCUnPublish

```
public static void FCUnPublish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCUnpublish method called by FME 2.5

Parameters:

client - client
function - function
params - params

FCUnpublish

```
public static void FCUnpublish(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

pauseRaw

```
public static void pauseRaw(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

pauseRaw method introduced in Flash player 10

Parameters:

client - client
function - function
params - params

getReferrer

```
public static void getReferrer(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

getReferrer returns the referrer from the onConnect metadata

Parameters:

client - client
function - function
params - params

getPageUrl

```
public static void getPageUrl(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

getPageUrl returns the pageUrl from the onConnect metadata

Parameters:

client - client
function - function
params - params

FCSubscribe

```
public static void FCSubscribe(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCSubscribe subscribes to a live stream (if origin edge will start the stream from the origin to the edge)

Parameters:

client - client
function - function
params - params (streamName:String, [mediaCasterType:String])

FCUnsubscribe

```
public static void FCUnsubscribe(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

FCUnSubscribe to a live stream

Parameters:

client - client

function - function


params - params (streamName:String)

FCUnSubscribe

```
public static void FCUnSubscribe(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```


com.wowza.wms.module Class ModuleFastPlay

java.lang.Object



public class **ModuleFastPlay**
extends [ModuleBase](#)

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK_PARAM1](#), [CALLBACK_PARAM10](#), [CALLBACK_PARAM2](#), [CALLBACK_PARAM3](#), [CALLBACK_PARAM4](#), [CALLBACK_PARAM5](#), [CALLBACK_PARAM6](#), [CALLBACK_PARAM7](#), [CALLBACK_PARAM8](#), [CALLBACK_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION_APPEND](#), [PLAYTRANSITION_APPEND_IMMEDIATE](#), [PLAYTRANSITION_RESET](#), [PLAYTRANSITION_RESET_IMMEDIATE](#), [PLAYTRANSITION_STOP](#), [PLAYTRANSITION_SWAP](#), [PLAYTRANSITION_SWITCH](#), [PLAYTRANSITION_UNKNOWN](#), [PLAYTRANSITIONSTR_APPEND](#), [PLAYTRANSITIONSTR_RESET](#), [PLAYTRANSITIONSTR_STOP](#), [PLAYTRANSITIONSTR_SWAP](#), [PLAYTRANSITIONSTR_SWITCH](#), [PLAYTRANSITIONSTR_UNKNOWN](#)

Constructor Summary

public	ModuleFastPlay()
--------	----------------------------------

Method Summary

static void	setFastPlay (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Turn on fast play NetStream.call("setFastPlay", null, multiplier, frames-per-second, direction);
-------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

Methods inherited from class java.lang.Object

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Constructors

(continued from last page)

ModuleFastPlay

```
public ModuleFastPlay()
```

Methods

setFastPlay

```
public static void setFastPlay(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Turn on fast play `NetStream.call("setFastPlay", null, multiplier, frames-per-second, direction);`

Parameters:


client - client

function - function

params - params (multiplier, frames-per-second, direction)

com.wowza.wms.module Class ModuleMediaCasterStreamMonitorAdvanced

java.lang.Object



All Implemented Interfaces:

[IMediaCasterValidateMediaCaster](#)

```
public class ModuleMediaCasterStreamMonitorAdvanced
extends ModuleBase
implements IMediaCasterValidateMediaCaster
```

ModuleMediaCasterStreamMonitorAdvanced: Advanced stream monitoring module.

Add this <Module> definition to the end of the <Modules> list in [install-dir]/conf/[application]/Application.xml:

```
<Module>
  <Name>ModuleMediaCasterStreamMonitorAdvanced</Name>
  <Description>ModuleMediaCasterStreamMonitorAdvanced</Description>
  <Class>com.wowza.wms.module.ModuleMediaCasterStreamMonitorAdvanced</Class>
</Module>
```

Add these properties to the application level <Properties> container at the bottom of [install-dir]/conf/[application]/Application.xml (be sure to get the correct <Properties> container - there are several in the Application.xml file). Carefully read the instructions above each set of properties and set accordingly:

```

<!--
Monitor incoming packets (stream, audio, video) to be sure packets continue to flow from
encoder to stream. The
streamMonitor[type]StartTimeout controls the timeout (milliseconds) for the first packet. The
streamMonitor[type]Timeout
controls the timeout (milliseconds) for packets after the first packet. The stream type
refers to a catch all of any packet of
any type (audio, video, data). If any of these values are set to zero, the test is turned
off.
-->
<Property>
    <Name>streamMonitorStreamStartTimeout</Name>
    <Value>20000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorStreamTimeout</Name>
    <Value>12000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorVideoStartTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorVideoTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioStartTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTimeout</Name>
    <Value>0</Value>
    <Type>Integer</Type>
</Property>

<!--
Monitor the incoming packet timecodes (audio, video or data) to be sure packets do not arrive
out of order or late. The
streamMonitor[type]TCPosTolerance and streamMonitor[type]TCNegTolerance (milliseconds) values
define a sliding window
based on the timecode of the previous packet. For example if these values are set to -500 and
3000 respectively then the
timecode difference between the current arriving packet and the previous packet of that type
must fall within
-500 and 3000 milliseconds. If not and streamMonitor[type]TCToleranceEnable is set to true

```

then stream will be considered
unhealthy and will be reset.

-->

```
<Property>
    <Name>streamMonitorVideoTCToleranceEnable</Name>
    <Value>>false</Value>
    <Type>Boolean</Type>
</Property>
<Property>
    <Name>streamMonitorVideoTCPosTolerance</Name>
    <Value>3000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorVideoTCNegTolerance</Name>
    <Value>-500</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTCToleranceEnable</Name>
    <Value>>false</Value>
    <Type>Boolean</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTCPosTolerance</Name>
    <Value>3000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorAudioTCNegTolerance</Name>
    <Value>-500</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorDataTCToleranceEnable</Name>
    <Value>>false</Value>
    <Type>Boolean</Type>
</Property>
<Property>
    <Name>streamMonitorDataTCPosTolerance</Name>
    <Value>3000</Value>
    <Type>Integer</Type>
</Property>
<Property>
    <Name>streamMonitorDataTCNegTolerance</Name>
    <Value>-500</Value>
    <Type>Integer</Type>
</Property>
```

<!--

Monitors the time difference between the audio and video channel of a stream. If the difference between the currently arriving video packet and the previous audio packet (or vice-versa) is greater than streamMonitorAVSyncTolerance and streamMonitorAVSyncToleranceEnable is set to true, then the stream will be considered unhealthy and will be reset.

```
-->
```

```
<Property>
```

```
    <Name>streamMonitorAVSyncToleranceEnable</Name>
```

```
    <Value>>false</Value>
```

```
    <Type>Boolean</Type>
```

```
</Property>
```

```
<Property>
```

```
    <Name>streamMonitorAVSyncTolerance</Name>
```

```
    <Value>1500</Value>
```

```
    <Type>Integer</Type>
```

```
</Property>
```

```
<!--
```

If set to true, then when a stream is reset and it belong to a MediaStreamNameGroup all streams in the group will be reset. If false only the unhealthy stream will be reset.

```
-->
```

```
<Property>
```

```
    <Name>streamMonitorResetNameGroups</Name>
```

```
    <Value>>true</Value>
```

```
    <Type>Boolean</Type>
```

```
</Property>
```

```
<!--
```

Turns on debug logging of the monitoring.

```
-->
```

```
<Property>
```

```
    <Name>streamMonitorDebug</Name>
```

```
    <Value>>false</Value>
```

```
    <Type>Boolean</Type>
```

```
</Property>
```

Field Summary

protected	appInstance
protected	badStreams
protected	monitors
protected	streamMonitorAudioStartTimeout

protected	streamMonitorAudioTCNegTolerance
protected	streamMonitorAudioTCPosTolerance
protected	streamMonitorAudioTCToleranceEnable
protected	streamMonitorAudioTimeout
protected	streamMonitorAVSyncTolerance
protected	streamMonitorAVSyncToleranceEnable
protected	streamMonitorDataTCNegTolerance
protected	streamMonitorDataTCPosTolerance
protected	streamMonitorDataTCToleranceEnable
protected	streamMonitorDebug
protected	streamMonitorResetNameGroups
protected	streamMonitorStreamStartTimeout
protected	streamMonitorStreamTimeout
protected	streamMonitorVideoStartTimeout
protected	streamMonitorVideoTCNegTolerance
protected	streamMonitorVideoTCPosTolerance
protected	streamMonitorVideoTCToleranceEnable
protected	streamMonitorVideoTimeout

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK_PARAM1](#), [CALLBACK_PARAM10](#), [CALLBACK_PARAM2](#), [CALLBACK_PARAM3](#), [CALLBACK_PARAM4](#), [CALLBACK_PARAM5](#), [CALLBACK_PARAM6](#), [CALLBACK_PARAM7](#), [CALLBACK_PARAM8](#), [CALLBACK_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION_APPEND](#), [PLAYTRANSITION_APPEND_IMMEDIATE](#), [PLAYTRANSITION_RESET](#), [PLAYTRANSITION_RESET_IMMEDIATE](#), [PLAYTRANSITION_STOP](#), [PLAYTRANSITION_SWAP](#), [PLAYTRANSITION_SWITCH](#), [PLAYTRANSITION_UNKNOWN](#), [PLAYTRANSITIONSTR_APPEND](#), [PLAYTRANSITIONSTR_RESET](#), [PLAYTRANSITIONSTR_STOP](#), [PLAYTRANSITIONSTR_SWAP](#), [PLAYTRANSITIONSTR_SWITCH](#), [PLAYTRANSITIONSTR_UNKNOWN](#)

Constructor Summary

public	ModuleMediaCasterStreamMonitorAdvanced()
--------	----------------------------------------------------------

Method Summary

void	onAppStart (IApplicationInstance appInstance)
void	onAppStop (IApplicationInstance appInstance)
boolean	onResetMediaCaster (IApplicationInstance appInstance, IMediaCaster mediaCaster)
void	onStreamCreate (IMediaStream stream)
void	onStreamDestroy (IMediaStream stream)
boolean	onValidateMediaCaster (IApplicationInstance appInstance, IMediaCaster mediaCaster)
void	onValidateMediaCastersStart (IApplicationInstance appInstance)
void	onValidateMediaCastersStop (IApplicationInstance appInstance)

Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#), [getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#), [getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#), [getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#), [getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#), [sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendStreamOnStatusError](#)

Methods inherited from class [java.lang.Object](#)

[clone](#), [equals](#), [finalize](#), [getClass](#), [hashCode](#), [notify](#), [notifyAll](#), [toString](#), [wait](#), [wait](#), [wait](#)

Methods inherited from interface [com.wowza.wms.mediacaster.IMediaCasterValidateMediaCaster](#)

[onResetMediaCaster](#), [onValidateMediaCaster](#), [onValidateMediaCastersStart](#), [onValidateMediaCastersStop](#)

Fields

streamMonitorStreamStartTimeout

protected int **streamMonitorStreamStartTimeout**

(continued from last page)

streamMonitorStreamTimeout

protected int **streamMonitorStreamTimeout**

streamMonitorVideoTCToleranceEnable

protected boolean **streamMonitorVideoTCToleranceEnable**

streamMonitorVideoTCPosTolerance

protected int **streamMonitorVideoTCPosTolerance**

streamMonitorVideoTCNegTolerance

protected int **streamMonitorVideoTCNegTolerance**

streamMonitorAudioTCToleranceEnable

protected boolean **streamMonitorAudioTCToleranceEnable**

streamMonitorAudioTCPosTolerance

protected int **streamMonitorAudioTCPosTolerance**

streamMonitorAudioTCNegTolerance

protected int **streamMonitorAudioTCNegTolerance**

streamMonitorDataTCToleranceEnable

protected boolean **streamMonitorDataTCToleranceEnable**

streamMonitorDataTCPosTolerance

protected int **streamMonitorDataTCPosTolerance**

streamMonitorDataTCNegTolerance

protected int **streamMonitorDataTCNegTolerance**

(continued from last page)

streamMonitorAVSyncToleranceEnableprotected boolean **streamMonitorAVSyncToleranceEnable**

streamMonitorAVSyncToleranceprotected int **streamMonitorAVSyncTolerance**

streamMonitorVideoStartTimeoutprotected int **streamMonitorVideoStartTimeout**

streamMonitorVideoTimeoutprotected int **streamMonitorVideoTimeout**

streamMonitorAudioStartTimeoutprotected int **streamMonitorAudioStartTimeout**

streamMonitorAudioTimeoutprotected int **streamMonitorAudioTimeout**

streamMonitorResetNameGroupsprotected boolean **streamMonitorResetNameGroups**

streamMonitorDebugprotected boolean **streamMonitorDebug**

appInstanceprotected com.wowza.wms.application.IApplicationInstance **appInstance**

(continued from last page)

monitors

```
protected java.util.Map monitors
```

badStreams

```
protected java.util.Set badStreams
```

Constructors

ModuleMediaCasterStreamMonitorAdvanced

```
public ModuleMediaCasterStreamMonitorAdvanced()
```

Methods

onAppStart

```
public void onAppStart(IApplicationInstance appInstance)
```

onAppStop

```
public void onAppStop(IApplicationInstance appInstance)
```

onStreamCreate

```
public void onStreamCreate(IMediaStream stream)
```

onStreamDestroy

```
public void onStreamDestroy(IMediaStream stream)
```

onValidateMediaCastersStart

```
public void onValidateMediaCastersStart(IApplicationInstance appInstance)
```

onValidateMediaCaster

```
public boolean onValidateMediaCaster(IApplicationInstance appInstance,  
    IMediaCaster mediaCaster)
```

onValidateMediaCastersStop


```
public void onValidateMediaCastersStop(IApplicationInstance appInstance)
```

onResetMediaCaster

```
public boolean onResetMediaCaster(IApplicationInstance appInstance,  
    IMediaCaster mediaCaster)
```

com.wowza.wms.module Class ModuleProperties

java.lang.Object



public class **ModuleProperties**
extends [ModuleBase](#)

Fields inherited from class [com.wowza.wms.module.ModuleBase](#)

[CALLBACK_PARAM1](#), [CALLBACK_PARAM10](#), [CALLBACK_PARAM2](#), [CALLBACK_PARAM3](#), [CALLBACK_PARAM4](#), [CALLBACK_PARAM5](#), [CALLBACK_PARAM6](#), [CALLBACK_PARAM7](#), [CALLBACK_PARAM8](#), [CALLBACK_PARAM9](#), [PARAM1](#), [PARAM10](#), [PARAM2](#), [PARAM3](#), [PARAM4](#), [PARAM5](#), [PARAM6](#), [PARAM7](#), [PARAM8](#), [PARAM9](#), [PARAMMETHODNAME](#), [PLAYTRANSITION_APPEND](#), [PLAYTRANSITION_APPEND_IMMEDIATE](#), [PLAYTRANSITION_RESET](#), [PLAYTRANSITION_RESET_IMMEDIATE](#), [PLAYTRANSITION_STOP](#), [PLAYTRANSITION_SWAP](#), [PLAYTRANSITION_SWITCH](#), [PLAYTRANSITION_UNKNOWN](#), [PLAYTRANSITIONSTR_APPEND](#), [PLAYTRANSITIONSTR_RESET](#), [PLAYTRANSITIONSTR_STOP](#), [PLAYTRANSITIONSTR_SWAP](#), [PLAYTRANSITIONSTR_SWITCH](#), [PLAYTRANSITIONSTR_UNKNOWN](#)

Constructor Summary

public	ModuleProperties ()
--------	--------------------------------------

Method Summary

static void	getAppInstanceProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get application instance level property value NetConnection.call("getAppInstanceProperty", resultObj, name);
static void	getApplicationProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get application level property value NetConnection.call("getApplicationProperty", resultObj, name);
static void	getClientProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get client level property value NetConnection.call("getClientProperty", resultObj, name);
static void	getStreamProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Get stream level property value NetConnection.call("getStreamProperty", resultObj, streamId, name);
static void	setAppInstanceProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set application instance level property NetConnection.call("setAppInstanceProperty", null, name, value);
static void	setApplicationProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set application level property NetConnection.call("setApplicationProperty", null, name, value);

static void	setClientProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set client level property NetConnection.call("setClientProperty", null, name, value);
static void	setStreamProperty (IClient client, com.wowza.wms.request.RequestFunction function, AMFDataList params) Set stream level property NetConnection.call("setStreamProperty", null, streamId, name, value);

Methods inherited from class [com.wowza.wms.module.ModuleBase](#)

[getAppInstance](#), [getApplication](#), [getCallbackParamCount](#), [getLogger](#), [getParam](#),
[getParamBoolean](#), [getParamBoolean](#), [getParamCount](#), [getParamDate](#), [getParamDouble](#),
[getParamDouble](#), [getParamInt](#), [getParamInt](#), [getParamLong](#), [getParamLong](#),
[getParamMixedArray](#), [getParamObj](#), [getParamString](#), [getParamString](#), [getParamType](#),
[getStream](#), [getVHost](#), [invokePrevious](#), [invokePrevious](#), [isSendResult](#),
[sendClientOnStatusError](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#), [sendResult](#),
[sendStreamOnStatusError](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait,
wait

Constructors

ModuleProperties

```
public ModuleProperties()
```

Methods

setApplicationProperty

```
public static void setApplicationProperty(IClient client,  
com.wowza.wms.request.RequestFunction function,  
AMFDataList params)
```

Set application level property NetConnection.call("setApplicationProperty", null, name, value);

Parameters:

client - client
function - function
params - params (name, value)

getApplicationProperty

```
public static void getApplicationProperty(IClient client,  
com.wowza.wms.request.RequestFunction function,  
AMFDataList params)
```

Get application level property value NetConnection.call("getApplicationProperty", resultObj, name);

Parameters:

client - client
function - function

(continued from last page)

params - params (name)

setAppInstanceProperty

```
public static void setAppInstanceProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set application instance level property `NetConnection.call("setAppInstanceProperty", null, name, value);`

Parameters:

client - client
function - function
params - params (name, value)

getAppInstanceProperty

```
public static void getAppInstanceProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get application instance level property value `NetConnection.call("getAppInstanceProperty", resultObj, name);`

Parameters:

client - client
function - function
params - params (name)

setClientProperty

```
public static void setClientProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Set client level property `NetConnection.call("setClientProperty", null, name, value);`

Parameters:

client - client
function - function
params - params (name, value)

getClientProperty

```
public static void getClientProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get client level property value `NetConnection.call("getClientProperty", resultObj, name);`

Parameters:

client - client
function - function
params - params (name)

setStreamProperty

```
public static void setStreamProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

(continued from last page)

Set stream level property NetConnection.call("setStreamProperty", null, streamId, name, value);

Parameters:

client - client

function - function

params - params (streamId, name, value)

getStreamProperty

```
public static void getStreamProperty(IClient client,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Get stream level property value NetConnection.call("getStreamProperty", resultObj, streamId, name);

Parameters:

client - client

function - function

params - params (streamId, name)

Package

com.wowza.wms.response

com.wowza.wms.response Class ResponseFunction

java.lang.Object

└-com.wowza.wms.response.ResponseFunction

public class **ResponseFunction**
extends Object

ResponseFunction: class for sending status messages to the client.

Field Summary

public	doBreak
--------	-------------------------

Constructor Summary

public	ResponseFunction (IClient client) Create an empty ResponseFunction
public	ResponseFunction (com.wowza.wms.netconnection.INetConnection netConnection) Create an empty ResponseFunction
public	ResponseFunction (com.wowza.wms.netconnection.INetConnection netConnection, AMFObj amfObj) Create an empty ResponseFunction
public	ResponseFunction (IClient client, AMFObj amfObj) Create an empty ResponseFunction
public	ResponseFunction (IMediaStream stream, AMFObj amfObj) Create an empty ResponseFunction

Method Summary

void	addBody (AMFData body) Add AMFData to the body of the message.
void	addBytes (byte[] inbytes) Add raw AMFData bytes[] to message body
void	createBroadcastMessage (java.nio.ByteBuffer messageBytes) Create broadcast message.
void	createConnectMessage (String inName, double inResultNum) Create net connection connect message.
void	createDefaultMessage (String inName, double inResultNum) Create a default message (onStatus type messages).
void	createEnhancedSeekMessage (byte[] messageBuffer, int src, int tc)

void	<u>createPlayStatusMessage</u> (String inName) Create onPlayStatus message.
void	<u>createSeekMessage</u> (String inName) Create a seek result message.
void	<u>createSOMessage</u> (byte[] messageBuffer, int objectEncoding) Create shared object message.
long	<u>getTimecode</u> () Get function timecode (milliseconds).
int	<u>getType</u> () Get message type.
boolean	<u>isForceAMF0</u> ()
void	<u>setBody</u> (int index, <u>AMFData</u> body) Add AMFData to the body of the message.
void	<u>setForceAMF0</u> (boolean forceAMF0)
void	<u>setMessageBytes</u> (byte[] messageBytes)
void	<u>setRetAMFNumber</u> (int innum) Set the return channel id
void	<u>setSrc</u> (int src) Set the src (stream id) for the message.
void	<u>setTimecode</u> (long timecode) Set function timecode (milliseconds).
void	<u>setType</u> (int type) Set message type.
int	<u>write</u> (java.io.OutputStream out, boolean isAbsTimecode, int chunkSize) Write message directly to OutputStream
int	<u>write</u> (java.io.OutputStream out, int chunkSize) Write message directly to OutputStream.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

doBreak

public boolean **doBreak**

(continued from last page)

Constructors

ResponseFunction

```
public ResponseFunction(IClient client)
```

Create an empty ResponseFunction

Parameters:

client - client

ResponseFunction

```
public ResponseFunction(com.wowza.wms.netconnection.INetConnection netConnection)
```

Create an empty ResponseFunction

Parameters:

netConnection - net connection

ResponseFunction

```
public ResponseFunction(com.wowza.wms.netconnection.INetConnection netConnection,  
AMFObj amfObj)
```

Create an empty ResponseFunction

Parameters:

netConnection - net connection

amfObj - amf object

ResponseFunction

```
public ResponseFunction(IClient client,  
AMFObj amfObj)
```

Create an empty ResponseFunction

Parameters:

client - client object

amfObj - amf object

ResponseFunction

```
public ResponseFunction(IMediaStream stream,  
AMFObj amfObj)
```

Create an empty ResponseFunction

Parameters:

stream - media stream object

amfObj - amf object

Methods

setSrc

```
public void setSrc(int src)
```

(continued from last page)

Set the src (stream id) for the message.

Parameters:

src - src (stream id)

createDefaultMessage

```
public void createDefaultMessage(String inName,  
    double inResultNum)
```

Create a default message (onStatus type messages).

Parameters:

inName - handler name (example: onStatus)

inResultNum - result number of 0 if not result

createConnectMessage

```
public void createConnectMessage(String inName,  
    double inResultNum)
```

Create net connection connect message.

Parameters:

inName - handler name (example: connection)

inResultNum - result number if 0 not a result

createSeekMessage

```
public void createSeekMessage(String inName)
```

Create a seek result message.

Parameters:

inName - handler name (example: onStatus)

createPlayStatusMessage

```
public void createPlayStatusMessage(String inName)
```

Create onPlayStatus message.

Parameters:

inName - handler name (example: onPlayStatus)

setMessageBytes

```
public void setMessageBytes(byte[] messageBytes)
```

createBroadcastMessage

```
public void createBroadcastMessage(java.nio.ByteBuffer messageBytes)
```

Create broadcast message. Used for ByteBuffer handler calls.

Parameters:

(continued from last page)

messageBytes - ByteBuffer with raw AMFData bytes to be sent to client

createSOMessage

```
public void createSOMessage(byte[] messageBuffer,  
    int objectEncoding)
```

Create shared object message. Used for ByteBuffer handler calls.

Parameters:

messageBuffer

createEnhancedSeekMessage

```
public void createEnhancedSeekMessage(byte[] messageBuffer,  
    int src,  
    int tc)
```

addBody

```
public void addBody(AMFData body)
```

Add AMFData to the body of the message.

Parameters:

body - AMFData message

setBody

```
public void setBody(int index,  
    AMFData body)
```

Add AMFData to the body of the message.

Parameters:

index - index in body list

body - AMFData message

addBytes

```
public void addBytes(byte[] inbytes)
```

Add raw AMFData bytes[] to message body

Parameters:

inbytes - raw AMFData bytes[]

setRetAMFNumber

```
public void setRetAMFNumber(int innum)
```

Set the return channel id

Parameters:

innum - return channel id

(continued from last page)

getTimecode

```
public long getTimecode()
```

Get function timecode (milliseconds).

Returns:

function timecode (milliseconds)

setTimecode

```
public void setTimecode(long timecode)
```

Set function timecode (milliseconds).

Parameters:

timecode - function timecode (milliseconds)

setType

```
public void setType(int type)
```

Set message type. See IVHost.CONTENTTYPE_*

Parameters:

type - message type

getType

```
public int getType()
```

Get message type. See IVHost.CONTENTTYPE_*

Returns:

message type

write

```
public int write(java.io.OutputStream out,  
int chunkSize)
```

Write message directly to OutputStream.

Parameters:

out - OutputStream

Returns:

number of bytes written

isForceAMF0

```
public boolean isForceAMF0()
```

setForceAMF0

```
public void setForceAMF0(boolean forceAMF0)
```

(continued from last page)

write

```
public int write(java.io.OutputStream out,  
                boolean isAbsTimecode,  
                int chunkSize)
```

Write message directly to OutputStream

Parameters:

out - OutputStream
isAbsTimecode - is timecode absolute

Returns:

number of bytes written

com.wowza.wms.response Class ResponseFunctions

java.lang.Object

└─com.wowza.wms.response.ResponseFunctions

public class **ResponseFunctions**
extends Object

ResponseFunctions: collection of ResponseFunction objects. This interface is used to asynchronously collect up a set of client responses that will be sent to the client at the next opportunity.

Constructor Summary

public	ResponseFunctions()
--------	-------------------------------------

Method Summary

void	add(ResponseFunction wmsResponseFunction) Add a function.
void	clear()
boolean	isPending() Are there any pending items in the list.
int	output(java.io.OutputStream out, int sendChunkSize) Write all functions (in order added to list) to OutputStream.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ResponseFunctions

public **ResponseFunctions()**

Methods

add

public void **add**([ResponseFunction wmsResponseFunction](#))

Add a function.

(continued from last page)

Parameters:wmsResponseFunction - function

clear

```
public void clear()
```

isPending

```
public boolean isPending()
```

Are there any pending items in the list.

Returns:

true if items in list

output

```
public int output(java.io.OutputStream out,  
int sendChunkSize)
```

Write all functions (in order added to list) to OutputStream.

Parameters:

out - OutputStream

Returns:

total number of bytes written

Package

com.wowza.wms.rtp.model

com.wowza.wms.rtp.model Interface IRTPMessageHandler

public interface **IRTPMessageHandler**
extends

IRTPMessageHandler: Internal use.

Method Summary

void	handleMessage (java.net.SocketAddress socketAddr, byte[] buffer, int offset, int len)
------	-------------------------------------------------------------------------------------------------------

Methods

handleMessage

```
public void handleMessage(java.net.SocketAddress socketAddr,  
    byte[] buffer,  
    int offset,  
    int len)
```

com.wowza.wms.rtp.model

Interface IRTPMetadataProvider

public interface **IRTPMetadataProvider**
extends

IRTPMetadataProvider: Internal use.

Method Summary	
byte[]	getMetadataPacket (RTPStream stream)

Methods

getMetadataPacket
public byte[] **getMetadataPacket**([RTPStream](#) stream)

com.wowza.wms.rtp.model

Interface IRTPSessionNotify

public interface **IRTPSessionNotify**
extends

IRTPSessionNotify: listener interface for RTP sessions. See RTPSessions.addSessionListener(IRTPSessionNotify listener)

Method Summary	
void	onRTPSessionCreate (RTPSession rtpSession) Invoked when RTP session is created
void	onRTPSessionDestroy (RTPSession rtpSession) Invoked when RTP session is destroyed

Methods

onRTPSessionCreate

public void **onRTPSessionCreate**([RTPSession](#) rtpSession)

 Invoked when RTP session is created

Parameters:
 rtpSession - RTP session

onRTPSessionDestroy

public void **onRTPSessionDestroy**([RTPSession](#) rtpSession)

 Invoked when RTP session is destroyed

Parameters:
 rtpSession - RTP session

com.wowza.wms.rtp.model Interface IRTSPActionNotify

public interface **IRTSPActionNotify**
extends

IRTSPActionNotify: listener interface for RTSP actions. See RTPSession.addActionListener(IRTSPActionNotify actionListener)

Method Summary

void	onAnnounce (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by ANNOUNCE command
void	onDescribe (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by DESCRIBE command
void	onGetParameter (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by GET_PARAMETER command
void	onOptions (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by OPTIONS command
void	onPause (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by PAUSE command
void	onPlay (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by PLAY command
void	onRecord (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by RECORD command
void	onRedirect (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by REDIRECT command
void	onSetParameter (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by SET_PARAMETER command
void	onSetup (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by SETUP command
void	onTeardown (RTPSession rtspSession, com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked by TEARDOWN command

Methods

onDescribe

```
public void onDescribe(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by DESCRIBE command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onAnnounce

```
public void onAnnounce(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by ANNOUNCE command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onSetParameter

```
public void onSetParameter(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by SET_PARAMETER command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onGetParameter

```
public void onGetParameter(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by GET_PARAMETER command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

(continued from last page)

onOptions

```
public void onOptions(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked by OPTIONS command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onPause

```
public void onPause(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked by PAUSE command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onPlay

```
public void onPlay(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked by PLAY command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onRecord

```
public void onRecord(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked by RECORD command

Parameters:

rtspSession
req
resp

onRedirect

```
public void onRedirect(RTPSession rtspSession,  
    com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked by REDIRECT command

(continued from last page)

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onSetup

```
public void onSetup(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by SETUP command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

onTeardown

```
public void onTeardown(RTPSession rtspSession,  
    com.wowza.wms.rtp.RTSPRequestMessage req,  
    com.wowza.wms.rtp.RTSPResponseMessages resp)
```

Invoked by TEARDOWN command

Parameters:

rtspSession - RTP session
req - RTP request
resp - RTP response

com.wowza.wms.rtp.model

Class RTPContext

java.lang.Object

└─com.wowza.wms.rtp.model.RTPContext

public class **RTPContext**
extends Object

RTPContext: RTP context

Constructor Summary

public	RTPContext (IVHost vhost)
	Constructor

Method Summary

boolean	acquireSocketAddress (java.net.SocketAddress socketAddress)
	Acquire UDP socket address
int	acquireUDPPortPair ()
	Acquire next available UDP port pair
int	acquireUDPPortPair (int port)
	Acquire UDP port pair
void	cacheRTPStream (RTPStream stream)
	Cache an RTP stream, Internal use.
void	doWatchdog ()
	Idle events for cleanup
boolean	existsRTSPTunnelingSession (String sessionId)
	Return true if session id is valid RTSP/RTP tunneling session id
int[]	expandToPortPair (int port)
	Expand a single port to a pair.
RTPPacketizerItem	getAudioPacketizerItem (IApplicationInstance appInstance, int codecId)
	Get audio packetizer for a given codec id.
com.wowza.wms.rtp.dep acketizer.RTPDePacket izerList	getDePacketizerList ()
	Get a list of the available depacketizers
String	getDePacketizerName (RTPTrack rtpTrack)
	Get a depacketizer by name
Object	getLock ()
	Get the UDP port manager lock
Object	getRTSPTunnelingLock ()
	Get the RTSP/RTP tunneling lock

com.wowza.wms.rtsp.RTSP TunnelingSession	<u>getRTSPTunnelingSession</u> (String sessionId) Get RTSP/RTP tunneling session by session id
<u>RTPSessions</u>	<u>getSessions</u> () Get RTP sessions
RTPPacketizerItem	<u>getStreamPacketizerItem</u> (<u>IApplicationInstance</u> appInstance, int codecId) Get stream packetizer for a given codec id.
com.wowza.wms.rtp.transport.UDPTransportManager	<u>getUDPTransportManager</u> () Get the UDP transport manager
<u>IVHost</u>	<u>getVHost</u> () Get vhost
RTPPacketizerItem	<u>getVideoPacketizerItem</u> (<u>IApplicationInstance</u> appInstance, int codecId) Get video packetizer for a given codec id.
void	<u>init</u> () Initialize
void	<u>putAudioPacketizerItem</u> (int codecId, RTPPacketizerItem rtpPacketizerInfo) Set the audio packetizer for a given codec id
void	<u>putRTSPTunnelingSession</u> (String sessionId, com.wowza.wms.rtsp.RTSP TunnelingSession rtspTunnelingSession) Remove RTSP/RTP tunneling session by session id
void	<u>putStreamPacketizerItem</u> (int codecId, RTPPacketizerItem rtpPacketizerInfo) Set the stream packetizer for a given codec id
void	<u>putVideoPacketizerItem</u> (int codecId, RTPPacketizerItem rtpPacketizerInfo) Set the video packetizer for a given codec id
boolean	<u>releaseSocketAddress</u> (java.net.SocketAddress socketAddress) Release UDP socket address
void	<u>releaseUDPPortPair</u> (int port) Release port pair
com.wowza.wms.rtsp.RTSP TunnelingSession	<u>removeRTSPTunnelingSession</u> (String sessionId) Remove RTSP/RTP tunneling session by session id
void	<u>shutdown</u> () Shutdown
void	<u>shutdownRTPSession</u> (<u>RTPSession</u> rtpSession) Gracefully and forcefully shutdown and RTP session
<u>RTPStream</u>	<u>uncacheRTPStream</u> (String streamId) UnCache an RTP stream, Internal use.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

RTPContext

```
public RTPContext(IVHost vhost)
```

Constructor

Parameters:

vhost - vhost

Methods

doWatchdog

```
public void doWatchdog()
```

Idle events for cleanup

init

```
public void init()
```

Initialize

shutdown

```
public void shutdown()
```

Shutdown

getAudioPacketizerItem

```
public RTPPacketizerItem getAudioPacketizerItem(IApplicationInstance appInstance,  
int codecId)
```

Get audio packetizer for a given codec id.

Parameters:

appInstance - application instance

codecId - codec id, see IVHost.CODEC_AUDIO_*

Returns:

packetizer info

putAudioPacketizerItem

```
public void putAudioPacketizerItem(int codecId,  
RTPPacketizerItem rtpPacketizerInfo)
```

Set the audio packetizer for a given codec id

Parameters:

codecId - codec id, see IVHost.CODEC_AUDIO_*

rtpPacketizerInfo - packetizer info

getVideoPacketizerItem

```
public RTPPacketizerItem getVideoPacketizerItem(IApplicationInstance appInstance,  
int codecId)
```

Get video packetizer for a given codec id.

Parameters:

appInstance - application instance
codecId - codec id, see IVHost.CODEC_VIDEO_*

Returns:

packetizer info

putVideoPacketizerItem

```
public void putVideoPacketizerItem(int codecId,  
RTPPacketizerItem rtpPacketizerInfo)
```

Set the video packetizer for a given codec id

Parameters:

codecId - codec id, see IVHost.CODEC_VIDEO_*

rtpPacketizerInfo - packetizer info

getStreamPacketizerItem

```
public RTPPacketizerItem getStreamPacketizerItem(IApplicationInstance appInstance,  
int codecId)
```

Get stream packetizer for a given codec id.

Parameters:

appInstance - application instance
codecId - codec id, see IVHost.CODEC_STREAM_*

Returns:

packetizer info

putStreamPacketizerItem

```
public void putStreamPacketizerItem(int codecId,  
RTPPacketizerItem rtpPacketizerInfo)
```

Set the stream packetizer for a given codec id

Parameters:

codecId - codec id, see IVHost.CODEC_STREAM_*

rtpPacketizerInfo - packetizer info

getSessions

```
public RTPSessions getSessions()
```

Get RTP sessions

Returns:

RTP sessions

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:
vhost

getUDPTransportManager

```
public com.wowza.wms.rtp.transport.UDPTransportManager getUDPTransportManager()
```

Get the UDP transport manager

Returns:
UDP transport manager

getLock

```
public Object getLock()
```

Get the UDP port manager lock

Returns:
UDP port manager lock

acquireSocketAddress

```
public boolean acquireSocketAddress(java.net.SocketAddress socketAddress)
```

Acquire UDP socket address

Parameters:
socketAddress - UDP socket address

Returns:
true if available

releaseSocketAddress

```
public boolean releaseSocketAddress(java.net.SocketAddress socketAddress)
```

Release UDP socket address

Parameters:
socketAddress - UDP socket address

Returns:
true if available

acquireUDPPortPair

```
public int acquireUDPPortPair(int port)
```

Acquire UDP port pair

(continued from last page)

Parameters:

port - starting port

Returns:

port

expandToPortPair

```
public int[] expandToPortPair(int port)
```

Expand a single port to a pair. Ports are allocated in pairs always starting with even port number.

Parameters:

port - port

Returns:

port

acquireUDPPortPair

```
public int acquireUDPPortPair()
```

Acquire next available UDP port pair

Returns:

port

releaseUDPPortPair

```
public void releaseUDPPortPair(int port)
```

Release port pair

Parameters:

port - first port of pair

cacheRTPStream

```
public void cacheRTPStream(RTPStream stream)
```

Cache an RTP stream, Internal use.

Parameters:

stream - RTP stream

uncacheRTPStream

```
public RTPStream uncacheRTPStream(String streamId)
```

UnCache an RTP stream, Internal use.

Parameters:

streamId - stream id

Returns:

RTP Stream

(continued from last page)

getDePacketizerList

```
public com.wowza.wms.rtp.depaketizer.RTPDePacketizerList getDePacketizerList()
```

Get a list of the available depacketizers

Returns:

list of the available depacketizers

getDePacketizerName

```
public String getDePacketizerName(RTPTrack rtpTrack)
```

Get a depacketizer by name

Parameters:

rtpTrack - track

Returns:

depacketizer

getRTSPTunnelingLock

```
public Object getRTSPTunnelingLock()
```

Get the RTSP/RTP tunneling lock

Returns:

RTSP/RTP tunneling lock

getRTSPTunnelingSession

```
public com.wowza.wms.rtsp.RTSPTunnelingSession getRTSPTunnelingSession(String  
sessionId)
```

Get RTSP/RTP tunneling session by session id

Parameters:

sessionId - session id

Returns:

RTSP/RTP tunneling session

removeRTSPTunnelingSession

```
public com.wowza.wms.rtsp.RTSPTunnelingSession removeRTSPTunnelingSession(String  
sessionId)
```

Remove RTSP/RTP tunneling session by session id

Parameters:

sessionId - session id

Returns:

RTSP/RTP tunneling session if removed

(continued from last page)

existsRTSPTunnelingSession

```
public boolean existsRTSPTunnelingSession(String sessionId)
```

Return true if session id is valid RTSP/RTP tunneling session id

Parameters:

sessionId - session id

Returns:

true if session id is valid RTSP/RTP tunneling session id

putRTSPTunnelingSession

```
public void putRTSPTunnelingSession(String sessionId,  
    com.wowza.wms.rtsp.RTSPTunnelingSession rtspTunnelingSession)
```

Remove RTSP/RTP tunneling session by session id

Parameters:

sessionId - session id

rtspTunnelingSession - RTSP/RTP tunneling session

shutdownRTPSession

```
public void shutdownRTPSession(RTPSession rtpSession)
```

Gracefully and forcefully shutdown and RTP session

Parameters:

rtpSession - RTP session

com.wowza.wms.rtp.model

Class RTPDestination

java.lang.Object

└─com.wowza.wms.rtp.model.RTPDestination

public class **RTPDestination**
extends Object

RTPDestination: Fully describes an RTP destination.

Constructor Summary

public	RTPDestination()
--------	----------------------------------

Method Summary

String	getAudioHost() Get audio host
int	getAudioPort() Get audio port
String	getHost() Get the host
String	getHostType() Get host type (default IP4)
String	getName() Get name
int	getStreamPort() Get stream port
int	getTTL() Get time to live
String	getVideoHost() Get video host
int	getVideoPort() Get video port
boolean	isMulticast() Return true if multicast destination
boolean	isRTPWrapped() Is stream wrapped in RTP (MPEG-TS in RTP)
boolean	isStream() Return true if stream destination (and not native RTP destination)

void	<code>setAudioHost</code> (String audioHost) Set audio host
void	<code>setAudioPort</code> (int audioPort) Set audio port
void	<code>setHost</code> (String host) Set host
void	<code>setHostType</code> (String hostType) Set host type (default IP4)
void	<code>setName</code> (String name) Set name
void	<code>setRTPWrapped</code> (boolean isRTPWrapped) Is stream wrapped in RTP (MPEG-TS in RTP)
void	<code>setStreamPort</code> (int streamPort) Set stream port
void	<code>setTTL</code> (int ttl) Set time to live
void	<code>setVideoHost</code> (String videoHost) Set video host
void	<code>setVideoPort</code> (int videoPort) Set video port
String	<code>toString</code> ()

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

RTPDestination

```
public RTPDestination()
```

Methods

toString

```
public String toString()
```

(continued from last page)

isMulticast

```
public boolean isMulticast()
```

Return true if multicast destination

Returns:

true if multicast destination

isStream

```
public boolean isStream()
```

Return true if stream destination (and not native RTP destination)

Returns:

true if stream destination

getHost

```
public String getHost()
```

Get the host

Returns:

host

setHost

```
public void setHost(String host)
```

Set host

Parameters:

host - host

getVideoPort

```
public int getVideoPort()
```

Get video port

Returns:

video port

setVideoPort

```
public void setVideoPort(int videoPort)
```

Set video port

Parameters:

videoPort - video port

getAudioPort

```
public int getAudioPort()
```

(continued from last page)

Get audio port

Returns:

audio port

setAudioPort

```
public void setAudioPort(int audioPort)
```

Set audio port

Parameters:

audioPort - audio port

getStreamPort

```
public int getStreamPort()
```

Get stream port

Returns:

stream port

setStreamPort

```
public void setStreamPort(int streamPort)
```

Set stream port

Parameters:

streamPort - stream port

getVideoHost

```
public String getVideoHost()
```

Get video host

Returns:

video host

setVideoHost

```
public void setVideoHost(String videoHost)
```

Set video host

Parameters:

videoHost - video host

getAudioHost

```
public String getAudioHost()
```

Get audio host

Returns:

audio host

setAudioHost

```
public void setAudioHost(String audioHost)
```

Set audio host

Parameters:

audioHost - audio host

getHostType

```
public String getHostType()
```

Get host type (default IP4)

Returns:

host type

setHostType

```
public void setHostType(String hostType)
```

Set host type (default IP4)

Parameters:

hostType - host type

getTTL

```
public int getTTL()
```

Get time to live

Returns:

time to live

setTTL

```
public void setTTL(int ttl)
```

Set time to live

Parameters:

ttl - time to live

isRTPWrapped

```
public boolean isRTPWrapped()
```

Is stream wrapped in RTP (MPEG-TS in RTP)

Returns:

true if stream wrapped in RTP

setRTPWrapped

```
public void setRTPWrapped(boolean isRTPWrapped)
```

(continued from last page)

Is stream wrapped in RTP (MPEG-TS in RTP)

Parameters:

isRTPWrapped - true if stream wrapped in RTP

getName

```
public String getName()
```

Get name

Returns:

name

setName

```
public void setName(String name)
```

Set name

Parameters:

name - name

com.wowza.wms.rtp.model

Class RTPPort

java.lang.Object

└─com.wowza.wms.rtp.model.RTPPort

All Implemented Interfaces:

com.wowza.wms.rtp.transport.IUDPMessageHandler

public class **RTPPort**
 extends Object
 implements com.wowza.wms.rtp.transport.IUDPMessageHandler

Constructor Summary

public	RTPPort (String inIpAddress, int inPort, String outIpAddress, int outPort, boolean isMulticast) Constructor
--------	--------------------------------------------------------------------------------------------------------------------------------

Method Summary

void	bind (int direction) Bind to port
int	getAddressCount () Get address count
I RTPMessageHandler	getHandler () Get the message handler
String	getInIpAddress () Get in IP address
int	getInPort () Get in port
String	getOutIpAddress () Get out IP address
int	getOutPort () Get out port
RTPTrack	getTrack () Get RTP track
int	getTTL () Get time to live (milliseconds)
com.wowza.wms.rtp.transport.IUDPTransport	getUDPTransport () Get the UDP transport
void	handleMessage (java.net.SocketAddress socketAddr, Object message)

boolean	<u>isInMulticast()</u> Is in stream multicast
boolean	<u>isMulticast()</u> Is multicast
boolean	<u>isOutMulticast()</u> Is out stream multicast
void	<u>sendMessage()</u> (byte[] message, int offset, int len) Send a message out
void	<u>sendResponse()</u> (byte[] message) Send a response
void	<u>sendResponse()</u> (byte[] message, int offset, int len) Send response
void	<u>sendResponse()</u> (byte[] message, int offset, int len, java.net.SocketAddress destination) Send response to destination
void	<u>sessionClosed()</u> (com.wowza.wms.rtp.transport.IUDPTransportSession session)
void	<u>sessionOpened()</u> (com.wowza.wms.rtp.transport.IUDPTransportSession session)
void	<u>setAddressCount()</u> (int addressCount) Set address count
void	<u>setHandler()</u> (IRTPMessageHandler handler) Set the message handler
void	<u>setTrack()</u> (RTPTrack track) Set RTP track
void	<u>setTTL()</u> (int ttl) Set time to live (milliseconds)
void	<u>shutdown()</u> Shutdown port
void	<u>unbind()</u> Unbind

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface com.wowza.wms.rtp.transport.IUDPMessageHandler

handleMessage, sessionClosed, sessionOpened

Constructors

(continued from last page)

RTPPort

```
public RTPPort(String inIpAddress,  
               int inPort,  
               String outIpAddress,  
               int outPort,  
               boolean isMulticast)
```

Constructor

Parameters:

inIpAddress - in ip address
inPort - in port
outIpAddress - out ip address
outPort - out port
isMulticast - true if multicast

Methods

getTrack

```
public RTPTrack getTrack()
```

Get RTP track

Returns:

RTP track

setTrack

```
public void setTrack(RTPTrack track)
```

Set RTP track

Parameters:

track - RTP track

getUDPTransport

```
public com.wowza.wms.rtp.transport.IUDPTransport getUDPTransport()
```

Get the UDP transport

Returns:

UDP transport

getInIpAddress

```
public String getInIpAddress()
```

Get in IP address

Returns:

in IP address

getOutIpAddress

```
public String getOutIpAddress()
```

(continued from last page)

Get out IP address

Returns:

out IP address

getInPort

```
public int getInPort()
```

Get in port

Returns:

in port

getOutPort

```
public int getOutPort()
```

Get out port

Returns:

out port

bind

```
public void bind(int direction)
```

Bind to port

Parameters:

direction - in or out, see IUDPTransport.DIRECTION_*

unbind

```
public void unbind()
```

Unbind

shutdown

```
public void shutdown()
```

Shutdown port

getHandler

```
public IRTPMessageHandler getHandler()
```

Get the message handler

Returns:

message handler

setHandler

```
public void setHandler(IRTPMessageHandler handler)
```

Set the message handler

(continued from last page)

Parameters:

handler - message handler

sendMessage

```
public void sendMessage(byte[] message,  
    int offset,  
    int len)
```

Send a message out

Parameters:message - message
offset - offset
len - len

sendResponse

```
public void sendResponse(byte[] message)
```

Send a response

Parameters:

message - message

sendResponse

```
public void sendResponse(byte[] message,  
    int offset,  
    int len)
```

Send response

Parameters:message - message
offset - offset
len - len

sendResponse

```
public void sendResponse(byte[] message,  
    int offset,  
    int len,  
    java.net.SocketAddress destination)
```

Send response to destination

Parameters:message - message
offset - offset
len - len
destination - destination address

sessionOpened

```
public void sessionOpened(com.wowza.wms.rtp.transport.IUDPTransportSession session)
```

sessionClosed

```
public void sessionClosed(com.wowza.wms.rtp.transport.IUDPTransportSession session)
```

handleMessage

```
public void handleMessage(java.net.SocketAddress socketAddr,  
    Object message)
```

isInMulticast

```
public boolean isInMulticast()
```

Is in stream multicast

Returns:

true if multicast

isOutMulticast

```
public boolean isOutMulticast()
```

Is out stream multicast

Returns:

true if multicast

isMulticast

```
public boolean isMulticast()
```

Is multicast

Returns:

true if multicast

getTTL

```
public int getTTL()
```

Get time to live (milliseconds)

Returns:

time to live (milliseconds)

setTTL

```
public void setTTL(int ttl)
```

Set time to live (milliseconds)

Parameters:

ttl - time to live (milliseconds)

getAddressCount

```
public int getAddressCount()
```

Get address count

Returns:

address count

setAddressCount

```
public void setAddressCount(int addressCount)
```

Set address count

Parameters:

addressCount - address count

com.wowza.wms.rtp.model Class RTPPushPublishSession

java.lang.Object

└--com.wowza.wms.rtp.model.RTPPushPublishSession

public class **RTPPushPublishSession**
extends Object

RTPPushPublishSession: RTP push publishing session

Constructor Summary

public	RTPPushPublishSession()
--------	-----------------------------------------

Method Summary

RTPSession	getRTPSession() Get RTP session
String	getSDPData() Get SDP data
void	setRTPSession(RTPSession rtpSession) Set RTP session
void	setSDPData(String sdpData) Set SDP data

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

RTPPushPublishSession

public **RTPPushPublishSession()**

Methods

getSDPData

public String **getSDPData()**

Get SDP data

(continued from last page)

Returns:SDP data

setSDPData

```
public void setSDPData(String sdpData)
```

Set SDP data

Parameters:sdpData - SDP data

getRTPSession

```
public RTPSession getRTPSession()
```

Get RTP session

Returns:RTP session

setRTPSession

```
public void setRTPSession(RTPSession rtpSession)
```

Set RTP session

Parameters:rtpSession - RTP session

com.wowza.wms.rtp.model Class RTPSession

java.lang.Object

└-com.wowza.wms.rtp.model.RTPSession

public class **RTPSession**
extends Object

RTPSession: RTP session

Field Summary

protected	actionListeners
protected	appInstance
protected	appInstanceShutdown
protected	audioPacketizers
protected	authenticatePlayHandler
protected	authenticatePublishHandler
public static final	AUTHMETHOD_PLAY Value: 1
public static final	AUTHMETHOD_PUBLISH Value: 2
public static final	AUTHMETHOD_UNKNOWN Value: 0
protected	connectionHolder
protected	cookieStr
protected	debugRTSPSession
protected	elapsedTime
protected	idleFrequency
protected	idleHandler

protected	<u>ioPerformanceCounter</u>
protected	<u>ip</u>
protected	<u>isAnnounce</u>
protected	<u>isConnected</u>
protected	<u>isDescribe</u>
protected	<u>isSessionValid</u>
protected	<u>lastAuthenticateMethod</u>
protected	<u>loggedConnect</u>
protected	<u>properties</u>
protected	<u>queryStr</u>
protected	<u>redirectSession</u>
protected	<u>redirectSessionCode</u>
protected	<u>redirectSessionMessage</u>
protected	<u>redirectSessionURL</u>
protected	<u>referrer</u>
protected	<u>rtpWriteListener</u>
protected	<u>rtspPlayRangeStart</u>
protected	<u>rtspPlayRangeStop</u>
protected	<u>rtspTunnelingSessionId</u>
protected	<u>serverIp</u>
protected	<u>serverPort</u>
protected	<u>sessionId</u>
protected	<u>shutdownClient</u>
protected	<u>streamPacketizers</u>

protected	streams
protected	streamsOrder
protected	timeCreated
protected	totalIOPerformance2Last
protected	totalIOPerformanceLast
protected	uri
protected	userAgent
protected	vhost
protected	videoPacketizers

Constructor Summary

public	RTPSession (String sessionId) Constructor
--------	--------------------------------------------------------------

Method Summary

void	acceptSession () Accept this session
void	addActionListener (IRTSPActionNotify actionListener) Add action listener
void	addIOPerformance (IOPerformanceCounter totalIOPerformanceResult) Internal use
void	addIOPerformance2 (IOPerformanceCounter totalIOPerformanceResult) Internal use
void	addRTSPStream (RTPStream stream) Add RTP stream
void	clearLoggingValues () Clear logging values, Internal use.
IApplicationInstance	getAppInstance () Get application instance
RTPPacketizerItem	getAudioPacketizerItem (RTPContext rtpContext, IApplicationInstance appInstance, int codecId) Get audio packetizer for a given codec id.
IAuthenticateRTSP	getAuthenticatePlayHandler () Get the authentication play handler

<u>IAuthenticateRTSP</u>	<u>getAuthenticatePublishHandler()</u> Get the RTP authentication handler
ConnectionHolder	<u>getConnectionHolder()</u> Get connection holder, Internal use.
String	<u>getCookieStr()</u> Get cookie string
<u>ElapsedTimer</u>	<u>getElapsedTime()</u> Get the elapsed timer for this RTP session
int	<u>getIdleFrequency()</u> Get idle frequency (milliseconds)
RTPIdleHandler	<u>getIdleHandler()</u> Get idle handler
<u>IOPerformanceCounter</u>	<u>getIOPerformanceCounter()</u> Get IO performance counter
String	<u>getIp()</u> Get remote IP address
int	<u>getLastAuthenticateMethod()</u> Get the last method received
<u>WMSProperties</u>	<u>getProperties()</u> Get properties
String	<u>getQueryStr()</u> Get query string
int	<u>getRedirectSessionCode()</u>
String	<u>getRedirectSessionMessage()</u>
String	<u>getRedirectSessionURL()</u>
String	<u>getReferrer()</u> Get referrer
RTPWriteListener	<u>getRTPWriteListener()</u> Get the RTP write listener for this session
double	<u>getRTSPPlayRangeStart()</u> Get play start range, Internal use.
double	<u>getRTSPPlayRangeStop()</u> Get play stop range, Internal use.
<u>RTPStream</u>	<u>getRTSPStream()</u> Get the default RTP Stream (all RTP sessions have a single RTP Stream)
<u>RTPStream</u>	<u>getRTSPStream(String streamId)</u> Get RTP Stream

String	<u>getRTSPTunnelingSessionId()</u> Get the RTSP/RTP tunneling session id
String	<u>getServerIp()</u> Get the server IP address
int	<u>getServerPort()</u> Get server port
String	<u>getSessionId()</u> Get session id
RTPPacketizerItem	<u>getStreamPacketizerItem(RTPContext rtpContext, IApplicationInstance appInstance, int codecId)</u> Get stream packetizer for a given codec id.
String	<u>getTimeRunning()</u> Get the time running for this RTP session
double	<u>getTimeRunningSeconds()</u> Get the number of second this RTP session has been running
String	<u>getUri()</u> Get URI
String	<u>getUserAgent()</u> Get user agent
<u>IVHost</u>	<u>getVHost()</u> Get vhost
RTPPacketizerItem	<u>getVideoPacketizerItem(RTPContext rtpContext, IApplicationInstance appInstance, int codecId)</u> Get video packetizer for a given codec id.
boolean	<u>isAnnounce()</u> Has ANNOUNCE command been called on this session
boolean	<u>isAnnounceOrDescribe()</u> Has announce or described been called
boolean	<u>isConnected()</u> Is session connection
boolean	<u>isDebugRTSPSession()</u> True if debugging RTSP session
boolean	<u>isDescribe()</u> Has DESCRIBE command been called on this session
boolean	<u>isLoggedConnect()</u> Is connect logged
boolean	<u>isRedirectSession()</u>
boolean	<u>isSessionValid()</u> Is this session valid
boolean	<u>isShutdownClient()</u> Is RTP session shutdown

void	<code>onAnnounce</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on ANNOUNCE command
void	<code>onDescribe</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on DESCRIBE command
void	<code>onGetParameter</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on GET_PARAMETER command
void	<code>onOptions</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on OPTIONS command
void	<code>onPause</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on PAUSE command
void	<code>onPlay</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on PLAY command
void	<code>onRecord</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on RECORD command
void	<code>onRedirect</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on REDIRECT command
void	<code>onSetParameter</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on SET_PARAMETER command
void	<code>onSetup</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on SETUP command
void	<code>onTeardown</code> (com.wowza.wms.rtsp.RTSPRequestMessage req, com.wowza.wms.rtsp.RTSPResponseMessages resp) Invoked on TEARDOWN command
void	<code>putAudioPacketizerItem</code> (int codecId, String classPath) Set the audio packetizer for a given codec id
void	<code>putStreamPacketizerItem</code> (int codecId, String classPath) Set the stream packetizer for a given codec id
void	<code>putVideoPacketizerItem</code> (int codecId, String classPath) Set the video packetizer for a given codec id
void	<code>redirectSession</code> (String redirectSessionURL)
void	<code>redirectSession</code> (String redirectSessionURL, int redirectSessionCode)
void	<code>rejectSession</code> () Reject this session

void	<u>removeActionListener</u> (<u>IRTSPActionNotify</u> actionListener) Remove action listener
<u>RTPStream</u>	<u>removeRTSPStream</u> (String streamId) Remove RTP stream
void	<u>setAnnounce</u> (boolean isAnnounce) Set ANNOUNCE command been called on this session
void	<u>setAppInstance</u> (<u>IApplicationInstance</u> appInstance) Set application instance
void	<u>setAuthenticatePlayHandler</u> (<u>IAuthenticateRTSP</u> authenticatePlayHandler) Set the authentication play handler
void	<u>setAuthenticatePublishHandler</u> (<u>IAuthenticateRTSP</u> authenticatePublishHandler) Set the RTP authentication handler
void	<u>setConnected</u> (boolean isConnected) Set session is connected
void	<u>setCookieStr</u> (String cookieStr) Set cooking string
void	<u>setDebugRTSPSession</u> (boolean debugRTSPSession) Set debugging RTSP session
void	<u>setDescribe</u> (boolean isDescribe) Set DESCRIBE command been called on this session
void	<u>setIdleFrequency</u> (int idleFrequency) Set idle frequency (milliseconds)
void	<u>setIdleHandler</u> (RTPIIdleHandler idleHandler) Set idle handler
void	<u>setIOPerformanceCounter</u> (<u>IOPerformanceCounter</u> ioPerformanceCounter) Set IO performance counter
void	<u>setIp</u> (String ip) Set remote IP address
void	<u>setLastAuthenticateMethod</u> (int lastAuthenticateMethod) Set last method received
void	<u>setLoggedConnect</u> (boolean loggedConnect) Set connect logged
void	<u>setQueryStr</u> (String queryStr) Set query string
void	<u>setRedirectSession</u> (boolean redirectSession)
void	<u>setRedirectSessionCode</u> (int redirectSessionCode)
void	<u>setRedirectSessionMessage</u> (String redirectSessionMessage)

void	<u>setRedirectSessionURL</u> (String redirectSessionURL)
void	<u>setReferrer</u> (String referrer) Set referrer
void	<u>setRTSPPlayRangeStart</u> (double rtspPlayRangeStart) Set play start range, Internal use.
void	<u>setRTSPPlayRangeStop</u> (double rtspPlayRangeStop) Set play stop range, Internal use.
void	<u>setRTSPTunnelingSessionId</u> (String rtspTunnelingSessionId) Set the RTSP/RTP tunneling session id
void	<u>setServerIp</u> (String serverIp) Set the server IP address
void	<u>setServerPort</u> (int serverPort) Set server port
void	<u>setSessionId</u> (String sessionId) Set session id
void	<u>setSessionValid</u> (boolean isSessionValid) Set session valid
void	<u>setShutdownClient</u> (boolean shutdownClient) Set RTP session shutdown
void	<u>setUri</u> (String uri) Set URI
void	<u>setUserAgent</u> (String userAgent) Set user agent
void	<u>setVHost</u> (<u>IVHost</u> vhost) Set vhost
void	<u>shutdown</u> () shutdown RTP session, Internal use.
void	<u>shutdown</u> (RTPRequestStatus status) shutdown RTP session, Internal use.
void	<u>touch</u> () Touch the stream so it doesn't timeout
void	<u>updateLoggingValues</u> () Update logging values, Internal use.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

(continued from last page)

AUTHMETHOD_UNKNOWN

```
public static final int AUTHMETHOD_UNKNOWN
```

Constant value: **0**

AUTHMETHOD_PLAY

```
public static final int AUTHMETHOD_PLAY
```

Constant value: **1**

AUTHMETHOD_PUBLISH

```
public static final int AUTHMETHOD_PUBLISH
```

Constant value: **2**

sessionId

```
protected java.lang.String sessionId
```

rtspTunnelingSessionId

```
protected java.lang.String rtspTunnelingSessionId
```

streams

```
protected java.util.Map streams
```

streamsOrder

```
protected java.util.List streamsOrder
```

vhost

```
protected com.wowza.wms.vhost.IVHost vhost
```

userAgent

```
protected java.lang.String userAgent
```

(continued from last page)

cookieStr

protected java.lang.String **cookieStr**

ip

protected java.lang.String **ip**

isSessionValid

protected boolean **isSessionValid**

authenticatePlayHandler

protected com.wowza.wms.authentication.IAuthenticateRTSP **authenticatePlayHandler**

authenticatePublishHandler

protected com.wowza.wms.authentication.IAuthenticateRTSP **authenticatePublishHandler**

lastAuthenticateMethod

protected int **lastAuthenticateMethod**

appInstance

protected com.wowza.wms.application.IApplicationInstance **appInstance**

appInstanceShutdown

protected com.wowza.wms.application.IApplicationInstance **appInstanceShutdown**

loggedConnect

protected boolean **loggedConnect**

properties

protected com.wowza.wms.application.WMSProperties **properties**

(continued from last page)

isDescribeprotected boolean **isDescribe**

isAnnounceprotected boolean **isAnnounce**

rtpWriteListenerprotected com.wowza.wms.rtp.model.RTPWriteListener **rtpWriteListener**

timeCreatedprotected long **timeCreated**

ioPerformanceCounterprotected com.wowza.util.IOPerformanceCounter **ioPerformanceCounter**

totalIOPerformanceLastprotected com.wowza.util.IOPerformanceCounter **totalIOPerformanceLast**

totalIOPerformance2Lastprotected com.wowza.util.IOPerformanceCounter **totalIOPerformance2Last**

connectionHolderprotected com.wowza.wms.client.ConnectionHolder **connectionHolder**

isConnectedprotected boolean **isConnected**

(continued from last page)

idleHandler

protected com.wowza.wms.rtp.model.RTPIdleHandler **idleHandler**

serverIp

protected java.lang.String **serverIp**

serverPort

protected int **serverPort**

uri

protected java.lang.String **uri**

referrer

protected java.lang.String **referrer**

queryStr

protected java.lang.String **queryStr**

actionListeners

protected java.util.List **actionListeners**

elapsedTime

protected com.wowza.util.ElapsedTimer **elapsedTime**

idleFrequency

protected int **idleFrequency**

debugRTSPSession

protected boolean **debugRTSPSession**

(continued from last page)

rtspPlayRangeStart

protected double **rtspPlayRangeStart**

rtspPlayRangeStop

protected double **rtspPlayRangeStop**

shutdownClient

protected boolean **shutdownClient**

audioPacketizers

protected java.util.Map **audioPacketizers**

videoPacketizers

protected java.util.Map **videoPacketizers**

streamPacketizers

protected java.util.Map **streamPacketizers**

redirectSession

protected boolean **redirectSession**

redirectSessionCode

protected int **redirectSessionCode**

redirectSessionMessage

protected java.lang.String **redirectSessionMessage**

(continued from last page)

redirectSessionURL

protected java.lang.String **redirectSessionURL**

Constructors

RTPSession

public **RTPSession**(String sessionId)

Constructor

Parameters:

sessionId - session id

Methods

acceptSession

public void **acceptSession**()

Accept this session

rejectSession

public void **rejectSession**()

Reject this session

getSessionId

public String **getSessionId**()

Get session id

Returns:

session id

setSessionId

public void **setSessionId**(String sessionId)

Set session id

Parameters:

sessionId - session id

addRTSPStream

public void **addRTSPStream**([RTPStream](#) stream)

Add RTP stream

Parameters:

stream - RTP stream

removeRTSPStream

```
public RTSPStream removeRTSPStream(String streamId)
```

Remove RTP stream

Parameters:

streamId - stream id

Returns:

RTP stream

getRTSPStream

```
public RTSPStream getRTSPStream(String streamId)
```

Get RTP Stream

Parameters:

streamId - stream id

Returns:

RTP Stream

getRTSPStream

```
public RTSPStream getRTSPStream()
```

Get the default RTP Stream (all RTP sessions have a single RTP Stream)

Returns:

RTP stream

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:

vhost

setVHost

```
public void setVHost(IVHost vhost)
```

Set vhost

Parameters:

vhost - vhost

getUserAgent

```
public String getUserAgent()
```

Get user agent

(continued from last page)

Returns:

user agent

setUserAgent

```
public void setUserAgent(String userAgent)
```

Set user agent

Parameters:userAgent - user agent

touch

```
public void touch()
```

Touch the stream so it doesn't timeout

shutdown

```
public void shutdown()
```

shutdown RTP session, Internal use.

shutdown

```
public void shutdown(RTPRequestStatus status)
```

shutdown RTP session, Internal use.

Parameters:status

isSessionValid

```
public boolean isSessionValid()
```

Is this session valid

Returns:true if valid

setSessionValid

```
public void setSessionValid(boolean isSessionValid)
```

Set session valid

Parameters:isSessionValid - true if valid

getAuthenticatePublishHandler

```
public IAuthenticateRTSP getAuthenticatePublishHandler()
```

Get the RTP authentication handler

Returns:

(continued from last page)

RTP authentication handler

setAuthenticatePublishHandler

```
public void setAuthenticatePublishHandler(IAuthenticateRTSP  
authenticatePublishHandler)
```

Set the RTP authentication handler

Parameters:

authenticatePublishHandler - RTP authentication handler

getAuthenticatePlayHandler

```
public IAuthenticateRTSP getAuthenticatePlayHandler()
```

Get the authentication play handler

Returns:

authentication play handler

setAuthenticatePlayHandler

```
public void setAuthenticatePlayHandler(IAuthenticateRTSP authenticatePlayHandler)
```

Set the authentication play handler

Parameters:

authenticatePlayHandler - authentication play handler

getLastAuthenticateMethod

```
public int getLastAuthenticateMethod()
```

Get the last method received

Returns:

last method received

setLastAuthenticateMethod

```
public void setLastAuthenticateMethod(int lastAuthenticateMethod)
```

Set last method received

Parameters:

lastAuthenticateMethod - last method received

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get application instance

Returns:

application instance

(continued from last page)

setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set application instance

Parameters:

appInstance - application instance

isLoggedConnect

```
public boolean isLoggedConnect()
```

Is connect logged

Returns:

true if logged

setLoggedConnect

```
public void setLoggedConnect(boolean loggedConnect)
```

Set connect logged

Parameters:

loggedConnect - true if logged

getIp

```
public String getIp()
```

Get remote IP address

Returns:

remote IP address

setIp

```
public void setIp(String ip)
```

Set remote IP address

Parameters:

ip - remote IP address

getProperties

```
public WMSPProperties getProperties()
```

Get properties

Returns:

properties

isDescribe

```
public boolean isDescribe()
```

(continued from last page)

Has DESCRIBE command been called on this session

Returns:

true if called

setDescribe

```
public void setDescribe(boolean isDescribe)
```

Set DESCRIBE command been called on this session

Parameters:

isDescribe - true if called

isAnnounce

```
public boolean isAnnounce()
```

Has ANNOUNCE command been called on this session

Returns:

true if called

setAnnounce

```
public void setAnnounce(boolean isAnnounce)
```

Set ANNOUNCE command been called on this session

Parameters:

isAnnounce - true if called

isAnnounceOrDescribe

```
public boolean isAnnounceOrDescribe()
```

Has announce or described been called

Returns:

true if either called

getRTPWriteListener

```
public RTPWriteListener getRTPWriteListener()
```

Get the RTP write listener for this session

Returns:

RTP write listener

addIOPerformance

```
public void addIOPerformance(IOPerformanceCounter totalIOPerformanceResult)
```

Internal use

Parameters:

totalIOPerformanceResult - IO performance counter

addIOPerformance2

```
public void addIOPerformance2(IOPerformanceCounter totalIOPerformanceResult)
```

Internal use

Parameters:

totalIOPerformanceResult - IO performance counter

getConnectionHolder

```
public ConnectionHolder getConnectionHolder()
```

Get connection holder, Internal use.

Returns:

connection holder

isConnected

```
public boolean isConnected()
```

Is session connection

Returns:

true if connected

setConnected

```
public void setConnected(boolean isConnected)
```

Set session is connected

Parameters:

isConnected - true if connected

getIdleHandler

```
public RTPIdleHandler getIdleHandler()
```

Get idle handler

Returns:

idle handler

setIdleHandler

```
public void setIdleHandler(RTPIdleHandler idleHandler)
```

Set idle handler

Parameters:

idleHandler - idle handler

getServerIp

```
public String getServerIp()
```

(continued from last page)

Get the server IP address

Returns:

IP address

setServerIp

```
public void setServerIp(String serverIp)
```

Set the server IP address

Parameters:

serverIp - IP address

getServerPort

```
public int getServerPort()
```

Get server port

Returns:

server port

setServerPort

```
public void setServerPort(int serverPort)
```

Set server port

Parameters:

serverPort - server port

getUri

```
public String getUri()
```

Get URI

Returns:

URI

setUri

```
public void setUri(String uri)
```

Set URI

Parameters:

uri - URI

getReferrer

```
public String getReferrer()
```

Get referrer

Returns:

referrer

setReferrer

```
public void setReferrer(String referrer)
```

Set referrer

Parameters:

referrer - referrer

getQueryStr

```
public String getQueryStr()
```

Get query string

Returns:

query string

setQueryStr

```
public void setQueryStr(String queryStr)
```

Set query string

Parameters:

queryStr - query string

updateLoggingValues

```
public void updateLoggingValues()
```

Update logging values, Internal use.

clearLoggingValues

```
public void clearLoggingValues()
```

Clear logging values, Internal use.

addActionListener

```
public void addActionListener(IRTSPActionNotify actionListener)
```

Add action listener

Parameters:

actionListener - action listener

removeActionListener

```
public void removeActionListener(IRTSPActionNotify actionListener)
```

Remove action listener

Parameters:

actionListener - action listener

onDescribe

```
public void onDescribe(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on DESCRIBE command

Parameters:

req - RTP request
resp - RTP response

onAnnounce

```
public void onAnnounce(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on ANNOUNCE command

Parameters:

req - RTP request
resp - RTP response

onGetParameter

```
public void onGetParameter(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on GET_PARAMETER command

Parameters:

req - RTP request
resp - RTP response

onSetParameter

```
public void onSetParameter(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on SET_PARAMETER command

Parameters:

req - RTP request
resp - RTP response

onOptions

```
public void onOptions(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on OPTIONS command

Parameters:

req - RTP request
resp - RTP response

(continued from last page)

onPause

```
public void onPause(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on PAUSE command

Parameters:

req - RTP request
resp - RTP response

onPlay

```
public void onPlay(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on PLAY command

Parameters:

req - RTP request
resp - RTP response

onRecord

```
public void onRecord(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on RECORD command

Parameters:

req - RTP request
resp - RTP response

onRedirect

```
public void onRedirect(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on REDIRECT command

Parameters:

req - RTP request
resp - RTP response

onSetup

```
public void onSetup(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

Invoked on SETUP command

Parameters:

req - RTP request
resp - RTP response

onTeardown

```
public void onTeardown(com.wowza.wms.rtsp.RTSPRequestMessage req,  
    com.wowza.wms.rtsp.RTSPResponseMessages resp)
```

(continued from last page)

Invoked on TEARDOWN command

Parameters:

req - RTP request
resp - RTP response

getIdleFrequency

```
public int getIdleFrequency()
```

Get idle frequency (milliseconds)

Returns:

idle frequency (milliseconds)

setIdleFrequency

```
public void setIdleFrequency(int idleFrequency)
```

Set idle frequency (milliseconds)

Parameters:

idleFrequency - idle frequency (milliseconds)

isDebugRTSPSession

```
public boolean isDebugRTSPSession()
```

True if debugging RTSP session

Returns:

true if debugging RTSP session

setDebugRTSPSession

```
public void setDebugRTSPSession(boolean debugRTSPSession)
```

Set debugging RTSP session

Parameters:

debugRTSPSession - true if debugging RTSP session

getRTSPTunnelingSessionId

```
public String getRTSPTunnelingSessionId()
```

Get the RTSP/RTP tunneling session id

Returns:

RTSP/RTP tunneling session id

setRTSPTunnelingSessionId

```
public void setRTSPTunnelingSessionId(String rtspTunnelingSessionId)
```

Set the RTSP/RTP tunneling session id

Parameters:

(continued from last page)

`rtspTunnelingSessionId` - RTSP/RTP tunneling session id

getRTSPPlayRangeStart

```
public double getRTSPPlayRangeStart()
```

Get play start range, Internal use.

Returns:

start range

setRTSPPlayRangeStart

```
public void setRTSPPlayRangeStart(double rtspPlayRangeStart)
```

Set play start range, Internal use.

Parameters:

`rtspPlayRangeStart` - start range

getRTSPPlayRangeStop

```
public double getRTSPPlayRangeStop()
```

Get play stop range, Internal use.

Returns:

stop range

setRTSPPlayRangeStop

```
public void setRTSPPlayRangeStop(double rtspPlayRangeStop)
```

Set play stop range, Internal use.

Parameters:

`rtspPlayRangeStop` - stop range

getCookieStr

```
public String getCookieStr()
```

Get cookie string

Returns:

cookie string

setCookieStr

```
public void setCookieStr(String cookieStr)
```

Set cooking string

Parameters:

`cookieStr` - cooking string

(continued from last page)

getIOPerformanceCounter

```
public IOPerformanceCounter getIOPerformanceCounter()
```

Get IO performance counter

Returns:

IO performance counter

setIOPerformanceCounter

```
public void setIOPerformanceCounter(IOPerformanceCounter ioPerformanceCounter)
```

Set IO performance counter

Parameters:

ioPerformanceCounter - IO performance counter

isShutdownClient

```
public boolean isShutdownClient()
```

Is RTP session shutdown

Returns:

true if shutdown

setShutdownClient

```
public void setShutdownClient(boolean shutdownClient)
```

Set RTP session shutdown

Parameters:

shutdownClient - true if shutdown

getAudioPacketizerItem

```
public RTPPacketizerItem getAudioPacketizerItem(RTPContext rtpContext,  
IApplicationInstance appInstance,  
int codecId)
```

Get audio packetizer for a given codec id.

Parameters:

rtpContext - RTP context

appInstance - application instance

codecId - codec id

Returns:

packetizer info

getVideoPacketizerItem

```
public RTPPacketizerItem getVideoPacketizerItem(RTPContext rtpContext,  
IApplicationInstance appInstance,  
int codecId)
```

Get video packetizer for a given codec id.

(continued from last page)

Parameters:

rtpContext - RTP context
appInstance - application instance
codecId - codec id

Returns:

packetizer info

getStreamPacketizerItem

```
public RTPPacketizerItem getStreamPacketizerItem(RTPContext rtpContext,  
    IApplicationInstance appInstance,  
    int codecId)
```

Get stream packetizer for a given codec id.

Parameters:

rtpContext - RTP context
appInstance - application instance
codecId - codec id

Returns:

packetizer info

putAudioPacketizerItem

```
public void putAudioPacketizerItem(int codecId,  
    String classPath)
```

Set the audio packetizer for a given codec id

Parameters:

codecId - codec id
classPath - class path

putVideoPacketizerItem

```
public void putVideoPacketizerItem(int codecId,  
    String classPath)
```

Set the video packetizer for a given codec id

Parameters:

codecId - codec id
classPath - class path

putStreamPacketizerItem

```
public void putStreamPacketizerItem(int codecId,  
    String classPath)
```

Set the stream packetizer for a given codec id

Parameters:

codecId - codec id
classPath - class path

(continued from last page)

getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get the elapsed timer for this RTP session

Returns:

elapsed timer

getTimeRunning

```
public String getTimeRunning()
```

Get the time running for this RTP session

Returns:

time running as a string

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get the number of second this RTP session has been running

Returns:

number of second this RTP session has been running

isRedirectSession

```
public boolean isRedirectSession()
```

setRedirectSession

```
public void setRedirectSession(boolean redirectSession)
```

getRedirectSessionCode

```
public int getRedirectSessionCode()
```

setRedirectSessionCode

```
public void setRedirectSessionCode(int redirectSessionCode)
```

getRedirectSessionURL

```
public String getRedirectSessionURL()
```

(continued from last page)

setRedirectSessionURL

```
public void setRedirectSessionURL(String redirectSessionURL)
```

redirectSession

```
public void redirectSession(String redirectSessionURL)
```

redirectSession

```
public void redirectSession(String redirectSessionURL,  
    int redirectSessionCode)
```

getRedirectSessionMessage

```
public String getRedirectSessionMessage()
```

setRedirectSessionMessage

```
public void setRedirectSessionMessage(String redirectSessionMessage)
```

com.wowza.wms.rtp.model

Class RTPSessions

java.lang.Object

└─com.wowza.wms.rtp.model.RTPSessions

public class **RTPSessions**
extends Object

RTPSessions: collection of RTP sessions

Constructor Summary

public	RTPSessions (IVHost vhost) Constructor
--------	----------------------------------------------------------------------------

Method Summary

RTPSession	addSession (RTPSession session) Add RTP session
void	addSessionListener (IRTPSessionNotify listener) Add a RTP session listener
String	getNextSessionId () Get next RTP session id for new session
RTPSession	getSession (String sessionId) Get RTP session by session id
java.util.List	getSessionIds () Get list of current RTP session ids
IVHost	getVHost () Get vhost
void	notifySessionCreate (IApplicationInstance appInstance, RTPSession rtpSession) Notify session create
void	notifySessionCreate (RTPSession rtpSession) Notify session create
void	notifySessionDestroy (IApplicationInstance appInstance, RTPSession rtpSession) Notify session destroy
void	notifySessionDestroy (RTPSession rtpSession) Notify session destroy
void	releaseSessionId (String sessionIdStr) Release an RTP session id

RTPSession	removeSession (RTPSession session) Remove RTP session by object
RTPSession	removeSession (String sessionId) Remove RTP session by session id
void	removeSessionListener (IRTPSessionNotify listener) Remove an RTP session listener

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

RTPSessions

```
public RTPSessions(IVHost vhost)
```

Constructor

Parameters:

vhost - vhost

Methods

getNextSessionId

```
public String getNextSessionId()
```

Get next RTP session id for new session

Returns:

RTP session id

getSessionIds

```
public java.util.List getSessionIds()
```

Get list of current RTP session ids

Returns:

list of current RTP session ids

releaseSessionId

```
public void releaseSessionId(String sessionIdStr)
```

Release an RTP session id

Parameters:

sessionIdStr - RTP session id

(continued from last page)

getSession

```
public RTPSession getSession(String sessionId)
```

Get RTP session by session id

Parameters:

sessionId - session id

Returns:

RTP session

removeSession

```
public RTPSession removeSession(String sessionId)
```

Remove RTP session by session id

Parameters:

sessionId - session id

Returns:

RTP session if removed

removeSession

```
public RTPSession removeSession(RTPSession session)
```

Remove RTP session by object

Parameters:

session - RTP session

Returns:

RTP session if removed

addSession

```
public RTPSession addSession(RTPSession session)
```

Add RTP session

Parameters:

session - RTP session

Returns:

RTP session added

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:

vhost

(continued from last page)

addSessionListener

```
public void addSessionListener(IRTPSessionNotify listener)
```

Add a RTP session listener

Parameters:

listener - RTP session listener

removeSessionListener

```
public void removeSessionListener(IRTPSessionNotify listener)
```

Remove an RTP session listener

Parameters:

listener - RTP session listener

notifySessionCreate

```
public void notifySessionCreate(IApplicationInstance appInstance,  
    RTPSession rtpSession)
```

Notify session create

Parameters:

appInstance - application instance

rtpSession - RTP session

notifySessionDestroy

```
public void notifySessionDestroy(IApplicationInstance appInstance,  
    RTPSession rtpSession)
```

Notify session destroy

Parameters:

appInstance - application instance

rtpSession - RTP session

notifySessionCreate

```
public void notifySessionCreate(RTPSession rtpSession)
```

Notify session create

Parameters:

rtpSession - RTP session

notifySessionDestroy

```
public void notifySessionDestroy(RTPSession rtpSession)
```

Notify session destroy

Parameters:

rtpSession - RTP session

com.wowza.wms.rtp.model Class RTPStream

java.lang.Object

└--com.wowza.wms.rtp.model.RTPStream

public class **RTPStream**
extends Object

RTPStream: RTP Stream class which encapsulates an IMediaStream class for RTP streaming.

Field Summary

public static final	AVSYNCMETHODS_RTPTIMECODE Value: 3
public static final	AVSYNCMETHODS_SENDERREPORT Value: 1
public static final	AVSYNCMETHODS_SYSTEMCLOCK Value: 2
public static final	AVSYNCMETHODS_UNKNOWN Value: 0
public static final	MODE_PLAY Value: 1
public static final	MODE_PUBLISH Value: 2
public static final	MODE_UNKNOWN Value: 0
public static final	SDPLOCATION_AUDIO Value: 1
public static final	SDPLOCATION_STREAM Value: 0
public static final	SDPLOCATION_VIDEO Value: 2
public static final	STREAMINFO_SESSIONATTRIBUTES Value: attributes

public static final	STREAMINFO_SESSIONBANDWIDTH Value: bandwidth
public static final	STREAMINFO_SESSIONCONNECTIONDATA Value: connectiondata
public static final	STREAMINFO_SESSIONEMAILADDRESS Value: emailaddress
public static final	STREAMINFO_SESSIONINFORMATION Value: information
public static final	STREAMINFO_SESSIONNAME Value: name
public static final	STREAMINFO_SESSIONPHONENUMBER Value: phonenummer
public static final	STREAMINFO_SESSIONPORIGIN Value: origin
public static final	STREAMINFO_SESSIONPROTOCOLVERSION Value: protocolversion
public static final	STREAMINFO_SESSIONREPEATTIMES Value: repeattimes
public static final	STREAMINFO_SESSIONTIMEZONES Value: timezones
public static final	STREAMINFO_SESSIONTIMING Value: timing
public static final	STREAMINFO_SESSIONURI Value: uri

Constructor Summary

public	RTPStream (RTPContext context, String streamId) Constructor
--------	-------------------------------------------------------------------------------------------------

Method Summary

void	addStreamAttribute (String key, String value) Add a name value pair to the stream attribute collection
void	addStreamInfo (String key, String value) Add a name value pair to the stream info collection

void	<u>addTrack</u> (RTPTrack track) Add a track
void	<u>addTrackId</u> (String seq, String trackId) Add track
void	<u>addTrackInternal</u> (RTPTrack track) Add RTP track
void	<u>announce</u> (RTPRequestStatus status) Execute announce command
void	<u>attachToWMSSession</u> (RtmpSessionInfo wmsSessionInfo) Attach to WMS session, Internal use
static int	<u>avSyncNameToId</u> (String avSyncName) Get audio/video sync id from name
void	<u>checkSendMetadata</u> (long adjTimecode, RTPTrack rtpTrack) Check to see if we have sent onMetadata event, if not send
void	<u>clearRTSPSessionExtraLines</u> () Clear SDP extra lines
void	<u>clearTracks</u> () Clear all tracks
boolean	<u>createStream</u> (RTPRequestStatus status) Create IMediaStream, Internal use.
String	<u>describe</u> (RTPSession rtspSession, int isStreamPacketizer, RTPRequestStatus status) Execute describe command
String	<u>describe</u> (RTPSession rtspSession, RTPRequestStatus status) Execute describe command
void	<u>detachFromWMSSession</u> (RtmpSessionInfo wmsSessionInfo) Detach from WMS session, Internal use.
void	<u>extractCodecConfigFromTrackInfo</u> () Extract codec config information from SDP data
String	<u>formatRTPInfo</u> (long timecode, int videoSeq, int audioSeq) Format RTP info
<u>IApplicationInstance</u>	<u>getAppInstance</u> () Get application instance
String	<u>getAppInstanceName</u> () Get the application instance name
String	<u>getAppName</u> () Get the application name
RTPTrack	<u>getAudioTrack</u> () Get the most likely audio track
int	<u>getAutoAllocateInterleavePorts</u> ()

int	<u>getAVSyncMethod()</u> Get the audio/video sync method.
double	<u>getDuration()</u> Get the duration of the stream if video on demand
String	<u>getHost()</u> Get host
<u>AMFPacket[]</u>	<u>getLastPacketsByType()</u> (<u>IMediaReader</u> localReader, double startTime) Analyzes stream to get information, Internal use.
<u>AMFPacket[]</u>	<u>getLastPacketsByType()</u> (<u>IMediaStream</u> localStream) Analyzes stream to get information, Internal use.
int	<u>getMaxRTCPWaitTime()</u> Get max time to wait for RTCP sender reports (milliseconds)
String	<u>getMediaCasterType()</u> Get the media caster stream type for this stream
<u>IMediaReader</u>	<u>getMediaReader()</u> Get media reader if video on demand stream
byte[]	<u>getMetadataPacket()</u> Get the onMetadata packet for this RTP stream
int	<u>getMode()</u> Get the current play/publish mode
String	<u>getMPEGTSAudioLanguage()</u>
int	<u>getMPEGTSAudioPID()</u> Get the audio PID id if MPEG-TS stream
int	<u>getMPEGTSProgramID()</u>
int	<u>getMPEGTSVideoPID()</u> Get the video PID id if MPEG-TS stream
long	<u>getNormalizedNTPTimecode()</u> (long timecode) Turn a millisecond timcode into an NTP timecode
String	<u>getOutHost()</u> Get the out host
<u>RTPContext</u>	<u>getRTPContext()</u> Get the RTP context
<u>RTPDestination</u>	<u>getRTPDestination()</u> Get RTP destination
RTPStream.RTPInfo	<u>getRTPInfo()</u> (double startTime, int videoSeq, int audioSeq) Get the RTP info
String	<u>getRTSPBindIpAddress()</u> Get the bind RTSP bind IP address

String	<u>getRTSPConnectionAddressType()</u> Get the connection address type
String	<u>getRTSPConnectionIpAddress()</u> Get the connection IP address
int	<u>getRTSPMaximumPendingWriteBytes()</u> Get the maximum number of waiting bytes allow for this RTSP session
String	<u>getRTSPOriginAddressType()</u> Get the origin address type
String	<u>getRTSPOriginIpAddress()</u> Get the origin IP address
String	<u>getRTSPSessionDescription()</u> Get session description
java.util.List	<u>getRTSPSessionExtraLines()</u> Get extra SDP lines
String	<u>getRTSPSessionName()</u> Get session name
int	<u>getRTSPSessionTimeout()</u> Get RTP session timeout (milliseconds)
String	<u>getSDPLang()</u> Get the SDP language
<u>RTPSession</u>	<u>getSession()</u> Get the RTP session
<u>IMediaStream</u>	<u>getStream()</u> Get the IMediaStream
java.util.Map	<u>getStreamAttributes()</u> Get all name/value pairs in the stream attributes collection
String	<u>getStreamExt()</u> Get the stream extension
String	<u>getStreamId()</u> Get the stream id
java.util.Map	<u>getStreamInfo()</u> Get all name/value pairs in the stream info collection
String	<u>getStreamInfo(String key)</u> Get stream info by name
Object	<u>getStreamLock()</u> Get the synchronization lock for this stream
String	<u>getStreamName()</u> Get stream name
String	<u>getStreamNameLogging()</u> Get the stream name used for logging

String	<u>getStreamQueryStr()</u> Get the stream query string
long	<u>getStreamSessionId()</u> Get the stream session id
String	<u>getStreamSessionIp()</u> Get the stream session ip
long	<u>getStreamSessionVersion()</u> Get the stream session version
RTPTrack	<u>getStreamTrack()</u> Get the most likely stream track
String	<u>getStreamType()</u> Get the stream type
RTPTrack	<u>getTrack()</u> (String trackId) Get track by id
String	<u>getTrackId()</u> (String seq) Get track by sequence number
java.util.List	<u>getTrackNames()</u> Get a list of track ids
String	<u>getTransportMode()</u> Get the transport mode
int	<u>getUDPManagedDeliveryCount()</u>
int	<u>getUDPManagedDeliveryDelay()</u>
com.wowza.wms.rtp.transport.IUDPTransport	<u>getUDPTransport()</u> (boolean isMulticast) Get the UDP transport for this stream
<u>IVHost</u>	<u>getVHost()</u> Get vhost
RTPTrack	<u>getVideoTrack()</u> Get the most likely video track
long	<u>getVODLastTimeTC()</u> Get the last timecode (milliseconds) sent for video on demand
long	<u>getVODPlayLen()</u> Get the video on demand play duration (milliseconds)
long	<u>getVODStartTimeTC()</u> Get the video on demand start time (milliseconds)
void	<u>idle()</u> (org.apache.mina.common.IoSession session, RtmpResponseMessage resp) Process idle event
void	<u>incrementMediaInBytes()</u> (long bytes) Increment the media bytes in, Internal use.

boolean	<u>isAVSyncNonSR</u> () Is sync method based on RTCP packets (sender report)
boolean	<u>isCheckIpAddr</u> () Are we checking the ip address of each incoming RTP packet
boolean	<u>isCheckSSRC</u> () Are we checking the ssrc values of each incoming RTP packet
boolean	<u>isForceMPEGTSOut</u> ()
boolean	<u>isForceRTSPInterleaved</u> () True if forcing RTSP interleaved
boolean	<u>isLive</u> () Is live stream
boolean	<u>isModePlay</u> () Is this a play stream
boolean	<u>isModePublish</u> () Is this a publish stream
boolean	<u>isModeUnknown</u> () Is the stream mode unknown (publish vs play)
boolean	<u>isMPEGTSOut</u> () Is MPEG-TS out
boolean	<u>isPaused</u> () Is stream paused
boolean	<u>isPublishStreamReady</u> () See if a publishing stream has enough data to start playback
boolean	<u>isResetPlayStream</u> () Is reset stream trigger, Internal use.
boolean	<u>isResyncAudioVideoOnSR</u> () Reset audio/video sync on new RTCP packets (not just first packet)
boolean	<u>isRTPIgnoreProfileLevelId</u> ()
boolean	<u>isRTSP</u> () Is this RTP Stream managed by RTSP session
boolean	<u>isRTSPAlwaysUseSDPPorts</u> () Force RTSP to use ports in SDP data
boolean	<u>isRTSPPull</u> () Is this RTP Stream managed by RTSP session
boolean	<u>isSendSDESEvents</u> () Send RTCP SDES events
boolean	<u>isStreamStarted</u> () Is stream started

boolean	<u>isTimeout</u> (long currTime, int timeout) Is the stream timeout out
void	<u>lockRepeaterStreams</u> (java.util.List streamNames) Lock a list of live repeater stream names, Internal use.
void	<u>pause</u> (RTPRequestStatus status) Execute pause
RTPStreamPlayResult	<u>play</u> (RTPRequestStatus status) Execute play
RTPStreamPlayResult	<u>play</u> (RTPRequestStatus status, double startTime, double stopTime) Execute play
void	<u>putRTSPSessionExtraLine</u> (int location, String line) Add an extra line to the SDP data
RTPStreamPlayResult	<u>record</u> (RTPRequestStatus status) Execute record
RTPStreamPlayResult	<u>record</u> (RTPRequestStatus status, double startTime, double stopTime) Execute record
RTPTrack	<u>removeTrack</u> (String trackId) Remove a track by id
RTPTrack	<u>removeTrackInternal</u> (String trackId) Remove track by track id
void	<u>resetSentMetadataFlag</u> () Reset sendMetadata flag
void	<u>setAppInstanceName</u> (String appInstanceName) Set the application instance name
void	<u>setAppName</u> (String appName) Get the application name
void	<u>setAVSyncMethod</u> (int avSyncMethod) Set the audio/video sync method.
void	<u>setCheckIpAddr</u> (boolean checkIpAddr) Are we checking the ip address of each incoming RTP packet
void	<u>setCheckSSRC</u> (boolean checkSSRC) Are we checking the ssrc values of each incoming RTP packet
void	<u>setForceMPEGTSOut</u> (boolean isForceMPEGTSOut)
void	<u>setForceRTSPInterleaved</u> (boolean isForceRTSPInterleaved) True if forcing RTSP interleaved
void	<u>setHost</u> (String host) Set host
void	<u>setLive</u> (boolean isLive) Is live stream

void	<u>setMaxRTCPWaitTime</u> (int maxRTCPWaitTime) Set max time to wait for RTCP sender reports (milliseconds)
void	<u>setMode</u> (int mode) Set the play/publish mode
void	<u>setMPEGTSAudioLanguage</u> (String mpegtsAudioLanguage)
void	<u>setMPEGTSAudioPID</u> (int mpegtsAudioPID) Set the audio PID id if MPEG-TS stream
void	<u>setMPEGTSOut</u> (boolean isMPEGTSOut) Is MPEG-TS out
void	<u>setMPEGTSProgramID</u> (int mpegtsProgramId)
void	<u>setMPEGTSVideoPID</u> (int mpegtsVideoPID) Set the video PID id if MPEG-TS stream
void	<u>setOutHost</u> (String outHost) Set out host
void	<u>setResetPlayStream</u> (boolean doResetPlayStream) Set reset stream trigger
void	<u>setResyncAudioVideoOnSR</u> (boolean resyncAudioVideoOnSR) Reset audio/video sync on new RTCP packets (not just first packet)
void	<u>setRTPDestination</u> (<u>RTPDestination</u> rtpDestination) Set RTP destination
void	<u>setRTPIgnoreProfileLevelId</u> (boolean rtpIgnoreProfileLevelId)
void	<u>setRTSP</u> (boolean isRTSP) Is this RTP Stream managed by RTSP session
void	<u>setRTSPAlwaysUseSDPPorts</u> (boolean rtspAlwaysUseSDPPorts) Force RTSP to use ports in SDP data
void	<u>setRTSPBindIpAddress</u> (String rtspBindIpAddress) Set the bind RTSP bind IP address
void	<u>setRTSPConnectionAddressType</u> (String rtspConnectionAddressType) Set the connection address type
void	<u>setRTSPConnectionIpAddress</u> (String rtspConnectionIpAddress) Set the connection IP address
void	<u>setRTSPMaximumPendingWriteBytes</u> (int rtspMaximumPendingWriteBytes) Set the maximum number of waiting bytes allow for this RTSP session
void	<u>setRTSPOriginAddressType</u> (String rtspOriginAddressType) Set the origin address type
void	<u>setRTSPOriginIpAddress</u> (String rtspOriginIpAddress) Set the origin IP address

void	<u>setRTSPPull</u> (boolean isRTSPPull) Is this RTP Stream managed by RTSP session
void	<u>setRTSPSessionDescription</u> (String rtspSessionDescription) Get session description
void	<u>setRTSPSessionName</u> (String rtspSessionName) Set session name
void	<u>setRTSPSessionTimeout</u> (int rtspSessionTimeout) Set RTP session timeout (milliseconds)
void	<u>setSDPLang</u> (String sdpLang) Set the SDP language
void	<u>setSendSDESEvents</u> (boolean sendSDESEvents) Send RTCP SDES events
void	<u>setSession</u> (<u>RTPSession</u> session) Set the RTP session
void	<u>setStreamExt</u> (String streamExt) Set the stream extension
void	<u>setStreamName</u> (String streamName) Set stream name
void	<u>setStreamNameLogging</u> (String streamNameLogging) Set the stream name used for logging
void	<u>setStreamQueryStr</u> (String streamQueryStr) Set the stream query string
void	<u>setStreamSessionId</u> (long streamSessionId) Set the stream session id
void	<u>setStreamSessionIp</u> (String streamSessionIp) Set the stream session ip
void	<u>setStreamSessionVersion</u> (long streamSessionVersion) Set the stream session version
void	<u>setStreamType</u> (String streamType) Set the stream type
void	<u>setTransportMode</u> (String transportMode) Set the transport mode
void	<u>setUDPManagedDeliveryCount</u> (int udpManagedDeliveryCount)
void	<u>setUDPManagedDeliveryDelay</u> (int udpManagedDeliveryDelay)
void	<u>setVODLastTimeTC</u> (long vodLastTimeTC) Set the last timecode (milliseconds) sent for video on demand
void	<u>setVODPlayLen</u> (long vodPlayLen) Set the video on demand play duration (milliseconds)

void	<code>setVODStartTimeTC</code> (long vodStartTimeTC) Set the video on demand start time (milliseconds)
void	<code>shutdown</code> (RTPRequestStatus status) shutdown RTP stream, Internal use.
RTPTrack	<code>sloppyGetTrack</code> (String trackId) Sloppy method for finding track by name, Internal use.
boolean	<code>streamExists</code> () Return true if RTP stream contains a IMediaStream
void	<code>switchSetupToMPEGTS</code> () Switch a stream to MPEG-TS, Internal use.
void	<code>touch</code> () Touch the stream so that it does not timeout
String	<code>transportFindBestMatch</code> (String transport) Based on a trasport string from SETUP command find best match
void	<code>unlockRepeaterStreams</code> () Unlock live repeater streams

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Fields

SDPLOCATION_STREAM

```
public static final int SDPLOCATION_STREAM
```

Constant value: **0**

SDPLOCATION_AUDIO

```
public static final int SDPLOCATION_AUDIO
```

Constant value: **1**

SDPLOCATION_VIDEO

```
public static final int SDPLOCATION_VIDEO
```

Constant value: **2**

MODE_UNKNOWN

```
public static final int MODE_UNKNOWN
```

(continued from last page)

Constant value: **0**

MODE_PLAY

```
public static final int MODE_PLAY
```

Constant value: **1**

MODE_PUBLISH

```
public static final int MODE_PUBLISH
```

Constant value: **2**

AVSYNCMETHODS_UNKNOWN

```
public static final int AVSYNCMETHODS_UNKNOWN
```

Constant value: **0**

AVSYNCMETHODS_SENDERREPORT

```
public static final int AVSYNCMETHODS_SENDERREPORT
```

Constant value: **1**

AVSYNCMETHODS_SYSTEMCLOCK

```
public static final int AVSYNCMETHODS_SYSTEMCLOCK
```

Constant value: **2**

AVSYNCMETHODS_RTPTIMECODE

```
public static final int AVSYNCMETHODS_RTPTIMECODE
```

Constant value: **3**

STREAMINFO_SESSIONPROTOCOLVERSION

```
public static final java.lang.String STREAMINFO_SESSIONPROTOCOLVERSION
```

Constant value: **protocolversion**

STREAMINFO_SESSIONPORIGIN

```
public static final java.lang.String STREAMINFO_SESSIONPORIGIN
```

Constant value: **origin**

(continued from last page)

STREAMINFO_SESSIONNAME

```
public static final java.lang.String STREAMINFO_SESSIONNAME
```

Constant value: **name**

STREAMINFO_SESSIONINFORMATION

```
public static final java.lang.String STREAMINFO_SESSIONINFORMATION
```

Constant value: **information**

STREAMINFO_SESSIONURI

```
public static final java.lang.String STREAMINFO_SESSIONURI
```

Constant value: **uri**

STREAMINFO_SESSIONEMAILADDRESS

```
public static final java.lang.String STREAMINFO_SESSIONEMAILADDRESS
```

Constant value: **emailaddress**

STREAMINFO_SESSIONPHONENUMBER

```
public static final java.lang.String STREAMINFO_SESSIONPHONENUMBER
```

Constant value: **phonenumber**

STREAMINFO_SESSIONCONNECTIONDATA

```
public static final java.lang.String STREAMINFO_SESSIONCONNECTIONDATA
```

Constant value: **connectiondata**

STREAMINFO_SESSIONBANDWIDTH

```
public static final java.lang.String STREAMINFO_SESSIONBANDWIDTH
```

Constant value: **bandwidth**

STREAMINFO_SESSIONTIMING

```
public static final java.lang.String STREAMINFO_SESSIONTIMING
```

Constant value: **timing**

STREAMINFO_SESSIONREPEATTIMES

```
public static final java.lang.String STREAMINFO_SESSIONREPEATTIMES
```

(continued from last page)

Constant value: **repeattimes**

STREAMINFO_SESSIONTIMEZONES

```
public static final java.lang.String STREAMINFO_SESSIONTIMEZONES
```

Constant value: **timezones**

STREAMINFO_SESSIONATTRIBUTES

```
public static final java.lang.String STREAMINFO_SESSIONATTRIBUTES
```

Constant value: **attributes**

Constructors

RTPStream

```
public RTPStream(RTPContext context,  
                 String streamId)
```

Constructor

Parameters:

context - RTP context
streamId - stream id

Methods

getRTPContext

```
public RTPContext getRTPContext()
```

Get the RTP context

Returns:

RTP context

getStreamLock

```
public Object getStreamLock()
```

Get the synchronization lock for this stream

Returns:

synchronization lock for this stream

addTrack

```
public void addTrack(RTPTrack track)
```

Add a track

Parameters:

track - RTP track

removeTrack

```
public RTPTrack removeTrack(String trackId)
```

Remove a track by id

Parameters:

trackId - track id

Returns:

RTP track

addTrackInternal

```
public void addTrackInternal(RTPTrack track)
```

Add RTP track

Parameters:

track - RTP track

removeTrackInternal

```
public RTPTrack removeTrackInternal(String trackId)
```

Remove track by track id

Parameters:

trackId - track id

Returns:

RTP track that was removed

clearTracks

```
public void clearTracks()
```

Clear all tracks

incrementMediaInBytes

```
public void incrementMediaInBytes(long bytes)
```

Increment the media bytes in, Internal use.

Parameters:

bytes

sloppyGetTrack

```
public RTPTrack sloppyGetTrack(String trackId)
```

Sloppy method for finding track by name, Internal use.

Parameters:

trackId - track name

(continued from last page)

Returns:

RTP track

getTrack

```
public RTPTrack getTrack(String trackId)
```

Get track by id

Parameters:

trackId - track id

Returns:

RTP track

addTrackId

```
public void addTrackId(String seq,  
    String trackId)
```

Add track

Parameters:

seq - sequence number

trackId - track id

getTrackId

```
public String getTrackId(String seq)
```

Get track by sequence number

Parameters:

seq - sequence number

Returns:

RTP track

getTrackNames

```
public java.util.List getTrackNames()
```

Get a list of track ids

Returns:

list of track ids

getSession

```
public RTPSession getSession()
```

Get the RTP session

Returns:

RTP session

(continued from last page)

setSession

```
public void setSession(RTPSession session)
```

Set the RTP session

Parameters:

session - RTP session

getStreamId

```
public String getStreamId()
```

Get the stream id

Returns:

stream id

getStream

```
public IMediaStream getStream()
```

Get the IMediaStream

Returns:

stream (IMediaStream) interface

getAudioTrack

```
public RTPTrack getAudioTrack()
```

Get the most likely audio track

Returns:

RTP track

getVideoTrack

```
public RTPTrack getVideoTrack()
```

Get the most likely video track

Returns:

RTP track

getStreamTrack

```
public RTPTrack getStreamTrack()
```

Get the most likely stream track

Returns:

RTP track

addStreamInfo

```
public void addStreamInfo(String key,  
                           String value)
```

(continued from last page)

Add a name value pair to the stream info collection

Parameters:

key - name
value - value

getStreamInfo

```
public String getStreamInfo(String key)
```

Get stream info by name

Parameters:

key - name

Returns:

value

addStreamAttribute

```
public void addStreamAttribute(String key,  
                                String value)
```

Add a name value pair to the stream attribute collection

Parameters:

key - name
value - value

getVHost

```
public IVHost getVHost()
```

Get vhost

Returns:

vhost

getHost

```
public String getHost()
```

Get host

Returns:

host

setHost

```
public void setHost(String host)
```

Set host

Parameters:

host - host

(continued from last page)

streamExists

```
public boolean streamExists()
```

Return true if RTP stream contains a IMediaStream

Returns:

true if RTP stream contains a IMediaStream

isPublishStreamReady

```
public boolean isPublishStreamReady()
```

See if a publishing stream has enough data to start playback

Returns:

true, if the stream is ready for playback

lockRepeaterStreams

```
public void lockRepeaterStreams(java.util.List streamNames)
```

Lock a list of live repeater stream names, Internal use.

Parameters:

streamNames - stream names

unlockRepeaterStreams

```
public void unlockRepeaterStreams()
```

Unlock live repeater streams

getMediaCasterType

```
public String getMediaCasterType()
```

Get the media caster stream type for this stream

Returns:

media caster stream type

createStream

```
public boolean createStream(RTPRequestStatus status)
```

Create IMediaStream, Internal use.

Parameters:

status - status

Returns:

true if successful

shutdown

```
public void shutdown(RTPRequestStatus status)
```

(continued from last page)

shutdown RTP stream, Internal use.

Parameters:

status - status

getAppInstance

```
public IApplicationInstance getAppInstance( )
```

Get application instance

Returns:

application instance

isPaused

```
public boolean isPaused( )
```

Is stream paused

Returns:

true if stream is paused

getDuration

```
public double getDuration( )
```

Get the duration of the stream if video on demand

Returns:

duration in seconds

isResetPlayStream

```
public boolean isResetPlayStream( )
```

Is reset stream trigger, Internal use.

Returns:

true if reset trigger

setResetPlayStream

```
public void setResetPlayStream(boolean doResetPlayStream)
```

Set reset stream trigger

Parameters:

doResetPlayStream - true if reset trigger

record

```
public RTPStreamPlayResult record(RTPRequestStatus status)
```

Execute record

Parameters:

status - RTP status

(continued from last page)

Returns:

status

record

```
public RTPStreamPlayResult record(RTPRequestStatus status,  
    double startTime,  
    double stopTime)
```

Execute record

Parameters:

status - RTP status

startTime - playback start time

stopTime - playback stop time

Returns:

status

play

```
public RTPStreamPlayResult play(RTPRequestStatus status)
```

Execute play

Parameters:

status - RTP status

Returns:

status

play

```
public RTPStreamPlayResult play(RTPRequestStatus status,  
    double startTime,  
    double stopTime)
```

Execute play

Parameters:

status - RTP status

startTime - playback start time

stopTime - playback stop time

Returns:

status

attachToWMSSession

```
public void attachToWMSSession(RtmpSessionInfo wmsSessionInfo)
```

Attach to WMS session, Internal use

Parameters:

wmsSessionInfo - session info

detachFromWMSSession

```
public void detachFromWMSSession(RtmpSessionInfo wmsSessionInfo)
```


(continued from last page)

Detach from WMS session, Internal use.

Parameters:

wmsSessionInfo - session info

pause

```
public void pause(RTPRequestStatus status)
```

Execute pause

Parameters:

status - RTP status

announce

```
public void announce(RTPRequestStatus status)
```

Execute announce command

Parameters:

status - RTP status

isResyncAudioVideoOnSR

```
public boolean isResyncAudioVideoOnSR()
```

Reset audio/video sync on new RTCP packets (not just first packet)

Returns:

true if resetting audio/video on new RTCP packets

setResyncAudioVideoOnSR

```
public void setResyncAudioVideoOnSR(boolean resyncAudioVideoOnSR)
```

Reset audio/video sync on new RTCP packets (not just first packet)

Parameters:

resyncAudioVideoOnSR - true if resetting audio/video on new RTCP packets

getMetadataPacket

```
public byte[] getMetadataPacket()
```

Get the onMetadata packet for this RTP stream

Returns:

onMetadata packet

resetSentMetadataFlag

```
public void resetSentMetadataFlag()
```

Reset sendMetadata flag

(continued from last page)

checkSendMetadata

```
public void checkSendMetadata(long adjTimecode,  
    RTPTrack rtpTrack)
```

Check to see if we have sent onMetadata event, if not send

Parameters:

adjTimecode - timecode (milliseconds)

extractCodecConfigFromTrackInfo

```
public void extractCodecConfigFromTrackInfo()
```

Extract codec config information from SDP data

getStreamType

```
public String getStreamType()
```

Get the stream type

Returns:

stream type

setStreamType

```
public void setStreamType(String streamType)
```

Set the stream type

Parameters:

streamType - stream type

getAppName

```
public String getAppName()
```

Get the application name

Returns:

application name

setAppName

```
public void setAppName(String appName)
```

Get the application name

Parameters:

appName - application name

getAppInstanceName

```
public String getAppInstanceName()
```

Get the application instance name

Returns:

(continued from last page)

application instance name

setAppInstanceName

```
public void setAppInstanceName(String appInstanceName)
```

Set the application instance name

Parameters:

appInstanceName - application instance name

getStreamExt

```
public String getStreamExt()
```

Get the stream extension

Returns:

stream extension

setStreamExt

```
public void setStreamExt(String streamExt)
```

Set the stream extension

Parameters:

streamExt - stream extension

getStreamName

```
public String getStreamName()
```

Get stream name

Returns:

stream name

setStreamName

```
public void setStreamName(String streamName)
```

Set stream name

Parameters:

streamName - stream name

getStreamNameLogging

```
public String getStreamNameLogging()
```

Get the stream name used for logging

Returns:

stream name used for logging

(continued from last page)

setStreamNameLogging

```
public void setStreamNameLogging(String streamNameLogging)
```

Set the stream name used for logging

Parameters:

streamNameLogging - stream name used for logging

getStreamSessionId

```
public long getStreamSessionId()
```

Get the stream session id

Returns:

stream session id

setStreamSessionId

```
public void setStreamSessionId(long streamSessionId)
```

Set the stream session id

Parameters:

streamSessionId - stream session id

getStreamSessionVersion

```
public long getStreamSessionVersion()
```

Get the stream session version

Returns:

stream session version

setStreamSessionVersion

```
public void setStreamSessionVersion(long streamSessionVersion)
```

Set the stream session version

Parameters:

streamSessionVersion - stream session version

getStreamSessionIp

```
public String getStreamSessionIp()
```

Get the stream session ip

Returns:

stream session ip

setStreamSessionIp

```
public void setStreamSessionIp(String streamSessionIp)
```

(continued from last page)

Set the stream session ip

Parameters:

streamSessionIp - stream session ip

isCheckSSRC

```
public boolean isCheckSSRC( )
```

Are we checking the ssrc values of each incoming RTP packet

Returns:

true if checking

setCheckSSRC

```
public void setCheckSSRC(boolean checkSSRC)
```

Are we checking the ssrc values of each incoming RTP packet

Parameters:

checkSSRC - true if checking

isCheckIpAddr

```
public boolean isCheckIpAddr( )
```

Are we checking the ip address of each incoming RTP packet

Returns:

true if checking ip address of each incoming RTP packet

setCheckIpAddr

```
public void setCheckIpAddr(boolean checkIpAddr)
```

Are we checking the ip address of each incoming RTP packet

Parameters:

checkIpAddr - true if checking ip address of each incoming RTP packet

getUDPTransport

```
public com.wowza.wms.rtp.transport.IUDPTransport getUDPTransport(boolean isMulticast)
```

Get the UDP transport for this stream

Parameters:

isMulticast - true if multicast

Returns:

UDP transport

getAVSyncMethod

```
public int getAVSyncMethod( )
```

Get the audio/video sync method. See AVSYNCMETHODS_*

(continued from last page)

Returns:

audio/video sync method. See AVSYNCMETHODS_*

setAVSyncMethod

```
public void setAVSyncMethod(int avSyncMethod)
```

Set the audio/video sync method. See AVSYNCMETHODS_*

Parameters:

avSyncMethod - audio/video sync method. See AVSYNCMETHODS_*

isAVSyncNonSR

```
public boolean isAVSyncNonSR()
```

Is sync method based on RTCP packets (sender report)

Returns:

true if based in RTCP sender reports

getMaxRTCPWaitTime

```
public int getMaxRTCPWaitTime()
```

Get max time to wait for RTCP sender reports (milliseconds)

Returns:

max time to wait for RTCP sender reports (milliseconds)

setMaxRTCPWaitTime

```
public void setMaxRTCPWaitTime(int maxRTCPWaitTime)
```

Set max time to wait for RTCP sender reports (milliseconds)

Parameters:

maxRTCPWaitTime - max time to wait for RTCP sender reports (milliseconds)

getStreamInfo

```
public java.util.Map getStreamInfo()
```

Get all name/value pairs in the stream info collection

Returns:

map of name/value pairs

getStreamAttributes

```
public java.util.Map getStreamAttributes()
```

Get all name/value pairs in the stream attributes collection

Returns:map of name/value pairs

(continued from last page)

avSyncNameToId

```
public static int avSyncNameToId(String avSyncName)
```

Get audio/video sync id from name

Parameters:

avSyncName - audio/video sync name

Returns:

audio/video sync id, see AVSYNCMETHODS_*

getMPEGTSAudioLanguage

```
public String getMPEGTSAudioLanguage()
```

setMPEGTSAudioLanguage

```
public void setMPEGTSAudioLanguage(String mpegtsAudioLanguage)
```

getMPEGTSProgramID

```
public int getMPEGTSProgramID()
```

setMPEGTSProgramID

```
public void setMPEGTSProgramID(int mpegtsProgramId)
```

getMPEGTSVideoPID

```
public int getMPEGTSVideoPID()
```

Get the video PID id if MPEG-TS stream

Returns:

video PID id if MPEG-TS stream

setMPEGTSVideoPID

```
public void setMPEGTSVideoPID(int mpegtsVideoPID)
```

Set the video PID id if MPEG-TS stream

Parameters:

mpegtsVideoPID - video PID id if MPEG-TS stream

getMPEGTSAudioPID

```
public int getMPEGTSAudioPID()
```

(continued from last page)

Get the audio PID id if MPEG-TS stream

Returns:

audio PID id if MPEG-TS stream

setMPEGTSAudioPID

```
public void setMPEGTSAudioPID(int mpegtsAudioPID)
```

Set the audio PID id if MPEG-TS stream

Parameters:

mpegtsAudioPID - audio PID id if MPEG-TS stream

isRTSP

```
public boolean isRTSP()
```

Is this RTP Stream managed by RTSP session

Returns:

true if managed by RTSP session

setRTSP

```
public void setRTSP(boolean isRTSP)
```

Is this RTP Stream managed by RTSP session

Parameters:

isRTSP - true if managed by RTSP session

isRTSPPull

```
public boolean isRTSPPull()
```

Is this RTP Stream managed by RTSP session

Returns:

true if managed by RTSP session

setRTSPPull

```
public void setRTSPPull(boolean isRTSPPull)
```

Is this RTP Stream managed by RTSP session

Parameters:

isRTSP - true if managed by RTSP session

getStreamQueryStr

```
public String getStreamQueryStr()
```

Get the stream query string

Returns:

stream query string

setStreamQueryStr

```
public void setStreamQueryStr(String streamQueryStr)
```

Set the stream query string

Parameters:

streamQueryStr - stream query string

isModePublish

```
public boolean isModePublish()
```

Is this a publish stream

Returns:

true if publish stream

isModePlay

```
public boolean isModePlay()
```

Is this a play stream

Returns:

true if play stream

isModeUnknown

```
public boolean isModeUnknown()
```

Is the stream mode unknown (publish vs play)

Returns:

true if stream mode is unknown

getOutHost

```
public String getOutHost()
```

Get the out host

Returns:

out host

setOutHost

```
public void setOutHost(String outHost)
```

Set out host

Parameters:

outHost - out host

(continued from last page)

idle

```
public void idle(org.apache.mina.common.Session session,  
    RtmpResponseMessage resp)
```

Process idle event

Parameters:

session - io session
resp - idle request

getLastPacketsByType

```
public AMFPacket\[\] getLastPacketsByType(IMediaStream localStream)
```

Analyzes stream to get information, Internal use.

Parameters:

localStream - local stream

Returns:

important packets

getLastPacketsByType

```
public AMFPacket\[\] getLastPacketsByType(IMediaReader localReader,  
    double startTime)
```

Analyzes stream to get information, Internal use.

Parameters:

localReader - media reader
startTime - start time

Returns:

important packets

describe

```
public String describe(RTPSession rtspSession,  
    RTPRequestStatus status)
```

Execute describe command

Parameters:

rtspSession - RTP session
status - RTP status

Returns:

describe response

switchSetupToMPEGTS

```
public void switchSetupToMPEGTS()
```

Switch a stream to MPEG-TS, Internal use.

(continued from last page)

describe

```
public String describe(RTPSession rtspSession,  
    int isStreamPacketizer,  
    RTPRequestStatus status)
```

Execute describe command

Parameters:

rtspSession - RTP session
isStreamPacketizer - true is stream
status - RTP status

Returns:

describe string

getMode

```
public int getMode()
```

Get the current play/publish mode

Returns:

play/publish mode

setMode

```
public void setMode(int mode)
```

Set the play/publish mode

Parameters:

mode - play/publish mode

getTransportMode

```
public String getTransportMode()
```

Get the transport mode

Returns:

transport mode

setTransportMode

```
public void setTransportMode(String transportMode)
```

Set the transport mode

Parameters:

transportMode - transport mode

getNormalizedNTPTimecode

```
public long getNormalizedNTPTimecode(long timecode)
```

Turn a millisecond timecode into an NTP timecode

Parameters:

(continued from last page)

timecode - timecode (milliseconds)

Returns:

NTP timecode

isForceRTSPInterleaved

```
public boolean isForceRTSPInterleaved()
```

True if forcing RTSP interleaved

Returns:

true if forcing RTSP interleaved

setForceRTSPInterleaved

```
public void setForceRTSPInterleaved(boolean isForceRTSPInterleaved)
```

True if forcing RTSP interleaved

Parameters:

isForceRTSPInterleaved - true if forcing RTSP interleaved

getRTPInfo

```
public RTPStream.RTPInfo getRTPInfo(double startTime,  
    int videoSeq,  
    int audioSeq)
```

Get the RTP info

Parameters:

startTime - start time
videoSeq - video sequence number
audioSeq - audio sequence number

Returns:

RTP info string

formatRTPInfo

```
public String formatRTPInfo(long timecode,  
    int videoSeq,  
    int audioSeq)
```

Format RTP info

Parameters:

timecode - timecode
videoSeq - video sequence number
audioSeq - audio sequence number

Returns:

RTP Info string

getRTSPSessionName

```
public String getRTSPSessionName()
```

(continued from last page)

Get session name

Returns:

session name

setRTSPSessionName

```
public void setRTSPSessionName(String rtspSessionName)
```

Set session name

Parameters:

rtspSessionName - session name

getRTSPSessionDescription

```
public String getRTSPSessionDescription()
```

Get session description

Returns:

session description

setRTSPSessionDescription

```
public void setRTSPSessionDescription(String rtspSessionDescription)
```

Get session description

Parameters:

rtspSessionDescription - session description

isSendSDESEvents

```
public boolean isSendSDESEvents()
```

Send RTCP SDES events

Returns:

true if sending RTCP SDES events

setSendSDESEvents

```
public void setSendSDESEvents(boolean sendSDESEvents)
```

Send RTCP SDES events

Parameters:

sendSDESEvents - true if sending RTCP SDES events

isMPEGTSOut

```
public boolean isMPEGTSOut()
```

Is MPEG-TS out

Returns:

true if MPEG-TS out

setMPEGTSOut

```
public void setMPEGTSOut(boolean isMPEGTSOut)
```

Is MPEG-TS out

Parameters:

isMPEGTSOut - true if MPEG-TS out

transportFindBestMatch

```
public String transportFindBestMatch(String transport)
```

Based on a trasport string from SETUP command find best match

Parameters:

transport - trasport string

Returns:

best match

getAutoAllocateInterleavePorts

```
public int getAutoAllocateInterleavePorts()
```

isLive

```
public boolean isLive()
```

Is live stream

Returns:

true if live

setLive

```
public void setLive(boolean isLive)
```

Is live stream

Parameters:

isLive - true if live

getMediaReader

```
public IMediaReader getMediaReader()
```

Get media reader if video on demand stream

Returns:

media reader

getRTSPSessionTimeout

```
public int getRTSPSessionTimeout()
```

(continued from last page)

Get RTP session timeout (milliseconds)

Returns:

RTP session timeout (milliseconds)

setRTSPSessionTimeout

```
public void setRTSPSessionTimeout(int rtspSessionTimeout)
```

Set RTP session timeout (milliseconds)

Parameters:

rtspSessionTimeout - RTP session timeout (milliseconds)

getRTSPMaximumPendingWriteBytes

```
public int getRTSPMaximumPendingWriteBytes()
```

Get the maximum number of waiting bytes allow for this RTSP session

Returns:

maximum number of waiting bytes allow for this RTSP session

setRTSPMaximumPendingWriteBytes

```
public void setRTSPMaximumPendingWriteBytes(int rtspMaximumPendingWriteBytes)
```

Set the maximum number of waiting bytes allow for this RTSP session

Parameters:

rtspMaximumPendingWriteBytes - maximum number of waiting bytes allow for this RTSP session

isTimeout

```
public boolean isTimeout(long currTime,  
    int timeout)
```

Is the stream timeout out

Parameters:

currTime - current time

timeout - timeout value

Returns:

true if timed out

touch

```
public void touch()
```

Touch the stream so that it does not timeout

getRTSPBindIpAddress

```
public String getRTSPBindIpAddress()
```

Get the bind RTSP bind IP address

(continued from last page)

Returns:

bind RTSP bind IP address

setRTSPBindIpAddress

```
public void setRTSPBindIpAddress(String rtspBindIpAddress)
```

Set the bind RTSP bind IP address

Parameters:

rtspBindIpAddress - bind RTSP bind IP address

getRTSPConnectionIpAddress

```
public String getRTSPConnectionIpAddress()
```

Get the connection IP address

Returns:

connection IP address

setRTSPConnectionIpAddress

```
public void setRTSPConnectionIpAddress(String rtspConnectionIpAddress)
```

Set the connection IP address

Parameters:

rtspConnectionIpAddress - connection IP address

getRTSPConnectionAddressType

```
public String getRTSPConnectionAddressType()
```

Get the connection address type

Returns:

connection address type

setRTSPConnectionAddressType

```
public void setRTSPConnectionAddressType(String rtspConnectionAddressType)
```

Set the connection address type

Parameters:

rtspConnectionAddressType - connection address type

getRTSPOriginIpAddress

```
public String getRTSPOriginIpAddress()
```

Get the origin IP address

Returns:

origin IP address

(continued from last page)

setRTSPOriginIpAddress

```
public void setRTSPOriginIpAddress(String rtspOriginIpAddress)
```

Set the origin IP address

Parameters:

rtspOriginIpAddress - origin IP address

getRTSPOriginAddressType

```
public String getRTSPOriginAddressType()
```

Get the origin address type

Returns:

origin address type

setRTSPOriginAddressType

```
public void setRTSPOriginAddressType(String rtspOriginAddressType)
```

Set the origin address type

Parameters:

rtspOriginAddressType - origin address type

getVODStartTimeTC

```
public long getVODStartTimeTC()
```

Get the video on demand start time (milliseconds)

Returns:

video on demand start time (milliseconds)

setVODStartTimeTC

```
public void setVODStartTimeTC(long vodStartTimeTC)
```

Set the video on demand start time (milliseconds)

Parameters:

vodStartTimeTC - video on demand start time (milliseconds)

getVODLastTimeTC

```
public long getVODLastTimeTC()
```

Get the last timecode (milliseconds) sent for video on demand

Returns:

last timecode (milliseconds) sent for video on demand

setVODLastTimeTC

```
public void setVODLastTimeTC(long vodLastTimeTC)
```

(continued from last page)

Set the last timecode (milliseconds) sent for video on demand

Parameters:

vodLastTimeTC - last timecode (milliseconds) sent for video on demand

getVODPlayLen

```
public long getVODPlayLen()
```

Get the video on demand play duration (milliseconds)

Returns:

video on demand play duration (milliseconds)

setVODPlayLen

```
public void setVODPlayLen(long vodPlayLen)
```

Set the video on demand play duration (milliseconds)

Parameters:

vodPlayLen - video on demand play duration (milliseconds)

isStreamStarted

```
public boolean isStreamStarted()
```

Is stream started

Returns:

true if stream has started playback

isRTSPAlwaysUseSDPPorts

```
public boolean isRTSPAlwaysUseSDPPorts()
```

Force RTSP to use ports in SDP data

Returns:

true if using ports in SDP data

setRTSPAlwaysUseSDPPorts

```
public void setRTSPAlwaysUseSDPPorts(boolean rtspAlwaysUseSDPPorts)
```

Force RTSP to use ports in SDP data

Parameters:

rtspAlwaysUseSDPPorts - true if using ports in SDP data

putRTSPSessionExtraLine

```
public void putRTSPSessionExtraLine(int location,  
    String line)
```

Add an extra line to the SDP data

Parameters:

location - location of line, see SDPLOCATION_

(continued from last page)

line - line to add

clearRTSPSessionExtraLines

```
public void clearRTSPSessionExtraLines()
```

Clear SDP extra lines

getRTSPSessionExtraLines

```
public java.util.List getRTSPSessionExtraLines()
```

Get extra SDP lines

Returns:

extra SDP lines

getRTPDestination

```
public RTPDestination getRTPDestination()
```

Get RTP destination

Returns:

RTP destination

setRTPDestination

```
public void setRTPDestination(RTPDestination rtpDestination)
```

Set RTP destination

Parameters:

rtpDestination - RTP destination

getSDPLang

```
public String getSDPLang()
```

Get the SDP language

Returns:

SDP language

setSDPLang

```
public void setSDPLang(String sdpLang)
```

Set the SDP language

Parameters:

sdpLang - SDP language

isRTPIgnoreProfileLevelId

```
public boolean isRTPIgnoreProfileLevelId()
```

setRTPIgnoreProfileLevelId

```
public void setRTPIgnoreProfileLevelId(boolean rtpIgnoreProfileLevelId)
```

getUDPManagedDeliveryDelay

```
public int getUDPManagedDeliveryDelay()
```

setUDPManagedDeliveryDelay

```
public void setUDPManagedDeliveryDelay(int udpManagedDeliveryDelay)
```

getUDPManagedDeliveryCount

```
public int getUDPManagedDeliveryCount()
```

setUDPManagedDeliveryCount

```
public void setUDPManagedDeliveryCount(int udpManagedDeliveryCount)
```

isForceMPEGTSOut

```
public boolean isForceMPEGTSOut()
```

setForceMPEGTSOut

```
public void setForceMPEGTSOut(boolean isForceMPEGTSOut)
```

Package

com.wowza.wms.server

com.wowza.wms.server Interface ICommandInterfaceCommand

public interface **ICommandInterfaceCommand**
extends

Method Summary

boolean	<u>canHandle</u> (CommandInterfaceRequestMessage req)
void	<u>invoke</u> (CommandInterfaceRequestMessage req, CommandInterfaceResponseMessage resp)

Methods

invoke

```
public void invoke(CommandInterfaceRequestMessage req,  
    CommandInterfaceResponseMessage resp)
```

canHandle

```
public boolean canHandle(CommandInterfaceRequestMessage req)
```

com.wowza.wms.server Interface IResponseListener

public interface **IResponseListener**
extends

IResponseListener: Internal use.

Method Summary

void	<u>onResponseWriteStart</u> (RtmpResponseMessage response)
void	<u>onResponseWriteStop</u> (RtmpResponseMessage response)

Methods

onResponseWriteStart

public void **onResponseWriteStart**(RtmpResponseMessage response)

onResponseWriteStop

public void **onResponseWriteStop**(RtmpResponseMessage response)

com.wowza.wms.server Interface IServer

All Known Implementing Classes:
[Server](#)

public interface **IServer**
extends

IServer: public interface to Server object.

Method Summary

void	addServerListener (IServerNotify serverListener) Add server listener
java.util.List	getAdminInterfaceObjectList () Get the list of objects exposed through JMX interface
RandomIdGenerator	getClientIdGenerator () Get the client id generator for the server
CommandInterfaceCommandHandler	getCommandInterfaceCommandHandler () Get the command interface command handler
HostPort	getCommandInterfaceHostPort () Get the definition of the command interface
ConnectionCounter	getConnectionCounter () Get the server connection counter.
ConnectionCounterSimple	getConnectionCounter (int counterIndex) Get the server connection counter for a specific technology (see IVHost.COUNTER_*)
int	getCoreHandlerPoolSize () Get the handler core thread pool size.
int	getCoreTransportPoolSize () Get the transport core thread pool size.
String	getDateStarted () Get the date and time the server was started.
java.util.Properties	getDynamicLogProperties () Get the dynamic log properties defined at the server level in conf/log4j.properties
ThreadPool	getHandlerThreadPool () Get the server handler thread pool.
IOPerformanceCounter	getIoPerformanceCounter () Get the server performance counter.
IOPerformanceCounter	getIoPerformanceCounter (int counterIndex) Get the server performance counter for a specific technology (see IVHost.COUNTER_*)

WMSProperties	getProperties() Get server level properties collection
ThreadPool	getThreadPool() Get the server handler thread pool.
String	getTimeRunning() Get a formatted String of how long the server has been running.
double	getTimeRunningSeconds() Get time running in seconds
ThreadPool	getTransportThreadPool() Get the server transport thread pool.
com.wowza.wms.transpo rt.udp.UDPPortManager	getUDPPortManager() Get the UDP port manager which manages the allocation of incoming UDP port binding to be sure there are not port conflicts
com.wowza.wms.transpo rt.udp.UDPPortSharing Manager	getUDPPortSharingManager() Get the UDP port sharing manager.
String[]	getUserAgents() Get a pipe " " delimited list of user agents that the server recognizes as RTMPT client.
String	getVersion() Get server version number.
VHostList	getVHostList() Returns the interface to the VHostList for the server
boolean	isDynamicLogContextLoaded(String logContext) Returns true if the given dynamic log context is already loaded.
boolean	isSuspended() Is the server current suspended
String	readConfig(String sName) Method to read xml config file..
void	reloadVHostConfig() Reload the VHosts.xml file.
void	removeServerListener(IServerNotify serverListener) Remove server listener
void	setCommandInterfaceHostPort(HostPort commandInterfaceHostPort) Set the definition for the command interface.
void	setCoreHandlerPoolSize(int corePoolSize) Set the handler core thread pool size.
void	setCoreTransportPoolSize(int corePoolSize) Set the transport core thread pool size.
void	setDynamicLogProperties(java.util.Properties dynamicLogProperties) Set the dynamic log properties set at the server level

void	<code>setUserAgents</code> (String[] userAgents) Set a pipe " " delimited list of user agents that the server recognizes as RTMPT client.
void	<code>startCommandInterface</code> () Start the command interface as defined in Server.xml.
void	<code>startVHost</code> (String vhostName) Start a vHost by name.
void	<code>startVHosts</code> () Start all vHosts
void	<code>stopAdminAgent</code> () Stop the JMX interface
void	<code>stopCommandInterface</code> () Stop the command interface as defined in Server.xml.
void	<code>stopVHost</code> (String vhostName) Stop a vHost by name.
void	<code>stopVHosts</code> () Stop all vHosts
void	<code>suspendAllVHosts</code> () Suspend all virtual hosts (Calls IVHost.suspendAllHostPorts for each vhost)
void	<code>suspendServer</code> () Suspend all virtual hosts and the command interface
void	<code>unbindAllVHosts</code> () Unbind all virtual hosts (Calls IVHost.unbindAllHostPorts for each vhost)
boolean	<code>writeConfig</code> (String sName, String data) Method to write xml config file..

Methods

startCommandInterface

```
public void startCommandInterface()
```

Start the command interface as defined in Server.xml. The command interface is used by shutdown.sh script to stop the server. It is also used by ant task to stop and start the server on build events.

stopCommandInterface

```
public void stopCommandInterface()
```

Stop the command interface as defined in Server.xml. The command interface is used by shutdown.sh script to stop the server. It is also used by ant task to stop and start the server on build events.

getVersion

```
public String getVersion()
```

Get server version number.

(continued from last page)

Returns:

server version number

reloadVHostConfig

```
public void reloadVHostConfig()
```

Reload the VHosts.xml file. This method can be invoked through the JMX interface to manage vHosts while the server is running.

stopVHost

```
public void stopVHost(String vhostName)
```

Stop a vHost by name.

Parameters:

vhostName - vHost name

stopVHosts

```
public void stopVHosts()
```

Stop all vHosts

startVHost

```
public void startVHost(String vhostName)
```

Start a vHost by name.

Parameters:

vhostName - vHost name

startVHosts

```
public void startVHosts()
```

Start all vHosts

getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter()
```

Get the server performance counter.

Returns:

io performance counter

getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

Get the server performance counter for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

(continued from last page)

Returns:io performance counter

getConnectionCounter

```
public ConnectionCounter getConnectionCounter( )
```

Get the server connection counter.

Returns:connection counter

getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get the server connection counter for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

Returns:connection counter

getDateStarted

```
public String getDateStarted( )
```

Get the date and time the server was started.

Returns:date and time the server was started

getTimeRunning

```
public String getTimeRunning( )
```

Get a formatted String of how long the server has been running.

Returns:formatted String of how long the server has been running

getTimeRunningSeconds

```
public double getTimeRunningSeconds( )
```

Get time running in seconds

Returns:time running in seconds

getCommandInterfaceHostPort

```
public HostPort getCommandInterfaceHostPort( )
```

Get the definition of the command interface

(continued from last page)

Returns:

host port definition of command interface

setCommandInterfaceHostPort

```
public void setCommandInterfaceHostPort(HostPort commandInterfaceHostPort)
```

Set the definition for the command interface.

Parameters:

commandInterfaceHostPort - host port definition of command interface

getUserAgents

```
public String[] getUserAgents()
```

Get a pipe "|" delimited list of user agents that the server recognizes as RTMPT client.

Returns:

pipe "|" delimited list of user agents that the server recognizes as RTMPT client

setUserAgents

```
public void setUserAgents(String[] userAgents)
```

Set a pipe "|" delimited list of user agents that the server recognizes as RTMPT client.

Parameters:

userAgents - pipe "|" delimited list of user agents that the server recognizes as RTMPT client

addServerListener

```
public void addServerListener(IServerNotify serverListener)
```

Add server listener

Parameters:

serverListener - server listener

removeServerListener

```
public void removeServerListener(IServerNotify serverListener)
```

Remove server listener

Parameters:

serverListener - server listener

getAdminInterfaceObjectList

```
public java.util.List getAdminInterfaceObjectList()
```

Get the list of objects exposed through JMX interface

Returns:

list of objects exposed through JMX interface

(continued from last page)

getCoreTransportPoolSize

```
public int getCoreTransportPoolSize()
```

Get the transport core thread pool size.

Returns:

default core thread pool size

setCoreTransportPoolSize

```
public void setCoreTransportPoolSize(int corePoolSize)
```

Set the transport core thread pool size.

Parameters:

corePoolSize - core thread pool size

getCoreHandlerPoolSize

```
public int getCoreHandlerPoolSize()
```

Get the handler core thread pool size.

Returns:

default core thread pool size

setCoreHandlerPoolSize

```
public void setCoreHandlerPoolSize(int corePoolSize)
```

Set the handler core thread pool size.

Parameters:

corePoolSize - core thread pool size

getThreadPool

```
public ThreadPool getThreadPool()
```

Get the server handler thread pool. Same as getHandlerThreadPool.

Returns:

server handler thread pool

getTransportThreadPool

```
public ThreadPool getTransportThreadPool()
```

Get the server transport thread pool. This thread pool is used to read/write data from the transports sockets.

Returns:

server transport thread pool

getHandlerThreadPool

```
public ThreadPool getHandlerThreadPool()
```

(continued from last page)

Get the server handler thread pool. This thread pool is used to process the incoming events.

Returns:

server handler thread pool

getProperties

```
public WMSProperties getProperties()
```

Get server level properties collection

Returns:

server level properties collection

getClientIdGenerator

```
public RandomIdGenerator getClientIdGenerator()
```

Get the client id generator for the server

Returns:

client id generator for the server

getDynamicLogProperties

```
public java.util.Properties getDynamicLogProperties()
```

Get the dynamic log properties defined at the server level in conf/log4j.properties

Returns:

dynamic log properties defined at the server level

setDynamicLogProperties

```
public void setDynamicLogProperties(java.util.Properties dynamicLogProperties)
```

Set the dynamic log properties set at the server level

Parameters:

dynamicLogProperties - dynamic log properties defined at the server level

isDynamicLogContextLoaded

```
public boolean isDynamicLogContextLoaded(String logContext)
```

Returns true if the given dynamic log context is already loaded. If not loaded it will return false and add it to the a Set of loaded log context. Log context is [VHost].[Application].[AppInstance]

getVHostList

```
public VHostList getVHostList()
```

Returns the interface to the VHostList for the server

Returns:

vhostList

(continued from last page)

suspendAllVHosts

```
public void suspendAllVHosts()
```

Suspend all virtual hosts (Calls IVHost.suspendAllHostPorts for each vhost)

unbindAllVHosts

```
public void unbindAllVHosts()
```

Unbind all virtual hosts (Calls IVHost.unbindAllHostPorts for each vhost)

suspendServer

```
public void suspendServer()
```

Suspend all virtual hosts and the command interface

isSuspended

```
public boolean isSuspended()
```

Is the server current suspended

stopAdminAgent

```
public void stopAdminAgent()
```

Stop the JMX interface

getUDPPortManager

```
public com.wowza.wms.transport.udp.UDPPortManager getUDPPortManager()
```

Get the UDP port manager which manages the allocation of incoming UDP port binding to be sure there are not port conflicts

Returns:

UDP port manager

getUDPPortSharingManager

```
public com.wowza.wms.transport.udp.UDPPortSharingManager getUDPPortSharingManager()
```

Get the UDP port sharing manager.

Returns:

UDP port sharing manager

readConfig

```
public String readConfig(String sName)
```

Method to read xml config file..

writeConfig

```
public boolean writeConfig(String sName,  
    String data)
```


(continued from last page)

Method to write xml config file..

getCommandInterfaceCommandHandler

```
public CommandInterfaceCommandHandler getCommandInterfaceCommandHandler( )
```

Get the command interface command handler

Returns:

command interface command handler

com.wowza.wms.server Interface IServerNotify

All Subinterfaces:

[IServerNotify2](#)

public interface **IServerNotify**
extends

IServerNotify: listener interface. Configured by adding class entries definitions to Server.xml.Startup order is: [constructor]; onServerConfigLoaded, onServerCreate, onServerInit Shutdown order is: onServerShutdownStart, onServerShutdownComplete, [exit]

Method Summary

void	onServerCreate (IServer server) Triggered when server object is first created.
void	onServerInit (IServer server) Triggered when server initialization is complete and all VHosts have been started
void	onServerShutdownComplete (IServer server) Triggered at the end of server shutdown
void	onServerShutdownStart (IServer server) Triggered at the beginning of server shutdown

Methods

onServerCreate

public void **onServerCreate**([IServer](#) server)

Triggered when server object is first created.

Parameters:

server - server object

onServerInit

public void **onServerInit**([IServer](#) server)

Triggered when server initialization is complete and all VHosts have been started

Parameters:

server - server object

onServerShutdownStart

public void **onServerShutdownStart**([IServer](#) server)

Triggered at the beginning of server shutdown

(continued from last page)

Parameters:

server - server object

onServerShutdownComplete

```
public void onServerShutdownComplete(IServer server)
```

Triggered at the end of server shutdown

Parameters:

server - server object

com.wowza.wms.server Interface IServerNotify2

All Superinterfaces:
[IServerNotify](#)

public interface **IServerNotify2**
extends [IServerNotify](#)

IServerNotify2: listener interface. Configured by adding class entries definitions to Server.xml.Startup order is: [constructor]; onServerConfigLoaded, onServerCreate, onServerInit Shutdown order is: onServerShutdownStart, onServerShutdownComplete, [exit]

Method Summary

void	onServerConfigLoaded (IServer server) Triggered when server configuration is loaded
------	-------------------------------------------------------------------------------------------------------------------------

Methods inherited from interface [com.wowza.wms.server.IServerNotify](#)

[onServerCreate](#), [onServerInit](#), [onServerShutdownComplete](#), [onServerShutdownStart](#)

Methods

onServerConfigLoaded

public void **onServerConfigLoaded**([IServer](#) server)

Triggered when server configuration is loaded

Parameters:

server - server object

com.wowza.wms.server Class Server

java.lang.Object

└─com.wowza.wms.server.Server

All Implemented Interfaces:

[IServer](#)

public class **Server**
extends Object
implements [IServer](#)

Field Summary

public static	logNotifier
---------------	-----------------------------

Constructor Summary

public	Server()
--------	--------------------------

Method Summary

void	addServerListener (IServerNotify serverListener)
------	-----------------------------------------------------------------------------------

static void	decodeS (String[] ins) Deprecated.
-------------	--------------------------------------------------------------

static boolean	decodeSS (String in) Deprecated.
----------------	------------------------------------------------------------

String	decodeStorageDir (IVHost vhost, String storageDir)
--------	-------------------------------------------------------------------------------------

void	doWatchdog ()
------	-------------------------------

static String	fS (byte[] kiIn, String p) Deprecated.
---------------	------------------------------------------------------------------

com.wowza.wms.admin.AdminAgent	getAdminAgent ()
--------------------------------	----------------------------------

String	getAdminGUID ()
--------	---------------------------------

java.util.List	getAdminInterfaceObjectList ()
----------------	------------------------------------------------

RandomIdGenerator	getClientIdGenerator ()
-------------------	-----------------------------------------

int	getClientIdGeneratorRecycleDelaySize ()
-----	---------------------------------------------------------

int	getClientIdGeneratorRecycleSize()
long	getClientIdGeneratorTimeout()
Object	getCommandInterface()
CommandInterfaceCommandHandler	getCommandInterfaceCommandHandler()
HostPort	getCommandInterfaceHostPort()
long	getCommittedVirtualMemory()
ConnectionCounter	getConnectionCounter()
ConnectionCounterSimple	getConnectionCounter(int counterIndex)
IConnectionValidator	getConnectionValidator()
int	getCoreHandlerPoolSize()
int	getCoreTransportPoolSize()
int	getCryptoPoolActiveCount()
int	getCryptoPoolMaxSize()
long	getCurrentHeapSize()
String	getDateStarted()
java.util.Properties	getDynamicLogProperties()
String	getGUID()
ThreadPool	getHandlerThreadPool()
static Server	getInstance()
IOPerformanceCounter	getIoPerformanceCounter()
IOPerformanceCounter	getIoPerformanceCounter(int counterIndex)
JMXRemoteConfig	getJmxRemoteConfig()
LicenseCounter	getLicenseCounter(int index)
Server.LicenseSessionTracker	getLicenseTracker(int index)

ILicenseValidator	getLicenseValidator()
long	getLiveThreads()
long	getMaxHeapSize()
long	getPeakThreads()
WMSProperties	getProperties()
String	getServerGUID()
String	getSessionGUID()
ThreadPool	getThreadPool()
String	getTimeRunning()
double	getTimeRunningSeconds()
ThreadPool	getTransportThreadPool()
com.wowza.wms.transpo rt.udp.UDPPortManager	getUDPPortManager()
com.wowza.wms.transpo rt.udp.UDPPortSharing Manager	getUDPPortSharingManager()
String[]	getUserAgents()
String	getVersion()
VHostList	getVHostList()
boolean	isDynamicLogContextLoaded() (String logContext)
boolean	isSuspended()
boolean	isVHostRunning() (String name)
static void	main() (String[] args)
void	onNewVHost() (IVHost vhost)
String	readConfig() (String sName)
static String	readXMLConfig() (String sPath)
void	reloadVHostConfig()

void	removeServerListener (IServerNotify serverListener)
void	setCommandInterface (Object commandInterface)
void	setCommandInterfaceHostPort (HostPort commandInterfaceHostPort)
void	setCoreHandlerPoolSize (int corePoolSize)
void	setCoreTransportPoolSize (int corePoolSize)
void	setDynamicLogProperties (java.util.Properties dynamicLogProperties)
void	setIoPerformanceCounter (IoPerformanceCounter ioPerformanceCounter)
void	setUserAgents (String[] userAgents)
static void	start ()
void	startCommandInterface ()
void	startServer ()
void	startVHost (String vhostName)
void	startVHosts ()
void	stopAdminAgent ()
void	stopCommandInterface ()
void	stopServer ()
void	stopVHost (String vhostName)
void	stopVHosts ()
void	suspendAllVHosts ()
void	suspendCommandInterface ()
void	suspendServer ()
void	unbindAllVHosts ()
IoPerformanceCounter	updateIoPerformance ()
void	updateLoggingDuration ()

boolean	writeConfig (String sName, String data)
static boolean	writeXMLConfig (String sPath, String data)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.server.IServer](#)

[addServerListener](#), [getAdminInterfaceObjectList](#), [getClientIdGenerator](#), [getCommandInterfaceCommandHandler](#), [getCommandInterfaceHostPort](#), [getConnectionCounter](#), [getConnectionCounter](#), [getCoreHandlerPoolSize](#), [getCoreTransportPoolSize](#), [getDateStarted](#), [getDynamicLogProperties](#), [getHandlerThreadPool](#), [getIoPerformanceCounter](#), [getIoPerformanceCounter](#), [getProperties](#), [getThreadPool](#), [getTimeRunning](#), [getTimeRunningSeconds](#), [getTransportThreadPool](#), [getUDPPortManager](#), [getUDPPortSharingManager](#), [getUserAgents](#), [getVersion](#), [getVHostList](#), [isDynamicLogContextLoaded](#), [isSuspended](#), [readConfig](#), [reloadVHostConfig](#), [removeServerListener](#), [setCommandInterfaceHostPort](#), [setCoreHandlerPoolSize](#), [setCoreTransportPoolSize](#), [setDynamicLogProperties](#), [setUserAgents](#), [startCommandInterface](#), [startVHost](#), [startVHosts](#), [stopAdminAgent](#), [stopCommandInterface](#), [stopVHost](#), [stopVHosts](#), [suspendAllVHosts](#), [suspendServer](#), [unbindAllVHosts](#), [writeConfig](#)

Fields

logNotifier

```
public static com.wowza.wms.logging.ILogNotify logNotifier
```

Constructors

Server

```
public Server()
```

Methods

getInstance

```
public static Server getInstance()
```

getAdminAgent

```
public com.wowza.wms.admin.AdminAgent getAdminAgent()
```

main

```
public static void main(String[] args)
```

start

```
public static void start()
```

stopServer

```
public void stopServer()
```

stopAdminAgent

```
public void stopAdminAgent()
```

isVHostRunning

```
public boolean isVHostRunning(String name)
```

suspendCommandInterface

```
public void suspendCommandInterface()
```

startCommandInterface

```
public void startCommandInterface()
```

stopCommandInterface

```
public void stopCommandInterface()
```

startServer

```
public void startServer()
```

getVersion

```
public String getVersion()
```

(continued from last page)

reloadVHostConfig

```
public void reloadVHostConfig()
```

stopVHost

```
public void stopVHost(String vhostName)
```

stopVHosts

```
public void stopVHosts()
```

decodeStorageDir

```
public String decodeStorageDir(IVHost vhost,  
    String storageDir)
```

startVHost

```
public void startVHost(String vhostName)
```

isSuspended

```
public boolean isSuspended()
```

suspendServer

```
public void suspendServer()
```

suspendAllVHosts

```
public void suspendAllVHosts()
```

unbindAllVHosts

```
public void unbindAllVHosts()
```

(continued from last page)

startVHosts

```
public void startVHosts()
```

doWatchdog

```
public void doWatchdog()
```

updateIOPerformance

```
public IOPerformanceCounter updateIOPerformance()
```

getIoPerformanceCounter

```
public IOPerformanceCounter getIoPerformanceCounter()
```

getIoPerformanceCounter

```
public IOPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

setIoPerformanceCounter

```
public void setIoPerformanceCounter(IOPerformanceCounter ioPerformanceCounter)
```

getConnectionCounter

```
public ConnectionCounter getConnectionCounter()
```

getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

getConnectionValidator

```
public IConnectionValidator getConnectionValidator()
```

getLicenseValidator

```
public ILicenseValidator getLicenseValidator()
```

(continued from last page)

onNewVHost

```
public void onNewVHost(IVHost vhost)
```

getDateStarted

```
public String getDateStarted()
```

getTimeRunning

```
public String getTimeRunning()
```

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

getCommandInterfaceHostPort

```
public HostPort getCommandInterfaceHostPort()
```

setCommandInterfaceHostPort

```
public void setCommandInterfaceHostPort(HostPort commandInterfaceHostPort)
```

getCommandInterface

```
public Object getCommandInterface()
```

setCommandInterface

```
public void setCommandInterface(Object commandInterface)
```

getUserAgents

```
public String[] getUserAgents()
```

(continued from last page)

setUserAgents

```
public void setUserAgents(String[] userAgents)
```

updateLoggingDuration

```
public void updateLoggingDuration()
```

addServerListener

```
public void addServerListener(IServerNotify serverListener)
```

removeServerListener

```
public void removeServerListener(IServerNotify serverListener)
```

getJmxRemoteConfig

```
public JMXRemoteConfig getJmxRemoteConfig()
```

getAdminInterfaceObjectList

```
public java.util.List getAdminInterfaceObjectList()
```

getCoreTransportPoolSize

```
public int getCoreTransportPoolSize()
```

setCoreTransportPoolSize

```
public void setCoreTransportPoolSize(int corePoolSize)
```

getCoreHandlerPoolSize

```
public int getCoreHandlerPoolSize()
```

setCoreHandlerPoolSize

```
public void setCoreHandlerPoolSize(int corePoolSize)
```

(continued from last page)

getThreadPool

```
public ThreadPool getThreadPool()
```

getTransportThreadPool

```
public ThreadPool getTransportThreadPool()
```

getHandlerThreadPool

```
public ThreadPool getHandlerThreadPool()
```

getProperties

```
public WMSProperties getProperties()
```

getClientIdGenerator

```
public RandomIdGenerator getClientIdGenerator()
```

getDynamicLogProperties

```
public java.util.Properties getDynamicLogProperties()
```

setDynamicLogProperties

```
public void setDynamicLogProperties(java.util.Properties dynamicLogProperties)
```

isDynamicLogContextLoaded

```
public boolean isDynamicLogContextLoaded(String logContext)
```

getVHostList

```
public VHostList getVHostList()
```

(continued from last page)

getSessionGUID

```
public String getSessionGUID()
```

getServerGUID

```
public String getServerGUID()
```

getGUID

```
public String getGUID()
```

getAdminGUID

```
public String getAdminGUID()
```

getUDPPortSharingManager

```
public com.wowza.wms.transport.udp.UDPPortSharingManager getUDPPortSharingManager()
```

getUDPPortManager

```
public com.wowza.wms.transport.udp.UDPPortManager getUDPPortManager()
```

getCryptoPoolMaxSize

```
public int getCryptoPoolMaxSize()
```

getCryptoPoolActiveCount

```
public int getCryptoPoolActiveCount()
```

getLiveThreads

```
public long getLiveThreads()
```

getPeakThreads

```
public long getPeakThreads()
```

(continued from last page)

getCurrentHeapSize

```
public long getCurrentHeapSize()
```

getMaxHeapSize

```
public long getMaxHeapSize()
```

getCommittedVirtualMemory

```
public long getCommittedVirtualMemory()
```

readConfig

```
public String readConfig(String sName)
```

writeConfig

```
public boolean writeConfig(String sName,  
    String data)
```

readXMLConfig

```
public static String readXMLConfig(String sPath)
```

writeXMLConfig

```
public static boolean writeXMLConfig(String sPath,  
    String data)
```

getClientIdGeneratorTimeout

```
public long getClientIdGeneratorTimeout()
```

getClientIdGeneratorRecycleSize

```
public int getClientIdGeneratorRecycleSize()
```

getClientIdGeneratorRecycleDelaySize

```
public int getClientIdGeneratorRecycleDelaySize()
```

getCommandInterfaceCommandHandler

```
public CommandInterfaceCommandHandler getCommandInterfaceCommandHandler()
```

getLicenseCounter

```
public LicenseCounter getLicenseCounter(int index)
```

getLicenseTracker

```
public Server.LicenseSessionTracker getLicenseTracker(int index)
```

decodeS

```
public static void decodeS(String[] ins)
```

Deprecated.

decodeSS

```
public static boolean decodeSS(String in)
```

Deprecated.

fS

```
public static String fS(byte[] kiIn,  
                        String p)
```

Deprecated.

Package

com.wowza.wms.sharedobject

com.wowza.wms.sharedobject Interface ISharedObject

All Known Implementing Classes:

[SharedObject](#)

public interface **ISharedObject**
extends

ISharedObject: public interface to SharedObject class.

Field Summary

public static final	FILEEXTENSION Value: rso
public static final	SHARED_OBJECT_CMD_CONNECT shared object command: connect Value: 1
public static final	SHARED_OBJECT_CMD_CONNECTSUCCESS shared object command: clear Value: 11
public static final	SHARED_OBJECT_CMD_DELETE shared object command: delete Value: 10
public static final	SHARED_OBJECT_CMD_DISCONNECT shared object command: disconnect Value: 2
public static final	SHARED_OBJECT_CMD_ERROR shared object command: error Value: 7
public static final	SHARED_OBJECT_CMD_SEND shared object command: send Value: 6
public static final	SHARED_OBJECT_CMD_SETVALUE shared object command: setvalue Value: 3
public static final	SHARED_OBJECT_STATUS_CHANGE shared object status: change Value: 4
public static final	SHARED_OBJECT_STATUS_CLEAR shared object status: clear Value: 8

public static final	<u>SHARED_OBJECT_STATUS_DELETE</u> shared object status: delete Value: 9
public static final	<u>SHARED_OBJECT_STATUS_SUCCESS</u> shared object status: success Value: 5

Method Summary

void	<u>acquire()</u> Increment the reference count to this shared object.
void	<u>addClient(IClient client)</u> Add a client to this shared object.
void	<u>addSlotListener(ISharedObjectSlotNotify slotListener)</u> Add a slot listener.
void	<u>clear()</u> Clear all properties from a shared object
void	<u>close()</u> Force close this shared object (not implemented)
boolean	<u>containsProperty(String slotName)</u> Returns true is slot/property name exists
boolean	<u>containsSlot(String slotName)</u> Returns true is slot/property name exists
void	<u>deleteSlot(IClient client, String slotName)</u> Remove a slot (property)
void	<u>deleteSlot(String slotName)</u> Remove slot (property)
void	<u>disconnect(IClient client)</u> Disconnect client from shared object.
void	<u>flush()</u> Flush (write to disk) shared object
java.util.List	<u>getClients()</u> Get a list of client that are connected to this shared object.
String	<u>getName()</u> Get shared object name
<u>ISharedObjects</u>	<u>getParent()</u> Get the shared object container to which this shared object belongs.
<u>AMFData</u>	<u>getProperty(String slotName)</u> Get slot (property) value.
int	<u>getRefCount()</u> Get the current reference (clients) connected to this shared object.

<u>ISharedObjectSlot</u>	<u>getSlot</u> (String name) Get ISharedObjectSlot interface to a slot (property) by name
java.util.List	<u>getSlotNames</u> () Get a list of slot (property) names
java.util.List	<u>getSlots</u> () Get a list of active slots
String	<u>getStorageDir</u> () Get path used to store shared object.
int	<u>getVersion</u> () Get the interval version number.
boolean	<u>isClient</u> (<u>IClient</u> client) Is this client connected to shared object
boolean	<u>isPersistent</u> () Is this shared object being persisted.
void	<u>lock</u> () Lock a shared object for write access
int	<u>purge</u> (int version) Purge all deleted properties older than the version number
void	<u>putSlot</u> (String name, <u>ISharedObjectSlot</u> slot) Add a new slot (property) to a shared object.
void	<u>release</u> () Decrement the reference count to this shared object.
void	<u>removeClient</u> (<u>IClient</u> client) Remove a client from this shared object.
void	<u>removeSlotListener</u> (<u>ISharedObjectSlotNotify</u> slotListener) Remove slot listener
void	<u>send</u> (String handlerName) Call client side handler attached to shared object (no parameters).
void	<u>send</u> (String handlerName, Object[] params) Call client side handler attached to shared object.
void	<u>setName</u> (String name) Set shared object name
void	<u>setPersistent</u> (boolean isPersistent) Set is shared object persisted.
void	<u>setProperty</u> (String slotName, <u>AMFData</u> data) Set slot (property) value as AMFData object.
void	<u>setProperty</u> (String slotName, boolean value) Set slot (property) value as a boolean value (will be wrapped in an AMFDataItem object)
void	<u>setProperty</u> (String slotName, java.util.Date value) Set slot (property) value as a date value (will be wrapped in an AMFDataItem object)

void	<code>setProperty</code> (String slotName, double value) Set slot (property) value as a double value (will be wrapped in an AMFDataItem object)
void	<code>setProperty</code> (String slotName, int value) Set slot (property) value as a int value (will be wrapped in an AMFDataItem object)
void	<code>setProperty</code> (String slotName, long value) Set slot (property) value as a long value (will be wrapped in an AMFDataItem object)
void	<code>setProperty</code> (String slotName, String value) Set slot (property) value as a string value (will be wrapped in an AMFDataItem object)
void	<code>setStorageDir</code> (String storageDir) Set path used to store shared object.
void	<code>setVersion</code> (int version) Set the internal version number.
int	<code>size</code> () Get the number of active slot (properties).
void	<code>unlock</code> () Unlock a shared object for write access
void	<code>writeDeleteError</code> (IClient client, String soName, boolean isPersistent, String slotName, String errorMsg) Write an delete error message back to the client
void	<code>writeSetValueError</code> (IClient client, String soName, boolean isPersistent, String slotName, String errorMsg) Write an set value error message back to the client

Fields

FILEEXTENSION

```
public static final java.lang.String FILEEXTENSION
```

Constant value: **rs0**

SHARED_OBJECT_CMD_CONNECT

```
public static final byte SHARED_OBJECT_CMD_CONNECT
```

shared object command: connect

Constant value: **1**

SHARED_OBJECT_CMD_DISCONNECT

```
public static final byte SHARED_OBJECT_CMD_DISCONNECT
```

shared object command: disconnect

Constant value: **2**

(continued from last page)

SHARED_OBJECT_CMD_SETVALUE

```
public static final byte SHARED_OBJECT_CMD_SETVALUE
```

shared object command: setvalue
Constant value: **3**

SHARED_OBJECT_CMD_SEND

```
public static final byte SHARED_OBJECT_CMD_SEND
```

shared object command: send
Constant value: **6**

SHARED_OBJECT_CMD_ERROR

```
public static final byte SHARED_OBJECT_CMD_ERROR
```

shared object command: error
Constant value: **7**

SHARED_OBJECT_CMD_DELETE

```
public static final byte SHARED_OBJECT_CMD_DELETE
```

shared object command: delete
Constant value: **10**

SHARED_OBJECT_CMD_CONNECTSUCCESS

```
public static final byte SHARED_OBJECT_CMD_CONNECTSUCCESS
```

shared object command: clear
Constant value: **11**

SHARED_OBJECT_STATUS_CHANGE

```
public static final byte SHARED_OBJECT_STATUS_CHANGE
```

shared object status: change
Constant value: **4**

SHARED_OBJECT_STATUS_SUCCESS

```
public static final byte SHARED_OBJECT_STATUS_SUCCESS
```

shared object status: success
Constant value: **5**

SHARED_OBJECT_STATUS_CLEAR

```
public static final byte SHARED_OBJECT_STATUS_CLEAR
```

shared object status: clear
Constant value: **8**

SHARED_OBJECT_STATUS_DELETE

```
public static final byte SHARED_OBJECT_STATUS_DELETE
```

(continued from last page)

shared object status: delete
Constant value: **9**

Methods

getSlotNames

```
public java.util.List getSlotNames()
```

Get a list of slot (property) names

Returns:

list of slot (property) names

getSlot

```
public ISharedObjectSlot getSlot(String name)
```

Get ISharedObjectSlot interface to a slot (property) by name

Parameters:

name - slot (property) name

Returns:

ISharedObjectSlot interface

putSlot

```
public void putSlot(String name,  
    ISharedObjectSlot slot)
```

Add a new slot (property) to a shared object.

Parameters:

name - slot (property) name

slot - new slot

getClients

```
public java.util.List getClients()
```

Get a list of client that are connected to this shared object.

Returns:

list of client that are connected to this shared object

isClient

```
public boolean isClient(IClient client)
```

Is this client connected to shared object

Parameters:

client - client

Returns:

true if client is conencted to shared object

addClient

```
public void addClient(IClient client)
```

Add a client to this shared object.

Parameters:

client - client

removeClient

```
public void removeClient(IClient client)
```

Remove a client from this shared object.

Parameters:

client - client

size

```
public int size()
```

Get the number of active slot (properties). Deleted slots are not counted.

Returns:

number of active slot (properties). Deleted slots are not counted

acquire

```
public void acquire()
```

Increment the reference count to this shared object.

release

```
public void release()
```

Decrement the reference count to this shared object.

close

```
public void close()
```

Force close this shared object (not implemented)

getRefCount

```
public int getRefCount()
```

Get the current reference (clients) connected to this shared object. Includes unbalanced count of calls to acquire.

Returns:

the current reference (clients) connected to this shared object

isPersistent

```
public boolean isPersistent()
```

(continued from last page)

Is this shared object being persisted.

Returns:

true if shared object is being persisted

setPersistent

```
public void setPersistent(boolean isPersistent)
```

Set is shared object persisted.

Parameters:

isPersistent - true if shared object is being persisted

getVersion

```
public int getVersion()
```

Get the interval version number.

Returns:

interval version number

setVersion

```
public void setVersion(int version)
```

Set the internal version number.

Parameters:

version - internal version number

flush

```
public void flush()
```

Flush (write to disk) shared object

deleteSlot

```
public void deleteSlot(IClient client,  
    String slotName)
```

Remove a slot (property)

Parameters:

client - client removing slot or null if server side code
slotName - slot (property) name

deleteSlot

```
public void deleteSlot(String slotName)
```

Remove slot (property)

Parameters:

slotName - slot (property) name

getProperty

```
public AMFData getProperty(String slotName)
```

Get slot (property) value.

Parameters:

slotName - slot (property) name

Returns:

slot (property) value as AMFData object

setProperty

```
public void setProperty(String slotName,  
                        String value)
```

Set slot (property) value as a string value (will be wrapped in an AMFDataItem object)

Parameters:

slotName - slot (property) name

value - string value

setProperty

```
public void setProperty(String slotName,  
                        double value)
```

Set slot (property) value as a double value (will be wrapped in an AMFDataItem object)

Parameters:

slotName - slot (property) name

value - double value

setProperty

```
public void setProperty(String slotName,  
                        int value)
```

Set slot (property) value as a int value (will be wrapped in an AMFDataItem object)

Parameters:

slotName - slot (property) name

value - int value

setProperty

```
public void setProperty(String slotName,  
                        long value)
```

Set slot (property) value as a long value (will be wrapped in an AMFDataItem object)

Parameters:

slotName - slot (property) name

value - long value

(continued from last page)

setProperty

```
public void setProperty(String slotName,  
    java.util.Date value)
```

Set slot (property) value as a date value (will be wrapped in an AMFDataItem object)

Parameters:

slotName - slot (property) name
value - date value

setProperty

```
public void setProperty(String slotName,  
    boolean value)
```

Set slot (property) value as a boolean value (will be wrapped in an AMFDataItem object)

Parameters:

slotName - slot (property) name
value - boolean value

setProperty

```
public void setProperty(String slotName,  
    AMFData data)
```

Set slot (property) value as AMFData object.

Parameters:

slotName - slot (property) name
data - slot value as AMFData object. Example: new AMFDataItem((double)1.234) or new AMFDataItem()

disconnect

```
public void disconnect(IClient client)
```

Disconnect client from shared object.

Parameters:

client - client to disconnect

getName

```
public String getName()
```

Get shared object name

Returns:

shared object name

setName

```
public void setName(String name)
```

Set shared object name

Parameters:

name - shared object name

send

```
public void send(String handlerName,  
                 Object[] params)
```

Call client side handler attached to shared object.

Parameters:

handlerName - handler name

params - variable argument list of parameters

send

```
public void send(String handlerName)
```

Call client side handler attached to shared object (no parameters).

Parameters:

handlerName - handler name

addSlotListener

```
public void addSlotListener(ISharedObjectSlotNotify slotListener)
```

Add a slot listener. Will receive the following events: onSlotSetValue and onSlotDelete

Parameters:

slotListener - slot listener

removeSlotListener

```
public void removeSlotListener(ISharedObjectSlotNotify slotListener)
```

Remove slot listener

Parameters:

slotListener - slot listener

getStorageDir

```
public String getStorageDir()
```

Get path used to store shared object.

Returns:

path used to store shared object

setStorageDir

```
public void setStorageDir(String storageDir)
```

Set path used to store shared object.

Parameters:

storageDir - path used to store shared object

(continued from last page)

writeSetValueError

```
public void writeSetValueError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

Write an set value error message back to the client

Parameters:

client - client removing slot or null if server side code
soName - sharedObject name
isPersistent - is persistent
slotName - slot name
errorMsg - error message

writeDeleteError

```
public void writeDeleteError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

Write an delete error message back to the client

Parameters:

client - client removing slot or null if server side code
soName - sharedObject name
isPersistent - is persistent
slotName - slot name
errorMsg - error message

clear

```
public void clear()
```

Clear all properties from a shared object

purge

```
public int purge(int version)
```

Purge all deleted properties older than the version number

Returns:

number of slots purged

getSlots

```
public java.util.List getSlots()
```

Get a list of active slots

Returns:

list of active slots

(continued from last page)

containsProperty

```
public boolean containsProperty(String slotName)
```

Returns true is slot/property name exists

Parameters:

slotName - slot/property name

Returns:

true is slot/property name exists

containsSlot

```
public boolean containsSlot(String slotName)
```

Returns true is slot/property name exists

Parameters:

slotName - slot/property name

Returns:

true is slot/property name exists

lock

```
public void lock()
```

Lock a shared object for write access

unlock

```
public void unlock()
```

Unlock a shared object for write access

getParent

```
public ISharedObjects getParent()
```

Get the shared object container to which this shared object belongs.

Returns:

shared object container

com.wowza.wms.sharedobject Interface ISharedObjectNotify

public interface **ISharedObjectNotify**
extends

ISharedObjectNotify: listener interface used by IApplicationInstance addSharedObjectListener

Method Summary

void	onSharedObjectConnect (ISharedObject sharedObject, IClient client) Triggered when client connects to sharedObject
void	onSharedObjectCreate (ISharedObject sharedObject) Triggered when sharedObject created
void	onSharedObjectDestroy (ISharedObject sharedObject) Triggered when sharedObject destroyed
void	onSharedObjectDisconnect (ISharedObject sharedObject, IClient client) Triggered when client disconnects from sharedObject

Methods

onSharedObjectCreate

public void **onSharedObjectCreate**([ISharedObject](#) sharedObject)

Triggered when sharedObject created

Parameters:

sharedObject - sharedObject

onSharedObjectDestroy

public void **onSharedObjectDestroy**([ISharedObject](#) sharedObject)

Triggered when sharedObject destroyed

Parameters:

sharedObject - sharedObject

onSharedObjectConnect

public void **onSharedObjectConnect**([ISharedObject](#) sharedObject, [IClient](#) client)

Triggered when client connects to sharedObject

Parameters:

sharedObject - sharedObject

client - client

onSharedObjectDisconnect

```
public void onSharedObjectDisconnect(ISharedObject sharedObject,  
    IClient client)
```

Triggered when client disconnects from sharedObject

Parameters:

sharedObject - sharedObject

client - client

com.wowza.wms.sharedobject Interface ISharedObjects

public interface **ISharedObjects**
extends

ISharedObjects: public interface to SharedObjects. Represent the list of shared objects managed by IApplicationInstance.

Method Summary

void	<u>addSharedObjectListener</u> (<u>ISharedObjectNotify</u> sharedObjectListener)
	Add a shared object listener.
void	<u>disconnect</u> (<u>IClient</u> client)
	Disconnect client from all shared objects in list.
boolean	<u>exists</u> (<u>ISharedObject</u> sharedObject)
	Is sharedObject in this list (by shared object reference).
boolean	<u>exists</u> (String objectName)
	Is sharedObject in this list (by name).
void	<u>flush</u> ()
	Flush all persistent shared objects to disk.
<u>ISharedObject</u>	<u>get</u> (String name)
	Get shared object by name.
java.util.List	<u>getObjectNames</u> ()
	Get a list of shared object names.
<u>ISharedObject</u>	<u>getOrCreate</u> (String name)
	Get shared object by name if it does not exist create a new shared object with the given name.
String	<u>getStorageDir</u> ()
	Get the storage directory for all shared objects in list.
boolean	<u>isPersistent</u> ()
	Are shared objects in list persistent.
void	<u>load</u> ()
	Load persistent shared objects from file system.
void	<u>put</u> (String objectName, <u>ISharedObject</u> sharedObject)
	Add or replace a shared object.
void	<u>remove</u> (String objectName)
	Remove a shared object.
void	<u>removeClient</u> (<u>IClient</u> client)
	Remove a client from any shared object that it is connected to in this list.
void	<u>removeSharedObjectListener</u> (<u>ISharedObjectNotify</u> sharedObjectListener)
	Remove a shared object listener.

void	<code>setPersistent</code> (boolean isPersistent) Set is shared object in list persistent
void	<code>setStorageDir</code> (String storageDir) Set the storage directory for all shared objects in list.
int	<code>size</code> () Get number of shared objects.

Methods

size

```
public int size()
```

Get number of shared objects.

Returns:

number of shared objects

get

```
public ISharedObject get(String name)
```

Get shared object by name. If the shared object does not exists null will be returned. (see `ISharedObjects.getOrCreate`)

Parameters:

name - shared object name

Returns:

shared object

getOrCreate

```
public ISharedObject getOrCreate(String name)
```

Get shared object by name if it does not exist create a new shared object with the given name.

Parameters:

name - shared object name

Returns:

shared object

getObjectNames

```
public java.util.List getObjectNames()
```

Get a list of shared object names.

Returns:

list of shared object names

(continued from last page)

put

```
public void put(String objectName,  
    ISharedObject sharedObject)
```

Add or replace a shared object.

Parameters:

objectName - shared object name
sharedObject - shared object

remove

```
public void remove(String objectName)
```

Remove a shared object.

Parameters:

objectName - shared object name

exists

```
public boolean exists(String objectName)
```

Is sharedObject in this list (by name).

Parameters:

objectName - shared object name

Returns:

true if shared object in list

exists

```
public boolean exists(ISharedObject sharedObject)
```

Is sharedObject in this list (by shared object reference).

Parameters:

sharedObject - shared object

Returns:

true if shared object in list

isPersistent

```
public boolean isPersistent()
```

Are shared objects in list persistent.

Returns:

true if shared objects in list are persistent

setPersistent

```
public void setPersistent(boolean isPersistent)
```

Set if shared object in list persistent

(continued from last page)

Parameters:

isPersistent - true is shared objects in list are persistent

removeClient

```
public void removeClient(IClient client)
```

Remove a client from any shared object that it is connected to in this list.

Parameters:

client - client

flush

```
public void flush()
```

Flush all persistent shared objects to disk.

disconnect

```
public void disconnect(IClient client)
```

Disconnect client from all shared objects in list.

Parameters:

client - client

addSharedObjectListener

```
public void addSharedObjectListener(ISharedObjectNotify sharedObjectListener)
```

Add a shared object listener. The listener will receive the following events: onSharedObjectCreate, onSharedObjectDestroy, onSharedObjectConnect, onSharedObjectDisconnect.

Parameters:

sharedObjectListener

removeSharedObjectListener

```
public void removeSharedObjectListener(ISharedObjectNotify sharedObjectListener)
```

Remove a shared object listener.

Parameters:

sharedObjectListener

getStorageDir

```
public String getStorageDir()
```

Get the storage directory for all shared objects in list.

Returns:

storage dir

setStorageDir

```
public void setStorageDir(String storageDir)
```

(continued from last page)

Set the storage directory for all shared objects in list.

Parameters:

storageDir

load

```
public void load()
```

Load persistent shared objects from file system.

com.wowza.wms.sharedobject Interface ISharedObjectSlot

public interface **ISharedObjectSlot**
extends

ISharedObjectSlot: public interface to SharedObjectSlot class.

Method Summary	
AMFData	getData() Get slot data as AMFData object.
int	getLastClientId() Get client id of client that performed last operation on slot.
int	getLastOperation() Get last slot (property) operation.
String	getName() Get slot (property) name.
int	getSlotVersion() Get slot version
int	getSoVersion() Get parent shared object version
void	incSlotVersion() Increment slot version by 1.
void	init (String name, AMFData data, int slotVersion) Initialize shared object slot
void	setData (AMFData data) Set slot data as AMFData object.
void	setData (byte[] data) Set slot data as byte[].
void	setData (byte[] data, AMFDataContextDeserialize context) Set slot data as byte[].
void	setLastClientId (int lastClientId) Set client id of client that performed last operation on slot.
void	setLastOperation (int lastOperation) Set last slot (property) operation.
void	setName (String name) Set slot (property) name
void	setSlotVersion (int slotVersion) Set slot version

void	setSoVersion (int soVersion) Set parent shared object version
------	----------------------------------------------------------------------------------

Methods

init

```
public void init(String name,  
    AMFData data,  
    int slotVersion)
```

Initialize shared object slot

Parameters:

name - slot (property) name
data - data
slotVersion - version

getData

```
public AMFData getData()
```

Get slot data as AMFData object.

Returns:

slot data as AMFData object

setData

```
public void setData(byte[] data,  
    AMFDataContextDeserialize context)
```

Set slot data as byte[]. Data will be deserialized as AMFData object.

Parameters:

data - data as byte[]
context - deserialization context

setData

```
public void setData(byte[] data)
```

Set slot data as byte[]. Data will be deserialized as AMFData object.

Parameters:

data - data as byte[]

setData

```
public void setData(AMFData data)
```

Set slot data as AMFData object.

Parameters:

data - data as AMFData object

getName

```
public String getName()
```

Get slot (property) name.

Returns:

slot (property) name

setName

```
public void setName(String name)
```

Set slot (property) name

Parameters:

name - slot (property) name

getSlotVersion

```
public int getSlotVersion()
```

Get slot version

Returns:

slot version

setSlotVersion

```
public void setSlotVersion(int slotVersion)
```

Set slot version

Parameters:

slotVersion - slot version

incSlotVersion

```
public void incSlotVersion()
```

Increment slot version by 1.

getSoVersion

```
public int getSoVersion()
```

Get parent shared object version

Returns:

parent shared object version

setSoVersion

```
public void setSoVersion(int soVersion)
```

Set parent shared object version

(continued from last page)

Parameters:

soVersion - parent shared object version

getLastOperation

```
public int getLastOperation()
```

Get last slot (property) operation. See ISharedObject.SHAREDOBJECT_CMD_*.

Returns:

last slot (property) operation (ISharedObject.SHAREDOBJECT_CMD_*)

setLastOperation

```
public void setLastOperation(int lastOperation)
```

Set last slot (property) operation. See ISharedObject.SHAREDOBJECT_CMD_*.

Parameters:

lastOperation - last slot (property) operation (ISharedObject.SHAREDOBJECT_CMD_*)

getLastClientId

```
public int getLastClientId()
```

Get client id of client that performed last operation on slot.

Returns:

client id of client that performed last operation on slot

setLastClientId

```
public void setLastClientId(int lastClientId)
```

Set client id of client that performed last operation on slot.

Parameters:

lastClientId - client id of client that performed last operation on slot

com.wowza.wms.sharedobject Interface ISharedObjectSlotNotify

public interface **ISharedObjectSlotNotify**
extends

ISharedObjectNotify: listener interface used by ISharedObject addSlotListener

Method Summary

void	onSlotDelete (ISharedObject sharedObject, ISharedObjectSlot slot) Triggered when sharedObject slot value deleted
void	onSlotSetValue (ISharedObject sharedObject, ISharedObjectSlot slot) Triggered when sharedObject slot value set

Methods

onSlotSetValue

public void **onSlotSetValue**([ISharedObject](#) sharedObject,
[ISharedObjectSlot](#) slot)

Triggered when sharedObject slot value set

Parameters:

sharedObject
slot

onSlotDelete

public void **onSlotDelete**([ISharedObject](#) sharedObject,
[ISharedObjectSlot](#) slot)

Triggered when sharedObject slot value deleted

Parameters:

sharedObject
slot

com.wowza.wms.sharedobject Class SharedObject

java.lang.Object

└─com.wowza.wms.sharedobject.SharedObject

All Implemented Interfaces:

[ISharedObject](#)

public class **SharedObject**
extends Object
implements [ISharedObject](#)

Field Summary

public static final	READACCESS Value: 0
public static final	WRITEACCESS Value: 1

Fields inherited from interface [com.wowza.wms.sharedobject.ISharedObject](#)

[FILEEXTENSION](#), [SHARED_OBJECT_CMD_CONNECT](#), [SHARED_OBJECT_CMD_CONNECTSUCCESS](#),
[SHARED_OBJECT_CMD_DELETE](#), [SHARED_OBJECT_CMD_DISCONNECT](#), [SHARED_OBJECT_CMD_ERROR](#),
[SHARED_OBJECT_CMD_SEND](#), [SHARED_OBJECT_CMD_SETVALUE](#), [SHARED_OBJECT_STATUS_CHANGE](#),
[SHARED_OBJECT_STATUS_CLEAR](#), [SHARED_OBJECT_STATUS_DELETE](#), [SHARED_OBJECT_STATUS_SUCCESS](#)

Constructor Summary

public	SharedObject (String name) Create new shared object
public	SharedObject (String name, boolean isPersistent, String storageDir) Create new shared object

Method Summary

void	acquire ()
void	addClient (IClient client)
void	addSlotListener (ISharedObjectSlotNotify slotListener)
void	clear ()
void	close ()

boolean	<u>containsProperty</u> (String slotName)
boolean	<u>containsSlot</u> (String slotName)
void	<u>deleteSlot</u> (<u>IClient</u> client, String slotName)
void	<u>deleteSlot</u> (String slotName)
void	<u>disconnect</u> (<u>IClient</u> client)
void	<u>flush</u> ()
static boolean[]	<u>getAccess</u> (<u>IClient</u> client, String soName)
java.util.List	<u>getClients</u> ()
void	<u>getClientUpdates</u> (<u>IClient</u> client)
String	<u>getName</u> ()
<u>ISharedObjects</u>	<u>getParent</u> ()
<u>AMFData</u>	<u>getProperty</u> (String slotName)
int	<u>getRefCount</u> ()
<u>ISharedObjectSlot</u>	<u>getSlot</u> (String name)
java.util.List	<u>getSlotNames</u> ()
java.util.List	<u>getSlots</u> ()
String	<u>getStorageDir</u> ()
int	<u>getVersion</u> ()
boolean	<u>isClient</u> (<u>IClient</u> client)
boolean	<u>isPersistent</u> ()
void	<u>load</u> ()
void	<u>lock</u> ()
void	<u>notifySlotDelete</u> (<u>ISharedObjectSlot</u> slot)
void	<u>notifySlotSetValue</u> (<u>ISharedObjectSlot</u> slot)

int	purge (int version)
void	putSlot (String name, ISharedObjectSlot slot)
void	release ()
void	removeClient (IClient client)
void	removeSlotListener (ISharedObjectSlotNotify slotListener)
void	send (String handlerName)
void	send (String handlerName, Object[] params)
void	sendInternal (IClient client, String handlerName, byte[] msgBytes)
void	sendInternal (IClient client, String handlerName, byte[] msgBytes, AMFDataContextDeserialize context)
void	sendInternal (String handlerName, AMFData[] params)
void	setName (String name)
void	setParent (ISharedObjects parent)
void	setPersistent (boolean isPersistent)
void	setProperty (String slotName, AMFData data)
void	setProperty (String slotName, boolean value)
void	setProperty (String slotName, java.util.Date value)
void	setProperty (String slotName, double value)
void	setProperty (String slotName, int value)
void	setProperty (String slotName, long value)
void	setProperty (String slotName, String value)
void	setSlotValue (IClient client, String slotName, AMFData amfData)
void	setSlotValue (IClient client, String slotName, byte[] byteData)
void	setSlotValue (IClient client, String slotName, byte[] byteData, AMFData amfData)

void	setSlotValue(IClient client, String slotName, byte[] byteData, AMFData amfData, AMFDataContextDeserialize context)
void	setSlotValue(IClient client, String slotName, byte[] byteData, AMFDataContextDeserialize context)
void	setStorageDir (String storageDir)
void	setVersion (int version)
int	size ()
void	unlock ()
void	writeDeleteError(IClient client, String soName, boolean isPersistent, String slotName, String errorMsg)
static void	writeError(IClient client, String soName, boolean isPersistent, String errorMsg, boolean isConnect)
void	writeSetValueError(IClient client, String soName, boolean isPersistent, String slotName, String errorMsg)

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface [com.wowza.wms.sharedobject.ISharedObject](#)

[acquire](#), [addClient](#), [addSlotListener](#), [clear](#), [close](#), [containsProperty](#), [containsSlot](#), [deleteSlot](#), [deleteSlot](#), [disconnect](#), [flush](#), [getClients](#), [getName](#), [getParent](#), [getProperty](#), [getRefCount](#), [getSlot](#), [getSlotNames](#), [getSlots](#), [getStorageDir](#), [getVersion](#), [isClient](#), [isPersistent](#), [lock](#), [purge](#), [putSlot](#), [release](#), [removeClient](#), [removeSlotListener](#), [send](#), [send](#), [setName](#), [setPersistent](#), [setProperty](#), [setProperty](#), [setProperty](#), [setProperty](#), [setProperty](#), [setProperty](#), [setStorageDir](#), [setVersion](#), [size](#), [unlock](#), [writeDeleteError](#), [writeSetValueError](#)

Fields

READACCESS

```
public static final int READACCESS
```

Constant value: **0**

WRITEACCESS

```
public static final int WRITEACCESS
```

Constant value: **1**

(continued from last page)

Constructors

SharedObject

```
public SharedObject(String name)
```

Create new shared object

Parameters:

name - shared object name

SharedObject

```
public SharedObject(String name,  
                    boolean isPersistent,  
                    String storageDir)
```

Create new shared object

Parameters:

name - shared object name

isPersistent - is persistent

storageDir - storage directory for persistent shared object

Methods

size

```
public int size()
```

purge

```
public int purge(int version)
```

clear

```
public void clear()
```

getSlots

```
public java.util.List getSlots()
```

getSlotNames

```
public java.util.List getSlotNames()
```

(continued from last page)

getSlot

```
public ISharedObjectSlot getSlot(String name)
```

putSlot

```
public void putSlot(String name,  
    ISharedObjectSlot slot)
```

getClients

```
public java.util.List getClients()
```

isClient

```
public boolean isClient(IClient client)
```

addClient

```
public void addClient(IClient client)
```

removeClient

```
public void removeClient(IClient client)
```

acquire

```
public void acquire()
```

release

```
public void release()
```

getRefCount

```
public int getRefCount()
```

isPersistent

```
public boolean isPersistent()
```

(continued from last page)

setPersistent

```
public void setPersistent(boolean isPersistent)
```

getVersion

```
public int getVersion()
```

setVersion

```
public void setVersion(int version)
```

deleteSlot

```
public void deleteSlot(String slotName)
```

containsProperty

```
public boolean containsProperty(String slotName)
```

containsSlot

```
public boolean containsSlot(String slotName)
```

deleteSlot

```
public void deleteSlot(IClient client,  
                        String slotName)
```

getProperty

```
public AMFData getProperty(String slotName)
```

setProperty

```
public void setProperty(String slotName,  
                        boolean value)
```

setProperty

```
public void setProperty(String slotName,  
    java.util.Date value)
```

setProperty

```
public void setProperty(String slotName,  
    double value)
```

setProperty

```
public void setProperty(String slotName,  
    long value)
```

setProperty

```
public void setProperty(String slotName,  
    int value)
```

setProperty

```
public void setProperty(String slotName,  
    String value)
```

setProperty

```
public void setProperty(String slotName,  
    AMFData data)
```

setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    AMFData amfData)
```

setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData)
```

(continued from last page)

setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData,  
    AMFDataContextDeserialize context)
```

setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData,  
    AMFData amfData)
```

setSlotValue

```
public void setSlotValue(IClient client,  
    String slotName,  
    byte[] byteData,  
    AMFData amfData,  
    AMFDataContextDeserialize context)
```

writeError

```
public static void writeError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String errorMsg,  
    boolean isConnect)
```

writeSetValueError

```
public void writeSetValueError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

writeDeleteError

```
public void writeDeleteError(IClient client,  
    String soName,  
    boolean isPersistent,  
    String slotName,  
    String errorMsg)
```

getClientUpdates

```
public void getClientUpdates(IClient client)
```

(continued from last page)

disconnect

```
public void disconnect(IClient client)
```

getName

```
public String getName()
```

setName

```
public void setName(String name)
```

send

```
public void send(String handlerName,  
                 Object[] params)
```

send

```
public void send(String handlerName)
```

sendInternal

```
public void sendInternal(String handlerName,  
                         AMFData\[\] params)
```

sendInternal

```
public void sendInternal(IClient client,  
                        String handlerName,  
                        byte[] msgBytes)
```

sendInternal

```
public void sendInternal(IClient client,  
                        String handlerName,  
                        byte[] msgBytes,  
                        AMFDataContextDeserialize context)
```

(continued from last page)

addSlotListener

```
public void addSlotListener(ISharedObjectSlotNotify slotListener)
```

removeSlotListener

```
public void removeSlotListener(ISharedObjectSlotNotify slotListener)
```

notifySlotSetValue

```
public void notifySlotSetValue(ISharedObjectSlot slot)
```

notifySlotDelete

```
public void notifySlotDelete(ISharedObjectSlot slot)
```

getStorageDir

```
public String getStorageDir()
```

setStorageDir

```
public void setStorageDir(String storageDir)
```

flush

```
public void flush()
```

load

```
public void load()
```

close

```
public void close()
```

lock

```
public void lock()
```

(continued from last page)

unlock

```
public void unlock()
```

setParent

```
public void setParent(ISharedObjects parent)
```

getParent

```
public ISharedObjects getParent()
```

getAccess

```
public static boolean[] getAccess(IClient client,  
    String soName)
```

Package

com.wowza.wms.stream

com.wowza.wms.stream

Class FastPlaySettings

java.lang.Object

└─com.wowza.wms.stream.FastPlaySettings

public class **FastPlaySettings**
extends Object

FastPlaySettings: data container for fast play settings

Constructor Summary

public	<u>FastPlaySettings()</u> Create empty object
public	<u>FastPlaySettings(double multiplier, int fps, int direction)</u> Create object

Method Summary

int	<u>getDirection()</u> Get direction (1 forward, -1 reverse)
int	<u>getFps()</u> Get frames per second
double	<u>getMultiplier()</u> Get speed of fast play
long	<u>getStartTC()</u> Get the timecode (milliseconds) where this fast play started
long	<u>getStartTCOffset()</u> Get the timecode (milliseconds) where this fast play started (not sure why we have both values)
void	<u>setDirection(int direction)</u> Set direction (1 forward, -1 reverse)
void	<u>setFps(int fps)</u> Set frames per second
void	<u>setMultiplier(double multiplier)</u> Set speed of fast play
void	<u>setStartTC(long startTC)</u> Set the timecode (milliseconds) where this fast play started
void	<u>setStartTCOffset(long startTCOffset)</u> Set the timecode (milliseconds) where this fast play started (not sure why we have both values)

Methods inherited from class java.lang.Object

```
clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait
```

Constructors

FastPlaySettings

```
public FastPlaySettings()
```

Create empty object

FastPlaySettings

```
public FastPlaySettings(double multiplier,  
                        int fps,  
                        int direction)
```

Create object

Parameters:

multiplier - speed

fps - frames per second

direction - direction (1 forward, -1 reverse)

Methods

getFps

```
public int getFps()
```

Get frames per second

Returns:

frames per second

setFps

```
public void setFps(int fps)
```

Set frames per second

Parameters:

fps - frames per second

getMultiplier

```
public double getMultiplier()
```

Get speed of fast play

Returns:

speed of fast play

(continued from last page)

setMultiplier

```
public void setMultiplier(double multiplier)
```

Set speed of fast play

Parameters:

multiplier - speed of fast play

getDirection

```
public int getDirection()
```

Get direction (1 forward, -1 reverse)

Returns:

direction (1 forward, -1 reverse)

setDirection

```
public void setDirection(int direction)
```

Set direction (1 forward, -1 reverse)

Parameters:

direction - direction (1 forward, -1 reverse)

getStartTC

```
public long getStartTC()
```

Get the timecode (milliseconds) where this fast play started

Returns:

timecode of start of fast play (milliseconds)

setStartTC

```
public void setStartTC(long startTC)
```

Set the timecode (milliseconds) where this fast play started

Parameters:

startTC - timecode of start of fast play (milliseconds)

getStartTCOffset

```
public long getStartTCOffset()
```

Get the timecode (milliseconds) where this fast play started (not sure why we have both values)

Returns:

timecode of start of fast play (milliseconds)

setStartTCOffset

```
public void setStartTCOffset(long startTCOffset)
```

(continued from last page)

Set the timecode (milliseconds) where this fast play started (not sure why we have both values)

Parameters:

`startTCOffset` - timecode of start of fast play (milliseconds)

com.wowza.wms.stream Interface IMediaIndexItem

public interface **IMediaIndexItem**
extends

IMediaIndexItem: generic interface to mediaIndex

Field Summary

public static final	MISSING media file is missing Value: **missing**
---------------------	-------------------------------------------------------------------------------

Method Summary

IMediaIndexItem	clone() Make a clone copy of media index
String	getChecksum() Get checksum for media index
int	getExtent() Get the duration (milliseconds) of media index
long	getLastAccessed() Get last time media index was accessed (milliseconds)
boolean	isHitEnd() Is media index complete
void	setChecksum(IRandomAccessReader file) Set media index checksum.
void	setChecksum(String checksum) Set media index checksum
void	setLastAccessed(long time) Set last time media index accessed (milliseconds)
void	touch() Set last time accessed to current time

Fields

MISSING

public static final java.lang.String **MISSING**

media file is missing
Constant value: ****missing****

(continued from last page)

Methods

getExtent

```
public int getExtent()
```

Get the duration (milliseconds) of media index

Returns:

duration (milliseconds)

getChecksum

```
public String getChecksum()
```

Get checksum for media index

Returns:

checksum

setChecksum

```
public void setChecksum(String checksum)
```

Set media index checksum

Parameters:

checksum

setChecksum

```
public void setChecksum(IRandomAccessReader file)
```

Set media index checksum. Extract data from File spec

Parameters:

file

clone

```
public IMediaIndexItem clone()
```

Make a clone copy of media index

Returns:

shallow copy of media index

getLastAccessed

```
public long getLastAccessed()
```

Get last time media index was accessed (milliseconds)

Returns:

time media index was accessed (milliseconds)

(continued from last page)

setLastAccessed

```
public void setLastAccessed(long time)
```

Set last time media index accessed (milliseconds)

Parameters:

time - media index was accessed (milliseconds)

isHitEnd

```
public boolean isHitEnd()
```

Is media index complete

Returns:

true if media index is complete

touch

```
public void touch()
```

Set last time accessed to current time

com.wowza.wms.stream Interface IMediaListProvider

public interface **IMediaListProvider**
extends

Method Summary

MediaList	resolveMediaList (IMediaListReader mediaListReader, IMediaStream stream, String streamName) Called to resolve a amlst:streamname to a media list
---------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

resolveMediaList

```
public MediaList resolveMediaList(IMediaListReader mediaListReader,  
    IMediaStream stream,  
    String streamName)
```

Called to resolve a amlst:streamname to a media list

Parameters:

mediaListReader - mediaListReader
stream - media stream
streamName - stream name

Returns:

media list

com.wowza.wms.stream Interface IMediaListReader

public interface **IMediaListReader**
extends

Method Summary

void	<code>close()</code> close file
<code>IHTTPStreamerSession</code>	<code>getHTTPStreamerSession()</code> Get the HTTPStreamerSession associated with this media list reader
String	<code>getMediaExtension()</code> Get media extension
<code>MediaList</code>	<code>getMediaList()</code> Get the MediaList object
String	<code>getPath()</code> Get abstract path to the media item
void	<code>init(IApplicationInstance appInstance, IMediaStream stream, String mediaReadType, String basePath, String mediaName, IHTTPStreamerSession httpStreamerSession)</code> Initialize mediaReader
boolean	<code>isOpen()</code> is file open
void	<code>open(String basePath, String name)</code> Open the file for reading
void	<code>setHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)</code> Set the HTTPStreamerSession associated with this media list reader
void	<code>setMediaReaderItem(MediaReaderItem mediaReaderItem)</code> Set the mediaReader item definition
void	<code>setProperties(WMSProperties properties)</code> Set the properties for this media reader

Methods

init

```
public void init(IApplicationInstance appInstance,
IMediaStream stream,
String mediaReadType,
String basePath,
String mediaName,
IHTTPStreamerSession httpStreamerSession)
```

(continued from last page)

Initialize mediaReader

Parameters:

stream - parent stream
mediaReadType - media reader type id. Example: flv
basePath - Base path for application instance
mediaName - name of the media item

setMediaReaderItem

```
public void setMediaReaderItem(MediaReaderItem mediaReaderItem)
```

Set the mediaReader item definition

Parameters:

mediaReaderItem

open

```
public void open(String basePath,  
String name)
```

Open the file for reading

Parameters:

basePath - base path to file
name - file name without extension

close

```
public void close()
```

close file

isOpen

```
public boolean isOpen()
```

is file open

Returns:

is file open

setProperties

```
public void setProperties(WMSPProperties properties)
```

Set the properties for this media reader

Parameters:

properties - properties

getPath

```
public String getPath()
```

Get abstract path to the media item

Returns:

(continued from last page)

abstract path to the media item

getMediaExtension

```
public String getMediaExtension()
```

Get media extension

Returns:

media extension

getMediaList

```
public MediaList getMediaList()
```

Get the MediaList object

Returns:

MediaList object

getHTTPStreamerSession

```
public IHTTPStreamerSession getHTTPStreamerSession()
```

Get the HTTPStreamerSession associated with this media list reader

Returns:

HTTPStreamerSession

setHTTPStreamerSession

```
public void setHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Set the HTTPStreamerSession associated with this media list reader

Parameters:

httpStreamerSession - HTTPStreamerSession

com.wowza.wms.stream Interface IMediaReader

public interface **IMediaReader**
extends

IMediaReader: generic media reader interface. All media types implement this interface to interact with PlaylistPlayer.

Field Summary

public static final	<u>CONTENTTYPE_MEDIA</u> Value: 1
public static final	<u>CONTENTTYPE_MEDIALIST</u> Value: 2
public static final	<u>DEFAULT_RANDOMACCESSREADER</u> Value: com.wowza.io.DirectRandomAccessReader
public static final	<u>PLAYEVENT_AFTERBUFFERFILL</u> Value: 5
public static final	<u>PLAYEVENT_AFTERMETADATA</u> Value: 3
public static final	<u>PLAYEVENT_BEFOREBUFFERFILL</u> Value: 4
public static final	<u>PLAYEVENT_BEFOREMETADATA</u> Value: 2
public static final	<u>PLAYEVENT_STARTPLAYBACK</u> Value: 1
public static final	<u>SEEK_EXACT</u> Seek direction: closest frame (audio, video) (key, no-key) Value: 4
public static final	<u>SEEK_KEYCLOSE</u> Seek direction: closest key frame Value: 3
public static final	<u>SEEK_KEYDOWN</u> Seek direction: down to closets key frame Value: 2

public static final	SEEK_KEYUP Seek direction: up to closets key frame Value: 1
public static final	SEEKTARGET_AUDIO Value: 3
public static final	SEEKTARGET_ENHANCED Value: 4
public static final	SEEKTARGET_VIDEOKEYFRAME Value: 1

Method Summary

void	close() close file
long	getDuration() Get duration or time (milliseconds) of the media file
long	getLength() Get the stream length in bytes
String	getMediaExtension() Get media extension
java.util.List	getMetadata() Get a collection of metadata packets in ByteBuffers for this file.
String	getPath() Get abstract path to the media item
IMediaReaderStreamPosition	getStreamPosition() Get a reference to the current stream position
void	init() (IApplicationInstance appInstance, IMediaStream stream, String mediaReadType, String basePath, String mediaName) Initialize mediaReader
boolean	isOpen() is file open
void	open() (String basePath, String name) Open the file for reading
void	rewind() rewind file to start
PlaylistSeekResult	seek() (long timecode, int seektype) seek to timecode in file
int	sendZeroLengthPacket() (int type, int timecode, boolean isAbsolute, IMediaStream stream, java.io.OutputStream out, AMFObj wmsObj, PlaylistCursor flvCursor, PlaylistWriteControl control, PlaylistReaderWriteResults results, long[] sizes, boolean isForceTCZero)

void	<code>setMediaReaderItem</code> (<code>MediaReaderItem</code> mediaReaderItem) Set the mediaReader item definition
void	<code>setProperties</code> (<code>WMSProperties</code> properties) Set the properties for this media reader
void	<code>setStreamPosition</code> (<code>IMediaReaderStreamPosition</code> pos) Set the file position within the media file
void	<code>startPlayback</code> () Called each time the player being playback (before the buffer it filled)
int	<code>writeGeneratedKeyFrame</code> (<code>IMediaStream</code> stream, java.io.OutputStream out, <code>AMFObj</code> wmsObjAudio, <code>AMFObj</code> wmsObjVideo, <code>AMFObj</code> wmsObjData, <code>PlaylistCursor</code> flvCursor, <code>PlaylistWriteControl</code> control, <code>PlaylistReaderWriteResults</code> results, long[] sizes, <code>FastPlaySettings</code> fastPlaySettings, boolean isForceTCZero) From current location in file generate a key frame (enhanced seek) and write it to out
int	<code>writePackets</code> (<code>IMediaStream</code> stream, java.io.OutputStream out, <code>AMFObj</code> wmsObjAudio, <code>AMFObj</code> wmsObjVideo, <code>AMFObj</code> wmsObjData, <code>PlaylistCursor</code> flvCursor, <code>PlaylistWriteControl</code> control, <code>PlaylistReaderWriteResults</code> results, long[] sizes, <code>FastPlaySettings</code> fastPlaySettings, boolean isForceTCZero) From current location in file write packets to output
int	<code>writePackets</code> (java.util.List packetList, <code>PlaylistCursor</code> flvCursor, <code>PlaylistWriteControl</code> control, <code>PlaylistReaderWriteResults</code> results, long[] sizes, <code>FastPlaySettings</code> fastPlaySettings) Write packets to the packetList as AMFPackets

Fields

CONTENTTYPE_MEDIA

```
public static final int CONTENTTYPE_MEDIA
```

Constant value: **1**

CONTENTTYPE_MEDIALIST

```
public static final int CONTENTTYPE_MEDIALIST
```

Constant value: **2**

DEFAULT_RANDOMACCESSREADER

```
public static final java.lang.String DEFAULT_RANDOMACCESSREADER
```

Constant value: **com.wowza.io.DirectRandomAccessReader**

SEEKTARGET_VIDEOKEYFRAME

```
public static final int SEEKTARGET_VIDEOKEYFRAME
```

Constant value: **1**

SEEKTARGET_AUDIO

```
public static final int SEEKTARGET_AUDIO
```

Constant value: **3**

SEEKTARGET_ENHANCED

```
public static final int SEEKTARGET_ENHANCED
```

Constant value: **4**

PLAYEVENT_STARTPLAYBACK

```
public static final int PLAYEVENT_STARTPLAYBACK
```

Constant value: **1**

PLAYEVENT_BEFOREMETADATA

```
public static final int PLAYEVENT_BEFOREMETADATA
```

Constant value: **2**

PLAYEVENT_AFTERMETADATA

```
public static final int PLAYEVENT_AFTERMETADATA
```

Constant value: **3**

PLAYEVENT_BEFOREBUFFERFILL

```
public static final int PLAYEVENT_BEFOREBUFFERFILL
```

Constant value: **4**

PLAYEVENT_AFTERBUFFERFILL

```
public static final int PLAYEVENT_AFTERBUFFERFILL
```

Constant value: **5**

SEEK_KEYUP

```
public static final int SEEK_KEYUP
```

Seek direction: up to closets key frame
Constant value: **1**

(continued from last page)

SEEK_KEYDOWN

```
public static final int SEEK_KEYDOWN
```

Seek direction: down to closets key frame
Constant value: **2**

SEEK_KEYCLOSE

```
public static final int SEEK_KEYCLOSE
```

Seek direction: closest key frame
Constant value: **3**

SEEK_EXACT

```
public static final int SEEK_EXACT
```

Seek direction: closest frame (audio, video) (key, no-key)
Constant value: **4**

Methods

init

```
public void init(IApplicationInstance appInstance,  
                IMediaStream stream,  
                String mediaReadType,  
                String basePath,  
                String mediaName)
```

Initialize mediaReader

Parameters:

stream - parent stream
mediaReadType - media reader type id. Example: flv
basePath - Base path for application instance
mediaName - name of the media item

setMediaReaderItem

```
public void setMediaReaderItem(MediaReaderItem mediaReaderItem)
```

Set the mediaReader item definition

Parameters:

mediaReaderItem

open

```
public void open(String basePath,  
                String name)
```

Open the file for reading

Parameters:

basePath - base path to file
name - file name without extension

getMetadata

```
public java.util.List getMetadata()
```

Get a collection of metadata packets in ByteBuffers for this file. You can use 'new AMFDataList(data)' to convert to AMF objects.

Returns:

collection of metadata packets in ByteBuffers

rewind

```
public void rewind()
```

rewind file to start

close

```
public void close()
```

close file

isOpen

```
public boolean isOpen()
```

is file open

Returns:

is file open

seek

```
public PlaylistSeekResult seek(long timecode,  
    int seektype)
```

seek to timecode in file

Parameters:

timecode - timecode (milliseconds) to seek to
seektype - seek type IMediaReader.SEEK_*

Returns:

detailed results object of seek or null if failure

writePackets

```
public int writePackets(IMediaStream stream,  
    java.io.OutputStream out,  
    AMFObj wmsObjAudio,  
    AMFObj wmsObjVideo,  
    AMFObj wmsObjData,  
    PlaylistCursor flvCursor,  
    PlaylistWriteControl control,  
    PlaylistReaderWriteResults results,  
    long[] sizes,  
    FastPlaySettings fastPlaySettings,  
    boolean isForceTCZero)
```

From current location in file write packets to output

(continued from last page)

Parameters:

stream - parent mediaStream
 out - output stream
 wmsObjAudio - audio channel amfObj
 wmsObjVideo - video channel amfObj
 wmsObjData - data channel amfObj
 flvCursor - current cursor that keeps track of timecodes and flags indicating position in media file
 control - write control flags. Mainly used to control when it should stop writing
 results - write results returned from this routine
 sizes - array of values that keep track of number of bytes written and number of packets for each data type (audio, video, data). See IMediaStreamPlay.PLAYSIZES_*
 fastPlaySettings - current fastPlay settings for the stream
 isForceTCZero - are we forcing all timecodes to zero

Returns:

number of bytes written

writePackets

```
public int writePackets(java.util.List packetList,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    FastPlaySettings fastPlaySettings)
```

Write packets to the packetList as AMFPackets

Parameters:

packetList - list to which to write packets
 flvCursor - current cursor that keeps track of timecodes and flags indicating position in media file
 control - write control flags. Mainly used to control when it should stop writing
 results - write results returned from this routine
 sizes - array of values that keep track of number of bytes written and number of packets for each data type (audio, video, data). See IMediaStreamPlay.PLAYSIZES_*
 fastPlaySettings - current fastPlay settings for the stream

Returns:

number of bytes written

writeGeneratedKeyFrame

```
public int writeGeneratedKeyFrame(IMediaStream stream,
    java.io.OutputStream out,
    AMFObj wmsObjAudio,
    AMFObj wmsObjVideo,
    AMFObj wmsObjData,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    FastPlaySettings fastPlaySettings,
    boolean isForceTCZero)
```

From current location in file generate a key frame (enhanced seek) and write it to out

Parameters:

stream - parent mediaStream
 out - output stream
 wmsObjAudio - audio channel amfObj
 wmsObjVideo - video channel amfObj

(continued from last page)

wmsObjData - data channel amfObj

flvCursor - current cursor that keeps track of timecodes and flags indicating position in media file

control - write control flags. Mainly used to control when it should stop writing

results - write results returned from this routine

sizes - array of values that keep track of number of bytes written and number of packets for each data type (audio, video, data). See IMediaStreamPlay.PLAYSIZES_*

fastPlaySettings - current fastPlay settings for the stream

isForceTCZero - are we forcing all timecodes to zero

Returns:

number of bytes written

sendZeroLengthPacket

```
public int sendZeroLengthPacket(int type,
    int timecode,
    boolean isAbsolute,
    IMediaStream stream,
    java.io.OutputStream out,
    AMFObj wmsObj,
    PlaylistCursor flvCursor,
    PlaylistWriteControl control,
    PlaylistReaderWriteResults results,
    long[] sizes,
    boolean isForceTCZero)
```

startPlayback

```
public void startPlayback()
```

Called each time the player being playback (before the buffer it filled)

getDuration

```
public long getDuration()
```

Get duration or time (milliseconds) of the media file

Returns:

duration or time (milliseconds) of the media file

getLength

```
public long getLength()
```

Get the stream length in bytes

Returns:

stream length in bytes

getPath

```
public String getPath()
```

Get abstract path to the media item

Returns:

abstract path to the media item

getMediaExtension

```
public String getMediaExtension()
```

Get media extension

Returns:

media extension

getStreamPosition

```
public IMediaReaderStreamPosition getStreamPosition()
```

Get a reference to the current stream position

Returns:

stream position

setStreamPosition

```
public void setStreamPosition(IMediaReaderStreamPosition pos)
```

Set the file position within the media file

Parameters:

pos - stream position

setProperty

```
public void setProperty(WMSProperties properties)
```

Set the properties for this media reader

Parameters:

properties - properties

com.wowza.wms.stream Interface IMediaReaderActionNotify

public interface **IMediaReaderActionNotify**
extends

IMediaReaderActionNotify: listener interface for IMediaReader actions: See
IApplicationInstance.addMediaReaderListener(IMediaReaderActionNotify mediaReaderListener)

Method Summary

void	onMediaReaderClose (IMediaReader mediaReader, IMediaStream stream) Called when media reader is closed
void	onMediaReaderCreate (IMediaReader mediaReader) Called when media reader is created
void	onMediaReaderExtractMetaData (IMediaReader mediaReader, IMediaStream stream) Called after media reader metadata is extraced from the file
void	onMediaReaderInit (IMediaReader mediaReader, IMediaStream stream) Called after media reader is initialized
void	onMediaReaderOpen (IMediaReader mediaReader, IMediaStream stream) Called after media reader is opened

Methods

onMediaReaderCreate

public void **onMediaReaderCreate**([IMediaReader](#) mediaReader)

Called when media reader is created

Parameters:

mediaReader - media reader

onMediaReaderInit

public void **onMediaReaderInit**([IMediaReader](#) mediaReader, [IMediaStream](#) stream)

Called after media reader is initialized

Parameters:

mediaReader - media reader

stream - stream

(continued from last page)

onMediaReaderOpen

```
public void onMediaReaderOpen(IMediaReader mediaReader,  
    IMediaStream stream)
```

Called after media reader is opened

Parameters:

mediaReader - media reader

stream - stream

onMediaReaderExtractMetaData

```
public void onMediaReaderExtractMetaData(IMediaReader mediaReader,  
    IMediaStream stream)
```

Called after media reader metadata is extracted from the file

Parameters:

mediaReader - media reader

stream - stream

onMediaReaderClose

```
public void onMediaReaderClose(IMediaReader mediaReader,  
    IMediaStream stream)
```

Called when media reader is closed

Parameters:

mediaReader - media reader

stream - stream

com.wowza.wms.stream Interface IMediaReaderStreamPosition

public interface **IMediaReaderStreamPosition**
extends

IMediaReaderStreamPosition: Internal use

Method Summary

boolean	isValid()
---------	---------------------------

Methods

isValid

public boolean **isValid()**

com.wowza.wms.stream Interface IMediaStream

public interface **IMediaStream**
extends

IMediaStream: public, generic interface to mediaStream object. Upon creation of a new mediaStream, the client connection's default streamType value will be used to dynamically create a mediaStream object based on the definitions available in the vHosts.mediaStreamMap. All mediaStream implementations implement this interface.

Field Summary

public static final	AUDIOSAMPLEACCESS Value: 2
public static final	READACCESS Value: 0
public static final	VIDEOSAMPLEACCESS Value: 3
public static final	WRITEACCESS Value: 1

Method Summary

void	addAudioCodecConfigPacket (long timecode, AMFPacket packet) Set audio codec configuration packet (needed for H.264/AAC playback)
void	addAudioData (byte[] data, int offset, int size) Add data to current audio packet
void	addClientListener (IMediaStreamActionNotify actionListener) Add client listener.
void	addClientListener (IMediaStreamActionNotify2 actionListener) Add client listener.
void	addClientListener (IMediaStreamActionNotify3 actionListener) Add client listener.
void	addDataData (byte[] data, int offset, int size) Add data to current data packet
void	addVideoCodecConfigPacket (long timecode, AMFPacket packet) Set video codec configuration packet (needed for H.264/AAC playback)
void	addVideoData (byte[] data, int offset, int size) Add data to current video packet

void	<u>clear()</u> Delete media file pointed to by this mediaStream (be careful)
void	<u>clearFastPlaySettings()</u> Clear fastPlay settings
void	<u>clearLoggingValues()</u>
void	<u>close()</u> Close mediaStream
void	<u>flush()</u> Force publishing packets to be flushed from the input buffers to the output buffers
boolean[]	<u>getAccess(IClient client, String name)</u> Get the read/write access to this stream for this client
<u>AMFPacket</u>	<u>getAudioCodecConfigPacket(long timecode)</u> Get audio codec configuration packet (needed for H.264/AAC playback)
int	<u>getAudioMissing()</u> Get number of audio bytes missing from current audio packet
int	<u>getAudioSize()</u> Get the size of the current audio packet that is being streamed from the client to the server
long	<u>getAudioTC()</u> Get last absolute audio timecode (milliseconds) sent to mediaStream
int	<u>getBufferTime()</u> Get buffer time for mediaStream (milliseconds)
byte[]	<u>getBurstStartStop(boolean isStart)</u> Get the dynamic streaming burst start/stop AMF packet
String	<u>getCacheName()</u> not used
<u>IClient</u>	<u>getClient()</u> Get parent client connection
int	<u>getClientId()</u> Get parent client connection (id)
String	<u>getContextStr()</u> Returns the stream context string in the form [application]/[appInstance]/[streamName].
int	<u>getDataMissing()</u> Get number of data bytes missing from current audio packet
int	<u>getDataSize()</u> Get the size of the current data packet that is being streamed from the client to the server
long	<u>getDataTC()</u> Get last absolute data timecode (milliseconds) sent to mediaStream
int	<u>getDataType()</u> Get the data packet type: (IVHost.CONTENTTYPE_DATA0 or IVHost.CONTENTTYPE_DATA3)

String	<code>getDvrRecorder()</code> Get the DVR Recorder for this stream
<code>ILiveStreamDvrRecorder</code>	<code>getDvrRecorder(String name)</code> Get the DVR Recorder interface to a stream by name
String	<code>getDvrRecorderList()</code> Get the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)
String	<code>getDvrRepeater()</code> Get the DVR repeater name for this stream
<code>ElapsedTimer</code>	<code>getElapsedTime()</code> Get the interface to the elapse timer
String	<code>getExt()</code> Get media file extension
<code>FastPlaySettings</code>	<code>getFastPlaySettings()</code> Get current fastPlay settings
int	<code>getHeaderSize()</code> Get the last packet header size (debugging)
<code>IHTTPStreamerSession</code>	<code>getHTTPStreamerSession()</code> Get the HTTPStreamer session associated with this stream
<code>AMFPacket</code>	<code>getLastKeyFrame()</code> Get most recent video key frame
<code>AMFPacket</code>	<code>getLastPacket()</code> Get most recent live packet
String	<code>getLiveStreamPacketizer()</code> Get the live stream packetizer that this stream is using
<code>ILiveStreamPacketizer</code>	<code>getLiveStreamPacketizer(String name)</code> Get the LiveStreamPacketizer interface to a stream by name
String	<code>getLiveStreamPacketizerList()</code> Get the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)
String	<code>getLiveStreamRepeater()</code> Get the live stream repeater name for the stream
<code>ILiveStreamTranscoder</code>	<code>getLiveStreamTranscoder(String name)</code> Get a live stream transcoder for this stream by name
String	<code>getLiveStreamTranscoderList()</code> Get the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)
java.util.Map	<code>getLiveStreamTranscoders()</code> Get the list of transcoders for this stream.
long	<code>getMaxTimecode()</code> Get the timecode of the latest received packet

<u>IOPerformanceCounter</u>	<u>getMediaIOPerformance()</u> Get IO performance counter
<u>IMediaStreamMetaDataProvider</u>	<u>getMetaDataProvider()</u> Get the metaData provider
String	<u>getName()</u> Get stream name
com.wowza.wms.netconnection.INetConnection	<u>getNetConnection()</u> Get parent netConnection (future server to server communication)
<u>IMediaStreamPlay</u>	<u>getPlayer()</u> Get underlying player (IMediaStreamPlay) object
java.util.List	<u>getPlayPackets()</u> Get all available live packets
<u>WMSProperties</u>	<u>getProperties()</u> Get mediaStream properties
int	<u>getPublishAudioCodecId()</u> Get the codec id of the most recently published audio packet
int	<u>getPublishVideoCodecId()</u> Get the codec id of the most recently published video packet
String	<u>getQueryStr()</u> Get play/publish name query string.
int	<u>getReceiveVideoFPS()</u> Set frame per seconds for video (not currently implemented)
<u>AMFObj</u>	<u>getRespAMFAudioObj()</u> Get audio response channel object
<u>AMFObj</u>	<u>getRespAMFDataObj()</u> Get data response channel object
<u>AMFObj</u>	<u>getRespAMFVideoObj()</u> Get video response channel object
<u>RTPStream</u>	<u>getRTPStream()</u> Get the RTP based stream this stream is associated with
int	<u>getSrc()</u> Get the stream id
java.io.File	<u>getStreamFileForRead()</u> Get the File object to read from a stream (get stream name, ext and query from stream object)
java.io.File	<u>getStreamFileForRead(String name, String ext, String query)</u> Get the File object to read from a stream (specify name, ext and query)
java.io.File	<u>getStreamFileForWrite()</u> Get the File object to write to a stream (get stream name, ext and query from stream object)
java.io.File	<u>getStreamFileForWrite(String name, String ext, String query)</u> Get the File object to write to a stream (specify name, ext and query)

MediaStreamMap	getStreams() Get parent mediaStreamMap (owned by applicationInstance)
String	getStreamType() Get mediaStream streamType
String	getUniqueStreamIdStr() Get a string that uniquely identifies this stream
AMFPacket	getVideoCodecConfigPacket(long timecode) Get video codec configuration packet (needed for H.264/AAC playback)
int	getVideoMissing() Get number of video bytes missing from current audio packet
int	getVideoSize() Get the size of the current video packet that is being streamed from the client to the server
long	getVideoTC() Get last absolute video timecode (milliseconds) sent to mediaStream
void	handleCallback(com.wowza.wms.request.RequestFunction function) Routes request function to callback handler onStatus, onPlayStatus or [method/handler]
boolean	idle() Allow the mediaStream to perform idle work (not currently in use)
long	incrementMediaInBytes(long increment) Increment the number of mediaStream bytes received
long	incrementMediaLossBytes(long bytes, long count) Increment the number of mediaStream loss bytes sent and number of packets sent
long	incrementMediaOutBytes(long bytes, long count) Increment the number of mediaStream bytes sent and number of packets sent
void	init(MediaStreamMap parent, int src, WMSProperties properties) Initialize the mediaStream object after creation.
void	initLiveStreamRepeating(String liveStreamPacketizer, String liveStreamRepeater) Initialize this stream for live stream repeating
boolean	isAppend() Is append to media file (only valid if isRecord)
boolean	isClustered() not used
boolean	isMediaCasterPlay() Is MediaCaster play enabled (if true, will trigger MediaCaster startup)
boolean	isMergeOnMetadata() If true, merge incoming onMetadata events with the current onMetadata event data.
boolean	isOpen() Is mediaStream open
boolean	isPlay() Is the stream a play stream (vs a publish stream)

boolean	<u>isPlaying()</u> Is mediaStream playing (or paused - false)
boolean	<u>isPublishStreamReady()</u> (boolean checkAudio, boolean checkVideo) Returns true if the publishing stream contains enough video/audio data to start playback
boolean	<u>isReceiveAudio()</u> Is client currently receiving audio.
boolean	<u>isReceiveVideo()</u> Is client currently receiving video.
boolean	<u>isRecord()</u> Is this stream being recorded to a file
boolean	<u>isSendPlayStopLogEvent()</u> Get need to send a log event for stop
boolean	<u>isSendPublishStopLogEvent()</u> Get need to send a log event for publishing
boolean	<u>isSendRecordStopLogEvent()</u> Get need to send a log event for recording
boolean	<u>isTranscodeResult()</u> Is this stream the result of a transcode operation.
double	<u>length()</u> Get length/duration (seconds) of media file pointed to by mediaStream
void	<u>notifyActionOnCodecInfoAudio()</u> (com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio) Notify client listeners of audio codec information change
void	<u>notifyActionOnCodecInfoVideo()</u> (com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Notify client listeners of video codec information change
void	<u>notifyActionOnMetaData()</u> (<u>AMFPacket</u> metaDataPacket) Notify client listeners of onMetaData change
void	<u>notifyActionPause()</u> (boolean isPause, long location) Notify client listeners of pause action
void	<u>notifyActionPauseRaw()</u> (boolean isPause, long location) Notify client listeners of pauseRaw action
void	<u>notifyActionPlay()</u> (String streamName, double playStart, double playLen, int playReset) Notify client listeners of play action
void	<u>notifyActionPublish()</u> (String streamName, boolean isRecord, boolean isAppend) Notify client listeners of publish action
void	<u>notifyActionSeek()</u> (double location) Notify client listeners of seek action
void	<u>notifyActionStop()</u> Notify client listeners of stop action

void	<u>notifyActionUnPublish</u> (String streamName, boolean isRecord, boolean isAppend) Notify client listeners of unpublish action
void	<u>packetComplete</u> () Invoked by requestAdapter when at the end of a set of packets
void	<u>publish</u> () Publish mediaStream
void	<u>putDvrRecorder</u> (String name, <u>ILiveStreamDvrRecorder</u> dvr) Add a live stream dvr to this stream
void	<u>putLiveStreamTranscoder</u> (String name, <u>ILiveStreamTranscoder</u> liveStreamTranscoder) Add a live stream transcoder to this stream
void	<u>registerCallback</u> (String handlerName, <u>IMediaStreamCallback</u> callback) Register a callback handler
void	<u>registerOnPlayStatus</u> (<u>IMediaStreamCallback</u> callback) Register onPlayStatus handler
void	<u>registerOnStatus</u> (<u>IMediaStreamCallback</u> callback) Register onStatus handler
void	<u>removeClientListener</u> (<u>IMediaStreamActionNotify</u> actionListener) Remove client listener.
void	<u>removeClientListener</u> (<u>IMediaStreamActionNotify2</u> actionListener) Remove client listener.
void	<u>removeClientListener</u> (<u>IMediaStreamActionNotify3</u> actionListener) Remove client listener.
<u>ILiveStreamDvrRecorder</u>	<u>removeDvrRecorder</u> (String name) Remove a live stream dvr by name
<u>ILiveStreamTranscoder</u>	<u>removeLiveStreamTranscoder</u> (String name) Remove a live stream transcoder by name
void	<u>send</u> (String handlerName) Call client side NetStream method/handler with no parameters
void	<u>send</u> (String handlerName, Object[] params) Call client side NetStream method/handler
void	<u>sendAMF3</u> (String handlerName) Call client side NetStream method/handler with no parameters.
void	<u>sendAMF3</u> (String handlerName, Object[] params) Call client side NetStream method/handler.
int	<u>sendControlBytes</u> (int controlType, java.io.OutputStream out) Send playback control bytes.
void	<u>sendDirect</u> (String handlerName) Call client side NetStream method/handler and send event to underlying stream (will record event)

void	<code>sendDirect</code> (String handlerName, Object[] params) Call client side NetStream method/handler and send event to underlying stream (will record event)
void	<code>sendDirectAMF3</code> (String handlerName) Call client side NetStream method/handler and send event to underlying stream (will record event).
void	<code>sendDirectAMF3</code> (String handlerName, Object[] params) Call client side NetStream method/handler and send event to underlying stream (will record event).
int	<code>sendLivePlaySeek</code> (java.io.OutputStream out, String name, long timecode) Send onStatus(NetStream.Seek.Notify) event
int	<code>sendLivePlayStart</code> (java.io.OutputStream out, String name, long timecode, long timecodeOffset) Send onStatus(NetStream.Play.Start) event
int	<code>sendLivePlaySwitch</code> (java.io.OutputStream out, String name, long timecode) Send onStatus(NetStream.Play.Transition) event
int	<code>sendPauseNotify</code> (long timecode, String name) Send onStatus(NetStream.Pause.Notify) event
int	<code>sendPauseNotify</code> (java.io.OutputStream out, long timecode, String name) Send onStatus(NetStream.Pause.Notify) event.
int	<code>sendPlayReset</code> (java.io.OutputStream out, String name) Send onStatus(NetStream.Play.Reset) event.
int	<code>sendPlayReset</code> (String name) Send onStatus(NetStream.Play.Reset) event
int	<code>sendPlaySeek</code> (long location, long seekLocation, String name) Send onStatus(NetStream.Seek.Notify) event.
int	<code>sendPlaySeek</code> (java.io.OutputStream out, long location, long seekLocation, String name) Send onStatus(NetStream.Seek.Notify) event.
int	<code>sendPlaySeek</code> (java.io.OutputStream out, long location, long seekLocation, String name, java.util.List seekTypes) Send onStatus(NetStream.Seek.Notify) event.
int	<code>sendPlayStart</code> (java.io.OutputStream out, String name, boolean isSwitch, boolean isLive, long timecode, java.util.List seekTypes) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<code>sendPlayStart</code> (java.io.OutputStream out, String name, boolean isSwitch, long timecode) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<code>sendPlayStart</code> (java.io.OutputStream out, String name, boolean isSwitch, long timecode, java.util.List seekTypes) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).

int	<code>sendPlayStart</code> (String name, long timecode) Send onStatus(NetStream.Play.Start) event
int	<code>sendPlayStatus</code> (long timecode, int statusType, double duration, double bytesSent) Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event
int	<code>sendPlayStatus</code> (java.io.OutputStream out, long timecode, int statusType, double duration, double bytesSent) Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event.
int	<code>sendPlayStop</code> (long location, String name) Send onStatus(NetStream.Play.Stop) event
int	<code>sendPlayStop</code> (java.io.OutputStream out, long location, String name) Send onStatus(NetStream.Play.Stop) event.
int	<code>sendPlaySwitch</code> (java.io.OutputStream out, String name, boolean isSwitch, long timecode) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<code>sendPlaySwitch</code> (String name, long timecode) Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).
int	<code>sendStreamNotFound</code> (java.io.OutputStream out, String name) Send onStatus(NetStream.Play.StreamNotFound) event.
int	<code>sendStreamNotFound</code> (String name) Send onStatus(NetStream.Play.StreamNotFound) event
int	<code>sendUnpauseNotify</code> (long location, String name) Send onStatus(NetStream.Unpause.Notify) event
int	<code>sendUnpauseNotify</code> (java.io.OutputStream out, long location, String name) Send onStatus(NetStream.Unpause.Notify) event.
int	<code>sendUnpauseNotify</code> (java.io.OutputStream out, long location, String name, java.util.List seekTypes) Send onStatus(NetStream.Unpause.Notify) event
int	<code>sendVODPlaySwitch</code> (java.io.OutputStream out, String name, long timecode) Send onStatus(NetStream.Play.Transition) event
void	<code>setAppend</code> (boolean isAppend) Set is append to media file (only valid if isRecord)
void	<code>setAudioSize</code> (int audioSize) Set the size of the current audio packet that is being streamed from the client to the server
void	<code>setAudioTC</code> (long audioTC) Set last absolute audio timecode (milliseconds) sent to mediaStream
void	<code>setAudioTC</code> (long audioTC, boolean isAbsolute) Set last absolute audio timecode (milliseconds) sent to mediaStream
void	<code>setBufferTime</code> (int bufferTime) Set buffer time for mediaStream (milliseconds)

void	<u>setClient</u> (<u>IClient</u> client) Set parent client connection
void	<u>setClustered</u> (boolean isClustered) not used
void	<u>setDataSize</u> (int dataSize) Set the size of the current data packet that is being streamed from the client to the server
void	<u>setDataTC</u> (long dataTC) Set last absolute data timecode (milliseconds) sent to mediaStream
void	<u>setDataTC</u> (long dataTC, boolean isAbsolute) Set last absolute data timecode (milliseconds) sent to mediaStream
void	<u>setDataType</u> (int dataType) Set the data packet type: (IVHost.CONTENTTYPE_DATA0 or IVHost.CONTENTTYPE_DATA3)
void	<u>setDvrRecorder</u> (String recorderName) Set the DVR Recorder that this stream is using
void	<u>setDvrRecorderList</u> (String recorderList) Set the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)
void	<u>setExt</u> (String ext) Set media file extension
void	<u>setFastPlaySettings</u> (<u>FastPlaySettings</u> fastPlaySettings) Set fastPlay settings
void	<u>setHeaderSize</u> (int headerSize) Set the last packet header size (debugging)
void	<u>setHTTPStreamerSession</u> (<u>IHTTPStreamerSession</u> httpStreamerSession) Set the HTTPStreamer session associated with this stream
void	<u>setIsPlaying</u> (boolean isPlaying) Set is mediaStream playing
void	<u>setLiveStreamPacketizer</u> (String liveStreamPacketizer) Set the live stream packetizer that this stream is using
void	<u>setLiveStreamPacketizerList</u> (String liveStreamPacketizerList) Set the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)
void	<u>setLiveStreamRepeater</u> (String liveStreamRepeater) Set the live stream repeater name for the stream
void	<u>setLiveStreamTranscoderList</u> (String liveStreamTranscoderList) Set the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)
void	<u>setMediaCasterPlay</u> (boolean isMediaCasterPlay) Is MediaCaster play enabled (if true, will trigger MediaCaster startup)
void	<u>setMergeOnMetadata</u> (boolean mergeOnMetadata) If true, merge incoming onMetadata events with the current onMetadata event data.

void	<u>setMetaDataProvider</u> (<u>IMediaStreamMetaDataProvider</u> metaDataProvider) Set the metaData provider
void	<u>setName</u> (String name) Set stream name
void	<u>setName</u> (String name, String ext) Set stream name and extension.
void	<u>setName</u> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Set stream name, extension, query string, play start, play len and play reset from play command.
void	<u>setNetConnection</u> (com.wowza.wms.netconnection.INetConnection netConnection) Set parent netConnection (future server to server communication)
void	<u>setOpen</u> (boolean isOpen) Set mediaStream open
void	<u>setPlay</u> (boolean isPlay) Set is the stream a play stream (vs a publish stream)
void	<u>setPlayer</u> (<u>IMediaStreamPlay</u> player) Set underlying player (IMediaStreamPlay) object
void	<u>setPublishAudioCodecId</u> (int publishAudioCodecId) Set the codec id of the most recently published audio packet
void	<u>setPublishVideoCodecId</u> (int publishVideoCodecId) Set the codec id of the most recently published video packet
void	<u>setQueryStr</u> (String queryStr) Set play/publish name query string.
void	<u>setReceiveAudio</u> (boolean receiveAudio) Set receive audio
void	<u>setReceiveVideo</u> (boolean receiveVideo) Set receive video
void	<u>setReceiveVideoFPS</u> (int receiveVideoFPS) Set frame per second for video (not currently implemented)
void	<u>setRecord</u> (boolean isRecord) Set is the stream being recorded
void	<u>setRTPStream</u> (<u>RTPStream</u> rtpStream) Set the RTP based stream this stream is associated with
void	<u>setSendPlayStopLogEvent</u> (boolean sendPlayStopLogEvent) Set need to send a log event for stop
void	<u>setSendPublishStopLogEvent</u> (boolean sendPlayStopLogEvent) Set need to send a log event for publishing
void	<u>setSendRecordStopLogEvent</u> (boolean sendPlayStopLogEvent) Set need to send a log event for recording

void	<code>setSrc(int src)</code> Set stream id
void	<code>setStreamType(String streamType)</code> Set mediaStream streamType.
void	<code>setTranscodeResult(boolean isTranscodeResult)</code> Is this stream the result of a transcode operation.
void	<code>setVideoSize(int videoSize)</code> Set the size of the current video packet that is being streamed from the client to the server
void	<code>setVideoTC(long videoTC)</code> Set last absolute video timecode (milliseconds) sent to mediaStream
void	<code>setVideoTC(long videoTC, boolean isAbsolute)</code> Set last absolute video timecode (milliseconds) sent to mediaStream
void	<code>shutdown()</code> shutdown or close this mediaStream
long	<code>size()</code> Get size (bytes) of media file pointed to by mediaStream
void	<code>startAudioPacket()</code> Called when an audio packet is first being populated with data
void	<code>startDataPacket()</code> Called when a data packet is first being populated with data
void	<code>startPublishing()</code> Start publishing live stream
void	<code>startVideoPacket()</code> Called when a video packet is first being populated with data
void	<code>stopName(String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition)</code> Stop stream name
void	<code>stopPublishing()</code> Stop publishing live stream
void	<code>switchName(String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition)</code> Switch to stream name
void	<code>trim()</code> Trim mediaStream.
void	<code>unregisterCallback(String handlerName)</code> Unregister a callback handler
void	<code>unregisterOnPlayStatus(IMediaStreamCallback callback)</code> Unregister onPlayStatus handler
void	<code>unregisterOnStatus(IMediaStreamCallback callback)</code> Unregister onStatus handler

void	updateLoggingDuration() Update logging.MDC with mediaStream logging information
void	updateLoggingValues() Update logging.MDC with mediaStream logging information

Fields

READACCESS

public static final int **READACCESS**

Constant value: **0**

WRITEACCESS

public static final int **WRITEACCESS**

Constant value: **1**

AUDIOSAMPLEACCESS

public static final int **AUDIOSAMPLEACCESS**

Constant value: **2**

VIDEOSAMPLEACCESS

public static final int **VIDEOSAMPLEACCESS**

Constant value: **3**

Methods

init

```
public void init(MediaStreamMap parent,
                 int src,
                 WMSProperties properties)
```

Initialize the mediaStream object after creation. Creation and initialization are separated due to the order of the creation events.

Parameters:

parent - parent mediaStreamMap of the parent applicationInstance
 src - stream id for this stream
 properties - initial properties as defined in Streams.xml

getBufferTime

```
public int getBufferTime()
```

Get buffer time for mediaStream (milliseconds)

(continued from last page)

Returns:

buffer time (milliseconds)

setBufferTime

```
public void setBufferTime(int bufferTime)
```

Set buffer time for mediaStream (milliseconds)

Parameters:

bufferTime - buffer time (milliseconds)

isPlaying

```
public boolean isPlaying()
```

Is mediaStream playing (or paused - false)

Returns:

is playing

setIsPlaying

```
public void setIsPlaying(boolean isPlaying)
```

Set is mediaStream playing

Parameters:

isPlaying

getAudioSize

```
public int getAudioSize()
```

Get the size of the current audio packet that is being streamed from the client to the server

Returns:

size

getVideoSize

```
public int getVideoSize()
```

Get the size of the current video packet that is being streamed from the client to the server

Returns:

size

getDataSize

```
public int getDataSize()
```

Get the size of the current data packet that is being streamed from the client to the server

Returns:

size

(continued from last page)

setAudioSize

```
public void setAudioSize(int audioSize)
```

Set the size of the current audio packet that is being streamed from the client to the server

Parameters:

audioSize

setVideoSize

```
public void setVideoSize(int videoSize)
```

Set the size of the current video packet that is being streamed from the client to the server

Parameters:

videoSize

setDataSize

```
public void setDataSize(int dataSize)
```

Set the size of the current data packet that is being streamed from the client to the server

Parameters:

dataSize

getSrc

```
public int getSrc()
```

Get the stream id

Returns:

stream id

setSrc

```
public void setSrc(int src)
```

Set stream id

Parameters:

src - stream id

getName

```
public String getName()
```

Get stream name

Returns:

stream name

setName

```
public void setName(String name)
```

(continued from last page)

Set stream name

Parameters:

name - stream name

setName

```
public void setName(String name,  
                    String ext)
```

Set stream name and extension. Example: if play command sent flv:test name=test, ext=flv.

Parameters:

name - stream name

ext - stream extension

setName

```
public void setName(String name,  
                    String oldName,  
                    String ext,  
                    String queryStr,  
                    double playStart,  
                    double playLen,  
                    int playTransition)
```

Set stream name, extension, query string, play start, play len and play reset from play command.

Parameters:

name - stream name

oldName - old stream name

ext - stream extension

queryStr - query string

playStart - play start

playLen - play len

playTransition - play transition (see MediaBase.PLAYTRANSITION_*)

switchName

```
public void switchName(String name,  
                        String oldName,  
                        String ext,  
                        String queryStr,  
                        double playStart,  
                        double playLen,  
                        int playTransition)
```

Switch to stream name

Parameters:

name - stream name

oldName - old stream name

ext - stream extension

queryStr - query string

playStart - play start

playLen - play len

playTransition - play transition (see MediaBase.PLAYTRANSITION_*)

(continued from last page)

stopName

```
public void stopName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Stop stream name

Parameters:

name - stream name

oldName - old stream name

ext - stream extension

queryStr - query string

playStart - play start

playLen - play len

playTransition - play transition (see MediaBase.PLAYTRANSITION_*)

shutdown

```
public void shutdown()
```

shutdown or close this mediaStream

getAudioTC

```
public long getAudioTC()
```

Get last absolute audio timecode (milliseconds) sent to mediaStream

Returns:

last absolute audio timecode (milliseconds)

setAudioTC

```
public void setAudioTC(long audioTC,  
    boolean isAbsolute)
```

Set last absolute audio timecode (milliseconds) sent to mediaStream

Parameters:

audioTC - timecode (milliseconds)

isAbsolute - is the timecode value relative to last timecode or absolute

setAudioTC

```
public void setAudioTC(long audioTC)
```

Set last absolute audio timecode (milliseconds) sent to mediaStream

Parameters:

audioTC - timecode (milliseconds)

getVideoTC

```
public long getVideoTC()
```

(continued from last page)

Get last absolute video timecode (milliseconds) sent to mediaStream

Returns:

last absolute video timecode (milliseconds)

setVideoTC

```
public void setVideoTC(long videoTC,  
    boolean isAbsolute)
```

Set last absolute video timecode (milliseconds) sent to mediaStream

Parameters:

videoTC - timecode (milliseconds)

isAbsolute - is the timecode value relative to last timecode or absolute

setVideoTC

```
public void setVideoTC(long videoTC)
```

Set last absolute video timecode (milliseconds) sent to mediaStream

Parameters:

videoTC - timecode (milliseconds)

getDataTC

```
public long getDataTC()
```

Get last absolute data timecode (milliseconds) sent to mediaStream

Returns:

last absolute data timecode (milliseconds)

setDataTC

```
public void setDataTC(long dataTC,  
    boolean isAbsolute)
```

Set last absolute data timecode (milliseconds) sent to mediaStream

Parameters:

dataTC - timecode (milliseconds)

isAbsolute - is the timecode value relative to last timecode or absolute

getDataType

```
public int getDataType()
```

Get the data packet type: (IVHost.CONTENTTYPE_DATA0 or IVHost.CONTENTTYPE_DATA3)

Returns:

data packet type

setDataType

```
public void setDataType(int dataType)
```

(continued from last page)

Set the data packet type: (IVHost.CONTENT*TYPE_DATA0 or IVHost.CONTENT*TYPE_DATA3)

Parameters:

data`Type` - data packet type

setDataTC

```
public void setDataTC(long dataTC)
```

Set last absolute data timecode (milliseconds) sent to mediaStream

Parameters:

dataTC - timecode (milliseconds)

isRecord

```
public boolean isRecord( )
```

Is this stream being recorded to a file

Returns:

is stream being recorded

setRecord

```
public void setRecord(boolean isRecord)
```

Set is the stream being recorded

Parameters:

isRecord

isPlay

```
public boolean isPlay( )
```

Is the stream a play stream (vs a publish stream)

Returns:

is play stream (has nothing to do with if its playing just that its play vs publish)

setPlay

```
public void setPlay(boolean isPlay)
```

Set is the stream a play stream (vs a publish stream)

Parameters:

isPlay - is play stream (has nothing to do with if its playing just that its play vs publish)

idle

```
public boolean idle( )
```

Allow the mediaStream to perform idle work (not currently in use)

Returns:

true if it did some work

getClientId

```
public int getClientId()
```

Get parent client connection (id)

Returns:

parent client connection (id)

getClient

```
public IClient getClient()
```

Get parent client connection

Returns:

parent client connection

getNetConnection

```
public com.wowza.wms.netconnection.INetConnection getNetConnection()
```

Get parent netConnection (future server to server communication)

Returns:

parent netConnection connection

setNetConnection

```
public void setNetConnection(com.wowza.wms.netconnection.INetConnection netConnection)
```

Set parent netConnection (future server to server communication)

Parameters:

netConnection - netConnection connection

setClient

```
public void setClient(IClient client)
```

Set parent client connection

Parameters:

client - parent client connection

getStreams

```
public MediaStreamMap getStreams()
```

Get parent mediaStreamMap (owned by applicationInstance)

Returns:

parent mediaStreamMap

packetComplete

```
public void packetComplete()
```

(continued from last page)

Invoked by requestAdapter when at the end of a set of packets

sendStreamNotFound

```
public int sendStreamNotFound(String name)
```

Send onStatus(NetStream.Play.StreamNotFound) event

Parameters:

name - stream name

Returns:

bytes sent to client

sendStreamNotFound

```
public int sendStreamNotFound(java.io.OutputStream out,  
    String name)
```

Send onStatus(NetStream.Play.StreamNotFound) event. Send directly to OutputStream.

Parameters:

out - OutputStream

name - stream name

Returns:

bytes sent to client

sendLivePlayStart

```
public int sendLivePlayStart(java.io.OutputStream out,  
    String name,  
    long timecode,  
    long timecodeOffset)
```

Send onStatus(NetStream.Play.Start) event

Parameters:

out - OutputStream

name - stream name

timecode - timecode

timecodeOffset - timecode offset

Returns:

bytes sent to client

sendVODPlaySwitch

```
public int sendVODPlaySwitch(java.io.OutputStream out,  
    String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Transition) event

Parameters:

out - OutputStream

name - stream name

timecode - timecode

(continued from last page)

Returns:

bytes sent to client

sendLivePlaySwitch

```
public int sendLivePlaySwitch( java.io.OutputStream out,  
    String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Transition) event

Parameters:

out - OutputStream
name - stream name
timecode - timecode

Returns:

bytes sent to client

sendLivePlaySeek

```
public int sendLivePlaySeek( java.io.OutputStream out,  
    String name,  
    long timecode)
```

Send onStatus(NetStream.Seek.Notify) event

Parameters:

out - OutputStream
name - stream name
timecode - timecode

Returns:

bytes sent to client

sendPlayReset

```
public int sendPlayReset(String name)
```

Send onStatus(NetStream.Play.Reset) event

Parameters:

name - stream name

Returns:

bytes sent to client

sendPlayReset

```
public int sendPlayReset( java.io.OutputStream out,  
    String name)
```

Send onStatus(NetStream.Play.Reset) event. Send directly to OutputStream.

Parameters:

out - OutputStream
name - stream name

Returns:

(continued from last page)

bytes sent to client

sendPlayStop

```
public int sendPlayStop(long location,  
    String name)
```

Send onStatus(NetStream.Play.Stop) event

Parameters:

location - timecode where play stopped
name - stream name

Returns:

bytes sent to client

sendPlayStop

```
public int sendPlayStop(java.io.OutputStream out,  
    long location,  
    String name)
```

Send onStatus(NetStream.Play.Stop) event. Send directly to OutputStream

Parameters:

out - OutputStream
location - timecode where play stopped
name - stream name

Returns:

bytes sent to client

sendPlaySeek

```
public int sendPlaySeek(java.io.OutputStream out,  
    long location,  
    long seekLocation,  
    String name,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Seek.Notify) event.

Parameters:

out - OutputStream
location - request location of seek
seekLocation - result location of seek
name - stream name
seekTypes - list of commands to respond to (seek, unpause, play)

Returns:

bytes sent to client

sendPlaySeek

```
public int sendPlaySeek(long location,  
    long seekLocation,  
    String name)
```

Send onStatus(NetStream.Seek.Notify) event.

(continued from last page)

Parameters:

location - request location of seek
seekLocation - result location of seek
name - stream name

Returns:

bytes sent to client

sendPlaySeek

```
public int sendPlaySeek(java.io.OutputStream out,  
    long location,  
    long seekLocation,  
    String name)
```

Send onStatus(NetStream.Seek.Notify) event. Send directly to OutputStream

Parameters:

out - OutputStream
location - request location of seek
seekLocation - result location of seek
name - stream name

Returns:

bytes sent to client

sendPlayStart

```
public int sendPlayStart(String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Start) event

Parameters:

name - stream name

Returns:

bytes sent to client

sendPlaySwitch

```
public int sendPlaySwitch(String name,  
    long timecode)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch).

Parameters:

name - stream name
timecode - timecode of event

Returns:

bytes sent to client

sendPlaySwitch

```
public int sendPlaySwitch(java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    long timecode)
```


(continued from last page)

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

Parameters:

out - OutputStream
name - stream name
isSwitch - is this a switch or a start
timecode - timecode of event

Returns:

bytes sent to client

sendPlayStart

```
public int sendPlayStart(java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    boolean isLive,  
    long timecode,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

Parameters:

out - OutputStream
name - stream name
isSwitch - is this a switch or a start
isLive - is the stream live
timecode - timecode of event
seekTypes - commands to respond to (seek, unpause, play)

sendPlayStart

```
public int sendPlayStart(java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    long timecode,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

Parameters:

out - OutputStream
name - stream name
isSwitch - is this a switch or a start
timecode - timecode of event
seekTypes - commands to respond to (seek, unpause, play)

Returns:

bytes sent to client

sendPlayStart

```
public int sendPlayStart(java.io.OutputStream out,  
    String name,  
    boolean isSwitch,  
    long timecode)
```

(continued from last page)

Send onStatus(NetStream.Play.Start) event (it is not a typo, this also send play start but with different control codes for media switch). Send directly to OutputStream

Parameters:

out - OutputStream
name - stream name
isSwitch - is this a switch or a start
timecode - timecode of event

Returns:

bytes sent to client

sendPlayStatus

```
public int sendPlayStatus(long timecode,  
    int statusType,  
    double duration,  
    double bytesSent)
```

Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event

Parameters:

timecode - timecode of event
statusType - status type IMediaStreamPlay.PLAYSTATUSTYPE_*
duration - (not used)
bytesSent - (not used)

Returns:

bytes sent to client

sendPlayStatus

```
public int sendPlayStatus(java.io.OutputStream out,  
    long timecode,  
    int statusType,  
    double duration,  
    double bytesSent)
```

Send onPlayStatus(NetStream.Play.Switch, NetStream.Play.Complete, NetStream.Play.Stop) event. Send directly to OutputStream.

Parameters:

out - OutputStream
timecode - timecode of event
statusType - status type IMediaStreamPlay.PLAYSTATUSTYPE_*
duration - (not used)
bytesSent - (not used)

Returns:

bytes sent to client

sendPauseNotify

```
public int sendPauseNotify(long timecode,  
    String name)
```

Send onStatus(NetStream.Pause.Notify) event

Parameters:

timecode - timecode of event

(continued from last page)

name - stream name

Returns:

bytes sent to client

sendPauseNotify

```
public int sendPauseNotify(java.io.OutputStream out,  
    long timecode,  
    String name)
```

Send onStatus(NetStream.Pause.Notify) event. Send directly to OutputStream.

Parameters:

out - OutputStream
timecode - timecode of event
name - stream name

Returns:

bytes sent to client

sendUnpauseNotify

```
public int sendUnpauseNotify(java.io.OutputStream out,  
    long location,  
    String name,  
    java.util.List seekTypes)
```

Send onStatus(NetStream.Unpause.Notify) event

Parameters:

out - OutputStream
location - timecode of event
name - stream name
seekTypes - list of operations to respond to (seek, play, unpause)

Returns:

bytes sent to client

sendUnpauseNotify

```
public int sendUnpauseNotify(long location,  
    String name)
```

Send onStatus(NetStream.Unpause.Notify) event

Parameters:

location - timecode of event
name - stream name

Returns:

bytes sent to client

sendUnpauseNotify

```
public int sendUnpauseNotify(java.io.OutputStream out,  
    long location,  
    String name)
```

Send onStatus(NetStream.Unpause.Notify) event. Send directly to OutputStream.

(continued from last page)

Parameters:

out - OutputStream
location - timecode of event
name - stream name

Returns:

bytes sent to client

isAppend

```
public boolean isAppend( )
```

Is append to media file (only valid if isRecord)

Returns:

is appending or rewriting media file

setAppend

```
public void setAppend(boolean isAppend)
```

Set is append to media file (only valid if isRecord)

Parameters:

isAppend - is appending or rewriting media file

setPlayer

```
public void setPlayer(IMediaStreamPlay player)
```

Set underlying player (IMediaStreamPlay) object

Parameters:

player - underlying player (IMediaStreamPlay) object

getPlayer

```
public IMediaStreamPlay getPlayer( )
```

Get underlying player (IMediaStreamPlay) object

Returns:

underlying player (IMediaStreamPlay) object

getAudioMissing

```
public int getAudioMissing( )
```

Get number of audio bytes missing from current audio packet

Returns:

number of bytes missing

getVideoMissing

```
public int getVideoMissing( )
```

(continued from last page)

Get number of video bytes missing from current audio packet

Returns:

number of bytes missing

getDataMissing

```
public int getDataMissing()
```

Get number of data bytes missing from current audio packet

Returns:

number of bytes missing

addVideoData

```
public void addVideoData(byte[] data,  
    int offset,  
    int size)
```

Add data to current video packet

Parameters:

data - byte array

offset - offset in byte array

size - size of data to add

addAudioData

```
public void addAudioData(byte[] data,  
    int offset,  
    int size)
```

Add data to current audio packet

Parameters:

data - byte array

offset - offset in byte array

size - size of data to add

addDataData

```
public void addDataData(byte[] data,  
    int offset,  
    int size)
```

Add data to current data packet

Parameters:

data - byte array

offset - offset in byte array

size - size of data to add

getProperties

```
public WMSProperties getProperties()
```

Get mediaStream properties

Returns:

(continued from last page)

properties

getPlayPackets

```
public java.util.List getPlayPackets()
```

Get all available live packets

Returns:

play packets

getMaxTimecode

```
public long getMaxTimecode()
```

Get the timecode of the latest received packet

Returns:

timecode of the latest received packet

getLastKeyFrame

```
public AMFPacket getLastKeyFrame()
```

Get most recent video key frame

Returns:

play packets

getLastPacket

```
public AMFPacket getLastPacket()
```

Get most recent live packet

Returns:

most recent live packet or null or no live packets

getStreamType

```
public String getStreamType()
```

Get mediaStream streamType

Returns:

streamType

setStreamType

```
public void setStreamType(String streamType)
```

Set mediaStream streamType. This method will not change the type of the current stream.

Parameters:

streamType

(continued from last page)

sendDirectAMF3

```
public void sendDirectAMF3(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler and send event to underlying stream (will record event). Force AMF3 encoding.

Parameters:

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

sendDirect

```
public void sendDirect(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler and send event to underlying stream (will record event)

Parameters:

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

sendDirectAMF3

```
public void sendDirectAMF3(String handlerName)
```

Call client side NetStream method/handler and send event to underlying stream (will record event). Force AMF3 encoding.

Parameters:

handlerName - handler name

sendDirect

```
public void sendDirect(String handlerName)
```

Call client side NetStream method/handler and send event to underlying stream (will record event)

Parameters:

handlerName - handler name

sendAMF3

```
public void sendAMF3(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler. Force AMF3 encoding.

Parameters:

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

send

```
public void send(String handlerName,  
    Object[] params)
```

Call client side NetStream method/handler

Parameters:

(continued from last page)

handlerName - handler name

params - variable list of parameters. All parameters will be wrapped in AMFDataObj.

sendAMF3

```
public void sendAMF3(String handlerName)
```

Call client side NetStream method/handler with no parameters. Force AMF3 encoding.

Parameters:

handlerName - handler name

send

```
public void send(String handlerName)
```

Call client side NetStream method/handler with no parameters

Parameters:

handlerName - handler name

close

```
public void close()
```

Close mediaStream

isOpen

```
public boolean isOpen()
```

Is mediaStream open

Returns:

is mediaStream open

setOpen

```
public void setOpen(boolean isOpen)
```

Set mediaStream open

Parameters:

isOpen - mediaStream open

getFastPlaySettings

```
public FastPlaySettings getFastPlaySettings()
```

Get current fastPlay settings

Returns:

fastPlay settings

setFastPlaySettings

```
public void setFastPlaySettings(FastPlaySettings fastPlaySettings)
```

(continued from last page)

Set fastPlay settings

Parameters:

fastPlaySettings - fastPlay settings

clearFastPlaySettings

```
public void clearFastPlaySettings()
```

Clear fastPlay settings

isReceiveAudio

```
public boolean isReceiveAudio()
```

Is client currently receiving audio. Controlled by client side call receiveAudio.

Returns:

receive audio

setReceiveAudio

```
public void setReceiveAudio(boolean receiveAudio)
```

Set receive audio

Parameters:

receiveAudio - receive audio

isReceiveVideo

```
public boolean isReceiveVideo()
```

Is client currently receiving video. Controlled by client side call receiveVideo

Returns:

receive video

setReceiveVideo

```
public void setReceiveVideo(boolean receiveVideo)
```

Set receive video

Parameters:

receiveVideo - receive video

getReceiveVideoFPS

```
public int getReceiveVideoFPS()
```

Set frame per seconds for video (not currently implemented)

Returns:

video frames per second

(continued from last page)

setReceiveVideoFPS

```
public void setReceiveVideoFPS(int receiveVideoFPS)
```

Set frame per second for video (not currently implemented)

Parameters:

receiveVideoFPS - video frames per second

getMediaIOPerformance

```
public IOPerformanceCounter getMediaIOPerformance()
```

Get IO performance counter

Returns:

IO performance counter

incrementMediaOutBytes

```
public long incrementMediaOutBytes(long bytes,  
    long count)
```

Increment the number of mediaStream bytes sent and number of packets sent

Parameters:

bytes - number of bytes sent

count - number of packets sent

Returns:

total number of bytes sent (after increment)

incrementMediaLossBytes

```
public long incrementMediaLossBytes(long bytes,  
    long count)
```

Increment the number of mediaStream loss bytes sent and number of packets sent

Parameters:

bytes - number of bytes sent

count - number of packets sent

Returns:

total number of bytes sent (after increment)

incrementMediaInBytes

```
public long incrementMediaInBytes(long increment)
```

Increment the number of mediaStream bytes received

Parameters:

increment - number of byte received

Returns:

total number of bytes received (after increment)

(continued from last page)

publish

```
public void publish()
```

Publish mediaStream

trim

```
public void trim()
```

Trim mediaStream. This method will remove live packets that are older than the live buffer size.

handleCallback

```
public void handleCallback(com.wowza.wms.request.RequestFunction function)
```

Routes request function to callback handler onStatus, onPlayStatus or [method/handler]

Parameters:

function - request function

unregisterCallback

```
public void unregisterCallback(String handlerName)
```

Unregister a callback handler

Parameters:

handlerName - handler name

registerCallback

```
public void registerCallback(String handlerName,  
    IMediaStreamCallback callback)
```

Register a callback handler

Parameters:

handlerName - handler name

callback - callback object

unregisterOnStatus

```
public void unregisterOnStatus(IMediaStreamCallback callback)
```

Unregister onStatus handler

Parameters:

callback

registerOnStatus

```
public void registerOnStatus(IMediaStreamCallback callback)
```

Register onStatus handler

Parameters:

callback - callback object

unregisterOnPlayStatus

```
public void unregisterOnPlayStatus(IMediaStreamCallback callback)
```

Unregister onPlayStatus handler

Parameters:

callback - callback object

registerOnPlayStatus

```
public void registerOnPlayStatus(IMediaStreamCallback callback)
```

Register onPlayStatus handler

Parameters:

callback - callback object

addClientListener

```
public void addClientListener(IMediaStreamActionNotify actionListener)
```

Add client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

Parameters:

actionListener - listener

addClientListener

```
public void addClientListener(IMediaStreamActionNotify2 actionListener)
```

Add client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

Parameters:

actionListener - listener

addClientListener

```
public void addClientListener(IMediaStreamActionNotify3 actionListener)
```

Add client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

Parameters:

actionListener - listener

removeClientListener

```
public void removeClientListener(IMediaStreamActionNotify actionListener)
```

Remove client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

Parameters:

actionListener - listener

removeClientListener

```
public void removeClientListener(IMediaStreamActionNotify2 actionListener)
```

(continued from last page)

Remove client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

Parameters:

actionListener - listener

removeClientListener

```
public void removeClientListener(IMediaStreamActionNotify3 actionListener)
```

Remove client listener. Listens for (onPlay, onPublish, onPause, onSeek, onStop)

Parameters:

actionListener - listener

notifyActionPlay

```
public void notifyActionPlay(String streamName,  
    double playStart,  
    double playLen,  
    int playReset)
```

Notify client listeners of play action

Parameters:

streamName - stream name

playStart - play start

playLen - play length

playReset - play reset

notifyActionPauseRaw

```
public void notifyActionPauseRaw(boolean isPause,  
    long location)
```

Notify client listeners of pauseRaw action

Parameters:

isPause - is pause or unpause

location - timecode (milliseconds) of action

notifyActionPause

```
public void notifyActionPause(boolean isPause,  
    long location)
```

Notify client listeners of pause action

Parameters:

isPause - is pause or unpause

location - timecode (milliseconds) of action

notifyActionSeek

```
public void notifyActionSeek(double location)
```

Notify client listeners of seek action

Parameters:

location - timecode (milliseconds) of seek request

notifyActionPublish

```
public void notifyActionPublish(String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Notify client listeners of publish action

Parameters:

streamName - stream name
isRecord - is record or live
isAppend - is append if isRecord is true

notifyActionUnPublish

```
public void notifyActionUnPublish(String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Notify client listeners of unpublish action

Parameters:

streamName - stream name
isRecord - is record or live
isAppend - is append if isRecord is true

notifyActionOnMetaData

```
public void notifyActionOnMetaData(AMFPacket metaDataPacket)
```

Notify client listeners of onMetaData change

Parameters:

metaDataPacket - metaDataPacket

notifyActionOnCodecInfoVideo

```
public void notifyActionOnCodecInfoVideo(com.wowza.wms.media.model.MediaCodecInfoVideo  
    codecInfoVideo)
```

Notify client listeners of video codec information change

Parameters:

codecInfoVideo - video codec information

notifyActionOnCodecInfoAudio

```
public void notifyActionOnCodecInfoAudio(com.wowza.wms.media.model.MediaCodecInfoAudio  
    codecInfoAudio)
```

Notify client listeners of audio codec information change

Parameters:

codecInfoAudio - audio codec information

notifyActionStop

```
public void notifyActionStop()
```

(continued from last page)

Notify client listeners of stop action

isClustered

```
public boolean isClustered()
```

not used

Returns:

isClustered

setClustered

```
public void setClustered(boolean isClustered)
```

not used

Parameters:

isClustered

getCacheName

```
public String getCacheName()
```

not used

Returns:

cache name

startPublishing

```
public void startPublishing()
```

Start publishing live stream

stopPublishing

```
public void stopPublishing()
```

Stop publishing live stream

getStreamFileForWrite

```
public java.io.File getStreamFileForWrite()
```

Get the File object to write to a stream (get stream name, ext and query from stream object)

Returns:

resultant File object

getStreamFileForWrite

```
public java.io.File getStreamFileForWrite(String name,  
                                           String ext,  
                                           String query)
```

Get the File object to write to a stream (specify name, ext and query)

(continued from last page)

Parameters:

name - stream name
ext - stream prefix (Ex. mp4:)
query - query part of stream name (Ex. mystream?param1=value1)

Returns:

resultant File object

getStreamFileForRead

```
public java.io.File getStreamFileForRead()
```

Get the File object to read from a stream (get stream name, ext and query from stream object)

Returns:

resultant File object

getStreamFileForRead

```
public java.io.File getStreamFileForRead(String name,  
String ext,  
String query)
```

Get the File object to read from a stream (specify name, ext and query)

Parameters:

name - stream name
ext - stream prefix (Ex. mp4:)
query - query part of stream name (Ex. mystream?param1=value1)

Returns:

resultant File object

sendControlBytes

```
public int sendControlBytes(int controlType,  
java.io.OutputStream out)
```

Send playback control bytes. Valid values are (0, 1, 4)

Parameters:

controlType - control types (0, 1, 4)
out - OutputStream

Returns:

bytes sent to client

getBurstStartStop

```
public byte[] getBurstStartStop(boolean isStart)
```

Get the dynamic streaming burst start/stop AMF packet

Parameters:

isStart - is start

Returns:

byte array with AMF packet

getRespAMFAudioObj

```
public AMFObj getRespAMFAudioObj()
```

Get audio response channel object

Returns:

audio response channel object

getRespAMFVideoObj

```
public AMFObj getRespAMFVideoObj()
```

Get video response channel object

Returns:

video response channel object

getRespAMFDataObj

```
public AMFObj getRespAMFDataObj()
```

Get data response channel object

Returns:

data response channel object

getQueryStr

```
public String getQueryStr()
```

Get play/publish name query string. Example: if play name is flv:test?param1=data1¶m2=data2, query string is "param1=data1¶m2=data2".

Returns:

query string

setQueryStr

```
public void setQueryStr(String queryStr)
```

Set play/publish name query string. Example: if play name is flv:test?param1=data1¶m2=data2, query string is "param1=data1¶m2=data2".

Parameters:

queryStr

updateLoggingDuration

```
public void updateLoggingDuration()
```

Update logging.MDC with mediaStream logging information

updateLoggingValues

```
public void updateLoggingValues()
```

Update logging.MDC with mediaStream logging information

clearLoggingValues

```
public void clearLoggingValues()
```

length

```
public double length()
```

Get length/duration (seconds) of media file pointed to by mediaStream

Returns:

length (seconds)

size

```
public long size()
```

Get size (bytes) of media file pointed to by mediaStream

Returns:

size (bytes)

getExt

```
public String getExt()
```

Get media file extension

Returns:

media file extension

setExt

```
public void setExt(String ext)
```

Set media file extension

Parameters:

ext

clear

```
public void clear()
```

Delete media file pointed to by this mediaStream (be careful)

isSendPlayStopLogEvent

```
public boolean isSendPlayStopLogEvent()
```

Get need to send a log event for stop

Returns:

need to send a log event for stop

setSendPlayStopLogEvent

```
public void setSendPlayStopLogEvent(boolean sendPlayStopLogEvent)
```

Set need to send a log event for stop

Parameters:

sendPlayStopLogEvent - need to send a log event for stop

isSendRecordStopLogEvent

```
public boolean isSendRecordStopLogEvent()
```

Get need to send a log event for recording

Returns:

need to send a log event for stop

setSendRecordStopLogEvent

```
public void setSendRecordStopLogEvent(boolean sendPlayStopLogEvent)
```

Set need to send a log event for recording

Parameters:

sendPlayStopLogEvent - need to send a log event for stop

isSendPublishStopLogEvent

```
public boolean isSendPublishStopLogEvent()
```

Get need to send a log event for publishing

Returns:

need to send a log event for stop

setSendPublishStopLogEvent

```
public void setSendPublishStopLogEvent(boolean sendPlayStopLogEvent)
```

Set need to send a log event for publishing

Parameters:

sendPlayStopLogEvent - need to send a log event for stop

getAccess

```
public boolean[] getAccess(IClient client,  
    String name)
```

Get the read/write access to this stream for this client

Parameters:

client - client
name - stream name

Returns:

array of booleans read[0], write[1]

getMetaDataProvider

```
public IMediaStreamMetaDataProvider getMetaDataProvider()
```

Get the metaData provider

Returns:

metaData provider

setMetaDataProvider

```
public void setMetaDataProvider(IMediaStreamMetaDataProvider metaDataProvider)
```

Set the metaData provider

Parameters:

metaDataProvider - metaData provider

getHeaderSize

```
public int getHeaderSize()
```

Get the last packet header size (debugging)

Returns:

last packet header size

setHeaderSize

```
public void setHeaderSize(int headerSize)
```

Set the last packet header size (debugging)

Parameters:

headerSize - last packet header size

getAudioCodecConfigPacket

```
public AMFPacket getAudioCodecConfigPacket(long timecode)
```

Get audio codec configuration packet (needed for H.264/AAC playback)

Parameters:

timecode - timecode of the packet to which you want to get the codec config information

Returns:

audio codec configuration packet (needed for H.264/AAC playback)

addAudioCodecConfigPacket

```
public void addAudioCodecConfigPacket(long timecode,  
    AMFPacket packet)
```

Set audio codec configuration packet (needed for H.264/AAC playback)

Parameters:

timecode - timecode in milliseconds of first packet that uses this timecode
packet - audio codec configuration packet (needed for H.264/AAC playback)

getVideoCodecConfigPacket

```
public AMFPacket getVideoCodecConfigPacket(long timecode)
```

Get video codec configuration packet (needed for H.264/AAC playback)

Parameters:

timecode - timecode of the packet to which you want to get the codec config information

Returns:

video codec configuration packet (needed for H.264/AAC playback)

addVideoCodecConfigPacket

```
public void addVideoCodecConfigPacket(long timecode,  
    AMFPacket packet)
```

Set video codec configuration packet (needed for H.264/AAC playback)

Parameters:

timecode - timecode in milliseconds of first packet that uses this timecode

packet - video codec configuration packet (needed for H.264/AAC playback)

getRTPStream

```
public RTPStream getRTPStream()
```

Get the RTP based stream this stream is associated with

Returns:

RTP based stream this stream is associated with

setRTPStream

```
public void setRTPStream(RTPStream rtpStream)
```

Set the RTP based stream this stream is associated with

Parameters:

rtpStream - RTP based stream this stream is associated with

flush

```
public void flush()
```

Force publishing packets to be flushed from the input buffers to the output buffers

startAudioPacket

```
public void startAudioPacket()
```

Called when an audio packet is first being populated with data

startVideoPacket

```
public void startVideoPacket()
```

(continued from last page)

Called when a video packet is first being populated with data

startDataPacket

```
public void startDataPacket()
```

Called when a data packet is first being populated with data

getLiveStreamPacketizerList

```
public String getLiveStreamPacketizerList()
```

Get the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)

Returns:

comma separated list of LiveStreamPacketizers names

setLiveStreamPacketizerList

```
public void setLiveStreamPacketizerList(String liveStreamPacketizerList)
```

Set the comma separated list of LiveStreamPacketizers names being used by this stream (see conf/LiveStreamPacketizers.xml)

Parameters:

liveStreamPacketizerList - comma separated list of LiveStreamPacketizers names

getLiveStreamTranscoderList

```
public String getLiveStreamTranscoderList()
```

Get the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)

Returns:

comma separated list of LiveStreamTranscoders names

setLiveStreamTranscoderList

```
public void setLiveStreamTranscoderList(String liveStreamTranscoderList)
```

Set the comma separated list of LiveStreamTranscoders names being used by this stream (see conf/LiveStreamTranscoders.xml)

Parameters:

liveStreamTranscoderList - comma separated list of LiveStreamTranscoders names

getLiveStreamPacketizer

```
public ILiveStreamPacketizer getLiveStreamPacketizer(String name)
```

Get the LiveStreamPacketizer interface to a stream by name

Parameters:

name - LiveStreamPacketizer name

Returns:

LiveStreamPacketizer interface

(continued from last page)

getDvrRecorderList

```
public String getDvrRecorderList()
```

Get the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)

Returns:

comma separated list of DVR Recorder names

setDvrRecorderList

```
public void setDvrRecorderList(String recorderList)
```

Set the comma separated list of DVR Recorder names being used by this stream (see conf/Dvr.xml)

Parameters:

recorderList - comma separated list of DVR Recorder names

getDvrRecorder

```
public ILiveStreamDvrRecorder getDvrRecorder(String name)
```

Get the DVR Recorder interface to a stream by name

Parameters:

name - DVR Recorder name

Returns:

DVR Recorder interface

getUniqueStreamIdStr

```
public String getUniqueStreamIdStr()
```

Get a string that uniquely identifies this stream

Returns:

unique stream identifier

getHTTPStreamerSession

```
public IHTTPStreamerSession getHTTPStreamerSession()
```

Get the HTTPStreamer session associated with this stream

Returns:

HTTPStreamer session associated with this stream

setHTTPStreamerSession

```
public void setHTTPStreamerSession(IHTTPStreamerSession httpStreamerSession)
```

Set the HTTPStreamer session associated with this stream

Parameters:

httpStreamerSession - HTTPStreamer session associated with this stream

(continued from last page)

getElapsedTime

```
public ElapsedTimer getElapsedTime()
```

Get the interface to the elapse timer

Returns:

interface to the elapse timer

getLiveStreamPacketizer

```
public String getLiveStreamPacketizer()
```

Get the live stream packetizer that this stream is using

Returns:

live stream packetizer

setLiveStreamPacketizer

```
public void setLiveStreamPacketizer(String liveStreamPacketizer)
```

Set the live stream packetizer that this stream is using

Parameters:

liveStreamPacketizer - live stream packetizer

getLiveStreamRepeater

```
public String getLiveStreamRepeater()
```

Get the live stream repeater name for the stream

Returns:

live stream repeater name

setLiveStreamRepeater

```
public void setLiveStreamRepeater(String liveStreamRepeater)
```

Set the live stream repeater name for the stream

Parameters:

liveStreamRepeater - live stream repeater name

initLiveStreamRepeating

```
public void initLiveStreamRepeating(String liveStreamPacketizer,  
    String liveStreamRepeater)
```

Initialize this stream for live stream repeating

Parameters:

liveStreamPacketizer - live stream packetizer
liveStreamRepeater - live stream repeater name

(continued from last page)

getPublishVideoCodecId

```
public int getPublishVideoCodecId()
```

Get the codec id of the most recently published video packet

Returns:

codec id of the most recently published video packet

setPublishVideoCodecId

```
public void setPublishVideoCodecId(int publishVideoCodecId)
```

Set the codec id of the most recently published video packet

Parameters:

publishVideoCodecId - codec id of the most recently published video packet

getPublishAudioCodecId

```
public int getPublishAudioCodecId()
```

Get the codec id of the most recently published audio packet

Returns:

codec id of the most recently published audio packet

setPublishAudioCodecId

```
public void setPublishAudioCodecId(int publishAudioCodecId)
```

Set the codec id of the most recently published audio packet

Parameters:

publishAudioCodecId - codec id of the most recently published audio packet

isPublishStreamReady

```
public boolean isPublishStreamReady(boolean checkAudio,  
    boolean checkVideo)
```

Returns true if the publishing stream contains enough video/audio data to start playback

Parameters:

checkAudio - check audio stream

checkVideo - check video stream

Returns:

true if the publishing stream contains enough video/audio data to start playback

getContextStr

```
public String getContextStr()
```

Returns the stream context string in the form [application]/[appInstance]/[streamName].

Returns:

stream context string

isMediaCasterPlay

```
public boolean isMediaCasterPlay()
```

Is MediaCaster play enabled (if true, will trigger MediaCaster startup)

Returns:

true if MediaCaster play enabled

setMediaCasterPlay

```
public void setMediaCasterPlay(boolean isMediaCasterPlay)
```

Is MediaCaster play enabled (if true, will trigger MediaCaster startup)

Parameters:

isMediaCasterPlay - true if MediaCaster play enabled

isMergeOnMetadata

```
public boolean isMergeOnMetadata()
```

If true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

Returns:

true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

setMergeOnMetadata

```
public void setMergeOnMetadata(boolean mergeOnMetadata)
```

If true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

Parameters:

mergeOnMetadata - true, merge incoming onMetadata events with the current onMetadata event data. If false, replace.

getDvrRecorder

```
public String getDvrRecorder()
```

Get the DVR Recorder for this stream

Returns:

DVR Recorder

getDvrRepeater

```
public String getDvrRepeater()
```

Get the DVR repeater name for this stream

Returns:

repeater name

setDvrRecorder

```
public void setDvrRecorder(String recorderName)
```

(continued from last page)

Set the DVR Recorder that this stream is using

Parameters:

recorderName - DVR Recorder

removeDvrRecorder

```
public ILiveStreamDvrRecorder removeDvrRecorder(String name)
```

Remove a live stream dvr by name

Parameters:

name - dvr name

Returns:

live stream dvr

putDvrRecorder

```
public void putDvrRecorder(String name,  
    ILiveStreamDvrRecorder dvr)
```

Add a live stream dvr to this stream

Parameters:

name - dvr name

dvr - live stream dvr

getLiveStreamTranscoders

```
public java.util.Map getLiveStreamTranscoders()
```

Get the list of transcoders for this stream.

Returns:

list of transcoders for this stream

getLiveStreamTranscoder

```
public ILiveStreamTranscoder getLiveStreamTranscoder(String name)
```

Get a live stream transcoder for this stream by name

Parameters:

name - transcoder name

Returns:

live stream transcoder

removeLiveStreamTranscoder

```
public ILiveStreamTranscoder removeLiveStreamTranscoder(String name)
```

Remove a live stream transcoder by name

Parameters:

name - transcoder name

(continued from last page)

Returns:

live stream transcoder

putLiveStreamTranscoder

```
public void putLiveStreamTranscoder(String name,  
    ILiveStreamTranscoder liveStreamTranscoder)
```

Add a live stream transcoder to this stream

Parameters:

name - transcoder name

liveStreamTranscoder - live stream transcoder

isTranscodeResult

```
public boolean isTranscodeResult()
```

Is this stream the result of a transcode operation.

Returns:

true if stream the result of a transcode operation

setTranscodeResult

```
public void setTranscodeResult(boolean isTranscodeResult)
```

Is this stream the result of a transcode operation.

Parameters:

isTranscodeResult - true if stream the result of a transcode operation

com.wowza.wms.stream Interface IMediaStreamActionNotify

All Subinterfaces:

[IMediaStreamActionNotify2](#), [IMediaStreamActionNotify3](#)

public interface **IMediaStreamActionNotify**
extends

IMediaStreamActionNotify: listener interface used by IMediaStream addClientListener

Method Summary

void	onPause (IMediaStream stream, boolean isPause, double location) Triggered on mediaStream pause
void	onPlay (IMediaStream stream, String streamName, double playStart, double playLen, int playReset) Triggered on mediaStream play
void	onPublish (IMediaStream stream, String streamName, boolean isRecord, boolean isAppend) Triggered on mediaStream publish
void	onSeek (IMediaStream stream, double location) Triggered on mediaStream seek
void	onStop (IMediaStream stream) Triggered on mediaStream stop
void	onUnPublish (IMediaStream stream, String streamName, boolean isRecord, boolean isAppend) Triggered on mediaStream unpublish

Methods

onPlay

```
public void onPlay(IMediaStream stream,
    String streamName,
    double playStart,
    double playLen,
    int playReset)
```

Triggered on mediaStream play

Parameters:

stream - mediaStream
streamName - streamName
playStart - playStart offset
playLen - playLen
playReset - reset playlist

onPublish

```
public void onPublish(IMediaStream stream,  
    String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Triggered on mediaStream publish

Parameters:

stream - mediaStream
streamName - streamName
isRecord - recording stream
isAppend - appending to file

onUnPublish

```
public void onUnPublish(IMediaStream stream,  
    String streamName,  
    boolean isRecord,  
    boolean isAppend)
```

Triggered on mediaStream unpublish

Parameters:

stream - mediaStream
streamName - streamName
isRecord - recording stream
isAppend - appending to file

onPause

```
public void onPause(IMediaStream stream,  
    boolean isPause,  
    double location)
```

Triggered on mediaStream pause

Parameters:

stream - mediaStream
isPause - pause or unpause
location - location (milliseconds)

onSeek

```
public void onSeek(IMediaStream stream,  
    double location)
```

Triggered on mediaStream seek

Parameters:

stream - mediaStream
location - location (milliseconds)

onStop

```
public void onStop(IMediaStream stream)
```

Triggered on mediaStream stop

(continued from last page)

Parameters:

stream - mediaStream

com.wowza.wms.stream Interface IMediaStreamActionNotify2

All Superinterfaces:

[IMediaStreamActionNotify](#)

All Subinterfaces:

[IMediaStreamActionNotify3](#)

public interface **IMediaStreamActionNotify2**
extends [IMediaStreamActionNotify](#)

Method Summary

void	onMetaData (IMediaStream stream, AMFPacket metaDataPacket) Triggered when a published streams metadata is set or changes
void	onPauseRaw (IMediaStream stream, boolean isPause, double location) Triggered on mediaStream pauseRaw.

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify](#)

[onPause](#), [onPlay](#), [onPublish](#), [onSeek](#), [onStop](#), [onUnPublish](#)

Methods

onMetaData

```
public void onMetaData(IMediaStream stream,  
    AMFPacket metaDataPacket)
```

Triggered when a published streams metadata is set or changes

onPauseRaw

```
public void onPauseRaw(IMediaStream stream,  
    boolean isPause,  
    double location)
```

Triggered on mediaStream pauseRaw. The pauseRaw method is called when a pause occurs in the player.

Parameters:

stream - mediaStream
isPause - pause or unpause
location - location (milliseconds)

com.wowza.wms.stream Interface IMediaStreamActionNotify3

All Superinterfaces:

[IMediaStreamActionNotify2](#), [IMediaStreamActionNotify](#)

public interface **IMediaStreamActionNotify3**
extends [IMediaStreamActionNotify2](#)

Method Summary

void	onCodecInfoAudio (IMediaStream stream, com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio) Triggered when publishing stream receives codec information.
void	onCodecInfoVideo (IMediaStream stream, com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Triggered when publishing stream receives codec information.

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify2](#)

[onMetaData](#), [onPauseRaw](#)

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamActionNotify](#)

[onPause](#), [onPlay](#), [onPublish](#), [onSeek](#), [onStop](#), [onUnPublish](#)

Methods

onCodecInfoVideo

```
public void onCodecInfoVideo(IMediaStream stream,  
    com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
```

Triggered when publishing stream receives codec information.

Parameters:

stream - mediaStream
codecInfoVideo - video codec information

onCodecInfoAudio

```
public void onCodecInfoAudio(IMediaStream stream,  
    com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
```

Triggered when publishing stream receives codec information.

Parameters:

stream - mediaStream
codecInfoAudio - video codec information

com.wowza.wms.stream Interface IMediaStreamCallback

public interface **IMediaStreamCallback**
extends

IMediaStreamCallback: callback interface used by IMediaStream registerCallback, registerOnStatus, registerOnPlayStatus

Method Summary

void	onCallback (IMediaStream stream, com.wowza.wms.request.RequestFunction function, AMFDataList params) Triggered on callback event
------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

onCallback

```
public void onCallback(IMediaStream stream,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Triggered on callback event

Parameters:

stream - mediaStream
function - function that triggered callback
params - function parameters

com.wowza.wms.stream Interface IMediaStreamFileMapper

public interface **IMediaStreamFileMapper**
extends

Interface for mapping a IMediaStream to the underlying file system. Implement this interface and set your class using `IApplicationInstance.setStreamFileMapper(IMediaStreamFileMapper streamFileMapper)`. Your class will then be called each time a stream needs to be mapped to the underlying file system.

Method Summary

java.io.File	<code>streamToFileForRead(IMediaStream stream)</code> Get the File object to read from a stream (get stream name, ext and query from stream object)
java.io.File	<code>streamToFileForRead(IMediaStream stream, String name, String ext, String query)</code> Get the File object to read from a stream (specify name, ext and query)
java.io.File	<code>streamToFileForWrite(IMediaStream stream)</code> Get the File object to write to a stream (get stream name, ext and query from stream object)
java.io.File	<code>streamToFileForWrite(IMediaStream stream, String name, String ext, String query)</code> Get the File object to write to a stream (specify name, ext and query)

Methods

streamToFileForRead

```
public java.io.File streamToFileForRead(IMediaStream stream,  
    String name,  
    String ext,  
    String query)
```

Get the File object to read from a stream (specify name, ext and query)

Parameters:

stream - stream
name - stream name
ext - stream prefix (Ex. mp4:)
query - query part of stream name (Ex. mystream?param1=value1)

Returns:

resultant File object

streamToFileForRead

```
public java.io.File streamToFileForRead(IMediaStream stream)
```

Get the File object to read from a stream (get stream name, ext and query from stream object)

Parameters:

(continued from last page)

stream - stream

Returns:

resultant File object

streamToFileForWrite

```
public java.io.File streamToFileForWrite(IMediaStream stream,  
    String name,  
    String ext,  
    String query)
```

Get the File object to write to a stream (specify name, ext and query)

Parameters:

stream - stream

name - stream name

ext - stream prefix (Ex. mp4:)

query - query part of stream name (Ex. mystream?param1=value1)

Returns:

resultant File object

streamToFileForWrite

```
public java.io.File streamToFileForWrite(IMediaStream stream)
```

Get the File object to write to a stream (get stream name, ext and query from stream object)

Parameters:

stream - stream

Returns:

resultant File object

com.wowza.wms.stream Interface IMediaStreamMediaCaster

public interface **IMediaStreamMediaCaster**
extends

IMediaStreamMediaCaster: Internal use

Method Summary

IMediaCaster	getMediaCaster()
void	setMediaCasterItem(MediaCasterItem mediaCasterItem)

Methods

setMediaCasterItem

public void **setMediaCasterItem**([MediaCasterItem](#) mediaCasterItem)

getMediaCaster

public [IMediaCaster](#) **getMediaCaster**()

com.wowza.wms.stream Interface IMediaStreamMetaDataProvider

public interface **IMediaStreamMetaDataProvider**
extends

IMediaStreamMetaDataProvider: Live streaming metadata provider.

Method Summary

void	onStreamStart (java.util.List metaDataList, long timecode) Called to get the onMetadata data at a particular point in time in the stream
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

onStreamStart

```
public void onStreamStart(java.util.List metaDataList,  
    long timecode)
```

Called to get the onMetadata data at a particular point in time in the stream

Parameters:

metaDataList - list of onMetadata data (should always be one item in list)
timecode - timecode in milliseconds

com.wowza.wms.stream Interface IMediaStreamNameAliasProvider

All Subinterfaces:

[IMediaStreamNameAliasProvider2](#)

public interface **IMediaStreamNameAliasProvider**
extends

IMediaStreamNameAliasProvider: alias provider interface. See `IApplication.setStreamNameAliasProvider(IMediaStreamNameAliasProvider streamNameAliasProvider)`. See updated interface `IMediaStreamNameAliasProvider2` which provides more complete context information.

Method Summary

String	resolvePlayAlias (IApplicationInstance appInstance, String name) Called to resolve a play alias
String	resolveStreamAlias (IApplicationInstance appInstance, String name) Called to resolve a stream alias

Methods

resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name)
```

Called to resolve a play alias

Parameters:

appInstance - applicationInstance
name - stream name

Returns:

resultant name, null if want to block playback

resolveStreamAlias

```
public String resolveStreamAlias(IApplicationInstance appInstance,  
    String name)
```

Called to resolve a stream alias

Parameters:

appInstance - applicationInstance
name - stream name

Returns:

resultant name, null if want to block playback

com.wowza.wms.stream Interface IMediaStreamNameAliasProvider2

All Superinterfaces:

[IMediaStreamNameAliasProvider](#)

public interface **IMediaStreamNameAliasProvider2**

extends [IMediaStreamNameAliasProvider](#)

IMediaStreamNameAliasProvider: alias provider interface. See

`IApplication.setStreamNameAliasProvider(IMediaStreamNameAliasProvider streamNameAliasProvider)`.

Method Summary

String	resolvePlayAlias (IApplicationInstance appInstance, String name, IClient client) Resolve play alias for RTMP streaming
String	resolvePlayAlias (IApplicationInstance appInstance, String name, IHTTPStreamerSession httpSession) Resolve play alias for HTTP streaming.
String	resolvePlayAlias (IApplicationInstance appInstance, String name, ILiveStreamPacketizer liveStreamPacketizer) Resolve play alias for live stream packetizer
String	resolvePlayAlias (IApplicationInstance appInstance, String name, RTPSession rtpSession) Resolve play alias for RTSP/RTP streaming
String	resolveStreamAlias (IApplicationInstance appInstance, String name, IMediaCaster mediaCaster) Resolve stream alias for MediaCaster

Methods inherited from interface [com.wowza.wms.stream.IMediaStreamNameAliasProvider](#)

[resolvePlayAlias](#), [resolveStreamAlias](#)

Methods

resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    IClient client)
```

Resolve play alias for RTMP streaming

Parameters:

appInstance - application instance
name - stream name
client - client interface

Returns:

(continued from last page)

resultant name, null if want to block playback

resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    IHTTPStreamerSession httpSession)
```

Resolve play alias for HTTP streaming. This callback may be called when there is not a valid HTTP session. In this case a phantom HTTP session will be created and will be populated with information from the underlying HTTP request (such as IP address and query string) but the session Id will be null.

Parameters:

appInstance - application instance

name - name

httpSession - HTTP session

Returns:

resultant name, null if want to block playback

resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    RTPSession rtpSession)
```

Resolve play alias for RTSP/RTP streaming

Parameters:

appInstance - application instance

name - name

rtpSession - RTP session

Returns:

resultant name, null if want to block playback

resolvePlayAlias

```
public String resolvePlayAlias(IApplicationInstance appInstance,  
    String name,  
    ILiveStreamPacketizer liveStreamPacketizer)
```

Resolve play alias for live stream packetizer

Parameters:

appInstance - application instance

name - name

liveStreamPacketizer - live stream packetizer

Returns:

resultant name, null if want to block playback

resolveStreamAlias

```
public String resolveStreamAlias(IApplicationInstance appInstance,  
    String name,  
    IMediaCaster mediaCaster)
```

Resolve stream alias for MediaCaster

(continued from last page)

Parameters:

appInstance - application instance
name - name
mediaCaster - media caster

Returns:

resultant name, null if want to block playback

com.wowza.wms.stream Interface IMediaStreamNotify

public interface **IMediaStreamNotify**
extends

IMediaStreamNotify: listener interface used by IApplicationInstance addMediaStreamListener

Method Summary

void	onMediaStreamCreate (IMediaStream stream) Triggered when mediaStream created
void	onMediaStreamDestroy (IMediaStream stream) Triggered when mediaStream destroyed

Methods

onMediaStreamCreate

public void **onMediaStreamCreate**([IMediaStream](#) stream)

Triggered when mediaStream created

Parameters:

stream - mediaStream

onMediaStreamDestroy

public void **onMediaStreamDestroy**([IMediaStream](#) stream)

Triggered when mediaStream destroyed

Parameters:

stream - mediaStream

com.wowza.wms.stream Interface IMediaStreamPlay

public interface **IMediaStreamPlay**
extends

IMediaStreamPlay: public interface of mediaPlayer object.

Field Summary

public static final	<u>PAUSE_PAUSE</u> Pause type: pause Value: 1
public static final	<u>PAUSE_PLAY</u> Pause type: play Value: 0
public static final	<u>PAUSE_TOGGLE</u> Pause type: toggle Value: -1
public static final	<u>PLAYSIZES_AUDIO_BYTES</u> IMediaReader sizes array: audio byte count Value: 0
public static final	<u>PLAYSIZES_AUDIO_COUNT</u> IMediaReader sizes array: audio packet count Value: 1
public static final	<u>PLAYSIZES_DATA_BYTES</u> IMediaReader sizes array: data byte count Value: 4
public static final	<u>PLAYSIZES_DATA_COUNT</u> IMediaReader sizes array: data packet count Value: 5
public static final	<u>PLAYSIZES_LOSS_BYTES</u> IMediaReader sizes array: data byte count Value: 6
public static final	<u>PLAYSIZES_LOSS_COUNT</u> IMediaReader sizes array: data packet count Value: 7
public static final	<u>PLAYSIZES_SIZE</u> IMediaReader sizes array: size of sizes array long[PLAYSIZES_SIZE] Value: 8
public static final	<u>PLAYSIZES_VIDEO_BYTES</u> IMediaReader sizes array: video byte count Value: 2

public static final	PLAYSIZES_VIDEO_COUNT IMediaReader sizes array: video packet count Value: 3
public static final	PLAYSTATUSTYPE_COMPLETE onPlayStatus type: complete Value: 2
public static final	PLAYSTATUSTYPE_STOP onPlayStatus type: stop Value: 3
public static final	PLAYSTATUSTYPE_SWITCH onPlayStatus type: switch Value: 1

Method Summary

void	close() Close mediaStreamPlay
IMediaStream	getParent() Get the parent media stream object
void	init (IMediaStream parent, MediaStreamMap streams) Initialize mediaStreamPlayer
void	initLiveStreamRepeating (String liveStreamPacketizer, String liveStreamRepeater) Initialize this stream for live stream repeating
void	interruptPlay() Interrupt play to perform operation.
double	length() Get stream length/seconds (seconds)
void	pause (int pauseType, long timecode) pause mediaPlayStream
void	pauseRaw (int pauseType, long timecode) pauseRaw mediaPlayStream
boolean	play() Return true if there are packets to play
int	play (java.io.OutputStream out, AMFObj wmsObjAudio, AMFObj wmsObjVideo, AMFObj wmsObjData, long[] sizes) Write new packets or play packets
void	reset (boolean isReset) Reset mediaStreamPlayer
void	resetNoLookup() Reset but do not lookup current position in live stream
void	seek (int location) seek mediaPlayStream

void	<code>setBufferTime</code> (int bufferTime) Set buffer time
void	<code>setName</code> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Set mediaPlayStream name, extension, query string, play start, play len, play reset
void	<code>shutdown</code> () Shutdown mediaStreamPlayer
long	<code>size</code> () Get stream media file size
void	<code>startPlay</code> () Start playing stream
void	<code>stopName</code> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Stop stream name
void	<code>switchName</code> (String name, String oldName, String ext, String queryStr, double playStart, double playLen, int playTransition) Switch to stream name
void	<code>switchPlay</code> ()
void	<code>updateLoggingValues</code> () Update internal logging values

Fields

PAUSE_PAUSE

```
public static final int PAUSE_PAUSE
```

Pause type: pause
Constant value: **1**

PAUSE_TOGGLE

```
public static final int PAUSE_TOGGLE
```

Pause type: toggle
Constant value: **-1**

PAUSE_PLAY

```
public static final int PAUSE_PLAY
```

Pause type: play
Constant value: **0**

PLAYSTATUSTYPE_SWITCH

```
public static final int PLAYSTATUSTYPE_SWITCH
```

onPlayStatus type: switch

(continued from last page)

Constant value: **1**

PLAYSTATUSTYPE_COMPLETE

```
public static final int PLAYSTATUSTYPE_COMPLETE
```

onPlayStatus type: complete
Constant value: **2**

PLAYSTATUSTYPE_STOP

```
public static final int PLAYSTATUSTYPE_STOP
```

onPlayStatus type: stop
Constant value: **3**

PLAYSIZES_AUDIO_BYTES

```
public static final int PLAYSIZES_AUDIO_BYTES
```

IMediaReader sizes array: audio byte count
Constant value: **0**

PLAYSIZES_AUDIO_COUNT

```
public static final int PLAYSIZES_AUDIO_COUNT
```

IMediaReader sizes array: audio packet count
Constant value: **1**

PLAYSIZES_VIDEO_BYTES

```
public static final int PLAYSIZES_VIDEO_BYTES
```

IMediaReader sizes array: video byte count
Constant value: **2**

PLAYSIZES_VIDEO_COUNT

```
public static final int PLAYSIZES_VIDEO_COUNT
```

IMediaReader sizes array: video packet count
Constant value: **3**

PLAYSIZES_DATA_BYTES

```
public static final int PLAYSIZES_DATA_BYTES
```

IMediaReader sizes array: data byte count
Constant value: **4**

PLAYSIZES_DATA_COUNT

```
public static final int PLAYSIZES_DATA_COUNT
```

IMediaReader sizes array: data packet count
Constant value: **5**

(continued from last page)

PLAYSIZES_LOSS_BYTES

```
public static final int PLAYSIZES_LOSS_BYTES
```

IMediaReader sizes array: data byte count
Constant value: **6**

PLAYSIZES_LOSS_COUNT

```
public static final int PLAYSIZES_LOSS_COUNT
```

IMediaReader sizes array: data packet count
Constant value: **7**

PLAYSIZES_SIZE

```
public static final int PLAYSIZES_SIZE
```

IMediaReader sizes array: size of sizes array long[PLAYSIZES_SIZE]
Constant value: **8**

Methods

init

```
public void init(IMediaStream parent,  
                 MediaStreamMap streams)
```

Initialize mediaStreamPlayer

Parameters:

parent - parent mediaStream object
streams - parent mediaStreamMap

shutdown

```
public void shutdown()
```

Shutdown mediaStreamPlayer

reset

```
public void reset(boolean isReset)
```

Reset mediaStreamPlayer

Parameters:

isReset - is this a playlist reset or addition, true if reset

resetNoLookup

```
public void resetNoLookup()
```

Reset but do not lookup current position in live stream

(continued from last page)

play

```
public int play(java.io.OutputStream out,
    AMFObj wmsObjAudio,
    AMFObj wmsObjVideo,
    AMFObj wmsObjData,
    long[] sizes)
```

Write new packets or play packets

Parameters:

out - OutputStream
wmsObjAudio - audio response channel
wmsObjVideo - video response channel
wmsObjData - data response channel
sizes - sizes array. See IMediaStreamPlay.PLAYSIZES_*

Returns:

total byte output

play

```
public boolean play()
```

Return true if there are packets to play

Returns:

true if packets to play

seek

```
public void seek(int location)
```

seek mediaPlayStream

Parameters:

location - timecode (milliseconds)

pause

```
public void pause(int pauseType,
    long timecode)
```

pause mediaPlayStream

Parameters:

pauseType - pause type. See IMediaStreamPlay.PAUSE_*
timecode - timecode (milliseconds)

pauseRaw

```
public void pauseRaw(int pauseType,
    long timecode)
```

pauseRaw mediaPlayStream

Parameters:

pauseType - pause type. See IMediaStreamPlay.PAUSE_*
timecode - timecode (milliseconds)

setBufferTime

```
public void setBufferTime(int bufferTime)
```

Set buffer time

Parameters:

bufferTime

setName

```
public void setName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Set mediaPlayStream name, extension, query string, play start, play len, play reset

Parameters:

name - stream name
oldName - old stream name
ext - extension
queryStr - query string
playStart - play start
playLen - play len
playTransition - play reset

switchName

```
public void switchName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

Switch to stream name

Parameters:

name - stream name
oldName - old stream name
ext - stream extension
queryStr - query string
playStart - play start
playLen - play len
playTransition - play transition (see MediaBase.PLAYTRANSITION_*)

stopName

```
public void stopName(String name,  
    String oldName,  
    String ext,  
    String queryStr,  
    double playStart,  
    double playLen,  
    int playTransition)
```

(continued from last page)

Stop stream name

Parameters:

name - stream name
oldName - old stream name
ext - stream extension
queryStr - query string
playStart - play start
playLen - play len
playTransition - play transition (see MediaBase.PLAYTRANSITION_*)

close

```
public void close()
```

Close mediaStreamPlay

interruptPlay

```
public void interruptPlay()
```

Interrupt play to perform operation. Usually for seek or pause.

startPlay

```
public void startPlay()
```

Start playing stream

switchPlay

```
public void switchPlay()
```

updateLoggingValues

```
public void updateLoggingValues()
```

Update internal logging values

length

```
public double length()
```

Get stream length/seconds (seconds)

Returns:

length/duration (seconds)

size

```
public long size()
```

Get stream media file size

Returns:

media file size

getParent

```
public IMediaStream getParent( )
```

Get the parent media stream object

Returns:

parent media stream object

initLiveStreamRepeating

```
public void initLiveStreamRepeating(String liveStreamPacketizer,  
    String liveStreamRepeater)
```

Initialize this stream for live stream repeating

Parameters:

liveStreamPacketizer - live stream packetizer

liveStreamRepeater - live stream repeater name

com.wowza.wms.stream**Interface IMediaStreamTimecodeControl**

public interface **IMediaStreamTimecodeControl**
extends

IMediaStreamTimecodeControl: Internal use.

Method Summary

void	<u>resetTimecodes()</u>
------	-----------------------------------------

Methods

resetTimecodes

public void **resetTimecodes()**

com.wowza.wms.stream

Interface IMediaWriter

public interface **IMediaWriter**
extends

IMediaWriter: generic media writer interface. The flv recording system using this interface to persist .flv data captured from the Flash client. These classes are referenced in [\[install-dir\]/conf/MediaWriters.xml](#).

Example IMediaWriter implementation: MediaWriterFLVBasic

This is a basic IMediaWriter implementation that can handle record and append.

```
import java.io.*;
import java.nio.ByteBuffer;
import java.util.*;

import com.wowza.util.*;
import com.wowza.wms.stream.*;
import com.wowza.wms.amf.AMFData;
import com.wowza.wms.logging.*;

public class MediaWriterFLV implements IMediaWriter
{
    private IMediaStream parent = null;
    private MediaWriterItem mediaWriterItem = null;
    private long[] currentTCs = new long[3];
    private long duration = 0;
    private Map extraMetadata = new HashMap();
    private boolean versionFile = false;

    public void setMediaWriterItem(MediaWriterItem mediaWriterItem)
    {
        this.mediaWriterItem = mediaWriterItem;
    }

    public void setParent(IMediaStream parent)
    {
        this.parent = parent;
    }

    public void writePackets(List audioPackets, List videoPackets,
                             List dataPackets, List audioTCs, List videoTCs, List dataTCs, List
dataTypes,
                             boolean isFirst, boolean isLast)
    {
        File newFile = this.parent.getStreamFile();

        boolean localAppend = this.parent.isAppend();

        if (isFirst)
        {
            long startTC = 0;
            if (newFile.exists())
            {
                if (localAppend)
                    startTC = FLVUtils.getLastTC(newFile);
                else
                {
                    if (versionFile)
                        FileUtils.versionFile(newFile);
                    else
                    {
                        try
```

```

        {
            newFile.delete();
        }
        catch (Exception e)
        {
        }
    }
}
else
    localAppend = false;

this.currentTCs[FLVUtils.FLV_TCINDEXAUDIO] = startTC;
this.currentTCs[FLVUtils.FLV_TCINDEXVIDEO] = startTC;
this.currentTCs[FLVUtils.FLV_TCINDEXDATA] = startTC;
}
else
    localAppend = true;

try
{
    if (newFile.getParentFile() == null)

WMSLoggerFactory.getLogger(MediaWriterFLV.class).warn("MediaWriterFLV: File path does not
exist: "+newFile.getPath());
        else if (!newFile.getParentFile().exists())

WMSLoggerFactory.getLogger(MediaWriterFLV.class).warn("MediaWriterFLV: Folder does not exist:
"+newFile.getParentFile().getPath());
        else if (newFile.exists() && !newFile.canWrite())

WMSLoggerFactory.getLogger(MediaWriterFLV.class).warn("MediaWriterFLV: Cannot write to file
(permission error): "+newFile.getPath());

        FileOutputStream ds = new FileOutputStream(newFile, localAppend);

        if (isFirst)
        {
            if (!localAppend)
            {
                FLVUtils.writeHeader(ds, 0.0, extraMetadata);

                boolean writeZeroPacket = true;
                while(true)
                {
                    if (audioPackets.size() == 0)
                        break;

                    ByteBuffer data =
(ByteBuffer)audioPackets.get(0);

                    long tcA = ((Long)audioTCs.get(0)).longValue();

```



```

        if (tcA == 0 && data.limit() == 0)
            writeZeroPacket = false;

        break;
    }

    if (writeZeroPacket)
    {
        FLVUtils.writeChunk(ds, null, 0,

this.currentTCs[FLVUtils.FLV_TCINDEXAUDIO],

                                                                    (byte) 0x08); //
write zero length audio block
    }
}

    FLVUtils.writePackets(ds, audioPackets, videoPackets, dataPackets,
        audioTCs, videoTCs, dataTCs, dataTypes, currentTCs);

    ds.flush();
    ds.close();
}
catch (Exception e)
{
    WMSLoggerFactory.getLogger(MediaWriterFLV.class).error(
        "MediaWriterFLV: Error writing to file:
"+newFile.getPath()+" :"+e.toString());
    e.printStackTrace();
}

    if (isLast)
    {
        duration = Math.max(Math.max(currentTCs[FLVUtils.FLV_TCINDEXAUDIO],
            currentTCs[FLVUtils.FLV_TCINDEXVIDEO]),
            currentTCs[FLVUtils.FLV_TCINDEXDATA]);
        double durationSecs = ((double)duration) / 1000.0;

        FLVUtils.writeDuration(newFile, durationSecs);
    }
}

public Map getExtraMetadata()
{
    return extraMetadata;
}

public void setExtraMetadata(Map extraMetadata)
{
    this.extraMetadata = extraMetadata;
}

```

```
    }

    public boolean isVersionFile()
    {
        return versionFile;
    }

    public void setVersionFile(boolean versionFile)
    {
        this.versionFile = versionFile;
    }

    public void putMetaData(String name, AMFData value)
    {
        this.extraMetadata.put(name, value);
    }
}
```

To use this class, edit [install-dir]/conf/MediaWriter and replace the definition for the **flv** MediaWriter:

```
<MediaWriter>
  <Name>flv</Name>
  <Description>FLV Media Writer</Description>
  <FileExtension>flv</FileExtension>
  <ClassBase>com.wowza.wms.plugin.mediawriter.flv.MediaWriterFLVBasic</ClassBase>
</MediaWriter>
```

Example IMediaWriter implementation: MediaWriterFLVMetadata

This example illustrates how to write custom metadata into the recorded flv file on the fly.

```
public class MediaWriterFLVMetadata implements IMediaWriter
{
    private IMediaStream parent = null;
    private MediaWriterItem mediaWriterItem = null;
    private long[] currentTCs = new long[3];
    private long duration = 0;
    private File tmpFile = null;
    private Map extraMetadata = new HashMap();
    private boolean versionFile = false;

    public void setMediaWriterItem(MediaWriterItem mediaWriterItem)
    {
        this.mediaWriterItem = mediaWriterItem;
    }

    public void setParent(IMediaStream parent)
    {
        this.parent = parent;
    }

    public void writePackets(List audioPackets, List videoPackets,
        List dataPackets, List audioTCs, List videoTCs, List dataTCs,
        boolean isFirst, boolean isLast)
    {
        File newFile = this.parent.getStreamFile();
        try
        {
            if (tmpFile == null)
                tmpFile = File.createTempFile("wowza", "flv");
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
                "MediaWriterFLVMetadata: Error createTempFile: "+
                tmpFile+" :"+e.toString());
        }

        boolean localAppend = this.parent.isAppend();
        if (isFirst)
        {
            AMFDataArray keyFrames = null;

            long startTC = 0;
            if (newFile.exists())
            {
                if (localAppend)
                {
                    startTC = FLVUtils.getLastTC(newFile);
                    keyFrames = getKeyFrames(newFile);
                    copyPacketsToTmpFile(newFile, tmpFile);
                }
            }
        }
    }
}
```

```

        if (versionFile)
            FileUtils.versionFile(newFile);
        else
        {
            try
            {
                newFile.delete();
            }
            catch (Exception e)
            {
            }
        }
    }
    else
        localAppend = false;

    if (keyFrames == null)
        keyFrames = new AMFDataArray();
    extraMetadata.put("keyFrames", keyFrames);

    this.currentTCs[FLVUtils.FLV_TCINDEXAUDIO] = startTC;
    this.currentTCs[FLVUtils.FLV_TCINDEXVIDEO] = startTC;
    this.currentTCs[FLVUtils.FLV_TCINDEXDATA] = startTC;
}
else
    localAppend = true;

    AMFDataArray keyFrames = (AMFDataArray)extraMetadata.get("keyFrames");
    long timecode = this.currentTCs[FLVUtils.FLV_TCINDEXVIDEO];
    int size = videoPackets.size();
    for(int i=0;i<size;i++)
    {
        ByteBuffer data = (ByteBuffer)videoPackets.get(i);
        int firstByte = data.get(0);
        timecode += ((Long)videoTCs.get(i)).longValue();
        if (FLVUtils.getFrameType(firstByte) == FLVUtils.FLV_KFRAME)
        {
            double durationSecs = ((double)timecode) / 1000.0;
            AMFDataObj dataObj = new AMFDataObj();
            dataObj.put("name", new AMFDataItem("keyframe
"+durationSecs));

            dataObj.put("time", new AMFDataItem(durationSecs));
            keyFrames.add(dataObj);
        }
    }

    try
    {
        FileOutputStream ds = new FileOutputStream(tmpFile, localAppend);
        FLVUtils.writePackets(ds, audioPackets, videoPackets, dataPackets,

```

```

        audioTCs, videoTCs, dataTCs, currentTCs);

        ds.flush();
        ds.close();
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
            "MediaWriterFLVMetadata: Error writing to tmp file:

"+

            newFile.getPath()+" :"+e.toString());
    }

    if (isLast)
    {
        duration = Math.max(Math.max(currentTCs[FLVUtils.FLV_TCINDEXAUDIO],
            currentTCs[FLVUtils.FLV_TCINDEXVIDEO]),
            currentTCs[FLVUtils.FLV_TCINDEXDATA]);
        double durationSecs = ((double)duration) / 1000.0;

        try
        {
            AMFPacket packet = null;
            FileOutputStream ds = new FileOutputStream(newFile);

            FileInputStream di = new FileInputStream(tmpFile);
            FLVUtils.writeHeader(ds, durationSecs, extraMetadata);
            while((packet = FLVUtils.readChunk(di)) != null)
            {
                FLVUtils.writeChunk(ds, packet.getDataBuffer(),
packet.getSize(),

                                packet.getTimecode(),
(byte)packet.getType());
            }
            di.close();

            ds.flush();
            ds.close();

            tmpFile.delete();
        }
        catch (Exception e)
        {
            WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
                "MediaWriterFLVMetadata: Error tmp writing to

file: "+

                newFile.getPath()+" :"+e.toString());
        }
    }
}

private void copyPacketsToTmpFile(File newFile, File tmpFile)

```

```

{
    AMFDataArray keyFrames = null;
    try
    {
        AMFPacket packet = null;
        FileOutputStream ds = new FileOutputStream(tmpFile);

        FileInputStream di = new FileInputStream(newFile);
        FLVUtils.readHeader(di);
        FLVUtils.readChunk(di); // skip metaData packet
        while((packet = FLVUtils.readChunk(di)) != null)
        {
            FLVUtils.writeChunk(ds, packet.getDataBuffer(),
packet.getSize(),
                                packet.getTimecode(),
(byte)packet.getType());
        }
        di.close();

        ds.flush();
        ds.close();
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
            "MediaWriterFLVMetadata: Error copyPacketsToTmpFile:
"+
            newFile.getPath()+" "+e.toString());
    }
}

private AMFDataArray getKeyFrames(File newFile)
{
    AMFDataArray keyFrames = null;
    try
    {
        BufferedInputStream inStream = new BufferedInputStream(new
FileInputStream(newFile));
        FLVUtils.readHeader(inStream);
        AMFPacket packet = FLVUtils.readChunk(inStream);
        if (packet.getType() == IVHost.CONTENTTYPE_DATA0 || packet.getType()
== IVHost.CONTENTTYPE_DATA3)
        {
            byte[] mbytes = packet.getData();
            int moffset = 0;
            if (packet.getType() == IVHost.CONTENTTYPE_DATA3 &&
mbytes.length > 0)
            {
                if (mbytes[0] == 0)
                    moffset = 1;
            }
        }
    }
}

```

```

        AMFDataList dataList = new AMFDataList(mbytes, moffset,
mbytes.length-moffset);
        if (dataList.size() > 1)
        {
            if (dataList.get(1).getType() ==
AMFData.DATA_TYPE_MIXED_ARRAY)
            {
                AMFDataMixedArray metaValues =
                (AMFDataMixedArray)dataList.get(1);
                if (metaValues.containsKey("keyFrames"))
                    keyFrames =
                (AMFDataArray)metaValues.get("keyFrames");
            }
        }
        inStream.close();
    }
    catch (Exception e)
    {
        WMSLoggerFactory.getLogger(MediaWriterFLVBasic.class).error(
            "MediaWriterFLVMetadata: Error getKeyFrames: " +
            newFile.getPath()+" "+e.toString());
    }

    return keyFrames;
}

public boolean isVersionFile()
{
    return versionFile;
}

public void setVersionFile(boolean versionFile)
{
    this.versionFile = versionFile;
}

public void putMetaData(String name, AMFData value)
{
    this.extraMetadata.put(name, value);
}
}

```

To use this class, edit [install-dir]/conf/MediaWriter and replace the definition for the **flv** MediaWriter:

```

<MediaWriter>
  <Name>flv</Name>
  <Description>FLV Media Writer</Description>
  <FileExtension>flv</FileExtension>
  <ClassBase>com.wowza.wms.plugin.mediawriter.flv.MediaWriterFLVMetadata</ClassBase>
</MediaWriter>

```

Method Summary

long	getDuration() Get the recorded duration of the file in seconds
boolean	isVersionFile() Return true if the old file is to be versioned
boolean	isWaitForVideoKeyFrame() get wait for key frame
void	putMetaData (String name, AMFData value) Add metadata to the metadata packet.
void	setMediaWriterItem (MediaWriterItem mediaWriterItem) Set the media write definition
void	setParent (IMediaStream parent) Set the parent stream for this media write object
void	setVersionFile (boolean versionFile) Set to true if the old file is to be versioned
void	setWaitForVideoKeyFrame (boolean waitForVideoKeyFrame) Set to true if you want the recorder to skip opening frames until it hits a key frame
void	writePackets (java.util.List audioPackets, java.util.List videoPackets, java.util.List dataPackets, java.util.List audioTCs, java.util.List videoTCs, java.util.List dataTCs, java.util.List dataTypes, boolean isFirst, boolean isLast) Invoked each time a set of packets are ready to be presisted.

Methods

writePackets

```

public void writePackets(java.util.List audioPackets,
    java.util.List videoPackets,
    java.util.List dataPackets,
    java.util.List audioTCs,
    java.util.List videoTCs,
    java.util.List dataTCs,
    java.util.List dataTypes,
    boolean isFirst,
    boolean isLast)

```

Invoked each time a set of packets are ready to be presisted.

(continued from last page)

Parameters:

audioPackets - List of audio packets
videoPackets - List of video packets
dataPackets - List of data packets
audioTCs - List of audio timecodes
videoTCs - List of video timecodes
dataTCs - List of data timecodes
dataTypes - list of integer packets types (IVHost.CONTENTTYPE_DATA0, IVHost.CONTENTTYPE_DATA3) - if null assumed to be IVHost.CONTENTTYPE_DATA0
isFirst - true if first packet to be written
isLast - false if last packet to be written

setMediaWriterItem

```
public void setMediaWriterItem(MediaWriterItem mediaWriterItem)
```

Set the media write definition

Parameters:

mediaWriterItem - media write definition

setParent

```
public void setParent(IMediaStream parent)
```

Set the parent stream for this media write object

Parameters:

parent

isVersionFile

```
public boolean isVersionFile()
```

Return true if the old file is to be versioned

Returns:

true if the old file is to be versioned

setVersionFile

```
public void setVersionFile(boolean versionFile)
```

Set to true if the old file is to be versioned

Parameters:

versionFile

isWaitForVideoKeyFrame

```
public boolean isWaitForVideoKeyFrame()
```

get wait for key frame

Returns:

wait for key frame

(continued from last page)

setWaitForVideoKeyFrame

```
public void setWaitForVideoKeyFrame(boolean waitForVideoKeyFrame)
```

Set to true if you want the recorder to skip opening frames until it hits a key frame

Parameters:

waitForVideoKeyFrame - wait for key frame

putMetaData

```
public void putMetaData(String name,  
    AMFData value)
```

Add metadata to the metadata packet. Only metadata added before the first call to writePackets will be included in the file

Parameters:

name - field name

value - metadata value

getDuration

```
public long getDuration()
```

Get the recorded duration of the file in seconds

Returns:

recorded duration of the file in seconds

com.wowza.wms.stream Interface IMediaWriterActionNotify

public interface **IMediaWriterActionNotify**
extends

IMediaWriterActionNotify: listener interface for file writing. See
IApplicationInstance.addMediaWriterListener(IMediaWriterActionNotify listener)

Method Summary

void	onFLVAddMetadata (IMediaStream stream, java.util.Map extraMetadata) Called just before metadata is written to the file (FLV only)
void	onWriteComplete (IMediaStream stream, java.io.File file) Called when writing is complete

Methods

onWriteComplete

```
public void onWriteComplete(IMediaStream stream,  
    java.io.File file)
```

Called when writing is complete

Parameters:

stream - stream
file - file handle

onFLVAddMetadata

```
public void onFLVAddMetadata(IMediaStream stream,  
    java.util.Map extraMetadata)
```

Called just before metadata is written to the file (FLV only)


Parameters:

stream - stream
extraMetadata - additional metadata, add to this collection to add items to onMetadata event written to FLV file.

com.wowza.wms.stream

Class MediaStreamBase

java.lang.Object



All Implemented Interfaces:

[IMediaStream](#)

```
public class MediaStreamBase
extends MediaStream
```

Field Summary

public static	p Deprecated.
public static	sinfo Deprecated.

Fields inherited from class com.wowza.wms.stream.MediaStream

actionListeners, audioBytes, audioSize, audioTC, BASE_STREAM_EXT, baseTC, bufferTime, callbacks, client, dataBytes, dataSize, dataTC, dataType, dvrLock, dvrMap, dvrPlayer, dvrRecorder, dvrRecorderList, dvrRepeater, elapsedTime, ext, fastPlaySettings, headerSize, httpStreamerSession, ID3_STREAM_EXT, isAppend, isAudioBase, isClustered, isDataBase, isMediaCasterPlay, isOpen, isPlay, isPlaying, isRecord, isTranscodeResult, isVideoBase, liveStreamPacketizer, liveStreamPacketizerList, liveStreamRepeater, liveStreamTranscoderList, mediaIOPerformance, mergeOnMetadata, metaDataProvider, MP3_STREAM_EXT, MP4_STREAM_EXT, name, netConnection, parent, player, playLen, playStart, playTransition, properties, queryStr, receiveAudio, receiveVideo, receiveVideoFPS, rtpStream, SEND_CONTROL0, SEND_CONTROL1, SEND_CONTROL3, SEND_CONTROL4, sendDirectLock, sendDirectMessages, sendPlayStopLogEvent, sendPublishStopLogEvent, sendRecordStopLogEvent, SMIL_STREAM_EXT, src, STREAM_DEFAULTNAME, streamType, transcoderLock, transcoderMap, tss, videoBytes, videoSize, videoTC

Fields inherited from interface [com.wowza.wms.stream.IMediaStream](#)

[AUDIOSAMPLEACCESS](#), [READACCESS](#), [VIDEOSAMPLEACCESS](#), [WRITEACCESS](#)

Constructor Summary

public	MediaStreamBase()
--------	-----------------------------------

Method Summary

void	init (MediaStreamMap parent, int src, WMSProperties properties)
void	publish ()

void	trim()
------	------------------------

Methods inherited from class com.wowza.wms.stream.MediaStream

addAudioCodecConfigPacket, addAudioData, addClientListener, addClientListener, addClientListener, addDataData, addVideoCodecConfigPacket, addVideoData, clear, clearFastPlaySettings, clearLoggingValues, close, flush, getAccess, getAudioCodecConfigPacket, getAudioMissing, getAudioSize, getAudioTC, getBufferTime, getBurstStartStop, getCacheName, getClient, getClientId, getContextStr, getDataMissing, getDataSize, getDataTC, getDataTC, getDataTC, getDataTC, getDvrRecorder, getDvrRecorder, getDvrRecorderList, getDvrRepeater, getElapsedTime, getExt, getFastPlaySettings, getHeaderSize, getHTTPStreamerSession, getLastKeyFrame, getLastPacket, getLiveStreamDvr, getLiveStreamDvrs, getLiveStreamPacketizer, getLiveStreamPacketizer, getLiveStreamPacketizerList, getLiveStreamRepeater, getLiveStreamTranscoder, getLiveStreamTranscoderList, getLiveStreamTranscoders, getMaxTimecode, getMediaIOPerformance, getMetaDataProvider, getName, getNetConnection, getPlayer, getPlayPackets, getProperties, getPublishAudioCodecId, getPublishVideoCodecId, getQueryStr, getReceiveVideoFPS, getRespAMFAudioObj, getRespAMFDataObj, getRespAMFVideoObj, getRTPStream, getSrc, getStreamFileForRead, getStreamFileForRead, getStreamFileForWrite, getStreamFileForWrite, getStreams, getStreamType, getTss, getUniqueStreamIdStr, getVideoCodecConfigPacket, getVideoMissing, getVideoSize, getVideoTC, handleCallback, idle, incrementMediaInBytes, incrementMediaLossBytes, incrementMediaOutBytes, init, initDvrRepeating, initLiveStreamRepeating, isAppend, isClustered, isMediaCasterPlay, isMergeOnMetadata, isOpen, isPlay, isPlaying, isPublishStreamReady, isReceiveAudio, isReceiveVideo, isRecord, isSendDirectMessages, isSendPlayStopLogEvent, isSendPublishStopLogEvent, isSendRecordStopLogEvent, isTranscodeResult, length, notifyActionOnCodecInfoAudio, notifyActionOnCodecInfoVideo, notifyActionOnMetaData, notifyActionPause, notifyActionPauseRaw, notifyActionPlay, notifyActionPublish, notifyActionSeek, notifyActionStop, notifyActionUnPublish, packetComplete, processSendDirectMessages, publish, putDvrRecorder, putLiveStreamTranscoder, registerCallback, registerOnPlayStatus, registerOnStatus, removeClientListener, removeClientListener, removeClientListener, removeDvrRecorder, removeLiveStreamTranscoder, reset, send, send, sendAMF3, sendAMF3, sendControlBytes, sendDirect, sendDirect, sendDirectAMF3, sendDirectAMF3, sendDirectInternal, sendDirectInternal, sendInternal, sendInternal, sendLivePlaySeek, sendLivePlayStart, sendLivePlaySwitch, sendPauseNotify, sendPauseNotify, sendPlayReset, sendPlayReset, sendPlaySeek, sendPlaySeek, sendPlaySeek, sendPlayStart, sendPlayStart, sendPlayStart, sendPlayStart, sendPlayStatus, sendPlayStatus, sendPlayStop, sendPlayStop, sendPlaySwitch, sendPlaySwitch, sendStreamNotFound, sendStreamNotFound, sendUnpauseNotify, sendUnpauseNotify, sendUnpauseNotify, sendVODPlaySwitch, setAppend, setAudioSize, setAudioTC, setAudioTC, setBufferTime, setClient, setClustered, setDataSize, setDataTC, setDataTC, setDataTC, setDataTC, setDataTC, setDvrRecorder, setDvrRecorderList, setDvrRepeater, setExt, setFastPlaySettings, setHeaderSize, setHTTPStreamerSession, setIsPlaying, setJustName, setLiveStreamPacketizer, setLiveStreamPacketizerList, setLiveStreamRepeater, setLiveStreamTranscoderList, setMediaCasterPlay, setMergeOnMetadata, setMetaDataProvider, setName, setName, setName, setNetConnection, setOpen, setPlay, setPlayer, setPublishAudioCodecId, setPublishVideoCodecId, setQueryStr, setReceiveAudio, setReceiveVideo, setReceiveVideoFPS, setRecord, setRTPStream, setSendPlayStopLogEvent, setSendPublishStopLogEvent, setSendRecordStopLogEvent, setSrc, setStreamType, setTranscodeResult, setTss, setVideoSize, setVideoTC, setVideoTC, shutdown, size, startAudioPacket, startDataPacket, startPublishing, startVideoPacket, stopName, stopPublishing, switchName, trim, unregisterCallback, unregisterOnPlayStatus, unregisterOnStatus, updateLoggingDuration, updateLoggingValues

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.stream.IMediaStream](#)

[addAudioCodecConfigPacket](#), [addAudioData](#), [addClientListener](#), [addClientListener](#), [addClientListener](#), [addDataData](#), [addVideoCodecConfigPacket](#), [addVideoData](#), [clear](#), [clearFastPlaySettings](#), [clearLoggingValues](#), [close](#), [flush](#), [getAccess](#), [getAudioCodecConfigPacket](#), [getAudioMissing](#), [getAudioSize](#), [getAudioTC](#), [getBufferTime](#), [getBurstStartStop](#), [getCacheName](#), [getClient](#), [getClientId](#), [getContextStr](#), [getDataMissing](#), [getDataSize](#), [getDataTC](#), [getDataType](#), [getDvrRecorder](#), [getDvrRecorder](#), [getDvrRecorderList](#), [getDvrRepeater](#), [getElapsedTime](#), [getExt](#), [getFastPlaySettings](#), [getHeaderSize](#), [getHTTPStreamerSession](#), [getLastKeyFrame](#), [getLastPacket](#), [getLiveStreamPacketizer](#), [getLiveStreamPacketizer](#), [getLiveStreamPacketizerList](#), [getLiveStreamRepeater](#), [getLiveStreamTranscoder](#), [getLiveStreamTranscoderList](#), [getLiveStreamTranscoders](#), [getMaxTimecode](#), [getMediaIOPerformance](#), [getMetaDataProvider](#), [getName](#), [getNetConnection](#), [getPlayer](#), [getPlayPackets](#), [getProperties](#), [getPublishAudioCodecId](#), [getPublishVideoCodecId](#), [getQueryStr](#), [getReceiveVideoFPS](#), [getRespAMFAudioObj](#), [getRespAMFDataObj](#), [getRespAMFVideoObj](#), [getRTPStream](#), [getSrc](#), [getStreamFileForRead](#), [getStreamFileForRead](#), [getStreamFileForWrite](#), [getStreamFileForWrite](#), [getStreams](#), [getStreamType](#), [getUniqueStreamIdStr](#), [getVideoCodecConfigPacket](#), [getVideoMissing](#), [getVideoSize](#), [getVideoTC](#), [handleCallback](#), [idle](#), [incrementMediaInBytes](#), [incrementMediaLossBytes](#), [incrementMediaOutBytes](#), [init](#), [initLiveStreamRepeating](#), [isAppend](#), [isClustered](#), [isMediaCasterPlay](#), [isMergeOnMetadata](#), [isOpen](#), [isPlay](#), [isPlaying](#), [isPublishStreamReady](#), [isReceiveAudio](#), [isReceiveVideo](#), [isRecord](#), [isSendPlayStopLogEvent](#), [isSendPublishStopLogEvent](#), [isSendRecordStopLogEvent](#), [isTranscodeResult](#), [length](#), [notifyActionOnCodecInfoAudio](#), [notifyActionOnCodecInfoVideo](#), [notifyActionOnMetadata](#), [notifyActionPause](#), [notifyActionPauseRaw](#), [notifyActionPlay](#), [notifyActionPublish](#), [notifyActionSeek](#), [notifyActionStop](#), [notifyActionUnPublish](#), [packetComplete](#), [publish](#), [putDvrRecorder](#), [putLiveStreamTranscoder](#), [registerCallback](#), [registerOnPlayStatus](#), [registerOnStatus](#), [removeClientListener](#), [removeClientListener](#), [removeClientListener](#), [removeDvrRecorder](#), [removeLiveStreamTranscoder](#), [send](#), [send](#), [sendAMF3](#), [sendAMF3](#), [sendControlBytes](#), [sendDirect](#), [sendDirect](#), [sendDirectAMF3](#), [sendDirectAMF3](#), [sendLivePlaySeek](#), [sendLivePlayStart](#), [sendLivePlaySwitch](#), [sendPauseNotify](#), [sendPauseNotify](#), [sendPlayReset](#), [sendPlayReset](#), [sendPlaySeek](#), [sendPlaySeek](#), [sendPlaySeek](#), [sendPlayStart](#), [sendPlayStart](#), [sendPlayStart](#), [sendPlayStart](#), [sendPlayStatus](#), [sendPlayStatus](#), [sendPlayStop](#), [sendPlayStop](#), [sendPlaySwitch](#), [sendPlaySwitch](#), [sendStreamNotFound](#), [sendStreamNotFound](#), [sendUnpauseNotify](#), [sendUnpauseNotify](#), [sendUnpauseNotify](#), [sendVODPlaySwitch](#), [setAppend](#), [setAudioSize](#), [setAudioTC](#), [setAudioTC](#), [setBufferTime](#), [setClient](#), [setClustered](#), [setDataSize](#), [setDataTC](#), [setDataTC](#), [setDataTC](#), [setDataTC](#), [setDataTC](#), [setDvrRecorder](#), [setDvrRecorderList](#), [setExt](#), [setFastPlaySettings](#), [setHeaderSize](#), [setHTTPStreamerSession](#), [setIsPlaying](#), [setLiveStreamPacketizer](#), [setLiveStreamPacketizerList](#), [setLiveStreamRepeater](#), [setLiveStreamTranscoderList](#), [setMediaCasterPlay](#), [setMergeOnMetadata](#), [setMetaDataProvider](#), [setName](#), [setName](#), [setName](#), [setNetConnection](#), [setOpen](#), [setPlay](#), [setPlayer](#), [setPublishAudioCodecId](#), [setPublishVideoCodecId](#), [setQueryStr](#), [setReceiveAudio](#), [setReceiveVideo](#), [setReceiveVideoFPS](#), [setRecord](#), [setRTPStream](#), [setSendPlayStopLogEvent](#), [setSendPublishStopLogEvent](#), [setSendRecordStopLogEvent](#), [setSrc](#), [setStreamType](#), [setTranscodeResult](#), [setVideoSize](#), [setVideoTC](#), [setVideoTC](#), [shutdown](#), [size](#), [startAudioPacket](#), [startDataPacket](#), [startPublishing](#), [startVideoPacket](#), [stopName](#), [stopPublishing](#), [switchName](#), [trim](#), [unregisterCallback](#), [unregisterOnPlayStatus](#), [unregisterOnStatus](#), [updateLoggingDuration](#), [updateLoggingValues](#)

(continued from last page)

Fields

sinfo

```
public static java.util.Map sinfo
```

Deprecated.

p

```
public static java.lang.String p
```

Deprecated.

Constructors

MediaStreamBase

```
public MediaStreamBase()
```

Methods

init

```
public void init(MediaStreamMap parent,  
                int src,  
                WMSPProperties properties)
```

publish

```
public void publish()
```

trim

```
public void trim()
```

com.wowza.wms.stream

Class MediaStreamMap

java.lang.Object

└─com.wowza.wms.stream.MediaStreamMap

public class **MediaStreamMap**
extends Object

MediaStreamMap: collection of IMediaStream object. This collection is usually attached to an IApplicationInstance object.

Field Summary

protected	appInstance
protected	dvrRecorders
protected	liveStreamPacketizers
public static final	MAXSTREAMINDEX Value: 65536
protected	mediaStreamListeners
protected	nameGroupId
protected	nameGroups
protected	nextStreamId
protected	packetizerLicenses
protected	streamLicenses
protected	streamLock
protected	streamNames
protected	streamNamesLock
protected	streamNameToGroup
protected	streams

Constructor Summary

public	MediaStreamMap (IApplicationInstance appInstance) Create empty MediaStreamMap collection
--------	------------------------------------------------------------------------------------------------------------------------------

Method Summary

LicenseHolder	addLicense (ILiveStreamPacketizer liveStreamPacketizer, int licenseType)
LicenseHolder	addLicense (IMediaStream stream, int licenseType)
void	addMediaStreamListener (IMediaStreamNotify mediaStreamListener) Add a media stream listener.
MediaStreamMapGroup	addNameGroup (MediaStreamMapGroup newGroup)
void	broadcastPlayMessage (IMediaStream stream, long timecode, java.nio.ByteBuffer msg, int objectEncoding) Send a broadcast message to all play stream that are listening to this live published stream.
int	broadcastGetObjectEncoding (IMediaStream stream) Get the minimum object encoding level for the clients playing this stream.
void	clearStreamName (String name) Unregister a published live media stream name.
void	clearStreamName (String name, IMediaStream stream) Unregister a published live media stream name.
IApplicationInstance	getAppInstance () Get the parent applicationInstance.
String	getAppInstanceName () Get the name of the parent applicationInstance.
String	getAppName () Get the name of the parent application.
int	getCount () Get the total number of streams stored in the mediaStreamMap
ILiveStreamDvrRecorder	getDvrRecorder (String streamName, String recorderName, boolean doCreate) Get a DVR recorder by name and recorder name
java.util.List	getDvrRecorders () Returns a list of ILiveStreamDvrRecorder objects
ILiveStreamPacketizer	getLiveStreamPacketizer (String streamName, String packetizerName, boolean doCreate) Get a live stream packetizer by name and packetizer id
Object	getLiveStreamPacketizerLock () Get the lock to the live stream packetizer system
MediaStreamMapGroup	getNameGroupByGroupName (String groupName)
java.util.Set	getNameGroups ()

java.util.Set	<u>getNameGroups</u> (String streamName)
java.util.Set	<u>getNameGroupStreamNames</u> (String streamName)
long	<u>getNextNameGroupId</u> (MediaStreamMapGroup newGroup)
int	<u>getNextStreamIndex</u> () Reserve a clientless stream id for a new media stream.
int	<u>getNextStreamIndex</u> (<u>IClient</u> client) Reserve a stream for a client connection.
int	<u>getNextStreamIndex</u> (com.wowza.wms.netconnection.INetConnection netConnection) Reserve a stream for a netConnection connection.
java.util.List	<u>getPublishStreamNames</u> () Returns a List of published stream names
<u>IMediaStream</u>	<u>getStream</u> (<u>IClient</u> client, int index) Get a media stream reference by stream id.
<u>IMediaStream</u>	<u>getStream</u> (<u>IClient</u> client, int index, boolean doCreate) Get a media stream reference by stream id.
<u>IMediaStream</u>	<u>getStream</u> (com.wowza.wms.netconnection.INetConnection netConnection, int index) Get a media stream object that is owned by a server to server netConnection object (not yet implemented).
<u>IMediaStream</u>	<u>getStream</u> (com.wowza.wms.netconnection.INetConnection netConnection, int index, boolean doCreate) Get a media stream reference by stream id.
<u>IMediaStream</u>	<u>getStream</u> (String name) Get a media stream by stream name.
<u>IMediaStream</u>	<u>getStreamClientless</u> (int index, String streamTypeStr) Get a media stream reference by stream id.
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<u>getStreamListLock</u> () Get the underlying read/write lock associated with the list of streams
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<u>getStreamNameLock</u> () Get the underlying read/write lock associated with the stream names list
java.util.List	<u>getStreams</u> () Returns a list of IMediaStream objects
<u>IVHost</u>	<u>getVHost</u> () Get the parent vHost.
void	<u>notifyMediaStreamCreate</u> (<u>IMediaStream</u> mediaStream) Notify all media stream listeners that a new media stream object has been created.

void	<u>notifyMediaStreamDestroy</u> (<u>IMediaStream</u> mediaStream) Notify all media stream listeners that a media stream object is being destroyed.
void	<u>notifyPlayPublish</u> (<u>IMediaStream</u> stream) Notify all play streams that are listening to this stream that the stream is going into a state of publish (NetStream.Play.PublishNotify).
void	<u>notifyPlayUnpublish</u> (<u>IMediaStream</u> stream) Notify all play streams that are listening to this stream that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).
void	<u>notifyPlayUnpublish</u> (String streamName) Notify all play streams that are listening to this stream name that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).
void	<u>removeDvrRecorder</u> (String streamName)
<u>ILiveStreamDvrRecorder</u>	<u>removeDvrRecorder</u> (String streamName, String recorderName) Remove DVR Recorder
void	<u>removeLiveStreamPacketizer</u> (String streamName) Remove all live stream packetizers for this stream name
<u>ILiveStreamPacketizer</u>	<u>removeLiveStreamPacketizer</u> (String streamName, String packetizerName) Remove live stream packetizer
void	<u>removeMediaStreamListener</u> (<u>IMediaStreamNotify</u> mediaStreamListener) Remove a media stream listener.
MediaStreamMapGroup	<u>removeNameGroup</u> (int groupId)
MediaStreamMapGroup	<u>removeNameGroup</u> (MediaStreamMapGroup nameGroup)
void	<u>removeStream</u> (<u>IClient</u> client, int index) Remove a stream associated with a client connection
void	<u>removeStream</u> (com.wowza.wms.netconnection.INetConnection netConnection, int index) Remove a stream associated with a netConnection object
void	<u>removeStream</u> (int index) Remove a clientless media stream
void	<u>setStreamName</u> (<u>IMediaStream</u> stream, String name) Insert live media stream into the mediaStreamMap by name.
long	<u>streamToIndex</u> (<u>IMediaStream</u> stream) Get the unique stream identifier for a given stream

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

(continued from last page)

MAXSTREAMINDEX

```
public static final int MAXSTREAMINDEX
```

Constant value: **65536**

streams

```
protected java.util.Map streams
```

streamNames

```
protected java.util.Map streamNames
```

streamLicenses

```
protected java.util.Map streamLicenses
```

packetizerLicenses

```
protected java.util.Map packetizerLicenses
```

streamNameToGroup

```
protected java.util.Map streamNameToGroup
```

nameGroups

```
protected java.util.List nameGroups
```

nameGroupId

```
protected long nameGroupId
```

streamLock

```
protected edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
streamLock
```

(continued from last page)

streamNamesLock

protected edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock
streamNamesLock

appInstance

protected com.wowza.wms.application.IApplicationInstance **appInstance**

mediaStreamListeners

protected java.util.List **mediaStreamListeners**

nextStreamId

protected java.util.concurrent.atomic.AtomicLong **nextStreamId**

liveStreamPacketizers

protected java.util.Map **liveStreamPacketizers**

dvrRecorders

protected java.util.Map **dvrRecorders**

Constructors

MediaStreamMap

public **MediaStreamMap**([IApplicationInstance](#) appInstance)

Create empty MediaStreamMap collection

Parameters:

appInstance - parent applicationInstance

Methods

getStreamListLock

public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock
getStreamListLock()

Get the underlying read/write lock associated with the list of streams

Returns:

(continued from last page)

underlying read/write lock associated with the list of streams

getStreamNameLock

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
getStreamNameLock()
```

Get the underlying read/write lock associated with the stream names list

Returns:

underlying read/write lock associated with the stream names list

getPublishStreamNames

```
public java.util.List getPublishStreamNames()
```

Returns a List of published stream names

Returns:

List of published stream names

getStreams

```
public java.util.List getStreams()
```

Returns a list of IMediaStream objects

Returns:

list of IMediaStream objects

getStream

```
public IMediaStream getStream(IClient client,  
int index)
```

Get a media stream reference by stream id.

Parameters:

client - client
index - stream id

Returns:

media stream object or null if does not exist.

getStreamClientless

```
public IMediaStream getStreamClientless(int index,  
String streamTypeStr)
```

Get a media stream reference by stream id. If it does not exist, create a new one with the given id. This is a clientless stream that is served by the backend of the server. If creating a new media stream object, its id must first be obtained by calling [getNextStreamIndex\(\)](#).

Parameters:

index - stream id
streamTypeStr - stream type

Returns:

media stream object

getStream

```
public IMediaStream getStream(IClient client,  
                               int index,  
                               boolean doCreate)
```

Get a media stream reference by stream id. If it does not exist, create a new one with the given id. If creating a new media stream object, its id must first be obtained by calling [getNextStreamIndex\(IClient\)](#) .

Parameters:

client - client
index - stream id
doCreate - true to create if it does not exist

Returns:

media stream object

getStream

```
public IMediaStream getStream(com.wowza.wms.netconnection.INetConnection  
netConnection,  
                               int index)
```

Get a media stream object that is owned by a server to server netConnection object (not yet implemented).

Parameters:

netConnection - netConnection to remote server
index - stream id

Returns:

media stream object or null if does not exist

getStream

```
public IMediaStream getStream(com.wowza.wms.netconnection.INetConnection  
netConnection,  
                               int index,  
                               boolean doCreate)
```

Get a media stream reference by stream id. If it does not exist, create a new one with the given id. If creating a new media stream object, its id must first be obtained by calling [getNextStreamIndex\(INetConnection\)](#) .

Parameters:

netConnection - netConnection to remote server
index - stream id
doCreate - true to create if it does not exist

Returns:

media stream object

getStream

```
public IMediaStream getStream(String name)
```

Get a media stream by stream name. Only published live streams are stored in the mediaStreamMap by name. This method is used to lookup a published live stream by name.

Parameters:

name - stream name

(continued from last page)

Returns:

media stream object or null if does not exist

setStreamName

```
public void setStreamName(IMediaStream stream,  
    String name)
```

Insert live media stream into the mediaStreamMap by name.

Parameters:

stream - media stream object
name - media stream name

clearStreamName

```
public void clearStreamName(String name)
```

Unregister a published live media stream name.

Parameters:

name - stream name

streamToIndex

```
public long streamToIndex(IMediaStream stream)
```

Get the unique stream identifier for a given stream

Parameters:

stream - stream

Returns:

unique stream identifier

clearStreamName

```
public void clearStreamName(String name,  
    IMediaStream stream)
```

Unregister a published live media stream name.

Parameters:

name - stream name
stream - stream

getNextStreamIndex

```
public int getNextStreamIndex(com.wowza.wms.netconnection.INetConnection  
    netConnection)
```

Reserve a stream for a netConnection connection. Use [getStream\(INetConnection, int, boolean\)](#) to create stream.**Parameters:**

netConnection

Returns:

next stream index

getNextStreamIndex

```
public int getNextStreamIndex(IClient client)
```

Reserve a stream for a client connection. Use [getStream\(IClient, int, boolean\)](#) to create stream.

Parameters:

client - parent client

Returns:

stream index

getNextStreamIndex

```
public int getNextStreamIndex()
```

Reserve a clientless stream id for a new media stream. Use this method to obtain a stream id for a new media stream object that is then created with a call to getClientlessStream().

Returns:

new reserved stream id

getCount

```
public int getCount()
```

Get the total number of streams stored in the mediaStreamMap

Returns:

total number of streams stored in the mediaStreamMap

removeStream

```
public void removeStream(com.wowza.wms.netconnection.INetConnection netConnection,  
int index)
```

Remove a stream associated with a netConnection object

Parameters:

netConnection - net connection

index - stream index

removeStream

```
public void removeStream(IClient client,  
int index)
```

Remove a stream associated with a client connection

Parameters:

client - client

index - stream index

removeStream

```
public void removeStream(int index)
```

Remove a clientless media stream

(continued from last page)

Parameters:

index - stream index

getAppName

```
public String getAppName()
```

Get the name of the parent application.

Returns:

parent application name.

getAppInstanceName

```
public String getAppInstanceName()
```

Get the name of the parent applicationInstance.

Returns:

parent applicationInstance name

getVHost

```
public IVHost getVHost()
```

Get the parent vHost.

Returns:

parent vHost

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get the parent applicationInstance.

Returns:

parent applicationInstance

notifyPlayUnpublish

```
public void notifyPlayUnpublish(IMediaStream stream)
```

Notify all play streams that are listening to this stream that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).

Parameters:

stream - live published stream that is being unpublished

notifyPlayUnpublish

```
public void notifyPlayUnpublish(String streamName)
```

Notify all play streams that are listening to this stream name that the stream is going into a state of unpublished (NetStream.Play.UnpublishNotify).

Parameters:

streamName - live published stream that is being unpublished

broadcastGetObjectEncoding

```
public int broadcastGetObjectEncoding(IMediaStream stream)
```

Get the minimum object encoding level for the clients playing this stream.

Parameters:

stream - publish stream

Returns:

object encoding level (AMF0 or AMF3)

broadcastPlayMessage

```
public void broadcastPlayMessage(IMediaStream stream,  
    long timecode,  
    java.nio.ByteBuffer msg,  
    int objectEncoding)
```

Send a broadcast message to all play stream that are listening to this live published stream.

Parameters:

stream - media stream

timecode - timecode (milliseconds)

msg - byte[] of data that will be deserialized as an AMFData object.

objectEncoding - object encoding (AMF0 or AMF3)

notifyPlayPublish

```
public void notifyPlayPublish(IMediaStream stream)
```

Notify all play streams that are listening to this stream that the stream is going into a state of publish (NetStream.Play.PublishNotify).

Parameters:

stream - live published stream that is being published

addMediaStreamListener

```
public void addMediaStreamListener(IMediaStreamNotify mediaStreamListener)
```

Add a media stream listener. A media stream listener will receive the following events: onMediaStreamCreate, onMediaStreamDestroy.

Parameters:

mediaStreamListener - media stream listener

removeMediaStreamListener

```
public void removeMediaStreamListener(IMediaStreamNotify mediaStreamListener)
```

Remove a media stream listener.

Parameters:

mediaStreamListener - media stream listener

(continued from last page)

notifyMediaStreamCreate

```
public void notifyMediaStreamCreate(IMediaStream mediaStream)
```

Notify all media stream listeners that a new media stream object has been created.

Parameters:

mediaStream - new media stream object

notifyMediaStreamDestroy

```
public void notifyMediaStreamDestroy(IMediaStream mediaStream)
```

Notify all media stream listeners that a media stream object is being destroyed.

Parameters:

mediaStream - media stream object being destroyed

removeLiveStreamPacketizer

```
public void removeLiveStreamPacketizer(String streamName)
```

Remove all live stream packetizers for this stream name

Parameters:

streamName - streamName

removeLiveStreamPacketizer

```
public ILiveStreamPacketizer removeLiveStreamPacketizer(String streamName,  
String packetizerName)
```

Remove live stream packetizer

Parameters:

streamName - stream name

packetizerName - packetizer id

Returns:

live stream packetizer

getLiveStreamPacketizerLock

```
public Object getLiveStreamPacketizerLock()
```

Get the lock to the live stream packetizer system

Returns:

lock to the live stream packetizer system

getLiveStreamPacketizer

```
public ILiveStreamPacketizer getLiveStreamPacketizer(String streamName,  
String packetizerName,  
boolean doCreate)
```

Get a live stream packetizer by name and packetizer id

Parameters:

(continued from last page)

streamName - stream name
packetizerName - packetizer id
doCreate - create if does not exist

Returns:

live stream packetizer

getNextNameGroupId

```
public long getNextNameGroupId(MediaStreamMapGroup newGroup)
```

addNameGroup

```
public MediaStreamMapGroup addNameGroup(MediaStreamMapGroup newGroup)
```

removeNameGroup

```
public MediaStreamMapGroup removeNameGroup(int groupId)
```

removeNameGroup

```
public MediaStreamMapGroup removeNameGroup(MediaStreamMapGroup nameGroup)
```

getNameGroups

```
public java.util.Set getNameGroups()
```

getNameGroupByGroupName

```
public MediaStreamMapGroup getNameGroupByGroupName(String groupName)
```

getNameGroups

```
public java.util.Set getNameGroups(String streamName)
```

getNameGroupStreamNames

```
public java.util.Set getNameGroupStreamNames(String streamName)
```

(continued from last page)

getDvrRecorder

```
public ILiveStreamDvrRecorder getDvrRecorder(String streamName,  
      String recorderName,  
      boolean doCreate)
```

Get a DVR recorder by name and recorder name

Parameters:

streamName - stream name
recorderName - packetizer id
doCreate - create if does not exist

Returns:

dvr recorder

removeDvrRecorder

```
public void removeDvrRecorder(String streamName)
```

removeDvrRecorder

```
public ILiveStreamDvrRecorder removeDvrRecorder(String streamName,  
      String recorderName)
```

Remove DVR Recorder

Parameters:

streamName - stream name
recorderName - recorder name

Returns:

DVR Recorder

getDvrRecorders

```
public java.util.List getDvrRecorders()
```

Returns a list of [ILiveStreamDvrRecorder](#) objects

Returns:

list of [ILiveStreamDvrRecorder](#) objects

addLicense

```
public LicenseHolder addLicense(IMediaStream stream,  
      int licenseType)
```

addLicense

```
public LicenseHolder addLicense(ILiveStreamPacketizer liveStreamPacketizer,  
      int licenseType)
```

Package

com.wowza.wms.stream.livedvr

com.wowza.wms.stream.livedvr Interface IDvrStreamManagerActionNotify

public interface **IDvrStreamManagerActionNotify**
extends

IDvrActionNotify notify interface for dvr stores. See IApplicationInstance.addDvrStoreListener(IDvrStoreActionNotify storeListener)

Method Summary

void	onDvrStreamManagerCreate (IDvrStreamManager dvrMgr) Called when DVR stream manager created but before it is initialized.
void	onDvrStreamManagerDestroy (IDvrStreamManager dvrMgr) Called when DVR stream manager destroyed.
void	onDvrStreamManagerInit (IDvrStreamManager dvrMgr) Called when DVR stream manager initialized.

Methods

onDvrStreamManagerCreate

public void **onDvrStreamManagerCreate**([IDvrStreamManager](#) dvrMgr)

Called when DVR stream manager created but before it is initialized.

Parameters:

dvrMgr - DVR stream manager

onDvrStreamManagerInit

public void **onDvrStreamManagerInit**([IDvrStreamManager](#) dvrMgr)

Called when DVR stream manager initialized.

Parameters:

dvrMgr - DVR stream manager

onDvrStreamManagerDestroy

public void **onDvrStreamManagerDestroy**([IDvrStreamManager](#) dvrMgr)

Called when DVR stream manager destroyed.

Parameters:

dvrMgr - DVR stream manager

com.wowza.wms.stream.livedvr Interface **ILiveStreamDvrRecorder**

public interface **ILiveStreamDvrRecorder**
extends

ILiveStreamDvrRecorder: DVR Recorder interface.

Method Summary

boolean	<u>canRecordAudio()</u> True if audio is being recorded
boolean	<u>canRecordData()</u> True if data is being recorded
boolean	<u>canRecordVideo()</u> True if video is being recorded
<u>IApplicationInstance</u>	<u>getAppInstance()</u> Get associated applicationInstance.
<u>IDvrStreamManager</u>	<u>getDvrManager()</u> Get DVR recorder's associated DVR stream manager
int	<u>getDvrRecorderId()</u> Get the DVR recorder id
LicenseHolder	<u>getLicenseHolder()</u>
<u>WMSProperties</u>	<u>getProperties()</u> Get properties
String	<u>getRecordingName()</u>
<u>IMediaStream</u>	<u>getStream()</u> Get the current stream that is being recorded
void	<u>handlePacket()</u> (<u>IMediaStream</u> stream, <u>AMFPacket</u> packet) Called to handle an incoming packet
void	<u>init()</u> (String streamName, String recorderName, <u>IApplicationInstance</u> appInstance, DvrRecorderItem dvrRecorderItem) Initialize DVR recorder.
boolean	<u>isActive()</u> Is the DVR recorder active
boolean	<u>isRecording()</u> Is this stream currently recording.
boolean	<u>isRecordingPaused()</u> Is this stream currently paused from recording.

boolean	<u>pauseRecording()</u> Request that stream recording pause.
void	<u>resetStream()</u> (<u>IMediaStream</u> stream) Called when something happens that forces the stream to reset
boolean	<u>resumeRecording()</u> Request that stream recording resume.
void	<u>setDvrRecorderId()</u> (int liveStreamId) Set the DVR recorder id
void	<u>setRecordAudio()</u> (boolean recordAudio) Set to true to record audio
void	<u>setRecordData()</u> (boolean recordVideo) Set to true to record data
void	<u>setRecordingName()</u> (String name)
void	<u>setRecordVideo()</u> (boolean recordVideo) Set to true to record video
void	<u>setStartRecordingOnStartup()</u> (boolean shouldStartRecordingOnStartup) Set recording behavior of DVR Manager on startup.
boolean	<u>shouldStartRecordingOnStartup()</u> Should DVR start recording when packets start flowing.
void	<u>shutdown()</u> Called to shutdown the DVR recorder
<u>IDvrStreamManager</u>	<u>startRecording()</u> Request that stream recording start.
void	<u>startStream()</u> (<u>IMediaStream</u> stream) Called when the stream starts
boolean	<u>stopRecording()</u> Request that stream recording stop.
void	<u>touch()</u> (long timecode) Touch the stream to keep it active

Methods

init

```
public void init(String streamName,
    String recorderName,
    IApplicationInstance appInstance,
    DvrRecorderItem dvrRecorderItem)
```

Initialize DVR recorder.

Parameters:

streamName - stream name

(continued from last page)

recorderName - DVR recorder name
appInstance - application instance
dvrRecorderItem - DVR recorder

shutdown

```
public void shutdown()
```

Called to shutdown the DVR recorder

getStream

```
public IMediaStream getStream()
```

Get the current stream that is being recorded

Returns:
stream

getAppInstance

```
public IApplicationInstance getAppInstance()
```

Get associated applicationInstance.

Returns:
application Instance

handlePacket

```
public void handlePacket(IMediaStream stream,  
    AMFPacket packet)
```

Called to handle an incoming packet

Parameters:
stream - stream
packet - packet

startStream

```
public void startStream(IMediaStream stream)
```

Called when the stream starts

Parameters:
stream - stream

resetStream

```
public void resetStream(IMediaStream stream)
```

Called when something happens that forces the stream to reset

Parameters:
stream - stream

(continued from last page)

touch

```
public void touch(long timecode)
```

Touch the stream to keep it active

Parameters:

timecode - timecode of touch in milliseconds

isActive

```
public boolean isActive()
```

Is the DVR recorder active

Returns:

true if active

getProperties

```
public WMSProperties getProperties()
```

Get properties

Returns:

properties

getDvrRecorderId

```
public int getDvrRecorderId()
```

Get the DVR recorder id

Returns:

DVR recorder id

setDvrRecorderId

```
public void setDvrRecorderId(int liveStreamId)
```

Set the DVR recorder id

Parameters:

liveStreamId

getDvrManager

```
public IDvrStreamManager getDvrManager()
```

Get DVR recorder's associated DVR stream manager

Returns:

DVR manager

canRecordAudio

```
public boolean canRecordAudio()
```

(continued from last page)

True if audio is being recorded

Returns:

True if audio is being recorded

setRecordAudio

```
public void setRecordAudio(boolean recordAudio)
```

Set to true to record audio

Parameters:

recordAudio - true to record audio

canRecordVideo

```
public boolean canRecordVideo()
```

True if video is being recorded

Returns:

True if video is being recorded

setRecordVideo

```
public void setRecordVideo(boolean recordVideo)
```

Set to true to record video

Parameters:

recordVideo - true to record video

canRecordData

```
public boolean canRecordData()
```

True if data is being recorded

Returns:

True if data is being recorded

setRecordData

```
public void setRecordData(boolean recordVideo)
```

Set to true to record data

Parameters:

recordVideo - true to record data

startRecording

```
public IDvrStreamManager startRecording()
```

Request that stream recording start.

Returns:

stream manager if successful. null otherwise.

isRecording

```
public boolean isRecording()
```

Is this stream currently recording. If this stream is not recordable, the method returns false.

Returns:

true if has a recording stream and it is recording.

isRecordingPaused

```
public boolean isRecordingPaused()
```

Is this stream currently paused from recording. If this stream is not recording and not paused, the method returns false.

Returns:

true if has a recording is paused.

stopRecording

```
public boolean stopRecording()
```

Request that stream recording stop. Note that this call places the DVR stream in the *not* recording state.

A successful stop will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingStopped\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Success only occurs if the stream is already in the recording state [IDvrStreamStore.isRecording\(\)](#).

Returns:

store if successful. null otherwise.

pauseRecording

```
public boolean pauseRecording()
```

Request that stream recording pause. The stream does not have to be actively recording to be paused. For example, it could be paused before packets start flowing.

A successful pause will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingPaused\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Returns:

store if successful. null otherwise.

resumeRecording

```
public boolean resumeRecording()
```

Request that stream recording resume. The stream does not have to be actively recording to be resumed. For example, it could have been paused before the stream started, and this call would move it out of the paused state.

A successful resume will result in registered [IDvrRecordingListeners](#) to have their [IDvrRecordingListener.recordingResumed\(IDvrStreamManager, IDvrStreamStore\)](#) method called.

Returns:

store if successful. null otherwise.

(continued from last page)

setRecordingName

```
public void setRecordingName(String name)
```

getRecordingName

```
public String getRecordingName()
```

shouldStartRecordingOnStartup

```
public boolean shouldStartRecordingOnStartup()
```

Should DVR start recording when packets start flowing.

Returns:

true if should start recording initially, false otherwise

setStartRecordingOnStartup

```
public void setStartRecordingOnStartup(boolean shouldStartRecordingOnStartup)
```

Set recording behavior of DVR Manager on startup.

Parameters:

shouldStartRecordingOnStartup - should recording start when DVR manager starts.

getLicenseHolder

```
public LicenseHolder getLicenseHolder()
```

com.wowza.wms.stream.livedvr Interface **ILiveStreamDvrRecorderActionNotify**

public interface **ILiveStreamDvrRecorderActionNotify**
extends

ILiveStreamDvrRecorderActionNotify: notify interface for dvr recorders.

See Also:

[IApplicationInstance.addDvrRecorderListener\(ILiveStreamDvrRecorderActionNotify\)](#),

Method Summary

void	onLiveStreamDvrRecorderCreate (ILiveStreamDvrRecorder recorder, String streamName) Called when recorder created
void	onLiveStreamDvrRecorderDestroy (ILiveStreamDvrRecorder recorder) Called when recorder destroyed
void	onLiveStreamDvrRecorderInit (ILiveStreamDvrRecorder recorder, String streamName) Called after recorder is initialized

Methods

onLiveStreamDvrRecorderCreate

```
public void onLiveStreamDvrRecorderCreate(ILiveStreamDvrRecorder recorder,  
String streamName)
```

Called when recorder created

Parameters:

recorder - recorder
streamName - stream name

onLiveStreamDvrRecorderInit

```
public void onLiveStreamDvrRecorderInit(ILiveStreamDvrRecorder recorder,  
String streamName)
```

Called after recorder is initialized

Parameters:

recorder - recorder
streamName - stream name

onLiveStreamDvrRecorderDestroy

```
public void onLiveStreamDvrRecorderDestroy(ILiveStreamDvrRecorder recorder)
```

Called when recorder destroyed

(continued from last page)

Parameters:

recorder - recorder

com.wowza.wms.stream.livedvr Interface **ILiveStreamDvrRecorderControl**

public interface **ILiveStreamDvrRecorderControl**
extends

ILiveStreamDvrRecorderControl: interface to control which recorders are run for which streams.
See Also:
[IApplicationInstance.setLiveStreamDvrRecorderControl\(ILiveStreamDvrRecorderControl\)](#)

Method Summary	
boolean	shouldDvrRecord (String recorderName, IMediaStream stream) Returns true if given string should be recorded.;

Methods

shouldDvrRecord

public boolean **shouldDvrRecord**(String recorderName, [IMediaStream](#) stream)

Returns true if given string should be recorded.;

Parameters:

- recorderName - recorder name
- stream - stream

Returns:

true to record

Package

com.wowza.wms.stream.livepacketizer

com.wowza.wms.stream.livepacketizer

Interface ILiveStreamPacketizer

All Subinterfaces:

[IDvrStreamManager](#)

public interface **ILiveStreamPacketizer**

extends

ILiveStreamPacketizer: live stream packetizer interface.

Method Summary

IApplicationInstance	getApplicationInstance() Get the application instance associated with this live stream packetizer.
int	getLiveStreamPacketizerId() Get the live stream packetizer id
WMSProperties	getProperties() Get properties
long	getRepeaterLastSequence() Get the sequence number of the last added repeater item
IMediaStream	getStartStream() Get the current stream that is being packetized
void	handlePacket() (IMediaStream stream, AMFPacket packet) Called to handle an incoming packet
void	init() (String streamName, String packetizerName, IApplicationInstance appInstance, LiveStreamPacketizerItem liveStreamPacketizerItem) Initialize live stream packetizer
boolean	isActive() Is the live stream packetizer active
boolean	isPacketizeAudio() True if audio is being packetized
boolean	isPacketizeData() True if data is being packetized
boolean	isPacketizeVideo() True if video is being packetized
boolean	isRepeaterEdge() Is this packetizer a live repeater edge
void	resetStream() (IMediaStream stream) Called when something happens that forces the stream to reset
void	setLiveStreamPacketizerId() (int id) Set the live stream packetizer id

void	<u>setPacketizeAudio</u> (boolean packetizeAudio) Set to true to packetize audio
void	<u>setPacketizeData</u> (boolean packetizeVideo) Set to true to packetize data
void	<u>setPacketizeVideo</u> (boolean packetizeVideo) Set to true to packetize video
void	<u>setRepeaterEdge</u> (boolean isRepeaterEdge) Set is live repeater edge
void	<u>shutdown</u> () Called to shutdown the live stream packetizer
void	<u>startStream</u> (<u>IMediaStream</u> stream) Called when the stream starts
void	<u>touch</u> (long timecode) Touch the stream to keep it active

Methods

init

```
public void init(String streamName,
String packetizerName,
IApplicationInstance appInstance,
LiveStreamPacketizerItem liveStreamPacketizerItem)
```

Initialize live stream packetizer

Parameters:

streamName - stream name
packetizerName - packetizer name
appInstance - application instance
liveStreamPacketizerItem - live stream packetizer

shutdown

```
public void shutdown( )
```

Called to shutdown the live stream packetizer

isActive

```
public boolean isActive( )
```

Is the live stream packetizer active

Returns:

true if active

getProperties

```
public WMSProperties getProperties( )
```

(continued from last page)

Get properties

Returns:
properties

getRepeaterLastSequence

```
public long getRepeaterLastSequence()
```

Get the sequence number of the last added repeater item

Returns:
sequence number

getLiveStreamPacketizerId

```
public int getLiveStreamPacketizerId()
```

Get the live stream packetizer id

Returns:
live stream packetizer id

setLiveStreamPacketizerId

```
public void setLiveStreamPacketizerId(int id)
```

Set the live stream packetizer id

Parameters:
id

handlePacket

```
public void handlePacket(IMediaStream stream,  
    AMFPacket packet)
```

Called to handle an incoming packet

Parameters:
stream - stream
packet - packet

startStream

```
public void startStream(IMediaStream stream)
```

Called when the stream starts

Parameters:
stream - stream

resetStream

```
public void resetStream(IMediaStream stream)
```

Called when something happens that forces the stream to reset

Parameters:

(continued from last page)

stream - stream

touch

```
public void touch(long timecode)
```

Touch the stream to keep it active

Parameters:

timecode - timecode of touch in milliseconds

isRepeaterEdge

```
public boolean isRepeaterEdge()
```

Is this packetizer a live repeater edge

Returns:

true if live repeater edge

setRepeaterEdge

```
public void setRepeaterEdge(boolean isRepeaterEdge)
```

Set is live repeater edge

Parameters:

isRepeaterEdge - is live repeater edge

isPacketizeAudio

```
public boolean isPacketizeAudio()
```

True if audio is being packetized

Returns:

True if audio is being packetized

setPacketizeAudio

```
public void setPacketizeAudio(boolean packetizeAudio)
```

Set to true to packetize audio

Parameters:

packetizeAudio - true to packetize audio

isPacketizeVideo

```
public boolean isPacketizeVideo()
```

True if video is being packetized

Returns:

True if video is being packetized

(continued from last page)

setPacketizeVideo

```
public void setPacketizeVideo(boolean packetizeVideo)
```

Set to true to packetize video

Parameters:

packetizeVideo - true to packetize video

isPacketizeData

```
public boolean isPacketizeData()
```

True if data is being packetized

Returns:

True if data is being packetized

setPacketizeData

```
public void setPacketizeData(boolean packetizeVideo)
```

Set to true to packetize data

Parameters:

packetizeVideo - true to packetize data

getStartStream

```
public IMediaStream getStartStream()
```

Get the current stream that is being packetized

Returns:

stream

getApplicationInstance

```
public IApplicationInstance getApplicationInstance()
```

Get the application instance associated with this live stream packetizer.

Returns:

application instance

com.wowza.wms.stream.livepacketizer Interface **ILiveStreamPacketizerActionNotify**

public interface **ILiveStreamPacketizerActionNotify**
extends

ILiveStreamPacketizerActionNotify: notify interface for live stream packetizers. See
IApplicationInstance.addLiveStreamPacketizerListener(ILiveStreamPacketizerActionNotify liveStreamPacketizerListener)

Method Summary

void	onLiveStreamPacketizerCreate (ILiveStreamPacketizer liveStreamPacketizer, String streamName) Called when packetizer created
void	onLiveStreamPacketizerDestroy (ILiveStreamPacketizer liveStreamPacketizer) Called when packetizer destroyed
void	onLiveStreamPacketizerInit (ILiveStreamPacketizer liveStreamPacketizer, String streamName) Called after packetizer is initialized

Methods

onLiveStreamPacketizerCreate

```
public void onLiveStreamPacketizerCreate(ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Called when packetizer created

Parameters:

liveStreamPacketizer - packetizer
streamName - stream name

onLiveStreamPacketizerDestroy

```
public void onLiveStreamPacketizerDestroy(ILiveStreamPacketizer liveStreamPacketizer)
```

Called when packetizer destroyed

Parameters:

liveStreamPacketizer - packetizer

onLiveStreamPacketizerInit

```
public void onLiveStreamPacketizerInit(ILiveStreamPacketizer liveStreamPacketizer,  
String streamName)
```

Called after packetizer is initialized

Parameters:

(continued from last page)

liveStreamPacketizer - packetizer
streamName - stream name

com.wowza.wms.stream.livepacketizer Interface ILiveStreamPacketizerControl

public interface **ILiveStreamPacketizerControl**
extends

ILiveStreamPacketizerControl: interface to control which packetizers are run for which streams. See:
IApplicationInstance.setLiveStreamPacketizerControl(ILiveStreamPacketizerControl liveStreamPacketizerControl)

Method Summary

boolean	isLiveStreamPacketize (String packetizer, IMediaStream stream) Return true to packetize stream
---------	-----------------------------------------------------------------------------------------------------------------------------------

Methods

isLiveStreamPacketize

public boolean **isLiveStreamPacketize**(String packetizer,
[IMediaStream](#) stream)

Return true to packetize stream

Parameters:

packetizer - packetizer name
stream - stream

Returns:

true to packetize

Package

com.wowza.wms.stream.livetranscoder

com.wowza.wms.stream.livetranscoder

Interface ILiveStreamTranscoder

public interface **ILiveStreamTranscoder**
 extends

ILiveStreamTranscoder: Interface to live stream transcoder.

Method Summary

void	<code>close()</code> (<code>IMediaStream</code> stream) Called when live stream transcoder is stream is closed
<code>IApplicationInstance</code>	<code>getAppInstance()</code> Get the application instance associated with this live stream transcoder.
LicenseHolder	<code>getLicenseHolder()</code> Get license holder.
LiveStreamTranscoderItem	<code>getLiveStreamTranscoderItem()</code> Get the definition for live stream transcoder.
<code>WMSProperties</code>	<code>getProperties()</code> Get the user properties
String	<code>getStreamName()</code> Get the stream name of the source stream.
String	<code>getTranscoderName()</code> Get the live stream transcoder name
void	<code>handleOnMetadata()</code> (<code>IMediaStream</code> stream, <code>AMFPacket</code> packet, long timecode, boolean isSetDataFrame) Called for each new onMetaData packet
void	<code>handlePacket()</code> (<code>IMediaStream</code> stream, <code>AMFPacket</code> packet) Called for each new source packet
void	<code>init()</code> (String streamName, String transcoderName, <code>IApplicationInstance</code> appInstance, LiveStreamTranscoderItem liveStreamTranscoderItem) Called when live stream transcoder interface is initialized.
void	<code>resetStream()</code> (<code>IMediaStream</code> stream) Called when source stream changes.
void	<code>setAppInstance()</code> (<code>IApplicationInstance</code> appInstance) Set the application instance associated with this live stream transcoder.
void	<code>setLiveStreamTranscoderItem()</code> (LiveStreamTranscoderItem liveStreamTranscoderItem) Set the definition for live stream transcoder.
void	<code>setStreamName()</code> (String streamName) Set source stream name.

void	setTranscoderName (String transcoderName) Get the live stream transcoder name
void	shutdown (IMediaStream stream) Called when live stream transcoder is shutdown

Methods

init

```
public void init(String streamName,  
                String transcoderName,  
                IApplicationInstance appInstance,  
                LiveStreamTranscoderItem liveStreamTranscoderItem)
```

Called when live stream transcoder interface is initialized.

Parameters:

streamName - stream name
transcoderName - transcoder name
appInstance - application instance
liveStreamTranscoderItem - live stream transcoder config item

handlePacket

```
public void handlePacket(IMediaStream stream,  
                        AMFPacket packet)
```

Called for each new source packet

Parameters:

stream - stream
packet - packet

handleOnMetadata

```
public void handleOnMetadata(IMediaStream stream,  
                            AMFPacket packet,  
                            long timecode,  
                            boolean isSetDataFrame)
```

Called for each new onMetaData packet

Parameters:

stream - stream
packet - packet
timecode - timecode (milliseconds)
isSetDataFrame - is SetDataFrame call

resetStream

```
public void resetStream(IMediaStream stream)
```

Called when source stream changes.

Parameters:

stream - stream interface

close

```
public void close(IMediaStream stream)
```

Called when live stream transcoder is stream is closed

Parameters:

stream - stream interface

shutdown

```
public void shutdown(IMediaStream stream)
```

Called when live stream transcoder is shutdown

Parameters:

stream - stream interface

getStreamName

```
public String getStreamName()
```

Get the stream name of the source stream.

Returns:

stream name of the source stream

setStreamName

```
public void setStreamName(String streamName)
```

Set source stream name.

Parameters:

streamName - source stream name

getTranscoderName

```
public String getTranscoderName()
```

Get the live stream transcoder name

Returns:

live stream transcoder name

setTranscoderName

```
public void setTranscoderName(String transcoderName)
```

Get the live stream transcoder name

Parameters:

transcoderName - live stream transcoder name

getAppInstance

```
public IApplicationInstance getAppInstance()
```

(continued from last page)

Get the application instance associated with this live stream transcoder.

Returns:

application instance associated with this live stream transcoder

setAppInstance

```
public void setAppInstance(IApplicationInstance appInstance)
```

Set the application instance associated with this live stream transcoder.

Parameters:

appInstance - application instance associated with this live stream transcoder

getLiveStreamTranscoderItem

```
public LiveStreamTranscoderItem getLiveStreamTranscoderItem()
```

Get the definition for live stream transcoder.

Returns:

definition for live stream transcoder

setLiveStreamTranscoderItem

```
public void setLiveStreamTranscoderItem(LiveStreamTranscoderItem  
liveStreamTranscoderItem)
```

Set the definition for live stream transcoder.

Parameters:

liveStreamTranscoderItem - definition for live stream transcoder

getProperties

```
public WMSProperties getProperties()
```

Get the user properties

Returns:

user properties

getLicenseHolder

```
public LicenseHolder getLicenseHolder()
```

Get license holder.

Returns:

license holder

com.wowza.wms.stream.livetranscoder Interface **ILiveStreamTranscoderControl**

public interface **ILiveStreamTranscoderControl**
extends

Interface used to control if stream is transcoded. See
`IApplicationInstance.setLiveStreamTranscoderControl(ILiveStreamTranscoderControl)`

Method Summary

boolean	<code>isLiveStreamTranscode</code> (String transcoder, <code>IMediaStream</code> stream) Called each time a new publishing stream is started.
---------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Methods

isLiveStreamTranscode

```
public boolean isLiveStreamTranscode(String transcoder,  
    IMediaStream stream)
```

Called each time a new publishing stream is started. Return true if you wish stream to be transcoded. See
`IApplicationInstance.setLiveStreamTranscoderControl(ILiveStreamTranscoderControl)`

Parameters:

transcoder - name of transcoder
stream - stream interface

Returns:

true if wish stream to be transcoded

com.wowza.wms.stream.livetranscoder Interface **ILiveStreamTranscoderNotify**

public interface **ILiveStreamTranscoderNotify**
extends

ILiveStreamTranscoderNotify: Listener interface for listening for new live stream transcoders. See
IApplicationInstance.addLiveStreamTranscoderListener(ILiveStreamTranscoderNotify)

Method Summary

void	onLiveStreamTranscoderCreate (ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream) Triggered when live stream transcoder is created.
void	onLiveStreamTranscoderDestroy (ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream) Triggered when live stream transcoder is destroyed.
void	onLiveStreamTranscoderInit (ILiveStreamTranscoder liveStreamTranscoder, IMediaStream stream) Triggered after live stream transcoder is initialized.

Methods

onLiveStreamTranscoderCreate

```
public void onLiveStreamTranscoderCreate(ILiveStreamTranscoder liveStreamTranscoder,  
    IMediaStream stream)
```

Triggered when live stream transcoder is created.

Parameters:

liveStreamTranscoder - live stream transcoder
stream - source stream

onLiveStreamTranscoderDestroy

```
public void onLiveStreamTranscoderDestroy(ILiveStreamTranscoder liveStreamTranscoder,  
    IMediaStream stream)
```

Triggered when live stream transcoder is destroyed.

Parameters:

liveStreamTranscoder - live stream transcoder
stream - source stream

onLiveStreamTranscoderInit

```
public void onLiveStreamTranscoderInit(ILiveStreamTranscoder liveStreamTranscoder,  
    IMediaStream stream)
```

Triggered after live stream transcoder is initialized.

(continued from last page)

Parameters:

liveStreamTranscoder - live stream transcoder

stream - source stream

Package

com.wowza.wms.stream.publish

com.wowza.wms.stream.publish Interface IPublishingProvider

All Known Implementing Classes:

[PublishingProviderMediaReader](#), [PublishingProviderLive](#)

public interface **IPublishingProvider**
extends

IPublishingProvider: publishing provider interface.

Method Summary

void	close() Invoked on stream close
boolean	isSendOnMetadata() Get to send onMetadata event when stream starts
boolean	play(Publisher publisher) Invoked on play
boolean	seek(long timecode) Invoked on seek
boolean	seek(long timecode, int seekType) Invoked on seek
void	setDuration(long duration) Set target duration for playback (milliseconds)
void	setRealTimeStartTime(long realTimeStartTime) Set real start time (milliseconds)
void	setSendOnMetadata(boolean sendOnMetadata) Set to send onMetadata event when stream starts

Methods

play

public boolean **play**([Publisher](#) publisher)

Invoked on play

Parameters:

publisher - publisher

Returns:

true if successful

(continued from last page)

close

```
public void close()
```

Invoked on stream close

seek

```
public boolean seek(long timecode,  
                    int seekType)
```

Invoked on seek

Parameters:

timecode - target timecode

seekType - seek type, see IMediaReader.SEEKTARGET_*

Returns:

true, if seek successful

seek

```
public boolean seek(long timecode)
```

Invoked on seek

Parameters:

timecode - target timecode

Returns:

true, if seek successful

setDuration

```
public void setDuration(long duration)
```

Set target duration for playback (milliseconds)

Parameters:

duration - duration for playback (milliseconds)

setRealTimeStartTime

```
public void setRealTimeStartTime(long realTimeStartTime)
```

Set real start time (milliseconds)

Parameters:

realTimeStartTime - real start time (milliseconds)

setSendOnMetadata

```
public void setSendOnMetadata(boolean sendOnMetadata)
```

Set to send onMetadata event when stream starts

Parameters:

sendOnMetadata - true to send onMetadata event

isSendOnMetadata

```
public boolean isSendOnMetadata()
```

Get to send onMetadata event when stream starts

Returns:

true to send onMetadata event

com.wowza.wms.stream.publish Interface IStreamActionNotify

public interface **IStreamActionNotify**
extends

IStreamActionNotify: listener interface to Stream class for playlist items. See Stream.addListener(IStreamActionNotify listener)

Method Summary

void	onPlaylistItemStart (Stream stream, PlaylistItem playlistItem) Invoked when playlist item playback is started
void	onPlaylistItemStop (Stream stream, PlaylistItem playlistItem) Invoked when playlist item playback has ended

Methods

onPlaylistItemStart

```
public void onPlaylistItemStart(Stream stream,  
    PlaylistItem playlistItem)
```

Invoked when playlist item playback is started

Parameters:

stream - stream

playlistItem - playlist item

onPlaylistItemStop

```
public void onPlaylistItemStop(Stream stream,  
    PlaylistItem playlistItem)
```

Invoked when playlist item playback has ended

Parameters:

stream - stream

playlistItem - playlist item

com.wowza.wms.stream.publish Class Playlist

java.lang.Object

└─com.wowza.wms.stream.publish.Playlist

public class **Playlist**
extends Object

Constructor Summary

public	Playlist (String sName) Class constructor - A simple structure that maintains a list of playlist items.
--------	----------------------------------------------------------------------------------------------------------------------------

Method Summary

void	addItem (String sName, int start, int length) Appends an item to this playlist
java.util.List	getItems () Get the items in the playlist (returns a copy of the list)
String	getName () Returns the name of this playlist as defined in the XML definition file
boolean	getRepeat ()
boolean	open (Stream s) Opens this playlist on the given stream...
void	removeItem (int index) Remove an item from the list
void	setRepeat (boolean repeat)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

Playlist

public **Playlist**(String sName)

Class constructor - A simple structure that maintains a list of playlist items.

Parameters:

sName -- name of playlist - as defined in the XML definition file

Methods

getItems

```
public java.util.List getItems()
```

Get the items in the playlist (returns a copy of the list)

Returns:

items in the playlist (returns a copy of the list)

getRepeat

```
public boolean getRepeat()
```

setRepeat

```
public void setRepeat(boolean repeat)
```

addItem

```
public void addItem(String sName,  
                    int start,  
                    int length)
```

Appends an item to this playlist

Parameters:

sName - - item name

start - - start seconds

length - - playlength seconds

removeItem

```
public void removeItem(int index)
```

Remove an item from the list

Parameters:

index - index of item to remove

open

```
public boolean open(Stream s)
```

Opens this playlist on the given stream... stopping anything currently playing on that stream and switching over.

Parameters:

s - - stream to play on

Returns:

- true if successful

getName

```
public String getName()
```

Returns the name of this playlist as defined in the XML definition file

Returns:

name of this playlist

com.wowza.wms.stream.publish Class PlaylistItem

java.lang.Object

└─com.wowza.wms.stream.publish.PlaylistItem

public class **PlaylistItem**
extends Object

Constructor Summary

public	PlaylistItem (String name, int start, int length, int index) Class constructor - A simple structure to define parameters associated with a playlist item
--------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Method Summary

int	getIndex ()
int	getLength () Number of seconds of track to play
String	getName () Name of playlist stream
int	getStart () Number of seconds into track to start from
void	setIndex (int index)
String	toString ()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

PlaylistItem

```
public PlaylistItem(String name,
                    int start,
                    int length,
                    int index)
```

Class constructor - A simple structure to define parameters associated with a playlist item

Parameters:

name - - name of the playlist stream

start - - number of seconds into the track to start from (-2 means live stream)

(continued from last page)

length -- number of seconds of track to play

index -- index in the playlist

Methods

getName

```
public String getName()
```

Name of playlist stream

Returns:- name of stream

getStart

```
public int getStart()
```

Number of seconds into track to start from

Returns:- number of seconds

getLength

```
public int getLength()
```

Number of seconds of track to play

Returns:- number of seconds

getIndex

```
public int getIndex()
```

setIndex

```
public void setIndex(int index)
```

toString

```
public String toString()
```

com.wowza.wms.stream.publish Class Publisher

java.lang.Object

└─com.wowza.wms.stream.publish.Publisher

```
public class Publisher  
extends Object
```

Publisher: clientless stream publisher. This class can be used to publish raw video, audio and metadata packets to the Wowza Pro server. Here is a quick snippet of code that illustrates how to use it.

This code below will publish data the stream named "myStream". It will be streamed to the default virtual host and available at the rtmp address rtmp://[server-ip-address]/streamtest.

```
IVHost vhost = VHostSingleton.getInstance(VHost.VHOST_DEFAULT);
Publisher publisher = Publisher.createInstance(vhost, "streamtest");

publisher.setFileExtension("flv");
publisher.setStreamType("live");

publisher.publish("myStream", "live");

// sit in a loop adding data
boolean done = false;
while(true)
{
    AMFPacket amfPacket;

    // read packet from audio, video, data source
    // amfPacket = readPacketFromSomewhere();

    switch (amfPacket.getType())
    {
        case IVHost.CONTENTTYPE_AUDIO:
            publisher.addAudioData(amfPacket.getData(), amfPacket.getSize(),
amfPacket.getTimecode());
            break;
        case IVHost.CONTENTTYPE_VIDEO:
            publisher.addVideoData(amfPacket.getData(), amfPacket.getSize(),
amfPacket.getTimecode());
            break;
        case IVHost.CONTENTTYPE_DATA:
            publisher.addDataData(amfPacket.getData(), amfPacket.getSize(),
amfPacket.getTimecode());
            break;
    }
    if (done)
        break;
}

publisher.unpublish();
publisher.close();
```

Basic packet format:

Audio:

AAC

[1-byte header]

[1-byte codec config indicator (1 - audio data, 0 - codec config packet)]

[n-bytes audio content or codec config data]

All others

[1-byte header]

[n-bytes audio content]

Below is the bit

layout of the header byte of data (table goes from least significant bit to most significant bit):

1 bit Number of channels:

- 0 mono
- 1 stereo

1 bit Sample size:

- 0 8 bits per sample
- 1 16 bits per sample

2 bits Sample rate:

- 0 special or 8KHz
- 1 11KHz
- 2 22KHz
- 3 44KHz

4 bits Audio type:

- 0 PCM (big endian)
- 1 PCM (swf - ADPCM)
- 2 MP3
- 3 PCM (little endian)
- 4 Nelly Moser ASAO 16KHz Mono
- 5 Nelly Moser ASAO 8KHz Mono
- 6 Nelly Moser ASAO
- 7 G.711 ALaw
- 8 G.711 MULaw
- 9 Reserved
- a AAC
- b Speex
- f MP3 8Khz

Note: For AAC the codec config data is generally a two byte packet that describes the stream. It must

be published first. Here is the basic code to fill in the codec config data.

```
AACFrame frame = new AACFrame();
```



```

int sampleRate = 22100;
int channels = 2;
frame.setSampleRate(sampleRate);
frame.setRateIndex(AACUtils.sampleRateToIndex(sampleRate));
frame.setChannels(channels);
frame.setChannelIndex(AACUtils.channelCountToIndex(sampleRate));
byte[] codecConfig = new byte[2];
AACUtils.encodeAACCodecConfig(frame, codecConfig, 0);

```

Note: For AAC the header byte is always 0xaf

Note: For Speex the audio data must be encoded as 16000Hz wide band

Video:

H.264

```

[1-byte header]
[1-byte codec config indicator (1 - video data, 0 - codec config packet)]
[3-byte time difference between dts and pts in milliseconds]
[n-bytes video content or codec config data]

```

All others

```

[1-byte header]
[n-bytes audio content]

```

Below is the bit layout of the header byte of data (table goes from least significant bit to most significant bit):

4 bits Video type:

2	Sorenson Spark (H.263)
3	Screen
4	On2 VP6
5	On2 VP6A
6	Screen2
7	H.264

2 bit Frame type:

1	K frame (key frame)
2	P frame
3	B frame

Note: H.264 codec config data is the same as the AVCc packet in a QuickTime container.

Note: All timecode data is in milliseconds

Method Summary

void	addAudioData (byte[] data, int offset, int len, long timecode) Add audio data
void	addAudioData (byte[] data, int len, long timecode) Add audio data
void	addAudioData (byte[] data, long timecode) Add audio data
void	addAudioDataInc (byte[] data, int offset, int len)
void	addDataData (byte[] data, int offset, int len, long timecode) Add metadata
void	addDataData (byte[] data, int len, long timecode) Add metadata
void	addDataData (byte[] data, long timecode) Add metadata
void	addDataDataInc (byte[] data, int offset, int len)
void	addVideoData (byte[] data, int offset, int len, long timecode) Add video data
void	addVideoData (byte[] data, int len, long timecode) Add video data
void	addVideoData (byte[] data, long timecode) Add video data
void	addVideoDataInc (byte[] data, int offset, int len)
void	close () Close the publisher
static Publisher	createInstance (IApplicationInstance appInstance)
static Publisher	createInstance (IVHost vhost, String applicationName)
static Publisher	createInstance (IVHost vhost, String applicationName, String appInstanceName)
void	flush () Flush the packets from the input buffer to the output buffer
IApplicationInstance	getAppInstance ()
String	getFileExtension () Get the file extension (default flv)
long	getLastAudioTimecode () Get last audio timecode written through this publisher (milliseconds).
long	getLastDataTimecode () Get last data timecode written through this publisher (milliseconds).

long	getLastVideoTimecode() Get last video timecode written through this publisher (milliseconds).
long	getMaxTimecode() Highest timecode written through this publisher (milliseconds).
IMediaStream	getStream() Get the media stream object
String	getStreamType()
void	publish(String streamName) Publish a stream (null to stop publishing)
void	publish(String streamName, String howToPublish) Start publishing a stream (streamName = null to stop).
void	setFileExtension(String fileExtension) Set the file extension
void	setStream(IMediaStream stream) Set the media stream object
void	setStreamType(String streamType) Set the stream type (default live)
void	startAudioData(int len, long timecode)
void	startDataData(int len, long timecode)
void	startVideoData(int len, long timecode)
void	unpublish()

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods

createInstance

```
public static Publisher createInstance(IVHost vhost,
    String applicationName)
```

createInstance

```
public static Publisher createInstance(IVHost vhost,
    String applicationName,
    String appInstanceName)
```

createInstance

```
public static Publisher createInstance(IApplicationInstance appInstance)
```

getStream

```
public IMediaStream getStream()
```

Get the media stream object

Returns:

media stream object

setStream

```
public void setStream(IMediaStream stream)
```

Set the media stream object

Parameters:

stream - media stream object

getStreamType

```
public String getStreamType()
```

setStreamType

```
public void setStreamType(String streamType)
```

Set the stream type (default live)

Parameters:

streamType - stream type

publish

```
public void publish(String streamName)
```

Publish a stream (null to stop publishing)

Parameters:

streamName - stream name

getFileExtension

```
public String getFileExtension()
```

Get the file extension (default flv)

Returns:

file extension

setFileExtension

```
public void setFileExtension(String fileExtension)
```

Set the file extension

Parameters:

fileExtension - file extension

getAppInstance

```
public IApplicationInstance getAppInstance()
```

unpublish

```
public void unpublish()
```

publish

```
public void publish(String streamName,  
                    String howToPublish)
```

Start publishing a stream (streamName = null to stop). Valid howToPublish values are (live, record, append)

Parameters:

streamName - stream name

howToPublish - publish method (live, record, append)

addVideoData

```
public void addVideoData(byte[] data,  
                          long timecode)
```

Add video data

Parameters:

data - data

timecode - absolute timecode (milliseconds)

addVideoData

```
public void addVideoData(byte[] data,  
                          int len,  
                          long timecode)
```

Add video data

Parameters:

data - data

len - data length

timecode - absolute timecode (milliseconds)

(continued from last page)

addVideoData

```
public void addVideoData(byte[] data,  
    int offset,  
    int len,  
    long timecode)
```

Add video data

Parameters:

data - data
offset - offset
len - data length
timecode - absolute timecode (milliseconds)

startVideoData

```
public void startVideoData(int len,  
    long timecode)
```

addVideoDataInc

```
public void addVideoDataInc(byte[] data,  
    int offset,  
    int len)
```

startAudioData

```
public void startAudioData(int len,  
    long timecode)
```

addAudioDataInc

```
public void addAudioDataInc(byte[] data,  
    int offset,  
    int len)
```

addAudioData

```
public void addAudioData(byte[] data,  
    long timecode)
```

Add audio data

Parameters:

data - data
timecode - absolute timecode (milliseconds)

(continued from last page)

addAudioData

```
public void addAudioData(byte[] data,  
    int len,  
    long timecode)
```

Add audio data

Parameters:

data - data
len - data length
timecode - absolute timecode (milliseconds)

addAudioData

```
public void addAudioData(byte[] data,  
    int offset,  
    int len,  
    long timecode)
```

Add audio data

Parameters:

data - data
len - data length
offset - offset
timecode - absolute timecode (milliseconds)

addDataData

```
public void addDataData(byte[] data,  
    long timecode)
```

Add metadata

Parameters:

data - data
timecode - absolute timecode (milliseconds)

addDataData

```
public void addDataData(byte[] data,  
    int len,  
    long timecode)
```

Add metadata

Parameters:

data - data
len - data length
timecode - absolute timecode (milliseconds)

addDataData

```
public void addDataData(byte[] data,  
    int offset,  
    int len,  
    long timecode)
```

Add metadata

(continued from last page)

Parameters:

data - data
offset - offset
len - data length
timecode - absolute timecode (milliseconds)

startDataData

```
public void startDataData(int len,  
    long timecode)
```

addDataDataInc

```
public void addDataDataInc(byte[] data,  
    int offset,  
    int len)
```

flush

```
public void flush()
```

Flush the packets from the input buffer to the output buffer

close

```
public void close()
```

Close the publisher

getMaxTimecode

```
public long getMaxTimecode()
```

Highest timecode written through this publisher (milliseconds).

Returns:

highest timecode written through this publisher (milliseconds)

getLastAudioTimecode

```
public long getLastAudioTimecode()
```

Get last audio timecode written through this publisher (milliseconds).

Returns:

last audio timecode written through this publisher (milliseconds).

getLastVideoTimecode

```
public long getLastVideoTimecode()
```

Get last video timecode written through this publisher (milliseconds).

Returns:

(continued from last page)

last video timecode written through this publisher (milliseconds).

getLastDataTimecode

```
public long getLastDataTimecode( )
```

Get last data timecode written through this publisher (milliseconds).

Returns:

last data timecode written through this publisher (milliseconds).

com.wowza.wms.stream.publish Class PublishingProviderBase

java.lang.Object

└--com.wowza.wms.stream.publish.PublishingProviderBase

Direct Known Subclasses:

[PublishingProviderMediaReader](#), [PublishingProviderLive](#)

```
public class PublishingProviderBase
extends Object
```

PublishingProviderBase: Base class for publishing providers.

Field Summary

protected	sendOnMetadata
-----------	--------------------------------

Constructor Summary

public	PublishingProviderBase()
--------	------------------------------------------

Method Summary

boolean	isSendOnMetadata() True to send onMetadata event on stream start
void	setSendOnMetadata (boolean sendOnMetadata) True to send onMetadata event on stream start

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Fields

sendOnMetadata

protected boolean **sendOnMetadata**

Constructors

PublishingProviderBase

```
public PublishingProviderBase()
```

(continued from last page)

Methods

isSendOnMetadata

```
public boolean isSendOnMetadata()
```

True to send onMetadata event on stream start

Returns:

True to send onMetadata event on stream start

setSendOnMetadata

```
public void setSendOnMetadata(boolean sendOnMetadata)
```


True to send onMetadata event on stream start

Parameters:

sendOnMetadata - True to send onMetadata event on stream start

com.wowza.wms.stream.publish Class PublishingProviderLive

java.lang.Object



All Implemented Interfaces:
[IPublishingProvider](#)

public class **PublishingProviderLive**
extends [PublishingProviderBase](#)
implements [IPublishingProvider](#)

Fields inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[sendOnMetadata](#)

Constructor Summary

public	PublishingProviderLive (Publisher publisher, long timeoffset, String streamName)
--------	-------------------------------------------------------------------------------------------------------------------

Method Summary

void	close ()
------	--------------------------

long	getDuration ()
------	--------------------------------

boolean	play (Publisher publisher)
---------	-------------------------------------------------------------

boolean	seek (long timecode)
---------	--------------------------------------

boolean	seek (long timecode, int seekType)
---------	----------------------------------------------------

void	setDuration (long duration)
------	---------------------------------------------

void	setRealTimeStartTime (long realTimeStartTime)
------	---------------------------------------------------------------

Methods inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[isSendOnMetadata](#), [setSendOnMetadata](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.stream.publish.IPublishingProvider](#)

[close](#), [isSendOnMetadata](#), [play](#), [seek](#), [seek](#), [setDuration](#), [setRealTimeStartTime](#), [setSendOnMetadata](#)

Constructors

PublishingProviderLive

```
public PublishingProviderLive(Publisher publisher,  
                             long timeoffset,  
                             String streamName)
```

Methods

close

```
public void close()
```

play

```
public boolean play(Publisher publisher)
```

seek

```
public boolean seek(long timecode)
```

seek

```
public boolean seek(long timecode,  
                    int seekType)
```

getDuration

```
public long getDuration()
```

setDuration

```
public void setDuration(long duration)
```


(continued from last page)

setRealTimeStartTime

```
public void setRealTimeStartTime(long realTimeStartTime)
```

com.wowza.wms.stream.publish Class PublishingProviderMediaReader

java.lang.Object



All Implemented Interfaces:

[IPublishingProvider](#)

public class **PublishingProviderMediaReader**

extends [PublishingProviderBase](#)

implements [IPublishingProvider](#)

PublishingProviderMediaReader: Publishing provider for media reader based stream (vod).

Fields inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[sendOnMetadata](#)

Constructor Summary

public	PublishingProviderMediaReader (Publisher publisher, long timeoffset, String streamName) Constructor
--------	-----------------------------------------------------------------------------------------------------------------------------------------

Method Summary

void	close ()
long	getDuration () Get the target playback duration (milliseconds)
boolean	play (Publisher publisher)
boolean	seek (long timecode)
boolean	seek (long timecode, int seekType)
void	setDuration (long duration)
void	setRealTimeStartTime (long realTimeStartTime)

Methods inherited from class [com.wowza.wms.stream.publish.PublishingProviderBase](#)

[isSendOnMetadata](#), [setSendOnMetadata](#)

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Methods inherited from interface [com.wowza.wms.stream.publish.IPublishingProvider](#)

[close](#), [isSendOnMetadata](#), [play](#), [seek](#), [seek](#), [setDuration](#), [setRealTimeStartTime](#), [setSendOnMetadata](#)

Constructors

PublishingProviderMediaReader

```
public PublishingProviderMediaReader(Publisher publisher,  
                                   long timeoffset,  
                                   String streamName)
```

Constructor

Parameters:

`publisher` - publisher
`timeoffset` - timeoffset (milliseconds)
`streamName` - stream name

Methods

seek

```
public boolean seek(long timecode)
```

seek

```
public boolean seek(long timecode,  
                   int seekType)
```

play

```
public boolean play(Publisher publisher)
```

close

```
public void close()
```

getDuration

```
public long getDuration()
```

Get the target playback duration (milliseconds)

(continued from last page)

Returns:

playback duration (milliseconds)

setDuration

```
public void setDuration(long duration)
```

setRealTimeStartTime

```
public void setRealTimeStartTime(long realTimeStartTime)
```

com.wowza.wms.stream.publish Class Stream

java.lang.Object

└─com.wowza.wms.stream.publish.Stream

All Implemented Interfaces:

Runnable

public class **Stream**
extends Object
implements Runnable

Constructor Summary

public	Stream()
--------	--------------------------

Method Summary

void	addListener(IStreamActionNotify listener) Add a listener
boolean	addToPlaylist(int index, String name, int start, int length) Inserts a media source item to this playlist at a particular index, without interruption.
boolean	addToPlaylist(String existing, String name, int start, int length) Insert item into playlist just after the first item in the playlist with a given name.
void	close() Call this method when you have finished with the playlist object.
void	closeAndWait() Call this method when you have finished with the playlist object.
static Stream	createInstance(IApplicationInstance appInstance, String sName) Use this to create a named Stream on an application instance.
static Stream	createInstance(IVHost vhost, String applicationName, String sName) Use this to create a named Stream on the default instance (_definst_) of an application on a particular VHost.
static Stream	createInstance(IVHost vhost, String applicationName, String appInstanceName, String sName) Use this to create a named Stream on the non-default instance of an application on a particular VHost.
PlaylistItem	getCurrentItem() Get the currently playing playlist item
Object	getLock() Get the synchronization lock for this interface.

String	<u>getName()</u> Returns the name of the playlist stream - the client would play this stream by this name.
java.util.List	<u>getPlaylist()</u> Get the current playlist
int	<u>getPollingInterval()</u> Get the polling interval (milliseconds)
<u>Publisher</u>	<u>getPublisher()</u>
boolean	<u>getRepeat()</u> Use this to determine if the playlist is auto-repeating
boolean	<u>isSendOnMetadata()</u> True if sending onMetadata events
boolean	<u>isSwitchLog()</u> Log when a playlist switch occurs
void	<u>next()</u>
void	<u>next(int n)</u>
void	<u>play(int n)</u>
boolean	<u>play(String sPlaylist)</u> Add a media item to the playlist as defined by an XML file ..
boolean	<u>play(String name, int start, int length, boolean reset)</u> Adds a media source item to this playlist -
void	<u>previous()</u>
void	<u>previous(int n)</u>
boolean	<u>removeFromPlaylist(String name)</u> Remove all items matching the given stream name from the playlist.
void	<u>removeListener(IStreamActionNotify listener)</u> Remove a listener
void	<u>run()</u> Overridden from class Runnable
void	<u>setPollingInterval(int pollingInterval)</u> Set the polling interval (milliseconds)
void	<u>setRepeat(boolean repeat)</u> Use this to make the playlist repeat or not...
void	<u>setSendOnMetadata(boolean sendOnMetadata)</u> True if sending onMetadata events
void	<u>setSwitchLog(boolean switchLog)</u> Log when a playlist switch occurs

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Methods inherited from interface `java.lang.Runnable`

`run`

Constructors

Stream

```
public Stream()
```

Methods

createInstance

```
public static Stream createInstance(IVHost vhost,  
    String applicationName,  
    String sName)
```

Use this to create a named Stream on the default instance (`_definst_`) of an application on a particular VHost.

Parameters:

`vhost` -- Virtual Host
`applicationName` -- Application name
`sName` -- Name of Stream

Returns:

stream interface

createInstance

```
public static Stream createInstance(IVHost vhost,  
    String applicationName,  
    String appInstanceName,  
    String sName)
```

Use this to create a named Stream on the non-default instance of an application on a particular VHost.

Parameters:

`vhost` -- Virtual Host
`applicationName` -- Application name
`appInstanceName` -- Instance name
`sName` -- Name of Stream

Returns:

stream interface

getLock

```
public Object getLock()
```

(continued from last page)

Get the synchronization lock for this interface.

Returns:

synchronization lock for this interface

createInstance

```
public static Stream createInstance(IApplicationInstance appInstance,  
    String sName)
```

Use this to create a named Stream on an application instance.

Parameters:

appInstance - - Application instance

sName - - Name of Stream

Returns:

stream interface

run

```
public void run()
```

Overridden from class Runnable do NOT call this directly. This method handles switching between media sources in the playlist.

getPlaylist

```
public java.util.List getPlaylist()
```

Get the current playlist

Returns:

current playlist

getCurrentItem

```
public PlaylistItem getCurrentItem()
```

Get the currently playing playlist item

Returns:

currently playing playlist item

play

```
public boolean play(String name,  
    int start,  
    int length,  
    boolean reset)
```

Adds a media source item to this playlist -

Parameters:

name - - name of media item

start - - where to start playing the item. (-2 implies play a live stream)

length - - how much of the item to play (-1 implies play the entire file or live stream)

reset - - if true, will begin a new playlist, otherwise items are appended

(continued from last page)

Returns:

- returns true if item was added successfully ...otherwise false.

addToPlaylist

```
public boolean addToPlaylist(int index,  
    String name,  
    int start,  
    int length)
```

Inserts a media source item to this playlist at a particular index, without interruption.

Parameters:

index - - insertion index
name - - name of media item being inserted
start - - where to start playing the item. (-2 implies play a live stream)
length - - how much of the item to play (-1 implies play the entire file or live stream)

Returns:

- returns true if item was inserted successfully ...otherwise false. this should not interrupt anything that might be currently playing.... will do nothing if existing item does not exist.. if existing == "" insert at head of list

addToPlaylist

```
public boolean addToPlaylist(String existing,  
    String name,  
    int start,  
    int length)
```

Insert item into playlist just after the first item in the playlist with a given name.

Parameters:

existing - name of playlist item in which to insert the item after
name - name of new item
start - where to start playing the item. (-2 implies play a live stream)
length - how much of the item to play (-1 implies play the entire file or live stream)

Returns:

true if item inserted

removeFromPlaylist

```
public boolean removeFromPlaylist(String name)
```

Remove all items matching the given stream name from the playlist. If the item is currently being played, it is not removed.

Parameters:

name - stream name

Returns:

true if at least one item from removed

play

```
public boolean play(String sPlaylist)
```

Add a media item to the playlist as defined by an XML file ..

Parameters:

sPlaylist - - the playlist XML definition file

(continued from last page)

Returns:

- returns true if item was added successfully ...otherwise false.

close

```
public void close()
```

Call this method when you have finished with the playlist object. It will terminate the playlist thread. The playlist object cannot be used after this call.

closeAndWait

```
public void closeAndWait()
```

Call this method when you have finished with the playlist object. It will terminate the playlist thread. The playlist object cannot be used after this call. This method will wait for the thread to exit.

getName

```
public String getName()
```

Returns the name of the playlist stream - the client would play this stream by this name.

Returns:

- the name of the playlist stream

getRepeat

```
public boolean getRepeat()
```

Use this to determine if the playlist is auto-repeating

Returns:

- true if repeating otherwise false.

setRepeat

```
public void setRepeat(boolean repeat)
```

Use this to make the playlist repeat or not...

Parameters:

repeat - - true to repeat otherwise false

play

```
public void play(int n)
```

next

```
public void next(int n)
```

(continued from last page)

next

```
public void next()
```

previous

```
public void previous()
```

previous

```
public void previous(int n)
```

getPollingInterval

```
public int getPollingInterval()
```

Get the polling interval (milliseconds)

Returns:

polling interval (milliseconds)

setPollingInterval

```
public void setPollingInterval(int pollingInterval)
```

Set the polling interval (milliseconds)

Parameters:

pollingInterval - polling interval (milliseconds)

getPublisher

```
public Publisher getPublisher()
```

addListener

```
public void addListener(IStreamActionNotify listener)
```

Add a listener

Parameters:

listener - listener

removeListener

```
public void removeListener(IStreamActionNotify listener)
```

Remove a listener

Parameters:

(continued from last page)

listener - listener

isSwitchLog

```
public boolean isSwitchLog()
```

Log when a playlist switch occurs

Returns:

log when a playlist switch occurs

setSwitchLog

```
public void setSwitchLog(boolean switchLog)
```

Log when a playlist switch occurs

Parameters:

switchLog - log when a playlist switch occurs

isSendOnMetadata

```
public boolean isSendOnMetadata()
```

True if sending onMetadata events

Returns:

True if sending onMetadata events

setSendOnMetadata

```
public void setSendOnMetadata(boolean sendOnMetadata)
```

True if sending onMetadata events

Parameters:

sendOnMetadata - True if sending onMetadata events

Package

com.wowza.wms.transcoder.model

com.wowza.wms.transcoder.model Interface ILiveStreamTranscoderActionNotify

public interface **ILiveStreamTranscoderActionNotify**
extends

ILiveStreamTranscoderActionNotify: listener interface for live stream transcoder events.

Method Summary

void	<code>onCalculateSourceAudioBitrate</code> (<code>LiveStreamTranscoder liveStreamTranscoder, long bitrate</code>) Called when the bitrate of the source audio stream is calculated
void	<code>onCalculateSourceVideoBitrate</code> (<code>LiveStreamTranscoder liveStreamTranscoder, long bitrate</code>) Called when the bitrate of the source video stream is calculated
void	<code>onInitAfterLoadTemplate</code> (<code>LiveStreamTranscoder liveStreamTranscoder</code>) Called just after transcoder template is loaded.
void	<code>onInitBeforeLoadTemplate</code> (<code>LiveStreamTranscoder liveStreamTranscoder</code>) Called just before transcoder template is loaded
void	<code>onInitStart</code> (<code>LiveStreamTranscoder liveStreamTranscoder, String streamName, String transcoderName, IApplicationInstance appInstance, LiveStreamTranscoderItem liveStreamTranscoderItem</code>) Call when live stream transcoder is first created
void	<code>onInitStop</code> (<code>LiveStreamTranscoder liveStreamTranscoder</code>) At the end of the initialization process
void	<code>onRegisterStreamNameGroup</code> (<code>LiveStreamTranscoder liveStreamTranscoder, TranscoderStreamNameGroup streamNameGroup</code>) Called after a stream name group is resolved and registered with MediaStreamMap
void	<code>onResetStream</code> (<code>LiveStreamTranscoder liveStreamTranscoder</code>) Called when the stream feeding the live stream transcoder switches.
void	<code>onSessionAudioDecodeCodecInfo</code> (<code>LiveStreamTranscoder liveStreamTranscoder, com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio</code>) Called when audio decoding information is available.
void	<code>onSessionAudioEncodeCodecInfo</code> (<code>LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode, com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio</code>) Called when audio encoding information is available.
void	<code>onSessionAudioEncodeCreate</code> (<code>LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode</code>) Called when audio encoder session is created.
void	<code>onSessionAudioEncodeInit</code> (<code>LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode</code>) Called after audio session is initialized.

void	<u>onSessionAudioEncodeSetup</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionAudioEncode sessionAudioEncode) Called after native audio encoder is created and initialized.
void	<u>onSessionDataEncodeCreate</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionDataEncode sessionDataEncode) Called when data encoder session is created.
void	<u>onSessionDataEncodeInit</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionDataEncode sessionDataEncode) Called after data session is initialized.
void	<u>onSessionDestinationCreate</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionDestination sessionDestination) Called when transcoding destination is created
void	<u>onSessionVideoDecodeCodecInfo</u> (LiveStreamTranscoder liveStreamTranscoder, com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Called when video decoding information is available.
void	<u>onSessionVideoEncodeCodecInfo</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode, com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo) Called when video encoding information is available.
void	<u>onSessionVideoEncodeCreate</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode) Called when video encoder session is created.
void	<u>onSessionVideoEncodeInit</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode) Called after video session is initialized.
void	<u>onSessionVideoEncodeSetup</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderSessionVideoEncode sessionVideoEncode) Called after native video encoder is created and initialized.
void	<u>onShutdownStart</u> (LiveStreamTranscoder liveStreamTranscoder) Called when the live stream transcoder starts to shutdown.
void	<u>onShutdownStop</u> (LiveStreamTranscoder liveStreamTranscoder) Called when the live stream transcoder is shutdown.
void	<u>onUnregisterStreamNameGroup</u> (LiveStreamTranscoder liveStreamTranscoder, TranscoderStreamNameGroup streamNameGroup) Called after a stream name group is unregistered with MediaStreamMap

Methods

onInitStart

```
public void onInitStart(LiveStreamTranscoder liveStreamTranscoder,
    String streamName,
    String transcoderName,
    IApplicationInstance appInstance,
    LiveStreamTranscoderItem liveStreamTranscoderItem)
```

Call when live stream transcoder is first created

Parameters:

(continued from last page)

liveStreamTranscoder - live stream transcoder
streamName - stream name
transcoderName - transcoder name
appInstance - application instance
liveStreamTranscoderItem - live stream transcoder definition

onInitBeforeLoadTemplate

```
public void onInitBeforeLoadTemplate(LiveStreamTranscoder liveStreamTranscoder)
```

Called just before transcoder template is loaded

Parameters:

liveStreamTranscoder - live stream transcoder

onInitAfterLoadTemplate

```
public void onInitAfterLoadTemplate(LiveStreamTranscoder liveStreamTranscoder)
```

Called just after transcoder template is loaded. Good place to modify values loaded from template.

Parameters:

liveStreamTranscoder - live stream transcoder

onInitStop

```
public void onInitStop(LiveStreamTranscoder liveStreamTranscoder)
```

At the end of the initialization process

Parameters:

liveStreamTranscoder - live stream transcoder

onCalculateSourceVideoBitrate

```
public void onCalculateSourceVideoBitrate(LiveStreamTranscoder liveStreamTranscoder,  
long bitrate)
```

Called when the bitrate of the source video stream is calculated

Parameters:

liveStreamTranscoder - live stream transcoder
bitrate - source bitrate (bytes per second)

onCalculateSourceAudioBitrate

```
public void onCalculateSourceAudioBitrate(LiveStreamTranscoder liveStreamTranscoder,  
long bitrate)
```

Called when the bitrate of the source audio stream is calculated

Parameters:

liveStreamTranscoder - live stream transcoder
bitrate - source bitrate (bytes per second)

(continued from last page)

onSessionDestinationCreate

```
public void onSessionDestinationCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionDestination sessionDestination)
```

Called when transcoding destination is created

Parameters:

liveStreamTranscoder - live stream transcoder
sessionDestination - destination

onSessionVideoEncodeCreate

```
public void onSessionVideoEncodeCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode)
```

Called when video encoder session is created.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionVideoEncode - video session

onSessionAudioEncodeCreate

```
public void onSessionAudioEncodeCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode)
```

Called when audio encoder session is created.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionAudioEncode - audio session

onSessionDataEncodeCreate

```
public void onSessionDataEncodeCreate(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionDataEncode sessionDataEncode)
```

Called when data encoder session is created.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionDataEncode - data session

onSessionVideoEncodeInit

```
public void onSessionVideoEncodeInit(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode)
```

Called after video session is initialized.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionVideoEncode - video session

onSessionAudioEncodeInit

```
public void onSessionAudioEncodeInit(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode)
```

(continued from last page)

Called after audio session is initialized.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionAudioEncode - audio session

onSessionDataEncodeInit

```
public void onSessionDataEncodeInit(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionDataEncode sessionDataEncode)
```

Called after data session is initialized.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionDataEncode - data session

onSessionVideoEncodeSetup

```
public void onSessionVideoEncodeSetup(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode)
```

Called after native video encoder is created and initialized.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionVideoEncode - video session

onSessionAudioEncodeSetup

```
public void onSessionAudioEncodeSetup(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode)
```

Called after native audio encoder is created and initialized.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionAudioEncode - audio session

onSessionVideoEncodeCodecInfo

```
public void onSessionVideoEncodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionVideoEncode sessionVideoEncode,  
    com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
```

Called when video encoding information is available.

Parameters:

liveStreamTranscoder - live stream transcoder
sessionVideoEncode - video session
codecInfoVideo - encoding info

onSessionAudioEncodeCodecInfo

```
public void onSessionAudioEncodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
    TranscoderSessionAudioEncode sessionAudioEncode,  
    com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
```

Called when audio encoding information is available.

(continued from last page)

Parameters:

liveStreamTranscoder - live stream transcoder
sessionAudioEncode - audio session
codecInfoAudio - encoding info

onSessionVideoDecodeCodecInfo

```
public void onSessionVideoDecodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
com.wowza.wms.media.model.MediaCodecInfoVideo codecInfoVideo)
```

Called when video decoding information is available.

Parameters:

liveStreamTranscoder - live stream transcoder
codecInfoVideo - video info

onSessionAudioDecodeCodecInfo

```
public void onSessionAudioDecodeCodecInfo(LiveStreamTranscoder liveStreamTranscoder,  
com.wowza.wms.media.model.MediaCodecInfoAudio codecInfoAudio)
```

Called when audio decoding information is available.

Parameters:

liveStreamTranscoder - live stream transcoder
codecInfoAudio - audio info

onRegisterStreamNameGroup

```
public void onRegisterStreamNameGroup(LiveStreamTranscoder liveStreamTranscoder,  
TranscoderStreamNameGroup streamNameGroup)
```

Called after a stream name group is resolved and registered with MediaStreamMap

Parameters:

liveStreamTranscoder - live stream transcoder
streamNameGroup - stream name group

onUnregisterStreamNameGroup

```
public void onUnregisterStreamNameGroup(LiveStreamTranscoder liveStreamTranscoder,  
TranscoderStreamNameGroup streamNameGroup)
```

Called after a stream name group is unregistered with MediaStreamMap

Parameters:

liveStreamTranscoder - live stream transcoder
streamNameGroup - stream name group

onShutdownStart

```
public void onShutdownStart(LiveStreamTranscoder liveStreamTranscoder)
```

Called when the live stream transcoder starts to shutdown.

Parameters:

liveStreamTranscoder - live stream transcoder

onShutdownStop

```
public void onShutdownStop(LiveStreamTranscoder liveStreamTranscoder)
```

Called when the live stream transcoder is shutdown.

Parameters:

liveStreamTranscoder - live stream transcoder

onResetStream

```
public void onResetStream(LiveStreamTranscoder liveStreamTranscoder)
```

Called when the stream feeding the live stream transcoder switches.

Parameters:

liveStreamTranscoder - live stream transcoder

com.wowza.wms.transcoder.model Interface ITranscoderFrameGrabProvider

public interface **ITranscoderFrameGrabProvider**
extends

ITranscoderFrameGrabProvider: interface used to grab frames from the live stream transcoder.

Method Summary

java.util.List	getAndClearPendingFrameGrabs() Returns a list of all grab frame requests that are pending and clears the pending list.
void	grabFrame(ITranscoderFrameGrabResult grabResult) Call to grab a frame.
void	grabFrame(ITranscoderFrameGrabResult grabResult, int width, int height) Call to grab a frame.

Methods

grabFrame

public void **grabFrame**([ITranscoderFrameGrabResult](#) grabResult)

Call to grab a frame. The size of the frame will be the full size of the video frame.

Parameters:

grabResult - the class that will be called back when frame is available

grabFrame

public void **grabFrame**([ITranscoderFrameGrabResult](#) grabResult,
int width,
int height)

Call to grab a frame. The size of the frame is controlled by width and height.

Parameters:

grabResult - the class that will be called back when frame is available

width - frame width

height - frame height

getAndClearPendingFrameGrabs

public java.util.List **getAndClearPendingFrameGrabs**()

Returns a list of all grab frame requests that are pending and clears the pending list.

Returns:

list of pending grab frames

com.wowza.wms.transcoder.model

Interface ITranscoderFrameGrabResult

public interface **ITranscoderFrameGrabResult**
extends

ITranscoderFrameGrabResult: Implement this interface when using frame grabber interface to grab transcoder video frames.

Method Summary	
void	onGrabFrame (TranscoderNativeVideoFrame nativeFrame) Trigger when frame is available.

Methods

onGrabFrame

public void **onGrabFrame**(TranscoderNativeVideoFrame nativeFrame)

Trigger when frame is available.

Parameters:

nativeFrame - native video frame.

com.wowza.wms.transcoder.model Interface ITranscoderOverlayProvider

public interface **ITranscoderOverlayProvider**
extends

ITranscoderOverlayProvider: interface to add and remove video overlays.

Method Summary

void	<code>addOverlay</code> (int index, TranscoderVideoOverlayFrame overlay) Add an overlay to a video stream.
void	<code>clearOverlay</code> (int index) Clear video overlay
java.util.Map	<code>getAndClearPendingOverlays</code> () Get a list of pending overlay requests and clear the pending overlay queue.
boolean	<code>isOverlayAvailable</code> () Returns true if there is a pending overlay request.

Methods

addOverlay

```
public void addOverlay(int index,  
    TranscoderVideoOverlayFrame overlay)
```

Add an overlay to a video stream.

Parameters:

index - over lay index (zero is bottom in z-order)
overlay - overlay object

clearOverlay

```
public void clearOverlay(int index)
```

Clear video overlay

Parameters:

index - over lay index (zero is bottom in z-order)

isOverlayAvailable

```
public boolean isOverlayAvailable()
```

Returns true if there is a pending overlay request.

Returns:

true if there is a pending overlay request

getAndClearPendingOverlays

```
public java.util.Map getAndClearPendingOverlays()
```

Get a list of pending overlay requests and clear the pending overlay queue.

Returns:

list of pending overlay requests

com.wowza.wms.transcoder.model

Interface ITranscoderWorker

public interface ITranscoderWorker

extends

For internal use.

Method Summary	
boolean	isRunning() Returns true if transcoder worker is running (internal use)

Methods

isRunning

public boolean **isRunning()**

Returns true if transcoder worker is running (internal use)

Returns:
true if transcoder worker is running (internal use)

com.wowza.wms.transcoder.model

Interface ITranscoderWorkerSorterSender

public interface ITranscoderWorkerSorterSender
extends

For internal use.

Method Summary	
void	addSorterPacket (TranscoderPacketSorterHolder sorterHolder) For internal use.

Methods

addSorterPacket

public void **addSorterPacket**(TranscoderPacketSorterHolder sorterHolder)

For internal use.

Parameters:
sorterHolder - sorter holder

Package

com.wowza.wms.util

com.wowza.wms.util

Class RTPUtils

java.lang.Object

└─com.wowza.wms.util.RTPUtils

public class **RTPUtils**
extends Object

Constructor Summary

public	RTPUtils()
--------	----------------------------

Method Summary

static double[]	decodeRangeHeader (String rangeStr) Decode RTP range header, Internal use.
static RTPStream	decodeStreamInfo (RTPContext context, String streamId, String streamInfo) Decode SDP info and create RTP stream
static byte[]	formatH264CodecConfig (byte[] sps, java.util.List ppss, byte[] profileLevel) Format codec config info, Internal use.
static byte[]	formatH264CodecConfigPacket (byte[] sps, java.util.List ppss, byte[] profileLevel) Format codec config info, Internal use.
static void	loadConfigFile (RTPContext rtpContext, String fileURL) Load config file, Internal use.
static RTTPushPublishSession	startRTTPull (IApplicationInstance appInstance, String streamName, boolean streamPacketizer, String ipAddress, int streamPort) Start pushing an RTP stream
static RTTPushPublishSession	startRTTPull (IApplicationInstance appInstance, String streamName, boolean streamPacketizer, String ipAddress, int streamPort, boolean isRTPWrapped) Start pushing an RTP stream
static RTTPushPublishSession	startRTTPull (IApplicationInstance appInstance, String streamName, boolean streamPacketizer, String ipAddress, int audioPort, int videoPort) Start pushing an RTP stream
static RTTPushPublishSession	startRTTPull (IApplicationInstance appInstance, String streamName, boolean streamPacketizer, String ipAddress, int audioPort, int videoPort, boolean isRTPWrapped) Start pushing an RTP stream
static RTTPushPublishSession	startRTTPull (IApplicationInstance appInstance, String streamName, RTPDestination rtpDestination) Start pushing an RTP stream

static void	stopRTPPull (RTPPushPublishSession rtpPushPublishSession) Stop pushing an RTP stream
static String	updateSDPDestination (RTPDestination rtpDestination, String sdpData) Update SDP data information with RTP destination information
static void	writeCodecConfig (RTPTrack rtpTrack, int codecId, long adjTimecode, byte[] codecConfig)
static void	writeCodecConfig (RTPTrack rtpTrack, long adjTimecode, byte[] codecConfig) Write codec config information, Internal use.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

RTPUtils

```
public RTPUtils()
```

Methods

updateSDPDestination

```
public static String updateSDPDestination(RTPDestination rtpDestination,  
String sdpData)
```

Update SDP data information with RTP destination information

Parameters:

rtpDestination - RTP destination
sdpData - SDP data

Returns:

modified SDP data

decodeRangeHeader

```
public static double[] decodeRangeHeader(String rangeStr)
```

Decode RTP range header, Internal use.

Parameters:

rangeStr

Returns:

range values

(continued from last page)

stopRTPPull

```
public static void stopRTPPull(RTPPushPublishSession rtpPushPublishSession)
```

Stop pushing an RTP stream

Parameters:

rtpPushPublishSession - RTP push session

startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int streamPort,  
    boolean isRTPWrapped)
```

Start pushing an RTP stream

Parameters:

appInstance - application instance
streamName - stream name
streamPacketizer - stream packetizer
ipAddress - IP address
streamPort - stream port
isRTPWrapped - is RTP wrapped

Returns:

RTP push session

startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int streamPort)
```

Start pushing an RTP stream

Parameters:

appInstance - application instance
streamName - stream name
streamPacketizer - stream packetizer
ipAddress - IP address
streamPort - stream port

Returns:

RTP push session

startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int audioPort,  
    int videoPort)
```

Start pushing an RTP stream

(continued from last page)

Parameters:

appInstance - application instance
streamName - stream name
streamPacketizer - stream packetizer
ipAddress - IP address
audioPort - audio port
videoPort - video port

Returns:

RTP push session

startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    boolean streamPacketizer,  
    String ipAddress,  
    int audioPort,  
    int videoPort,  
    boolean isRTPWrapped)
```

Start pushing an RTP stream

Parameters:

appInstance - application instance
streamName - stream name
streamPacketizer - stream packetizer
ipAddress - IP address
audioPort - audio port
videoPort - video port
isRTPWrapped - is RTP wrapped

Returns:

RTP push session

startRTPPull

```
public static RTPPushPublishSession startRTPPull(IApplicationInstance appInstance,  
    String streamName,  
    RTPDestination rtpDestination)
```

Start pushing an RTP stream

Parameters:

appInstance - application instance
streamName - stream name
rtpDestination - RTP destination

Returns:

RTP push session

writeCodecConfig

```
public static void writeCodecConfig(RTPTrack rtpTrack,  
    int codecId,  
    long adjTimecode,  
    byte[] codecConfig)
```

writeCodecConfig

```
public static void writeCodecConfig(RTPTrack rtpTrack,  
    long adjTimecode,  
    byte[] codecConfig)
```

Write codec config information, Internal use.

Parameters:

rtpTrack - RTP track
adjTimecode - timecode (milliseconds)
codecConfig - codec config

loadConfigFile

```
public static void loadConfigFile(RTPContext rtpContext,  
    String fileURL)
```

Load config file, Internal use.

Parameters:

rtpContext
fileURL

decodeStreamInfo

```
public static RTPStream decodeStreamInfo(RTPContext context,  
    String streamId,  
    String streamInfo)
```

Decode SDP info and create RTP stream

Parameters:

context - RTP context
streamId - stream id
streamInfo - SDP data

Returns:

RTP stream

formatH264CodecConfigPacket

```
public static byte[] formatH264CodecConfigPacket(byte[] sps,  
    java.util.List ppss,  
    byte[] profileLevel)
```

Format codec config info, Internal use.

Parameters:

sps
ppss
profileLevel

Returns:

bytes

(continued from last page)

formatH264CodecConfig

```
public static byte[] formatH264CodecConfig(byte[] sps,  
      java.util.List ppss,  
      byte[] profileLevel)
```

Format codec config info, Internal use.

Parameters:

sps
ppss
profileLevel

Returns:

bytes

com.wowza.wms.util Class StreamUtils

java.lang.Object

└─com.wowza.wms.util.StreamUtils

public class **StreamUtils**
extends Object

Constructor Summary

public	StreamUtils()
--------	-------------------------------

Method Summary

static int	directOutput (byte[] dataBuffer, int[] headerValues, boolean isAbsTimecode, int src, java.io.OutputStream out, AMFObj wmsObj, byte[] workBuffer, int chunkSize) Direct output, Internal use.
static double	getStreamBitrate (IApplicationInstance appInstance, String streamName)
static double	getStreamBitrate (IMediaStream stream) Get the approximate bitrate of a media file in bits/per-second.
static double	getStreamLength (IApplicationInstance appInstance, String streamName) Get the duration of a media file in seconds.
static double	getStreamLength (IMediaStream stream) Get the duration of a media file in seconds.
static void	loadConfigFile (StreamList streamDefs, String fileURL) Load Streams.xml, Internal use.
static int	packetOutput (java.io.OutputStream out, IMediaStream stream, AMFPacket packet, long timecode, AMFObj wmsObj, byte[] workBuffer, int chunkSize) Packet output.
static int	packetOutput (java.io.OutputStream out, IMediaStream stream, AMFPacket packet, long timecode, AMFObj wmsObj, byte[] workBuffer, int chunkSize, boolean referenceWrite) Packet output.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

(continued from last page)

StreamUtils

```
public StreamUtils()
```

Methods

getStreamLength

```
public static double getStreamLength(IMediaStream stream)
```

Get the duration of a media file in seconds. This will work correctly with all RandomAccessReaders and caching technology

Parameters:

stream - stream

Returns:

duration in seconds

getStreamBitrate

```
public static double getStreamBitrate(IMediaStream stream)
```

Get the approximate bitrate of a media file in bits/per-second. This will work correctly with all RandomAccessReaders and caching technology.

Parameters:

stream - stream

Returns:

bitrate in bits/per-second

getStreamLength

```
public static double getStreamLength(IApplicationInstance appInstance,  
String streamName)
```

Get the duration of a media file in seconds. This will work correctly with all RandomAccessReaders and caching technology

Parameters:

appInstance - application instance
streamName - stream name

Returns:

duration in seconds

getStreamBitrate

```
public static double getStreamBitrate(IApplicationInstance appInstance,  
String streamName)
```


(continued from last page)

directOutput

```
public static int directOutput(byte[] dataBuffer,  
    int[] headerValues,  
    boolean isAbsTimecode,  
    int src,  
    java.io.OutputStream out,  
    AMFObj wmsObj,  
    byte[] workBuffer,  
    int chunkSize)
```

Direct output. Internal use.

Parameters:

dataBuffer
headerValues
isAbsTimecode
src
out
wmsObj
workBuffer
chunkSize

Returns:

c

packetOutput

```
public static int packetOutput(java.io.OutputStream out,  
    IMediaStream stream,  
    AMFPacket packet,  
    long timecode,  
    AMFObj wmsObj,  
    byte[] workBuffer,  
    int chunkSize)
```

Packet output. Internal use.

Parameters:

out
stream
packet
timecode
wmsObj
workBuffer
chunkSize

Returns:

bytes

packetOutput

```
public static int packetOutput(java.io.OutputStream out,  
    IMediaStream stream,  
    AMFPacket packet,  
    long timecode,  
    AMFObj wmsObj,  
    byte[] workBuffer,  
    int chunkSize,  
    boolean referenceWrite)
```

Packet output. Internal use.

(continued from last page)

Parameters:

out
stream
packet
timecode
wmsObj
workBuffer
chunkSize
referenceWrite

Returns:

bytes

loadConfigFile

```
public static void loadConfigFile(StreamList streamDefs,  
    String fileURL)
```

Load Strreams.xml, Internal use.

Parameters:

streamDefs
fileURL

Package

com.wowza.wms.vhost

com.wowza.wms.vhost Class HostPort

java.lang.Object

└─com.wowza.wms.vhost.HostPort

public class **HostPort**
extends Object

HostPort: data object that describes a socket connection. The address can be defined by ipAddress or by domainName. It can also contain a reference to an SSLFactory class that can be used to create a secure connection to the server.

Constructor Summary

public	HostPort() Create an empty HostPort object
--------	---------------------------------------------------------------

Method Summary

void	addHttpProvider(IHTTPProvider httpProvider)
void	addHttpProvider(IHTTPProvider2 httpProvider)
void	addHTTPStreamerAdapterID(String ID)
void	configureSocketAcceptor(org.apache.mina.transport.socket.nio.SocketAcceptorConfig socketConfig) Configure a socketAcceptor
java.net.InetAddress	getAddress() Get the ipAddress as an InetAddress object
String	getAddressRawStr()
String	getAddressStr() Get a String representation of the address
HostPortConfig	getConfiguration() Get the socket configuration
java.util.List	getHttpProviders()
java.util.List	getHTTPStreamerAdapterIDs()
int	getPort() Get port
int	getProcessorCount() Get the number of threads to use to service this incoming port

HostPortSSLConfig	<u>getSSLConfig()</u>
String	<u>getSslFactoryClass()</u> Get full class name or SSLFactory class
boolean	<u>isSuspended()</u>
void	<u>setDomainName()</u> (String domainName) Set domainName.
void	<u>setIpAddress()</u> (String ipAddress) Set ipAddress for object.
void	<u>setPort()</u> (int port) Set port
void	<u>setProcessorCount()</u> (int processorCount) Set the number of threads to use to service this incoming port
void	<u>setSSLConfig()</u> (HostPortSSLConfig sslConfig)
void	<u>setSslFactoryClass()</u> (String sslFactoryClass) Set full class name of SSLFactory class
void	<u>setSuspended()</u> (boolean isSuspended)
String	<u>toString()</u> Return object as formatted string
String	<u>toString()</u> (boolean mBeanSafe) Return object as formatted string

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

HostPort

```
public HostPort()
```

Create an empty HostPort object

Methods

setDomainName

```
public void setDomainName(String domainName)
```

Set domainName. A domainName of * defines a local connection.

Parameters:

domainName - domainName like www.mycompany.com or * for local

getAddress

```
public java.net.InetAddress getAddress()
```

Get the ipAddress as an InetAddress object

Returns:

ipAddress as an InetAddress object. At this point the domainName (if specified) will be resolved.

getAddressStr

```
public String getAddressStr()
```

Get a String representation of the address

Returns:

String representation of the address/domainName. If * it will return [any]

getAddressRawStr

```
public String getAddressRawStr()
```

setIpAddress

```
public void setIpAddress(String ipAddress)
```

Set ipAddress for object. A ipAddress of * defines a local connection.

Parameters:

ipAddress - ipAddress like 127.0.0.1 or * for local

getPort

```
public int getPort()
```

Get port

Returns:

port

setPort

```
public void setPort(int port)
```

Set port

Parameters:

port - port

getSslFactoryClass

```
public String getSslFactoryClass()
```

Get full class name or SSLFactory class

(continued from last page)

Returns:

full class name or SSLFactory or "" if not specified

setSslFactoryClass

```
public void setSslFactoryClass(String sslFactoryClass)
```

Set full class name of SSLFactory class

Parameters:

sslFactoryClass - full class name or SSLFactory or "" if not specified

getProcessorCount

```
public int getProcessorCount()
```

Get the number of threads to use to service this incoming port

Returns:

number of processor threads

setProcessorCount

```
public void setProcessorCount(int processorCount)
```

Set the number of threads to use to service this incoming port

Parameters:

processorCount - number of processor threads

toString

```
public String toString(boolean mBeanSafe)
```

Return object as formatted string

Parameters:

mBeanSafe - make the name safe for JMX management interface

Returns:

formmatted string

toString

```
public String toString()
```

Return object as formatted string

Returns:

formmatted string

getConfiguration

```
public HostPortConfig getConfiguration()
```

Get the socket configuration

Returns:

(continued from last page)

socket configuration

configureSocketAcceptor

```
public void  
configureSocketAcceptor(org.apache.mina.transport.socket.nio.SocketAcceptorConfig  
socketConfig)
```

Configure a socketAcceptor

Parameters:

socketConfig - socket acceptor

getHttpProviders

```
public java.util.List getHttpProviders()
```

addHttpProvider

```
public void addHttpProvider(IHTTPProvider httpProvider)
```

addHttpProvider

```
public void addHttpProvider(IHTTPProvider2 httpProvider)
```

isSuspended

```
public boolean isSuspended()
```

setSuspended

```
public void setSuspended(boolean isSuspended)
```

getHTTPStreamerAdapterIDs

```
public java.util.List getHTTPStreamerAdapterIDs()
```

addHTTPStreamerAdapterID

```
public void addHTTPStreamerAdapterID(String ID)
```

getSSLConfig

```
public HostPortSSLConfig getSSLConfig()
```

(continued from last page)

setSSLConfig

```
public void setSSLConfig(HostPortSSLConfig sslConfig)
```

com.wowza.wms.vhost Class HostPortList

java.lang.Object

└--com.wowza.wms.vhost.HostPortList

```
public class HostPortList
    extends Object
```

HostPortList: data object that contains a collection of HostPort objects.

Constructor Summary

public	HostPortList () Create empty HostPortList
--------	--------------------------------------------------------------

Method Summary

void	add (HostPort hostPort) Add HostPort object
HostPort	get (int index) Get HostPort object at index, null if out of bounds
int	size () Get number of HostPort objects

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

HostPortList

```
public HostPortList()
```

Create empty HostPortList

Methods

add

```
public void add(HostPort hostPort)
```

Add HostPort object

Parameters:

hostPort

size

```
public int size()
```

Get number of HostPort objects

Returns:

number of HostPort objects

get

```
public HostPort get(int index)
```

Get HostPort object at index, null if out of bounds

Parameters:

index - index

Returns:

HostPort object at index, null if out of bounds

com.wowza.wms.vhost Interface IAcceptorNotify

public interface **IAcceptorNotify**
extends

IAcceptorNotify: listener interface used by IVHost addAcceptorListener

Method Summary

void	<code>onAcceptorCreate</code> (<code>HostPort</code> hostPort, java.util.Map acceptorMap) Triggered when a new acceptor is created
void	<code>onAcceptorDestroy</code> (<code>HostPort</code> hostPort, java.util.Map acceptorMap) Triggered when a new acceptor is deleted

Methods

onAcceptorCreate

```
public void onAcceptorCreate(HostPort hostPort,  
                             java.util.Map acceptorMap)
```

Triggered when a new acceptor is created

Parameters:

hostPort - HostPort object

acceptorMap - Map of acceptors

onAcceptorDestroy

```
public void onAcceptorDestroy(HostPort hostPort,  
                               java.util.Map acceptorMap)
```

Triggered when a new acceptor is deleted

Parameters:

hostPort - HostPort object

acceptorMap - Map of acceptors

com.wowza.wms.vhost Interface IVHost

public interface **IVHost**
extends

IVHost: public interface to VHost object.

Field Summary

public static final	ACCEPTORS_ACCEPTOR Acceptor types: acceptor Value: acceptor
public static final	ACCEPTORS_HANDLERADAPTER Acceptor types: handler Value: handlerAdapter
public static final	CODEC_AUDIO_AAC Value: 10
public static final	CODEC_AUDIO_G711_ALAW Value: 7
public static final	CODEC_AUDIO_G711_MULAW Value: 8
public static final	CODEC_AUDIO_MP3 Value: 2
public static final	CODEC_AUDIO_MP3_8 Value: 15
public static final	CODEC_AUDIO_NELLYMOSER Value: 6
public static final	CODEC_AUDIO_NELLYMOSER_16MONO Value: 4
public static final	CODEC_AUDIO_NELLYMOSER_8MONO Value: 5
public static final	CODEC_AUDIO_PCM_BE Value: 0
public static final	CODEC_AUDIO_PCM_LE Value: 3

public static final	CODEC_AUDIO_PCM_SWF Value: 1
public static final	CODEC_AUDIO_RESERVED Value: 9
public static final	CODEC_AUDIO_SPEEX Value: 11
public static final	CODEC_AUDIO_UNKNOWN Value: -1
public static final	CODEC_AUDIO_VORBIS Value: 9
public static final	CODEC_STREAM_MP2T Value: 0
public static final	CODEC_STREAM_UNKNOWN Value: -1
public static final	CODEC_VIDEO_H263 Value: 9
public static final	CODEC_VIDEO_H264 Value: 7
public static final	CODEC_VIDEO_MPEG2 Value: 11
public static final	CODEC_VIDEO_MPEG4 Value: 10
public static final	CODEC_VIDEO_SCREEN Value: 3
public static final	CODEC_VIDEO_SCREEN2 Value: 6
public static final	CODEC_VIDEO_SPARK Value: 2
public static final	CODEC_VIDEO_UNKNOWN Value: -1
public static final	CODEC_VIDEO_VP6 Value: 4

public static final	CODEC_VIDEO_VP6A Value: 5
public static final	CODEC_VIDEO_VP8 Value: 8
public static final	CONTENTTYPE_ACKBANDWIDTH AMF Content type: set acknowledge bandwidth size Value: 5
public static final	CONTENTTYPE_AUDIO AMF Content type: audio packet Value: 8
public static final	CONTENTTYPE_BUFFERSIZE AMF Content type: set buffer size Value: 4
public static final	CONTENTTYPE_DATA AMF Content type: data packet Value: 18
public static final	CONTENTTYPE_DATA0 AMF Content type: data packet (AMF0) Value: 18
public static final	CONTENTTYPE_DATA3 AMF Content type: data packet (AMF3) Value: 15
public static final	CONTENTTYPE_FUNCTION AMF Content type: function data (AMF0) Value: 20
public static final	CONTENTTYPE_FUNCTION0 AMF Content type: function data (AMF0) Value: 20
public static final	CONTENTTYPE_FUNCTION3 AMF Content type: function data (AMF3) Value: 17
public static final	CONTENTTYPE_MEDIACHUNK AMF Content type: media chunk Value: 22
public static final	CONTENTTYPE_PLAYCALLBACK AMF Content type: play callback Value: 127
public static final	CONTENTTYPE_SETBANDWIDTH AMF Content type: set bandwidth size Value: 6

public static final	CONTENTTYPE_SETCHUNKSIZE AMF Content type: set packet chunk size Value: 1
public static final	CONTENTTYPE_SHAREDOBJECTS AMF Content type: shared object packet (AMF0) Value: 19
public static final	CONTENTTYPE_SHAREDOBJECTS0 AMF Content type: shared object packet (AMF0) Value: 19
public static final	CONTENTTYPE_SHAREDOBJECTS3 AMF Content type: shared object packet (AMF3) Value: 16
public static final	CONTENTTYPE_UNKNOWN AMF Content type: unknown Value: 0
public static final	CONTENTTYPE_VIDEO AMF Content type: video packet Value: 9
public static final	CONTENTTYPE_WATCHDOG AMF Content type: watch dog Value: 3
public static final	COUNTER_HTTPCUPERTINO Value: 2
public static final	COUNTER_HTTPDVRCHUNKS Value: 7
public static final	COUNTER_HTTPSANJOSE Value: 4
public static final	COUNTER_HTTPSMOOTH Value: 3
public static final	COUNTER_HTTPWEBM Value: 5
public static final	COUNTER_RTMP Value: 0
public static final	COUNTER_RTP Value: 1
public static final	COUNTER_TOTAL Value: 6

public static final	FILEFORMAT_FLV Value: 1
public static final	FILEFORMAT_MP4 Value: 2
public static final	FILEFORMAT_UNKNOWN Value: -1
public static final	LICENSECOUNTER_DRM_EZDRM_LIVE Value: 4
public static final	LICENSECOUNTER_DRM_EZDRM_VOD Value: 5
public static final	LICENSECOUNTER_DRM_VERIMATRIX_LIVE Value: 6
public static final	LICENSECOUNTER_DRM_VERIMATRIX_VOD Value: 7
public static final	LICENSECOUNTER_NDVR Value: 3
public static final	LICENSECOUNTER_PUBLISHER Value: 0
public static final	LICENSECOUNTER_PUBLISHERTRANSCODER Value: 8
public static final	LICENSECOUNTER_TOTAL Value: 9
public static final	LICENSECOUNTER_TRANSCODE_DECODE Value: 1
public static final	LICENSECOUNTER_TRANSCODE_ENCODE Value: 2
public static final	VHOST_DEFAULT Value: _defaultVHost_

Method Summary

void	addAcceptorListener (IAcceptorNotify acceptorListener) Add acceptor listener.
void	addApplicationListener (IApplicationNotify applicationListener) Add application listener.

void	<u>addIdleWorkerListener</u> (IdleWorkerNotify idleWorkerListener) Add idleWorker listener.
void	<u>addStartupStream</u> (StartupStream startupStream) Add a stream to the list of streams to start and virtual host startup
boolean	<u>applicationExists</u> (String name) Return true if an application folder exists for this application name
void	<u>closeHostPort</u> (HostPort hostPort, boolean isSuspend) Close an individual HostPort
boolean	<u>createApplication</u> (String sName, String sStreamType, String sContentLoc) Method to create a new application
<u>IApplication</u>	<u>getApplication</u> (String applicationName) Get application by name.
java.util.List	<u>getApplicationFolderNames</u> () Get a list of application folder names
edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock	<u>getApplicationLock</u> () Get the object used in synchronized statements to lock and application.
java.util.List	<u>getApplicationNames</u> () Get a list of application names
int	<u>getApplicationTimeout</u> () Get application time out (milliseconds).
AuthenticationList	<u>getAuthenticationList</u> () Get the list of available authentication methods
<u>IClient</u>	<u>getClient</u> (int clientId) Get client by client id.
<u>IClient</u>	<u>getClient</u> (int clientId, boolean create) Get client by client id and create if does not exist.
int	<u>getClientCount</u> () Get number of clients connected to this vHost.
int	<u>getClientIdleFrequency</u> () Get default client idle frequency (milliseconds)
int	<u>getClientTimeout</u> () Get client timeout.
<u>ConnectionCounter</u>	<u>getConnectionCounter</u> () Get vHost connection counter.
ConnectionCounterSimple	<u>getConnectionCounter</u> (int counterIndex) Get vHost connection counter for a specific technology (see IVHost.COUNTER_*)
int	<u>getConnectionLimit</u> () Get vHost connection limit.

int	<u>getCoreHandlerPoolSize()</u> Get the handler core thread pool size.
int	<u>getCoreTransportPoolSize()</u> Get the transport core thread pool size.
String	<u>getDateStarted()</u> Get date and time the server was started.
DvrRecorderList	<u>getDvrRecorderList()</u> Get the DvrRecorderList
DvrStoreList	<u>getDvrStoreList()</u> Get the list of DVR Stores
java.util.Properties	<u>getDynamicLogProperties()</u> Get the dynamic log properties defined at the vhost level in conf/log4j.properties
int	<u>getFileIOPoolSize()</u> Get the default file io pool size.
<u>ThreadPool</u>	<u>getHandlerThreadPool()</u> Get the VHost handler thread pool.
String	<u>getHomePath()</u> Get vHost configuration path.
<u>HostPortList</u>	<u>getHostPortsList()</u> Get list of host port definitions for vHost.
<u>IHTTPStreamerAdapter</u>	<u>getHTTPStreamerAdapter(String ID)</u> Get an HTTPStreamerAdapter by ID
java.util.List	<u>getHTTPStreamerAdapterIDs()</u> Get a list of HTTPStreamerAdapter IDs
HTTPStreamerContext	<u>getHTTPStreamerContext()</u> Get the HTTPStreamer (Cupertino Streaming and Silverlight Smooth Streaming) host context
HTTPStreamerList	<u>getHTTPStreamerList()</u> Get the list of HTTPStreamers
int	<u>getIdleCheckFrequency()</u> Get idle check frequency (milliseconds)
int	<u>getIdleMinimumWaitTime()</u> Get the minimum time (milliseconds) the idle worker thread will sleep before generating idle events
int	<u>getIdleWorkerCount()</u> Get number of threads used to generate idle events
IdleWorkersUtil	<u>getIdleWorkers()</u> Get the idle worker utility
<u>IOPerformanceCounter</u>	<u>getIoPerformanceCounter()</u> Get vHost IO performance counter.
<u>IOPerformanceCounter</u>	<u>getIoPerformanceCounter(int counterIndex)</u> Get vHost IO performance counter for a specific technology (see IVHost.COUNTER_*)

IOScheduler	getIOScheduler() Get IO scheduler for vHost.
int	getKeepAliveTimeout() Get the RTMPT connection keep alive timeout
LiveStreamPacketizerList	getLiveStreamPacketizerList() Get the LiveStreamPacketizerList
LiveStreamTranscoderList	getLiveStreamTranscoderList() Get the LiveStreamTranscoderList
int	getMaximumPendingReadBytes() Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
int	getMaximumPendingWriteBytes() Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
int	getMaximumSetBufferTime() Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
MediaCasterList	getMediaCasterList() Get the list of media caster definitions (MediaCaster.xml)
MediaCasterSettings	getMediaCasterSettings() Get the media caster settings
int	getMediaReaderContentType(String mediaType) Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE_*)
MediaReaderList	getMediaReaders() Get the media readers attached to vHost (MediaReaders.xml).
MediaWriterList	getMediaWriters() Get the media writers attached to vHost (MediaWriters.xml).
java.util.Map	getMp3TagMap() Get MP3 tag map attached to vHost (MP3Tags.xml).
String	getName() Get vHost name
HostPortConfig	getNetConnectionHostPortConfig() Get the socket configuration for server to server connections
int	getNetConnectionIdleFrequency() Get server to server idle frequency (milliseconds)
int	getNetConnectionProcessorCount() Get net connection processor count.
int	getNextNetConnectionId() Get next connection id.
int	getPingTimeout() Get ping timeout (milliseconds)

WMSProperties	getProperties() Get properties attached to this vHost.
String	getProperty(String key) Get virtual host property.
RTPContext	getRTPContext() Get the RTP (real time protocol) virtual host context
com.wowza.wms.rtp.transport.RTPUDPDatagramConfig	getRTPDatagramConfigIncoming() Get the RTP Datagram Socket configuration
com.wowza.wms.rtp.transport.RTPUDPDatagramConfig	getRTPDatagramConfigOutgoing() Get the RTP Datagram Socket configuration
int	getRTPIdleFrequency() Get default RTP idle frequency (milliseconds)
java.util.List	getStartupStreams() Get the list of streams to start at virtual host startup
StreamList	getStreamTypes() Get default stream type.
ThreadPool	getThreadPool() Get the VHost handler thread pool.
String	getTimeRunning() Get the time vHost has been running.
double	getTimeRunningSeconds() Get time running in seconds
ThreadPool	getTransportThreadPool() Get the VHost transport thread pool.
com.wowza.wms.rtp.transport.UDPTransportManager	getUDPTransportManager() Get the UDP transport manager.
int	getValidationFrequency() Get time between validation pings (milliseconds)
void	init(String basePath) Initialize vHost.
boolean	isApplicationLoaded(String applicationName) Return true is the application is loaded
boolean	isShuttingDown() Is the VHost shutting down
boolean	isStartStarupStreams() Returns true if the startup streams are to start and vhost startup
boolean	isSuspended() Returns true is all HostPorts connected to this VHost are suspended

void	<u>killClient</u> (int clientId) Remove client from vHost and send disconnect message.
void	<u>killRTSPSession</u> (String rtspSessionId) Kill an RTSP connection by the RTSP session id
void	<u>putHTTPStreamerAdapter</u> (String ID, <u>IHTTPStreamerAdapter</u> adapter) Add an HTTPStreamerAdapter
String	<u>readVHostConfig</u> (String sName) Method to read xml config file..
void	<u>removeAcceptorListener</u> (<u>IAcceptorNotify</u> acceptorListener) Remove acceptor listener.
boolean	<u>removeApplication</u> (String sName) Method to remove an application
void	<u>removeApplicationListener</u> (<u>IApplicationNotify</u> applicationListener) Remove applation listener.
void	<u>removeClient</u> (int clientId) Remove client from vHost.
void	<u>removeIdleWorkerListener</u> (<u>IIdleWorkerNotify</u> idleWorkerListener) Remove idleWorker listener
void	<u>reparentClient</u> (<u>IClient</u> client) Move a client object to a new vhost.
void	<u>setAdminInterfaceHostPort</u> (<u>HostPort</u> adminInterfaceHostPort) Set admin interface host port (not used)
void	<u>setApplicationTimeout</u> (int applicationTimeout) Set application time out (milliseconds).
void	<u>setClientIdleFrequency</u> (int clientIdleFrequency) Set default client idle frequency (milliseconds)
void	<u>setClientTimeout</u> (int clientTimeout) Set client timeout.
void	<u>setCoreHandlerPoolSize</u> (int corePoolSize) Set the handler core thread pool size.
void	<u>setCoreTransportPoolSize</u> (int corePoolSize) Set the transport core thread pool size.
void	<u>setDynamicLogProperties</u> (java.util.Properties dynamicLogProperties) Set the dynamic log properties set at the vhost level
void	<u>setFileIOPoolSize</u> (int fileIOPoolSize) Set default file io thread pool size.
void	<u>setIdleCheckFrequency</u> (int idleCheckFrequency) Set idle check frequency (milliseconds)
void	<u>setIdleMinimumWaitTime</u> (int idleMinimumWaitTime) Set the minimum time (milliseconds) the idle worker thread will sleep before generating idle events

void	<u>setIdleWorkerCount</u> (int idleWorkerCount) Set number of threads used to generate idle events
void	<u>setKeepAliveTimeout</u> (int keepAliveTimeout) Set the RTMPT connection keep alive timeout
void	<u>setMaximumPendingReadBytes</u> (int maximumPendingReaderBytes) Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated.
void	<u>setMaximumPendingWriteBytes</u> (int maximumPendingWriteBytes) Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated.
void	<u>setMaximumSetBufferTime</u> (int maximumSetBufferTime) Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call.
void	<u>setNetConnectionIdleFrequency</u> (int netConnectionIdleFrequency) Set the server to server idle frequency (milliseconds)
void	<u>setNetConnectionProcessorCount</u> (int netConnectionProcessorCount) Set net connection processor count.
void	<u>setPingTimeout</u> (int pingTimeout) Set ping timeout (milliseconds)
void	<u>setRTPIIdleFrequency</u> (int rtpIdleFrequency) Set default RTP idle frequency (milliseconds)
void	<u>setShuttingDown</u> (boolean shuttingDown) Set VHost shutting down flag
void	<u>setStartStarupStreams</u> (boolean startStarupStreams) Set to true to startup startup stream as vhost startup
void	<u>setValidationFrequency</u> (int validationFrequency) Set time between validation pings (milliseconds)
void	<u>shutdown</u> () Shutdown.
void	<u>shutdownApplication</u> (String appName) Shutdown an application by name.
boolean	<u>startApplicationInstance</u> (String appName) Start an application instance.
boolean	<u>startApplicationInstance</u> (String appName, String appInstanceName) Start an application instance.
void	<u>startStartupStreams</u> () Method to start startup streams
void	<u>stopStartupStreams</u> () Method to stop startup streams
void	<u>suspendAllHostPorts</u> () Suspend all HostPorts from accepting new connections.

boolean	<code>touchApplicationInstance</code> (String appName) Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds.
boolean	<code>touchApplicationInstance</code> (String appName, String appInstanceName) Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds.
void	<code>unbindAllHostPorts</code> () Unbind all HostPorts and drop all connections
void	<code>updateLoggingDuration</code> () Internal: update the internal logging values.
boolean	<code>writeVHostConfig</code> (String sName, String data) Method to write xml config file..

Fields

VHOST_DEFAULT

```
public static final java.lang.String VHOST_DEFAULT
```

Constant value: `_defaultVHost_`

LICENSECOUNTER_PUBLISHER

```
public static final int LICENSECOUNTER_PUBLISHER
```

Constant value: `0`

LICENSECOUNTER_TRANSCODE_DECODE

```
public static final int LICENSECOUNTER_TRANSCODE_DECODE
```

Constant value: `1`

LICENSECOUNTER_TRANSCODE_ENCODE

```
public static final int LICENSECOUNTER_TRANSCODE_ENCODE
```

Constant value: `2`

LICENSECOUNTER_NDVR

```
public static final int LICENSECOUNTER_NDVR
```

Constant value: `3`

LICENSECOUNTER_DRM_EZDRM_LIVE

```
public static final int LICENSECOUNTER_DRM_EZDRM_LIVE
```


(continued from last page)

Constant value: **4**

LICENSECOUNTER_DRM_EZDRM_VOD

```
public static final int LICENSECOUNTER_DRM_EZDRM_VOD
```

Constant value: **5**

LICENSECOUNTER_DRM_VERIMATRIX_LIVE

```
public static final int LICENSECOUNTER_DRM_VERIMATRIX_LIVE
```

Constant value: **6**

LICENSECOUNTER_DRM_VERIMATRIX_VOD

```
public static final int LICENSECOUNTER_DRM_VERIMATRIX_VOD
```

Constant value: **7**

LICENSECOUNTER_PUBLISHERTRANSCODER

```
public static final int LICENSECOUNTER_PUBLISHERTRANSCODER
```

Constant value: **8**

LICENSECOUNTER_TOTAL

```
public static final int LICENSECOUNTER_TOTAL
```

Constant value: **9**

COUNTER_RTMP

```
public static final int COUNTER_RTMP
```

Constant value: **0**

COUNTER_RTP

```
public static final int COUNTER_RTP
```

Constant value: **1**

COUNTER_HTTPCUPERTINO

```
public static final int COUNTER_HTTPCUPERTINO
```

Constant value: **2**

COUNTER_HTTPSMOOTH

```
public static final int COUNTER_HTTPSMOOTH
```

Constant value: **3**

COUNTER_HTTPSANJOSE

```
public static final int COUNTER_HTTPSANJOSE
```

Constant value: **4**

COUNTER_HTTPWEBM

```
public static final int COUNTER_HTTPWEBM
```

Constant value: **5**

COUNTER_TOTAL

```
public static final int COUNTER_TOTAL
```

Constant value: **6**

COUNTER_HTTPDVRCHUNKS

```
public static final int COUNTER_HTTPDVRCHUNKS
```

Constant value: **7**

CODEC_VIDEO_UNKNOWN

```
public static final int CODEC_VIDEO_UNKNOWN
```

Constant value: **-1**

CODEC_VIDEO_SPARK

```
public static final int CODEC_VIDEO_SPARK
```

Constant value: **2**

CODEC_VIDEO_SCREEN

```
public static final int CODEC_VIDEO_SCREEN
```

Constant value: **3**

(continued from last page)

CODEC_VIDEO_VP6

```
public static final int CODEC_VIDEO_VP6
```

Constant value: **4**

CODEC_VIDEO_VP6A

```
public static final int CODEC_VIDEO_VP6A
```

Constant value: **5**

CODEC_VIDEO_SCREEN2

```
public static final int CODEC_VIDEO_SCREEN2
```

Constant value: **6**

CODEC_VIDEO_H264

```
public static final int CODEC_VIDEO_H264
```

Constant value: **7**

CODEC_VIDEO_VP8

```
public static final int CODEC_VIDEO_VP8
```

Constant value: **8**

CODEC_VIDEO_H263

```
public static final int CODEC_VIDEO_H263
```

Constant value: **9**

CODEC_VIDEO_MPEG4

```
public static final int CODEC_VIDEO_MPEG4
```

Constant value: **10**

CODEC_VIDEO_MPEG2

```
public static final int CODEC_VIDEO_MPEG2
```

Constant value: **11**

CODEC_AUDIO_UNKNOWN

```
public static final int CODEC_AUDIO_UNKNOWN
```

(continued from last page)

Constant value: **-1**

CODEC_AUDIO_PCM_BE

```
public static final int CODEC_AUDIO_PCM_BE
```

Constant value: **0**

CODEC_AUDIO_PCM_SWF

```
public static final int CODEC_AUDIO_PCM_SWF
```

Constant value: **1**

CODEC_AUDIO_MP3

```
public static final int CODEC_AUDIO_MP3
```

Constant value: **2**

CODEC_AUDIO_PCM_LE

```
public static final int CODEC_AUDIO_PCM_LE
```

Constant value: **3**

CODEC_AUDIO_NELLYMOSER_16MONO

```
public static final int CODEC_AUDIO_NELLYMOSER_16MONO
```

Constant value: **4**

CODEC_AUDIO_NELLYMOSER_8MONO

```
public static final int CODEC_AUDIO_NELLYMOSER_8MONO
```

Constant value: **5**

CODEC_AUDIO_NELLYMOSER

```
public static final int CODEC_AUDIO_NELLYMOSER
```

Constant value: **6**

CODEC_AUDIO_G711_ALAW

```
public static final int CODEC_AUDIO_G711_ALAW
```

Constant value: **7**

CODEC_AUDIO_G711_MULAW

```
public static final int CODEC_AUDIO_G711_MULAW
```

Constant value: **8**

CODEC_AUDIO_RESERVED

```
public static final int CODEC_AUDIO_RESERVED
```

Constant value: **9**

CODEC_AUDIO_VORBIS

```
public static final int CODEC_AUDIO_VORBIS
```

Constant value: **9**

CODEC_AUDIO_AAC

```
public static final int CODEC_AUDIO_AAC
```

Constant value: **10**

CODEC_AUDIO_SPEEX

```
public static final int CODEC_AUDIO_SPEEX
```

Constant value: **11**

CODEC_AUDIO_MP3_8

```
public static final int CODEC_AUDIO_MP3_8
```

Constant value: **15**

CODEC_STREAM_UNKNOWN

```
public static final int CODEC_STREAM_UNKNOWN
```

Constant value: **-1**

CODEC_STREAM_MP2T

```
public static final int CODEC_STREAM_MP2T
```

Constant value: **0**

(continued from last page)

FILEFORMAT_UNKNOWN

```
public static final int FILEFORMAT_UNKNOWN
```

Constant value: **-1**

FILEFORMAT_FLV

```
public static final int FILEFORMAT_FLV
```

Constant value: **1**

FILEFORMAT_MP4

```
public static final int FILEFORMAT_MP4
```

Constant value: **2**

CONTENTTYPE_UNKNOWN

```
public static final byte CONTENTTYPE_UNKNOWN
```

AMF Content type: unknown
Constant value: **0**

CONTENTTYPE_SETCHUNKSIZE

```
public static final byte CONTENTTYPE_SETCHUNKSIZE
```

AMF Content type: set packet chunk size
Constant value: **1**

CONTENTTYPE_WATCHDOG

```
public static final byte CONTENTTYPE_WATCHDOG
```

AMF Content type: watch dog
Constant value: **3**

CONTENTTYPE_BUFFERSIZE

```
public static final byte CONTENTTYPE_BUFFERSIZE
```

AMF Content type: set buffer size
Constant value: **4**

CONTENTTYPE_ACKBANDWIDTH

```
public static final byte CONTENTTYPE_ACKBANDWIDTH
```

AMF Content type: set acknowledge bandwidth size
Constant value: **5**

CONTENTTYPE_SETBANDWIDTH

```
public static final byte CONTENTTYPE_SETBANDWIDTH
```

(continued from last page)

AMF Content type: set bandwidth size
Constant value: **6**

CONTENTTYPE_AUDIO

public static final byte **CONTENTTYPE_AUDIO**

AMF Content type: audio packet
Constant value: **8**

CONTENTTYPE_VIDEO

public static final byte **CONTENTTYPE_VIDEO**

AMF Content type: video packet
Constant value: **9**

CONTENTTYPE_DATA

public static final byte **CONTENTTYPE_DATA**

AMF Content type: data packet
Constant value: **18**

CONTENTTYPE_DATA0

public static final byte **CONTENTTYPE_DATA0**

AMF Content type: data packet (AMF0)
Constant value: **18**

CONTENTTYPE_DATA3

public static final byte **CONTENTTYPE_DATA3**

AMF Content type: data packet (AMF3)
Constant value: **15**

CONTENTTYPE_SHAREDOBJECTS

public static final byte **CONTENTTYPE_SHAREDOBJECTS**

AMF Content type: shared object packet (AMF0)
Constant value: **19**

CONTENTTYPE_SHAREDOBJECTS0

public static final byte **CONTENTTYPE_SHAREDOBJECTS0**

AMF Content type: shared object packet (AMF0)
Constant value: **19**

CONTENTTYPE_SHAREDOBJECTS3

public static final byte **CONTENTTYPE_SHAREDOBJECTS3**

AMF Content type: shared object packet (AMF3)
Constant value: **16**

CONTENTTYPE_FUNCTION

public static final byte **CONTENTTYPE_FUNCTION**

AMF Content type: function data (AMF0)
Constant value: **20**

CONTENTTYPE_FUNCTION0

public static final byte **CONTENTTYPE_FUNCTION0**

AMF Content type: function data (AMF0)
Constant value: **20**

CONTENTTYPE_MEDIACHUNK

public static final byte **CONTENTTYPE_MEDIACHUNK**

AMF Content type: media chunk
Constant value: **22**

CONTENTTYPE_FUNCTION3

public static final byte **CONTENTTYPE_FUNCTION3**

AMF Content type: function data (AMF3)
Constant value: **17**

CONTENTTYPE_PLAYCALLBACK

public static final byte **CONTENTTYPE_PLAYCALLBACK**

AMF Content type: play callback
Constant value: **127**

ACCEPTORS_ACCEPTOR

public static final java.lang.String **ACCEPTORS_ACCEPTOR**

Acceptor types: acceptor
Constant value: **acceptor**

ACCEPTORS_HANDLERADAPTER

public static final java.lang.String **ACCEPTORS_HANDLERADAPTER**

Acceptor types: handler
Constant value: **handlerAdapter**

Methods

init

public void **init**(String basePath)

Initialize vHost.

Parameters:

(continued from last page)

basePath - base path to configuration files

shutdown

```
public void shutdown()
```

Shutdown.

getStreamTypes

```
public StreamList getStreamTypes()
```

Get default stream type.

Returns:

default stream type

getProperty

```
public String getProperty(String key)
```

Get virtual host property.

Parameters:

key - key

Returns:

property value or null if does not exist

getClientTimeout

```
public int getClientTimeout()
```

Get client timeout.

Returns:

client timeout

getNextNetConnectionId

```
public int getNextNetConnectionId()
```

Get next connection id.

Returns:

next connection id

getClient

```
public IClient getClient(int clientId)
```

Get client by client id.

Parameters:

clientId - client id

Returns:

client

getClient

```
public IClient getClient(int clientId,  
                        boolean create)
```

Get client by client id and create if does not exist.

Parameters:

clientId - client id
create - create if does not exist

Returns:

client

removeClient

```
public void removeClient(int clientId)
```

Remove client from vHost.

Parameters:

clientId - client id

killClient

```
public void killClient(int clientId)
```

Remove client from vHost and send disconnect message.

Parameters:

clientId - client id

killRTSPSession

```
public void killRTSPSession(String rtspSessionId)
```

Kill an RTSP connection by the RTSP session id

Parameters:

rtspSessionId - RTSP session id

getApplication

```
public IApplication getApplication(String applicationName)
```

Get application by name.

Parameters:

applicationName - application name

Returns:

application

isApplicationLoaded

```
public boolean isApplicationLoaded(String applicationName)
```

Return true is the application is loaded

(continued from last page)

Parameters:

applicationName - application name

Returns:

true if application is loaded

getHomePath

```
public String getHomePath()
```

Get vHost configuration path.

Returns:

configuration path

getProperties

```
public WMSProperties getProperties()
```

Get properties attached to this vHost.

Returns:

properties attached to this vHost

getCoreTransportPoolSize

```
public int getCoreTransportPoolSize()
```

Get the transport core thread pool size.

Returns:

default core thread pool size

setCoreTransportPoolSize

```
public void setCoreTransportPoolSize(int corePoolSize)
```

Set the transport core thread pool size.

Parameters:

corePoolSize - core thread pool size

getCoreHandlerPoolSize

```
public int getCoreHandlerPoolSize()
```

Get the handler core thread pool size.

Returns:

default core thread pool size

setCoreHandlerPoolSize

```
public void setCoreHandlerPoolSize(int corePoolSize)
```

Set the handler core thread pool size.

(continued from last page)

Parameters:

corePoolSize - core thread pool size

getFileIOPoolSize

```
public int getFileIOPoolSize()
```

Get the default file io pool size.

Returns:

default file io pool size

setFileIOPoolSize

```
public void setFileIOPoolSize(int fileIOPoolSize)
```

Set default file io thread pool size.

Parameters:

fileIOPoolSize - default file io thread pool size

setClientTimeout

```
public void setClientTimeout(int clientTimeout)
```

Set client timeout. An inactive client connected by RTMPT protocol will be deleted after this timeout.

Parameters:

clientTimeout - client timeout

getHostPortsList

```
public HostPortList getHostPortsList()
```

Get list of host port definitions for vHost.

Returns:

list of host port definitions for vHost

getThreadPool

```
public ThreadPool getThreadPool()
```

Get the VHost handler thread pool. Same as getHandlerThreadPool.

Returns:

VHost handler thread pool

getTransportThreadPool

```
public ThreadPool getTransportThreadPool()
```

Get the VHost transport thread pool. This thread pool is used to read/write data from the transports sockets.

Returns:

VHost transport thread pool

(continued from last page)

getHandlerThreadPool

```
public ThreadPool getHandlerThreadPool()
```

Get the VHost handler thread pool. This thread pool is used to process the incoming events.

Returns:

VHost handler thread pool

getName

```
public String getName()
```

Get vHost name

Returns:

vHost name

setAdminInterfaceHostPort

```
public void setAdminInterfaceHostPort(HostPort adminInterfaceHostPort)
```

Set admin interface host port (not used)

Parameters:

adminInterfaceHostPort - admin interface host port

getClientCount

```
public int getClientCount()
```

Get number of clients connected to this vHost.

Returns:

number of clients connected to this vHost

getNetConnectionProcessorCount

```
public int getNetConnectionProcessorCount()
```

Get net connection processor count. Number of threads used for server to server communication (not finished).

Returns:

net connection processor count

setNetConnectionProcessorCount

```
public void setNetConnectionProcessorCount(int netConnectionProcessorCount)
```

Set net connection processor count. Number of threads used for server to server communication (not finished).

Parameters:

netConnectionProcessorCount - net connection processor count

addApplicationListener

```
public void addApplicationListener(IApplicationNotify applicationListener)
```

(continued from last page)

Add application listener. An application listener will receive the following events: onApplicationCreate, onApplicationDestroy.

Parameters:

applicationListener - application listener

removeApplicationListener

```
public void removeApplicationListener(IApplicationNotify applicationListener)
```

Remove application listener.

Parameters:

applicationListener - application listener

addAcceptorListener

```
public void addAcceptorListener(IAcceptorNotify acceptorListener)
```

Add acceptor listener. Acceptor listeners will receive the following events: onAcceptorCreate, onAcceptorDestroy.

Parameters:

acceptorListener - acceptor listener

removeAcceptorListener

```
public void removeAcceptorListener(IAcceptorNotify acceptorListener)
```

Remove acceptor listener.

Parameters:

acceptorListener - acceptor listener

getIOScheduler

```
public IOScheduler getIOScheduler()
```

Get IO scheduler for vHost. IO scheduler is used to schedule reads from the disk to increase server throughput for static flv serving.

Returns:

IO scheduler for vHost

getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter()
```

Get vHost IO performance counter.

Returns:

io performance counter

getIoPerformanceCounter

```
public IoPerformanceCounter getIoPerformanceCounter(int counterIndex)
```

Get vHost IO performance counter for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

(continued from last page)

Returns:

io performance counter

getConnectionCounter

```
public ConnectionCounter getConnectionCounter()
```

Get vHost connection counter.

Returns:

connection counter

getConnectionCounter

```
public ConnectionCounterSimple getConnectionCounter(int counterIndex)
```

Get vHost connection counter for a specific technology (see IVHost.COUNTER_*)

Parameters:

counterIndex - counter index (see IVHost.COUNTER_*)

Returns:

connection counter

getDateStarted

```
public String getDateStarted()
```

Get date and time the server was started.

Returns:

date and time the server was started

getTimeRunning

```
public String getTimeRunning()
```

Get the time vHost has been running.

Returns:

formatted string with vHost uptime

getTimeRunningSeconds

```
public double getTimeRunningSeconds()
```

Get time running in seconds

Returns:

time running in seconds

getConnectionLimit

```
public int getConnectionLimit()
```

Get vHost connection limit.

(continued from last page)

Returns:

vHost connection limit

getMediaReaders

```
public MediaReaderList getMediaReaders()
```

Get the media readers attached to vHost (MediaReaders.xml).

Returns:

media readers attached to vHost

getMediaWriters

```
public MediaWriterList getMediaWriters()
```

Get the media writers attached to vHost (MediaWriters.xml).

Returns:

media writers attached to vHost

getMp3TagMap

```
public java.util.Map getMp3TagMap()
```

Get MP3 tag map attached to vHost (MP3Tags.xml).

Returns:

MP3 tag map attached to vHost

updateLoggingDuration

```
public void updateLoggingDuration()
```

Internal: update the internal logging values.

getApplicationTimeout

```
public int getApplicationTimeout()
```

Get application time out (milliseconds). Time from last client disconnect to application destruction.

Returns:

application time out (milliseconds)

setApplicationTimeout

```
public void setApplicationTimeout(int applicationTimeout)
```

Set application time out (milliseconds).

Parameters:

applicationTimeout - application time out (milliseconds)

getPingTimeout

```
public int getPingTimeout()
```


(continued from last page)

Get ping timeout (milliseconds)

Returns:

ping timeout (milliseconds)

setPingTimeout

```
public void setPingTimeout(int pingTimeout)
```

Set ping timeout (milliseconds)

Parameters:

pingTimeout - ping timeout (milliseconds)

getValidationFrequency

```
public int getValidationFrequency()
```

Get time between validation pings (milliseconds)

Returns:

time between validation pings (milliseconds)

setValidationFrequency

```
public void setValidationFrequency(int validationFrequency)
```

Set time between validation pings (milliseconds)

Parameters:

validationFrequency - time between validation pings (milliseconds)

getMaximumPendingWriteBytes

```
public int getMaximumPendingWriteBytes()
```

Get maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

Returns:

maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

setMaximumPendingWriteBytes

```
public void setMaximumPendingWriteBytes(int maximumPendingWriteBytes)
```

Set maximum number a bytes a client connection can have waiting to be sent before the connection is terminated. If set to zero this feature is turned off.

Parameters:

maximumPendingWriteBytes - maximum number a bytes a client connection can have waiting to be sent before the connection is terminated

getMaximumPendingReadBytes

```
public int getMaximumPendingReadBytes()
```

Set maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

(continued from last page)

Returns:

maximum number of bytes a client connection can have waiting to be written before the connection is terminated

setMaximumPendingReadBytes

```
public void setMaximumPendingReadBytes(int maximumPendingReaderBytes)
```

Get maximum number of bytes a client connection can have waiting to be written before the connection is terminated. If set to zero this feature is off.

Parameters:

maximumPendingReaderBytes - maximum number of bytes a client connection can have waiting to be written before the connection is terminated

getMaximumSetBufferTime

```
public int getMaximumSetBufferTime()
```

Get maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

Returns:

maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

setMaximumSetBufferTime

```
public void setMaximumSetBufferTime(int maximumSetBufferTime)
```

Set maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call. If set to zero this feature is turned off.

Parameters:

maximumSetBufferTime - maximum number of milliseconds allowed for the NetStream.setBufferTime(secs) call

getApplicationLock

```
public edu.emory.mathcs.backport.java.util.concurrent.locks.WMSReadWriteLock  
getApplicationLock()
```

Get the object used in synchronized statements to lock and application.

Returns:

object used in synchronized statements to lock and application

getClientIdleFrequency

```
public int getClientIdleFrequency()
```

Get default client idle frequency (milliseconds)

Returns:

default client idle frequency (milliseconds)

setClientIdleFrequency

```
public void setClientIdleFrequency(int clientIdleFrequency)
```

Set default client idle frequency (milliseconds)

(continued from last page)

Parameters:

clientIdFrequency - default client idle frequency (milliseconds)

getRTPIdleFrequency

```
public int getRTPIdleFrequency( )
```

Get default RTP idle frequency (milliseconds)

Returns:

default RTP idle frequency (milliseconds)

setRTPIdleFrequency

```
public void setRTPIdleFrequency(int rtpIdleFrequency)
```

Set default RTP idle frequency (milliseconds)

Parameters:

rtpIdleFrequency - RTP default client idle frequency (milliseconds)

getNetConnectionIdleFrequency

```
public int getNetConnectionIdleFrequency( )
```

Get server to server idle frequency (milliseconds)

Returns:

server to server idle frequency (milliseconds)

setNetConnectionIdleFrequency

```
public void setNetConnectionIdleFrequency(int netConnectionIdleFrequency)
```

Set the server to server idle frequency (milliseconds)

Parameters:

netConnectionIdleFrequency - server to server idle frequency (milliseconds)

getIdleCheckFrequency

```
public int getIdleCheckFrequency( )
```

Get idle check frequency (milliseconds)

Returns:

idle check frequency (milliseconds)

setIdleCheckFrequency

```
public void setIdleCheckFrequency(int idleCheckFrequency)
```

Set idle check frequency (milliseconds)

Parameters:

idleCheckFrequency - idle check frequency (milliseconds)

getIdleWorkerCount

```
public int getIdleWorkerCount()
```

Get number of threads used to generate idle events

Returns:

number of threads used to generate idle events

setIdleWorkerCount

```
public void setIdleWorkerCount(int idleWorkerCount)
```

Set number of threads used to generate idle events

Parameters:

idleWorkerCount - number of threads used to generate idle events

getKeepAliveTimeout

```
public int getKeepAliveTimeout()
```

Get the RTMPT connection keep alive timeout

Returns:

RTMPT connection keep alive timeout

setKeepAliveTimeout

```
public void setKeepAliveTimeout(int keepAliveTimeout)
```

Set the RTMPT connection keep alive timeout

Parameters:

keepAliveTimeout - RTMPT connection keep alive timeout

addIdleWorkerListener

```
public void addIdleWorkerListener(IIdleWorkerNotify idleWorkerListener)
```

Add idleWorker listener. An idleWorker listener will receive the following events: onIdleWorkerCreate, onIdleWorkerDestroy.

Parameters:

idleWorkerListener - idleWorker listener

removeIdleWorkerListener

```
public void removeIdleWorkerListener(IIdleWorkerNotify idleWorkerListener)
```

Remove idleWorker listener

Parameters:

idleWorkerListener - idleWorker listener

getNetConnectionHostPortConfig

```
public HostPortConfig getNetConnectionHostPortConfig()
```

(continued from last page)

Get the socket configuration for server to server connections

Returns:

socket configuration for server to server connections

getMediaCasterSettings

```
public MediaCasterSettings getMediaCasterSettings()
```

Get the media caster settings

Returns:

media caster settings

getMediaCasterList

```
public MediaCasterList getMediaCasterList()
```

Get the list of media caster definitions (MediaCaster.xml)

Returns:

list of media caster definitions

getApplicationNames

```
public java.util.List getApplicationNames()
```

Get a list of application names

Returns:

list of application names

getApplicationFolderNames

```
public java.util.List getApplicationFolderNames()
```

Get a list of application folder names

Returns:

list of application folder names

applicationExists

```
public boolean applicationExists(String name)
```

Return true if an application folder exists for this application name

Parameters:

name - application name

Returns:

true if an application folder exists for this application name

getRTPContext

```
public RTPContext getRTPContext()
```

Get the RTP (real time protocol) virtual host context

(continued from last page)

Returns:

RTP (real time protocol) virtual host context

getHTTPStreamerContext

```
public HTTPStreamerContext getHTTPStreamerContext()
```

Get the HTTPStreamer (Cupertino Streaming and Silverlight Smooth Streaming) host context

Returns:

HTTPStreamer (Cupertino Streaming and Silverlight Smooth Streaming) host context

getRTPDatagramConfigIncoming

```
public com.wowza.wms.rtp.transport.RTPUDPDatagramConfig getRTPDatagramConfigIncoming()
```

Get the RTP Datagram Socket configuration

Returns:

RTP Datagram Socket configuration

getRTPDatagramConfigOutgoing

```
public com.wowza.wms.rtp.transport.RTPUDPDatagramConfig getRTPDatagramConfigOutgoing()
```

Get the RTP Datagram Socket configuration

Returns:

RTP Datagram Socket configuration

getAuthenticationList

```
public AuthenticationList getAuthenticationList()
```

Get the list of available authentication methods

Returns:

list of available authentication methods

getIdleMinimumWaitTime

```
public int getIdleMinimumWaitTime()
```

Get the minimum time (milliseconds) the idle worker thread will sleep before generating idle events

Returns:

minimum time (milliseconds) the idle worker thread will sleep before generating idle events

setIdleMinimumWaitTime

```
public void setIdleMinimumWaitTime(int idleMinimumWaitTime)
```

Set the minimum time (milliseconds) the idle worker thread will sleep before generating idle events

Parameters:

idleMinimumWaitTime - minimum time (milliseconds) the idle worker thread will sleep before generating idle events

getIdleWorkers

```
public IdleWorkersUtil getIdleWorkers()
```

Get the idle worker utility

Returns:

idle worker utility

isShuttingDown

```
public boolean isShuttingDown()
```

Is the VHost shutting down

Returns:

true if the vhost is shutting down

setShuttingDown

```
public void setShuttingDown(boolean shuttingDown)
```

Set VHost shutting down flag

Parameters:

shuttingDown - true if the vhost is shutting down

reparentClient

```
public void reparentClient(IClient client)
```

Move a client object to a new vhost. This can only be done right after the handshake process has completed. See `IVHostNotify.onVHostClientConnect`.

Parameters:

client - client object to move

getDynamicLogProperties

```
public java.util.Properties getDynamicLogProperties()
```

Get the dynamic log properties defined at the vhost level in `conf/log4j.properties`

Returns:

dynamic log properties defined at the vhost level

setDynamicLogProperties

```
public void setDynamicLogProperties(java.util.Properties dynamicLogProperties)
```

Set the dynamic log properties set at the vhost level

Parameters:

dynamicLogProperties - dynamic log properties defined at the vhost level

(continued from last page)

shutdownApplication

```
public void shutdownApplication(String appName)
```

Shutdown an application by name. This will disconnect all clients connected to all child application instances.

Parameters:

appName - application name

unbindAllHostPorts

```
public void unbindAllHostPorts()
```

Unbind all HostPorts and drop all connections

suspendAllHostPorts

```
public void suspendAllHostPorts()
```

Suspend all HostPorts from accepting new connections. Current connections will continue to be serviced

closeHostPort

```
public void closeHostPort(HostPort hostPort,  
    boolean isSuspend)
```

Close an individual HostPort

Parameters:

hostPort - host port to close

isSuspend - if true will just suspend the HostPort from accepting new connections, if false will unbind and drop all connections

isSuspended

```
public boolean isSuspended()
```

Returns true if all HostPorts connected to this VHost are suspended

touchApplicationInstance

```
public boolean touchApplicationInstance(String appName)
```

Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds.

Parameters:

appName - application name

Returns:

true is successful

touchApplicationInstance

```
public boolean touchApplicationInstance(String appName,  
    String appInstanceName)
```

Start an application instance if it is not already started then touch it so it stays loaded for at least 3 seconds. The default appInstanceName `_default_` will be used.

(continued from last page)

Parameters:

appName - application name
appInstanceName - app instance name

Returns:

true is successful

startApplicationInstance

```
public boolean startApplicationInstance(String appName)
```

Start an application instance. The default appInstanceName _definst_ will be used.

Parameters:

appName - application name

Returns:

true is successful

startApplicationInstance

```
public boolean startApplicationInstance(String appName,  
String appInstanceName)
```

Start an application instance.

Parameters:

appName - application name
appInstanceName - app instance name

Returns:

true is successful

getUDPTransportManager

```
public com.wowza.wms.rtp.transport.UDPTransportManager getUDPTransportManager()
```

Get the UDP transport manager.

Returns:

UDP transport manager

getHTTPStreamerList

```
public HTTPStreamerList getHTTPStreamerList()
```

Get the list of HTTPStreamers

Returns:

list of HTTPStreamers

getHTTPStreamerAdapter

```
public IHTTPStreamerAdapter getHTTPStreamerAdapter(String ID)
```

Get an HTTPStreamerAdapter by ID

Parameters:

ID - HTTPStreamerAdapter ID

(continued from last page)

Returns:

HTTPStreamerAdapter

putHTTPStreamerAdapter

```
public void putHTTPStreamerAdapter(String ID,  
    IHTTPStreamerAdapter adapter)
```

Add an HTTPStreamerAdapter

Parameters:

ID - HTTPStreamerAdapter ID

adapter - HTTPStreamerAdapter

getHTTPStreamerAdapterIDs

```
public java.util.List getHTTPStreamerAdapterIDs()
```

Get a list of HTTPStreamerAdapter IDs

Returns:

list of HTTPStreamerAdapter IDs

getLiveStreamPacketizerList

```
public LiveStreamPacketizerList getLiveStreamPacketizerList()
```

Get the LiveStreamPacketizerList

Returns:

LiveStreamPacketizerList

getLiveStreamTranscoderList

```
public LiveStreamTranscoderList getLiveStreamTranscoderList()
```

Get the LiveStreamTranscoderList

Returns:

LiveStreamTranscoderList

getStartupStreams

```
public java.util.List getStartupStreams()
```

Get the list of streams to start at virtual host startup

Returns:

list of streams to start at virtual host startup

addStartupStream

```
public void addStartupStream(StartupStream startupStream)
```

Add a stream to the list of streams to start and virtual host startup

Parameters:

startupStream - startup stream

isStartStarupStreams

```
public boolean isStartStarupStreams()
```

Returns true if the startup streams are to start and vhost startup

Returns:

true if the startup streams are to start and vhost startup

setStartStarupStreams

```
public void setStartStarupStreams(boolean startStarupStreams)
```

Set to true to startup startup stream as vhost startup

Parameters:

startStarupStreams - true if the startup streams are to start and vhost startup

startStartupStreams

```
public void startStartupStreams()
```

Method to start startup streams

stopStartupStreams

```
public void stopStartupStreams()
```

Method to stop startup streams

createApplication

```
public boolean createApplication(String sName,  
    String sStreamType,  
    String sContentLoc)
```

Method to create a new application

removeApplication

```
public boolean removeApplication(String sName)
```

Method to remove an application

readVHostConfig

```
public String readVHostConfig(String sName)
```

Method to read xml config file..

writeVHostConfig

```
public boolean writeVHostConfig(String sName,  
    String data)
```

Method to write xml config file..

(continued from last page)

getDvrRecorderList

```
public DvrRecorderList getDvrRecorderList()
```

Get the DvrRecorderList

Returns:

list of DVR Recorders

getDvrStoreList

```
public DvrStoreList getDvrStoreList()
```

Get the list of DVR Stores

Returns:

list of DVR Stores

getMediaReaderContentType

```
public int getMediaReaderContentType(String mediaType)
```

Get the content type of a media stream name prefix (see IMediaReader.CONTENTTYPE_*)

Parameters:

mediaType - mediaType (such as flv or smil)

Returns:

content type (see IMediaReader.CONTENTTYPE_*)

com.wowza.wms.vhost Interface IVHostItemNotify

public interface **IVHostItemNotify**
extends

IVHostItemNotify: listener interface used by VHostList addVHostItemListener

VHostList is the list vHost definitions in VHosts.xml not the vHosts themselves. With this listener interface you can monitor the vHost definition changes.

Method Summary

void	onVHostItemCreate (VHostItem vhostItem) Triggered when vHostItem created
void	onVHostItemDestroy (VHostItem vhostItem) Triggered when vHostItem destroyed
void	onVHostItemUpdate (VHostItem vhostItem) Triggered when vHostItem updated

Methods

onVHostItemCreate

public void **onVHostItemCreate**([VHostItem](#) vhostItem)

Triggered when vHostItem created

Parameters:

vhostItem - vhostItem

onVHostItemUpdate

public void **onVHostItemUpdate**([VHostItem](#) vhostItem)

Triggered when vHostItem updated

Parameters:

vhostItem - vhostItem

onVHostItemDestroy

public void **onVHostItemDestroy**([VHostItem](#) vhostItem)

Triggered when vHostItem destroyed

Parameters:

vhostItem - vhostItem

com.wowza.wms.vhost Interface IVHostNotify

public interface **IVHostNotify**
extends

IVHostNotify: listener interface used by VHostSingleton addVHostListener

Method Summary

void	onVHostClientConnect (IVHost vhost, IClient inClient, com.wowza.wms.request.RequestFunction function, AMFDataList params) Triggered before a client connects to this virtual host.
void	onVHostCreate (IVHost vhost) Triggered when vHost created
void	onVHostInit (IVHost vhost) Triggered when vHost initialized
void	onVHostShutdownComplete (IVHost vhost) Triggered at the end of vhost shutdown
void	onVHostShutdownStart (IVHost vhost) Triggered at the beginning of vhost shutdown

Methods

onVHostCreate

public void **onVHostCreate**([IVHost](#) vhost)

Triggered when vHost created

Parameters:

vhost

onVHostInit

public void **onVHostInit**([IVHost](#) vhost)

Triggered when vHost initialized

Parameters:

vhost - vhost

onVHostShutdownStart

public void **onVHostShutdownStart**([IVHost](#) vhost)

Triggered at the beginning of vhost shutdown

(continued from last page)

Parameters:vhost - vhost

onVHostShutdownComplete

```
public void onVHostShutdownComplete(IVHost vhost)
```

Triggered at the end of vhost shutdown

Parameters:vhost - vhost

onVHostClientConnect

```
public void onVHostClientConnect(IVHost vhost,  
    IClient inClient,  
    com.wowza.wms.request.RequestFunction function,  
    AMFDataList params)
```

Triggered before a client connects to this virtual host. Provides an opportunity to rewrite the information that is being used to connect.

Parameters:

vhost

inClient - client object of the connection

function - function

params - parameters

com.wowza.wms.vhost Interface IWorkerThreadClear

public interface **IWorkerThreadClear**
extends

IWorkerThreadClear: Internal use.

Method Summary

void	clear()
void	reset()

Methods

reset

public void **reset**()

clear

public void **clear**()

com.wowza.wms.vhost Class StreamItem

java.lang.Object

└─com.wowza.wms.vhost.StreamItem

public class **StreamItem**
extends Object

StreamItem: data object that defines a streamType.

Constructor Summary

public	StreamItem (String name, String baseClass, String playClass) Create a new streamItem
--------	---------------------------------------------------------------------------------------------------------

Method Summary

void	clearProperty (String name) Clear property.
String	getBaseClass () Get base class path.
String	getDescription () Get streamType description.
String	getName () Get streamType name.
String	getPlayClass () Get play class path.
WMSProperties	getProperties () Get properties.
String	getProperty (String name) Get property by name.
void	setBaseClass (String baseClass) Set base class path.
void	setDescription (String description) Set streamType description.
void	setName (String name) Set streamType name.
void	setPlayClass (String playClass) Set play class path.
void	setProperty (String name, String value) Set property value.

String	toString()
--------	----------------------------

Methods inherited from class `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructors

StreamItem

```
public StreamItem(String name,  
                  String baseClass,  
                  String playClass)
```

Create a new streamItem

Parameters:

name - streamType name
baseClass - base class path
playClass - play class path

Methods

getBaseClass

```
public String getBaseClass()
```

Get base class path.

Returns:

base clas path

setBaseClass

```
public void setBaseClass(String baseClass)
```

Set base class path.

Parameters:

baseClass - base class path

getName

```
public String getName()
```

Get streamType name.

Returns:

streamType name

setName

```
public void setName(String name)
```

(continued from last page)

Set streamType name.

Parameters:

name - streamType name

getPlayClass

```
public String getPlayClass()
```

Get play class path.

Returns:

play class path

setPlayClass

```
public void setPlayClass(String playClass)
```

Set play class path.

Parameters:

playClass - play class path

setProperty

```
public void setProperty(String name,  
                        String value)
```

Set property value.

Parameters:

name - property name

value - property value

clearProperty

```
public void clearProperty(String name)
```

Clear property.

Parameters:

name - property name

getProperty

```
public String getProperty(String name)
```

Get property by name.

Parameters:

name - property name

Returns:

property value

getProperties

```
public WMSProperties getProperties()
```

(continued from last page)

Get properties.

Returns:

properties

getDescription

```
public String getDescription()
```

Get streamType description.

Returns:

streamType description

setDescription

```
public void setDescription(String description)
```

Set streamType description.

Parameters:

description - streamType description

toString

```
public String toString()
```

com.wowza.wms.vhost Class StreamList

java.lang.Object

└─com.wowza.wms.vhost.StreamList

```
public class StreamList
    extends Object
```

StreamList: collection of StreamItems

Constructor Summary

public	StreamList() Create empty StreamList
--------	---------------------------------------------------------

Method Summary

StreamItem	getStreamDef(String name) Get streamItem by streamType name.
java.util.Map	getStreamDefs() Get Map of streamItems (by streamType names).
java.util.List	getStreamTypeNames() Get list of streamType names.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

StreamList

```
public StreamList()
```

Create empty StreamList

Methods

getStreamDefs

```
public java.util.Map getStreamDefs()
```

Get Map of streamItems (by streamType names).

Returns:

Map of streamItems

getStreamTypeNames

```
public java.util.List getStreamTypeNames()
```

Get list of streamType names. Returns shallow copy of list.

Returns:

list of streamType names

getStreamDef

```
public StreamItem getStreamDef(String name)
```

Get streamItem by streamType name.

Parameters:

name - streamType name

Returns:

streamItem

com.wowza.wms.vhost Class ThreadPool

java.lang.Object

└─com.wowza.wms.vhost.ThreadPool

public class **ThreadPool**
extends Object

ThreadPool: class for managing a pool of threads.

Constructor Summary

public	ThreadPool (IVHost vhost, String name) Create a new thread pool attached to a vHost.
--------	--------------------------------------------------------------------------------------------------------------------------

Method Summary

void	execute (Runnable command) Execute a runnable object.
int	getActiveCount () Get number of active threads.
java.util.concurrent. Executor	getExecutor () Get the underlying Executor pool.
int	getQueueSize () Get the number of command objects in the LinkedBlockingQueue.
void	init (int corePoolSize) Initialize threadPool.
void	terminate () Terminate all threads and cleanup threadPool.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

ThreadPool

public **ThreadPool**([IVHost](#) vhost,
[String](#) name)

Create a new thread pool attached to a vHost.

Parameters:

(continued from last page)

vhost - vHost

Methods

init

```
public void init(int corePoolSize)
```

Initialize threadPool.

Parameters:

corePoolSize - core pool size

terminate

```
public void terminate()
```

Terminate all threads and cleanup threadPool.

execute

```
public void execute(Runnable command)
```

Execute a runnable object. If the threadPool is at the corePool size, the object will be added to a LinkedBlockingQueue in the order it was received.

Parameters:

command

getExecutor

```
public java.util.concurrent.Executor getExecutor()
```

Get the underlying Executor pool.

Returns:

Executor pool

getActiveCount

```
public int getActiveCount()
```

Get number of active threads.

Returns:

number of active threads

getQueueSize

```
public int getQueueSize()
```

Get the number of command objects in the LinkedBlockingQueue.

Returns:

number of command objects in the LinkedBlockingQueue

com.wowza.wms.vhost Class VHostItem

java.lang.Object

└─com.wowza.wms.vhost.VHostItem

public class **VHostItem**
extends Object

VHostItem: data class that hold definition of a virtual host.

Constructor Summary

public	<u>VHostItem()</u> Create empty vHostItem
--------	--------------------------------------------------------------

Method Summary

String	<u>getConfigDir()</u> Get configuration path for vHost.
int	<u>getConnectionLimit()</u> Get connection limit of this vHost item.
String	<u>getName()</u> Get vHost name
<u>WMSProperties</u>	<u>getProperties()</u> Get properties
boolean	<u>isVisited()</u> Has this vHostItem been visited during load of VHosts.xml file.
void	<u>reset()</u> Reset vHostItem to empty state
void	<u>setConfigDir</u> (String configDir) Set configuration path for vHost.
void	<u>setConnectionLimit</u> (int connectionLimit) Set connection limit of this vHost item.
void	<u>setName</u> (String name) Set vHost name
void	<u>setProperties</u> (<u>WMSProperties</u> properties) Set properties
void	<u>setVisited</u> (boolean visited) Set is visited.
String	<u>toString()</u> Format vHost item

Methods inherited from class `java.lang.Object`

`clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait`

Constructors

VHostItem

```
public VHostItem()
```

Create empty vHostItem

Methods

reset

```
public void reset()
```

Reset vHostItem to empty state

getConfigDir

```
public String getConfigDir()
```

Get configuration path for vHost.

Returns:

configuration path for vHost

setConfigDir

```
public void setConfigDir(String configDir)
```

Set configuration path for vHost.

Parameters:

configDir - configuration path for vHost

getName

```
public String getName()
```

Get vHost name

Returns:

vHost name

setName

```
public void setName(String name)
```

Set vHost name

Parameters:

(continued from last page)

name - vHost name

getProperties

```
public WMSProperties getProperties()
```

Get properties

Returns:

properties

setProperties

```
public void setProperties(WMSProperties properties)
```

Set properties

Parameters:

properties - properties

isVisited

```
public boolean isVisited()
```

Has this vHostItem been visited during load of VHosts.xml file. Internally used to track and delete vHost definitions on reload of VHosts.xml.

Returns:

Has this vHostItem been visited during load

setVisited

```
public void setVisited(boolean visited)
```

Set is visited.

Parameters:

visited - is visited

getConnectionLimit

```
public int getConnectionLimit()
```

Get connection limit of this vHost item.

Returns:

connection limit of this vHost item

setConnectionLimit

```
public void setConnectionLimit(int connectionLimit)
```

Set connection limit of this vHost item.

Parameters:

connectionLimit - connection limit of this vHost item

(continued from last page)

toString

```
public String toString()
```

Format vHost item

com.wowza.wms.vhost Class VHostList

java.lang.Object

└─com.wowza.wms.vhost.VHostList

public class **VHostList**
extends Object

VHostList: list of VHost items. Result of parsing VHosts.xml at server startup or VHosts.xml reload. This interface can keep track of reloads and carefully mark items for deletion.

Constructor Summary

public	<u>VHostList()</u> Create empty vHostList
--------	--------------------------------------------------------------

Method Summary

void	<u>addVHostItemListener()</u> (<u>IVHostItemNotify</u> vHostItemListener) Add vHostItem listener.
java.util.List	<u>getVHostItems()</u> Get a list of vHostItems.
java.util.Map	<u>getVHostMap()</u> Get the Map of vHostItem definitions.
java.util.List	<u>getVHostNames()</u> Get a list of vHost names.
void	<u>loadConfig()</u>
void	<u>notifyVHostItemCreate()</u> (<u>VHostItem</u> vhostItem) Notify vHostItem listener of item create.
void	<u>notifyVHostItemDestroy()</u> (<u>VHostItem</u> vhostItem) Notify vHostItem listener of item destroy.
void	<u>notifyVHostItemUpdate()</u> (<u>VHostItem</u> vhostItem) Notify vHostItem listener of item update.
void	<u>reloadConfig()</u> Reload VHosts.xml file.
void	<u>removeVHostItemListener()</u> (<u>IVHostItemNotify</u> vHostItemListener) Remove vHostItem listener.

Methods inherited from class java.lang.Object

clone, equals, finalize, getClass, hashCode, notify, notifyAll, toString, wait, wait, wait

Constructors

VHostList

```
public VHostList()
```

Create empty vHostList

Methods

loadConfig

```
public void loadConfig()
```

reloadConfig

```
public void reloadConfig()
```

Reload VHosts.xml file.

getVHostMap

```
public java.util.Map getVHostMap()
```

Get the Map of vHostItem defintions.

Returns:

Map of vHostItem defintions

addVHostItemListener

```
public void addVHostItemListener(IVHostItemNotify vHostItemListener)
```

Add vHostItem listener. vHostItem listeners will receive the following events: onVHostItemCreate, onVHostItemUpdate, onVHostItemDestroy.

Parameters:

vHostItemListener - vHostItem listener

removeVHostItemListener

```
public void removeVHostItemListener(IVHostItemNotify vHostItemListener)
```

Remove vHostItem listener.

Parameters:

vHostItemListener - vHostItem listener

notifyVHostItemCreate

```
public void notifyVHostItemCreate(VHostItem vhostItem)
```

Notify vHostItem listener of item create.

(continued from last page)

Parameters:

vhostItem - vHostItem

notifyVHostItemUpdate

```
public void notifyVHostItemUpdate(VHostItem vhostItem)
```

Notify vHostItem listener of item update.

Parameters:

vhostItem - vHostItem

notifyVHostItemDestroy

```
public void notifyVHostItemDestroy(VHostItem vhostItem)
```

Notify vHostItem listener of item destroy.

Parameters:

vhostItem - vHostItem

getVHostNames

```
public java.util.List getVHostNames()
```

Get a list of vHost names. Creates a copy of list.

Returns:

list of vHost names

getVHostItems

```
public java.util.List getVHostItems()
```

Get a list of vHostItems. Create a shallow copy of list.

Returns:

list of vHostItems

com.wowza.wms.vhost Class VHostSingleton

java.lang.Object

└-com.wowza.wms.vhost.VHostSingleton

public class **VHostSingleton**
extends Object

VHostSingleton: singleton that provide access to running vHosts.

Constructor Summary

public	VHostSingleton()
--------	----------------------------------

Method Summary

static void	addVHostListener (IVHostNotify vhostListener) Add a vHost listener.
static IVHost	getInstance (String vhostName) Get vHost by name.
static IVHost	getInstance (String vhostName, boolean doCreate) Get vHost by name.
static java.util.List	getVHostNames () Get a list of vHost names.
static void	init (String vhostName, String configHome) Initialize vhost by name.
static void	notifyVHostClientConnect (IVHost vhost, IClient inClient, com.wowza.wms.request.RequestFunction function, AMFDataList params) Notify vhost client connect
static void	notifyVHostCreate (IVHost vhost) Notify vHost listener of create.
static void	notifyVHostInit (IVHost vhost) Notify vHost listener of ini.
static void	notifyVHostShutdownComplete (IVHost vhost) Notify vHost listener of destruction.
static void	notifyVHostShutdownStart (IVHost vhost) Notify vHost listener of destruction.
static void	remove (String vhostName) Remove a vHost from list of running vHosts.
static void	removeApplicationListener (IVHostNotify vhostListener) Remove vHost listener

static void	setServer (IServer server) Set a reference to the current running server.
static void	shutdown (String vhostName) Shutdown a vHost by name.

Methods inherited from class `java.lang.Object`

`clone`, `equals`, `finalize`, `getClass`, `hashCode`, `notify`, `notifyAll`, `toString`, `wait`, `wait`, `wait`

Constructors

VHostSingleton

```
public VHostSingleton()
```

Methods

getInstance

```
public static IVHost getInstance(String vhostName)
```

Get vHost by name. Do NOT create if does not exist.

Parameters:

vhostName - vHost name

Returns:

vHost

getInstance

```
public static IVHost getInstance(String vhostName,  
    boolean doCreate)
```

Get vHost by name. Create if does not exist.

Parameters:

vhostName - vhost name

doCreate - if true, create if does not exist

Returns:

vHost

init

```
public static void init(String vhostName,  
    String configHome)
```

Initialize vhost by name.

Parameters:

vhostName - vHost name

(continued from last page)

configHome - configuration path, path to VHost.xml

setServer

```
public static void setServer(IServer server)
```

Set a reference to the current running server.

Parameters:

server - server

shutdown

```
public static void shutdown(String vhostName)
```

Shutdown a vHost by name.

Parameters:

vhostName - vhost name

getVHostNames

```
public static java.util.List getVHostNames()
```

Get a list of vHost names. Return copy of list.

Returns:

vHost names

remove

```
public static void remove(String vhostName)
```

Remove a vHost from list of running vHosts.

Parameters:

vhostName - vhost name

addVHostListener

```
public static void addVHostListener(IVHostNotify vhostListener)
```

Add a vHost listener. A vHost listener receives the following events: onVHostCreate, onVHostInit, onVHostDestroy

Parameters:

vhostListener - vHost listener

removeApplicationListener

```
public static void removeApplicationListener(IVHostNotify vhostListener)
```

Remove vHost listener

Parameters:

vhostListener - vHost listener

(continued from last page)

notifyVHostClientConnect

```
public static void notifyVHostClientConnect(IVHost vhost,  
      IClient inClient,  
      com.wowza.wms.request.RequestFunction function,  
      AMFDataList params)
```

Notify vhost client connect

Parameters:

vhost - vHost
inClient - client
function - function
params - parameters

notifyVHostCreate

```
public static void notifyVHostCreate(IVHost vhost)
```

Notify vHost listener of create.

Parameters:

vhost - vHost

notifyVHostInit

```
public static void notifyVHostInit(IVHost vhost)
```

Notify vHost listener of ini.

Parameters:

vhost - vHost

notifyVHostShutdownStart

```
public static void notifyVHostShutdownStart(IVHost vhost)
```

Notify vHost listener of destruction.

Parameters:

vhost - vHost

notifyVHostShutdownComplete

```
public static void notifyVHostShutdownComplete(IVHost vhost)
```

Notify vHost listener of destruction.

Parameters:

vhost - vHost

Index

A

ABSOLUTE_FORMAT 553
ABSOLUTE_TIME_PATTERN 553
acceptConnection 310, 327
ACCEPTORS_ACCEPTOR 1248
ACCEPTORS_HANDLERADAPTER 1248
acceptSession 522, 863
acquire 699, 706, 707, 708, 962, 986
acquireAndRelease 699, 707
acquireMediaCaster 713
acquireSocketAddress 831
acquireUDPPortPair 831, 832
actionListeners 861
activateOptions 563
add 76, 133, 134, 135, 168, 169, 170, 817, 1226
addAcceptConnectionAttribute 341
addAcceptorListener 1254
addActionListener 871
addApplicationInstanceListener 229
addApplicationListener 1253
addAudioCodecConfigPacket 1060
addAudioData 1045, 1174, 1175
addAudioDataInc 1174
addBody 814
addBouncyCastleSecurityProvider 96
addBytes 814
addChunk 200
addClient 962, 986
addClientListener 249, 1052
addConnectionListener 309
addContentDescriptor 652
addData 211
addDataData 1045, 1175
addDataDataInc 1176
addDataEx 214
addDifference 76
addDvrChunkListener 462
addDvrRecorderListener 286
addDvrRecordingListener 452
addDvrStoreListener 452
addDvrStreamManagerListener 287
addFirstABSTRequest 539

addHttpProvider 1224
addHTTPStreamerAdapterID 1224
addHTTPStreamerSession 274
addIdleWorkerListener 1260
addIOPerformance 517, 868
addIOPerformance2 518, 869
addItem 1162
addLicense 1126
addListener 1192
addLiveStreamPacketizerListener 282
addLiveStreamTranscoderListener 283
addManifestEntries 451, 462
addMediaCasterListener 253
addMediaReaderListener 279
addMediaStreamListener 251, 1123
addMediaWriterListener 277
addMember 195
addMetaDataListener 721
addModuleListener 257
addNameGroup 1125
addObject 150
addOverlay 1204
addPlayStreamByName 255
addPublisher 272
addRange 379
addRendition 740
addRTPIncomingDatagramPortAll 275
addRTPIncomingDatagramPortRange 274
addRTPSession 267
addRTSPStream 863
addSegment 727
addServerListener 933, 950
addSession 882
addSessionListener 882
addSharedObjectListener 251, 974
addSlotListener 966, 990
addSorterPacket 1207
addStartupStream 1266
addStreamAttribute 901
addStreamDomainStr 526
addStreamDomainStrs 526
addStreamInfo 900
addStreamSrcToMediaCaster 709
addString 149
addToCache 387

addToChunk 430
addToManifest 417
addToPlaylist 1190
addTrack 897
addTrackId 899
addTrackInternal 898
addTrailingZero 656
addTrait 150
addUserHTTPHeaders 529
addVHostItemListener 1286
addVHostListener 1290
addVideoCodecConfigPacket 1061
addVideoData 1045, 1173
addVideoDataInc 1174
adjustFirstPacketTCs 63
AMF3Utils 110
AMF_LEVEL0 121
AMF_LEVEL3 121
AMFData 122
AMFDataArray 131, 132
AMFDataByteArray 142, 143
AMFDataContextDeserialize 148
AMFDataContextSerialize 153
AMFDataItem 159, 160, 161
AMFDataList 167, 168
AMFDataMixedArray 179, 180
AMFDataObj 187, 188
AMFDataTrait 195
AMFObj 200
AMFObjChunk 206
AMFPacket 209, 210
AMFUtils 11
announce 905
append 564
appendParamsToUrl 101
appInstance 802, 859, 1117
appInstanceShutdown 859
APPLICATION_KEY 552
applicationExists 1261
artifact 361, 382
assembleQueryStr 69
attachToWMSSession 904
audioCodecId 732
audioCodecStringToId 55
audioCodecToMetaDataString 56

audioCodecToString 56
audioCodecTypeToString 88
audioPacketizers 862
AUDIOSAMPLE_ACCESS_ALL 323
AUDIOSAMPLE_ACCESS_NONE 323
AUDIOSAMPLEACCESS 1029
authenticateHandler 472
authenticateHTTPProvider 301
authenticateHTTPProviderHandler 472
authenticatePlayHandler 859
authenticatePublishHandler 859
authenticateRTSP 302
AuthenticateUsernamePasswordProviderBase 297
authenticationMethod 472
AUTHMETHOD_PLAY 858
AUTHMETHOD_PUBLISH 858
AUTHMETHOD_UNKNOWN 857
AVSYNCMETHODS_RTPTIMECODE 895
AVSYNCMETHODS_SENDERREPORT 895
AVSYNCMETHODS_SYSTEMCLOCK 895
AVSYNCMETHODS_UNKNOWN 895
avSyncNameToId 910

B

badStreams 803
bind 844
bitrateAudio 732
bitrateTotal 732
bitrateVideo 732
booleanValue 162
broadcastPlayMessage 1123
broadcastGetObjectEncoding 1123
broadcastMsg 254
buffer 206
BufferUtils 30
byteArrayToFile 41
byteArrayToInt 32, 33
byteArrayToIntSafeSync 661
byteArrayToLong 31, 32
byteArrayToLongSafeSync 661
byteArrayToShort 33, 34
byteArrayToString 30, 31
byteStringLen 631
byteValue 162

C

- cacheRTPStream 832
- calcBitrate 432
- calcTotalPacketSize 214
- calculateChunkGroupTime 386
- call 330
- CALLBACK_PARAM1 766
- CALLBACK_PARAM10 767
- CALLBACK_PARAM2 766
- CALLBACK_PARAM3 766
- CALLBACK_PARAM4 766
- CALLBACK_PARAM5 766
- CALLBACK_PARAM6 766
- CALLBACK_PARAM7 766
- CALLBACK_PARAM8 767
- CALLBACK_PARAM9 767
- canHandle 473, 480, 500, 926
- canPlay 459
- canRecord 449, 459
- canRecordAudio 430, 1132
- canRecordData 430, 1133
- canRecordVideo 430, 1133
- CAT_ALL 604
- CAT_application 592
- CAT_cupertino 593
- CAT_dvrchunk 593
- CAT_rtsp 593
- CAT_sanjose 593
- CAT_server 592
- CAT_session 593
- CAT_smoothstreaming 593
- CAT_stream 593
- CAT_transcoder 594
- CAT_vhost 592
- CAT_webm 593
- checkAndSetPlayLogged 517
- checkSendMetadata 905
- cleanUp 563
- clear 76, 608, 818, 967, 985, 1058, 1272
- clearByteContainer 203
- clearFastPlaySettings 332, 1049
- clearIntData 149
- clearLoggingValues 494, 520, 538, 544, 871, 1058
- clearOverlay 1204
- clearProperty 687, 1275
- clearRTSPSessionExtraLines 923
- clearSegments 727, 740
- clearStreamName 1120
- clearStreamSrcToMediaCaster 709
- clearTracks 898
- client 297
- clone 76, 195, 210, 412, 999
- cloneProperties 292
- close 7, 27, 563, 962, 991, 1003, 1010, 1048, 1091, 1151, 1157, 1176, 1181, 1184, 1191
- closeAndWait 1191
- closeHostPort 1264
- closeStream 786
- CODEC_AUDIO_AAC 1245
- CODEC_AUDIO_G711_ALAW 1244
- CODEC_AUDIO_G711_MULAW 1245
- CODEC_AUDIO_MP3 1244
- CODEC_AUDIO_MP3_8 1245
- CODEC_AUDIO_NELLYMOSER 1244
- CODEC_AUDIO_NELLYMOSER_16MONO 1244
- CODEC_AUDIO_NELLYMOSER_8MONO 1244
- CODEC_AUDIO_PCM_BE 1244
- CODEC_AUDIO_PCM_LE 1244
- CODEC_AUDIO_PCM_SWF 1244
- CODEC_AUDIO_RESERVED 1245
- CODEC_AUDIO_SPEEX 1245
- CODEC_AUDIO_UNKNOWN 1243
- CODEC_AUDIO_VORBIS 1245
- CODEC_STREAM_MP2T 1245
- CODEC_STREAM_UNKNOWN 1245
- CODEC_TYPE 416
- CODEC_VIDEO_H263 1243
- CODEC_VIDEO_H264 1243
- CODEC_VIDEO_MPEG2 1243
- CODEC_VIDEO_MPEG4 1243
- CODEC_VIDEO_SCREEN 1242
- CODEC_VIDEO_SCREEN2 1243
- CODEC_VIDEO_SPARK 1242
- CODEC_VIDEO_UNKNOWN 1242
- CODEC_VIDEO_VP6 1242
- CODEC_VIDEO_VP6A 1243
- CODEC_VIDEO_VP8 1243
- CODES_HREF 553

- compress 145
 - CONFIGURATOR_CLASS_KEY 552
 - configureSocketAcceptor 1224
 - ConnectionCounter 309
 - connectionHolder 860
 - containsDvrRecorder 271
 - containsHeader 487
 - containsHTTPStreamer 270
 - containsIndex 493, 537, 543
 - containsKey 188, 217
 - containsLiveStreamPacketizer 271
 - containsLiveStreamTranscoder 284
 - containsProperty 967, 987
 - containsSlot 968, 987
 - containsStreamDomainStr 526
 - containsStreamNameParts 524
 - CONTENTTYPE_ACKBANDWIDTH 1246
 - CONTENTTYPE_AUDIO 1247
 - CONTENTTYPE_BUFFERSIZE 1246
 - CONTENTTYPE_CHORD 649
 - CONTENTTYPE_DATA 1247
 - CONTENTTYPE_DATA0 1247
 - CONTENTTYPE_DATA3 1247
 - CONTENTTYPE_EVENTS 649
 - CONTENTTYPE_FUNCTION 1248
 - CONTENTTYPE_FUNCTION0 1248
 - CONTENTTYPE_FUNCTION3 1248
 - CONTENTTYPE_LYRICS 649
 - CONTENTTYPE_MEDIA 1007
 - CONTENTTYPE_MEDIACHUNK 1248
 - CONTENTTYPE_MEDIALIST 1007
 - CONTENTTYPE_MOVEMENT 649
 - CONTENTTYPE_OTHER 649
 - CONTENTTYPE_PLAYCALLBACK 1248
 - CONTENTTYPE_SETBANDWIDTH 1246
 - CONTENTTYPE_SETCHUNKSIZE 1246
 - CONTENTTYPE_SHAREDOBJECTS 1247
 - CONTENTTYPE_SHAREDOBJECTS0 1247
 - CONTENTTYPE_SHAREDOBJECTS3 1247
 - CONTENTTYPE_TRANSCRIPTION 649
 - CONTENTTYPE_TRIVIA 650
 - CONTENTTYPE_UNKNOWN 1246
 - CONTENTTYPE_URLIMAGES 650
 - CONTENTTYPE_URLWEBPAGES 650
 - CONTENTTYPE_VIDEO 1247
 - CONTENTTYPE_WATCHDOG 1246
 - convertParams 11
 - COOKIEDATEFORMAT 68
 - cookieStr 858
 - copyFile 47
 - copyFile2 47
 - COUNTER_HTTPCUPERTINO 1241
 - COUNTER_HTTPDVRCRUNKS 1242
 - COUNTER_HTTPSANJOSE 1242
 - COUNTER_HTTPSMOOTH 1242
 - COUNTER_HTTPWEBM 1242
 - COUNTER_RTMP 1241
 - COUNTER_RTP 1241
 - COUNTER_TOTAL 1242
 - createApplication 1267
 - createBroadcastMessage 813
 - createConnectMessage 813
 - createContextDeserialize 125
 - createContextSerialize 125
 - createDefaultMessage 813
 - createDvrAudioChunk 427
 - createDvrDataChunk 428
 - createDvrOnMetadataChunk 428
 - createDvrVideoChunk 427
 - createEnhancedSeekMessage 814
 - createIndexLive 537
 - createInstance 1171, 1172, 1188, 1189
 - createPlayStatusMessage 813
 - createSeekMessage 813
 - createSOMessage 814
 - createStream 784, 902
 - CTRL_playlist_node 598
- ## D
- data 382
 - DATA_TYPE_AMF3 119
 - DATA_TYPE_AMF3_ARRAY 121
 - DATA_TYPE_AMF3_BOOLEAN_FALSE 120
 - DATA_TYPE_AMF3_BOOLEAN_TRUE 120
 - DATA_TYPE_AMF3_BYTEARRAY 121
 - DATA_TYPE_AMF3_DATE 121
 - DATA_TYPE_AMF3_INTEGER 120
 - DATA_TYPE_AMF3_NULL 120
 - DATA_TYPE_AMF3_NUMBER 120

DATA_TYPE_AMF3_OBJECT 121
DATA_TYPE_AMF3_STRING 120
DATA_TYPE_AMF3_UNDEFINED 120
DATA_TYPE_AMF3_XML_LEGACY 121
DATA_TYPE_AMF3_XML_TOP 121
DATA_TYPE_ARRAY 118
DATA_TYPE_AS_OBJECT 119
DATA_TYPE_BOOLEAN 117
DATA_TYPE_BYTEARRAY 119
DATA_TYPE_CUSTOM_CLASS 119
DATA_TYPE_DATE 118
DATA_TYPE_INTEGER 119
DATA_TYPE_LONG_STRING 119
DATA_TYPE_MIXED_ARRAY 118
DATA_TYPE_MOVIE_CLIP 118
DATA_TYPE_NULL 118
DATA_TYPE_NUMBER 117
DATA_TYPE_OBJECT 118
DATA_TYPE_OBJECT_END 118
DATA_TYPE_RECORDSET 119
DATA_TYPE_REFERENCE_OBJECT 118
DATA_TYPE_STRING 117
DATA_TYPE_UNDEFINED 118
DATA_TYPE_UNKNOWN 117
DATA_TYPE_XML 119
DATA_TYPE_XML_TOP 120
DATE_AND_TIME_FORMAT 553
DATE_AND_TIME_PATTERN 553
DATEFORMAT 159
dateValue 162
debug 572, 573
debugRTSPSession 861
DebugUtils 39
DECODE 15
decode 18, 19
DECODE_OBJ_REF 186
DECODE_TRAITS 186
DECODE_TRAITS_EXT 186
DECODE_TRAITS_REF 186
DECODE_UNDEFINED 186
decodeFileToFile 21
decodeFromFile 20
decodeHexString 30
decodeRangeHeader 1210
decodeS 954
decodeSS 954
decodeStorageDir 270, 947
decodeStreamInfo 1213
decodeToFile 20
decodeToObject 19
decodeValue 101
decompress 146
decrement 311
DEFAULT_APPINSTANCE_NAME 245
DEFAULT_APPLICATION_NAME 227
DEFAULT_CHUNK_CACHE_CLASS 399
DEFAULT_CHUNK_GROUPING_SECONDS 396
DEFAULT_CHUNK_READER_CLASS 398
DEFAULT_CHUNK_WRITER_CLASS 398
DEFAULT_CONFIGURATION_FILE 552
DEFAULT_CONFIGURATION_KEY 552
DEFAULT_DVR_ALLOWABLE_AV_PACKET_DELTA 401
DEFAULT_DVR_APPEND_DISCONTINUITY_DELTA 396
DEFAULT_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION 405
DEFAULT_DVR_BREAK_ON_PTS 406
DEFAULT_DVR_CHUNK_DURATION_MINIMUM 410
DEFAULT_DVR_DEBUG_MAX_RAW_PACKETS 403
DEFAULT_DVR_DEBUG_RAW_PACKETS 403
DEFAULT_DVR_MAX_CHUNK_LOG 405
DEFAULT_DVR_MAX_ILLEGAL_CHUNKS_LOGGED 402
DEFAULT_DVR_PACKET_DELTA_TO_NOTIFY 403
DEFAULT_DVR_PACKET_DELTA_TO_RESET_TIME 402
DEFAULT_DVR_PACKET_SORT_TIME 405
DEFAULT_DVR_RECORDINGS_LOADER_CLASS 400
DEFAULT_DVR_SANJOSE_ABST_DURATION_TOLERANCE 410
DEFAULT_DVR_SANJOSE_ABST_TIMESCALE 409
DEFAULT_FILE_SYSTEM_CLASS 398
DEFAULT_MANIFEST_PERSISTER_CLASS 399
DEFAULT_PORT 563
DEFAULT_RANDOMACCESSREADER 1007
DEFAULT_REPOSITORY_NAME 551
DEFAULT_TEXT_READER_CLASS 401
DEFAULT_TEXT_WRITER_CLASS 400
DEFAULT_XML_CONFIGURATION_FILE 552

- DefaultDvrStreamVersionHandler 358
- defaultLocale 95
- defaultTimeZone 95
- deleteArchivedStore 451
- deleteDirectory 47
- deleteSlot 963, 987
- deleteStream 785
- describe 914
- deserialize 127, 139, 145, 162, 174, 180, 191, 192, 374, 377, 379, 426
- deserializeBody 615, 635, 638, 641, 643, 645, 651, 656, 659, 664
- deserializeDate 110
- deserializeFrame 632
- deserializeInnerObject 125
- deserializeInt 110
- deserializeString 111, 632
- detachFromWMSSession 904
- determineChunkGroupIdentifier 386
- determineExistingStoreForPlaying 359, 465
- determineExistingStoreForRecording 359, 464
- determineStreamVersion 432
- directOutput 1216
- disconnect 311, 965, 974, 990
- doBreak 811
- doCRC32 36
- doesFileExist 493
- doesStackContainMethod 42
- doHTTPAuthentication 474
- doIdle 716
- DONT_BREAK_LINES 16
- doSessionRedirect 530
- doSet 77
- doubleValue 161
- doWatchdog 673, 698, 705, 829, 948
- dummy 82
- DVR_DEFAULT_FILESTORE 396
- DVR_DEFAULT_RECORDER_ID 395
- DVR_DEFAULT_REPEATER_PACKETIZER_ID 395
- DVR_DEFAULT_STREAMER_PACKETIZER_ID 395
- DVR_STORAGE_STRATEGY_APPEND 397
- DVR_STORAGE_STRATEGY_DELETE 397
- DVR_STORAGE_STRATEGY_VERSION 397
- DVR_WINDOW_DURATION_UNLIMITED 397
- DvrManifestChunkEntry 361
- DvrManifestCodecEntry 365
- DvrManifestEntry 371
- DvrManifestEntryFactory 374
- DvrManifestEntryRangeGroup 378
- DvrManifestOnMetadataEntry 382
- DvrManifestTimeMapEntry 384
- dvrRecorders 1117
- dvrStreamStorageDeleted 443
- dvrStreamStorageLoaded 443
- dvrStreamStoreCreate 442
- dvrStreamStoreDestroy 442
- dvrStreamStoreInit 442
- E
- elapsedTime 861
- ElapsedTimer 44
- ENCODE 15
- encodeBytes 17, 18, 373
- encodeFileToFile 20
- encodeFromFile 20
- encodeHexString 30
- encodeObject 16
- encodeToFile 19
- encodeValue 101
- ENCRYPTION_TYPE_CUPERTINO 411
- ENCRYPTION_TYPE_PLAYREADY 411
- encryptions 361
- end 98
- endChunk 430
- equals 93
- error 571
- EVT_ALL 604
- EVT_announce 597
- EVT_app_start 596
- EVT_app_stop 596
- EVT_comment 596
- EVT_connect 594
- EVT_connect_burst 594
- EVT_connect_pending 594
- EVT_create 595
- EVT_decoderaudiostart 597
- EVT_decoderaudiostop 597
- EVT_decodervideostart 597
- EVT_decodervideostop 597
- EVT_describe 597

EVT_destroy 595
EVT_disconnect 594
EVT_encoderaudiostart 597
EVT_encoderaudiostop 597
EVT_encodervideostart 597
EVT_encodervideostop 598
EVT_pause 594
EVT_play 594
EVT_publish 594
EVT_record 595
EVT_recordstop 596
EVT_seek 595
EVT_server_start 596
EVT_server_stop 596
EVT_setbuffertime 595
EVT_setstreamtype 595
EVT_stop 595
EVT_unpause 595
EVT_unpublish 594
EVT_vhost_start 596
EVT_vhost_stop 596
execute 1280
exists 8, 973
existsRTSPTunnelingSession 833
expandEndTime 424
expandEnvironmentVariables 95, 96
expandStartTime 424
expandToPortPair 832
extractCodecConfigFromTrackInfo 906
extractHTTPRequestInfo 528

F

fastDateFormat 159
FastPlaySettings 995
fatal 572
FCPublish 790
FCSubscribe 791
fcSubscribe 347
FCUnPublish 790
FCUnpublish 791
FCUnSubscribe 792
FCUnsubscribe 792
fcUnSubscribe 347
fcUnSubscribeAll 347

FD_ALL 603
FD_c_client_id 589
FD_c_ip 589
FD_c_proto 589
FD_c_referrer 589
FD_c_user_agent 589
FD_cs_bytes 589
FD_cs_bytes_inc 559
FD_cs_stream_bytes 590
FD_cs_stream_bytes_inc 559
FD_cs_uri_query 591
FD_cs_uri_stem 591
FD_date 588
FD_s_ip 590
FD_s_port 592
FD_s_uri 589
FD_sc_bytes 590
FD_sc_bytes_inc 559
FD_sc_stream_bytes 590
FD_sc_stream_bytes_inc 559
FD_time 588
FD_tz 588
FD_x_app 588
FD_x_appinst 589
FD_x_category 588
FD_x_comment 592
FD_x_ctx 588
FD_x_ctx_override 588
FD_x_duration 591
FD_x_duration_inc 559
FD_x_event 587
FD_x_file_ext 591
FD_x_file_length 590
FD_x_file_name 591
FD_x_file_size 590
FD_x_severity 592
FD_x_sname 590
FD_x_sname_query 591
FD_x_spos 590
FD_x_status 591
FD_x_stream_id 592
FD_x_suri 592
FD_x_suri_query 591
FD_x_suri_stem 591
FD_x_vhost 588

- FILEEXTENSION 959
- FILEFORMAT_FLV 1246
- FILEFORMAT_MP4 1246
- FILEFORMAT_UNKNOWN 1245
- fileToByteArray 47
- FileUtils 46
- filters 472
- FLAGS_DEFAULT 631
- floatValue 161
- flush 963, 974, 991, 1061, 1176
- flushBase64 27
- FLV_CHUNKHEADER_BUFFER_SIZE 54
- FLV_CHUNKHEADER_FIRST_BYTE 53
- FLV_CHUNKHEADER_HEADER_SIZE 54
- FLV_CHUNKHEADER_ISIZE 53
- FLV_CHUNKHEADER_ITIMECODE 53
- FLV_CHUNKHEADER_ITYPE 53
- FLV_CHUNKHEADER_SECONDBYTE 53
- FLV_CHUNKHEADER_VALUESIZE 54
- FLV_DFRAME 54
- FLV_KFRAME 54
- FLV_PFRAME 54
- FLV_TCINDEXAUDIO 54
- FLV_TCINDEXDATA 55
- FLV_TCINDEXVIDEO 54
- FLV_UFRAME 54
- FLVUtils 55
- forceNewLoggerInstance 576
- forceReset 673
- formatBytes 40
- formatBytesShort 39
- formatBytesStruct 41
- formatDeleteCookie 70
- formatH264CodecConfig 1213
- formatH264CodecConfigPacket 1213
- formatMilliseconds 42
- formatRTPIInfo 916
- formatSeconds 42
- formatSetCookie 71
- formatUtcTime 42
- FORWARD 6
- frameTypeToString 56
- fS 954
- G
- generateAuth 84, 85, 86
- generateAuthHTTP 85
- generateHash 87
- generateHashBytes 86, 87
- get 136, 172, 189, 219, 220, 972, 1227
- getAbsTimecode 203, 212
- getAccess 992, 1059
- getActiveCount 1280
- getAdapterName 502
- getAddress 1222
- getAddressCount 847
- getAddressRawStr 1222
- getAddressStr 1222
- getAdminAgent 945
- getAdminGUID 952
- getAdminInterfaceObjectList 933, 950
- getAllAsStrings 294
- getAllowDomains 260
- getAndClearPendingFrameGrabs 1202
- getAndClearPendingOverlays 1205
- getAppInstance 228, 324, 458, 505, 518, 671, 773, 866, 903, 1122, 1131, 1151, 1173
- getAppInstanceName 906, 1122
- getAppInstanceNames 230
- getAppInstanceProperty 807
- getApplication 246, 324, 564, 773, 1250
- getApplicationFolderNames 1261
- getApplicationInstance 705, 1144
- getApplicationInstanceTouchTimeout 278
- getApplicationLock 1258
- getApplicationNames 1261
- getApplicationPath 227
- getApplicationProperty 806
- getApplicationTimeout 257, 1256
- getAppName 906, 1122
- getArchiveStrategy 359, 449, 465
- getArtifactsTextRepresentation 363, 383
- getAudioCodec 57, 65, 365
- getAudioCodecConfigPacket 1060
- getAudioCodecId 735
- getAudioHost 838
- getAudioMissing 1044
- getAudioMP3Layer 64
- getAudioPacketizerItem 829, 876

getAudioPort 837
getAudioSize 1030
getAudioTC 1033
getAudioTrack 900
getAuthenticatePlayHandler 866
getAuthenticatePublishHandler 865
getAuthenticationList 1262
getAuthenticationMethod 474, 480
getAutoAllocateInterleavePorts 918
getAVSyncMethod 909
getBaseClass 688, 1274
getBasePath 8
getBitrateAudio 734
getBitrateTotal 734
getBitrateVideo 734
getBodySize 615, 636, 639, 641, 643, 645, 651, 657, 659, 664
getBoolean 138, 174, 190, 191, 222, 224
getBufferSize 646
getBufferTime 334, 1029
getBurstStartStop 1056
getByte 137, 174, 190, 191, 222, 223
getByteAllocation 72
getByteContainerLevel 203
getCacheName 1055
getCallbackParamCount 769
getChecksum 999
getChunkCounter 205
getChunker 458
getChunkGroupDuration 386
getChunks 200
getClassName 193, 196
getClient 249, 298, 304, 1036, 1249, 1250
getClientById 248
getClientCount 248, 1253
getClientCountTotal 248
getClientID 787
getClientId 323, 1036
getClientIdGenerator 935, 951
getClientIdGeneratorRecycleDelaySize 954
getClientIdGeneratorRecycleSize 953
getClientIdGeneratorTimeout 953
getClientIdleFrequency 260, 1258
getClientProperty 807
getClients 248, 961, 986
getClientsLockObj 268
getClientTimeout 1249
getClientUpdates 989
getClosestStartTime 424, 463
getCodecEntryForTime 419
getCodecId 735
getCommandInterface 949
getCommandInterfaceCommandHandler 937, 954
getCommandInterfaceHostPort 932, 949
getCommittedVirtualMemory 953
getCommonInitialTextRepString 373
getConfigDir 1282
getConfigPath 228
getConfiguration 1223
getConnectionCounter 229, 253, 932, 948, 1255
getConnectionHolder 518, 869
getConnectionLimit 1255, 1283
getConnectionTimeout 688
getConnectionValidator 948
getConnectLastAttempt 675
getConnectLastForceReset 675
getConnectLastSuccess 675
getConnectTime 332
getContentDescriptors 652
getContentLength 483
getContentType 484, 651
getContextStr 277, 446, 457, 1065
getCookieStr 523, 875
getCoreHandlerPoolSize 934, 950, 1251
getCoreTransportPoolSize 933, 950, 1251
getCount 1121
getCpuTime 96
getCryptoPoolActiveCount 952
getCryptoPoolMaxSize 952
getCurrent 311
getCurrentHeapSize 953
getCurrentItem 1189
getCurrentTime 434
getData 214, 382, 639, 977
getDataBuffer 213
getDataMissing 1045
getDataSize 1030
getDataTC 1034
getDataType 1034
getDate 44, 138, 174, 190, 191, 222, 224
getDateStarted 230, 253, 333, 932, 949, 1255

getDateString 45
getDefaultStreamingStore 448
getDePacketizerList 832
getDePacketizerName 833
getDescription 616, 636, 639, 688, 1276
getDirection 996
getDirecton 7
getDouble 138, 173, 190, 191, 221, 223
getDuration 372, 903, 1012, 1106, 1181, 1184
getDvrApplicationContext 285
getDvrArtifact 362, 382
getDvrChunkAtTime 463
getDvrChunkByIndex 462
getDvrFileSystemClass 448
getDvrManager 458, 1132
getDvrPlaylistRequest 432
getDvrProperties 285
getDvrRecorder 1063, 1066, 1125
getDvrRecorderId 1132
getDvrRecorderList 286, 1062, 1267
getDvrRecorders 1126
getDvrRepeater 1066
getDvrSessionInfo 527
getDvrStorageDir 448
getDvrStorageWindowSeconds 448
getDvrStoreList 1268
getDvrTime 423
getDynamicLogProperties 935, 951, 1263
getElapsedTime 346, 526, 877, 1063
getEmbeddedFlag 646
getEncoding 564
getEncryptionDelegate 449
getEncryptionRepeaterSharedSecret 449
getEncryptions 362
getEncryptionsTextRepresentation 363
getEncryptionType 412
getEndIndex 376
getEntriesToPurge 419
getExecutor 1280
getExt 1058
getExtent 998
getFastPlaySettings 331, 1048
getFileExtension 1172
getFileInBytes 80
getFileInBytesRate 82
getFileInfo 525
getFileIOPoolSize 1252
getFileOutBytes 81
getFileOutBytesRate 82
getFilePointer 7
getFileSystem 458
getFirstByte 214
getFirstEntry 421
getFirstRendition 740
getFirstSegment 727
getFlags 633, 664
getFlashVer 324
getFloat 138, 173, 190, 191, 221, 224
getFips 995
getFrameIdentifier 639
getFrameMapIds 609
getFrames 609
getFrameType 56, 57
getGlobalLogValue 578
getGUID 952
getHandler 844
getHandlerThreadPool 934, 951, 1252
getHeader 482, 488
getHeaderMap 482
getHeaderNames 483
getHeaders 488
getHeaderSize 489, 1060
getHeight 736
getHighestVersionedStore 447
getHomePath 1251
getHost 837, 901
getHostPortsList 1252
getHostType 839
getHTTPHeader 528
getHTTPHeaderMap 528
getHTTPHeaderNames 528
getHTTPIntHeader 528
getHttpProviders 1224
getHTTPStreamerAdapter 518, 1265
getHTTPStreamerAdapterIDs 1224, 1266
getHTTPStreamerApplicationContext 274
getHTTPStreamerContext 1262
getHTTPStreamerItem 501
getHTTPStreamerList 270, 1265
getHTTPStreamerProperties 269

getHTTPStreamerSession 1004, 1063
getHTTPStreamerSessionCount 273, 274
getHTTPStreamerSessionCountsByName 272
getHTTPStreamerSessions 272, 273
getId 502
getId 201
getIdleCheckFrequency 1259
getIdleFrequency 337, 502, 874
getIdleHandler 869
getIdleMinimumWaitTime 1262
getIdleTimeout 672
getIdleWorkerCount 1260
getIdleWorkers 1263
getIdStr 632, 663
getIdString 689
getIndex 372, 494, 538, 543, 1165
getIndexLive 538
getInIpAddress 843
getInitialRepeaterItems 453
getInnerObj 196
getInPort 844
getInputStream 485
getInstance 577, 945, 1289
getInt 137, 173, 190, 191, 220, 223
getIntData 148
getIntHeader 482, 488
getIOPerformanceCounter 255, 525, 875
getIoPerformanceCounter 230, 931, 948, 1254
getIOScheduler 1254
getIp 331, 867
getIpAddress 519
getItems 1161
getJmxRemoteConfig 950
getKeepAliveTime 689
getKeepAliveTimeout 1260
getKey 189, 219
getKeys 189, 219
getLanguage 651
getLastAccessed 999
getLastAudioTimecode 1176
getLastAuthenticateMethod 866
getLastClientId 979
getLastConnectAcceptedStamp 312
getLastConnectAcceptedStampString 312
getLastConnectAcceptedTime 312
getLastConnectAcceptedTimeString 312
getLastConnectRejectedByReasonStamp 313
getLastConnectRejectedByReasonStampString 313
getLastConnectRejectedByReasonTime 313
getLastConnectRejectedByReasonTimeString 313
getLastConnectRejectedStamp 312
getLastConnectRejectedStampString 312
getLastConnectRejectedTime 312
getLastConnectRejectedTimeString 313
getLastDataTimecode 1177
getLastDisconnectStamp 314
getLastDisconnectStampString 314
getLastDisconnectTime 314
getLastDisconnectTimeString 314
getLastKeyFrame 1046
getLastLiveEntry 421
getLastOperation 979
getLastPacket 1046
getLastPacketsByType 914
getLastPurgeTime 434
getLastRecordedEntry 418
getLastRecordedIndex 423
getLastRequest 532
getLastStreamId 785
getLastTC 64
getLastTouchTime 278
getLastValidateTime 342
getLastVideoTimecode 1176
getLength 1012, 1165
getLicenseCounter 954
getLicenseHolder 1135, 1152
getLicenseTracker 954
getLicenseValidator 948
getLiveEntries 421
getLiveEntriesWithLimit 422
getLivePlaylist 544
getLiveRepeaterCapabilities 346
getLiveStreamDvrRecorderControl 285
getLiveStreamingPacketizer 519
getLiveStreamPacketizer 699, 788, 1062, 1064, 1124
getLiveStreamPacketizerControl 275
getLiveStreamPacketizerId 1142
getLiveStreamPacketizerList 270, 345, 1062, 1266
getLiveStreamPacketizerLock 1124
getLiveStreamPacketizerProperties 268

getLiveStreamRepeater 700, 1064
getLiveStreamTranscoder 1067
getLiveStreamTranscoderControl 285
getLiveStreamTranscoderItem 1152
getLiveStreamTranscoderList 284, 346, 1062, 1266
getLiveStreamTranscoders 1067
getLiveThreads 952
getLocale 486
getLock 515, 608, 696, 705, 728, 733, 741, 831, 1188
getLockCount 698, 712
getLogger 568, 578, 775
getLoggerObj 576, 578
getLong 137, 173, 190, 191, 221, 223
getMACAddress 96
getManifest 458
getManifestChannel 424
getManifestRepresentation 362, 365, 372, 383, 385
getMapIdStr 615, 633, 663
getMaxHeapSize 953
getMaximumPendingReadBytes 259, 1257
getMaximumPendingWriteBytes 258, 345, 1257
getMaximumSetBufferTime 259, 345, 1258
getMaxRTCPWaitTime 910
getMaxStorageDirDepth 269
getMaxTimecode 1046, 1176
getMediaCaster 697, 706, 1077
getMediaCasterCount 705
getMediaCasterDef 671, 692
getMediaCasterDefs 691
getMediaCasterHostPortConfig 693
getMediaCasterId 671, 697
getMediaCasterList 1261
getMediaCasterNames 691, 705
getMediaCasterProcessorCount 694
getMediaCasterProperties 268
getMediaCasterSettings 1261
getMediaCasterStreamItem 673
getMediaCasterStreams 256
getMediaCasterType 676, 902
getMediaCasterValidator 278
getMediaExtension 8, 1004, 1013
getMediaIOPerformance 1050
getMediaIOPerformanceCounter 324
getMediaList 741, 1004
getMediaListProvider 288
getMediaListSegment 733
getMediaName 8
getMediaReader 918
getMediaReaderContentType 288, 1268
getMediaReaderProperties 268
getMediaReaders 1256
getMediaWriterProperties 268
getMediaWriters 1256
getMember 196
getMemberCount 195
getMembers 195
getMessagesInBytes 80
getMessagesInBytesRate 81
getMessagesInCount 80
getMessagesInCountRate 81
getMessagesLossBytes 81
getMessagesLossBytesRate 82
getMessagesLossCount 80
getMessagesLossCountRate 81
getMessagesOutBytes 80
getMessagesOutBytesRate 82
getMessagesOutCount 80
getMessagesOutCountRate 81
getMetadata 1010
getMetadataEntryForTime 419
getMetadataPacket 821, 905
getMetaDataProvider 1060
getMethod 483
getMimeType 616
getMinimumAvailableChunks 447
getMissing 210
getMode 915
getModFunctions 256
getModuleInstance 257
getModuleList 257
getMp3TagMap 1256
getMPEGTSAudioLanguage 911
getMPEGTSAudioPID 911
getMPEGTSProgramID 911
getMPEGTSVideoPID 911
getMultiplier 995
getName 228, 246, 687, 728, 735, 840, 965, 978, 990, 1031, 1163, 1165, 1191, 1253, 1274, 1282
getNameGroupByGroupName 1125
getNameGroups 1125

getNameGroupStreamNames 1125
getNetConnection 678, 1036
getNetConnectionHostPortConfig 1260
getNetConnectionIdleFrequency 1259
getNetConnectionProcessorCount 1253
getNextChunkIndex 423
getNextCodecIndex 424
getNextMetadataIndex 423
getNextNameGroupId 1125
getNextNetConnectionId 1249
getNextSessionId 881
getNextStreamIndex 1120, 1121
getNextTimeMapIndex 424
getNodeByTagName 104
getNodeValue 104
getNodeValueByTagName 104
getNormalizedNTPTimecode 915
getNumberLiveEntries 420
getNumberRecordedEntries 420
getObject 138, 150, 174, 190, 191, 222, 224
getObjectEncoding 149, 153, 205, 344
getObjectNames 972
getObjectReference 154
getOffsetToNextTag 646
getOrCreate 972
getOutHost 913
getOutIpAddress 843
getOutPort 844
getOutputStream 487
getPacketizerName 447
getPageUrl 336, 791
getParam 769
getParamBoolean 772, 773
getParamCount 769
getParamDate 771
getParamDouble 771, 772
getParameter 484
getParameterMap 485
getParameterNames 484
getParameterValues 484
getParamInt 771
getParamLong 772
getParamMixedArray 770
getParamObj 770
getParamString 770
getParamType 769
getParamValue 102
getParent 968, 992, 1092
getPassword 303
getPath 9, 473, 486, 1003, 1012
getPeakThreads 952
getPictureData 616
getPictureType 616
getPingRoundTripTime 333
getPingTimeout 258, 342, 1256
getPlayClass 1275
getPlayDuration 529, 736
getPlayer 1044
getPlayerCount 698, 712
getPlaylist 1189
getPlayPackets 1046
getPlayStart 528, 736
getPlayStreamCount 256
getPlayStreamCountsByName 256
getPlayStreams 325
getPlayStreamsByName 256
getPollingInterval 1192
getPort 565, 1222
getProcessorCount 1223
getProperties 229, 247, 326, 457, 501, 504, 527, 688, 728, 734, 741, 867, 935, 951, 1045, 1132, 1141, 1152, 1251, 1275, 1283
getProperty 293, 687, 964, 987, 1249, 1275
getPropertyBoolean 293
getPropertyDouble 294
getPropertyInt 293
getPropertyLong 294
getPropertyStr 293
getProtocol 337, 485
getPublishAudioCodecId 1065
getPublisher 1192
getPublisherCount 272
getPublishers 271
getPublishStreamNames 277, 1118
getPublishStreams 325
getPublishVideoCodecId 1064
getPurgeController 458
getQueryStr 335, 522, 871, 1057
getQueryString 483
getQueueSize 1280
getRange 376

getReceiveVideoFPS 1049
getReconnectWaitTime 675
getRecordedEntries 417, 422, 423
getRecordedEntriesInRange 418
getRecordedEntriesMap 417
getRecordedEntriesWithLimit 422, 462
getRecordedEntryByIndex 418, 462
getRecordedEntryByTimeKey 418
getRecordingName 1135
getRecordingStreamStore 448
getRedirectSessionBody 531
getRedirectSessionCode 530, 878
getRedirectSessionContentType 531
getRedirectSessionMessage 879
getRedirectSessionURL 530, 878
getRefCount 962, 986
getReference 124
getReferrer 336, 521, 791, 870
getRemoteAddr 486
getRemoteHost 486, 564
getRendition 740
getRenditions 740
getRepeat 1162, 1191
getRepeaterItemsDvr 454
getRepeaterLastSequence 1142
getRepeaterMediaCasterDef 505
getRepeaterOriginUrl 259, 342, 790
getRepeaterQueryString 260
getRequestFilters 473, 480
getRequestURI 483
getRequestURL 483
getRespAMFAudioObj 335, 1057
getRespAMFDataObj 335, 1057
getRespAMFVideoObj 335, 1057
getRespFunctions 332
getResponseAMFObj 335
getRsoStorageDir 262
getRsoStoragePath 262
getRTPAVSyncMethod 265
getRTPContext 897, 1261
getRTPDatagramConfigIncoming 1262
getRTPDatagramConfigOutgoing 1262
getRTPDestination 923
getRTPIIdleFrequency 261, 1259
getRTPIInfo 916
getRTPMMaxRTCPWaitTime 266
getRTPPlayAuthenticationMethod 265
getRTPProperties 268
getRTPPublishAuthenticationMethod 265
getRTPSession 297, 304, 849
getRTPSessionCount 267
getRTPSessionCountsByName 267
getRTPSessions 266
getRTPStream 344, 1061
getRTPWriteListener 868
getRTSPBindIpAddress 280, 919
getRTSPConnectionAddressType 281, 920
getRTSPConnectionIpAddress 281, 920
getRTSPMaximumPendingWriteBytes 279, 919
getRTSPOriginAddressType 282, 921
getRTSPOriginIpAddress 281, 920
getRTSPPlayRangeStart 875
getRTSPPlayRangeStop 875
getRTSPSessionDescription 917
getRTSPSessionExtraLines 923
getRTSPSessionName 916
getRTSPSessionTimeout 279, 918
getRTSPStream 864
getRTSPTunnelingLock 833
getRTSPTunnelingSession 833
getRTSPTunnelingSessionId 874
getScheme 485
getSDPData 848
getSDPLang 923
getSecondByte 214
getSegment 727, 728
getSeq 213
getSerializeSize 411
getServerGUID 952
getServerHostPort 337
getServerIp 520, 869
getServerName 485
getServerPort 485, 520, 870
getSession 881, 899
getSessionDescriptionData 715
getSessionGUID 951
getSessionId 514, 863
getSessionIds 881
getSessionProtocol 520
getSessions 830

getSessionTimeout 517
getSessionTracker 548
getSessionType 519
getSharedObjectReadAccess 264, 338
getSharedObjects 249
getSharedObjectWriteAccess 264, 338
getShort 137, 173, 190, 191, 221, 223
getSize 201, 210, 609, 633, 664, 736
getSlot 961, 985
getSlotNames 961, 985
getSlots 967, 985
getSlotVersion 978
getSoVersion 978
getSrc 202, 211, 1031
getSSLConfig 1224
getSslFactoryClass 1222
getStart 1165
getStartIndex 376
getStartStream 1144
getStartTC 996
getStartTCOffset 996
getStartTimeCode 371
getStartupStreams 1266
getStopTimeCode 371
getStorageDir 966, 974, 991
getStream 516, 671, 775, 900, 1118, 1119, 1131, 1172
getStreamArray 701
getStreamAttributes 910
getStreamAudioSampleAccess 263, 339
getStreamBaseName 446
getStreamBitrate 789, 1216
getStreamClientless 1118
getStreamCount 256
getStreamDef 1278
getStreamDefs 1277
getStreamExt 523, 699, 907
getStreamFile 333, 334
getStreamFileForRead 1056
getStreamFileForWrite 1055
getStreamFileMapper 269
getStreamId 900
getStreamInfo 901, 910
getStreamIsRunningLock 675
getStreamKeyDir 261
getStreamKeyPath 262
getStreamLastSeq 674
getStreamLength 789, 1216
getStreamList 702
getStreamListLock 1117
getStreamLock 897
getStreamManager 705
getStreamMissingTime 673
getStreamName 457, 523, 907, 1151
getStreamNameAliasProvider 271
getStreamNameLock 1118
getStreamNameLogging 907
getStreamNameParts 524
getStreamNames 712
getStreamPacketizerItem 830, 877
getStreamPort 838
getStreamPosition 524, 1013
getStreamProperties 268
getStreamProperty 808
getStreamQueryStr 912
getStreamReadAccess 263, 340
getStreams 246, 1036, 1118
getStreamSessionId 908
getStreamSessionIp 908
getStreamSessionVersion 908
getStreamStorageDir 261
getStreamStoragePath 262
getStreamStore 447
getStreamStores 447
getStreamTimeout 673
getStreamTimeoutLastReset 674
getStreamTimeoutLastTime 674
getStreamTimeoutReason 674
getStreamTrack 900
getStreamType 247, 326, 686, 788, 906, 1046, 1172
getStreamTypeNames 1278
getStreamTypes 1249
getStreamTypeStr 505
getStreamVersionHandler 449
getStreamVideoSampleAccess 262, 339
getStreamWriteAccess 264, 341
getString 137, 150, 172, 189, 190, 220, 222
getStringReference 154
getSystemTime 97
getTargetEncoding 153
getTextEncoding 615, 636, 651, 657, 660

getThreadPool 934, 951, 1252
getTime 45
getTimecode 202, 212, 653, 814
getTimeMapper 458
getTimeMapping 385
getTimeRunning 230, 254, 333, 526, 878, 932, 949, 1255
getTimeRunningSeconds 230, 254, 333, 527, 878, 932, 949, 1255
getTimeSeconds 45
getTimeStampFormat 651
getTimeString 45
getTotal 314
getTotalAccepted 314
getTotalIOPerformanceCounter 324
getTotalRejected 315
getTrack 843, 899
getTrackId 899
getTrackNames 899
getTrait 150, 193
getTraitReference 154
getTranscoderApplicationContext 285
getTranscoderName 1151
getTranscoderProperties 269
getTransportMode 915
getTransportThreadPool 934, 951, 1252
getTTL 839, 846
getType 122, 172, 201, 211, 372, 375, 735, 815
getTypeAsString 733
getUDPManagedDeliveryCount 924
getUDPManagedDeliveryDelay 924
getUDPPortManager 936, 952
getUDPPortSharingManager 936, 952
getUDPTransport 843, 909
getUDPTransportManager 831, 1265
getUniqueId 697
getUniqueStreamIdStr 1063
getUnsignedShort 36
getUri 336, 521, 870
getURL 639, 659
getUserAgent 521, 864
getUserAgents 933, 949
getUserHTTPHeaders 529
getUserQueryStr 527
getUserTime 97
getValidationFrequency 258, 1257
getValue 127, 139, 144, 162, 176, 192, 636, 654, 657
getVersion 787, 930, 946, 963, 987
getVHost 229, 247, 297, 304, 329, 502, 505, 515, 670, 774, 831, 864, 882, 901, 1122
getVHostItems 1287
getVHostList 935, 951
getVHostMap 1286
getVHostNames 1287, 1290
getVideoCodec 57, 65, 365
getVideoCodecConfigPacket 1061
getVideoCodecId 734
getVideoHost 838
getVideoMissing 1044
getVideoPacketizerItem 830, 876
getVideoPort 837
getVideoSize 1030
getVideoTC 1033
getVideoTimecodeOffset 65
getVideoTrack 900
getVODLastTimeTC 921
getVODPlayLen 922
getVODStartTimeTC 921
getWidth 736
getWriteListener 341
getXMLPropertyBool 107
getXMLPropertyDouble 106
getXMLPropertyExists 106
getXMLPropertyInt 106
getXMLPropertyLong 106
getXMLPropertyStr 105
gmtTimeZone 95
grabFrame 1202
GZIP 16

H

handleArchivedStream 359, 465
handleCallback 1051
handleMessage 820, 846
handleOnMetadata 1150
handlePacket 1131, 1142, 1150
hasAudio 425, 460
hasCodecData 425
hasData 425, 460
hasEncryption 459
hasOnMetadata 425, 460

- hasTimeMapData 425
- hasVideo 425, 460
- HEADERSIZE 623
- height 732
- HOSTNAME_KEY 552
- HostPort 1221
- HostPortList 1226
- HTTPRequestToByteArray 68, 69
- HTTPRequestToFile 68
- HTTPProvider2Base 472
- HTTPStreamerSessionCupertino 493
- HTTPStreamerSessionSanJose 537
- HTTPStreamerSessionSmoothStreamer 543
- HTTPStreamerSessionWebM 548
- HTTPUtils 68
-
- I
-
- ID3FOOTER_SIZE 607
- ID3Frames 608
- ID3HEADER_SIZE 607
- ID3HEADER_VERSION 607
- ID3HEADERFLAGS_DEFAULT 607
- ID3HEADERFLAGS_EXPERIMENTAL 608
- ID3HEADERFLAGS_EXTENDED 608
- ID3HEADERFLAGS_FOOTERPRESENT 608
- ID3HEADERFLAGS_UNSYNC 608
- ID3V2FrameAttachedPicture 615
- ID3V2FrameBase 631
- ID3V2FrameComment 635
- ID3V2FrameLinkedInformation 638
- ID3V2FramePrivate 641
- ID3V2FrameRawBytes 643
- ID3V2FrameRecommendedBufferSize 645
- ID3V2FrameSynchronizedText 650
- ID3V2FrameSynchronizedTextDescriptor 653
- ID3V2FrameTextInformation 656
- ID3V2FrameURLLink 659
- ID3V2Utils 661
- idle 913, 1035
- idleFrequency 861
- idleHandler 860
- idStringToName 689
- importManifest 424
- incAbsTimecode 203
- incByteContainerLevel 204
- incClientCountTotal 248
- incrementAccept 310
- incrementBytesIn 77
- incrementBytesLoss 79
- incrementBytesOut 79
- incrementFileIn 77
- incrementFileOut 78
- incrementMediaInBytes 898, 1050
- incrementMediaLossBytes 1050
- incrementMediaOutBytes 1050
- incrementMessagesIn 77, 78
- incrementMessagesLoss 78, 79, 80
- incrementMessagesOut 78, 79
- incrementReject 310
- incSlotVersion 978
- index 371
- indexOf 36
- indexOfDifferent 37
- info 570, 571
- init 6, 299, 300, 387, 433, 438, 457, 467, 468, 473, 480, 502, 504, 670, 697, 715, 829, 977, 1002, 1009, 1029, 1088, 1111, 1130, 1141, 1150, 1248, 1280, 1289
- initContextLogging 577
- initialize 417
- initializeLogging 577
- initialManifest 454
- initLiveStreamRepeating 788, 1064, 1092
- initStream 785
- InputStream 23
- interleavePackets 60, 61
- interruptPlay 1091
- intToByteArray 34, 35
- intToByteArraySafeSync 662
- intValue 161
- invoke 926
- invokePrevious 775, 776
- IOPerformanceCounter 76
- ioPerformanceCounter 860
- ip 859
- isAcceptConnection 248, 327
- isAcceptSession 522
- isActive 516, 564, 1132, 1141
- isAddressMulticast 90
- isAMF0 149, 154

isAMF3 149, 154
isAMF3Start 123
isAnnounce 860, 868
isAnnounceOrDescribe 868
isAppend 1044
isAppInstanceLoaded 228
isApplicationLoaded 1250
isArrayStart 123
isAudio 213
isAudioCodecConfig 64
isAVSyncNonSR 910
isByteArrayStart 124
isByteContainerEmpty 204
isByteContainerFull 204
isCheckIpAddr 909
isCheckSSRC 909
isClient 961, 986
isClustered 1055
isConnected 326, 860, 869
isDebug 432
isDebugEnabled 569
isDebugLog 82
isDebugRTSPSession 874
isDescribe 860, 867
isDynamic 196
isDynamicLogContextLoaded 935, 951
isEmpty 92, 377, 379, 608
isEnabledFor 569
isEncrypted 337
isErrorEnabled 569
isFileInfo 525
isFirstABSTRequest 538
isFlashMediaLiveEncoder 343
isFlashVersion10 343
isFlashVersion90115 343
isFlashVersionH264Capable 343
isForceAMF0 815
isForceMPEGTSOut 924
isForceRTSPInterleaved 916
isGlobalLogValueSet 578
isHitEnd 1000
isInfoEnabled 569
isInMulticast 846
isInRange 376, 379
isIntData 148
isLastSentAbsTimecode 205
isLive 918
isLiveRepeater 342
isLiveStreamPacketize 1147
isLiveStreamTranscode 1153
isLoggedConnect 867
isLongTimecode 204
isMediaCasterPlay 1066
isMember 195
isMergeOnMetadata 1066
isMixedArrayStart 124
isModePlay 913
isModePublish 913
isModeUnknown 913
isMPEGTSOut 917
isMulticast 836, 846
isNew 202
ISO8601_FORMAT 554
ISO8601_PATTERN 554
isObjectEncodingAMF0 205, 344
isObjectEncodingAMF3 205, 343
isObjEnd 124
isObjStart 123
isOnMetadataPacket 66
isOpen 7, 1003, 1010, 1048
isOutMulticast 846
isOverlayAvailable 1204
isPacketizeAudio 1143
isPacketizeData 1144
isPacketizeVideo 1143
isPaused 903
isPending 818
isPersistent 962, 973, 986
isPlay 1035
isPlaying 1030
isPlaylistReady 431
isPlayLogged 517
isPublishStreamReady 902, 1065
isPurgingEnabled 433
isReceiveAudio 1049
isReceiveVideo 1049
isRecord 1035
isRecording 450, 461, 1134
isRecordingPaused 450, 461, 1134
isRedirectSession 530, 878

isRepeaterEdge 1143
isResetPlayStream 903
isResyncAudioVideoOnSR 905
isRTPIgnoreProfileLevelId 923
isRTPIncomingDatagramPortValid 275
isRTPWrapped 839
isRTSP 912
isRTSPAlwaysUseSDPPorts 922
isRTSPPull 912
isRunning 1206
isSecure 337, 486
isSendOnMetadata 1159, 1179, 1193
isSendPlayStopLogEvent 1058
isSendPublishStopLogEvent 1059
isSendRecordStopLogEvent 1059
isSendResult 773
isSendSDESEvents 917
isSession 674
isSessionValid 859, 865
isShutdownClient 876
isShutdownOnRelease 699
isShuttingDown 1263
isSSL 337
isStartStartupStreams 1267
isStream 674, 837
isStreamIsRunning 675
isStreamStarted 922
isSuspended 936, 947, 1224, 1264
isSwitchLog 1193
isTimeout 515, 919
isTimeoutSession 516
isTraceEnabled 569
isTranscodeResult 1068
isValid 697, 1016
isValidated 517
isValidateFMLEConnections 283, 347
isValidStreamDomainStr 525
isVersionFile 1105
isVHostRunning 946
isVideo 213
isVideoCodecConfig 64
isVideoKeyFrame 64, 65, 66
isVisited 1283
isWaitForVideoKeyFrame 1105
isWarnEnabled 569

isWowzaAudioOnly 735

J

JNDI_CONTEXT_NAME 553

K

KEYDATA_MODE_ENCRYPT 750

KEYDATA_MODE_INIT 749

KEYDATA_MODE_PLAYLIST 750

killClient 1250

killRTSPSession 1250

L

lastAuthenticateMethod 859

lastModified 8

len 206

length 9, 93, 1058, 1091

LICENSECOUNTER_DRM_EZDRM_LIVE 1240

LICENSECOUNTER_DRM_EZDRM_VOD 1241

LICENSECOUNTER_DRM_VERIMATRIX_LIVE 1241

LICENSECOUNTER_DRM_VERIMATRIX_VOD 1241

LICENSECOUNTER_NDVR 1240

LICENSECOUNTER_PUBLISHER 1240

LICENSECOUNTER_PUBLISHERTRANSCODER 1241

LICENSECOUNTER_TOTAL 1241

LICENSECOUNTER_TRANSCODE_DECODE 1240

LICENSECOUNTER_TRANSCODE_ENCODE 1240

liveStreamPacketizers 1117

load 975, 991

loadArchivedRecordings 438

loadArchivedStore 451

loadConfig 1286

loadConfigFile 1213, 1218

loadConfigProperties 105

loadFile 617

lock 726, 731, 739, 968, 991

lockRepeaterStreams 522, 902

log 569, 570

LOG4J_ID_KEY 552

LOG4J_PACKAGE_NAME 551

logDebug 779

logError 779

loggedConnect 859
LOGGERNAME_SERVER 576
logInfo 779
logLiveChunk 494, 538
logLiveFragment 544
logNotifier 945
LogNotifyCalculateIncremental 559
logVODChunk 494, 538
logVODFragment 544
logWarn 779
longToByteArray 35, 36
longValue 161

M

main 16, 946
makeNewLoggerInstance 577
MANIFEST_TAGNAME_CAN_PLAY 416
MANIFEST_TAGNAME_CAN_RECORD 416
MANIFEST_TAGNAME_CHUNK_GROUPING 416
MANIFEST_TAGNAME_CURRENT_TIME 417
MANIFEST_TAGNAME_HAS_ENCRYPTION 416
MANIFEST_TAGNAME_PURGE_TIME 417
MANIFESTFILE_KEY_ARTIFACT 369
MANIFESTFILE_KEY_AUDIO_CODEC 370
MANIFESTFILE_KEY_DVRTIME 369
MANIFESTFILE_KEY_ENCRYPTIONS 370
MANIFESTFILE_KEY_INDEX 369
MANIFESTFILE_KEY_METADATA 370
MANIFESTFILE_KEY_NAME 370
MANIFESTFILE_KEY_PACKETTIME 370
MANIFESTFILE_KEY_PACKETTIME90 370
MANIFESTFILE_KEY_SIZE 369
MANIFESTFILE_KEY_START 369
MANIFESTFILE_KEY_STOP 369
MANIFESTFILE_KEY_TYPE 369
MANIFESTFILE_KEY_UTCTIME 370
MANIFESTFILE_KEY_VIDEO_CODEC 370
MAXSTREAMINDEX 1115
md5Digest 84
MD5DigestUtils 84
md5Lock 84
MediaCasterItem 686
MediaCasterList 691
MediaCasterSettings 693

MediaCasterStreamItem 696
MediaCasterStreamManager 701
MediaCasterStreamMap 704
MEDIACASTERTYPE_LIVEREPEATER 670
MEDIACASTERTYPE_RTPLIVE 670
MEDIACASTERTYPE_SHOUTCAST 670
MEDIACASTERTYPE_UNKNOWN 670
MediaList 726
mediaList 739
MediaListRendition 733
MediaListSegment 739
mediaListSegment 731
MediaStreamBase 1111
mediaStreamListeners 1117
MediaStreamMap 1117
MediaUtils 88
members 187
MILLS_PER_HOUR 121
MIMETYPE_VIDEO_MP4 409
MIMETYPES_JPEG 614
MIMETYPES_PNG 614
MIMETYPES_URL 614
MISSING 998
MODE_PLAY 895
MODE_PUBLISH 895
MODE_UNKNOWN 894
ModuleBase 769
ModuleClientLogging 779
ModuleCore 784
ModuleFastPlay 793
ModuleMediaCaster 711
ModuleMediaCasterStreamMonitorAdvanced 803
ModuleProperties 806
monitors 802
msb0baseTime 95
msb1baseTime 95
MSG_STARTSTREAM 506
MSG_SWITCHSTREAM 506

N

name 726, 732
nameGroupId 1116
nameGroups 1116
NetworkUtils 90

newValue 98
newXPathFactory 107
next 1191
nextStreamId 1117
NO_OPTIONS 15
notifyActionOnCodecInfoAudio 1054
notifyActionOnCodecInfoVideo 1054
notifyActionOnMetaData 1054
notifyActionPause 1053
notifyActionPauseRaw 1053
notifyActionPlay 1053
notifyActionPublish 1054
notifyActionSeek 1053
notifyActionStop 1054
notifyActionUnPublish 1054
notifyDvrStreamManagerCreate 287
notifyDvrStreamManagerDestroy 288
notifyDvrStreamManagerInit 287
notifyDvrStreamStorageDeleted 453
notifyDvrStreamStoreCreate 453
notifyDvrStreamStoreDestroy 453
notifyDvrStreamStoreInit 453
notifyDvrStreamStoreLoaded 453
notifyLiveStreamDvrRecorderCreate 286
notifyLiveStreamDvrRecorderDestroy 287
notifyLiveStreamDvrRecorderInit 287
notifyLiveStreamPacketizerCreate 282
notifyLiveStreamPacketizerDestroy 283
notifyLiveStreamPacketizerInit 283
notifyLiveStreamTranscoderCreate 284
notifyLiveStreamTranscoderDestroy 284
notifyLiveStreamTranscoderInit 284
notifyMediaReaderClose 280
notifyMediaReaderCreate 280
notifyMediaReaderExtractMetaData 280
notifyMediaReaderInit 280
notifyMediaReaderOpen 280
notifyMediaStreamCreate 1123
notifyMediaStreamDestroy 1124
notifyMediaWriterOnFLVAddMetadata 277
notifyMediaWriterOnWriteComplete 277
notifyPlayPublish 1123
notifyPlayUnpublish 1122
notifySessionCreate 883
notifySessionDestroy 883
notifySlotDelete 991
notifySlotSetValue 991
notifyTimeReset 453
notifyVHostClientConnect 1290
notifyVHostCreate 1291
notifyVHostInit 1291
notifyVHostItemCreate 1286
notifyVHostItemDestroy 1287
notifyVHostItemUpdate 1287
notifyVHostShutdownComplete 1291
notifyVHostShutdownStart 1291

O

offset 206
ON_METADATA_TYPE 416
onAACEncodeInfo 722
onAcceptConnection 351
onAcceptLicense 354
onAcceptorCreate 1228
onAcceptorDestroy 1228
onAnnounce 824, 872
onApplicationCreate 290
onApplicationDestroy 290
onApplicationInstanceCreate 289
onApplicationInstanceDestroy 289
onAppStart 711, 745, 803
onAppStop 711, 745, 803
onBind 474, 476
onCalculateSourceAudioBitrate 1197
onCalculateSourceVideoBitrate 1197
onCall 746
onCallback 1074
onClientAccept 349
onClientConnect 349
onClientDisconnect 349
onClientReject 350
onCodecConfigAAC 719
onCodecInfoAudio 1073
onCodecInfoVideo 1073
onConnect 747
onConnectAccept 747
onConnectFailure 682
onConnectReject 748
onConnectStart 681

onConnectSuccess 681
onCreate 495
onData 677
onDescribe 824, 872
onDestroy 497
onDisconnect 352, 355, 717, 747
onDvrStreamManagerCreate 1128
onDvrStreamManagerDestroy 1128
onDvrStreamManagerInit 1128
onFile 73
onFillChunkDataPacket 498
onFillChunkEnd 497
onFillChunkStart 497
onFLVAddMetadata 1107
onFrameAAC 719
onFrameMP3 719
onGetParameter 824, 872
onGrabFrame 1203
onHeaderData 720, 722
onHTTPCupertinoEncryptionKeyCreateLive 751
onHTTPCupertinoEncryptionKeyCreateVOD 750
onHTTPCupertinoEncryptionKeyData 750
onHTTPCupertinoEncryptionKeyLiveChunk 751
onHTTPCupertinoEncryptionKeyRequest 750
onHTTPCupertinoEncryptionKeyVODChunk 751
onHTTPCupertinoStreamingSessionCreate 752
onHTTPCupertinoStreamingSessionDestroy 752
onHTTPRequest 476
onHTTPSsanJoseStreamingSessionCreate 753
onHTTPSsanJoseStreamingSessionDestroy 753
onHTTPSessionCreate 754
onHTTPSessionDestroy 754
onHTTPSmoothStreamingPlayReadyCreateLive 755
onHTTPSmoothStreamingPlayReadyCreateVOD 755
onHTTPSmoothStreamingSessionCreate 756
onHTTPSmoothStreamingSessionDestroy 756
onHTTPStreamerSessionCreate 533
onHTTPStreamerSessionDestroy 533
onIndex 496
onInit 496
onInitAfterLoadTemplate 1197
onInitBeforeLoadTemplate 1197
onInitStart 1196
onInitStop 1197
onLiveStreamDvrRecorderCreate 1136
onLiveStreamDvrRecorderDestroy 1136
onLiveStreamDvrRecorderInit 1136
onLiveStreamPacketizerCreate 1145
onLiveStreamPacketizerDestroy 1145
onLiveStreamPacketizerInit 1145
onLiveStreamTranscoderCreate 1154
onLiveStreamTranscoderDestroy 1154
onLiveStreamTranscoderInit 1154
onLog 556, 560
onMediaCasterCreate 679
onMediaCasterDestroy 679
onMediaReaderClose 1015
onMediaReaderCreate 1014
onMediaReaderExtractMetaData 1015
onMediaReaderInit 1014
onMediaReaderOpen 1014
onMediaStreamCreate 1083
onMediaStreamDestroy 1083
onMetaData 720, 722, 1072
onModuleLoad 744
onModuleUnload 744
onMP3EncodeInfo 722
onNewVHost 949
onOpen 496
onOptions 824, 872
onPause 825, 872, 1070
onPauseRaw 1072
onPlay 825, 873, 1069
onPlaylistItemStart 1160
onPlaylistItemStop 1160
onPublish 1070
onRecord 825, 873
onRedirect 825, 873
onRegisterPlayer 679
onRegisterStreamNameGroup 1200
onRejectConnection 351
onRejectLicense 354
onResetMediaCaster 684, 804
onResetStream 1201
onResponseWriteStart 927
onResponseWriteStop 927
onResult 743, 759
onRTPSessionCreate 757, 822
onRTPSessionDestroy 757, 822
onSeek 1070

onServerConfigLoaded 940
onServerCreate 938
onServerInit 938
onServerShutdownComplete 939
onServerShutdownStart 938
onSessionAudioDecodeCodecInfo 1200
onSessionAudioEncodeCodecInfo 1199
onSessionAudioEncodeCreate 1198
onSessionAudioEncodeInit 1198
onSessionAudioEncodeSetup 1199
onSessionDataEncodeCreate 1198
onSessionDataEncodeInit 1199
onSessionDestinationCreate 1197
onSessionVideoDecodeCodecInfo 1200
onSessionVideoEncodeCodecInfo 1199
onSessionVideoEncodeCreate 1198
onSessionVideoEncodeInit 1198
onSessionVideoEncodeSetup 1199
onSetParameter 824, 872
onSetSourceStream 680
onSetup 826, 873
onSharedObjectConnect 969
onSharedObjectCreate 969
onSharedObjectDestroy 969
onSharedObjectDisconnect 970
onShutdownStart 1200
onShutdownStop 1201
onSlotDelete 980
onSlotSetValue 980
onStop 1070
onStreamCreate 758, 803
onStreamDestroy 758, 803
onStreamStart 682, 1078
onStreamStop 682
onTeardown 826, 873
onTrim 720
onUnbind 474, 477
onUnPublish 1070
onUnRegisterPlayer 680
onUnregisterStreamNameGroup 1200
onValidateMediaCaster 683, 803
onValidateMediaCastersStart 683, 803
onValidateMediaCastersStop 683, 804
onVHostClientConnect 1271
onVHostCreate 1270

onVHostInit 1270
onVHostItemCreate 1269
onVHostItemDestroy 1269
onVHostItemUpdate 1269
onVHostShutdownComplete 1271
onVHostShutdownStart 1270
onWriteComplete 1107
open 6, 1003, 1009, 1162
order 187
ORDERED 16
output 818
OutputStream 26

P

p 1111
packetComplete 1036
packetizerLicenses 1116
packetOutput 1217
PARAM1 764
PARAM10 766
PARAM2 765
PARAM3 765
PARAM4 765
PARAM5 765
PARAM6 765
PARAM7 765
PARAM8 765
PARAM9 765
PARAMMETHODNAME 764
parseAllowDomains 260
parseBodyForParams 484
parseIdString 689
parseQueryStr 102
PASSWORDFILEFORMAT_CLEAR 299
PASSWORDFILEFORMAT_UNKNOWN 299
pathToFileURL 100
pause 787, 905, 1089
PAUSE_PAUSE 1086
PAUSE_PLAY 1086
PAUSE_TOGGLE 1086
pauseRaw 791, 1089
pauseRecording 451, 460, 1134
peekByte 122
PICTUREMAXFILESIZE 614

-
- PICTURETYPE_ARTISTLOGO 614
 - PICTURETYPE_COVERBACK 614
 - PICTURETYPE_COVERFRONT 613
 - PICTURETYPE_FILEICON 613
 - PICTURETYPE_ILLUSTRATION 614
 - PICTURETYPE_MOVIESCREENCAPTURE 614
 - PICTURETYPE_OTHER 613
 - PICTURETYPE_OTHERFILEICON 613
 - PICTURETYPE_PUBLISHERLOGO 614
 - ping 330
 - play 786, 904, 1088, 1089, 1157, 1181, 1184, 1189, 1190, 1191
 - play2 786
 - playDuration 733
 - PLAYEVENT_AFTERBUFFERFILL 1008
 - PLAYEVENT_AFTERMETADATA 1008
 - PLAYEVENT_BEFOREBUFFERFILL 1008
 - PLAYEVENT_BEFOREMETADATA 1008
 - PLAYEVENT_STARTPLAYBACK 1008
 - Playlist 1161
 - PlaylistItem 1164
 - PLAYSIZES_AUDIO_BYTES 1087
 - PLAYSIZES_AUDIO_COUNT 1087
 - PLAYSIZES_DATA_BYTES 1087
 - PLAYSIZES_DATA_COUNT 1087
 - PLAYSIZES_LOSS_BYTES 1087
 - PLAYSIZES_LOSS_COUNT 1088
 - PLAYSIZES_SIZE 1088
 - PLAYSIZES_VIDEO_BYTES 1087
 - PLAYSIZES_VIDEO_COUNT 1087
 - playStart 733
 - PLAYSTATUSTYPE_COMPLETE 1087
 - PLAYSTATUSTYPE_STOP 1087
 - PLAYSTATUSTYPE_SWITCH 1086
 - PLAYTRANSITION_APPEND 768
 - PLAYTRANSITION_APPEND_IMMEDIATE 768
 - PLAYTRANSITION_RESET 768
 - PLAYTRANSITION_RESET_IMMEDIATE 768
 - PLAYTRANSITION_STOP 768
 - PLAYTRANSITION_SWAP 768
 - PLAYTRANSITION_SWITCH 768
 - PLAYTRANSITION_UNKNOWN 768
 - PLAYTRANSITIONSTR_APPEND 767
 - PLAYTRANSITIONSTR_RESET 767
 - PLAYTRANSITIONSTR_STOP 767
 - PLAYTRANSITIONSTR_SWAP 767
 - PLAYTRANSITIONSTR_SWITCH 767
 - PLAYTRANSITIONSTR_UNKNOWN 767
 - postChunkAdded 440
 - postChunksPurged 441
 - preChunkAdded 440
 - preChunksPurged 440
 - previous 1192
 - properties 472, 726, 731, 739, 859
 - PROPKEY_CHUNK_CACHE_CLASS 399
 - PROPKEY_DVR_ALLOWABLE_AV_PACKET_DELTA 401
 - PROPKEY_DVR_APPEND_DISCONTINUITY_DELTA 396
 - PROPKEY_DVR_AUDIO_ONLY_CHUNK_TARGET_DURATION 404
 - PROPKEY_DVR_BREAK_ON_PTS 406
 - PROPKEY_DVR_CHUNK_DURATION_MINIMUM 410
 - PROPKEY_DVR_CHUNK_GROUPING_SECONDS 396
 - PROPKEY_DVR_CHUNK_READER_CLASS 397
 - PROPKEY_DVR_CHUNK_WRITER_CLASS 398
 - PROPKEY_DVR_DEBUG_MAXIMUM_RAW_PACKETS 403
 - PROPKEY_DVR_DEBUG_METHODS 406
 - PROPKEY_DVR_DEBUG_PLAYER_ADAPTER 406
 - PROPKEY_DVR_DEBUG_RAW_PACKETS 403
 - PROPKEY_DVR_DEBUG_TOSSED_HOLDERS 403
 - PROPKEY_DVR_ENCRYPTION_INFO_DELEGATE 407
 - PROPKEY_DVR_FILE_SYSTEM_CLASS 398
 - PROPKEY_DVR_LOG_ILLEGAL_CHUNK_DETAILS 401
 - PROPKEY_DVR_MANIFEST_PERSISTENT_CLASS 399
 - PROPKEY_DVR_MAX_CHUNK_LOG 405
 - PROPKEY_DVR_MAX_ILLEGAL_CHUNKS_LOGGED 402
 - PROPKEY_DVR_PACKET_DELTA_TO_NOTIFY 402
 - PROPKEY_DVR_PACKET_DELTA_TO_RESET_TIME 402
 - PROPKEY_DVR_PACKET_SORT_TIME 405
 - PROPKEY_DVR_PLAYLIST_REQUEST_DELEGATE 407
 - PROPKEY_DVR_RECORDINGS_LOADER_CLASS 400
 - PROPKEY_DVR_SANJOSE_ABST_DURATION_TOLERANCE 409
 - PROPKEY_DVR_SANJOSE_ABST_TIMESCALE 409
 - PROPKEY_DVR_SANJOSE_PLAYLIST_DELIVERYTYPE 407
 - PROPKEY_DVR_SANJOSE_PLAYLIST_LIVE_STREAMTYPE
-

PE 408
PROPKEY_DVR_SANJOSE_PLAYLIST_MIMETYPE 407
PROPKEY_DVR_SANJOSE_PLAYLIST_RECORDED_STR
EAMTYPE 407
PROPKEY_DVR_SANJOSE_PLAYLIST_VERSION 407
PROPKEY_DVR_SHARED_SECRET 406
PROPKEY_DVR_TEXT_READER_CLASS 400
PROPKEY_DVR_TEXT_WRITER_CLASS 400
PROPKEY_DVR_WINDOW_DURATION 397
PROPKEY_RECORD_AUDIO 404
PROPKEY_RECORD_DATA 404
PROPKEY_RECORD_VIDEO 404
PROPKEY_START_RECORDING_ON_STARTUP 404
PROTO_HTTPCUPERTINO 602
PROTO_HTTPDVARCHUNK 603
PROTO_HTTPSANJOSE 603
PROTO_HTTPSCUPERTINO 603
PROTO_HTTPSDVARCHUNK 603
PROTO_HTTPSMOOTH 603
PROTO_HTTPSSANJOSE 603
PROTO_HTTPSSMOOTH 603
PROTO_HTTPSSTREAMER 603
PROTO_HTTPSTREAMER 602
PROTO_RTMP 601
PROTO_RTMPE 602
PROTO_RTMPS 602
PROTO_RTMPT 602
PROTO_RTMPTE 602
PROTO_RTMPTS 602
PROTO_RTSP 602
publish 785, 1050, 1111, 1172, 1173
PublishingProviderBase 1178
PublishingProviderLive 1181
PublishingProviderMediaReader 1184
purge 967, 985
purgeEntries 419, 462
purgeManifestEntries 452
put 188, 189, 218, 219, 972
putAudioPacketizerItem 829, 877
putDvrRecorder 1067
putFileInfo 525
putFrame 609
putGlobalLogValue 578
putHTTPStreamerAdapter 1266
putLiveStreamTranscoder 1068
putMetaData 1106
putRTSPSessionExtraLine 922
putRTSP TunnelingSession 834
putSlot 961, 986
putStreamNameParts 524
putStreamPacketizerItem 830, 877
putVideoPacketizerItem 830, 877

Q

QUERY_PARAM_DVR 431
queryStr 861

R

ranges 378
read 7, 23
READ_ACCESS_ALL 323
READ_ACCESS_NONE 323
READACCESS 984, 1029
readAppConfig 231
readAppInstConfig 275
readChunk 58
readChunkHeader 58
readConfig 936, 953
readHeader 58, 59
readPrevChunkHeader 58
readVHostConfig 1267
readXMLConfig 953
receiveAudio 789
RECEIVER_NAME_KEY 552
receiveVideo 789
record 903, 904
recordingPaused 436
recordingReset 437
recordingResumed 437
recordingStarted 436
recordingStopped 437
redirectConnection 328, 329
redirectSession 531, 862, 879
redirectSessionCode 862
redirectSessionMessage 862
redirectSessionURL 862
referrer 861
refreshManifest 417

registerCallback 1051
registerOnPlayStatus 1052
registerOnStatus 1051
registerPlayer 672, 698, 709
registerPlayRTPSession 267
rejectConnection 310, 327, 328
rejectSession 522, 863
release 699, 708, 962, 986
releaseMediaCaster 713
releaseSessionId 881
releaseSocketAddress 831
releaseStream 785
releaseUDPPortPair 832
reloadConfig 1286
reloadVHostConfig 931, 947
remove 132, 168, 189, 220, 708, 973, 1290
removeAcceptorListener 1254
removeActionListener 871
removeAppInstance 231
removeApplication 1267
removeApplicationInstanceListener 229
removeApplicationListener 1254, 1290
removeClient 962, 974, 986, 1250
removeClientListener 250, 1052, 1053
removeConnectionListener 309
removeDvrChunkListener 462
removeDvrRecorder 1067, 1126
removeDvrRecorderListener 286
removeDvrRecordingListener 453
removeDvrStoreListener 452
removeDvrStreamManagerListener 287
removeFrame 609
removeFromPlaylist 1190
removeGlobalLogValue 578
removeGlobalLogValues 577
removeHTTPStreamerSession 274
removeIdleWorkerListener 1260
removeItem 1162
removeListener 1192
removeLiveStreamPacketizer 1124
removeLiveStreamPacketizerListener 282
removeLiveStreamTranscoder 1067
removeLiveStreamTranscoderListener 283
removeMediaCasterListener 253
removeMediaReaderListener 279
removeMediaStreamListener 251, 1123
removeMediaWriterListener 277
removeMetaDataListener 721
removeModuleListener 257
removeNameGroup 1125
removePlayStreamByName 255
removePublisher 272
removeRendition 740
removeRTPSession 267
removeRTSPStream 864
removeRTSPTunnelingSession 833
removeSegment 727
removeServerListener 933, 950
removeSession 882
removeSessionListener 883
removeSharedObjectListener 252, 974
removeSlotListener 966, 991
removeStream 1121
removeStreamDomainStr 526
removeTrack 898
removeTrackInternal 898
removeVHostItemListener 1286
renditions 739
reparentClient 345, 1263
ReplaceItem 98
requestFilters 472
requiresLayout 564
reset 457, 698, 727, 1088, 1272, 1282
resetMDC 577
resetMediaCasterStream 276
resetNoLookup 1088
resetSentMetadataFlag 905
resetStream 430, 449, 712, 1131, 1142, 1150
resetTimecodes 1093
resolveMediaList 1001
resolvePlayAlias 1079, 1080, 1081
resolveStreamAlias 1079, 1081
ResponseFunction 811, 812
ResponseFunctions 817
resumeEncoding 27
resumeRecording 451, 461, 1134
retrieveRawChunk 387, 435
REVERSE 6
rewind 1010
RTPContext 829

RTPDestination 836
RTPPort 842
RTPPushPublishSession 848
RTPSession 863
rtpSession 297
RTPSessions 881
RTPStream 897
RTPUtils 1210
rtpWriteListener 860
rtspPlayRangeStart 862
rtspPlayRangeStop 862
rtspTunnelingSessionId 858
run 1189

S

SANJOSE_F4M_STREAMINGTYPE_STREAMING 409
SANJOSE_F4M_STREAMTYPE_DVR 408
SANJOSE_F4M_STREAMTYPE_LIVE 408
SANJOSE_F4M_STREAMTYPE_LIVEORRECORDED 408
SANJOSE_F4M_STREAMTYPE_RECORDED 408
SANJOSE_F4M_VERSION_1_0 409
SANJOSE_F4M_VERSION_2_0 409
SDPLOCATION_AUDIO 894
SDPLOCATION_STREAM 894
SDPLOCATION_VIDEO 894
seek 7, 786, 1010, 1089, 1158, 1181, 1184
SEEK_EXACT 1009
SEEK_KEYCLOSE 1009
SEEK_KEYDOWN 1008
SEEK_KEYUP 1008
SEEKTARGET_AUDIO 1008
SEEKTARGET_ENHANCED 1008
SEEKTARGET_VIDEOKEYFRAME 1007
segments 726
send 966, 990, 1047, 1048
sendAMF3 1047, 1048
sendClientOnStatusError 776
sendControlBytes 1056
sendDirect 1047
sendDirectAMF3 1046, 1047
sendInternal 990
sendLivePlaySeek 1038
sendLivePlayStart 1037
sendLivePlaySwitch 1038

sendMessage 845
sendOnMetadata 429, 1178
sendPauseNotify 1042, 1043
sendPlayReset 1038
sendPlaySeek 1039, 1040
sendPlayStart 1040, 1041
sendPlayStatus 1042
sendPlayStop 1039
sendPlaySwitch 1040
sendResponse 845
sendResult 774, 775
sendStreamNotFound 1037
sendStreamOnStatusError 776
sendUnpauseNotify 1043
sendVODPlaySwitch 1037
sendZeroLengthPacket 1012
serialize 126, 139, 145, 162, 163, 175, 180, 192, 362, 365, 372, 376, 379, 383, 385, 412, 426, 610, 632, 664
serializeBody 615, 635, 638, 641, 643, 645, 650, 656, 659, 664
serializeDate 110
serializeFooter 609
serializeHeader 609
serializeInt 110
serializeString 112, 632
serializeStringLen 632
serializeStringNoLength 112
serializeTags 609
serializeZeroLengthString 111
Server 945
serverIp 861
serverPort 861
service 501
sessionClosed 673, 846
sessionId 858
sessionOpened 672, 845
SESSIONPROTOCOL_COUNT 514
SESSIONPROTOCOL_CUPERTINOSTREAMING 514
SESSIONPROTOCOL_DVRCHUNKSTREAMING 514
SESSIONPROTOCOL_SANJOSESTREAMING 514
SESSIONPROTOCOL_SMOOTHSTREAMING 514
SESSIONPROTOCOL_UNKNOWN 514
SESSIONPROTOCOL_WEBMSTREAMING 514
sessionStart 715
sessionStop 715
SESSIONTYPE_LIVE 513

SESSIONTYPE_LIVEDVR 513
SESSIONTYPE_UNKNOWN 513
SESSIONTYPE_VOD 513
set 135, 136, 171, 172
setAbsTimecode 213
setAbsTimecodeLong 203
setAbsTimecodeShort 203
setAcceptConnection 248, 345
setAcceptConnectionDescription 344
setAcceptConnectionExObj 344
setAcceptConnectionObj 344
setAcceptSession 523
setActive 516
setAddressCount 847
setAdminInterfaceHostPort 1253
setAllowDomains 260
setAnnounce 868
setAppend 1044
setAppInstance 518, 671, 866, 1152
setAppInstanceName 907
setAppInstanceProperty 807
setApplication 564
setApplicationInstanceTouchTimeout 278
setApplicationProperty 806
setApplicationTimeout 257, 1256
setAppName 906
setAudioCodecId 735
setAudioHost 839
setAudioPort 838
setAudioSize 1030
setAudioTC 1033
setAuthenticatePlayHandler 866
setAuthenticatePublishHandler 866
setAuthenticationMethod 474, 480
setAVSyncMethod 910
setBandwidthLimit 786
setBaseClass 688, 1274
setBitrateAudio 734
setBitrateTotal 734
setBitrateVideo 734
setBody 814
setBufferSize 646
setBufferTime 334, 787, 1030, 1090
setByteContainerLevel 204
setCanPlay 459
setCanRecord 459
setCheckIpAddr 909
setCheckSSRC 909
setChecksum 999
setChunkCounter 205
setChunkGroupDuration 386
setClassName 193, 196
setClient 298, 304, 1036
setClientIdleFrequency 261, 1258
setClientProperty 807
setClientTimeout 1252
setClustered 1055
setCodecInfoAudio 430
setCodecInfoVideo 430
setCommandInterface 949
setCommandInterfaceHostPort 933, 949
setConfigDir 1282
setConnected 869
setConnectionLimit 1283
setConnectionTimeout 688
setConnectionValidator 309
setContentTypes 652
setCookieStr 523, 875
setCoreHandlerPoolSize 934, 950, 1251
setCoreTransportPoolSize 934, 950, 1251
setCurrentDvrTime 433
setData 639, 977
setDataBuffer 211
setDataSize 1031
setDataTC 1034, 1035
setDataTypes 1034
setDebug 432
setDebugLog 82
setDebugRTSPSession 874
setDefaultStreamingStore 448
setDescribe 868
setDescription 616, 636, 639, 688, 1276
setDirection 996
setDirecton 8
setDomainName 1221
setDuration 1158, 1181, 1185
setDvrRecorder 1066
setDvrRecorderId 1132
setDvrRecorderList 286, 1063
setDvrSessionInfo 527

setDynamic 196
setDynamicLogProperties 935, 951, 1263
setEmbeddedFlag 646
setEncoding 564
setEncryptions 362
setExt 1058
setFastPlay 794
setFastPlaySettings 331, 1048
setFileExtension 1173
setFileIOPoolSize 1252
setFlags 633, 664
setFlashVer 324
setForceAMF0 815
setForceMPEGTSOut 924
setForceRTSPInterleaved 916
setFps 995
setFrameIdentifier 639
setHandler 844
setHasEncryption 459
setHeader 488
setHeaderSize 1060
setHeight 736
setHost 837, 901
setHostType 839
setHTTPStreamerAdapter 518
setHTTPStreamerItem 501
setHTTPStreamerList 270
setHTTPStreamerSession 1004, 1063
setID 503
setId 201
setIdleCheckFrequency 1259
setIdleFrequency 338, 874
setIdleHandler 869
setIdleMinimumWaitTime 1262
setIdleWorkerCount 1260
setIdStr 632, 663
setIndex 1165
setInnerObj 197
setIntData 148
setIntHeader 488
setIOPerformanceCounter 876
setIoPerformanceCounter 948
setIp 867
setIpAddress 519, 1222
setIsPlaying 1030
setKeepAliveTime 689
setKeepAliveTimeout 1260
setLanguage 651
setLastAccessed 999
setLastAuthenticateMethod 866
setLastClientId 979
setLastOperation 979
setLastSentAbsTimecode 205
setLastValidateTime 342
setLive 918
setLivePlaylist 544
setLiveRepeaterCapabilities 346
setLiveStreamDvrRecorderControl 286
setLiveStreamingPacketizer 519
setLiveStreamPacketizer 700, 787, 1064
setLiveStreamPacketizerControl 275
setLiveStreamPacketizerId 1142
setLiveStreamPacketizerList 270, 346, 1062
setLiveStreamRepeater 700, 1064
setLiveStreamTranscoderControl 285
setLiveStreamTranscoderItem 1152
setLiveStreamTranscoderList 284, 346, 1062
setLock 733, 741
setLoggedConnect 867
setLongTimecode 204
setMaximumPendingReadBytes 259, 1258
setMaximumPendingWriteBytes 258, 1257
setMaximumSetBufferTime 259, 1258
setMaxRTCPWaitTime 910
setMaxStorageDirDepth 269
setMediaCasterDef 672
setMediaCasterHostPortConfig 694
setMediaCasterId 671
setMediaCasterItem 1077
setMediaCasterPlay 1066
setMediaCasterProcessorCount 694
setMediaCasterType 676
setMediaCasterValidator 278
setMediaList 741
setMediaListProvider 288
setMediaListSegment 734
setMediaReaderItem 1003, 1009
setMediaWriterItem 1105
setMergeOnMetadata 1066
setMessageBytes 813

setMetaDataProvider 1060
setMimeType 616
setMode 915
setMPEGTSAudioLanguage 911
setMPEGTSAudioPID 912
setMPEGTSOut 918
setMPEGTSProgramID 911
setMPEGTSVideoPID 911
setMultiplier 995
setName 228, 246, 687, 728, 735, 840, 965, 978, 990, 1031, 1032, 1090, 1274, 1282
setNetConnection 1036
setNetConnectionIdleFrequency 1259
setNetConnectionProcessorCount 1253
setNew 202
setObjectEncoding 149, 153, 205, 344
setOffsetToNextTag 646
setOpen 1048
setOutHost 913
setPacketizeAudio 1143
setPacketizeData 1144
setPacketizeVideo 1143
setParent 992, 1105
setPersistent 963, 973, 987
setPictureData 616
setPictureDataAsURL 616
setPictureType 616
setPingTimeout 258, 1257
setPlay 1035
setPlayClass 1275
setPlayDuration 529, 737
setPlayer 1044
setPlayLogged 517
setPlayStart 529, 736
setPollingInterval 1192
setPort 565, 1222
setProcessorCount 1223
setProperties 474, 477, 501, 1003, 1013, 1283
setProperty 292, 687, 964, 965, 987, 988, 1275
setPublishAudioCodecId 1065
setPublishVideoCodecId 1065
setQueryStr 522, 871, 1057
setRange 376
setRealTimeStartTime 1158, 1181, 1185
setReceiveAudio 1049
setReceiveVideo 1049
setReceiveVideoFPS 1049
setReconnectWaitTime 676
setRecord 1035
setRecordAudio 1133
setRecordData 1133
setRecordingName 1134
setRecordingStreamStore 447
setRecordVideo 1133
setRedirectSession 530, 878
setRedirectSessionBody 531
setRedirectSessionCode 530, 878
setRedirectSessionContentType 532
setRedirectSessionMessage 879
setRedirectSessionURL 531, 878
setReferrer 521, 871
setRemoteHost 564
setRepeat 1162, 1191
setRepeaterEdge 1143
setRepeaterMediaCasterDef 505
setRepeaterOriginUrl 259, 342, 790
setRepeaterQueryString 260
setRequestFilters 473, 480
setResetPlayStream 903
setResponseCode 489
setResyncAudioVideoOnSR 905
setRetAMFNumber 814
setRsoStorageDir 262
setRTPAVSyncMethod 266
setRTPDestination 923
setRTPIIdleFrequency 261, 1259
setRTPIgnoreProfileLevelId 924
setRTTPMaxRTCPWaitTime 266
setRTTPPlayAuthenticationMethod 265
setRTTPublishAuthenticationMethod 265
setRTTPSession 298, 304, 849
setRTTPStream 1061
setRTTPWrapped 839
setRTSP 912
setRTSPAlwaysUseSDPPorts 922
setRTSPBindIpAddress 281, 920
setRTSPConnectionAddressType 281, 920
setRTSPConnectionIpAddress 281, 920
setRTSPMaximumPendingWriteBytes 279, 919
setRTSPOriginAddressType 282, 921

setRTSPOriginIpAddress 282, 920
setRTSPPlayRangeStart 875
setRTSPPlayRangeStop 875
setRTSPPull 912
setRTSPSessionDescription 917
setRTSPSessionName 917
setRTSPSessionTimeout 279, 919
setRTSPTunnelingSessionId 874
setSDPData 849
setSDPLang 923
setSendOnMetadata 1158, 1179, 1193
setSendPlayStopLogEvent 1059
setSendPublishStopLogEvent 1059
setSendRecordStopLogEvent 1059
setSendSDESEvents 917
setSeq 213
setServer 1290
setServerIp 520, 870
setServerPort 521, 870
setSession 899
setSessionId 515, 863
setSessionProtocol 520
setSessionTimeout 517
setSessionTracker 548
setSessionType 519
setSessionValid 865
setSharedObjectReadAccess 264, 338
setSharedObjectWriteAccess 265, 338
setShutdownClient 345, 876
setShutdownOnRelease 699
setShuttingDown 1263
setSize 201, 210, 736
setSlotValue 988, 989
setSlotVersion 978
setSoVersion 978
setSrc 202, 212, 812, 1031
setSSLConfig 1225
setSslFactoryClass 1223
setStartRecordingOnStartup 1135
setStartStartupStreams 1267
setStartTC 996
setStartTCOffset 996
setStorageDir 966, 974, 991
setStream 516, 671, 1172
setStreamAudioSampleAccess 263, 340
setStreamExt 523, 699, 907
setStreamFileMapper 269
setStreamKeyDir 261
setStreamName 523, 907, 1120, 1151
setStreamNameAliasProvider 271
setStreamNameLogging 907
setStreamPort 838
setStreamPosition 524, 1013
setStreamProperty 807
setStreamQueryStr 913
setStreamReadAccess 263, 340
setStreamSessionId 908
setStreamSessionIp 908
setStreamSessionVersion 908
setStreamStorageDir 261
setStreamTimeout 673
setStreamType 247, 327, 686, 788, 906, 1046, 1172
setStreamTypeStr 505
setStreamVersionHandler 449
setStreamVideoSampleAccess 263, 339
setStreamWriteAccess 264, 341
setSuspended 1224
setSwitchLog 1193
setTargetEncoding 153
setTextEncoding 615, 636, 651, 657, 660
setThreadContext 347
setTimecode 202, 212, 654, 815
setTimecodes 212
setTimeoutSession 516
setTimeStampFormat 651
setTrack 843
setTranscodeResult 1068
setTranscoderName 1151
setTransportMode 915
setTTL 839, 846
setType 122, 201, 211, 736, 815
setUDPMangedDeliveryCount 924
setUDPMangedDeliveryDelay 924
setUri 521, 870
setURL 639, 660
setUserAgent 521, 865
setUserAgents 933, 949
setUserHTTPHeader 529
setUserQueryStr 527
setValid 697

-
- setValidateFMLEConnections 283, 347
 - setValidationFrequency 258, 1257
 - setValue 636, 654, 657
 - setVersion 963, 987
 - setVersionFile 1105
 - setVHost 297, 304, 502, 515, 864
 - setVideoCodecId 735
 - setVideoHost 838
 - setVideoPort 837
 - setVideoSize 1031
 - setVideoTC 1034
 - setVisited 1283
 - setVODLastTimeTC 921
 - setVODPlayLen 922
 - setVODStartTimeTC 921
 - setWaitForVideoKeyFrame 1105
 - setWidth 736
 - setWowzaAudioOnly 735
 - SharedObject 984, 985
 - SHARED_OBJECT_CMD_CONNECT 959
 - SHARED_OBJECT_CMD_CONNECT_SUCCESS 960
 - SHARED_OBJECT_CMD_DELETE 960
 - SHARED_OBJECT_CMD_DISCONNECT 959
 - SHARED_OBJECT_CMD_ERROR 960
 - SHARED_OBJECT_CMD_SEND 960
 - SHARED_OBJECT_CMD_SETVALUE 959
 - SHARED_OBJECT_STATUS_CHANGE 960
 - SHARED_OBJECT_STATUS_CLEAR 960
 - SHARED_OBJECT_STATUS_DELETE 960
 - SHARED_OBJECT_STATUS_SUCCESS 960
 - shortValue 161
 - shouldDeleteArchivedStream 359, 466
 - shouldDvrRecord 1138
 - shouldLoadArchivedStream 359, 466
 - shouldLoadStream 438
 - shouldLoadStreamVersion 439
 - shouldStartRecordingOnStartup 1135
 - shutdown 227, 246, 457, 493, 516, 537, 543, 548, 672, 698, 705, 829, 844, 865, 902, 1033, 1088, 1131, 1141, 1151, 1249, 1290
 - shutdownAppInstance 231
 - shutdownApplication 1263
 - shutdownClient 246, 326, 862
 - shutdownRTPSession 834
 - shutdownSession 502
 - shutdownStream 712
 - sinfo 1110
 - size 133, 143, 168, 188, 962, 972, 985, 1058, 1091, 1227
 - skipByte 123
 - sloppyGetTrack 898
 - splitCookie 70
 - splitPragmas 69
 - splitQueryStr 69
 - stackTraceToString 42
 - stampToString 93
 - start 98, 371, 946
 - startApplicationInstance 1265
 - startAudioData 1174
 - startAudioPacket 1061
 - startChunk 429
 - startCommandInterface 930, 946
 - startDataData 1176
 - startDataPacket 1062
 - startMediaCasterStream 276
 - startPlay 1091
 - startPlayback 1012
 - startPublishing 1055
 - startRecording 450, 460, 1133
 - startRTPPull 1211, 1212
 - startServer 946
 - startStartupStreams 1267
 - startStream 702, 1131, 1142
 - startsWith 37
 - startVHost 931, 947
 - startVHosts 931, 947
 - startVideoData 1174
 - startVideoPacket 1061
 - STAT_connect_application_not_available 598
 - STAT_connect_application_not_found 599
 - STAT_connect_bad_gateway 599
 - STAT_connect_internal_error 599
 - STAT_connect_license_limit 599
 - STAT_connect_pending_wating 598
 - STAT_connect_redirect 599
 - STAT_connect_rejected_by_application 598
 - STAT_connect_rejected_by_module 598
 - STAT_connect_resource_limit 599
 - STAT_connect_service_unavailable 599
 - STAT_connect_successful 598
 - STAT_connect_unknown_protocol 598
 - STAT_general_internal_error 601
-

- STAT_general_successful 601
- STAT_play_bad_request 600
- STAT_play_internal_error 600
- STAT_play_rejected_by_application 600
- STAT_play_rejected_by_module 600
- STAT_play_stream_not_found 600
- STAT_play_successful 599
- STAT_play_unsupported_media_type 600
- STAT_publish_bad_request 600
- STAT_publish_in_use 601
- STAT_publish_internal_error 601
- STAT_publish_rejected_by_application 600
- STAT_publish_successful 600
- STAT_publish_unsupported_media_type 601
- STAT_stop_client_disconnect 601
- STAT_stop_successful 601
- statusCodeToStr 71
- stop 371
- stopAdminAgent 936, 946
- stopCommandInterface 930, 946
- stopMediaCasterStream 276
- stopName 1032, 1090
- stopPublishing 1055
- stopRecording 450, 461, 1134
- stopRTPPull 1210
- stopServer 946
- stopStartupStreams 1267
- stopStream 702
- stopVHost 931, 947
- stopVHosts 931, 947
- storeChunks 452, 461
- storeOnMetadata 452, 461
- Stream 1188
- streamCodecToString 55
- streamExists 702, 901
- STREAMINFO_SESSIONATTRIBUTES 897
- STREAMINFO_SESSIONBANDWIDTH 896
- STREAMINFO_SESSIONCONNECTIONDATA 896
- STREAMINFO_SESSIONEMAILADDRESS 896
- STREAMINFO_SESSIONINFORMATION 896
- STREAMINFO_SESSIONNAME 895
- STREAMINFO_SESSIONPHONENUMBER 896
- STREAMINFO_SESSIONPORIGIN 895
- STREAMINFO_SESSIONPROTOCOLVERSION 895
- STREAMINFO_SESSIONREPEATTIMES 896
- STREAMINFO_SESSIONTIMEZONES 897
- STREAMINFO_SESSIONTIMING 896
- STREAMINFO_SESSIONURI 896
- StreamItem 1274
- streamLicenses 1116
- StreamList 1277
- streamLock 1116
- streamMonitorAudioStartTimeout 802
- streamMonitorAudioTCNegTolerance 801
- streamMonitorAudioTCPosTolerance 801
- streamMonitorAudioTCToleranceEnable 801
- streamMonitorAudioTimeout 802
- streamMonitorAVSyncTolerance 802
- streamMonitorAVSyncToleranceEnable 802
- streamMonitorDataTCNegTolerance 801
- streamMonitorDataTCPosTolerance 801
- streamMonitorDataTCToleranceEnable 801
- streamMonitorDebug 802
- streamMonitorResetNameGroups 802
- streamMonitorStreamStartTimeout 800
- streamMonitorStreamTimeout 800
- streamMonitorVideoStartTimeout 802
- streamMonitorVideoTCNegTolerance 801
- streamMonitorVideoTCPosTolerance 801
- streamMonitorVideoTCToleranceEnable 801
- streamMonitorVideoTimeout 802
- streamNames 1116
- streamNamesLock 1116
- streamNameToGroup 1116
- streamNameToValidFilename 47
- streamPacketizers 862
- streams 858, 1116
- streamsOrder 858
- streamSrcToMediaCaster 708
- STREAMTIMEOUTREASON_GOOD 669
- STREAMTIMEOUTREASON_MISSING 669
- STREAMTIMEOUTREASON_NORTSPSESSION 669
- STREAMTIMEOUTREASON_NOSESSION 669
- STREAMTIMEOUTREASON_NOSTREAM 669
- STREAMTIMEOUTREASON_NOTIMEOUT 669
- STREAMTIMEOUTREASON_NOURL 669
- STREAMTIMEOUTREASON_RECONNECTRUNNING 669
- STREAMTIMEOUTREASON_UNKNOWN 668
- streamToFileForRead 1075

streamToFileForWrite 1076
streamToIndex 1120
StreamUtils 1215
StringUtils 92
suspendAllHostPorts 1264
suspendAllVHosts 935, 947
suspendCommandInterface 946
suspendEncoding 27
suspendServer 936, 947
switchName 1032, 1090
switchPlay 1091
switchSetupToMPEGTS 914
SystemUtils 95

T

TAG_APIC 624
TAG_COMM 631
TAG_LINK 624
TAG_PRIV 624
TAG_RBUF 624
TAG_SYLT 624
TAG_TALB 624
TAG_TBPM 625
TAG_TCOM 625
TAG_TCON 625
TAG_TCOP 625
TAG_TDEN 625
TAG_TDLY 625
TAG_TDOR 625
TAG_TDRC 625
TAG_TDRL 626
TAG_TDTG 626
TAG_TENC 626
TAG_TEXT 626
TAG_TFLT 626
TAG_TIPL 626
TAG_TTT1 626
TAG_TTT2 626
TAG_TTT3 626
TAG_TKEY 627
TAG_TLAN 627
TAG_TLEN 627
TAG_TMCL 627
TAG_TMED 627
TAG_TMOO 627
TAG_TOAL 627
TAG_TOFN 627
TAG_TOLY 628
TAG_TOPE 628
TAG_TOWN 628
TAG_TPE1 628
TAG_TPE2 628
TAG_TPE3 628
TAG_TPE4 628
TAG_TPOS 628
TAG_TPRO 629
TAG_TPUB 629
TAG_TRCK 629
TAG_TRSN 629
TAG_TRSO 629
TAG_TSOA 629
TAG_TSOP 629
TAG_TSOT 629
TAG_TSRC 629
TAG_TSSE 630
TAG_TSST 630
TAG_TXXX 631
TAG_UNKN 624
TAG_WCOM 630
TAG_WCOP 630
TAG_WOAF 630
TAG_WOAR 630
TAG_WOAS 630
TAG_WORS 631
TAG_WPAY 631
TAG_WPUB 631
TAG_WXXX 631
TAGS_TEXTINFORMATION 630
TEMP_CONSOLE_APPENDER_NAME 553
TEMP_LIST_APPENDER_NAME 553
terminate 1280
testFlashVersion 343
testNextByte 122
TEXTENCODING_ISO_8859_1 623
TEXTENCODING_UTF16 623
TEXTENCODING_UTF16BE 623
TEXTENCODING_UTF8 624
ThreadPool 1279
TIME_MAP_TYPE 416

timeCreated 860
timeReset 437
TIMESTAMP_RULE_FORMAT 552
TIMESTAMPFORMAT_MILLISECONDS 650
TIMESTAMPFORMAT_MPEG 650
toArray 144
toByteBuffer 144
toHex 41
toLong 41
toNTPTime 96
toSMILString 727, 733, 740
toString 140, 146, 162, 176, 180, 192, 202, 212, 294, 363, 365, 377, 380, 383, 385, 689, 726, 733, 739, 836, 1165, 1223, 1276, 1283
totalIOPerformance2Last 860
totalIOPerformanceLast 860
touch 278, 326, 515, 865, 919, 1000, 1131, 1143
touchApplicationInstance 1264
toValidFilename 47
trait 187
transportFindBestMatch 918
traverseDirectory 48
triggerAMF3Switch 127
trim 1051, 1111
trimTrailingZero 632
truncatePacket 210
type 122, 371, 732

U

UDPAppender 563
unbind 844
unbindAllHostPorts 1264
unbindAllVHosts 936, 947
uncacheRTPStream 832
unlock 968, 992
unlockRepeaterStreams 902
unpublish 1173
unregisterCallback 1051
unregisterOnPlayStatus 1052
unregisterOnStatus 1051
unregisterPlayer 672, 698, 709
updateIOPerformance 948
updateLoggingDuration 950, 1057, 1256
updateLoggingValues 494, 520, 538, 544, 871, 1057, 1091

updateOnCuePointTimecode 66
updateSDPDestination 1210
uri 861
URL_SAFE 16
urlToId 101
URLUtils 100
userAgent 858
userExists 303

V

validateConnection 353
validateLicense 356
validateNewConnection 309
validStreamDomainToString 525
valueOf 93
versionFile 48
vhost 297, 858
VHOST_DEFAULT 1240
VHostItem 1282
VHostList 1286
VHostSingleton 1289
videoCodecId 732
videoCodecStringToId 56
videoCodecToMetaDataString 55
videoCodecToString 56
videoCodecTypeToString 89
videoPacketizers 862
VIDEOSAMPLE_ACCESS_ALL 322
VIDEOSAMPLE_ACCESS_NONE 323
VIDEOSAMPLEACCESS 1029

W

warn 573
width 732
WMSLogger 568
WMSLoggerFactory 576
WMSLoggerIDs 604
WMSProperties 292
wowzaAudioOnly 732
wrap 144
write 27, 815, 816
WRITE_ACCESS_ALL 323
WRITE_ACCESS_NONE 323

WRITEACCESS 984, 1029
writeAppConfig 231
writeAppInstConfig 275
writeChunk 60
writeCodecConfig 1212, 1213
writeConfig 936, 953
writeDeleteError 967, 989
writeDuration 63
writeError 989
writeGeneratedKeyFrame 1011
writeHeader 59
writePackets 62, 63, 1010, 1011, 1104
writeSetValueError 966, 989
writeShortHeader 59
writeString 154
writeVHostConfig 1267
writeXMLConfig 953

X

XMLUtils 104